

# Maximum Permissible Exposure

**FCC ID: AZPR9001SB**

**Product Name: RECEIVER**

**Model No: R9001SB**

According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

**Futaba Corporation** declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

Mode	Max Output Power (dBm)	Tune-up factor	Tune-up max power (dBm)
904.6MHz	12.54	1.0367	13.00

\*\*The value presented in the MPE is the maximum tune-up power.

## 2. MPE Calculation

Based on safety distance (r) **20cm**, the antenna gain (G) is **1.259Numerical**, and the highest power output (P) is **19.953mW**, the power density (S) is **0.004998mW/cm<sup>2</sup>**.

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

**Where :**

Based on safety distance (r)=	20 cm
Highest Power Output (P)=	13.0 dBm = <b>19.953 mW</b>
Antenna Gain (G)=	1.0 dBi = <b>1.259 Numerical</b>
MPE (S) = (P*G) / (4*π*r <sup>2</sup> ) =	= <b>(19.953*1.259)/(4*π*20<sup>2</sup>)= 0.004998 mW/cm<sup>2</sup></b>

Sincerely Yours,

*Johnny Hsueh*

Mr. Johnny Hsueh  
Section Manager  
AUDIX Technology Corporation