



# TA Technology (Shanghai)Co.,Ltd. Test Report

Report No.:RZA1202-0233MPE01

Page 1 of 6

## MPE REPORT

<b>Product Name</b>	Embedded WiFi module
<b>Manufacture</b>	Hi-flying Electronics Technology Co.,Ltd.
<b>Model</b>	HF-A11x
<b>FCC ID</b>	AZYHF-A11X
<b>Test date</b>	2012-03-09

### **Test By**

**Company:** TA Technology (Shanghai) Co., Ltd.  
**Address:** No.145, Jintang Rd, Tangzhen Industry Park, Pudong  
Shanghai,China  
**Contact:** Yang Weizhong  
**Telephone:** +86-021-50791141/2/3  
**Fax:** +86-021-50791141/2/3-8000  
**Website:** <http://www.ta-shanghai.com>  
**E-mail:** yangweizhong@ta-shanghai.com

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.:RZA1202-0233MPE01

Page 2 of 6

### Maximum Permissible Exposure

Type of EUT: Embedded WiFi module

FCC ID: AZYHF-A11X

Manufacturer: Hi-flying Electronics Technology Co.,Ltd.

Model: HF-A11x

Maximum conducted output power (measured) and antenna Gain:

Band	Maximum average conducted output power (dBm)	Antenna Gain (dBi)
802.11b	15.65	0.8
802.11g	11.98	0.8
802.11n HT20	11.84	0.8
802.11n HT40	12.25	0.8

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0 .....	614	1.63	*(100)	6
3-30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300 .....	61.4	0.163	1.0	6
300-1500 .....			<u>f/300</u>	6
1500-100,000 .....			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34 .....	614	1.63	*(100)	30
1.34-30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300 .....	27.5	0.073	0.2	30
300-1500 .....			<u>f/1500</u>	30
1500-100,000 .....			1.0	30

f = frequency in MHz  
 \* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.:RZA1202-0233MPE01

Page 4 of 6

The maximum permissible exposure for 1500~100000MHz is 1.0. So

Band	The maximum permissible exposure
802.11b	1.0 mW/cm <sup>2</sup>
802.11g	1.0 mW/cm <sup>2</sup>
802.11n HT20	1.0 mW/cm <sup>2</sup>
802.11n HT40	1.0 mW/cm <sup>2</sup>

**IMPORTANT NOTE:** To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.:RZA1202-0233MPE01

Page 5 of 6

### RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in OET Bulletin 65 is used in the calculation.

Equation from OET Bulletin 65, Edition 97-01 is:

$$S = PG / 4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

802.11b: **PG** = 15.65dBm+(0.8dBi)=16.45dBm=44 mW

802.11g **PG** = 11.98dBm+(0.8dBi)=12.78dBm=19 mW

802.11n HT20 **PG** = 11.84dBm+(0.8dBi)=12.64dBm=18 mW

802.11n HT40 **PG** = 12.25dBm+(0.8dBi)=13.05dBm=20 mW

**R** =20 cm

$\pi$  = 3.1416

Solving for S, the power density at 20 cm is

Band	Test Result (mW/cm <sup>2</sup> )	Limit Value (mW/cm <sup>2</sup> )
802.11b	0.009	1.0
802.11g	0.004	1.0
802.11n HT20	0.004	1.0
802.11n HT40	0.004	1.0

Note: For mobile or fixed location transmitters, minimum separation distance is 20cm, even if

# TA Technology (Shanghai)Co.,Ltd.

## Test Report

Report No.:RZA1202-0233MPE01

Page 6 of 6

calculations indicate MPE distance is less.

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of 47 CFR Part 15.247 (b) (5)

