

**HYAK LABORATORIES, INC.**

7011 CALAMO STREET, SUITE 107  
SPRINGFIELD, VIRGINIA 22150  
(703) 451-1188  
FAX (703) 644-7492

ENGINEERING STATEMENT  
IN REGARD TO MEASUREMENTS ON  
AUTO PAGE, INC.

Model AR-51

FCC ID: B23AR51

Super-Regenerative Receiver

**A. INTRODUCTION**

Hyak Laboratories Inc. has been authorized by Auto Page Inc., to perform measurements on the AR-51 R/C receiver to determine compliance with FCC Rules, Part 15 Subpart B, Para. 15.109.

The AR-51 is a super-regenerative receiver to remotely control various automobile alarm functions. It operates at a nominal 433.9 MHz frequency. The receiver, constructed on an etched circuit card, is powered by 13.8 Vdc from a vehicle power system.

**B. DESCRIPTION OF MEASUREMENT FACILITIES**

A description of the Hyak Laboratories Inc. radiation test facility is a matter of record with the FCC. The facility was accepted for radiation measurements on October 1, 1976, and is currently listed as an accepted site.

**C. DESCRIPTION OF MEASUREMENT PROCEDURE: RADIATED MEASUREMENTS**

Measurements of receiver radiation field strength were made using ANSI 63.4 (1992) as the test procedure. Measurements were made with 3 meter spacing between the receiver under test and the test equipment antenna. The antenna connected to the equipment under test consisted of a short wire antenna, permanently attached to the receiver.

C. DESCRIPTION OF MEASUREMENT PROCEDURE: RADIATED MEASUREMENTS  
(Continued)

The receiver under test was placed on a rotatable table approximately one meter in height.

Measurement of field strength was made through use of HP 8593B and Advantest R3361A spectrum analyzers in conjunction with a HP 8447D wide band, low noise preamp. Compliance Designs Bi-conical calibrated dipoles were used as the test antennas in the 25-1000 MHz range. Above 1 GHz the Tektronix 494P spectrum analyzer was used with a Avantek 1-2 GHz amplifier. An EMCO 3115 calibrated horn antenna was used between 1 and 2 GHz.

For each spurious emission identified between 30 to 2000 MHz, the test sample was rotated for maximum pickup, the test antenna varied in elevation, and the test antenna polarization shifted between horizontal to vertical in order to maximize observed signals.

Spurious emissions within the 30 - 1000 MHz band were measured with the receiver cohored and a peak-responding detector employed. Above 1 GHz, the Tektronix 494P spectrum analyzer, a peak-responding instrument, with 100 kHz RBW, and no video filtering was used.

The measurement procedure included recording the worst-case field strength for receiving antenna polarization, test antenna height variation from 3 feet to 10 feet and test sample rotation.

The sample was measured in three orientation planes with the wiring harness attached.

The spectrum was checked from 30 to 2000 MHz. All emissions not reported were more than 20 dB below the permitted level or below the applicable limits but obscured by ambient or instrumentation noise. Tabulation of the measurements are shown in Table 1.

The forbidden band frequencies of 15.205 were specifically searched.

D. REPORT OF RADIATED MEASUREMENTS

Table 1 lists the frequency and amplitude of all signals observed from 30 to 2000 MHz that were within 20 dB of the limits of FCC Rules.

TABLE 1

RADIATED SPURIOUS EMISSIONS  
 Measured at 3 meters  
 PART 15(B) PARA. 15.109

Frequency To Which Tuned (MHz)	Frequency of Emission (MHz)	Meter Reading (dBm)	Antenna Factor (dB)	Field <sup>1</sup> uV/m @ 3m	FCC Limit uV/m @ 3m	dB to Limit
433.990	428.320	-88.8	17.0	58	200	-11
433.990	434.520	-80.8	17.0	145	200	-2.8
433.990	438.720	-83.2	17.1	111	200	-5.1
433.990	428.120	-82.0	17.0	126	200	-4.0
433.990	434.520	-87.2	17.0	69	200	-9
433.990	439.320	-92.8	17.1	37	200	-15
433.990	428.320	-85.2	17.0	87	200	-7.2

Note 1:  $uV/m = \log_{10} \frac{dBu/m}{20}$   
 $dBu = dBm + \text{antenna factor} + 107$

\*Reference data, 20 dB or more below FCC limit.

All other emissions were 20 dB or more below FCC limits or, for  
 forbidden band, below ambient or instrumentation noise level.

Cohered, peak-detector

Measured in three planes of orientation.

RADIATED FIELD INTENSITY  
 FCC ID: B23AR51

TABLE 1

## E. POWER LINE CONDUCTED MEASUREMENTS

No AC line-conducted spurious measurements were made since the device is battery operated.

## F. EXHIBITS

FCC ID Label, Exhibit 1.  
Photographs, Exhibit 2.  
Schematic Diagram, Exhibit 3.  
User Instructions, Exhibit 4.  
Block Diagram, Exhibit 5.  
Circuit Description, Exhibit 6.

## G. FORBIDDEN BAND MEASUREMENTS

All forbidden bands of 15.205 from 73 MHz to 2 GHz were searched and any signals above ambient noise or interference levels are shown in Table 1.

## H. STATEMENT

Technical test data are from tests performed by me or under my supervision. My qualifications are a matter of record with the Federal Communications Commission. I personally attest to the accuracy of the test data submitted as a part of this engineering statement.



Rowland S. Johnson

Dated: April 22, 1998