



# FCC RADIO TEST REPORT

**FCC ID** : B32C6803GBTWN  
**Equipment** : Point of Sales Terminal  
**Brand Name** : Verifone  
**Model Name** : C680 3G-BT-WiFi  
**Applicant** : Verifone, Inc.  
1400 West Stanford Ranch Road,  
Suite 200, Rocklin CA 95765 USA  
**Manufacturer** : Verifone, Inc.  
**Standard** : FCC Part 15 Subpart E §15.407

The product was received on Jan. 20, 2020 and testing was started from Jul. 07, 2020 and completed on Aug. 12, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Approved by: Louis Wu

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Location .....	6
1.4 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Carrier Frequency and Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	9
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 Test Result .....</b>	<b>11</b>
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement .....	11
3.2 Maximum Conducted Output Power Measurement .....	14
3.3 Power Spectral Density Measurement .....	15
3.4 Unwanted Emissions Measurement.....	17
3.5 AC Conducted Emission Measurement.....	23
3.6 Automatically Discontinue Transmission .....	25
3.7 Antenna Requirements .....	26
<b>4 List of Measuring Equipment.....</b>	<b>27</b>
<b>5 Uncertainty of Evaluation .....</b>	<b>29</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	
<b>Appendix F. Setup Photographs</b>	



### History of this test report

Report No.	Version	Description	Issued Date
FR692114-08F	01	Initial issue of report	Sep. 04, 2020



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407 (a)	Maximum Conducted Output Power	Pass	-
3.3	15.407 (a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 10.53 dB at 902.030 MHz
3.5	15.207	AC Conducted Emission	Pass	Under limit 13.29 dB at 0.570 MHz
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass	-
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang****Report Producer: Tina Chuang**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

GSM/WCDMA, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n, and RFID.

Product Feature	
Antenna Type	WWAN: PCB Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna RFID: Bobbin Antenna

Specification of Accessory		
AC Adapter	Brand Name	Verifone, Inc.
	Manufacturer	PHIHONG
	Model Name	AM11A-050A
	Power Rating	Input:100-240Vac, 50-60Hz 0.5A Output: 5.0V DC 2.2A
	Power Cord	1.8 meter, non-shielded cable, without ferrite core
Battery	Brand Name	Verifone, Inc.
	Model Name	BPK260-001

## 1.2 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.3 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH15-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

### 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
  
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	-	-	165	5825

**Note:** The above Frequency and Channel in "\*" were 802.11n HT40.



## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Tx + WLAN (5GHz) Tx + Battery + Charging from AC Adapter + Primary micro-USB port (Cable Load) + RS-232/4-Pin load + RS-232/RJ11 load + Secondary micro-USB port (USB Storage device Load)

Ch. #	Band IV : 5725-5850 MHz		
	802.11a	802.11n HT20	802.11n HT40
L Low	149	149	151
M Middle	157	157	-
H High	165	165	159

Remark: For radiation spurious emission, the final modulation and the worst data rate was reference the max RF conducted power.



### 2.3 Connection Diagram of Test System



### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	USB Flash Driver	Kingston	DTDUO3C	FCC DoC	N/A	N/A
2.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A



## 2.5 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

##### 3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


##### 3.1.4 Test Setup



##### 3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.





**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Maximum Conducted Output Power Measurement

### 3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


### 3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

##### # Method SA-3 #

(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
  - Set RBW = 300 kHz.
  - Set VBW  $\geq$  1 MHz.
  - Number of points in sweep  $\geq$  2 Span / RBW.
  - Sweep time  $\leq$  (number of points in sweep)  $\times$  T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
  - Detector = power averaging (rms).
  - Trace mode = max hold.
  - Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
  2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.







### 3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

#### 3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:  
 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:** The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$



<b>EIRP (dBm)</b>	<b>Field Strength at 3m (dB<math>\mu</math>V/m)</b>
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.
- (ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

### **3.4.2 Measuring Instruments**

See list of measuring equipment of this test report.



### **3.4.3 Test Procedures**

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW  $\geq$  3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW  $\geq$  1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

### 3.4.7 Duty Cycle

Please refer to Appendix E.

### 3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### 3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.5.4 Test Setup



### 3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.





## **3.6 Automatically Discontinue Transmission**

### **3.6.1 Limit of Automatically Discontinue Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **3.6.2 Measuring Instruments**

See list of measuring equipment of this test report.

### **3.6.3 Test Result of Automatically Discontinue Transmission**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02. 2020	Jul. 07, 2020~ Aug. 12, 2020	Mar. 01. 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 23, 2019	Jul. 07, 2020~ Aug. 12, 2020	Dec. 22, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Dec. 30, 2019	Jul. 07, 2020~ Aug. 12, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Aug. 22,2019	Jul. 07, 2020~ Aug. 12, 2020	Aug. 21,2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 11, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Aug. 11, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Aug. 11, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Aug. 11, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Aug. 11, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Aug. 11, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Aug. 11, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 09, 2020	Jul. 17, 2020~ Aug. 03, 2020	Jan. 08, 2021	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0800N1D01N- 06	41912&05	30MHz to 1GHz	Feb. 09, 2020	Jul. 17, 2020~ Aug. 03, 2020	Feb. 08, 2021	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 27, 2019	Jul. 17, 2020~ Aug. 03, 2020	Dec. 26, 2020	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-162 0	1-18GHz	Oct. 28, 2019	Jul. 17, 2020~ Aug. 03, 2020	Oct. 27, 2020	Radiation (03CH15-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Dec. 10, 2019	Jul. 17, 2020~ Aug. 03, 2020	Dec. 09, 2020	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055006	1GHz~18GHz	May 07, 2020	Jul. 17, 2020~ Aug. 03, 2020	May 06, 2021	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY53270195	1GHz~26.5GHz	Aug. 23, 2019	Jul. 17, 2020~ Aug. 03, 2020	Aug. 22, 2020	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Jul. 17, 2020~ Aug. 03, 2020	Dec. 12, 2020	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20MHz~8.4GHz	Nov. 01, 2019	Jul. 17, 2020~ Aug. 03, 2020	Oct. 31, 2020	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY50180136	3Hz~44GHz	May 04, 2020	Jul. 17, 2020~ Aug. 03, 2020	May 03, 2021	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 17, 2020~ Aug. 03, 2020	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 17, 2020~ Aug. 03, 2020	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k5)	RK-000451	N/A	N/A	Jul. 17, 2020~ Aug. 03, 2020	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/4	30M-18G	Apr. 14, 2020	Jul. 17, 2020~ Aug. 03, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9838/4PE	30M-18G	Apr. 14, 2020	Jul. 17, 2020~ Aug. 03, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY37710/4	30M-18G	Apr. 17, 2020	Jul. 17, 2020~ Aug. 03, 2020	Apr. 16, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz-40GHz	Feb. 25, 2020	Jul. 17, 2020~ Aug. 03, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz-40GHz	Feb. 25, 2020	Jul. 17, 2020~ Aug. 03, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40S	SN4	1.53G Low Pass	Jul. 03, 2020	Jul. 17, 2020~ Aug. 03, 2020	Jul. 02, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WHKX8-5872.5-6750-18000-40ST	SN6	6.75GHz High Pass Filter	Jul. 03, 2020	Jul. 17, 2020~ Aug. 03, 2020	Jul. 02, 2021	Radiation (03CH15-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.4
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0
---	-----

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Junyu Chou	Temperature:	23.7~23.9	°C
Test Date:	2020/7/7~2020/8/12	Relative Humidity:	52.6~53.4	%

**TEST RESULTS DATA**  
**6dB and 26dB EBW and 99% OBW**

Band IV single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	16.55	-	20.45	-	15.05	-	0.5	Pass
11a	6Mbps	1	157	5785	16.55	-	20.75	-	15.10	-	0.5	Pass
11a	6Mbps	1	165	5825	16.55	-	21.30	-	15.10	-	0.5	Pass
HT20	MCS0	1	149	5745	17.55	-	20.95	-	15.10	-	0.5	Pass
HT20	MCS0	1	157	5785	17.55	-	21.30	-	15.05	-	0.5	Pass
HT20	MCS0	1	165	5825	17.55	-	21.10	-	15.10	-	0.5	Pass
HT40	MCS0	1	151	5755	36.10	-	40.86	-	35.01	-	0.5	Pass
HT40	MCS0	1	159	5795	36.20	-	40.86	-	35.10	-	0.5	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Band IV single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	8.40	-		30.00	-	3.11	-	Pass
11a	6Mbps	1	157	5785	8.30	-		30.00	-	3.11	-	Pass
11a	6Mbps	1	165	5825	8.60	-		30.00	-	3.11	-	Pass
HT20	MCS0	1	149	5745	7.30	-		30.00	-	3.11	-	Pass
HT20	MCS0	1	157	5785	7.20	-		30.00	-	3.11	-	Pass
HT20	MCS0	1	165	5825	7.30	-		30.00	-	3.11	-	Pass
HT40	MCS0	1	151	5755	7.50	-		30.00	-	3.11	-	Pass
HT40	MCS0	1	159	5795	7.40	-		30.00	-	3.11	-	Pass



**TEST RESULTS DATA**  
**Power Spectral Density**

Band IV single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	2.22	-	-1.75	-		30.00	-	3.11	-	Pass
11a	6Mbps	1	157	5785	2.22	-	-2.31	-		30.00	-	3.11	-	Pass
11a	6Mbps	1	165	5825	2.22	-	-1.57	-		30.00	-	3.11	-	Pass
HT20	MCS0	1	149	5745	2.22	-	-2.70	-		30.00	-	3.11	-	Pass
HT20	MCS0	1	157	5785	2.22	-	-2.60	-		30.00	-	3.11	-	Pass
HT20	MCS0	1	165	5825	2.22	-	-2.87	-		30.00	-	3.11	-	Pass
HT40	MCS0	1	151	5755	2.22	-	-5.12	-		30.00	-	3.11	-	Pass
HT40	MCS0	1	159	5795	2.22	-	-5.30	-		30.00	-	3.11	-	Pass




## Appendix B. AC Conducted Emission Test Results

Test Engineer :	Howard Huang	Temperature :	21~25°C
		Relative Humidity :	40~45%

# EUT Information

Report NO : 692114-08  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.162780	---	35.13	55.32	20.19	L1	OFF	19.6
0.162780	47.03	---	65.32	18.29	L1	OFF	19.6
0.203100	---	32.34	53.48	21.14	L1	OFF	19.6
0.203100	41.73	---	63.48	21.75	L1	OFF	19.6
0.571380	---	32.58	46.00	13.42	L1	OFF	19.6
0.571380	40.65	---	56.00	15.35	L1	OFF	19.6
0.618000	---	32.17	46.00	13.83	L1	OFF	19.6
0.618000	39.57	---	56.00	16.43	L1	OFF	19.6
2.501250	---	27.06	46.00	18.94	L1	OFF	19.6
2.501250	31.18	---	56.00	24.82	L1	OFF	19.6
10.644000	---	29.78	50.00	20.22	L1	OFF	20.1
10.644000	33.50	---	60.00	26.50	L1	OFF	20.1

# EUT Information

Report NO : 692114-08  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161970	---	34.20	55.36	21.16	N	OFF	19.5
0.161970	46.42	---	65.36	18.94	N	OFF	19.5
0.375900	---	30.02	48.37	18.35	N	OFF	19.5
0.375900	35.54	---	58.37	22.83	N	OFF	19.5
0.570120	---	32.71	46.00	13.29	N	OFF	19.5
0.570120	40.46	---	56.00	15.54	N	OFF	19.5
0.629520	---	31.93	46.00	14.07	N	OFF	19.5
0.629520	39.98	---	56.00	16.02	N	OFF	19.5
2.505750	---	27.19	46.00	18.81	N	OFF	19.6
2.505750	31.30	---	56.00	24.70	N	OFF	19.6
6.605610	---	27.46	50.00	22.54	N	OFF	19.7
6.605610	30.35	---	60.00	29.65	N	OFF	19.7
15.917640	---	26.22	50.00	23.78	N	OFF	19.9
15.917640	28.82	---	60.00	31.18	N	OFF	19.9



### Appendix C. Radiated Spurious Emission

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.1~23.1°C
		Relative Humidity :	52~61%

**Band 4 - 5725~5850MHz**  
**WIFI 802.11a (Band Edge @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)	
802.11a CH 149 5745MHz		5601.6	51.31	-16.89	68.2	39	31.9	10.9	30.49	155	55	P	H	
		5700	52.57	-52.63	105.2	40.25	32	10.87	30.55	155	55	P	H	
		5708	57.23	-50.21	107.44	44.92	32	10.87	30.56	155	55	P	H	
		5725	59.61	-62.59	122.2	47.31	32	10.87	30.57	155	55	P	H	
	*	5745	102.33	-	-	90.05	32	10.86	30.58	155	55	P	H	
	*	5745	94.44	-	-	82.16	32	10.86	30.58	155	55	A	H	
														H
														H
			5624.2	53.04	-15.16	68.2	40.81	31.85	10.89	30.51	265	334	P	V
			5695	53.39	-48.12	101.51	41.08	31.98	10.88	30.55	265	334	P	V
			5716.8	58.79	-51.12	109.91	46.48	32	10.87	30.56	265	334	P	V
			5724.6	62.23	-59.06	121.29	49.93	32	10.87	30.57	265	334	P	V
	*		5745	104.49	-	-	92.21	32	10.86	30.58	265	334	P	V
	*		5745	95.21	-	-	82.93	32	10.86	30.58	265	334	A	V
													V	
													V	



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5619.6	51.99	-16.21	68.2	39.74	31.86	10.89	30.5	187	51	P	H
		5700	51.17	-54.03	105.2	38.85	32	10.87	30.55	187	51	P	H
		5705.8	51.75	-55.08	106.83	39.44	32	10.87	30.56	187	51	P	H
		5720.4	50.68	-61.03	111.71	38.38	32	10.87	30.57	187	51	P	H
	*	5785	101.75	-	-	89.37	32.14	10.85	30.61	187	51	P	H
	*	5785	93.75	-	-	81.37	32.14	10.85	30.61	187	51	A	H
		5852	51.61	-66.03	117.64	39.07	32.21	10.98	30.65	187	51	P	H
		5863.6	51.68	-56.71	108.39	39.08	32.25	11.01	30.66	187	51	P	H
		5910	51.25	-28.02	79.27	38.38	32.42	11.13	30.68	187	51	P	H
		5936.4	52.46	-15.74	68.2	39.5	32.47	11.19	30.7	187	51	P	H
													H
													H
802.11a													
CH 157													
5785MHz		5625.8	52.39	-15.81	68.2	40.16	31.85	10.89	30.51	291	338	P	V
		5687.4	52.37	-43.54	95.91	40.09	31.95	10.88	30.55	291	338	P	V
		5715.8	51.45	-58.18	109.63	39.14	32	10.87	30.56	291	338	P	V
		5720.8	51.39	-61.23	112.62	39.09	32	10.87	30.57	291	338	P	V
	*	5785	102.53	-	-	90.15	32.14	10.85	30.61	291	338	P	V
	*	5785	94.35	-	-	81.97	32.14	10.85	30.61	291	338	A	V
		5850	51.11	-71.09	122.2	38.58	32.2	10.98	30.65	291	338	P	V
		5861.4	50.94	-58.07	109.01	38.34	32.25	11	30.65	291	338	P	V
		5900.4	52.8	-33.56	86.36	39.98	32.4	11.1	30.68	291	338	P	V
		5946.6	51.36	-16.84	68.2	38.36	32.49	11.22	30.71	291	338	P	V
													V
													V



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11a CH 165 5825MHz	*	5825	101.05	-	-	88.57	32.2	10.91	30.63	191	52	P	H	
	*	5825	93.22	-	-	80.74	32.2	10.91	30.63	191	52	A	H	
		5851.4	55.22	-63.79	119.01	42.68	32.21	10.98	30.65	191	52	P	H	
		5870.6	54.55	-51.88	106.43	41.9	32.28	11.03	30.66	191	52	P	H	
		5877.8	53.05	-50.07	103.12	40.35	32.31	11.05	30.66	191	52	P	H	
		5935.2	52.28	-15.92	68.2	39.32	32.47	11.19	30.7	191	52	P	H	
														H
														H
	*	5825	100.69	-	-	88.21	32.2	10.91	30.63	300	326	P	V	
	*	5825	93.04	-	-	80.56	32.2	10.91	30.63	300	326	A	V	
		5851.4	55.86	-63.15	119.01	43.32	32.21	10.98	30.65	300	326	P	V	
		5861.6	54.72	-54.23	108.95	42.11	32.25	11.01	30.65	300	326	P	V	
		5879.8	52.52	-49.11	101.63	39.82	32.32	11.05	30.67	300	326	P	V	
		5935.6	52.88	-15.32	68.2	39.92	32.47	11.19	30.7	300	326	P	V	
														V
														V
														V
	<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz**  
**WIFI 802.11a (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 149 5745MHz		11490	49.44	-24.56	74	54.97	40.48	14.89	60.9	100	0	P	H
		17235	49.49	-18.71	68.2	48.4	40.94	18.97	58.82	100	0	P	H
													H
													H
		11490	49.5	-24.5	74	55.03	40.48	14.89	60.9	100	0	P	V
		17235	49.57	-18.63	68.2	48.48	40.94	18.97	58.82	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		11570	49.68	-24.32	74	55.39	40.29	14.98	60.98	100	0	P	H
		17355	50.93	-17.27	68.2	48.74	41.75	19.11	58.67	100	0	P	H
													H
													H
		11570	48.77	-25.23	74	54.48	40.29	14.98	60.98	100	0	P	V
		17355	52.32	-15.88	68.2	50.13	41.75	19.11	58.67	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	48.62	-25.38	74	54.79	39.85	15.06	61.08	100	0	P	H
		17475	52.07	-16.13	68.2	48.86	42.5	19.24	58.53	100	0	P	H
													H
													H
		11650	47.6	-26.4	74	53.77	39.85	15.06	61.08	100	0	P	V
		17475	51.27	-16.93	68.2	48.06	42.5	19.24	58.53	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





**Band 4 5725~5850MHz**  
**WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 149 5745MHz		5626.2	52.8	-15.4	68.2	40.57	31.85	10.89	30.51	195	50	P	H	
		5675.8	52.87	-34.46	87.33	40.63	31.9	10.88	30.54	195	50	P	H	
		5718.4	56.17	-54.18	110.35	43.87	32	10.87	30.57	195	50	P	H	
		5724.8	61.39	-60.35	121.74	49.09	32	10.87	30.57	195	50	P	H	
	*	5745	100.91	-	-	88.63	32	10.86	30.58	195	50	P	H	
	*	5745	92.76	-	-	80.48	32	10.86	30.58	195	50	A	H	
														H
														H
			5625.2	52.45	-15.75	68.2	40.22	31.85	10.89	30.51	296	331	P	V
			5699.2	53.13	-51.48	104.61	40.81	32	10.87	30.55	296	331	P	V
			5718.6	57.81	-52.6	110.41	45.51	32	10.87	30.57	296	331	P	V
			5724	60.53	-59.39	119.92	48.23	32	10.87	30.57	296	331	P	V
	*		5745	102.55	-	-	90.27	32	10.86	30.58	296	331	P	V
	*		5745	93.77	-	-	81.49	32	10.86	30.58	296	331	A	V
													V	
													V	



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5648.2	52.22	-15.98	68.2	40.05	31.8	10.89	30.52	190	51	P	H
		5653.8	51.9	-19.12	71.02	39.73	31.82	10.88	30.53	190	51	P	H
		5711.8	52.48	-56.03	108.51	40.17	32	10.87	30.56	190	51	P	H
		5721.2	52.68	-60.86	113.54	40.38	32	10.87	30.57	190	51	P	H
	*	5785	100.73	-	-	88.35	32.14	10.85	30.61	190	51	P	H
	*	5785	92.14	-	-	79.76	32.14	10.85	30.61	190	51	A	H
		5850.2	51.95	-69.79	121.74	39.42	32.2	10.98	30.65	190	51	P	H
		5859.2	53.35	-56.27	109.62	40.76	32.24	11	30.65	190	51	P	H
		5920.8	53.17	-18.13	71.3	40.27	32.44	11.15	30.69	190	51	P	H
		5948.6	52.54	-15.66	68.2	39.53	32.5	11.22	30.71	190	51	P	H
802.11n													H
HT20													H
CH 157		5635	52.38	-15.82	68.2	40.17	31.83	10.89	30.51	276	331	P	V
5785MHz		5690.6	51.85	-46.42	98.27	39.56	31.96	10.88	30.55	276	331	P	V
		5713.6	52.58	-56.43	109.01	40.27	32	10.87	30.56	276	331	P	V
		5723.2	52.54	-65.56	118.1	40.24	32	10.87	30.57	276	331	P	V
	*	5785	101.92	-	-	89.54	32.14	10.85	30.61	276	331	P	V
	*	5785	93.58	-	-	81.2	32.14	10.85	30.61	276	331	A	V
		5851.4	52.07	-66.94	119.01	39.53	32.21	10.98	30.65	276	331	P	V
		5867	53.36	-54.08	107.44	40.73	32.27	11.02	30.66	276	331	P	V
		5898.6	53.24	-34.46	87.7	40.43	32.39	11.1	30.68	276	331	P	V
		5934.2	53.91	-14.29	68.2	40.95	32.47	11.19	30.7	276	331	P	V
													V
													V



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
802.11n HT20 CH 165 5825MHz	*	5825	98.18	-	-	85.7	32.2	10.91	30.63	191	54	P	H	
	*	5825	91.02	-	-	78.54	32.2	10.91	30.63	191	54	A	H	
		5850.2	57.04	-64.7	121.74	44.51	32.2	10.98	30.65	191	54	P	H	
		5856.2	53.12	-57.34	110.46	40.56	32.22	10.99	30.65	191	54	P	H	
		5918.6	52.22	-20.7	72.92	39.32	32.44	11.15	30.69	191	54	P	H	
		5936.8	52.54	-15.66	68.2	39.58	32.47	11.19	30.7	191	54	P	H	
														H
														H
	*	5825	99.63	-	-	87.15	32.2	10.91	30.63	290	337	P	V	
	*	5825	92.05	-	-	79.57	32.2	10.91	30.63	290	337	A	V	
		5851.4	54.49	-64.52	119.01	41.95	32.21	10.98	30.65	290	337	P	V	
		5860.2	56.76	-52.58	109.34	44.17	32.24	11	30.65	290	337	P	V	
		5901.6	52.48	-33	85.48	39.65	32.4	11.11	30.68	290	337	P	V	
		5942.4	52	-16.2	68.2	39.01	32.48	11.21	30.7	290	337	P	V	
														V
														V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



**Band 4 5725~5850MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 149 5745MHz		11490	48.42	-25.58	74	53.95	40.48	14.89	60.9	100	0	P	H	
		17235	49.2	-19	68.2	48.11	40.94	18.97	58.82	100	0	P	H	
													H	
													H	
			11490	48.71	-25.29	74	54.24	40.48	14.89	60.9	100	0	P	V
			17235	49.46	-18.74	68.2	48.37	40.94	18.97	58.82	100	0	P	V
														V
802.11n HT20 CH 157 5785MHz		11570	49.59	-24.41	74	55.27	40.32	14.97	60.97	400	0	P	H	
		17355	50.67	-17.53	68.2	48.48	41.75	19.11	58.67	100	0	P	H	
													H	
													H	
			11570	49.22	-24.78	74	54.93	40.29	14.98	60.98	100	0	P	V
			17355	50.83	-17.37	68.2	48.64	41.75	19.11	58.67	100	0	P	V
														V
802.11n HT20 CH 165 5825MHz		11650	48.55	-25.45	74	54.72	39.85	15.06	61.08	100	0	P	H	
		17475	50.89	-17.31	68.2	47.68	42.5	19.24	58.53	100	0	P	H	
													H	
													H	
			11650	48	-26	74	54.17	39.85	15.06	61.08	100	0	P	V
			17475	51.8	-16.4	68.2	48.59	42.5	19.24	58.53	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



**Band 4 5725~5850MHz  
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5640.4	52.57	-15.63	68.2	40.38	31.82	10.89	30.52	175	55	P	H
		5690.4	52.88	-45.24	98.12	40.59	31.96	10.88	30.55	175	55	P	H
		5720	61.71	-49.09	110.8	49.41	32	10.87	30.57	175	55	P	H
		5721.4	63.73	-50.26	113.99	51.43	32	10.87	30.57	175	55	P	H
	*	5755	99.97	-	-	87.68	32.02	10.86	30.59	175	55	P	H
	*	5755	91.22	-	-	78.93	32.02	10.86	30.59	175	55	A	H
		5851	52.78	-67.14	119.92	40.25	32.2	10.98	30.65	175	55	P	H
		5870.6	52.6	-53.83	106.43	39.95	32.28	11.03	30.66	175	55	P	H
		5902	52.28	-32.9	85.18	39.45	32.4	11.11	30.68	175	55	P	H
		5949.6	52.72	-15.48	68.2	39.7	32.5	11.23	30.71	175	55	P	H
													H
													H
<b>802.11n</b>													
<b>HT40</b>													
<b>CH 151</b>		5632.2	52.69	-15.51	68.2	40.47	31.84	10.89	30.51	294	338	P	V
<b>5755MHz</b>		5695.4	52.36	-49.45	101.81	40.05	31.98	10.88	30.55	294	338	P	V
		5717.6	61.22	-48.91	110.13	48.91	32	10.87	30.56	294	338	P	V
		5724.8	64.27	-57.47	121.74	51.97	32	10.87	30.57	294	338	P	V
	*	5755	99.37	-	-	87.08	32.02	10.86	30.59	294	338	P	V
	*	5755	91.81	-	-	79.52	32.02	10.86	30.59	294	338	A	V
		5850.4	52.58	-68.71	121.29	40.05	32.2	10.98	30.65	294	338	P	V
		5867	52.7	-54.74	107.44	40.07	32.27	11.02	30.66	294	338	P	V
		5905.2	52.68	-30.13	82.81	39.84	32.41	11.11	30.68	294	338	P	V
		5948.2	52.66	-15.54	68.2	39.65	32.5	11.22	30.71	294	338	P	V
													V
													V



WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
		5637.8	52	-16.2	68.2	39.81	31.82	10.89	30.52	200	51	P	H
		5689.2	52.55	-44.69	97.24	40.26	31.96	10.88	30.55	200	51	P	H
		5706.8	52.95	-54.16	107.11	40.64	32	10.87	30.56	200	51	P	H
		5720	52	-58.8	110.8	39.7	32	10.87	30.57	200	51	P	H
	*	5795	97.44	-	-	85.02	32.18	10.85	30.61	200	51	P	H
	*	5795	90.07	-	-	77.65	32.18	10.85	30.61	200	51	A	H
		5850	52.77	-69.43	122.2	40.24	32.2	10.98	30.65	200	51	P	H
		5865.4	52.81	-55.08	107.89	40.2	32.26	11.01	30.66	200	51	P	H
		5885.6	53.07	-44.26	97.33	40.33	32.34	11.07	30.67	200	51	P	H
		5929.2	52.76	-15.44	68.2	39.83	32.46	11.17	30.7	200	51	P	H
802.11n													H
HT40													H
CH 159		5629.4	52.79	-15.41	68.2	40.57	31.84	10.89	30.51	290	337	P	V
5795MHz		5676.8	52.65	-35.42	88.07	40.4	31.91	10.88	30.54	290	337	P	V
		5705.2	52.63	-54.03	106.66	40.32	32	10.87	30.56	290	337	P	V
		5722	53.05	-62.31	115.36	40.75	32	10.87	30.57	290	337	P	V
	*	5795	98.8	-	-	86.38	32.18	10.85	30.61	290	337	P	V
	*	5795	90.9	-	-	78.48	32.18	10.85	30.61	290	337	A	V
		5851	53.25	-66.67	119.92	40.72	32.2	10.98	30.65	290	337	P	V
		5860.8	53.23	-55.94	109.17	40.64	32.24	11	30.65	290	337	P	V
		5893.8	53.44	-37.81	91.25	40.64	32.38	11.09	30.67	290	337	P	V
		5939.8	53.16	-15.04	68.2	40.18	32.48	11.2	30.7	290	337	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 4 5725~5850MHz  
WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 151 5755MHz		11510	48.79	-25.21	74	54.32	40.47	14.91	60.91	100	0	P	H
		17265	49.61	-18.59	68.2	48.33	41.06	19	58.78	100	0	P	H
													H
													H
		11510	49.88	-24.12	74	55.41	40.47	14.91	60.91	100	0	P	V
		17265	49.99	-18.21	68.2	48.71	41.06	19	58.78	100	0	P	V
													V
													V
802.11n HT40 CH 159 5795MHz		11590	49.14	-24.86	74	54.92	40.23	15	61.01	100	0	P	H
		17385	50.7	-17.5	68.2	48.15	42.05	19.14	58.64	100	0	P	H
													H
													H
		11590	48.87	-25.13	74	54.65	40.23	15	61.01	100	0	P	V
		17385	51.75	-16.45	68.2	49.2	42.05	19.14	58.64	100	0	P	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												







**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.1~23.1°C
		Relative Humidity :	52~61%

### Note symbol

-L	Low channel location
-R	High channel location



Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

Table with 2 columns: WIFI (Band 4 5725~5850MHz Band Edge @ 3m), ANT (802.11a CH149 5745MHz). Row 1: 1, Horizontal, Fundamental. Includes two spectral plots and technical details like Site, Condition, Detector, Project.



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_8E(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH15-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL            Detector : Peak            Project : 692114-08</p>	<p>Site : 03CH15-HY            Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL            Detector : Peak            Project : 692114-08</p>
Peak	<p>Site : 03CH15-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL            Detector : Peak            Project : 692114-08</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Vertical	Fundamental
Peak	<p>Date: 2020-07-28 PEAK_BE(84)_15-24</p> <p>Site : 03CH15-HY Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>	<p>Date: 2020-07-28 PEAK(UNB)</p> <p>Site : 03CH15-HY Condition : PEAK(UNB) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>
Peak	<p>Date: 2020-07-28 PEAK_BE(84)_16-24</p> <p>Site : 03CH15-HY Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH15-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 692114-08</p>	<p>Site : 03CH15-HY            Condition : PEAK(U)B 3m 91200_15_1620 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 692114-08</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Vertical	Fundamental
Peak	 <p>Date: 2020-07-28</p> <p>Site : 03CH15-HY          Condition : PEAK_8E(84)_16-24 3m 91200_15_1620 VERTICAL          RBW:1000.000KHz VBW:3000.000KHz SWT:Auto          Detector : Peak          Project : 692114-08</p>	 <p>Date: 2020-07-28</p> <p>Site : 03CH15-HY          Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL          RBW:1000.000KHz VBW:3000.000KHz SWT:Auto          Detector : Peak          Project : 692114-08</p>



**Band 4 5725~5850MHz  
WIFI 802.11n HT20 (Band Edge @ 3m)**

<b>WIFI</b>	<b>Band 4 5725~5850MHz Band Edge @ 3m</b>	
<b>ANT</b>	<b>802.11n HT20 CH149 5745MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Fundamental</b>
<b>Peak</b>	<p>Site : 03CH15-HY          Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL          Detector : Peak          Project : 692114-08</p>	<p>Site : 03CH15-HY          Condition : PEAK(FUNB)_16-24 3m 91200_15_1620 HORIZONTAL          Detector : Peak          Project : 692114-08</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_8E(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Fundamental
<p><b>Peak</b></p>	<p>Site : 03CH15-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL            Detector : Peak            Project : 692114-08</p>	<p>Site : 03CH15-HY            Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL            Detector : Peak            Project : 692114-08</p>
<p><b>Peak</b></p>	<p>Site : 03CH15-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL            Detector : Peak            Project : 692114-08</p>	<p><b>Left blank</b></p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Vertical	Fundamental
Peak	<p>Date: 2020-07-28 PEAK_BE(84)_15-24</p> <p>Site : 03CH15-HY Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>	<p>Date: 2020-07-28 PEAK(UNII)</p> <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>
Peak	<p>Date: 2020-07-28 PEAK_BE(84)_16-24</p> <p>Site : 03CH15-HY Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH15-HY Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 692114-08</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Vertical	Fundamental
Peak	 <p>Date: 2020-07-28</p> <p>Site : 03CH15-HY          Condition : PEAK_8E(84)_16-24 3m 91200_15_1620 VERTICAL          RBW:1000.000KHz VBW:3000.000KHz SWT:Auto          Detector : Peak          Project : 692114-08</p>	 <p>Date: 2020-07-28</p> <p>Site : 03CH15-HY          Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL          RBW:1000.000KHz VBW:3000.000KHz SWT:Auto          Detector : Peak          Project : 692114-08</p>






**Band 4 5725~5850MHz  
WIFI 802.11n HT40 (Band Edge @ 3m)**




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Horizontal	Fundamental
<b>Peak</b>	<p>Site : 03CH15-HY Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-HY Condition : PEAK(UNIT) 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 692114-08</p>
<b>Peak</b>	<p>Site : 03CH15-HY Condition : PEAK_BE(B4)_16-24 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 692114-08</p>	<b>Left blank</b>








WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Vertical	Fundamental
Peak	 <p>Date: 2020-07-28 PEAK_BE(84)_16-24</p> <p>Site : 03CH15-HY Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 692114-08</p>	 <p>Date: 2020-07-28 PEAK(UNB)</p> <p>Site : 03CH15-HY Condition : PEAK(UNB) 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 692114-08</p>
Peak	 <p>Date: 2020-07-28 PEAK_BE(84)_16-24</p> <p>Site : 03CH15-HY Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 692114-08</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY            Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 HORIZONTAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 692114-08</p>	 <p>Site : 03CH15-HY            Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 692114-08</p>
Peak	 <p>Site : 03CH15-HY            Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 HORIZONTAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 692114-08</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH15-HY            Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 692114-08</p>	 <p>Site : 03CH15-HY            Condition : PEAK(UNB) 3m 91200_15_1620 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 692114-08</p>
Peak	 <p>Site : 03CH15-HY            Condition : PEAK_BE(84)_16-24 3m 91200_15_1620 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 692114-08</p>	Left blank



**Band 4 - 5725~5850MHz**  
**WIFI 802.11a (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	<p>Site : 03CH15-11Y            Condition : PEAK(UWB) 3m 9120D_15_1620 HORIZONTAL            Detector : Peak            Project : 692114-08</p>	<p>Site : 03CH15-11Y            Condition : PEAK(UWB) 3m 9120D_15_1620 VERTICAL            Detector : Peak            Project : 692114-08</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Vertical
<p>Peak Avg.</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 692114-08</p>	 <p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL Detector : Peak Project : 692114-08</p>





<b>WIFI</b>	<b>Band 4 5725~5850MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>802.11a CH165 5825MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL Detector : Peak Project : 692114-08</p>



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

Table with 2 columns: WIFI (Band 4 5725~5850MHz Harmonic @ 3m), ANT (802.11n HT20 CH149 5745MHz). Row 1: 1, Horizontal, Vertical. Includes two spectral plots and metadata for Peak and Avg. measurements.



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH15-HY          Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL          Detector : Peak          Project : 692114-08</p>	 <p>Site : 03CH15-HY          Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL          Detector : Peak          Project : 692114-08</p>





<b>WIFI</b>	<b>Band 4 5725~5850MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>802.11n HT20 CH165 5825MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak Avg.</b>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL Detector : Peak Project : 692114-08</p>



**Band 4 5725~5850MHz  
WIFI 802.11n HT40 (Harmonic @ 3m)**

<b>WIFI</b>	<b>Band 4 5725~5850MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>802.11n HT40 CH151 5755MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-HY Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL Detector : Peak Project : 692114-08</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	<p>Site : 03CH15-HY          Condition : PEAK(UNII) 3m 91200_15_1620 HORIZONTAL          Detector : Peak          Project : 692114-08</p>	<p>Site : 03CH15-HY          Condition : PEAK(UNII) 3m 91200_15_1620 VERTICAL          Detector : Peak          Project : 692114-08</p>



Emission below 1GHz  
5GHz WIFI 802.11n HT20 (LF)

WIFI	5GHz 5725-5850MHz	
ANT	802.11n HT20 LF	
1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH15-11Y Condition : QP 3m B1LOG_15_41912 HORIZONTAL Detector : Peak Project : 692114-08</p>	<p>Site : 03CH15-11Y Condition : QP 3m B1LOG_15_41912 VERTICAL Detector : Peak Project : 692114-08</p>




## Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1	802.11a	92.86	1430	0.70	1kHz	0.32
1	5GHz 802.11n HT20	92.39	1340	0.75	1kHz	0.34
1	5GHz 802.11n HT40	90.45	966	1.04	3kHz	0.44




802.11a



Date: 8.JUL.2020 00:37:26


802.11n HT20



Date: 8.JUL.2020 00:49:13



802.11n HT40



Date: 8.JUL.2020 01:00:51