

FCC ID: B320MNI3600

Exhibit 2

Engineering Report d)Spurious Emissions, Antenna Terminal (2.1051)

Document

R902M-2-O RADIO MODEM DEVICE SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Page 1(1)

| RESEARCH IN MOTION 21112 21 (111111 122) | | | |
|--|--|---------------|------------------------------|
| Author Data | | Date | Document No. |
| Masud S. Attayi | | April 8, 1999 | 01947-CERT-FCC-TEST-SPURIOUS |
| Approved | | Rev | File / Reference |
| | | | Spurious |

SPURIOUS EMISSIONS AT ANTENNA TERMINALS

TEST PROCEDURE:

The Research In Motion Limited R902M-2-O radio modem device was connected together with a radio monitor board 02120-001, host computer, external power supply, a 20 dB external attenuator, and a coaxial cable. The R902M-2-O antenna output terminal was connected to the input of a 50 Ω spectrum analyzer through a matched 20 dB attenuator and a coaxial cable. The transmitter was operating at full output power with and without internal data modulation. The calculated limit below the unmodulated carrier at +12.1 dBm, including the 20 dB external attenuator and 1 dB cable loss, is +33.1 dBm. The actual limit is 53.1 dBc lower, or -20.0 dB.

TEST RESULTS:

Ref 899 +33.1 (- 53.1) -20.0

| FREQUENCY | LEVEL | LIMIT |
|-----------|-------|---------------|
| MHz | dBm | $d\mathbf{B}$ |
| 899 | 33.1 | |
| 1,798 | -37.0 | -20.0 |
| 2,697 | -39.3 | -20.0 |
| 3,596 | -62.9 | -20.0 |
| 4,495 | -55.1 | -20.0 |
| 5,394 | -39.8 | -20.0 |
| 6,293 | -41.7 | -20.0 |
| 7,192 | -73.1 | -20.0 |
| 8,091 | -57.2 | -20.0 |
| 8,990 | -66.5 | -20.0 |

NOTE:

The above limits take into account the unmodulated carrier level of 33.1 dBm inclusive of the 20 dB external attenuator and 1 dB coaxial cable loss. The modulation used was a worst case, random data pattern while still representing a normal modulation pattern.

EQUIPMENT:

- H.P. 8563E Spectrum Analyzer 9.0 KHz 26.5 GHz
- HP6632A DC POWER SUPPLY
- Mini Circuits 20 dB att. # NAT-20 0 Hz 1.5 GHz