



Name of Test: Emission Masks (Occupied Bandwidth)  
State 1:Low Power




Power: LOW  
Modulation: PCS 1900  
99% BANDWIDTH

**Name of Test:** Emission Masks (Occupied Bandwidth)  
 State 2:High Power



Power: HIGH  
 Modulation: PCS 1900  
 99% BANDWIDTH

Name of Test: Emission Masks (Occupied Bandwidth)  
State 2:High Power



Power: HIGH  
Modulation: PCS 1900  
UPPER BAND EDGE

**Name of Test:** Field Strength of Spurious Radiation

**Specification:** 47 CFR 2.1053(a)

**Guide:** ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16

**Measurement Procedure**


1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement

A) Connect the equipment as illustrated


- B) Adjust the spectrum analyzer for the following settings:
- 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
  - 2) Video Bandwidth  $\geq$  3 times Resolution Bandwidth
  - 3) Sweep Speed  $\leq$ 2000 Hz/second
  - 4) Detector Mode = Mean or Average Power

C) Place the transmitter to be tested on the turntable in the standard test site. If the antenna is detachable, The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



**Name of Test:** Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should cover the measured frequency. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to  $\pm$  the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.
- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna. The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.



**Name of Test:** Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

*Tim Kao*

Tested By:

Tim Kao

---

**SPORTON International Inc.**

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

FCC ID B32OMNI 3750G

Page No. 35 of 58

Issued Date May 20, 2004

**FCC TEST REPORT**

Report No. : F441316

**Name of Test:** Field Strength of Spurious Radiation

GSM 850 (Channel 189)

Freq MHz	Pol	Substitution Antenna Input Power (dBm)	Substitution Antenna Gain (dBd)	Et (dBuV/m)	Es (dBuV/m)	Et - Es (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
118.06	H	-1.09	-1.19	26.22	92.39	-66.17	-68.44	-13.0	-55.44
142.54	H	-1.07	-0.84	35.28	91.93	-56.65	-58.56	-13.0	-45.56
152.23	H	-1.06	-0.37	30.51	91.64	-61.13	-62.56	-13.0	-49.56
252.80	H	-1.44	-0.38	35.67	93.68	-58.01	-59.83	-13.0	-46.83
524.80	H	-1.93	-0.26	36.07	95.09	-59.02	-61.21	-13.0	-48.21
556.80	H	-1.93	-0.55	35.04	95.13	-60.09	-62.57	-13.0	-49.57
1670.00	H	-3.59	4.42	58.56	102.06	-43.50	-42.68	-13.0	-29.68
3342.00	H	-4.91	5.32	48.00	99.63	-51.63	-51.23	-13.0	-38.23
5014.00	H	-6.17	6.25	45.34	98.27	-52.93	-52.85	-13.0	-39.85
6692.00	H	-7.57	6.90	46.08	97.28	-51.20	-51.88	-13.0	-38.88
8820.00	H	-8.89	6.69	46.90	94.26	-47.36	-49.56	-13.0	-36.56
88.31	V	-0.91	0.32	29.26	91.46	-62.20	-62.79	-13.0	-49.79
118.06	V	-1.09	-1.19	29.93	92.39	-62.46	-64.73	-13.0	-51.73
147.47	V	-1.07	-0.50	32.03	91.82	-59.79	-61.35	-13.0	-48.35
272.80	V	-1.39	-0.40	31.83	92.43	-60.60	-62.39	-13.0	-49.39
556.80	V	-1.93	-0.55	36.03	95.13	-59.10	-61.58	-13.0	-48.58
621.60	V	-2.10	-0.91	33.61	94.12	-60.51	-63.51	-13.0	-50.51
1670.00	V	-3.59	4.42	60.86	102.06	-41.20	-40.38	-13.0	-27.38
2748.00	V	-4.86	5.30	41.16	98.77	-57.61	-57.17	-13.0	-44.17
3342.00	V	-4.91	5.32	48.06	99.63	-51.57	-51.17	-13.0	-38.17
5014.00	V	-6.17	6.25	50.47	98.27	-47.80	-47.72	-13.0	-34.72
6692.00	V	-7.57	6.90	47.10	97.28	-50.18	-50.86	-13.0	-37.86
8812.00	V	-8.87	6.70	47.08	94.21	-47.13	-49.29	-13.0	-36.29

**SPORTON International Inc.**

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

FCC ID B32OMNI 3750G

Page No. 36 of 58

Issued Date May 20, 2004

**FCC TEST REPORT**

Report No. : F441316

## PCS 1900 (Channel 661)

Freq MHz	Pol	Substitution Antenna Input Power (dBm)	Substitution Antenna Gain (dBi)	Et (dBuV/m)	Es (dBuV/m)	Et - Es (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
118.06	H	-1.09	0.96	18.59	92.39	-73.80	-73.92	-13.0	-60.92
153.59	H	-1.06	1.75	22.75	91.55	-68.80	-68.12	-13.0	-55.12
192.35	H	-1.22	1.36	30.57	90.45	-59.88	-59.74	-13.0	-46.74
524.80	H	-1.93	1.89	34.43	95.09	-60.66	-60.70	-13.0	-47.70
589.60	H	-1.95	1.28	35.13	94.46	-59.33	-60.00	-13.0	-47.00
621.60	H	-2.10	1.24	35.52	94.12	-58.60	-59.45	-13.0	-46.45
1500.00	H	-3.44	6.50	39.90	102.40	-62.50	-59.44	-13.0	-46.44
1878.00	H	-3.78	6.65	44.48	101.64	-57.16	-54.29	-13.0	-41.29
1958.00	H	-3.85	6.68	41.45	101.48	-60.03	-57.20	-13.0	-44.20
3758.00	H	-5.25	7.45	53.05	99.07	-46.02	-43.82	-13.0	-30.82
5638.00	H	-6.67	8.44	51.64	98.79	-47.15	-45.38	-13.0	-32.38
8910.00	H	-9.17	8.77	47.19	94.83	-47.64	-48.04	-13.0	-35.04
10188.00	H	-10.41	8.92	47.79	96.05	-48.26	-49.75	-13.0	-36.75
58.90	V	-0.86	0.36	20.33	84.05	-63.72	-64.21	-13.0	-51.21
88.31	V	-0.91	2.47	20.97	91.46	-70.49	-68.93	-13.0	-55.93
171.78	V	-1.02	1.72	23.56	90.84	-67.28	-66.57	-13.0	-53.57
524.80	V	-1.93	1.89	34.36	95.09	-60.73	-60.77	-13.0	-47.77
589.60	V	-1.95	1.28	34.61	94.46	-59.85	-60.52	-13.0	-47.52
621.60	V	-2.10	1.24	35.42	94.12	-58.70	-59.55	-13.0	-46.55
1510.00	V	-3.45	6.50	43.19	102.38	-59.19	-56.14	-13.0	-43.14
1884.00	V	-3.79	6.65	46.85	101.63	-54.78	-51.91	-13.0	-38.91
1958.00	V	-3.85	6.68	44.63	101.48	-56.85	-54.02	-13.0	-41.02
3758.00	V	-5.25	7.45	57.33	99.07	-41.74	-39.54	-13.0	-26.54
5638.00	V	-6.67	8.44	54.33	98.79	-44.46	-42.69	-13.0	-29.69
7518.00	V	-8.44	8.52	45.80	94.67	-48.87	-48.79	-13.0	-35.79
9398.00	V	-9.78	8.94	48.87	95.76	-46.89	-47.74	-13.0	-34.74
10188.00	V	-10.41	8.92	47.79	96.05	-48.26	-49.75	-13.0	-36.75

**SPORTON International Inc.**

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255


FCC ID B32OMNI 3750G

Page No. 37 of 58

Issued Date May 20, 2004




**Radiated Scanned Data  
GSM 850, Horizontal Polarization**




Site : 03CH03-HY  
 Condition : 3m BIC-9124--301 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (Idle)

No.	Freq MHz	Level dBuV/m	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
			Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	118.060	26.22	-----	-----	41.59	10.55	1.94	27.86	Peak	---	---
2	142.540	35.28	-----	-----	49.09	11.91	2.09	27.81	Peak	---	---
3	152.230	30.51	-----	-----	43.60	12.45	2.25	27.79	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m LOG-9111-221 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (Idle)

No.	Freq MHz	Level dBuV/m	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
			Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	252.800	35.67	-----	-----	47.91	12.40	2.85	27.49	Peak	---	---
2	524.800	36.07	-----	-----	43.21	17.56	4.03	28.73	Peak	---	---
3	556.800	35.04	-----	-----	41.71	17.94	4.15	28.76	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (link)

1	Freq MHz	Level dBuV/m	Over Limit dB	Limit Line dBuV/m	Read Level dBuV	Probe Factor dB	Cable Loss dB	Preamp Factor dB	Remark	Ant Pos cm	Table Pos deg
1	1670.000	58.56	-----	-----	71.66	26.06	1.55	40.71	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (link)

1	Freq MHz	Level dBuV/m	Over Limit dB	Limit Line dBuV/m	Read Level dBuV	Probe Factor dB	Cable Loss dB	Preamp Factor dB	Remark	Ant Pos cm	Table Pos deg
1	3342.000	48.00	-----	-----	56.28	30.84	2.15	41.27	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (link)


	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		Pos	Pos
1	5014.000	45.34	-----	-----	51.92	33.43	2.61	42.62	Peak	---	---
2	6692.000	46.08	-----	-----	51.58	34.69	2.99	43.18	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (link)


	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		Pos	Pos
1	8820.000	46.90	-----	-----	46.60	38.03	3.41	41.14	Peak	---	---

GSM 850, Vertical Polarization



Site : 03CH03-HY  
 Condition : 3m BIC-9124--301 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (Idle)

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
		dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	88.310	29.26	-----	46.19	9.39	1.60	27.92	Peak	---	---
2	118.060	29.93	-----	45.30	10.55	1.94	27.86	Peak	---	---
3	147.470	32.03	-----	45.40	12.22	2.21	27.80	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m LOG-9111-221 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (Idle)

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
		dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	272.800	31.83	-----	43.64	12.63	2.97	27.41	Peak	---	---
2	556.800	36.03	-----	42.70	17.94	4.15	28.76	Peak	---	---
3	621.600	33.61	-----	38.96	18.90	4.53	28.78	Peak	---	---


**FCC TEST REPORT**

Report No. : F441316



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (lnk)

	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	1670.000	60.86	-----	-----	73.96	26.06	1.55	40.71	Peak	---	---
2	2780.000	41.16	-----	-----	51.11	29.31	1.94	41.20	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (lnk)

	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	3342.000	48.06	-----	-----	56.34	30.84	2.15	41.27	Peak	---	---


**FCC TEST REPORT**

Report No. : F441316



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (link)


Peak	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	5014.000	50.47	-----	-----	57.05	33.43	2.61	42.62	Peak	---	---
2	6692.000	47.10	-----	-----	52.60	34.69	2.99	43.18	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : GSM 850MHz (link)


Peak	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	8812.000	47.08	-----	-----	46.78	38.03	3.42	41.15	Peak	---	---

**PCS 1900, Horizontal Polarization**



Site : 03CH03-HY  
 Condition : 3m BIC-9124--301 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS CH 810

Peak	Freq (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Remark	Ant Pos (cm)	Table Pos (deg)
1	118.060	18.59	-----	-----	33.96	10.55	1.94	27.86	Peak	---	---
2	153.590	22.75	-----	-----	35.80	12.49	2.25	27.79	Peak	---	---
3	192.350	30.57	-----	-----	41.17	14.62	2.49	27.71	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m LOG-9111-221 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS CH 810

Peak	Freq (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Remark	Ant Pos (cm)	Table Pos (deg)
1	524.800	34.43	-----	-----	41.57	17.56	4.03	28.73	Peak	---	---
2	589.600	35.13	-----	-----	40.87	18.74	4.31	28.79	Peak	---	---
3	621.600	35.52	-----	-----	40.87	18.90	4.53	28.78	Peak	---	---




**FCC TEST REPORT**

Report No. : F441316



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHz


Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
-----	-----	53.69	25.36	1.46	40.61	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHz


Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
-----	-----	60.68	31.96	1.82	41.41	Peak	---	---






Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHz

Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1 5638.000	51.64	-----	-----	58.21	34.06	2.53	43.16	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHz


Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1 8910.000	47.19	-----	-----	46.90	38.06	3.24	41.01	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 HORIZONTAL  
 EUT  
 Power : 120V/60Hz  
 Model  
 Memo : PCS 1900MHZ


Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1 10188.000	47.79	-----	-----	44.28	39.04	3.93	39.46	Peak	---	---

**PCS 1900, Vertical Polarization**



Site : 03CH03-HY  
 Condition : 3m BIC-9124--301 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS CH 810

Peak	Freq (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Remark	Ant Pos (cm)	Table Pos (deg)
1	58.900	20.33	-----	-----	36.74	10.29	1.28	27.98	Peak	---	---
2	88.310	20.97	-----	-----	37.90	9.39	1.60	27.92	Peak	---	---
3	171.780	23.56	-----	-----	35.64	13.31	2.37	27.76	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m LOG-9111-221 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS CH 810

Peak	Freq (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Remark	Ant Pos (cm)	Table Pos (deg)
1	524.800	34.36	-----	-----	41.50	17.56	4.03	28.73	Peak	---	---
2	589.600	34.61	-----	-----	40.35	18.74	4.31	28.79	Peak	---	---
3	621.600	35.42	-----	-----	40.77	18.90	4.53	28.78	Peak	---	---


**FCC TEST REPORT**

Report No. : F441316



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHz

1	Freq MHz	Level dBuV/m	Over Limit dB	Limit Line dBuV/m	Read Level dBuV	Probe Factor dB	Cable Loss dB	Preamp Factor dB	Remark	Ant Pos cm	Table Pos deg
1	1510.000	43.19	-----	-----	56.94	25.40	1.46	40.61	Peak	---	---




Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHz

1	Freq MHz	Level dBuV/m	Over Limit dB	Limit Line dBuV/m	Read Level dBuV	Probe Factor dB	Cable Loss dB	Preamp Factor dB	Remark	Ant Pos cm	Table Pos deg
1	3758.000	57.33	-----	-----	64.96	31.96	1.82	41.41	Peak	---	---


**FCC TEST REPORT**

Report No. : F441316




Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHZ

1	Freq MHz	Level dBuV/m	Over Limit dB	Limit Line dBuV/m	Read Level dBuV	Probe Factor dB	Cable Loss dB	Preamp Factor dB	Remark	Ant Pos cm	Table Pos deg
1	5638.000	54.33	-----	-----	60.90	34.06	2.53	43.16	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHZ

1	Freq MHz	Level dBuV/m	Over Limit dB	Limit Line dBuV/m	Read Level dBuV	Probe Factor dB	Cable Loss dB	Preamp Factor dB	Remark	Ant Pos cm	Table Pos deg
1	7518.000	45.80	-----	-----	48.93	36.53	2.72	42.38	Peak	---	---



Site : 03CH03-HY  
 Condition : 3m HORN-ANT-6741 VERTICAL  
 EUT :  
 Power : 120V/60Hz  
 Model :  
 Memo : PCS 1900MHz

1	9398.000	48.87	-----	-----	47.34	37.94	3.75	40.16	Peak	---	---
Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg	
1	9398.000	48.87	-----	-----	47.34	37.94	3.75	40.16	Peak	---	---

**Name of Test:** Frequency Stability (Temperature Variation)

**Specification:** 47 CFR 2.1055(a)(1)

**Test Conditions:** As Indicated

**Test Equipment:** As per previous page

#### **Measurement Procedure**

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to  $-30^{\circ}\text{C}$  and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. Measurement Results: Attached



Tested By:

Tim Kao

---

***SPORTON International Inc.***

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255


FCC ID B32OMNI 3750G

Page No. 52 of 58

Issued Date May 20, 2004

**Transmitter Test Set-Up**

Frequency Stability: Temperature Variation  
Frequency Stability: Voltage Variation



Asset	Model Name	S/N
Temperature & Humidity Controller	P-9000	612
AC/DC Power Source	HPA-500W	HPA0100024
Base Station Simulator	CMU200	102278
Base Station Simulator	E5515C	GB43460754



**Name of Test:** Frequency Stability (Temperature Variation)**GSM 850 (Channel 189)**

Temperature(°C)	Change, Hz	Change, ppm
-30	34	0.02
-20	28	0.01
-10	21	0.01
0	19	0.01
10	16	0.01
20	15	0.01
30	18	0.01
40	19	0.01
50	21	0.01

**PCS 1900 (Channel 611)**

Temperature(°C)	Change, Hz	Change, ppm
-30	43	0.02
-20	35	0.02
-10	31	0.02
0	30	0.02
10	29	0.02
20	26	0.01
30	29	0.02
40	28	0.01
50	34	0.02

**Name of Test:** Frequency Stability (Voltage Variation)**Specification:** 47 CFR 2.1055 (b)(1)**Test Equipment:** As per previous page**Measurement Procedure**

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

**Results:** Frequency Stability (Voltage Variation)

GSM 850 (Channel 189)

Nominal Value (Voltage) = 24.0

Voltage(Volt)	Change, Hz	Change, ppm
24.0	15	0.01
20.4	26	0.01
27.6	18	0.01

PCS 1900 (Channel 611)

Nominal Value (Voltage) = 24.0

Voltage(Volt)	Change, Hz	Change, ppm
24.0	26	0.01
20.4	38	0.02
27.6	25	0.01

Limit: Must remain within authorized frequency block.

Tested By:

Tim Kao

**Antenna Factor & Cable Loss**

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)
30	15.35	4.50	1000	24.10	3.92
35	13.63	1.13	2000	27.40	5.66
40	11.11	1.18	3000	30.00	7.20
45	10.59	1.26	4000	32.60	9.36
50	6.47	1.31	5000	33.40	9.16
55	5.83	1.34	6000	34.20	10.70
60	5.18	1.43	7000	35.30	12.16
65	4.81	1.52	8000	36.90	13.12
70	4.43	1.56	9000	38.10	13.81
75	5.10	1.57	10000	39.00	14.83
80	5.91	1.60	11000	38.60	15.83
85	7.33	1.66	12000	39.50	17.11
90	8.74	1.75	13000	39.30	17.62
95	9.05	1.76	14000	41.60	18.37
100	9.36	1.83	15000	40.60	19.10
110	9.65	1.86	16000	37.20	19.72
120	9.97	1.92	17000	40.20	21.98
130	10.51	2.00	18000	48.90	21.22
140	10.32	2.11	19000	37.60	23.90
150	9.42	2.18	20000	37.30	24.07
160	8.09	2.22	21000	37.00	25.49
170	7.43	2.26	22000	38.00	24.92
180	7.60	2.31	23000	38.70	25.60
190	7.43	2.37	24000	38.60	25.70
200	7.26	2.43	25000	24.10	3.92
220	9.11	2.56	14000	27.40	5.66
240	10.88	2.70	15000	30.00	7.20
260	11.75	2.83	16000	32.60	9.36
280	11.55	2.93	17000	33.40	9.16
300	11.36	3.03	18000	34.20	10.70
320	12.03	3.13	19000	35.30	12.16
340	12.69	3.23	20000	36.90	13.12
360	13.33	3.32	21000	38.10	13.81
380	14.00	3.41	22000	39.00	14.83
400	14.63	3.48	23000	38.60	15.83
450	15.33	3.71	24000	39.50	17.11
500	16.03	3.85	25000	39.30	17.62
550	16.65	4.03			
600	17.29	4.32			
650	17.64	4.51			
700	18.00	4.54			
750	18.39	4.90			
800	18.79	5.04			
850	19.10	5.04			
900	19.42	5.20			
950	19.58	5.28			
1000	19.75	5.58			

**List of Measuring Equipments**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz~1GHz 3m	Jun. 21, 2003	Radiation (03CH03-HY)
Spectrum analyzer	R&S	FSP40	100004	9KHZ~40GHz	Aug. 23, 2003	Radiation (03CH03-HY)
Amplifier	HP	8447D	2944A09072	100KHz – 1.3GHz	Nov. 05, 2003	Radiation (03CH03-HY)
Biconical Antenna	SCHWARZBECK	VHBB 9124	301	30MHz –200MHz	Jul. 24, 2003	Radiation (03CH03-HY)
Log Antenna	SCHWARZBECK	VUSLP 9111	221	200MHz -1GHz	Jul. 24, 2003	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz~1GHz	Dec. 03, 2003	Radiation (03CH03-HY)
Amplifier	MITEQ	AFS44	879981	100MHz~26.5GHz	Jul. 23, 2003	Radiation (03CH03-HY)
Horn Antenna	COM-POWER	3115	6821	1GHz – 18GHz	Sep. 12, 2003	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Horn Antenna	Schwarzbeck	BBHA9170	154	15GHz~40GHz	Jun. 02, 2003	Radiation (03CH03-HY)
RF Cable-HIGH	Jye Bao	RG142	CB030-HIGH	1GHz~29.5GHz	Dec. 05, 2003	Radiation (03CH03-HY)

- ※ Calibration Interval of instruments listed above is one year, except for Horn Antenna, BBHA9170.
- ※ Calibration Interval of Horn Antenna, BBHA9170, is three years.

**Uncertainty of Test Site**

Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Contribution	Uncertainty of $x_i$		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch Receiver VSWR $\Gamma_1 = 0.20$ Antenna VSWR $\Gamma_2 = 0.23$ Uncertainty = $20\log(1-\Gamma_1*\Gamma_2)$	+0.39/-0.41	U-shaped	0.28
<b>combined standard uncertainty Uc(y)</b>			<b>1.27</b>
<b>Measuring uncertainty for a level of confidence of 95% U=2Uc(y)</b>			<b>2.54</b>

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Contribution	Uncertainty of $x_i$		$u(x_i)$	$C_i$	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\log(1-\Gamma_1*\Gamma_2*\Gamma_3)$	+0.34/-0.35	U-shaped	0.244	1	0.244
<b>Combined standard uncertainty Uc(y)</b>			<b>2.36</b>		
<b>Measuring uncertainty for a level of confidence of 95% U=2Uc(y)</b>			<b>4.72</b>		

$U = \sqrt{\{(1/2)^2 + (0.3/2)^2 + (2^2 + 0.5^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\}} = 2.2$  for 10m test distance

$U = \sqrt{\{(1/2)^2 + (0.3/2)^2 + (2^2 + 3^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\}} = 2.7$  for 3m test distance

END OF TEST REPORT