



RF EXPOSURE REPORT (FOR BLUETOOTH)

REPORT NO.: SA111021C03A
MODEL NO.: VX600 Bluetooth
FCC ID: B32VX600BTCTLS
RECEIVED: Oct. 24, 2011
TESTED: Oct. 26 ~ Nov. 07, 2011
ISSUED: Feb. 23, 2012

APPLICANT: VeriFone, Inc.

ADDRESS: 1400 West Stanford Ranch Road Suit 200 Rocklin CA
95765 USA

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. REDUCED CONDITION FOR SAR	5
3. MAXIMUM MEASURED POWER OF EUT	5
4. CONCLUSION	5



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Feb. 23, 2012



1. CERTIFICATION

PRODUCT: Point of Sale Terminal
MODEL: VX600 Bluetooth
BRAND: VeriFone
APPLICANT: VeriFone, Inc.
TESTED: Oct. 26 ~ Nov. 07, 2011
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 2 (Section 2.1093)**
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment (model: VX600 Bluetooth) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Ivy Lin , DATE: Feb. 23, 2012
Ivy Lin / Specialist

APPROVED BY : Gary Chang , DATE: Feb. 23, 2012
Gary Chang / Technical Manager

2. REDUCED CONDITION FOR SAR

When output power is $\leq 60/f(\text{GHz})$ mW, SAR evaluation is not required.

3. MAXIMUM MEASURED POWER OF EUT

Mode	Conducted power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Threshold for SAR (dBm)
Bluetooth	0.38	1.02	1.40	13.84

4. CONCLUSION

No SAR evaluation is required since output power of EUT is less than threshold of SAR.