** For Official Use Only *** (ALL INFORMATION IN THIS DOCUMENT IS PROPRIETARY)

| RE/ | /IQI | | ш | STO | RΥ |
|----------|------|---|---|-------|--------------|
| Γ | , , | v | | 3 I U | \mathbf{r} |

| REV | DESCRIPTION | DATE | APPROVED |
|-----|-------------|----------|----------|
| Q4 | Q4 | 05/27/10 | |
| | | | |
| | | | |
| | | | |
| | | | |

GUARDIAN II PORTABLE LABEL SET

| Al | PPROVA | L SIGNATURES | | DATR | Z |
|---------------------------|---------|--------------|------|--------------------|--------------|
| ORIGINATOR | DATE | QA | DATE | | |
| WILSON | 5/27/10 | | | Guardian II Portab | e I abel Set |
| SUSTAINING ENGINEERING | | | | Guardian in Tortas | 0 Luboi 00t |
| | | | | DOCUMENT NO. | REV |
| MFG. ENGINEERING | | | | S991123 | Q4 |
| | | | | SHEET 1 | of 3 |

ALL INFORMATION IN THIS DOCUMENT IS PROPRIETARY

Notes:

- 1. Material = Matte metalized polyester thermal transfer printable label Brady # TLSPC, B-486, 1.125" x .875" (DWC part number TBD)
- 2. Label set consists of four labels. 4 each of p/n TBD
- 3. Serial Number is derived when the unit is plugged to the computer and read the program.
- 4. Revision level is issued by the Configuration Control Department.
- 5. Labels are printed with text indicated on Sheet 2. Referenced fonts are using Brady LabelMark Software (current version) and Windows Operating System.
- 6. Labels are printed with Brady thermal printer TLS PCLink.

| DATRO | ν |
|--------------|---------------|
| DOCUMENT NO. | REV |
| S991123 | Q4 |
| SHEET | 2 OF 3 |

ALL INFORMATION IN THIS DOCUMENT IS PROPRIETARY **ALL FONTS ARE** ARIAL FCC ID: B3TG2P150 2 ROWS - FONT 5 IC: xxxxxxxxxxx This device complies with part 15 of 4 ROWS - FONT 4 the FCC rules. Operation is subject to the condition that this device does not cause harmful interference. This device made under license 7 ROWS - FONT 4 under one or more of the following U.S. patents: 4590473, 4636791, 4833701, 4972460, 5146497, 5148482, 5164986, 5185795, 5185796, 5164986, 5185796, 5271017, 5377229. 1 ROW - FONT 6 **ATTENTION** Restricted to occupational use to satisfy FCC RF exposure limits. 4 ROWS - FONT 5 See user manual for operating requirements MODEL NUMBER AND **Datron World Communications Inc.** REVISION PER CONFIGURATION Vista, CA USA www.dtwc.com 2 ROWS - FONT 5 CONTROL Model G2P-XXX-XXX REV. X ◆ 5 DIGIT SERIAL NUMBER Serial no. XXXXX 4 ROWS - FONT 6 Options: XXXXX PER WORK/SALES ORDER MADÈ IN USA 310 DATRON DOCUMENT NO. REV

S991123

04

SHEET 3 OF 3

| ** For Official Use Only *** (ALL INFORMATION IN THIS DOCUMENT IS PROPRIETARY) | | |
|---|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

DATRON GII Label Locations

