

Intentional Radiator Test Report

For the

Nautel Limited

FM Broadcast Transmitter Model VX150

Tested under

The FCC Rules contained in Title 47 of the CFR, Part 73 Subpart G and Part 74 Subpart L for

Radio Broadcast Services

February 26, 2021

Prepared for:

Nautel Limited

10089 Peggy's Cove Road,

Hackett's Cove, Nova Scotia, Canada B3Z 3J4

Prepared By:

H.B. Compliance Solutions

5005 S. Ash Avenue, Suite A-10

Tempe, Arizona 85282

Reviewed By:

Hoosamuddin Bandukwala



Cert # ATL-0062-E

Engineering Statement: The measurements shown in this report were made in accordance with the procedure indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurement made, the equipment tested is capable of operation in accordance with the requirements of Part 74 of the FCC Rules under normal use and maintenance. All results contained herein relate only to the sample tested.



Report Status Sheet

Revision #	Report Date	Reason for Revision	
Ø	August 21, 2020	Initial Issue	
1	February 26, 2021	Corrected high band channel	



Table of Contents

EXECU	TIVE SUMMARY	4
1.	Testing Summary	4
EQUIPI	MENT CONFIGURATION	5
1.	Overview	5
2.	Test Facility	6
3.	Description of Test Sample	7
4.	Equipment Configuration	7
5.	Support Equipment	7
6.	Ports and Cabling Information	7
7.	Method of Monitoring EUT Operation	8
8.	Mode of Operation	8
9.	Modifications	8
10.	Disposition of EUT	8
Criteria	a for Intentional Radiators	9
1.	RF Power Output	9
2.	Modulation Characteristics	12
3.	Occupied Bandwidth (Emission Mask)	15
4.	Spurious Emissions at Antenna Terminals	19
5.	Radiated Spurious Emissions	23
6.	Frequency Stability vs Temperature	27
7.	Frequency Stability vs Voltage	29
8.	Necessary Bandwidth	31
9.	Test Equipment	32
10.	Measurement Uncertainty	



EXECUTIVE SUMMARY

1. Testing Summary

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with CFR 47 FCC Part 73 and 74. All tests were conducted using measurement procedure from ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9kHz to 40GHz and ANSI C63.26-2015 Procedures for Compliance Testing of Transmitters Used in Licensed Radio Services as appropriate.

Test Name	Test	Result	Comments
	Method/Standard		
RF Output Power	§2.1046; §73.811,	Pass	
	§74.1235		
Modulation	§2.1047(a);	Pass	
Characteristics	§73.1590		
Occupied Bandwidth	§2.1049; §73.317,	Pass	
	§74.1236		
Spurious Emissions at	§2.1051; §73.317;	Pass	
Antenna Terminals	§74.1236		
Radiated Spurious	§2.1053	Pass	
Emissions			
Frequency Stability over	§2.1055(a)(1);	Pass	
Temperature Variations	§73.1545(b);		
	§74.1261		
Frequency Stability over	§2.1055(d);	Pass	
Voltage Variations	§73.1545(b);		
	§74.1261		



EQUIPMENT CONFIGURATION

1. Overview

H.B Compliance Solutions was contracted by Nautel Limited to perform testing on the FM Broadcast Transmitter VX150 under the purchase order number 10096213.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Nautel Limited, FM Broadcast Transmitter VX150.

The tests were based on FCC Part 90 Rules. The tests described in this document were formal tests as described with the objective of the testing was to evaluate compliance of the Equipment Under Test (EUT) to the requirements of the aforementioned specifications. Nautel Limited should retain a copy of this document and it should be kept on file for at least five years after the manufacturing of the EUT has been permanently discontinued. The results obtained relate only to the item(s) tested.

Product Name:	FM Broadcast Transmitter
Model(s) Tested:	VX150
FCC ID:	B3W-VX150
Supply Voltage Input:	Primary Power: 230 Vac
Frequency Range:	88MHz to 108MHz
No. of Channels:	N/A
Necessary Bandwidth	180kHz
Type(s) of Modulation:	FM
Range of Operation Power:	15W to 150W
Voltage into final Transistor	24.75 volts
Current into final Transistor	8.67 amps
Emission Designator:	180KF3E
Channel Spacing(s)	None
Test Item:	Pre-Production
Type of Equipment:	Fixed
Antenna:	External N Connector – Device is not sold with antenna
Environmental Test	Temperature: 15-35°C
Conditions:	Humidity: 30-60%
	Barometric Pressure: 860-1060 mbar
Modification to the EUT:	None
Evaluated By:	Staff at H.B. Compliance Solutions
Test Date(s):	08/03/2020 till 08/24/2020
Firmware Number	0.0.0.3
PCBA Version	C



All testing was performed at H.B. Compliance Solutions. This facility is located at 5005 S. Ash Avenue, Suite # A-10, Tempe AZ-85282. All equipment used in making physical determination is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements from 30MHz to 1GHz were performed in a GTEM chamber (equivalent to an Open Area Test Site). Radiated Emission above 1GHz were performed on an Open Area Test Site (OATS). In accordance with §2.948(a)(3), a complete site description is contained at H.B. Compliance Solutions.

Test facility H.B. Compliance Solutions is an ANAB accredited test site. The ANAB certificate number is L2458. The scope of accreditation can be found on ANAB website <u>www.anab.org</u>

ISED Test Site Registration number is 9481A





3. Description of Test Sample

The Nautel, VX150 FM Broadcast transmitter is a FM transmitter with rated 150W in a compact 2RU rack mounted design. The key parameters for this series are improved cost, increased power density, and industry leading efficiency.

This transmitter is intended to be used by licensed FM broadcasting services and have been designed for use in a traditional transmission sites with controlled access and adequate services for transmitter operation.

4. Equipment Configuration

Ref. ID	Name / Description	Model Number	Serial Number
#1 F	FM Transmitter	VX150	10011320

Table 1. Equipment Configuration

5. Support Equipment

All support equipment supplied is listed in the following Support Equipment List.

Ref ID	Name / Description	Manufacturer	Model #	Serial #
# 2	2kW 30dB RF Load	Bird	8329	120501251

Table 2. Support Equipment

6. Ports and Cabling Information

Ref ID	Port	Cable Description	Qty.	Length (m)	Shielded?	Termination
	name on				(Y/N)	Box ID &
	the EUT					Port ID
# 3	RF Out	RG 393 with 7/16	1	1.5	Y	# 2
		DIN				
# 4	AC In	C19	1	2.5	Ν	AC Power
# 5	Analog	XLR3	2	1.5	Y	Audio
	Audio					Source

Table 3. Ports and Cabling Information



7. Method of Monitoring EUT Operation

A test receiver will be used to monitor the data transmission from the EUT.

8. Mode of Operation

The EUT will be configured to transmit at maximum power level. Test mode was provided to select the lower, middle and upper band of the transmitter by customer provided front panel access to the software. These settings were created for testing purpose only.

9. Modifications

9.1 Modifications to EUT

No modifications were made to the EUT

9.2 Modifications to Test Standard

No Modifications were made to the test standard.

10. Disposition of EUT

The test sample including all support equipment submitted to H.B Compliance Solutions for testing will be returned to Nautel Limited upon completion of testing & certification.



Criteria for Intentional Radiators

1. **RF Power Output**

Test Requirement(s):	§2.1046; §73.811 and §74.1235	Test Engineer(s):	Sean Eggleston
Test Results:	Pass	Test Date(s):	02/26/2021

Test Procedures: As required by 47 CFR 2.1046, RF Power output measurements were made at the RF output terminals of the EUT.

Customer provided a test mode internal to the EUT to control the RF modulation, and frequency channel. The EUT was connected through an attenuator to a Spectrum Analyzer capable of making power measurements. Measurements were made at the low, mid, and high channels of the entire frequency band.

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Rated Output Power (W)
88.0	51.69	147.6	150
98.0	51.64	145.8	150
107.9	51.56	143.2	150

Table 4. RF Power Output, Test Results

Test Setup:



Figure 1 Output RF power Test Setup















Plot 3 – Output Power – High



2. Modulation Characteristics

Test	§2.1047 and §73.1590	Test Engineer(s):	Sean Eggleston
Requirement(s):			
Test Results:	Pass	Test Date(s):	08/11/2020

Test Procedure:As required by 47 CFR 2.1047, Modulation characteristics measurements
were made at the RF output terminals of the EUT. Measurements were
made in accordance with the procedures of the ANSI C63.26-2015

Customer provided a test mode internal to the EUT to control the RF modulation, and frequency channel. The EUT was connected through an attenuator to an Spectrum Analyzer.

For Modulating Limiting – Data was plotted as a percentage of deviation relative to the 0 dB reference point versus input voltage.

For Audio Response – As per standard a curve or equivalent data showing frequency response of the audio modulating circuit shall be submitted.

The plot(s) of the modulation characteristic is presented hereinafter as reference.

Test Setup:



Figure 2: Modulation Characteristics Bandwidth Test Setup



Test Results:

	Peak Frequency	Peak Frequency	Peak Frequency	Peak Frequency
Modulation Level	Deviation	Deviation	Deviation @	Deviation @
(dB)	@300Hz	@1000Hz	2500Hz	3000Hz
20	75	75	75	75
15	75	75	75	75
10	75	75	75	75
5	75	75	75	75
0	45.6	46.1	45.8	46.1
-5	36.6	36.1	32.3	28.2
-10	20.65	25.2	18.24	26.6
-15	11.68	15.3	10.32	15.28
-20	6.63	8.67	5.88	8.65

Table 5. Modulating Limiting, Test Results



Plot 4 – Modulating Limiting





Plot 5 – Audio Frequency Response



3. Occupied Bandwidth (Emission Mask)

Test	§2.1049; §73.317 and	Test Engineer(s):	Keith T.
Requirement(s):	§74.1236		
Test Results:	Pass	Test Date(s):	02/26/2021

Test Procedure: As required by 47 CFR 2.1049, occupied bandwidth measurements were made at the output terminals of the EUT.

Customer provided a test mode internal to the EUT to control the RF modulation, and frequency channel. The EUT was connected through an attenuator to a Spectrum Analyzer. The measured highest peak power was set relative to zero dB reference. The RBW of the Spectrum Analyzer was set to at least 1% of the channel bandwidth. Measurements were carried out at the low, mid and high channels of the TX band.

Test Setup:



Figure 3: Occupied Bandwidth Test Setup

The following pages show measurements of Emission Mask plots:





Plot 6 – Low Channel 15 kHz @ 85%



Plot 7 – Mid Channel 15 kHz @ 85%





Plot 8 – High Channel 15 kHz @85%



Plot 9 – Low Channel





Plot 10 – Mid Channel



Plot 11 – High Channel



4. Spurious Emissions at Antenna Terminals

Test	§2.1051; §73.317 and	Test Engineer(s):	Sean E.
Requirement(s):	§74.1236		
Test Results:	Pass	Test Date(s):	08/14/2020

Test Procedures:As required by 47 CFR 2.1051, spurious emissions at antenna
terminal measurements were made at the RF output antenna
terminal of the EUT.

Customer provided a test mode internal to the EUT to control the RF modulation, and frequency channel. The EUT was connected through an attenuator to a Spectrum Analyzer. The Spectrum Analyzer was set to sweep from 9kHz up to 10th harmonic of the fundamental or 40GHz whichever is the lesser. Measurements were made at the low, mid and high frequency of the transmit band.

Test Setup:



Figure 4: Spurious Emission at Antenna Terminal Test setup



ж А	🔆 Agilent 15:28:05 Aug 14, 2020							R	Т		
Ref 35	dBm		At	ten 10 di	3						
Norm Log											*
12 dB/										DC	Coupled
0ffst 62.8 dB											
 DI 13.0											
dBm LaAv	land.										
V1 S2					tereting tereting			at in the second	alari tekar	in a station of	والراجع أرتجار إفاد وحمر
S3 FC AA											
£ (f): FTun											
Ѕ₩р											
Start S) kHz W 20 kU-							¢		Stop 30.	000 MHz
™Nes D	M DU KHZ				VDM DI K	11Z		. JW	eep .	JE IIIS (OK	ρου μιs/_

Plot 12 – Low Band



Plot 13 – Low Band



🔆 🔆 🗛	gilent 15:	29 : 43 Au	ig 14, 20	20				R	Т			
Ref 35	dBm		At	ten 10 di	3					Mkr1 –	28.14 25.5	40 MHz 4 dBm
Norm Log												*
12 dB/										[oc¦ c	oupled
62.8 dB												
DI <u>-</u> 13.0												
dBm LgAv	4											
V1 S2		in this such	in the second	halan ja jilah		ula istaali	la pilla registra	Hele h		ua junți d	spi de	
S3 FC AA												
£(f): F⊤un												
Ѕพр												
Start S	9 kHz									Stop 3	30.00	10 MHz
#Res B	3W 30 kHz				VBW 91 kl	Hz		_ Sw	eep	32 ms ((800	0 pts)_

Plot 14 – Mid Band



Plot 15 – Mid Band



· 米 A	Agilent 15:30:17 Aug 14, 2020							R 1	Г		
Ref 35	dBm		At	ten 10 dl	3					Mkr1 21 –25	.620 MHz .21 dBm
Norm Log											*
12 dB7										DC	Coupled
62.8 dB											
DI -13.0											
dBm LgAv	telefit and an										
			an air ar bi	and the second second	والمرابة والقار المرابة	- In the state of the state	والمحاول والمحاولة	- 1 - 1 - 1 - 1 - 1	1. J. A.	A CONTRACTOR OF THE	the test of the
V1 S2								and here	10.00		
S3 FC AA											
£(f): F⊤un											
Ѕ₩р											
Start <u>9</u>	kHz									Stop 30.	000 MHz
#Res B	W 30 kHz				VBW 91 k	Hz		Swe	ep	32 ms (80	000 pts)_

Plot 16 – High Band

Ж А	gilent 15:	30:45 Au	ıg 14, 20	20				RT		
Ref 35	dBm		At	ten 10 dl	В				Mkr1 81 –24	.0.93 MHz 1.46 dBm
Norm Log										*
12 dB/ 055-+										
62.8 dB										
DI -13.0										
dBm LgAv										
	 alphalistic et al. 					i a di kata kata sa kata Manazarta	il de la la la la constant de la sur- la constant de la constant de la constant			
V1 S2										
S3 FC AA										
£ (f): FTun										
Swp										
Start_3	30.00 MHz								Stop 1.10	0 00 GHz
#Res B	W 30 kHz				VBW 91 k	Hz		Sweep 1	.135 s (8	000 pts)_

Plot 17 – High Band



5. Radiated Spurious Emissions

Test	§2.1053 and §74.1236	Test Engineer(s):	Sean E.
Requirement(s):			
Test Results:	Pass	Test Date(s):	08/03/2020

Test Procedures: As required by 47 CFR 2.1053, field strength of radiated spurious measurements was made in accordance with the procedures of the ANSI C63.26-2015.

The EUT was placed on a wooden table inside a GTEM chamber. The EUT was transmitting into a 50Ω non-radiating load which was directly connected to the EUT antenna port.

The measurement antenna was set at 3 meters from the EUT. During the tests, EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3 orthogonal axis. The frequency range up to the 10th harmonic was investigated.

To get a maximum emissions level from the EUT, the EUT was rotated throughout the X-axis, Y-axis and Z-Axis. Worst case is X-

Frequency	Detector	Resolution	Video	Span
Range	Setting	Bandwidth	Bandwidth	
30MHz –	Peak	120kHz	As Specified in	Zero
1000 MHz			§15.35(c)	
1000 MHz –	Peak	1MHz	1MHz	As
5GHz				necessary
1000 MHz –	Average	1MHz	10Hz	0 Hz
5GHz				

Table 5. Analyzer Settings

Limit: Any emissions appearing on a frequency removed from the carrier by more than 600kHz must be attenuated at least 43 + 10Log₁₀ (Power, in watts) dB below the level of the unmodulated carrier, or 80dB, whichever is the lesser attenuation.



Test Setup:



Figure 5 – Radiated Spurious Emissions



Plot 14 – Low Band









Plot 14 – High Band



Test Results:

Frequency (MHZ)	Peak Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
175	36.5	84.38	-47.88
350	48.3	84.38	-36.08
437.5	54.5	84.38	-29.88
525	47.3	84.38	-37.08
875	40.0	84.38	-44.38
962.5	41.2	84.38	-43.18

Table 5 - Spurious Radiated Emission Data – Low Band

Frequency (MHZ)	Peak Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
195.4	34.1	84.38	-50.28
488.5	42.0	84.38	-42.38
586.2	40.1	84.38	-44.28
683.9	35.7	84.38	-48.68
781.6	35.0	84.38	-49.38
977.0	48.6	84.38	-35.78

Table 6 – Spurious Radiated Emission Data – Mid Band

Frequency	Peak Amplitude	Limit	Margin
(MHZ)	(dBuV/m)	(dBuV/m)	(dB)
216	37.0	84.38	-47.38
324	52.6	84.38	-31.78
432	48.6	84.38	-35.78
540	46.2	84.38	-38.18
864	42.5	84.38	-41.88

Table 7 – Spurious Radiated Emission Data – High Band

Note: ERP Limit = -13dBm which converts to 84.38dBuV/m @ 3meter



6. Frequency Stability vs Temperature

Test	§2.1055; §73.1545(b)	Test Engineer(s):	Jerry M.
Requirement(s):	and §74.1261		
Test Results:	Pass	Test Date(s):	08/24/2020

Test Procedures:As required by 47 CFR 2.0155, Frequency Stability measurements were
made at the RF antenna output terminals of the EUT.

The EUT was placed in an Environmental Chamber with all the support equipment outside the chamber. The EUT was set to transmit a modulated carrier. The reference frequency at 20°C was observed and noted down. The frequency drift was investigated for every 10°C increment until the unit was stabilized then recorded the reading in tabular format with the temperature range of -30°C to 50°C.

Test Setup:



Figure 6 – Frequency Stability Test Setup



Test Results:

Temperature centigrade	Measured Frequency (MHz)	Upper Margin (MHz)	Lower Margin (MHz)	Limit
-30	98.099921	-0.0020790	0.001921	±2kHz
-20	98.099903	-0.0020970	0.001903	±2kHz
-10	98.099904	-0.0020960	0.001904	±2kHz
0	98.099903	-0.0020970	0.001903	±2kHz
10	98.099905	-0.0020950	0.001905	±2kHz
20	98.099902	-0.0020980	0.001902	±2kHz
30	98.099901	-0.0020990	0.001901	±2kHz
40	98.099900	-0.0021000	0.001900	±2kHz
50	98.099902	-0.0020980	0.001902	±2kHz

 Table 8 – Temperature vs Frequency Test Result



Plot 21 – Temperature vs Frequency



7. Frequency Stability vs Voltage

Test	§2.1055; §73.1545(b)	Test Engineer(s):	Jerry Mejak
Requirement(s):	and §74.1261		
Test Results:	Pass	Test Date(s):	08/24/2020

Test Procedures: As required by 47 CFR 2.0155, Frequency Stability measurements were made at the RF antenna output terminals of the EUT.

The EUT was connected to a variable AC source. The frequency was measured at both the nominal 230Vac of the EUT and at the extreme lower and upper voltages.

With the voltage set to a measurement point, the transmitted signal was captured by the spectrum analyzer and the frequency value determined. The frequencies are compared to the tuned frequency. All data for these measurements are found in the table 9.

Reference Frequency: 98.1MHz at 230Vac at 20°C

Test Setup:







Test Results:

Input Voltage (Vdc)	Measured Frequency (MHz)	Upper Margin (MHz)	Lower Margin (MHz)
230.00	98.09990	-0.98110	0.98090
195.50	98.09990	-0.98110	0.98090
264.50	98.09990	-0.98110	0.98090

Table 9. Ten	nperature vs.	Voltage	Test	Result
--------------	---------------	---------	------	--------



Plot 22 – Temperature vs Voltage



8. Necessary Bandwidth

Referencing Part 2.202 of the FCC Rules and Regulation and using the following formula for calculating the Necessary Bandwidth for Sound broadcasting

B = 2M + 2DK

Where M = Baud Rate, D = Deviation and K= Constant

Calculation

M = 15K

Peak Deviation of Carrier (D) = 75kHz

K = 1

Bn = 2(15kHz) + 2(75kHz) (1) = 180kHz

Emission Designator: 180KF3E



9. Test Equipment

Equipment	Manufacturer	Model	Serial #	Last Cal	Cal Due
				Date	Date
Digital Multimeter	Fluke	77 III	72550270	Apr-10-20	Apr-10-21
Spectrum Analyzer	Agilent	E4443A	US41420164	Jan/03/20	Jan/03/21
Temperature Chamber	Test Equity	1207C	60161	Aug/31/20	Aug/31/21
Antenna	EMCO	GTEM 5417	1063	Ver	ified
Spectrum Analyzer	Hewlett Packard	8563E	3821A09316	May/01/20	May/01/21
Modulation Analyzer	Hewlett Packard	8901B	2806A01528	Aug/24/20	Aug/24/21
Function Generator	Wavetek	145	L6610707	Verified	
Band Stop Filter	Mini-Circuits	ZX7BS- 88108S+	None	Ver	ified
EMI Receiver	Hewlett Packard	8568B	2314A02642	11-Oct-19	11-Oct-20
Signal Generator	Agilent	E4432B	US40053021	Sep/23/19	Sep/23/20
Attenuator 30dB	Weinschel	33-30-34	8F1679	Verified	
Horn Antenna	Com-Power	AHA-118	711150	Nov/12/18	Nov/12/20
Diode/Crystal Detector	H.P.	8470B	None	Ver	ified
Combiner/Splitter	Mini-Circuits	ZFSC-2-2	None	Verified	
Oscilloscope	Tektronix	TDS 3052	B013389	Oct/10/19	Oct/10/20

Table 11 – Test Equipment List

*Statement of Traceability: Test equipment is maintained and calibrated on a regular basis. All calibrations have been performed by a 17025 accredited test facility, traceable to National Institute of Standards and Technology (NIST)



10. Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. These measurements figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2. Instrumentation measurement uncertainty has **not** been taken into account to determine compliance.

The following measurement uncertainty values have been calculated as show in the table below:

Measured Parameter	Measurement Unit	Frequency Range	Expanded Uncertainty
Conducted Emissions (AC	dBuV or dBuA	150kHz – 30MHz	± 4.3dB
Power)			
RF Power, Conducted	dBm	150kHz – 18GHz	± 0.2dB
Radiated Emissions below 1GHz	dBuV/m	30 – 1000MHz	± 5.6dB
Radiated Emissions above 1GHz	dBuV/m	1 – 26.5GHz	± 4.1dB

The reported expanded uncertainty has been estimated at a 95% confidence level (k=2)

END OF TEST REPORT