

TEST REPORT

Applicant Name : FCC: Porta Phone Company Inc
 ISEDC: PORTA PHONE CO., INC.

Address : FCC: 145 Dean Knauss Drive Narragansett, Rhode Island 02882
 United States
 ISEDC: 145 Dean Knauss Drive Narragansett, RI 02882, United States of America

Report Number : SZNS211206-61773E-RF
 FCC ID: B4HEVXM
 IC: 3064A-EVXM

Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-247, ISSUE 2, FEBRUARY 2017

Sample Description

Product Type: 2.4 GHz Transceiver-Main
 Model No.: EVX-MS
 Multiple Model(s) No.: EVX-MD (Please refer to DOS for Model difference)
 Trade Mark: N/A
 Date Received: 2021/12/06
 Date of Test: 2021/12/25~2022/03/04
 Report Date: 2022/03/04

| | |
|--------------|-------|
| Test Result: | Pass* |
|--------------|-------|

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Black Ding

Black Ding
 EMC Engineer

Approved By:

Robert Li

Robert Li
 EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*" .

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "**". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
 Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION..... | 4 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 4 |
| OBJECTIVE | 4 |
| TEST METHODOLOGY | 4 |
| MEASUREMENT UNCERTAINTY | 5 |
| TEST FACILITY | 5 |
| SYSTEM TEST CONFIGURATION..... | 6 |
| DESCRIPTION OF TEST CONFIGURATION | 6 |
| EUT EXERCISE SOFTWARE | 6 |
| SPECIAL ACCESSORIES..... | 6 |
| EQUIPMENT MODIFICATIONS | 6 |
| SUPPORT EQUIPMENT LIST AND DETAILS | 7 |
| EXTERNAL I/O CABLE..... | 7 |
| BLOCK DIAGRAM OF TEST SETUP | 7 |
| SUMMARY OF TEST RESULTS | 8 |
| TEST EQUIPMENT LIST | 9 |
| FCC§15.247 (I), §1.1307 (B) (1) & §2.1093 – RF EXPOSURE | 10 |
| APPLICABLE STANDARD | 10 |
| RSS-102 – RF EXPOSURE..... | 11 |
| APPLICABLE STANDARD | 11 |
| FCC §15.203 & RSS-GEN §6.8– ANTENNA REQUIREMENT | 12 |
| APPLICABLE STANDARD | 12 |
| ANTENNA CONNECTOR CONSTRUCTION | 12 |
| FCC §15.205, §15.209 & §15.247(D) & RSS-247§ 5.5 – RADIATED EMISSIONS..... | 13 |
| APPLICABLE STANDARD | 13 |
| EUT SETUP | 13 |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP | 14 |
| TEST PROCEDURE | 14 |
| CORRECTED FACTOR & MARGIN CALCULATION | 15 |
| TEST DATA | 15 |
| FCC §15.247(A) (1) & RSS-247 § 5.1 (B)-CHANNEL SEPARATION TEST | 21 |
| APPLICABLE STANDARD | 21 |
| TEST PROCEDURE | 21 |
| TEST DATA | 21 |
| FCC §15.247(A) (1) & RSS-GEN § 6.7 & RSS-247 § 5.1 (A)-99% OCCUPIED BANDWIDTH & 20 DB EMISSION BANDWIDTH..... | 23 |
| APPLICABLE STANDARD | 23 |
| TEST PROCEDURE | 23 |
| TEST DATA | 24 |

FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D)-QUANTITY OF HOPPING CHANNEL TEST.....27
 APPLICABLE STANDARD27
 TEST PROCEDURE27
 TEST DATA27

FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D) - TIME OF OCCUPANCY (DWELL TIME)29
 APPLICABLE STANDARD29
 TEST PROCEDURE29
 TEST DATA29

FCC §15.247(B) (1) & RSS-247§ 5.1(B) &§ 5.4(B) - PEAK OUTPUT POWER MEASUREMENT31
 APPLICABLE STANDARD31
 TEST PROCEDURE31
 TEST DATA31

FCC §15.247(D) & RSS-247 § 5.5 - BAND EDGES TESTING34
 APPLICABLE STANDARD34
 TEST PROCEDURE34
 TEST DATA34

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|-------------------------------------|---|
| HVIN | EVX-MS |
| Frequency Range | 2407-2475MHz |
| Maximum conducted Peak output power | 18.58dBm |
| Modulation Technique | GFSK |
| Antenna Specification* | 0 dBi(It is provided by the applicant) |
| Voltage Range | DC3.7V from battery |
| Sample number | SZNS211206-61773E-RF-S1 for RF conducted SZNS211206-61773E-RF-S2 for radiated test (Assigned by ATC) |
| Sample/EUT Status | Good condition |

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules and RSS-247, Issue 2, February 2017, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and RSS-247, Issue 2, February 2017, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Parameter | | Uncertainty |
|------------------------------------|-----------------|------------------------|
| Occupied Channel Bandwidth | | 5% |
| RF Frequency | | 0.082×10^{-7} |
| RF output power, conducted | | 0.73dB |
| Unwanted Emission, conducted | | 1.6dB |
| AC Power Lines Conducted Emissions | | 2.72dB |
| Emissions, Radiated | 9kHz - 30MHz | 2.66dB |
| | 30MHz - 1GHz | 4.28dB |
| | 1GHz - 18GHz | 4.98dB |
| | 18GHz - 26.5GHz | 5.06dB |
| | 26.5GHz - 40GHz | 4.72dB |
| Temperature | | 1°C |
| Humidity | | 6% |
| Supply voltages | | 0.4% |

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel list

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0 | 2407 | 15 | 2425 | 30 | 2443 | 45 | 2461 |
| 1 | 2408 | 16 | 2426 | 31 | 2444 | 46 | 2462 |
| 2 | 2409 | 17 | 2427 | 32 | 2445 | 47 | 2466 |
| 3 | 2410 | 18 | 2428 | 33 | 2446 | 48 | 2467 |
| 4 | 2411 | 19 | 2429 | 34 | 2450 | 49 | 2468 |
| 5 | 2412 | 20 | 2430 | 35 | 2451 | 50 | 2469 |
| 6 | 2413 | 21 | 2434 | 36 | 2452 | 51 | 2470 |
| 7 | 2414 | 22 | 2435 | 37 | 2453 | 52 | 2471 |
| 8 | 2418 | 23 | 2436 | 38 | 2454 | 53 | 2472 |
| 9 | 2419 | 24 | 2437 | 39 | 2455 | 54 | 2473 |
| 10 | 2420 | 25 | 2438 | 40 | 2456 | 55 | 2474 |
| 11 | 2421 | 26 | 2439 | 41 | 2457 | 56 | 2475 |
| 12 | 2422 | 27 | 2440 | 42 | 2458 | / | / |
| 13 | 2423 | 28 | 2441 | 43 | 2459 | / | / |
| 14 | 2424 | 29 | 2442 | 44 | 2460 | / | / |

The equipment has designed 57 channels totally, but only 20 channels selected from the 57 channels active at same time, which were separated by more than 2MHz.

EUT was test in channel 0, 34, 56.

EUT Exercise Software

EUT was configured to testing mode by applicant and power level is default*.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| / | / | / | / |

External I/O Cable

| Cable Description | Length (m) | From Port | To |
|-------------------|------------|-----------|----|
| / | / | / | / |

Block Diagram of Test Setup

For Radiated Emission



SUMMARY OF TEST RESULTS

| FCC Rules | ISED Rules | Description of Test | Result |
|-------------------------------|---------------------------------|---|----------------|
| §15.247 (i), §2.1093 | RSS-102 | RF EXPOSURE | Compliant |
| §15.203 | RSS-Gen §6.8 | Antenna Requirement | Compliant |
| §15.207(a) | RSS-Gen §8.8 | AC Line Conducted Emissions | Not Applicable |
| §15.205, §15.209 & §15.247(d) | RSS-247 § 5.5 | Radiated Emissions | Compliant |
| §15.247(a)(1) | RSS- Gen§6.7, RSS-247 § 5.1 (a) | 99% Occupied Bandwidth & 20 dB Emission Bandwidth | Compliant |
| §15.247(a)(1) | RSS-247 § 5.1 (b) | Channel Separation Test | Compliant |
| §15.247(a)(1)(iii) | RSS-247 § 5.1 (d) | Time of Occupancy (Dwell Time) | Compliant |
| §15.247(a)(1)(iii) | RSS-247 § 5.1 (d) | Quantity of hopping channel Test | Compliant |
| §15.247(b)(1) | RSS-247 § 5.1(b) & § 5.4(b) | Peak Output Power Measurement | Compliant |
| §15.247(d) | RSS-247 § 5.5 | Band edges | Compliant |

Not Applicable: EUT only powered by battery.

Note: Pre-scan all models, the worst case model EVX-MS was selected to test.

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|---|-------------------|-------------------|---------------|------------------|----------------------|
| Radiated Emissions Test | | | | | |
| Rohde& Schwarz | Test Receiver | ESR | 102725 | 2021/12/13 | 2022/12/12 |
| Rohde&Schwarz | Spectrum Analyzer | FSV40 | 101949 | 2021/12/13 | 2022/12/12 |
| SONOMA INSTRUMENT | Amplifier | 310 N | 186131 | 2021/11/09 | 2022/11/08 |
| A.H. Systems, inc. | Preamplifier | PAM-0118P | 135 | 2021/11/09 | 2022/11/08 |
| Quinstar | Amplifier | QLW-18405536-J0 | 15964001002 | 2021/11/11 | 2022/11/10 |
| Schwarzbeck | Bilog Antenna | VULB9163 | 9163-323 | 2021/07/06 | 2024/07/05 |
| Schwarzbeck | Horn Antenna | BBHA9120D | 9120D-1067 | 2020/01/05 | 2023/01/04 |
| Schwarzbeck | HORN ANTENNA | BBHA9170 | 9170-359 | 2020/01/05 | 2023/01/04 |
| Unknown | RF Coaxial Cable | No.10 | N050 | 2021/12/14 | 2022/12/13 |
| Unknown | RF Coaxial Cable | No.11 | N1000 | 2021/12/14 | 2022/12/13 |
| Unknown | RF Coaxial Cable | No.12 | N040 | 2021/12/14 | 2022/12/13 |
| Unknown | RF Coaxial Cable | No.13 | N300 | 2021/12/14 | 2022/12/13 |
| Unknown | RF Coaxial Cable | No.14 | N800 | 2021/12/14 | 2022/12/13 |
| Unknown | RF Coaxial Cable | No.15 | N600 | 2021/12/14 | 2022/12/13 |
| Unknown | RF Coaxial Cable | No.16 | N650 | 2021/12/14 | 2022/12/13 |
| Radiated Emission Test Software: e3 19821b (V9) | | | | | |
| Wainwright | High Pass Filter | WHKX3.6/18 G-10SS | 5 | 2021/12/14 | 2022/12/13 |
| RF Conducted Test | | | | | |
| WEINSCHHEL | 10dB Attenuator | 5324 | AU 3842 | 2021/12/14 | 2022/12/13 |
| SPECTRUM ANALYZER | Rohde & Schwarz | FSU26 | 200982 | 2021/07/06 | 2022/07/05 |

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Measurement Result

Please refer to SAR test report: SZNS211206-62025E-SA.

RSS-102 – RF EXPOSURE

Applicable Standard

According to RSS-102, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Result: Compliance.

Please refer to SAR test report: SZNS211206-62025E-SA.

FCC §15.203 & RSS-GEN §6.8– ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal antenna arrangements which were permanently attached and the gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

| Type | Antenna Gain | Impedance |
|----------|--------------|-----------|
| Monopole | 0dBi | 50 Ω |

Result: Compliance.

FCC §15.205, §15.209 & §15.247(d) & RSS-247§ 5.5 – RADIATED EMISSIONS


Applicable Standard


FCC §15.205; §15.209; §15.247(d) and RSS-247 §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

EUT Setup

Below 1 GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits and RSS-247/RSS-Gen limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Measurement |
|-------------------|---------|-----------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz | 120 kHz | QP |
| Above 1 GHz | 1 MHz | 3 MHz | / | PK |
| | 1 MHz | 10 Hz | / | Average |

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin/Over Limit} &= \text{Corrected Amplitude/Level-Limit} \\ \text{Corrected Amplitude/Level} &= \text{Reading} + \text{Corrected Factor} \end{aligned}$$

Test Data

Environmental Conditions


| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 64 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Bin Deng on 2021-12-28..

EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

30MHz-1GHz: (worst case for Middle channel)


Horizontal:



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : SZNS211206-61773E-RF
 Test Mode: 2.4G FHSS

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|---------|--------|------------|--------|------------|------------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 30.867 | -12.30 | 41.27 | 28.97 | 40.00 | -11.03 | Peak |
| 2 | 163.182 | -14.29 | 40.19 | 25.90 | 43.50 | -17.60 | Peak |
| 3 | 299.973 | -9.23 | 38.58 | 29.35 | 46.00 | -16.65 | Peak |
| 4 | 384.100 | -7.08 | 37.43 | 30.35 | 46.00 | -15.65 | Peak |
| 5 | 422.428 | -6.00 | 38.40 | 32.40 | 46.00 | -13.60 | Peak |
| 6 | 810.265 | -0.42 | 36.45 | 36.03 | 46.00 | -9.97 | Peak |

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS211206-61773E-RF
 Test Mode: 2.4G FHSS

| | Freq | Factor | Read Level | Limit Level | Limit Line | Over Limit | Remark |
|---|---------|--------|------------|-------------|------------|------------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 30.079 | -12.39 | 39.62 | 27.23 | 40.00 | -12.77 | Peak |
| 2 | 42.136 | -10.01 | 39.76 | 29.75 | 40.00 | -10.25 | Peak |
| 3 | 57.543 | -9.97 | 32.13 | 22.16 | 40.00 | -17.84 | Peak |
| 4 | 80.010 | -16.79 | 33.81 | 17.02 | 40.00 | -22.98 | Peak |
| 5 | 480.107 | -5.00 | 31.56 | 26.56 | 46.00 | -19.44 | Peak |
| 6 | 646.818 | -1.82 | 28.83 | 27.01 | 46.00 | -18.99 | Peak |

Above 1GHz:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|---------------------------|----------------------|------------|------------------|------------|-------------|-------------------------|------------------------------------|----------------------|-------------|
| | Reading (dB μ V) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | | |
| Low Channel (2407 MHz) | | | | | | | | | |
| 2310 | 68.35 | PK | 145 | 2.1 | H | -7.24 | 61.11 | 74 | -12.89 |
| 2310 | 53.43 | Ave. | 145 | 2.1 | H | -7.24 | 46.19 | 54 | -7.81 |
| 2310 | 68.57 | PK | 12 | 2.1 | V | -7.24 | 61.33 | 74 | -12.67 |
| 2310 | 53.66 | Ave. | 12 | 2.1 | V | -7.24 | 46.42 | 54 | -7.58 |
| 2390 | 74.03 | PK | 350 | 1.2 | H | -7.22 | 66.81 | 74 | -7.19 |
| 2390 | 54.24 | Ave. | 350 | 1.2 | H | -7.22 | 47.02 | 54 | -6.98 |
| 2390 | 74.21 | PK | 103 | 1.7 | V | -7.22 | 66.99 | 74 | -7.01 |
| 2390 | 54.29 | Ave. | 103 | 1.7 | V | -7.22 | 47.07 | 54 | -6.93 |
| 4814 | 55.09 | PK | 183 | 1.4 | H | -3.51 | 51.58 | 74 | -22.42 |
| 4814 | 55.45 | PK | 281 | 2.4 | V | -3.51 | 51.94 | 74 | -22.06 |
| Middle Channel (2450 MHz) | | | | | | | | | |
| 4900 | 55.10 | PK | 50 | 2.0 | H | -3.28 | 51.82 | 74 | -22.18 |
| 4900 | 55.69 | PK | 101 | 1.3 | V | -3.28 | 52.41 | 74 | -21.59 |
| High Channel (2475 MHz) | | | | | | | | | |
| 2483.5 | 75.57 | PK | 124 | 1.1 | H | -7.20 | 68.37 | 74 | -5.63 |
| 2483.5 | 55.06 | Ave. | 124 | 1.1 | H | -7.20 | 47.86 | 54 | -6.14 |
| 2483.5 | 77.26 | PK | 241 | 2.2 | V | -7.20 | 70.06 | 74 | -3.94 |
| 2483.5 | 54.95 | Ave. | 241 | 2.2 | V | -7.20 | 47.75 | 54 | -6.25 |
| 2500 | 69.23 | PK | 185 | 1.4 | H | -7.18 | 62.05 | 74 | -11.95 |
| 2500 | 55.09 | Ave. | 185 | 1.4 | H | -7.18 | 47.91 | 54 | -6.09 |
| 2500 | 68.53 | PK | 66 | 1.9 | V | -7.18 | 61.35 | 74 | -12.65 |
| 2500 | 54.92 | Ave. | 66 | 1.9 | V | -7.18 | 47.74 | 54 | -6.26 |
| 4950 | 55.26 | PK | 49 | 1.0 | H | -3.04 | 52.22 | 74 | -21.78 |
| 4950 | 55.61 | PK | 205 | 1.6 | V | -3.04 | 52.57 | 74 | -21.43 |

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.


The test result of peak was less than the limit of average, so just peak value were recorded.

1-18GHz


Pre-scan for Peak

High Channel

Horizontal:



Vertical:




18-25GHz


Pre-scan for Peak

High Channel

Horizontal:



Vertical:



FCC §15.247(a) (1) & RSS-247 § 5.1 (b)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel and in Operating mode, RBW was set at 30 kHz, VBW \geq 3RBW max-hold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Fan Yang on 2022-03-04.


EUT operation mode: Transmitting

Test Result: Compliant.

Note: According to frequency table in page 6 and investigating the hopping channel test in page 28, the minimum channel separation is the worst case which was recorded as below:

| Test Mode | Channel Separation (MHz) | 20 dBc BW (MHz) | Two-thirds of the 20 dB bandwidth (MHz) | Channel Separation Limit | Result |
|-----------|--------------------------|-----------------|---|-------------------------------------|--------|
| GFSK | | | | | |
| Hopping | 2.010 | 2.064 | 1.376 | > two-thirds of the 20 dB bandwidth | Pass |

Please refer to the below plots:



Date: 4.MAR.2022 10:22:40

FCC §15.247(a) (1) & RSS-GEN § 6.7 & RSS-247 § 5.1 (a)–99% OCCUPIED BANDWIDTH & 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “20 dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 20 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

Test Procedure


4. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
5. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
6. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
7. Repeat above procedures until all frequencies measured were complete.

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Fan Yang on 2021-12-25.

EUT operation mode: Transmitting


Test Result: Compliant.

| Mode | Channel | Frequency (MHz) | 20 dB Emission Bandwidth (MHz) | OBW (MHz) |
|------|---------|-----------------|--------------------------------|-----------|
| GFSK | Low | 2407 | 2.064 | 2.013 |
| | Middle | 2450 | 2.064 | 2.026 |
| | High | 2475 | 2.064 | 2.013 |

Please refer to the below plots:


20 dB EMISSION BANDWIDTH&OBW

Low Channel




Date: 25.DEC.2021 09:38:05

Middle Channel



Date: 25.DEC.2021 10:35:03

High Channel



Date: 25.DEC.2021 09:45:12

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems (FHSs) in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

8. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
9. Set the EUT in hopping mode from first channel to last.
10. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |


The testing was performed by Fan Yang on 2022-02-23.

EUT operation mode: Transmitting

Test Result: Compliant.

| Mode | Frequency Range (MHz) | Number of Hopping Channel (CH) | Limit (CH) |
|------|-----------------------|--------------------------------|------------|
| GFSK | 2400-2483.5 | 20 | ≥15 |

Hop



Date: 23.FEB.2022 19:30:07

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems (FHSs) in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

11. The EUT was worked in channel hopping.
12. Set the RBW to: 1MHz.
13. Set the VBW $\geq 3 \times$ RBW.
14. Set the span to 0Hz.
15. Detector = peak.
16. Sweep time = auto couple.
17. Trace mode = max hold.
18. Allow trace to fully stabilize.
19. Recorded the time of single pulses

Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Fan Yang on 2021-12-25.


EUT operation mode: Transmitting

Test Result: Compliant.

| Test Mode | Channel | Pulse Time [ms] | Total Hops [Num] | Result[s] | Limit[s] | Verdict |
|-----------|---------|-----------------|------------------|-----------|------------|---------|
| GFSK | Hop | 0.523 | 20 | 0.010 | ≤ 0.4 | PASS |


Note: A period time= $0.4 \times 20 = 8$ (s), Result= Pulse Time *Total hops

Hops



Date: 25.DEC.2021 10:59:38

Pulse time



Date: 25.DEC.2021 10:57:17

FCC §15.247(b) (1) & RSS-247§ 5.1(b) &§ 5.4(b) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard


According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

For frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W (see Section 5.4(e) for exceptions).

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |


The testing was performed by Fan Yang on 2021-12-25.

EUT operation mode: Transmitting

Test Result: Compliant.


| Mode | Channel | Frequency (MHz) | Peak Output Power | Limit (dBm) |
|------|---------|-----------------|-------------------|-------------|
| | | | (dBm) | |
| GFSK | Low | 2407 | 17.74 | 21 |
| | Middle | 2450 | 18.58 | 21 |
| | High | 2475 | 18.58 | 21 |

Note: the antenna gain is 0dBi, the maximum EIRP=18.58dBm+0dBi=18.58dBm<36dBm, so it's compliance with the EIRP limit of ISEDC.




Date: 25.DEC.2021 11:45:41

Middle Channel



Date: 25.DEC.2021 11:46:23

High Channel



Date: 25.DEC.2021 11:47:01

FCC §15.247(d) & RSS-247 § 5.5 - BAND EDGES TESTING

Applicable Standard

According to FCC §15.247(d) & RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)) & RSS-Gen.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |


The testing was performed by Fan Yang on 2021-12-25 and 2022-01-06.

EUT operation mode: Transmitting

Test Result: Compliant.


Conducted Band Edge Result:

GFSK_Low Channel




Date: 25.DEC.2021 10:38:26

GFSK_Hop_Low Channel




Date: 6.JAN.2022 15:38:08

GFSK_High Channel



Date: 25.DEC.2021 10:41:47

GFSK_Hop_High Channel



Date: 6.JAN.2022 15:54:33

***** END OF REPORT *****