

15, rue de la Claie  
Z.I. Angers-Beaucouzé  
49070 BEAUCOUZÉ  
**Tél. 02 41 73 26 27**  
Fax 02 41 73 26 40  
e-mail : atlantique@emitech.fr  
R.C.S. ANGERS 95 B 543  
SIRET 344 545 645 00055

**RA-03-24418/A/ST**

## **FCC CERTIFICATION RADIO Measurement Technical Report**

**standard to apply:  
FCC Part 15**

**Equipment under test:  
DIGITAINEER  
REMOTE CONTROL**


**FCC ID:  
B4S20018268**

**Company:  
X10**

**DISTRIBUTION: Mr ROSSI**

**Company: X10**

**Number of pages: 11 + 3 appendixes**

Ed.	Date	Modified pages	Editing		Verification Approval	
			Name	Visa	Name	Visa
0	25-Nov-03	Creation	P. BONNENFANT	B.P	Y. JUDEAUX	

Duplication of this test report is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.

This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample.

**SIEGE SOCIAL : EMITECH S.A.**

3, rue des Coudriers – Z.A. de l'Observatoire – 78180 MONTIGNY-LE-BRETONNEUX – Tél. 01 30 57 55 55 – Fax 01 30 43 74 48  
S.A. AU CAPITAL DE 480 000 € - R.C. VERSAILLES B 344 545 645 – SIRET 344 545 645 000 22 – CODE APE 742 C

***PRODUCT:*** **DIGITAINER**

**Reference / model:** /

**Serial number:** remote control transmitter: 20018268  
remote receiver: 20018267

***MANUFACTURER:*** X10

***COMPANY SUBMITTING THE PRODUCT:***

**Company:** X10

**Address:** 3, rue de Penthievre  
75008 PARIS  
FRANCE

**Responsible:** Mr ROSSI

***DATE(S) OF TEST:*** 06 November 2003

***TESTING LOCATION:*** EMITECH ATLANTIQUE open area test site in LA POUEZE  
(49) FRANCE  
Registration Number by FCC: 101696/FRN: 0006 6490 08

***TESTED BY:*** P. BONNENFANT  
L. BERTHAUD

CONTENTS

TITLE	PAGE
1. INTRODUCTION.....	4
2. PRODUCT DESCRIPTION .....	4
3. NORMATIVE REFERENCE.....	4
4. TEST METHODOLOGY .....	5
5. TEST UNIT CONFIGURATION.....	5
6. TESTS AND CONCLUSIONS .....	6
7. RADIATED EMISSION LIMITS (RECEIVER) .....	7
8. RADIATED EMISSION LIMITS; GENERAL REQUIREMENTS (TRANSMITTER).....	9
9. APPENDIXES .....	11
Appendix 1: “PHOTOGRAPHIES OF THE EQUIPEMENT UNDER TEST” .....	11
Appendix 2: “OPEN AREA TEST SITE, TEST SET UP” .....	11
Appendix 3: “BANDWIDTH OF EMISSION” .....	11

## **1.INTRODUCTION**

This document presents the result of RADIO test carried out on the following equipment: DIGITAINER in accordance with normative reference.

## **2.PRODUCT DESCRIPTION**

ITU Emission code: 200 K L1D

Class: B (paragraph FCC part 15.3)

Intermittent control signals with not continuous transmission, the transmitter operate only when a button is pressed.

Utilization: PC remote control

Antenna type: internal antenna

Operating frequency: 433.92 MHz

No of channels: 1

Channel spacing: not concerned

Frequency generation: ☒ SAW Resonator ☐ Crystal ☐ Synthetiser

Modulation: ☒ Amplitude ☐ Digital ☐ Frequency ☐ Phase

Power source: alkaline batteries (2 x 1.5 V) for remote control  
The receiver is directly supplied by the USB port.

Power level, frequency range and channels characteristics are not user adjustable.

The details pictures of the product and the circuit boards are joined with this file.

## **3.NORMATIVE REFERENCE**

FCC Part 15 (2000) Code of Federal Regulations  
Title 47 - Telecommunication  
Chapter 1 - Federal Communications Commission  
Part 15 - Radio frequency devices  
Subpart C - Intentional Radiators

ANSI C63.4 (01) American National Standard for Methods of measurement of Radio-Noise from low-voltage.  
Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

#### **4.TEST METHODOLOGY**

Radio performance tests procedures given in part 15:

Paragraph 109: radiated emission limits (Subpart B Unintentional Radiators)

Paragraph 111: antenna power conducted limits for receivers

(Subpart B unintentional Radiators)

Paragraph 203: antenna requirement (Subpart C intentional Radiators)

Paragraph 205: restricted bands of operation (Subpart C intentional Radiators)

Paragraph 209: radiated emission limits; general requirements (Subpart C intentional Radiators)

Paragraph 231: periodic operation in the band 40.66 – 40.7 MHz and above 70 MHz

(Subpart C intentional Radiators)

Paragraph 33: frequency range of radiated measurements

Paragraph 35: measurement detector functions and bandwidths

#### **5.TEST UNIT CONFIGURATION**

JOINED DOCUMENTATIONS

***“Synoptic “***

***“Block diagram “***

***“External photos and Product labeling “***

***“Assembly of components “***

***“Internal photos “***

***“Layout pcb “***

***“Bil of materials “***

***“Schematics “***

***“Product description “***

***“User guide “***

**6. TESTS AND CONCLUSIONS**

Test procedure	Description of test	Criteria respected ?				Comment
		Yes	No	NAp	NAs	
FCC Part 15.109	RADIATED EMISSION LIMITS	X				Receiver
FCC Part 15.111	ANTENNA POWER CONDUCTION FOR RECEIVERS			X		Note 1
FCC Part 15.203	ANTENNA REQUIREMENT	X				Note 1
FCC Part 15.205	RESTRICTED BANDS OF OPERATION	X				Transmitter
FCC Part 15.231	PERIODIC OPERATION IN THE BAND 40.66 – 40.7 MHz and above 70 MHz					Transmitter
a)		X				Note 2
b)		X				Note 3
c)		X				Note 4

NAp: Not Applicable

NAs: Not Asked

*Note 1: internal antenna without connector.*

*Note 2: the transmitter operate manually and employ a switch that deactivates automatically the transmitter and ceases transmission within 5 seconds after deactivation.  
The transmitter does not perform periodic transmissions.*

*Note 3: field strength limit of fundamental ( $F = 433.92 \text{ MHz}$ )  
 $41.666 (F) - 7083.3333 = 10996 \mu\text{V/m at } 3 \text{ m} = 80.8 \text{ dB}\mu\text{V/m at } 3 \text{ m}.$   
The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.*

*Note 4: the bandwidth of the emission at 20 dB is 557.114 kHz (see appendix 3), less than 0.25 % of the centre frequency (1.0848 MHz).*

**Conclusion:**

The sample of DIGITAINER submitted to the tests complies with the regulations of the standard FCC Part 15 in accordance with the limits or criteria defined in this report.

**7.RADIATED EMISSION LIMITS (RECEIVER)**

**Standard:** FCC Part 15 (2003)

**Test procedure:** paragraph 109

**Class:** B

**Test equipment:**

TYPE	BRAND	EMITECH NUMBER
Test receiver	Rohde & Schwarz ESVS 10	1219
Biconical antenna	Hewlet Packard 11966 C	728
Log periodic antenna	Rohde & Schwarz HL 223	1999
Double ridged guide antenna	Electrometrics EM 6961	1204
Spectrum analyser	Rohde & Schwarz FSEM30	1244
Open area test site	EMITECH	1274
Preamplifier	DBS Microwave DB97-1852	2648
High pass filter	Micro-tronics HPM11630	1673
Power source	TTI	2148

**Test set up:**

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

**Frequency range:** 30 MHz - 5 GHz (F < or = 1 GHz).

**Detection mode:** Quasi-peak (F < 1 GHz)  
Average (F > 1 GHz)

**Bandwidth:** 120 kHz (F < 1 GHz)  
1 MHz (F > 1 GHz)

**Distance of antenna:** 3 meters

**Antenna height:** 1 to 4 meters

**Antenna polarization:** vertical and horizontal (only the highest level is recorded)

**Equipment under test operating condition:**

The receiver equipment is tested with an USB port simulator provided by the applicant.

**Results:**

Ambient temperature (°C): 19

Relative humidity (%): 62

Power source: 5 Vd.c. apply to the simulator

The polarity column refers to the antenna polarity at which the maximum emissions level is measured.

FREQUENCIES (MHz)	E.U.T. orientation	Antenna height (cm)	Polarization of antenna H: Horizontal V: Vertical	Azimuth (degrees)	Field strength (dBμV/m)	Limits (dBμV/m)
267.761	X	119	H	331	34.2	46.0
435.722	X	110	V	82	25.2	46.0

E.U.T. orientation

X: to put flat

Y: on the edge

Z: up right

E.U.T.: Equipment Under Test

Note: 200 μV/m at 3 m = 46 dBμV/m at 3 m.



**8.RADIATED EMISSION LIMITS; GENERAL REQUIREMENTS (TRANSMITTER)**

**Standard:** FCC Part 15 (2003)

**Test procedure:** paragraph 205 / 209  
paragraph 231

**Test equipment:**

TYPE	BRAND	EMITECH NUMBER
Test receiver	Rohde & Schwarz ESVS 10	1219
Biconical antenna	Hewlet Packard 11966 C	728
Log periodic antenna	Rohde & Schwarz HL 223	1999
Double ridged guide antenna	Electrometrics EM 6961	1204
Spectrum analyser	Rohde & Schwarz FSEM30	1244
Open area test site	EMITECH	1274
Preamplifier	DBS Microwave DB97-1852	2648
High pass filter	Micro-tronics HPM11630	1673

**Test set up:**

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

**Frequency range:** from 30 MHz to harmonic 10 ( $F_{\text{carrier}} \leq 1 \text{ GHz}$ )

**Detection mode:** Quasi-peak or average ( $F < 1 \text{ GHz}$ )  
Average ( $F > 1 \text{ GHz}$ )

**Bandwidth:** 120 kHz ( $F < 1 \text{ GHz}$ )  
1 MHz ( $F > 1 \text{ GHz}$ )

**Distance of antenna:** 3 meters

**Antenna height:** 1 to 4 meters

**Antenna polarization:** vertical and horizontal (only the highest level is recorded)

**Equipment under test operating condition:**

The equipment is in continuous transmission mode.

**Results:**

Ambient temperature (°C): 18  
Relative humidity (%): 49

Power source: we used for power source the internal batteries of the equipment and we noted:

Voltage at the beginning of test (V): 3.17  
Voltage at the end of test (V): 3.09  
Percentage of the voltage drop during the test (%): 2.52  
Limits (%):  $\pm 5$

The polarity column refers to the antenna polarity at which the maximum emissions level is measured.

**Channel Emission**

FREQUENCIES (MHz)	Detector	E.U.T. orientation	Antenna height (cm)	Polarization of antenna H: Horizontal V: Vertical	Azimuth (degrees)	Field strength (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)
409.844	Q	X	100	H	277	36.6	46.0*
425.943	A	X	115	H	266	40.3	60.8
433.92 <sup>(1)</sup>	A	Z	111	V	0	80.7	80.8
442.044	A	Z	105	V	277	37.3	60.8
867.971	A	Z	120	V	25	46.0	61.9
1301.974	A	Z	186	V	01	50.6	54.0*
1735.902	A	Z	197	V	330	59.6	61.9
2169.904	A	Z	124	V	333	57.4	61.9
2603.487	A	Z	154	V	01	54.8	61.9
3471.902	A	Z	154	V	348	52.5	61.9
3905.992	A	X	237	H	181	51.9	54.0*
4339.609	A	X	250	H	19	48.02	54.0*

<sup>(1)</sup> fundamental.

E.U.T.: Equipment Under Test

\* restricted band of operation § 15.205.

E.U.T. orientation

X: to put flat

Y: on the edge

Z: up right

A: average

Q: quasi peak

Note: 1099  $\mu$ V/m at 3 m = 60.8 dB $\mu$ V/m at 3 m  
1250  $\mu$ V/m at 3 m = 61.9 dB $\mu$ V/m at 3 m

500  $\mu$ V/m at 3 m = 54.0 dB $\mu$ V/m at 3 m  
200  $\mu$ V/m at 3 m = 46.0 dB $\mu$ V/m at 3 m

The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

**9.APPENDIXES****Appendix 1: “PHOTOGRAPHIES OF THE EQUIPEMENT UNDER TEST”**

This appendix contains 7 pages.

**Appendix 2: “OPEN AREA TEST SITE, TEST SET UP”**

This appendix contains 3 pages.

**Appendix 3: “BANDWIDTH OF EMISSION”**

This appendix contains 2 pages.

□□□ End of report, 3 appendixes to be forwarded □□□