

**Interactive Technologies Inc**

**Interactive Technologies, Inc.  
ITI/Sentrol SharpShooter PIR Motion Detector  
B4Z-780A-PIR  
Certification**

05/04/01 11:29 AM	<b>FCC ID: B4Z-780A-PIR</b>	Page 1 of 23
C:\WINNT\Profiles\Kenl.Nelson\Desktop\FCC Documintation\Submittles\Sentrol Sharpshooter PIR\pcs\FCC_REPT.DOC		

**Interactive Technologies Inc**

**ITI/Sentrol SharpShooter PIR Motion Detector  
B4Z-780A-PIR**

**5/09/2001**

**Interactive Technologies, Inc.  
2266 North Second Street  
North Saint Paul, MN 55109  
(651) 777-2690**

FCC_REPT.DOC 05/04/01 11:29 AM	FCC ID: B4Z-780A-PIR	Page 2 of 23
-----------------------------------	----------------------	--------------

# Interactive Technologies Inc

1. INTRODUCTION	4
2. STATEMENT OF COMPLIANCE	4
3. LAB MEASUREMENTS DISCUSSION / TEST NOTES	7
3.1 Test Notes	7
3.1.1 Transmissions shall cease within 5 seconds of activation [ §15.231(a)(2) ]	7
3.1.2 Supervisory Calculation [ §15.231(a)(3) ]	9
3.1.3 Duty Cycle Correction Factor [§15.231(b)(2) and §15.35(c)]	9
3.1.4 Bandwidth Measurement [ §15.231(c) ]	12
3.1.5 Emissions Measurements	16
3.1.5.1 Radiated Emissions Summary	16
3.1.5.2 FCC Emissions Calculation	16
3.1.5.2.1 Terms	16
3.1.5.2.2 Example Calculation	17
3.1.5.3 Radiated Emissions	17
3.1.5.4 Forbidden Bands	17

# Interactive Technologies Inc

## 1. Introduction

This device is a wireless fire alarm transmitter for use in a wireless security system. The unit is self-contained and powered by one 3.0 Volt Lithium battery. The transmitter's frequency is crystal controlled and is not adjustable by the user. The device measures approximately 4" in height, 3" in width and 2.5" in depth. The unit weighs approximately 20 ounces with battery.

We are requesting Certification under FCC Rules, Part 15, Subpart C, Paragraph 15.231.

Please send comments/suggestions on the report format to KenL.Nelson@Interlogixinc.com.

## 2. Statement of Compliance

### §2.907 Certification

This is an application for certification

### §2.911 Application

- a) This is an application and has been filed electronically with form 731.
- b) All information required has been supplied.
- c) The applicant has signed the application (electronically).
- d) The technical data has been signed.  
(See Radiated Emissions)
- e) Applicant signature block on electronic form 731 completed by officer of the company or authorized company personnel.
- f) The appropriate fee has been paid electronically with VISA on 5/09/01.

### §2.915 Grant

This application demonstrates that all applicable technical standards have been met and a grant of this application will serve the public interest.

### §2.925 Label

Each piece of equipment for which authorization will be granted will be uniquely identified with "FCC ID: B4Z-780A-PIR." The required statement will appear with the FCC ID on the product and, although not required, in the installation instructions. See Exhibit A, PDF file *id\_label.pdf*

FCC_REPT.DOC 05/04/01 11:29 AM	FCC ID: B4Z-780A-PIR	Page 4 of 23
-----------------------------------	----------------------	--------------

## Interactive Technologies Inc

### §2.947 Measurement Procedure

- a) The measurement procedure follows ANSI C63.4 procedure.  
Procedural notes are contained in the laboratory report.
- d) A list of test equipment used is contained in the laboratory report.

### §2.948 Description of Measurement Facilities

Measurements were performed at TUV Testing Services Open Test Site. The FCC keeps a full description of the measurement facilities on file. TUV's acceptance and approval is dated as December 5, 1993 in a letter received from the FCC.

The address of the test facility is:

TUV Product Service  
19035 Wild Mountain Road  
Taylors Falls, MN 55084-1758

Phone: 651-638-0297  
Contact: Joel Schneider  
Test Engineer in Charge

See Exhibit F, PDF file *test\_pho.pdf* for sketch of measurement setup

### §2.1033 Application for Certification

- a) Form 731 has been electronically filed on 5/09/01. Items that did not apply were left blank.
- b) This technical report contains the following information where applicable.
  - 1) Full name and mailing address of manufacturer and applicant for certification:  
Interactive Technologies Inc  
2266 North Second Street  
North Saint Paul, MN 55109
  - 2) FCC Identifier:  
**B4Z-780A-PIR**
  - 3) Copy of installation instructions:  
See Exhibit G, PDF file: *user\_man.pdf*
  - 4) Brief Description of circuit functions and device operation:  
See Exhibit I, PDF file *op\_desc.pdf*

## Interactive Technologies Inc

See Exhibit D, PDF file *schemat.pdf* for schematics (page 1) and parts placement (pages 2 & 3) diagrams.

5) Block Diagram

See Exhibit C, PDF file *block.pdf*.

6) Report of the measurements of radiation and conducted emissions:

This document.

7) Photographs

External:

See Exhibit B, PDF file *extern.pdf*

Internal:

See Exhibit H, PDF file *intern.pdf*

8) Peripheral or Accessory devices:

This is not applicable since this device is stand-alone product.

9) Transition Rules

This application is not pursuant to the transition rules of §15.37

10) Emergency Broadcast decoding:

This is not applicable to device in this application.

11) Application for direct sequence spread spectrum devices...

This is not applicable to device in this application.

12) Application for scanning receivers...

This is not applicable to device in this application.

c) Composite Systems

This is not applicable to device in this application.

## Interactive Technologies Inc

### 3. Lab Measurements Discussion / Test Notes

#### 3.1 Test Notes

3.1.1 Transmissions shall cease within 5 seconds of activation [ **§15.231(a)(2)** ]

In the event of an alarm condition, 8 packets are sent in the transmission. The packet duration is, at most, 30 mS, see **Duty Cycle Correction Factor** [§15.231(b)(2) and §15.35(c)]. The time between packets random between 100 mS and 450 mS so the length of the longest transmission is:

$$8*30\text{mS} + 7*450\text{mS} = 3.39 \text{ seconds.}$$

The following plot shows an 8-packet transmission that concludes in less than 5 seconds.

(hp) 08:23:30 MAY 3, 2001

RL 0.00 dBm


MKR #1 SWT 1.925 sec

ATTEN 10 dB

-17.59 dBm

10.00 dB/DIV

MARKER  
1.925 sec  
-17.59 dBm  
1



CENTER 319.508 000 MHz

SPAN 0 Hz

\*RB 300 kHz

\*VB 100 kHz

\*ST 5.000 sec



## Interactive Technologies Inc

### 3.1.2 Supervisory Calculation [ §15.231(a)(3) ]

As permitted, this device will transmit three packets for supervision purposes. The inter-packet delay is a random time between 100 mS and 450 mS. The packet itself may be as long as 30 ms depending on the data sent. The longest time to conclude a supervisory transmission is then:

$$3 * 30 \text{ mS} + 2 * 450 \text{ mS} = 990 \text{ mS}$$

### 3.1.3 Duty Cycle Correction Factor [§15.231(b)(2) and §15.35(c)]

The transmitter employs amplitude modulation and transmits 64 bits. Each bit, except for one, has an “ON” time of 122  $\mu$ S. One bit has an on time of 366  $\mu$ S. The total on time of a single packet is:

$$63 * 122 \mu\text{S} + 366 \mu\text{S} = 8.052 \text{ mS}.$$

Only one packet is sent in any given 100 mS window for a duty cycle correction factor of:

$$20 * \text{LOG} (8.052/100) = -21.88 \text{ dB}$$

The maximum allowed correction factor is 20 dB.

The following plots show:

1. Single packet in 100 mS window.
2. Expanded view of a packet with a duration of 16.97 mS

08:12:19 MAY 3, 2001

RL 0.00 dBm

MKR #1 SWT 4.375 msec

ATTEN 10 dB

-17.20 dBm


10.00 dB/DIV

MARKER

4.375 msec

-17.20 dBm

1



CENTER 319.508 000 MHz

SPAN 0 Hz

\*RB 300 kHz

\*VB 100 kHz

\*ST 100.0 msec

(hp) 08:18:15 MAY 3, 2001

RL 0.00 dBm

MKR #1  $\Delta$ SWT 16.97 msec

ATTEN 10 dB

-0.05 dB


10.00 dB/DIV

MARKER

16.97 msec

-0.05 dB

1



CENTER 319.508 000 MHz

SPAN 0 Hz

\*RB 300 kHz

\*VB 100 kHz

\*ST 26.00 msec

## Interactive Technologies Inc

### 3.1.4 Bandwidth Measurement [ §15.231(c) ]

Bandwidth Measurements were made in peak mode, using a Hewlett Packard Spectrum Analyzer, model number 70000.

The spectrum analyzer 20 dB skirt bandwidth is 3.4 KHz.

The allowed 20 dB bandwidth is 0.25% of center frequency.

Estimated signal bandwidth = Measured signal bandwidth - analyzer bandwidth.

Center Frequency MHz	Measured 20 dB Bandwidth in KHz	Estimated 20 dB signal Bandwidth in KHz	FCC allowed 20 dB Bandwidth in KHz
319.5	26.0	25.6	799

The following three plots show:

1. Bandwidth of carrier without modulation
2. Bandwidth of signal with modulation, 200 KHz span
3. Bandwidth of signal with modulation, 200 MHz span

07:45:03 MAY 3, 2001

RL 0.00 dBm

MKR #3  $\Delta$ FRQ 1.4 kHz

ATTEN 10 dB

-20.80 dB

10.00 dB/DIV

MKR AMPLITUDE right


Marker Bandwidth

1.4 kHz

3.4 kHz

-20.13 dB

3



CENTER 319.512 4 MHz

SPAN 100.0 kHz

RB 1.00 kHz

VB 1.00 kHz

ST 305.0 msec

(hp) 08:03:32 MAY 3, 2001

RL 0.00 dBm

MKR #1  $\Delta$  FRQ 26.0 kHz

ATTEN 10 dB

-0.12 dB


10.00 dB/DIV

MARKER  $\Delta$

26.0 kHz

-0.12 dB

1



CENTER 319.508 0 MHz

SPAN 200.0 kHz

RB 2.15 kHz

VB 3.00 kHz

ST 141.9 msec

(hp) 08:07:36 MAY 3, 2001

RL 0.00 dBm

MKR #1 FRQ 320.0 MHz

ATTEN 10 dB

-14.59 dBm


10.00 dB/DIV

MARKER

320.0 MHz

-14.59 dBm

1



CENTER 319.5 MHz

SPAN 200.0 MHz

RB 300 kHz

VB 300 kHz

ST 10.00 msec

## Interactive Technologies Inc

### 3.1.5 Emissions Measurements

#### 3.1.5.1 Radiated Emissions Summary

The ITI/Sentrol PIR Motion Detector passes FCC Rules Part 15, Subpart C, Paragraph 15.231. The highest fundamental radiated emission was 7.3 dB below the FCC limit at 319.5 MHz. The highest spurious emission measurement was 6 dB below the FCC limit at 958.53MHz. This also is a forbidden band, and so the highest forbidden band emission was 14.3 dB below the FCC limit at 2236.66 MHz.

#### 3.1.5.2 FCC Emissions Calculation

##### 3.1.5.2.1 Terms

Term	Abbreviation	Units	Description
Analyzer Reading	AR	dB $\mu$ V	The power reading read directly from the analyzer without any correction for cabling or receive antenna.
Duty Cycle Correction	DC	dB	Correction for averaging measurement, see <b>Duty Cycle Correction Factor</b> [§15.231(b)(2) and §15.35(c)]
Antenna Factor	AF	dB	Calibration factor for measurement antenna which converts from dB $\mu$ V measured with antenna to the field strength received by the antenna in dB $\mu$ V/M.
Cable Loss	CL	dB	Amount of power lost in cable (and connectors, if any) between antenna and analyzer
Pre-Amp	PA	dB	Gain in pre-amp



## Interactive Technologies Inc

### 3.1.5.2.2 Example Calculation

AR = 99.3 dBμV

AF = 13.9 dB

CL = 3.8 dB

DC = 20 dB

PA=26.2 dB

The field strength for comparison to FCC limits is found to be:

$$AR + AF + CL - DC - PA = 99.3 + 13.9 + 3.8 - 20 - 26.2 = 70.8 \text{ dB}\mu\text{V/M}$$

Alternatively, the AR + AF + CL - PA is compared to the FCC limit + DC. This number is often written to the right of measurement data on the test results. For example, the FCC limit for ITI transmitters at 319.5 MHz is approximately 95.8 dBμV/M. The limit from §15.231(b) with linear interpolation yields a limit, without consideration for duty cycle, of approximately 75.8 dBμV/M.

To convert to μV/M the following equation is used:

$$\mu\text{V/M} = \text{INVLOG}(\text{dB}\mu\text{V/M} / 20)$$

For the above example, 70.8 dBμV/M is 3,467.369μV/M

### 3.1.5.3 Radiated Emissions

The highest fundamental emission along with the three highest spurious and restricted band emissions are listed below as per ANSI C63.4 paragraph 10.1.8.2. Emissions from 0.009 MHz to the tenth harmonic were measured as per FCC Rules Part 15, Subpart C, Paragraph 15.33(a). Emission limits were derived from §15.231(b).

Frequency	Analyzer Reading	Duty Cycle Correction	Cable Loss	Antenna Factor	Pre-Amp	Field Strength	Field Strength	FCC Limit
MHz	dBuV	dB	dB	dB	dB	dBuV/M	uV/M	uV/M
319.5	98.90	20	3.9	14.0	28.2	68.60	2,692	6,229
958.53	66.80	20	7.1	23.4	27.5	49.80	309	500
639.02	72.10	20	5.7	19.5	28.1	49.20	288	500
1491.14	52.60	20	9.5	27.0	28.4	40.70	108	623

### 3.1.5.4 Forbidden Bands

Noise floor of spectrum analyzer with antenna factors and duty cycle correction converted to μV/M at approximately one meter.

FCC_REPT.DOC 05/04/01 11:29 AM	FCC ID: B4Z-780A-PIR	Page 17 of 23
-----------------------------------	----------------------	---------------

## Interactive Technologies Inc

All measurements were taken with an HP 8566B Spectrum Analyzer. The bandwidth was 100 KHz for measurements below 1000 MHz. The bandwidth was 1 MHz for measurements above 1000 MHz. The video filter was off.

The noise floor measurements are summarized in the table below. See also the test data included in this report.

Frequency Range									
Low Limit	High Limit	Noise Floor Reading	Duty Cycle Corr	Field Strength	Field Strength	FCC Limit @ 3M	FCC Limit @ 1M		
MHz	MHz	dBuV	dB	dBuV/M	uV/M	uV/M	uV/M		
0.09000	0.11000	N/A	20	N/A	N/A	2400/F			
0.49500	0.50500	N/A	20	N/A	N/A	2400/F			
2.13750	2.19050	N/A	20	N/A	N/A	30	90		
4.12500	4.12800	N/A	20	N/A	N/A	30	90		
4.17725	4.17775	N/A	20	N/A	N/A	30	90		
4.20725	4.20775	N/A	20	N/A	N/A	30	90		
6.21500	6.21800	N/A	20	N/A	N/A	30	90		
6.26775	6.26825	N/A	20	N/A	N/A	30	90		
6.31175	6.31225	N/A	20	N/A	N/A	30	90		
8.29100	8.29400	N/A	20	N/A	N/A	30	90		
8.36200	8.36600	N/A	20	N/A	N/A	30	90		
8.37625	8.38675	N/A	20	N/A	N/A	30	90		
8.41425	8.41475	N/A	20	N/A	N/A	30	90		
12.29000	12.29300	N/A	20	N/A	N/A	30	90		
12.51975	12.52025	N/A	20	N/A	N/A	30	90		
12.57675	12.57725	N/A	20	N/A	N/A	30	90		
13.36000	13.41000	N/A	20	N/A	N/A	30	90		
16.42000	16.42300	N/A	20	N/A	N/A	30	90		
16.69475	16.69525	N/A	20	N/A	N/A	30	90		
16.80425	16.80475	N/A	20	N/A	N/A	30	90		
25.50000	25.67000	N/A	20	N/A	N/A	30	90		
37.50000	38.25000	23.00	20	3.0	1.4	100	300		
73.00000	74.60000	17.20	20	-2.8	0.7	100	300		
74.80000	75.20000	19.00	20	-1.0	0.9	100	300		
108.00000	121.94000	14.50	20	-5.5	0.5	150	450		
123.00000	138.00000	14.50	20	-5.5	0.5	150	450		
149.90000	150.05000	14.50	20	-5.5	0.5	150	450		
156.52475	156.52525	14.50	20	-5.5	0.5	150	450		
156.70000	156.90000	14.50	20	-5.5	0.5	150	450		
162.01250	167.17000	14.50	20	-5.5	0.5	150	450		
167.72000	173.20000	14.50	20	-5.5	0.5	150	450		
240.0	285.0	21.80	20	1.8	1.2	200	600		
322.0	335.4	21.80	20	1.8	1.2	200	600		
399.9	410.0	21.80	20	1.8	1.2	200	600		
608.0	614.0	21.80	20	1.8	1.2	200	600		
960.0	1240.0	21.80	20	1.8	1.2	500	1500	1065, 1171	
1300.0	1427.0	36.80	20	16.8	6.9	500	1500	1384	
1435.0	1626.5	38.00	20	18.0	7.9	500	1500	1491,1597	
1645.5	1646.5	40.90	20	20.9	11.1	500	1500		
1660.0	1710.0	40.90	20	20.9	11.1	500	1500	1704	
1718.8	1722.2	43.70	20	23.7	15.3	500	1500		
2200.0	2300.0	28.10	20	8.1	2.5	500	1500	2236	
2310.0	2390.0	28.10	20	8.1	2.5	500	1500	2343	
2483.5	2500.0	28.10	20	8.1	2.5	500	1500		
2655.0	2900.0	36.90	20	16.9	7.0	500	1500	2662, 2769, 2875	
3260.0	3267.0	32.90	20	12.9	4.4	500	1500		
3332.0	3339.0	32.90	20	12.9	4.4	500	1500		
3345.8	3358.0	32.90	20	12.9	4.4	500	1500		
3600.0	4400.0	32.90	20	12.9	4.4	500	1500		

## Interactive Technologies Inc

The test data follows on the next 4 pages:

FCC_REPT.DOC 05/04/01 11:29 AM	<b>FCC ID: B4Z-780A-PIR</b>	Page 19 of 23
-----------------------------------	-----------------------------	---------------

# Radiated Electromagnetic Emissions



Test Report #:	<b>3634 Run 03</b>	Test Area:	STS 3m	
Test Method:	N/A	Test Date:	24-Apr-2001	
EUT Model #:	SHARPSHOOTER (52-780)	EUT Power:	BATTERY	
EUT Serial #:		Temperature:	5.2	°C
Manufacturer:	ITI	Relative Humidity:	84	%
EUT Description:	PASSIVE INFRARED MOTION DETECTOR (PIR)	Air Pressure:	99	kPa
Notes:	CONSTANT TRANSMITT MODE		Page:	1 of 4

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB) (dBm) (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
ALL READINGS MAXIMIZED IN PEAK. 100KHZ RBW BELOW 1GHZ AND 1MHZ RBW ABOVE 1GHZ.						
319.53	98.9 Pk	3.9 / 14.0 / 28.2	88.5	V / 1.0 / 0.0	N/A	N/A
319.52	94.0 Pk	3.9 / 14.0 / 28.2	83.6	H / 1.0 / 0.0	N/A	N/A
106.51	70.2 Pk	2.2 / 9.2 / 27.8	53.8	V / 1.0 / 0.0	N/A	N/A
213.01	79.2 Pk	3.1 / 10.9 / 28.0	65.2	V / 1.0 / 0.0	N/A	N/A
426.01	56.6 Pk	4.6 / 17.0 / 28.0	50.2	V / 1.0 / 0.0	N/A	N/A
532.52	55.7 Pk	5.2 / 18.3 / 28.1	51.1	V / 1.0 / 0.0	N/A	N/A
639.02	72.1 Pk	5.7 / 19.5 / 28.1	69.2	V / 1.0 / 0.0	N/A	N/A
745.52	43.2 Pk	6.3 / 21.4 / 28.0	43.0	V / 1.0 / 0.0	N/A	N/A
852.03	62.9 Pk	6.7 / 22.4 / 27.6	64.4	V / 1.0 / 0.0	N/A	N/A
958.53	66.8 Pk	7.1 / 23.4 / 27.5	69.8	V / 1.0 / 0.0	N/A	N/A
1065.10	38.8 Pk	7.9 / 22.6 / 27.6	41.7	V / 1.0 / 0.0	N/A	N/A
1171.60	39.2 Pk	8.2 / 23.7 / 27.5	43.6	H / 1.0 / 0.0	N/A	N/A
1278.13	55.8 Pk	8.7 / 25.1 / 27.0	62.6	H / 1.0 / 0.0	N/A	N/A
1384.62	51.6 Pk	9.3 / 26.0 / 29.5	57.5	V / 1.0 / 0.0	N/A	N/A
1491.14	52.6 Pk	9.5 / 27.0 / 28.4	60.6	V / 1.0 / 0.0	N/A	N/A
1597.64	50.8 Pk	10.3 / 26.5 / 28.0	59.6	V / 1.0 / 0.0	N/A	N/A
1704.14	49.0 Pk	10.7 / 27.6 / 28.0	59.2	V / 1.0 / 0.0	N/A	N/A
1810.65	53.0 Pk	10.7 / 27.8 / 28.0	63.5	V / 1.0 / 0.0	N/A	N/A
1917.15	51.4 Pk	11.3 / 28.2 / 28.2	62.6	V / 1.0 / 0.0	N/A	N/A
2023.65	52.5 Pk	11.3 / 29.6 / 27.5	65.9	V / 1.0 / 0.0	N/A	N/A
2130.16	49.9 Pk	11.6 / 29.9 / 27.5	63.8	V / 1.0 / 0.0	N/A	N/A
2236.66	47.4 Pk	11.8 / 30.1 / 27.8	61.5	V / 1.0 / 0.0	N/A	N/A
2343.16	44.6 Pk	12.0 / 30.3 / 28.0	58.8	H / 1.0 / 0.0	N/A	N/A

Tested by: RMJ

Printed

Signature

Reviewed by: TKS

Printed

Signature

# Radiated Electromagnetic Emissions



Test Report #: 3634 Run 03 Test Area: STS 3m  
Test Method: N/A Test Date: 24-Apr-2001  
EUT Model #: SHARPSHOOTER EUT Power: BATTERY  
(52-780)  
EUT Serial #: \_\_\_\_\_ Temperature: 5.2 °C  
Manufacturer: ITI Relative Humidity: 84 %  
EUT Description: PASSIVE INFRARED MOTION DETECTOR (PIR) Air Pressure: 99 kPa  
Notes: CONSTANT TRANSMITT MODE Page: 2 of 4

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB) (dBm) (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
2449.68	38.8 Pk	12.4 / 30.5 / 27.9	53.8	V / 1.0 / 0.0	N/A	N/A
2556.18	38.1 Pk	12.8 / 30.7 / 28.7	52.9	H / 1.0 / 0.0	N/A	N/A
2662.68	38.0 Pk	13.0 / 30.8 / 28.4	53.4	H / 1.0 / 0.0	N/A	N/A
2769.18	39.1 Pk	13.2 / 31.0 / 28.6	54.7	H / 1.0 / 0.0	N/A	N/A
2875.68	37.6 Pk	13.6 / 31.1 / 28.6	53.7	H / 1.0 / 0.0	N/A	N/A
2982.18	37.1 Pk	14.0 / 31.3 / 28.2	54.2	H / 1.0 / 0.0	N/A	N/A
3195.18	39.2 Pk	14.8 / 31.8 / 28.2	57.7	H / 1.0 / 0.0	N/A	N/A
END OF SCAN.						

Tested by: RMJ

Printed

Signature

Reviewed by: TKS

Printed

Signature

# Radiated Electromagnetic Emissions



Test Report #:	<b>3634 Run 03</b>	Test Area:	STS 3m	
Test Method:	N/A	Test Date:	24-Apr-2001	
EUT Model #:	SHARPSHOOTER (52-780)	EUT Power:	BATTERY	
EUT Serial #:		Temperature:	5.2	°C
Manufacturer:	ITI	Relative Humidity:	84	%
EUT Description:	PASSIVE INFRARED MOTION DETECTOR (PIR)	Air Pressure:	99	kPa
Notes:	CONSTANT TRANSMITT MODE		Page:	3 of 4

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB) (dBm) (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
---------------	-----------------	---	-----------------	-----------------------------	---------------	---------------

***** MEASUREMENT SUMMARY *****						
106.51	70.2 Pk	2.2 / 9.2 / 27.8	53.8	V / 1.0 / 0.0	N/A	N/A
213.01	79.2 Pk	3.1 / 10.9 / 28.0	65.2	V / 1.0 / 0.0	N/A	N/A
319.53	98.9 Pk	3.9 / 14.0 / 28.2	88.5	V / 1.0 / 0.0	N/A	N/A
426.01	56.6 Pk	4.6 / 17.0 / 28.0	50.2	V / 1.0 / 0.0	N/A	N/A
532.52	55.7 Pk	5.2 / 18.3 / 28.1	51.1	V / 1.0 / 0.0	N/A	N/A
639.02	72.1 Pk	5.7 / 19.5 / 28.1	69.2	V / 1.0 / 0.0	N/A	N/A
745.52	43.2 Pk	6.3 / 21.4 / 28.0	43.0	V / 1.0 / 0.0	N/A	N/A
852.03	62.9 Pk	6.7 / 22.4 / 27.6	64.4	V / 1.0 / 0.0	N/A	N/A
958.53	66.8 Pk	7.1 / 23.4 / 27.5	69.8	V / 1.0 / 0.0	N/A	N/A
1065.10	38.8 Pk	7.9 / 22.6 / 27.6	41.7	V / 1.0 / 0.0	N/A	N/A
1171.60	39.2 Pk	8.2 / 23.7 / 27.5	43.6	H / 1.0 / 0.0	N/A	N/A
1278.13	55.8 Pk	8.7 / 25.1 / 27.0	62.6	H / 1.0 / 0.0	N/A	N/A
1384.62	51.6 Pk	9.3 / 26.0 / 29.5	57.5	V / 1.0 / 0.0	N/A	N/A
1491.14	52.6 Pk	9.5 / 27.0 / 28.4	60.6	V / 1.0 / 0.0	N/A	N/A
1597.64	50.8 Pk	10.3 / 26.5 / 28.0	59.6	V / 1.0 / 0.0	N/A	N/A
1704.14	49.0 Pk	10.7 / 27.6 / 28.0	59.2	V / 1.0 / 0.0	N/A	N/A
1810.65	53.0 Pk	10.7 / 27.8 / 28.0	63.5	V / 1.0 / 0.0	N/A	N/A
1917.15	51.4 Pk	11.3 / 28.2 / 28.2	62.6	V / 1.0 / 0.0	N/A	N/A
2023.65	52.5 Pk	11.3 / 29.6 / 27.5	65.9	V / 1.0 / 0.0	N/A	N/A
2130.16	49.9 Pk	11.6 / 29.9 / 27.5	63.8	V / 1.0 / 0.0	N/A	N/A
2236.66	47.4 Pk	11.8 / 30.1 / 27.8	61.5	V / 1.0 / 0.0	N/A	N/A
2343.16	44.6 Pk	12.0 / 30.3 / 28.0	58.8	H / 1.0 / 0.0	N/A	N/A
2449.68	38.8 Pk	12.4 / 30.5 / 27.9	53.8	V / 1.0 / 0.0	N/A	N/A
2556.18	38.1 Pk	12.8 / 30.7 / 28.7	52.9	H / 1.0 / 0.0	N/A	N/A

Tested by: RMJ

Printed

Signature

Reviewed by: TKS

Printed

Signature

# Radiated Electromagnetic Emissions



Test Report #: **3634 Run 03** Test Area: **STS 3m**  
Test Method: **N/A** Test Date: **24-Apr-2001**  
EUT Model #: **SHARPSHOOTER (52-780)** EUT Power: **BATTERY**  
EUT Serial #: \_\_\_\_\_ Temperature: **5.2** °C  
Manufacturer: **ITI** Relative Humidity: **84** %  
EUT Description: **PASSIVE INFRARED MOTION DETECTOR (PIR)** Air Pressure: **99** kPa  
Notes: **CONSTANT TRANSMITT MODE** Page: **4 of 4**

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB) (dBm) (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
---------------	-----------------	---	-----------------	-----------------------------	---------------	---------------

***** MEASUREMENT SUMMARY *****						
2662.68	38.0 Pk	13.0 / 30.8 / 28.4	53.4	H / 1.0 / 0.0	N/A	N/A
2769.18	39.1 Pk	13.2 / 31.0 / 28.6	54.7	H / 1.0 / 0.0	N/A	N/A
2875.68	37.6 Pk	13.6 / 31.1 / 28.6	53.7	H / 1.0 / 0.0	N/A	N/A
2982.18	37.1 Pk	14.0 / 31.3 / 28.2	54.2	H / 1.0 / 0.0	N/A	N/A
3195.18	39.2 Pk	14.8 / 31.8 / 28.2	57.7	H / 1.0 / 0.0	N/A	N/A

Tested by: **RMJ**

\_\_\_\_\_  
Printed

\_\_\_\_\_  
Signature

Reviewed by: **TKS**

\_\_\_\_\_  
Printed

\_\_\_\_\_  
Signature