

# RF Exposure Evaluation

*of*

E.U.T. : Handheld  
FCC ID. : B5DH2286M  
Model No. : RE3-HHT-6M  
Working Frequency : 657~663 MHz

*for*

APPLICANT : Bosch Security Systems, Inc.  
ADDRESS : 8601 East Cornhusker Highway Lincoln, NE 68507  
USA

Test Performed by

ELECTRONICS TESTING CENTER (ETC) , TAIWAN  
NO. 34. LIN 5, DINGFU VIL., LINKOU DIST.,  
NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.  
TEL : (02)26023052 FAX : (02)26010910  
[http:// www.etc.org.tw](http://www.etc.org.tw) ; e-mail:emc@etc.org.tw

Report Number : 18-09-RBF-012-10-MPE

## **TEST REPORT CERTIFICATION**

Applicant : Bosch Security Systems, Inc.  
 8601 East Cornhusker Highway Lincoln, NE 68507  
 USA

Manufacturer : JTS Professional Co., Ltd.  
 No. 148, Industry 9th Road, Tali Dist., Taichung City 41280  
 Taiwan, R.O.C.

Description of EUT :

a) Type of EUT : Handheld  
 b) Trade Name : Electro-Voice  
 c) Model No. : RE3-HHT-6M  
 d) FCC ID : B5DH2286M  
 e) Working Frequency : 657~663 MHz  
 f) Power Supply : DC 3V Battery

Regulation Applied: FCC KDB447498 D01. The equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of section 1.1310 of FCC 47 CFR Part 1.

Note:

1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC

Issued Date : Dec.27, 2018

Test Engineer :

*Brian Huang*

(Brian Huang, Engineer )



Approve & Authorized Signer :

*Vincent Chang*  
 Vincent Chang, Supervisor  
 EMC Dept. II of ELECTRONICS  
 TESTING CENTER, TAIWAN

**Product Information:**

Type of EUT: Handheld  
FCC ID: B5DH2286M  
Model: RE3-HHT-6M

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

The max. average power of channel, including tune-up tolerance(mW) is 10.0mW @ 662.950MHz (With Tune-up tolerance),

The min. test separation distance (mm) is 5 mm,

So,  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 1.63 < 3.0$  (With Tune-up tolerance).

Therefore, standalone SAR measurements are not required for both head and body.

.