

Prepared (also subject responsible if other) EAB/FJG/VR Per Helmersson		No. B5KEKRC1311005-2 Uen		
Approved KI/EAB/FJG/VR(P Helmersson)	Checked	Date 2007-09-19	Rev A	Reference

Federal Communications Commission  
Authorization & Evaluation Division  
7435 Oakland Mills Road  
Columbia, Maryland 21046  
Attention: Equipment Authorization Branch

SP Sveriges Provnings- och Forskningsinstitut  
Brinellgatan 4  
Box 857  
S-501 15 Borås  
Sweden

September 19, 2006

Subject: Certification for FCC ID: B5KEKRC1311005-2

Gentlemen;

Ericsson AB requests a Grant of Certification (Type Acceptance) for the mentioned FCC Identifier above.

This base station transceiver is designed for use in the GSM 800 MHz cellular telephone system. The transmitter will operate from 869.2 to 893.8 MHz. The receiver circuit supports 824.2 to 848.8 MHz. The base station operates in the 800 MHz broadband Cellular services as per 47 CFR Part 22 subpart H. It meets the requirements of GSM1900 11.10-1 version 4.19.1 specification for operation in GSM cellular systems except for the output frequency range. The transceiver can be used in the base station models RBS 2106, RBS 2106V3 RBS 2107, RBS 2206, RBS 2206V2 and RBS 2207.

These base stations will in normal mode operate at a nominal power out of 46.3 dBm for GMSK and 43 dBm for 8-PSK at the antenna connector when using combiner unit CDU-G, CDU-J or CDU-K. In TCC mode with two transmitters combined on the same frequency the nominal output power is 49 dBm for GMSK and 45.7 dBm for 8-PSK. The power output is reducible to ~0.3 watts.

The transmitter path in CDU-G CDU-J and CDU-K is identical.

Due to the too wide frequency spectrum at the band edges the output power has to be reduced in some cases. In both GMSK and 8-PSK mode the output power in channel 128 – 869.2 MHz and channel 251 – 893.8 MHz has to be reduced to a maximum of 37.7 dBm.

Ericsson AB requests confidentiality under CFR 0.459. Confidentiality for the following exhibits is requested:

Exhibit 4 Block diagram  
Exhibit 5 Part 1 Schematics  
Exhibit 5 Part 2 Schematics  
Exhibit 8 Internal manuals  
Exhibit 9 Internal photos  
Exhibit 12 Circuit description

The Radio Base Station (RBS) is always installed and placed in an area with access only to authorize personal. Sensitive information, such as internal photos and manuals is not available for general public in any form. Only customer with a Non-Disclosure Agreement (NDA) in place will get access to sensitive information. So the only way a competitor could get technical information on the RBS is from FCC records.

Justification of this request is in order to protect the large investment in developing this technology and to facilitate the circuit miniaturization utilized in this design and protect the innovative design as well as proprietary techniques which are implemented. In order to protect Ericsson's competitive advantage on these proprietary techniques, we request the above listed exhibits be held as confidential and withheld from the Public Information File.

We further certify that the applicant nor any party to the application is subject to a denial of Federal benefits, that includes FCC benefits, pursuant to section 5301 of the Anti-Drug abuse Act of 1988, 21 U.S.C. Section 862.

Prepared (also subject responsible if other) EAB/FJG/VR Per Helmersson		No. B5KEKRC1311005-2 Uen		
Approved KI/EAB/FJG/VR(P Helmersson)	Checked	Date 2007-09-19	Rev A	Reference

Ericsson AB accept by this request the agreement set out in the document "Bilaga SPCR 125 -Avtal om marknadskontroll för radioutrustning certifierad för USA-marknaden"

If additional information is needed, please contact me on the below listed number.

Sincerely,

Per Helmersson  
Staff Engineer, Regulatory Programs  
Ericsson AB  
Torshamnsgatan 21-23 (Färögatan 6)  
Kista, SE-164 80 Stockholm  
Sweden  
Telephone No.: +46 8 764 16 52  
Fax No.: +46 8 404 41 90  
e-mail per.helmersson@ericsson.com