

October 30, 2015

UL VERIFICATION SERVICES, INC  
47173 Benicia Street, Fremont, CA 94538

FCC ID: B6BZM-541PAA

To whom it may concern,

We, UL Japan, Inc, hereby declare that TRANSMITTER, model: ZM-541PA (FCC ID: B6BZM-541PAA) of NIHON KOHDEN CORPORATION is exempt from RF exposure SAR evaluation as its output power meets the exclusion limits stated in KDB 447498D01(v06).

KDB 447498D01(v06) has the following exclusion for portable devices:

The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

*[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]*

·  $[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

·  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

· Power and distance are rounded to the nearest mW and mm before calculation

· The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

This device has  $f = 1.43$  GHz and distance = 5 mm (minimum separation distance: 5 mm was used in the calculation) and the maximum average output power was 6 mW

So for this device:

$6 \text{ mW}[\text{maximum average output power}]/5 \text{ mm}[\text{minimum separation distance}] * \sqrt{1.43} = 1.4$

\*This is less than 3.0, so no SAR is required.

Even taking into account the tolerance, this device

Thank you for your attention to this matter.



---

Takahiro Hatakeda  
Leader of Ise EMC Lab.  
Consumer Technology Division  
UL Japan, Inc.