

Page: 1 of 89

SAR TEST REPORT





The following samples were submitted and identified on behalf of the client as:

Product Name Convertible PC

Brand Name HP

Model No. **TPN-C149** HP Inc. **Prepared for**

3390 East Harmony Road, Fort Collins Colorado, USA

80528

Standards IEEE/ANSI C95.1-1992, IEEE 1528-2013,

KDB248227D01v02r02,KDB865664D01v01r04,

KDB865664D02v01r02,KDB447498D01v06,

KDB616217D04v01r02.

FCC ID B94-AX201NGWS

Date of Receipt Nov. 21, 2019

Date of Test(s) Nov. 26, 2019 ~ Nov. 30, 2019

Date of Issue Dec. 30, 2019

In the configuration tested, the EUT complied with the standards specified above.

Remarks:

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Taiwan Electronic & Communication Laboratory or testing done by SGS Taiwan Electronic & Communication Laboratory in connection with distribution or use of the product described in this report must be approved by SGS Taiwan Electronic & Communication Laboratory in

Signed on behalf of SGS

Clerk / Ruby Ou	Engineer / Jay Tseng	Asst. Manager / John Yeh
Ruby Ou	Fory Tseng	John Teh

Date: Dec. 30, 2019

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms-e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

www.tw.sas.com



Page: 2 of 89

Revision History

Revision	Description	Issue Date
Rev.00	Initial creation of document	Dec. 30, 2019

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 3 of 89

Contents

1. General Information	4
1.1 Testing Laboratory	4
1.2 Details of Applicant	4
1.3 Description of EUT	5
1.4 Test Environment	38
1.5 Operation Description	38
1.6 Operating modes validation by power measurement	40
1.7 The SAR Measurement System	49
1.8 System Components	
1.9 SAR System Verification	
1.10 Tissue Simulant Fluid for the Frequency Band	
1.11 Evaluation Procedures	
1.12 Probe Calibration Procedures	
1.13 Test Standards and Limits	
2. Summary of Results	
2.1 Decision rules	
2.2 Summary of Results	
2.3 Reporting statements of conformity	64
3. Simultaneous Transmission Analysis	65
3.1 Estimated SAR calculation	
3.2 SPLSR evaluation and analysis	66
4. Instruments List	70
5. Measurements	71
6. SAR System Performance Verification	82
7. Uncertainty Budget	
Appendixes	
ES2019B0007 SAR_Appendix A Photographs	
ES2019B0007 SAR_Appendix B DAE & Probe Cal. Certificate	
ES2019B0007 SAR_Appendix C Phantom Description & Dipole Cal. Certificate	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 4 of 89

1. General Information

1.1 Testing Laboratory

SGS Taiwan Ltd. Electronics & Communication Laboratory						
No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei						
City, Taiwan						
Tel +886-2-2299-3279						
Fax +886-2-2298-0488						
Internet	http://www.tw.sgs.com/					

1.2 Details of Applicant

Company Name	HP Inc.
Company Address	3390 East Harmony Road, Fort Collins Colorado , USA 80528

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 5 of 89

1.3 Description of EUT

General Information of Host

General Information of Host:								
Equipment Under Test	Convertible PC							
Brand Name	HP							
Model No.	TPN-C149							
Integrated Module	Brand Name : Intel Model Name : AX201NGW							
FCC ID	B94-AX201NGWS							
Mode of Operation	⊠WLAN802.11 a/b/g/n/ac/ax(20M/40 ⊠Bluetooth	M/80M/	160M)				
Duty Cycle	WLAN802.11 a/b/g/n/ac/ax(20M/40M/80M/160M)		1					
	Bluetooth		1					
	WLAN802.11 b/g/n/ax(20M)	2412	_	2472				
	WLAN802.11 n/ax(40M)	2422	_	2462				
	WLAN802.11 a/n/ac/ax(20M) 5.2G	5180	_	5240				
	WLAN802.11 n/ac/ax(40M) 5.2G	5190	_	5230				
	WLAN802.11 ac/ax(80M) 5.2G 5210							
	WLAN802.11 ac/ax(160M) 5.2G		5250					
	WLAN802.11 a/n/ac/ax(20M) 5.3G	5260	_	5320				
TX Frequency Range (MHz)	WLAN802.11 n/ac/ax(40M) 5.3G	5270	_	5310				
,	WLAN802.11 ac/ax(80M) 5.3G	5290						
	WLAN802.11 a/n/ac/ax(20M) 5.6G	5500	_	5720				
	WLAN802.11 n/ac/ax(40M) 5.6G	5510	_	5710				
	WLAN802.11 ac/ax(80M) 5.6G	5530	_	5690				
	WLAN802.11 ac/ax(160M) 5.6G		5570)				
	WLAN802.11 a/n/ac/ax(20M) 5.8G	5745	_	5825				
	WLAN802.11 n/ac/ax(40M) 5.8G	5755	_	5795				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279 f (886-2) 2298-0488 www.tw.sas.com



Page: 6 of 89

TX Frequency Range	WLAN802.11 ac/ax(80M) 5.8G		5775	
(MHz)	Bluetooth	2402	_	2480
	WLAN802.11 b/g/n/ax(20M)	1	_	13
	WLAN802.11 n/ax(40M)	3	_	11
	WLAN802.11 a/n/ac/ax(20M) 5.2G	36	_	48
	WLAN802.11 n/ac/ax(40M) 5.2G	38	_	46
	WLAN802.11 ac/ax(80M) 5.2G		42	
	WLAN802.11 ac/ax(160M) 5.2G		50	
	WLAN802.11 a/n/ac/ax(20M) 5.3G	52	_	64
	WLAN802.11 n/ac/ax(40M) 5.3G	54	_	62
Channel Number (ARFCN)	WLAN802.11 ac/ax(80M) 5.3G		58	
(* ***)	WLAN802.11 a/n/ac/ax(20M) 5.6G	100	_	144
	WLAN802.11 n/ac/ax(40M) 5.6G	102	_	142
	WLAN802.11 ac/ax(80M) 5.6G	106	_	138
	WLAN802.11 ac/ax(160M) 5.6G		114	
	WLAN802.11 a/n/ac/ax(20M) 5.8G	149	_	165
	WLAN802.11 n/ac/ax(40M) 5.8G	151	_	159
	WLAN802.11 ac/ax(80M) 5.8G		155	
	Bluetooth	0	_	78

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 7 of 89

Max. SAR (1g) (Unit: W/Kg)							
Antenna	Band	Measured	Reported	Channel	Position		
	WLAN 802.11b	0.92	0.92	6	Top side		
	WLAN 802.11ac(80M) 5.2G	0.87	0.88	2	Top side		
Tx1	WLAN 802.11ac(80M) 5.3G	0.87	0.88	58	Top side		
	WLAN 802.11ac(80M) 5.6G	1.03	1.04	106	Top side		
	WLAN 802.11ac(80M) 5.8G	0.71	0.73	155	Top side		
	WLAN 802.11b	1.14	1.15	1	Top side		
	Bluetooth(GFSK)	0.20	0.23	78	Top side		
TvO	WLAN 802.11ac(80M) 5.2G	0.93	0.94	42	Top side		
Tx2	WLAN 802.11ac(80M) 5.3G	0.85	0.85	58	Top side		
	WLAN 802.11ac(80M) 5.6G	0.79	0.79	106	Top side		
	WLAN 802.11ac(80M) 5.8G	0.73	0.73	155	Top side		

Antenna Information

					Tablet mode					
Vendor		Wistron NeWeb Corp.								
Antenna			Tx1(PIFA)					Tx2 (PIFA)		
Part Number	DC33002DO00 81EAA415.GJK				DC33002DO10 81EAA415.GJL					
Frequency	2400-2500	5150-5250	5250-5350	5470-5725	5725-5850	60 2400-2500 5150-5250 5250-5350 5470-5725 572			5725-5850	
Gain (dBi)	0.22	1.35	1.92	1.94	1.68	0.75 -1.23 -1.23 -0.76 -				-1.21
				No	tebook mod	le				
Vendor					Wistron Ne	Web Corp.				
Antenna			Tx1(PIFA)					Tx2 (PIFA)		
Part Number	DC33002DO00 81EAA415.GJK				DC33002DO10 81EAA415.GJL					
Frequency	2400~2500	5150~5250	5250~5350	5470~5725	5725~5850	2400~2500	5150~5250	5250~5350	5470~5725	5725~5850
Gain (dBi)	-0.36	-0.68	-0.47	1.16	0.44	0.49	-1.12	-1.27	-0.77	-0.64

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 8 of 89

WLAN802.11 a/b/g/n(20M/40M)/ac/ax(20M/40M/80M/160M) conducted power table:

Antenna	SI	SO	MIMO
Band	Tx1	Tx2	Tx1 + Tx2
WLAN802.11b	V	V	-
WLAN802.11g	V	V	-
WLAN802.11n(20M)	V	V	V
WLAN802.11n(40M)	V	V	V
WLAN802.11ax(20M)	V	V	V
WLAN802.11ax(40M)	V	V	V
WLAN802.11a	V	V	-
WLAN802.11n(20M) 5G	V	V	V
WLAN802.11n(40M) 5G	V	V	V
WLAN802.11ac(20M) 5G	V	V	V
WLAN802.11ac(40M) 5G	V	V	V
WLAN802.11ac(80M) 5G	V	V	V
WLAN802.11ac(160M) 5G	V	V	V
WLAN802.11ax(20M) 5G	V	V	V
WLAN802.11ax(40M) 5G	V	V	V
WLAN802.11ax(80M) 5G	V	V	V
WLAN802.11ax(160M) 5G	V	V	V

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 9 of 89

Tablet mode

		Tx1	l antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		1	2412		19.00	18.91
		6	2437		19.00	18.99
	802.11b	11	2462	1Mbps	19.00	18.98
		12	2467		18.50	18.42
		13	2472		18.50	18.47
		1	2412		17.00	16.94
		2	2417		18.50	18.41
		6	2437		19.00	18.97
	802.11g	10	2457	6Mbps	18.75	18.71
		11	2462		16.25	16.22
		12	2467		15.00	14.96
		13	2472		10.50	10.41
2450 MHz		1	2412		17.00	16.98
2430 1011 12		2	2417		18.50	18.43
		6	2437		19.00	18.96
	802.11n20-HT0	10	2457	MCS0	18.75	18.66
		11	2462		16.25	16.19
		12	2467		15.00	14.95
		13	2472		10.50	10.47
		1	2412		17.00	16.94
		2	2417		18.50	18.49
		6	2437		19.00	18.98
	802.11ax20-HE0	10	2457	MCS0	18.75	18.73
		11	2462		16.25	16.25
		12	2467		15.00	14.92
		13	2472		10.50	10.46

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 10 of 89

		Tx1	l antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		3	2422		16.50	16.50
	802.11n40-HT0	4	2427	MCS0	17.50	17.42
		6	2437		17.50	17.41
		8	2447		16.25	16.22
		9	2452		16.00	15.92
		10	2457		12.25	12.17
2450 MHz		11	2462		12.50	12.46
2430 1011 12		3	2422		16.50	16.42
		4	2427		17.50	17.43
		6	2437		17.50	17.46
	802.11ax40-HE0	8	2447	MCS0	16.25	16.22
		9	2452		16.00	15.91
		10	2457		12.25	12.17
		11	2462		12.50	12.44

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 11 of 89

		Tx1 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		36	5180		16.00	15.98
	902.116	40	5200	GMbpa	16.00	16.00
	802.11a	44	5220	6Mbps	16.00	15.95
		48	5240		16.00	15.97
	802.11n20-HT0	36	5180		16.00	16.00
		40	5200	MCS0	16.00	15.92
		44	5220	IVICSU	16.00	15.96
		48	5240		16.00	15.91
		36	5180		16.00	15.99
	802.11ac20-VHT0	40	5200	MCS0	16.00	15.98
	002.11ac20-VH10	44	5220	IVICSO	16.00	16.00
		48	5240		16.00	16.00
5.15-5.25 GHz		36	5180		16.00	15.98
5.13-3.23 GHZ	802.11ax20-HE0	40	5200	MCS0	16.00	15.94
	602.11ax20-HE0	44	5220	MCSU	16.00	16.00
		48	5240		16.00	15.94
	802.11n40-HT0	38	5190	MCS0	16.00	15.95
	002.111140-1110	46	5230	MCSU	16.00	15.96
	802.11ac40-VHT0	38	5190	MCS0	16.00	15.99
	002.11ac+0-V1110	46	5230	IVICOU	16.00	15.95
	802.11ax40-HE0	38	5190	MCS0	16.00	15.94
		46	5230		16.00	15.92
	802.11ac80-VHT0	42	5210	MCS0	16.00	15.95
	802.11ax80-HE0	42	5210	MCS0	16.00	15.93
	802.11ac160-VHT0	50	5250	MCS0	14.75	14.68
	802.11ax160-HE0	50	5250	MCS0	14.75	14.70

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 12 of 89

		Tx1 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		52	5260		16.00	15.98
	802.11a	56	5280	GN/hna	16.00	15.99
	002.11a	60	5300	6Mbps	16.00	15.97
		64	5320		16.00	15.91
		52	5260		16.00	15.99
	802.11n20-HT0	56	5280	MOCO	16.00	15.96
	602.111120-H10	60	5300	MCS0	16.00	15.95
		64	5320		16.00	15.93
		52	5260		16.00	15.99
	802.11ac20-VHT0	56	5280	MCS0	16.00	15.92
	002.11ac20-VI110	60	5300		16.00	15.97
5.25-5.35 GHz		64	5320		16.00	15.94
0.23-3.33 GHZ		52	5260		16.00	15.96
	802.11ax20-HE0	56	5280	MCS0	16.00	15.97
	602.11ax20-HE0	60	5300	MCSU	16.00	15.95
		64	5320		16.00	15.99
	802.11n40-HT0	54	5270	MCS0	16.00	15.91
	002.1111 4 0-Π10	62	5310	IVICSU	16.00	15.96
	802.11ac40-VHT0	54	5270	MCS0	16.00	15.91
	002.11a040-VHTU	62	5310	IVICOU	16.00	15.91
	802.11ax40-HE0	54	5270	MCS0	16.00	15.93
	002.11ax40-11E0	62	5310	IVICOU	16.00	15.93
	802.11ac80-VHT0	58	5290	MCS0	16.00	15.97
	802.11ax80-HE0	58	5290	MCS0	16.00	15.93

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 13 of 89

		Tx1 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		100	5500		16.00	15.95
		116	5580		16.00	15.97
	802.11a	120	5600	6Mbps	16.00	15.93
		140	5700		16.00	15.96
		144	5720		16.00	15.91
	802.11n20-HT0	100	5500	MCS0	16.00	15.95
		116	5580		16.00	15.91
		120	5600		16.00	15.94
		140	5700		16.00	15.92
5600 MHz		144	5720		16.00	15.91
3000 10112		100	5500		16.00	15.91
		116	5580		16.00	16.00
	802.11ac20-VHT0	120	5600	MCS0	16.00	15.94
		140	5700		16.00	16.00
		144	5720		16.00	15.97
		100	5500		16.00	15.99
		116	5580		16.00	16.00
	802.11ax20-HE0	120	5600	MCS0	16.00	16.00
		140	5700		16.00	15.99
		144	5720		16.00	15.96

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 14 of 89

		Tx1 a	antenna			
		1710	interna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		102	5510		16.00	15.92
	802.11n40-HT0	110	5550	MCS0	16.00	15.94
	002.1111 4 0-1110	118	5590	IVICSU	16.00	15.98
		134	5670		16.00	15.97
		102	5510		16.00	15.91
		110	5550		16.00	15.97
	802.11ac40-VHT0	118	5590	MCS0	16.00	15.97
		134	5670		16.00	15.94
		142	5710		16.00	15.91
		102	5510		16.00	16.00
5600 MHz		110	5550		16.00	15.98
3000 101112	802.11ax40-HE0	118	5590	MCS0	16.00	15.94
		134	5670		16.00	15.98
		142	5710		16.00	15.99
		106	5530		16.00	15.96
	802.11ac80-VHT0	122	5610	MCS0	16.00	15.91
		138	5690		16.00	15.90
		106	5530		16.00	15.88
	802.11ax80-HE0	122	5610	MCS0	16.00	15.91
		138	5690		16.00	15.92
	802.11ac160-VHT0	114	5570	MCS0	14.50	14.41
	802.11ax160-HE0	114	5570	MCS0	14.50	14.45

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 15 of 89

		Tx1 a	antenna			
		1	a			
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		149	5745		16.00	16.00
	802.11a	157	5785	6Mbps	16.00	15.98
		165	5825		16.00	15.99
	802.11n20-HT0	149	5745		16.00	15.92
		157	5785	MCS0	16.00	15.92
		165	5825		16.00	15.96
	802.11ac20-VHT0	149	5745	MCS0	16.00	16.00
		157	5785		16.00	15.98
		165	5825		16.00	15.91
5800 MHz		149	5745		16.00	15.93
3600 1011 12	802.11ax20-HE0	157	5785	MCS0	16.00	15.93
		165	5825		16.00	15.98
	802.11n40-HT0	151	5755	MCS0	16.00	15.98
	002.111140-1110	159	5795	IVICOU	16.00	15.94
	802.11ac40-VHT0	151	5755	MCS0	16.00	16.00
	002.11ac40-VH10	159	5795	IVICOU	16.00	15.91
	802.11ax40-HE0	151	5755	MCS0	16.00	15.93
	002.11ax40-11L0	159	5795		16.00	16.00
	802.11ac80-VHT0	155	5775	MCS0	16.00	15.90
	802.11ax80-HE0	155	5775	MCS0	16.00	15.95

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 16 of 89

		Tx2	2 antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		1	2412		19.00	18.97
		6	2437		19.00	18.88
	802.11b	11	2462	1Mbps	19.00	18.96
		12	2467		18.50	18.49
		13	2472		18.50	18.49
		1	2412		16.75	16.74
		2	2417		18.50	18.50
		6	2437		19.00	18.94
	802.11g	10	2457	6Mbps	18.75	18.68
		11	2462		16.50	16.42
		12	2467		15.00	14.94
		13	2472		12.00	11.93
2450 MHz		1	2412		16.75	16.69
2430 1011 12		2	2417		18.50	18.44
		6	2437		19.00	18.93
	802.11n20-HT0	10	2457	MCS0	18.75	18.70
		11	2462		16.50	16.41
		12	2467		15.00	14.92
		13	2472		12.00	11.91
		1	2412		16.75	16.67
		2	2417		18.50	18.42
		6	2437		19.00	18.99
	802.11ax20-HE0	10	2457	MCS0	18.75	18.75
		11	2462		16.50	16.41
		12	2467		15.00	14.97
		13	2472		12.00	11.91

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 17 of 89

	Tx2 antenna									
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)				
		3	2422		16.50	16.46				
	802.11n40-HT0	4	2427		17.50	17.47				
		6	2437	MCS0	17.50	17.49				
		8	2447		16.25	16.22				
		9	2452		16.25	16.16				
		10	2457		12.00	11.98				
2450 MHz		11	2462		12.50	12.49				
2430 WII72		3	2422		16.50	16.48				
		4	2427		17.50	17.44				
		6	2437		17.50	17.49				
	802.11ax40-HE0	8	2447	MCS0	16.25	16.17				
		9	2452		16.25	16.20				
		10	2457		12.00	11.95				
		11	2462		12.50	12.46				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 18 of 89

		Tx2 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		36	5180		16.00	15.95
	802.11a	40	5200	6Mbpa	16.00	15.95
	602.11a	44	5220	6Mbps	16.00	15.94
		48	5240		16.00	15.95
	802.11n20-HT0	36	5180		16.00	15.91
		40	5200	MCS0	16.00	15.93
		44	5220	IVICSU	16.00	15.93
		48	5240		16.00	15.91
		36	5180		16.00	15.97
	802.11ac20-VHT0	40	5200	MCS0	16.00	15.91
	002.11ac20-VI110	44	5220	IVICSO	16.00	15.91
		48	5240		16.00	15.97
5.15-5.25 GHz		36	5180		16.00	16.00
5.15-5.25 GHZ	802.11ax20-HE0	40	5200	MCS0	16.00	16.00
	002.11ax20-11L0	44	5220	IVICOU	16.00	15.96
		48	5240		16.00	15.95
	802.11n40-HT0	38	5190	MCS0	16.00	15.99
	002.111140-1110	46	5230	MCSU	16.00	15.96
	802.11ac40-VHT0	38	5190	MCS0	16.00	15.98
	002.11ac+0-V1110	46	5230	IVICOU	16.00	16.00
	802.11ax40-HE0	38	5190	MCS0	16.00	15.96
	002.11ax+0-11L0	46	5230		16.00	15.96
	802.11ac80-VHT0	42	5210	MCS0	16.00	15.97
	802.11ax80-HE0	42	5210	MCS0	16.00	15.98
	802.11ac160-VHT0	50	5250	MCS0	15.00	14.98
	802.11ax160-HE0	50	5250	MCS0	15.00	14.92

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 19 of 89

		Tx2 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		52	5260		16.00	15.93
	802.11a	56	5280	GN/hna	16.00	15.97
	002.11a	60	5300	6Mbps	16.00	15.93
		64	5320		16.00	15.92
		52	5260		16.00	15.96
	802.11n20-HT0	56	5280	MOCO	16.00	15.97
	602.111120-H10	60	5300	MCS0	16.00	15.96
		64	5320		16.00	15.93
		52	5260	MCS0	16.00	15.94
	802.11ac20-VHT0	56	5280		16.00	15.98
	002.11ac20-VH10	60	5300		16.00	15.92
5.25-5.35 GHz		64	5320		16.00	15.92
0.23-3.33 GHZ		52	5260		16.00	15.97
	802.11ax20-HE0	56	5280	MCS0	16.00	15.97
	602.11ax20-HE0	60	5300	MCSU	16.00	15.98
		64	5320		16.00	15.95
	802.11n40-HT0	54	5270	MCS0	16.00	15.93
	ου ∠. ι ιιι 4 υ-Π ι υ	62	5310	IVICOU	16.00	15.93
	802.11ac40-VHT0	54	5270	MCS0	16.00	16.00
	002.11a040-VH10	62	5310	IVICOU	16.00	15.92
	802.11ax40-HE0	54	5270	MCS0	16.00	15.93
	002.11ax40-11E0	62	5310	IVICOU	16.00	15.96
	802.11ac80-VHT0	58	5290	MCS0	16.00	15.99
	802.11ax80-HE0	58	5290	MCS0	16.00	15.94

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 20 of 89

		Tx2 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		100	5500		16.00	15.94
		116	5580		16.00	16.00
	802.11a	120	5600	6Mbps	16.00	15.93
		140	5700		16.00	15.96
		144	5720		16.00	15.95
	802.11n20-HT0	100	5500	MCS0	16.00	15.95
		116	5580		16.00	15.97
		120	5600		16.00	15.95
		140	5700		16.00	15.96
5600 MHz		144	5720		16.00	15.96
3000 1011 12		100	5500		16.00	15.99
		116	5580		16.00	15.95
	802.11ac20-VHT0	120	5600		16.00	15.92
		140	5700		16.00	15.99
		144	5720		16.00	15.93
		100	5500		16.00	15.97
		116	5580		16.00	15.97
	802.11ax20-HE0	120	5600	MCS0	16.00	15.92
		140	5700		16.00	15.96
		144	5720		16.00	15.98

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 21 of 89

		Tx2 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		102	5510		16.00	16.00
	802.11n40-HT0	110	5550	MCS0	16.00	15.96
	002.1111 4 0-1110	118	5590	IVICSU	16.00	15.92
		134	5670		16.00	15.94
		102	5510		16.00	15.95
		110	5550	MCS0	16.00	15.99
	802.11ac40-VHT0	118	5590		16.00	15.92
		134	5670		16.00	16.00
		142	5710		16.00	15.96
		102	5510		16.00	15.95
5600 MHz		110	5550		16.00	15.97
3000 MITZ	802.11ax40-HE0	118	5590	MCS0	16.00	16.00
		134	5670		16.00	15.96
		142	5710		16.00	15.92
		106	5530		16.00	15.99
	802.11ac80-VHT0	122	5610	MCS0	16.00	15.98
		138	5690		16.00	15.91
		106	5530		16.00	16.00
	802.11ax80-HE0	122	5610	MCS0	16.00	15.94
		138	5690		16.00	15.96
	802.11ac160-VHT0	114	5570	MCS0	14.50	14.50
	802.11ax160-HE0	114	5570	MCS0	14.50	14.47

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 22 of 89

		Tx2 a	antenna			
		1				
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		149	5745		16.00	15.93
	802.11a	157	5785	6Mbps	16.00	15.92
		165	5825		16.00	15.92
	802.11n20-HT0	149	5745		16.00	15.91
		157	5785	MCS0	16.00	15.98
		165	5825		16.00	15.97
	802.11ac20-VHT0	149	5745	MCS0	16.00	15.95
		157	5785		16.00	15.93
		165	5825		16.00	15.95
5800 MHz		149	5745		16.00	15.96
3600 1011 12	802.11ax20-HE0	157	5785	MCS0	16.00	15.95
		165	5825		16.00	16.00
	802.11n40-HT0	151	5755	MCS0	16.00	15.96
	002.111140-1110	159	5795	IVICOU	16.00	15.94
	802.11ac40-VHT0	151	5755	MCS0	16.00	15.98
	002.11ac40-VH10	159	5795	IVICOU	16.00	15.96
	802.11ax40-HE0	151	5755	MCS0	16.00	15.89
	002.11ax40-11L0	159	5795		16.00	15.96
	802.11ac80-VHT0	155	5775	MCS0	16.00	15.98
	802.11ax80-HE0	155	5775	MCS0	16.00	15.91

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 23 of 89

Notebook mode

		Tx1	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		1	2412		19.50	19.46
		2	2417		20.50	20.44
		6	2437	1	20.50	20.47
	802.11b	10	2457	1Mbps	20.50	20.49
		11	2462		19.50	19.46
		12	2467		18.50	18.43
		13	2472		18.50	18.46
		1	2412		17.00	16.92
		2	2417		18.50	18.45
		6	2437		19.75	19.73
	802.11g	10	2457	6Mbps	18.75	18.72
		11	2462	<u> </u> -	16.25	16.23
		12	2467		15.00	14.99
2450 MHz		13	2472		10.50	10.41
2430 1011 12		1	2412		17.00	16.92
		2	2417		18.50	18.49
		6	2437		19.75	19.68
	802.11n20-HT0	10	2457	MCS0	18.75	18.73
		11	2462		16.25	16.25
		12	2467		15.00	14.94
		13	2472		10.50	10.43
		1	2412		17.00	16.98
		2	2417		18.50	18.47
		6	2437		19.75	19.67
	802.11ax20-HE0	10	2457	MCS0	18.75	18.70
		11	2462		16.25	16.23
		12	2467		15.00	14.99
		13	2472		10.50	10.42

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 24 of 89

	Tx1 antenna									
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)				
		3	2422		16.50	16.43				
		4	2427	MCS0	17.50	17.42				
	802.11n40-HT0	6	2437		17.50	17.49				
		8	2447		16.25	16.25				
		9	2452		16.00	15.98				
		10	2457		12.25	12.22				
2450 MHz		11	2462		12.50	12.46				
2430 1011 12		3	2422		16.50	16.43				
		4	2427		17.50	17.50				
		6	2437		17.50	17.43				
	802.11ax40-HE0	8	2447	MCS0	16.25	16.24				
		9	2452		16.00	15.93				
		10	2457		12.25	12.19				
		11	2462		12.50	12.42				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 25 of 89

		Tx1 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		36	5180		18.50	18.48
	802.11a	40	5200	6Mbpa	20.50	20.46
	602.11a	44	5220	6Mbps	20.50	20.40
		48	5240		20.50	20.49
	802.11n20-HT0	36	5180		18.50	18.42
		40	5200	MCS0	20.50	20.49
		44	5220	IVICSU	20.50	20.50
		48	5240		20.50	20.43
		36	5180		18.50	18.41
	802.11ac20-VHT0	40	5200	MCS0	20.50	20.44
		44	5220	MCSU	20.50	20.46
		48	5240		20.50	20.47
5.15-5.25 GHz		36	5180		18.50	18.47
0.10-0.20 0112	802.11ax20-HE0	40	5200	MCS0	20.50	20.41
	002.11ax20-11L0	44	5220	IVICOU	20.50	20.48
		48	5240		20.50	20.43
	802.11n40-HT0	38	5190	MCS0	18.00	18.00
	802.111140-1110	46	5230	MCSU	19.50	19.50
	802.11ac40-VHT0	38	5190	MCS0	18.00	17.98
	002.11ac40-V1110	46	5230	IVICOU	19.50	19.49
	802.11ax40-HE0	38	5190	MCS0	18.00	17.93
	002.11ax+0-11L0	46	5230	IVICOU	19.50	19.49
	802.11ac80-VHT0	42	5210	MCS0	18.00	17.92
	802.11ax80-HE0	42	5210	MCS0	18.00	18.00
	802.11ac160-VHT0	50	5250	MCS0	14.75	14.71
	802.11ax160-HE0	50	5250	MCS0	14.75	14.68

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 26 of 89

		Tx1 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		52	5260		20.50	20.47
	902.116	56	5280	GMbpa	20.00	19.92
	802.11a	60	5300	6Mbps	20.00	19.96
		64	5320		17.25	17.23
		52	5260		20.50	20.45
	802.11n20-HT0	56	5280	MOCO	20.00	19.94
		60	5300	MCS0	20.00	19.91
		64	5320		17.25	17.23
	802.11ac20-VHT0	52	5260	MCS0	20.50	20.49
		56	5280		20.00	20.00
		60	5300		20.00	19.97
5.25-5.35 GHz		64	5320		17.25	17.25
0.23-3.33 GHZ		52	5260		20.50	20.48
	802.11ax20-HE0	56	5280	MCS0	20.00	19.94
	602.11ax20-HE0	60	5300	IVICOU	20.00	19.94
		64	5320		17.25	17.16
	802.11n40-HT0	54	5270	MCS0	20.00	19.91
	002.1111 4 0-Π10	62	5310	IVICSU	16.50	16.44
	802.11ac40-VHT0	54	5270	MCS0	20.00	19.95
	002.11ac40-VH10	62	5310	MCSU	16.50	16.42
	802.11ax40-HE0	54	5270	MCS0	20.00	19.97
	002.11ax40-11E0	62	5310	IVICOU	16.50	16.43
	802.11ac80-VHT0	58	5290	MCS0	17.50	17.47
	802.11ax80-HE0	58	5290	MCS0	17.50	17.50

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 27 of 89

		Tx1 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		100	5500		17.75	17.66
		104	5520		20.50	20.41
		116	5580		20.50	20.42
	802.11a	120	5600	6Mbps	20.50	20.46
		136	5680		20.50	20.41
		140	5700		17.75	17.70
		144	5720		20.50	20.44
		100	5500		17.75	17.70
		104	5520		20.50	20.43
		116	5580		20.50	20.41
	802.11n20-HT0	120	5600	MCS0	20.50	20.45
		136	5680		20.50	20.46
		140	5700		17.75	17.75
5600 MHz		144	5720		20.50	20.44
3000 1011 12		100	5500		17.75	17.68
		104	5520		20.50	20.49
		116	5580		20.50	20.48
	802.11ac20-VHT0	120	5600	MCS0	20.50	20.42
		136	5680		20.50	20.50
		140	5700		17.75	17.73
		144	5720		20.50	20.46
		100	5500		17.75	17.73
		104	5520		20.50	20.45
		116	5580		20.50	20.45
	802.11ax20-HE0	120	5600	MCS0	20.50	20.48
		136	5680		20.50	20.47
		140	5700		17.75	17.75
		144	5720		20.50	20.50

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 28 of 89

		Tx1 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		102	5510		17.75	17.70
		110	5550		20.50	20.41
	802.11n40-HT0	118	5590	MCS0	20.50	20.50
		134	5670		19.00	18.92
		142	5710		20.50	20.42
	802.11ac40-VHT0	102	5510		17.75	17.67
		110	5550		20.50	20.49
		118	5590	MCS0	20.50	20.44
		134	5670		19.00	18.96
		142	5710		20.50	20.50
		102	5510		17.75	17.75
5600 MHz		110	5550		20.50	20.41
	802.11ax40-HE0	118	5590	MCS0	20.50	20.47
		134	5670		19.00	18.91
		142	5710		20.50	20.45
		106	5530		17.75	17.62
	802.11ac80-VHT0	122	5610	MCS0	19.50	19.48
		138	5690		20.50	20.42
		106	5530		17.75	17.65
	802.11ax80-HE0	122	5610	MCS0	19.50	19.38
		138	5690		20.50	20.39
	802.11ac160-VHT0	114	5570	MCS0	14.50	14.50
	802.11ax160-HE0	114	5570	MCS0	14.50	14.49

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 29 of 89

		Tx1 a	antenna			
		1	antonna –			
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		149	5745		20.50	20.50
	802.11a	157	5785	6Mbps	20.50	20.44
		165	5825		20.50	20.49
	802.11n20-HT0	149	5745		20.50	20.45
		157	5785	MCS0	20.50	20.46
		165	5825		20.50	20.48
	802.11ac20-VHT0	149	5745	MCS0	20.50	20.44
		157	5785		20.50	20.41
		165	5825		20.50	20.43
5800 MHz		149	5745		20.50	20.41
3600 1011 12	802.11ax20-HE0	157	5785	MCS0	20.50	20.43
		165	5825		20.50	20.49
	802.11n40-HT0	151	5755	MCS0	20.50	20.47
	002.111140-1110	159	5795	IVICOU	20.50	20.49
	802.11ac40-VHT0	151	5755	MCS0	20.50	20.50
	002.11ac40-VH10	159	5795	IVICOU	20.50	20.43
	802.11ax40-HE0	151	5755	MCS0	20.50	20.45
	002.11ax40-11L0	159	5795	IVICOU	20.50	20.45
	802.11ac80-VHT0	155	5775	MCS0	19.00	18.99
	802.11ax80-HE0	155	5775	MCS0	19.00	18.93

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 30 of 89

		Tx2	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		1	2412		19.50	19.46
		2	2417		20.50	20.49
		6	2437	1	20.50	20.46
	802.11b	10	2457	1Mbps	20.50	20.44
		11	2462		19.50	19.47
		12	2467		18.50	18.47
		13	2472		18.50	18.48
		1	2412		16.75	16.67
	802.11g	2	2417	6Mbps	18.50	18.44
		6	2437		19.75	19.72
		10	2457		18.75	18.72
		11	2462		16.50	16.42
		12	2467		15.00	14.97
2450 MHz		13	2472		12.00	11.96
2450 MITZ		1	2412		16.75	16.66
		2	2417		18.50	18.44
		6	2437		19.75	19.73
	802.11n20-HT0	10	2457	MCS0	18.75	18.73
		11	2462		16.50	16.42
		12	2467		15.00	14.97
		13	2472		12.00	11.95
		1	2412		16.75	16.72
		2	2417		18.50	18.43
		6	2437		19.75	19.68
	802.11ax20-HE0	10	2457	MCS0	18.75	18.66
		11	2462		16.50	16.43
		12	2467		15.00	15.00
		13	2472		12.00	11.95

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 31 of 89

Tx2 antenna								
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)		
		3	2422		16.50	16.48		
	802.11n40-HT0	4	2427	MCS0	17.50	17.42		
		6	2437		17.50	17.50		
		8	2447		16.25	16.21		
		9	2452		16.25	16.18		
		10	2457		12.00	11.95		
2450 MHz		11	2462		12.50	12.43		
2430 1011 12		3	2422		16.50	16.45		
		4	2427		17.50	17.48		
		6	2437		17.50	17.47		
	802.11ax40-HE0	8	2447	MCS0	16.25	16.21		
		9	2452		16.25	16.17		
		10	2457		12.00	11.94		
		11	2462		12.50	12.47		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 32 of 89

		Tx2 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		36	5180		18.50	18.41
	902 110	40	5200	6Mbpa	20.50	20.48
	802.11a	44	5220	6Mbps	20.50	20.45
		48	5240		20.50	20.43
	802.11n20-HT0	36	5180		18.50	18.46
		40	5200	MCS0	20.50	20.49
		44	5220	IVICSU	20.50	20.46
		48	5240		20.50	20.47
		36	5180		18.50	18.45
	802.11ac20-VHT0	40	5200	MCS0	20.50	20.45
	602.11ac20-VH10	44	5220	IVICSU	20.50	20.46
		48	5240		20.50	20.44
5.15-5.25 GHz		36	5180		18.50	18.44
0.10-0.20 0112	802.11ax20-HE0	40	5200	MCS0	20.50	20.50
	002.11ax20-11L0	44	5220	IVICOU	20.50	20.46
		48	5240		20.50	20.48
	802.11n40-HT0	38	5190	MCS0	18.00	17.97
	002.111140-1110	46	5230	IVICOU	20.50	20.43
	802.11ac40-VHT0	38	5190	MCS0	18.00	17.91
	002.11a0+0-V1110	46	5230	IVICOU	20.50	20.50
	802.11ax40-HE0	38	5190	MCS0	18.00	18.00
		46	5230		20.50	20.47
	802.11ac80-VHT0	42	5210	MCS0	18.50	18.42
	802.11ax80-HE0	42	5210	MCS0	18.50	18.41
	802.11ac160-VHT0	50	5250	MCS0	15.00	14.95
	802.11ax160-HE0	50	5250	MCS0	15.00	15.00

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 33 of 89

		Tx2 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		52	5260		20.50	20.46
	902.116	56	5280	GMbpa	20.00	19.96
	802.11a	60	5300	6Mbps	20.00	19.99
		64	5320		17.25	17.15
		52	5260		20.50	20.44
	802.11n20-HT0	56	5280	MOCO	20.00	19.95
		60	5300	MCS0	20.00	19.95
		64	5320		17.25	17.22
	802.11ac20-VHT0	52	5260	MCS0	20.50	20.44
		56	5280		20.00	19.92
		60	5300		20.00	19.94
5.25-5.35 GHz		64	5320		17.25	17.25
0.23-3.33 GHZ		52	5260		20.50	20.48
	802.11ax20-HE0	56	5280	MCS0	20.00	20.00
	602.11ax20-HE0	60	5300	IVICOU	20.00	19.93
		64	5320		17.25	17.24
	802.11n40-HT0	54	5270	MCS0	20.25	20.19
	002.1111 4 0-Π10	62	5310	IVICSU	16.50	16.49
	802.11ac40-VHT0	54	5270	MCS0	20.25	20.24
	002.11ac40-VH10	62	5310	MCSU	16.50	16.45
	802.11ax40-HE0	54	5270	MCS0	20.25	20.23
	002.11ax40-11E0	62	5310	IVICOU	16.50	16.48
	802.11ac80-VHT0	58	5290	MCS0	17.25	17.23
	802.11ax80-HE0	58	5290	MCS0	17.25	17.23

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 34 of 89

		Tx2 a	antenna			
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
		100	5500		17.50	17.48
		104	5520		20.50	20.45
		116	5580		20.50	20.42
	802.11a	120	5600	6Mbps	20.50	20.42
		136	5680		20.50	20.43
		140	5700		17.75	17.67
		144	5720		20.50	20.49
		100	5500		17.50	17.44
		104	5520		20.50	20.49
		116	5580		20.50	20.41
	802.11n20-HT0	120	5600	MCS0	20.50	20.41
		136	5680		20.50	20.42
		140	5700		17.75	17.74
5600 MHz		144	5720		20.50	20.48
3000 WII 12		100	5500		17.50	17.49
		104	5520		20.50	20.41
		116	5580		20.50	20.48
	802.11ac20-VHT0	120	5600	MCS0	20.50	20.46
		136	5680		20.50	20.45
		140	5700		17.75	17.72
		144	5720		20.50	20.43
		100	5500		17.50	17.50
		104	5520		20.50	20.42
		116	5580		20.50	20.42
	802.11ax20-HE0	120	5600	MCS0	20.50	20.48
		136	5680		20.50	20.41
		140	5700		17.75	17.68
		144	5720		20.50	20.45

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 35 of 89

Tx2 antenna									
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)			
5600 MHz	802.11n40-HT0	102	5510	MCS0	17.50	17.48			
		110	5550		20.50	20.50			
		118	5590		20.50	20.43			
		134	5670		19.00	18.97			
		142	5710		20.50	20.43			
	802.11ac40-VHT0	102	5510	MCS0	17.50	17.50			
		110	5550		20.50	20.46			
		118	5590		20.50	20.41			
		134	5670		19.00	18.95			
		142	5710		20.50	20.41			
	802.11ax40-HE0	102	5510	MCS0	17.50	17.46			
		110	5550		20.50	20.42			
		118	5590		20.50	20.43			
		134	5670		19.00	18.91			
		142	5710		20.50	20.47			
	802.11ac80-VHT0	106	5530	MCS0	17.75	17.65			
		122	5610		19.50	19.44			
		138	5690		20.50	20.42			
	802.11ax80-HE0	106	5530	MCS0	17.75	17.72			
		122	5610		19.50	19.47			
		138	5690		20.50	20.40			
	802.11ac160-VHT0	114	5570	MCS0	14.50	14.44			
	802.11ax160-HE0	114	5570	MCS0	14.50	14.43			

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 36 of 89

Tx2 antenna										
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)				
5800 MHz	802.11a	149	5745	6Mbps	20.50	20.41				
		157	5785		20.50	20.41				
		165	5825		20.50	20.47				
	802.11n20-HT0	149	5745	MCS0	20.50	20.44				
		157	5785		20.50	20.45				
		165	5825		20.50	20.44				
	802.11ac20-VHT0	149	5745	MCS0	20.50	20.45				
		157	5785		20.50	20.50				
		165	5825		20.50	20.41				
	802.11ax20-HE0	149	5745	MCS0	20.50	20.44				
		157	5785		20.50	20.46				
		165	5825		20.50	20.45				
	802.11n40-HT0	151	5755	MCS0	20.50	20.48				
		159	5795		20.50	20.47				
	802.11ac40-VHT0	151	5755	MCS0	20.50	20.46				
		159	5795		20.50	20.45				
	802.11ax40-HE0	151	5755	MCS0	20.50	20.45				
		159	5795		20.50	20.43				
	802.11ac80-VHT0	155	5775	MCS0	19.00	18.93				
	802.11ax80-HE0	155	5775	MCS0	19.00	18.94				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 37 of 89

Bluetooth conducted power table:

Diactoot		otoa pot	o. tabio.					
			1M	bps	2MI	ops	ЗМІ	bps
Mode	Channel	Frequency (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
	CH 00	2402		8.92		5.96		5.96
BR/EDR	CH 39	2441	10.80	9.77	7.00	6.11	7.00	6.12
	CH 78	2480		10.13		6.45		6.46

Mada	01	Frequency	GFS	SK
моде	Mode Channel		Max. Rated Avg.Power + Max. Tolerance (dBm)	Average Output Power (dBm)
	CH 37	2402		5.98
Bluetooth 4.0_1M	CH 17	2440	7	5.94
	CH 39	2480		6.43

Mada	Mode Channel		GFS	SK
Mode	Channel	(MHz)	Max. Rated Avg.Power + Max. Tolerance (dBm)	Average Output Power (dBm)
	CH 37	2402		5.43
Bluetooth 4.0_2M	CH 17	2440	7	5.33
	CH 39	2480		6.11

Mode	Channal	Frequency	GF	SK
Mode	Channel	(MHz)	Max. Rated Avg.Power + Max. Tolerance (dBm)	Average Output Power (dBm)
	CH 37	2402		5.94
Bluetooth 5.0_S8	CH 17	2440	7	5.99
	CH 39	2480		6.12

Mada	Channal	Frequency	GF	SK
Mode	Channel	(MHz)	Max. Rated Avg.Power + Max. Tolerance (dBm)	Average Output Power (dBm)
	CH 37	2402		5.92
Bluetooth 5.0_S2	CH 17	2440	7	5.87
	CH 39	2480		5.98

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 38 of 89

1.4 Test Environment

Ambient Temperature: 22±2° C Tissue Simulating Liquid: 22±2° C

1.5 Operation Description

Use chipset specific software to control the EUT, and makes it transmit in maximum power. Measurements are performed respectively on the lowest, middle and highest channels of the operating band(s). The EUT is set to maximum power level during all tests, and at the beginning of each test the battery is fully charged.

The device is a convertible laptop computer with RF feature. The device will adjust the maximum output power for different user scenario and EUT was tested as below based on FCC guidance.

Tablet mode

Back/edges_0mm with reduced power.

Laptop mode

SAR measurement for this mode is not required because the separation distance between antennas and user will be larger than 20cm.

Note:

802.11b DSSS SAR Test Requirements:

- 1. SAR is measured for 2.4 GHz 802.11b DSSS mode using the highest measured maximum output power channel, when the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2. When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

802.11g/n OFDM SAR Test Exclusion Requirements:

3. SAR is not required for 802.11g/n since the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Initial Test Configuration:

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,併報生结果僅對測試之樣具色書,同時什樣具僅保留的主。大報生主經太公司書面許可,不可無份複制。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

www.tw.sas.com



Page: 39 of 89

- 4. An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band.
- 5. SAR is measured using the highest measured maximum output power channel. When the reported SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
- 6. Since the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for subsequent test configuration.
- 7. BT and WLAN Tx2 use the same antenna path, but they can't transmit at the same time.
- 8. According to KDB447498 D01, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is ≤ 0.8 W/kg, when the transmission band is \leq 100 MHz.
- 9. According to KDB865664 D01, SAR measurement variability must be assessed for each frequency band. When the original highest measured SAR is ≥ 0.8 W/kg, repeated that measurement once. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~10% from the 1-g SAR limit)
- 10. Based on FCC guidance, general principles of KDB248227D01 can be applied to 802.11ax to determine initial test configuration with 802.11ax being considered as the highest 802.11 mode for the appropriate frequency band.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms-e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

> t (886-2) 2299-3279 f (886-2) 2298-0488 www.tw.sas.com



Page: 40 of 89

1.6 Operating modes validation by power measurement

The device is a convertible laptop computer with predefined single fixed power to each device modes.

For the operating modes validation, the measured conducted output power is monitored qualitatively to identify the triggering characteristics and recorded quantitatively.

90.0		
DUT operating mode	Lid Angle description	WLAN TX state
Lid Close	0° ≤ Lid angle <35 °	No TX Transmission
Laptop	35° ≤ Lid angle < 130°	Full Power Level
Non-Notebook mode (Tent/Tablet mode)	130° ≤ Lid angle ≤ 360°	Reduced Power Level
Non-Notebook mode (Book mode)	35° ≤ Lid angle < 200°	Reduced Power Level
Stand mode	200° ≤ Lid angle < 340°	Full Power Level

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 41 of 89

1.6.1 Results and conclusion

Based on 2019-11 TCB workshop guidance, the measured output power versus lid angle is tabulated in the following table, and the triggering verification complies with the device mode / power level declared by the manufacturer.

Operating mode validation by power measurement

Tx1 Antenna

Antenna	Operation mode	Lid angle	802.11b	802.11 a 5.2G	802.11 a 5.3G	802.11 a 5.6G	802.11 a 5.80
		0°	n/a	n/a	n/a	n/a	n/a
	I id alaaa	10°	n/a	n/a	n/a	n/a	n/a
	Lid close	20°	n/a	n/a	n/a	n/a	n/a
		30°	n/a	n/a	n/a	n/a	n/a
	Lautan	40°	20.35	20.35	20.34	20.39	20.44
	Laptop	35°	20.39	20.47	20.50	20.32	20.32
		30°	n/a	n/a	n/a	n/a	n/a
		31°	n/a	n/a	n/a	n/a	n/a
	Lid close	32°	n/a	n/a	n/a	n/a	n/a
		33°	n/a	n/a	n/a	n/a	n/a
	T T	34°	n/a	n/a	n/a	n/a	n/a
		35°	20.34	20.47	20.44	20.50	20.41
	-	36°	20.38	20.43	20.35	20.38	20.35
	-	37°	20.49	20.31	20.37	20.43	20.33
		38°	20.41	20.32	20.45	20.36	20.42
	-	39°	20.31	20.47	20.40	20.38	20.37
		40°	20.43	20.40	20.34	20.32	20.33
		50°	20.49	20.42	20.34	20.43	20.50
	Laptop	60°	20.36	20.42	20.34	20.43	20.42
		70°	20.49	20.47	20.34	20.49	20.42
		80°	20.49	20.44	20.32	20.35	20.36
	-						
	_	90° 100°	20.50 20.47	20.38	20.36 20.42	20.36 20.50	20.32
	_	110°	20.47	20.31	20.42	20.39	20.31
			20.33	20.47			
	T-11-1	120°			20.31	20.42	20.31
	Tablet	130°	18.96	15.81	15.91	15.99	15.98
		125°	20.39	20.35	20.31	20.43	20.36
		126°	20.47	20.43	20.46	20.43	20.40
	Laptop	127°	20.31	20.45	20.38	20.32	20.43
Tx1		128°	20.31	20.50	20.37	20.32	20.48
		129°	20.32	20.41	20.48	20.39	20.44
		130°	18.88	15.93	15.96	15.88	15.94
		131°	18.83	15.99	15.94	15.85	15.95
		132°	18.97	15.92	15.85	15.86	15.95
		133°	18.85	15.98	15.84	16.00	15.81
		134°	18.88	15.96	15.84	15.82	15.97
		135°	18.89	15.81	15.83	15.85	15.97
		145°	18.96	15.91	15.83	15.87	15.85
		155°	18.97	15.87	15.98	15.91	15.82
	Ī	165°	18.85	15.94	15.83	15.90	15.97
	Ī	175°	18.83	15.83	15.85	15.81	15.87
	ſ	185°	18.81	15.99	15.87	15.95	15.95
		195°	18.85	15.97	15.92	16.00	15.95
		205°	18.88	15.99	15.90	15.93	15.91
		215°	18.95	15.99	15.89	15.98	15.96
	Tablet	225°	18.96	15.81	15.94	15.86	15.82
		235°	18.87	15.90	15.93	15.86	15.87
		245°	18.93	15.82	16.00	15.82	15.83
		255°	18.85	16.00	15.84	15.85	15.87
		265°	18.87	15.96	15.88	16.00	15.99
		275°	18.96	15.98	15.89	15.97	15.83
	ļ	285°	18.86	15.95	15.93	15.99	15.98
		295°	18.89	15.99	15.85	15.97	16.00
		305°	18.83	15.89	15.91	15.89	15.95
		315°	18.83	15.87	15.90	15.91	15.98
		325°	18.94	15.85	15.97	15.87	15.85
		335°	18.89	15.82	15.90	15.98	15.86
		345°	18.90	15.84	15.93	15.83	15.96
		355°	18.91	15.95	15.93	15.93	15.85

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號 www.tw.sas.com



Page: 42 of 89

Antenna	Operation mode	Lid angle	802.11b	802.11 a 5.2G	802.11 a 5.3G	802.11 a 5.6G	802.11 a 5.8G
	.,	350°	18.86	15.89	15.87	15.90	15.95
		340°	19.00	15.97	15.94	15.90	15.98
		330°	18.99	15.98	15.99	15.86	15.96
		320°	18.89	15.91	15.87	15.88	15.99
		310°	18.85	15.86	15.83	15.89	15.89
		300°	18.93	15.97	15.86	15.84	15.84
	l l	290°	18.92	15.96	15.97	15.85	15.81
		280°	18.83	15.87	15.89	15.93	15.86
		270°	18.84	15.99	15.89	15.98	15.94
		260°	18.88	15.82	15.84	15.99	15.84
		250°	18.94	15.83	15.90	15.97	15.94
	Tablet	240°	18.99	15.98	16.00	15.92	15.96
		230°	18.99	15.82	15.96	15.85	15.84
		220°	18.93	15.89	15.96	15.88	15.94
	1	210°	18.90	15.98	15.81	15.86	15.81
		200°	18.82	15.91	15.93	15.93	15.88
		190°	18.85	15.90	15.97	15.85	15.94
		180°	18.86	15.83	15.93	15.92	15.90
		170°	18.85	15.98	15.89	15.96	15.97
		160°	18.81	15.93	15.85	15.94	15.97
		150°	18.81	15.94	15.89	16.00	15.94
		140°	18.87	15.89	15.84	16.00	15.97
		130°	18.89	15.85	15.98	15.93	15.87
		120°	20.48	20.46	20.41	20.32	20.40
	Laptop	125°	20.49	20.31	20.34	20.36	20.38
	T-1-1-1						
Tx1	Tablet	130°	18.94	15.81	15.85	15.99	16.00
		129°	20.41	20.35	20.46	20.49	20.38
		128°	20.50	20.31	20.35	20.36	20.48
		127°	20.38	20.37	20.31	20.33	20.43
		126°	20.38	20.42	20.44	20.47	20.38
		125°	20.33	20.48	20.50	20.44	20.47
		115°	20.39	20.46	20.48	20.47	20.50
	Lanton	105°	20.36	20.38	20.47	20.45	20.46
	Laptop	95°	20.40	20.49	20.49	20.39	20.47
		85°	20.34	20.36	20.42	20.40	20.40
		75°	20.34	20.31	20.36	20.50	20.38
		65°	20.37	20.43	20.50	20.45	20.44
		55°	20.42	20.31	20.39	20.35	20.36
		45°	20.42	20.39	20.35	20.32	20.50
	H	35°	20.31	20.33	20.40	20.48	20.41
	 	25°	n/a	n/a	n/a	n/a	n/a
	Lid close	30°	n/a	n/a	n/a	n/a	n/a
	Lonton		20.40	20.31	20.36	20.36	1/a 20.44
	Laptop	35° 34°					
			n/a	n/a	n/a	n/a	n/a
		33°	n/a	n/a	n/a	n/a	n/a
		32°	n/a	n/a	n/a	n/a	n/a
	Lid close	31°	n/a	n/a	n/a	n/a	n/a
		30°	n/a	n/a	n/a	n/a	n/a
		20°	n/a	n/a	n/a	n/a	n/a
		10°	n/a	n/a	n/a	n/a	n/a
		0°	n/a	n/a	n/a	n/a	n/a

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 43 of 89

Antenna	Operation mode	Lid angle	802.11b	802.11 a 5.2G	802.11 a 5.3G	802.11 a 5.6G	802.11 a 5.8G
		200°	20.37	20.39	20.33	20.41	20.36
	-	210°	20.46	20.42	20.45	20.34	20.32
		220°	20.44	20.42	20.34	20.43	20.46
	•	230°	20.38	20.32	20.44	20.50	20.43
	•	240°	20.31	20.44	20.40	20.48	20.37
	•	250°	20.32	20.42	20.47	20.31	20.31
	Stand mode (Full power)	260°	20.31	20.31	20.47	20.38	20.35
		270°	20.37	20.31	20.31	20.39	20.41
	(- 1)	280°	20.32	20.33	20.32	20.36	20.32
	-	290°	20.39	20.47	20.32	20.34	20.43
	-	300°	20.41	20.36	20.45	20.36	20.32
	-	310°	20.42	20.48	20.46	20.48	20.50
	-	320°	20.42	20.46	20.40	20.46	20.38
	-	330°	20.48	20.32	20.44	20.33	20.35
	Tablet	340°	18.91	15.98	15.94	15.96	15.99
		335°	20.44	20.38	20.50	20.31	20.39
	Stand mode	336°	20.35	20.47	20.45	20.34	20.34
	(Full power)	337°	20.49	20.48	20.38	20.46	20.38
	(· = p =)	338°	20.39	20.41	20.40	20.42	20.31
		339°	20.49	20.38	20.49	20.48	20.41
		340°	18.98	15.97	16.00	15.91	15.91
		341°	18.85	15.91	15.97	15.98	15.86
		342°	18.84	15.99	15.97	15.95	15.98
	Tablet	343°	18.83	15.83	15.87	15.97	15.89
	Tablet	344°	18.97	15.94	15.84	15.95	15.88
Tx1		345°	18.90	15.83	15.97	15.84	15.97
12.1		355°	18.81	15.81	15.92	15.94	15.92
		360°	18.84	15.87	15.99	15.87	15.81
	Tablet	350°	18.93	15.98	15.89	15.85	15.87
	Tablet	340°	18.90	15.89	15.81	15.94	15.89
	Stand mode	330°	20.48	20.38	20.49	20.45	20.50
	(Full power)	335°	20.41	20.46	20.38	20.37	20.40
	Tablet	340°	19.00	15.93	15.83	15.83	15.90
		339°	20.35	20.38	20.48	20.42	20.41
		338°	20.33	20.33	20.38	20.41	20.41
	•	337°	20.49	20.37	20.36	20.48	20.41
		336°	20.50	20.49	20.35	20.38	20.37
		335°	20.50	20.41	20.37	20.37	20.38
		325°	20.31	20.32	20.49	20.35	20.44
	-	315°	20.35	20.46	20.38	20.31	20.47
	ŀ	305°	20.46	20.41	20.41	20.34	20.38
	•	295°	20.38	20.37	20.46	20.39	20.50
	Stand mode	285°	20.42	20.39	20.49	20.49	20.39
	(Full power)	275°	20.44	20.47	20.45	20.42	20.34
	-	265°	20.44	20.47	20.45	20.42	20.34
		255°	20.39	20.32	20.50	20.42	20.38
		245°	20.38	20.38	20.48	20.47	20.46
		235°	20.38	20.42	20.44	20.38	20.49
		225°	20.42	20.31	20.32	20.36	20.42
		215°	20.45	20.48	20.46	20.41	20.39
		205°	20.38	20.43	20.45	20.33	20.33
		200°	20.43	20.34	20.50	20.48	20.36

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 44 of 89

Antenna	Operation mode	Lid angle	802.11b	802.11 a 5.2G	802.11 a 5.3G	802.11 a 5.6G	802.11 a 5.80
		0°	n/a	n/a	n/a	n/a	n/a
	l id alaaa	10°	n/a	n/a	n/a	n/a	n/a
	Lid close	20°	n/a	n/a	n/a	n/a	n/a
		30°	n/a	n/a	n/a	n/a	n/a
	Book mode	40°	18.84	15.83	15.95	15.82	15.98
	(Reduced power)	35°	18.85	15.90	15.98	15.83	15.98
		30°	n/a	n/a	n/a	n/a	n/a
		31°	n/a	n/a	n/a	n/a	n/a
	Lid close	32°	n/a	n/a	n/a	n/a	n/a
		33°	n/a	n/a	n/a	n/a	n/a
	-	34°	n/a	n/a	n/a	n/a	n/a
		35°	18.91	15.96	15.97	15.95	15.94
	 	36°	18.81	15.81	15.83	15.89	15.97
		37°	18.89	15.93	15.98	15.91	15.86
		38°	18.98	15.85	15.93	16.00	15.84
		39°	18.91	15.92	16.00	15.85	15.82
		40°	18.81	15.90	15.81	15.92	15.99
		50°	18.87	15.81	15.87	15.87	15.89
		60°	18.92	15.93	16.00	16.00	15.89
		70°	18.90	15.97	15.97	16.00	15.88
	-	80°	18.81	15.90	15.95	15.84	15.99
	Dools made	90°	18.97	16.00	15.83	15.89	15.92
	Book mode (Reduced power)	100°	18.84	15.90	15.94	15.85	15.95
	(Reduced power)	110°	18.89	15.96	15.90	15.82	15.94
		120°	18.89				
		130°	18.88	15.84 15.83	15.90 15.88	15.82 15.95	15.99 15.84
		140°	18.91	15.81	15.98	15.87	15.96
	<u> </u>						
	<u> </u>	150°	18.83	15.88	15.94	15.81	15.81
		160°	18.87	15.98	15.96	15.88	15.91
Tx1	<u> </u>	170°	18.83	15.99	15.93	15.96	15.98
		180°	18.99	15.94	15.81	15.99	15.99
		190°	18.97	15.85	15.99	15.90	15.87
		199°	18.96	16.00	15.93	15.86	15.87
		190°	18.88	16.00	15.82	15.95	15.97
		180°	18.94	15.92	15.93	15.88	15.93
		170°	18.94	15.89	15.91	15.93	15.97
		160°	18.94	15.91	15.89	15.87	16.00
		150°	18.90	15.93	16.00	15.90	15.88
		140°	18.84	15.85	15.81	15.97	15.97
		130°	18.81	15.97	15.93	15.95	15.89
	Book mode	120°	18.95	15.84	15.93	15.84	15.89
	(Reduced power)	110°	18.99	15.85	15.93	15.97	15.83
	Г	100°	19.00	15.83	15.95	15.83	15.97
	Ī	90°	18.95	15.92	15.93	15.81	15.84
	F	80°	18.98	15.86	15.87	15.87	15.98
	F	70°	18.81	15.92	15.89	15.95	15.87
	F	60°	18.87	15.82	15.88	15.89	15.91
	i F	50°	18.82	15.97	15.92	15.99	15.88
	i F	40°	18.87	15.86	15.84	15.86	15.96
	Lid close	30°	n/a	n/a	n/a	n/a	n/a
	Book mode						
	(Reduced power)	35°	18.84	15.93	15.87	15.81	15.85
	l L	34°	n/a	n/a	n/a	n/a	n/a
		33°	n/a	n/a	n/a	n/a	n/a
	Ī	32°	n/a	n/a	n/a	n/a	n/a
	Lid close	31°	n/a	n/a	n/a	n/a	n/a
	Liu ciose	30°	n/a	n/a	n/a	n/a	n/a
	F	20°	n/a	n/a	n/a	n/a	n/a
	i F	10°	n/a	n/a	n/a	n/a	n/a
	1	0°	n/a	n/a	n/a	n/a	n/a

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 45 of 89

Tx2 Antenna

Antenna	Operation mode	Lid angle	802.11b	802.11 a 5.2G	802.11 a 5.3G	802.11 a 5.6G	802.11 a 5.8G
		0°	n/a	n/a	n/a	n/a	n/a
	Lid close	10°	n/a	n/a	n/a	n/a	n/a
	2.0 0.000	20°	n/a	n/a	n/a	n/a	n/a
		30°	n/a	n/a	n/a	n/a	n/a
	Laptop	40°	20.31	20.50	20.43	20.44	20.31
	Laptop	35°	20.44	20.39	20.40	20.34	20.44
		30°	n/a	n/a	n/a	n/a	n/a
		31°	n/a	n/a	n/a	n/a	n/a
	Lid close	32°	n/a	n/a	n/a	n/a	n/a
		33°	n/a	n/a	n/a	n/a	n/a
		34°	n/a	n/a	n/a	n/a	n/a
		35°	20.46	20.42	20.40	20.50	20.40
		36°	20.39	20.35	20.33	20.34	20.33
		37°	20.46	20.38	20.37	20.38	20.37
		38°	20.49	20,47	20.33	20.37	20.32
		39°	20.31	20.32	20.35	20.48	20.34
		40°	20.34	20.42	20.46	20.33	20.40
	ŀ	50°	20.49	20.44	20.44	20.45	20.37
	Laptop	60°	20.48	20.46	20.39	20.45	20.42
	-	70°	20.41	20.39	20.49	20.48	20.36
	-	80°	20.44	20.48	20.35	20.38	20.36
		90°	20.33	20.50	20.46	20.39	20.50
		100°	20.47	20.40	20.40	20.39	20.37
		110°	20.46	20.46	20.38	20.46	20.47
		120°	20.49	20.50	20.45	20.45	20.38
	Tablet	130°	18.83	15.82	15.92	15.89	15.81
		125°	20.34	20.34	20.44	20.36	20.40
		126°	20.46	20.38	20.46	20.35	20.49
	Laptop	127°	20.43	20.35	20.50	20.36	20.38
Tx2		128°	20.45	20.45	20.47	20.38	20.33
1,7,2		129°	20.35	20.44	20.32	20.32	20.41
		130°	18.81	15.92	15.96	15.98	15.88
		131°	18.92	15.93	15.93	15.84	15.99
		132°	18.89	15.99	15.96	15.95	15.83
		133°	18.91	15.83	15.85	15.92	15.90
		134°	19.00	15.87	15.88	15.82	15.94
		135°	18.94	15.92	15.88	15.84	15.94
		145°	18.86	15.91	15.97	15.88	15.91
		155°	18.93	15.86	15.85	15.85	15.90
		165°	18.82	15.85	15.93	15.94	15.95
		175°	19.00	15.99	15.85	15.88	15.90
		185°	18.84	15.83	15.94	15.82	15.87
		195°	18.99	15.85	15.86	15.88	15.96
		205°	18.81	15.83	15.96	15.89	15.96
		215°	18.94	15.86	15.88	15.96	15.99
	Tablet	225°	18.85	15.99	15.98	15.92	15.81
		235°	18.93	15.86	15.91	15.92	15.93
	l l	245°	18.93	15.90	15.97	15.91	15.99
		255°	18.81	15.85	15.88	15.93	15.94
		265°	18.87	15.83	15.83	15.84	16.00
		275°	18.97	15.96	15.82	15.84	15.81
		285°	18.94	15.92	15.81	15.94	15.94
		295°	18.84	15.92	15.96	15.94	15.95
		305°		15.88		15.88	15.95
			18.85		15.85		
		315°	18.87	15.93	15.97	16.00	15.93
	1	325°	18.82	15.90	15.91	15.84	15.83
				15.81	15.96	15.91	15.89
		335°	18.97				
		345°	18.96	15.92	15.96	15.90	15.87

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 46 of 89

	Tablet	350° 340° 340° 330° 320° 310° 300° 290° 280° 270° 260° 250° 240° 230° 220° 210° 200° 190° 180°	18.86 19.00 18.99 18.85 19.00 18.92 18.95 18.98 18.83 18.82 18.83 18.82 18.83 18.93 18.93	15.85 15.93 15.90 15.87 15.91 15.96 15.92 15.90 15.99 16.00 15.89 15.94 15.89	15.87 15.81 15.96 15.92 15.94 15.92 15.91 15.98 15.90 15.95 15.93 15.87	15.84 15.89 15.88 15.85 15.83 15.84 15.85 15.86 16.00 16.00 15.97	15.90 15.97 15.90 15.92 15.89 15.82 15.90 15.83 15.97 15.86 15.99
	Tablet	330° 320° 310° 300° 290° 280° 270° 260° 250° 240° 230° 210° 20° 210° 20°	18.99 18.85 18.95 19.00 18.92 18.95 18.98 18.83 18.82 18.83 18.97 18.97	15.90 15.87 15.91 15.96 15.92 15.90 15.99 16.00 15.89 15.94	15.96 15.92 15.94 15.92 15.91 15.98 15.90 15.95 15.95 15.93	15.88 15.85 15.83 15.84 15.86 16.00 16.00 15.97	15.90 15.92 15.89 15.82 15.90 15.83 15.97 15.86 15.99
	Tablet	320° 310° 300° 290° 280° 270° 260° 250° 240° 230° 210° 200° 190°	18.85 18.95 19.00 18.92 18.95 18.98 18.83 18.82 18.83 18.82 18.83 18.97	15.87 15.91 15.96 15.92 15.90 15.99 16.00 15.89 15.94	15.92 15.94 15.92 15.91 15.98 15.90 15.95 15.93 15.87	15.85 15.83 15.84 15.85 15.86 16.00 16.00 15.97	15.92 15.89 15.82 15.90 15.83 15.97 15.86 15.99
	Tablet	310° 300° 290° 280° 270° 260° 250° 240° 230° 210° 200° 190°	18.95 19.00 18.92 18.95 18.98 18.83 18.82 18.83 18.93 18.97 18.92	15.91 15.96 15.92 15.90 15.99 16.00 15.89 15.94	15.94 15.92 15.91 15.98 15.90 15.95 15.93 15.87	15.83 15.84 15.85 15.86 16.00 16.00 15.97	15.89 15.82 15.90 15.83 15.97 15.86 15.99
	Tablet	300° 290° 280° 280° 270° 260° 250° 240° 230° 210° 210° 200° 190°	19.00 18.92 18.95 18.98 18.83 18.82 18.83 18.93 18.97 18.97	15.96 15.92 15.90 15.99 16.00 15.89 15.94	15.92 15.91 15.98 15.90 15.95 15.93 15.87	15.84 15.85 15.86 16.00 16.00 15.97	15.82 15.90 15.83 15.97 15.86 15.99
	Tablet	290° 280° 270° 260° 250° 240° 230° 240° 210° 200° 190°	18.92 18.95 18.98 18.83 18.82 18.83 18.93 18.97 18.97	15.92 15.90 15.99 16.00 15.89 15.94 15.89	15.91 15.98 15.90 15.95 15.93 15.87	15.85 15.86 16.00 16.00 15.97 15.83	15.83 15.87 15.86 15.99
	Tablet	280° 270° 260° 250° 240° 230° 210° 210° 200° 190°	18.95 18.98 18.83 18.82 18.83 18.93 18.97 18.97	15.90 15.99 16.00 15.89 15.94 15.89	15.98 15.90 15.95 15.93 15.87	15.86 16.00 16.00 15.97 15.83	15.83 15.97 15.86 15.99
	Tablet	270° 260° 250° 240° 230° 220° 210° 200° 190°	18.98 18.83 18.82 18.83 18.93 18.97 18.97	15.99 16.00 15.89 15.94 15.89	15.90 15.95 15.93 15.87	16.00 16.00 15.97 15.83	15.97 15.86 15.99
	Tablet	260° 250° 240° 230° 220° 210° 200° 190°	18.83 18.82 18.83 18.93 18.97 18.92	16.00 15.89 15.94 15.89	15.95 15.93 15.87	16.00 15.97 15.83	15.86 15.99
	Tablet	250° 240° 230° 220° 210° 200° 190°	18.82 18.83 18.93 18.97 18.92	15.89 15.94 15.89	15.93 15.87	15.97 15.83	15.99
	Tablet	240° 230° 220° 210° 200° 190°	18.83 18.93 18.97 18.92	15.94 15.89	15.87	15.83	
	Tablet	230° 220° 210° 200° 190°	18.93 18.97 18.92	15.89			15.83
		220° 210° 200° 190°	18.97 18.92		15 94		
		210° 200° 190°	18.92	16.00		15.95	15.86
		200° 190°			15.98	15.95	15.85
		190°	18 82	15.96	15.94	15.96	15.96
				15.92	15.93	15.83	15.98
		180°	18.82	15.82	15.84	16.00	15.82
	-		18.90	15.88	15.91	15.82	16.00
		170°	18.95	15.95	15.90	15.81	15.90
		160°	18.97	15.83	15.91	15.93	15.81
	<u> </u>	150°	18.81	15.82	15.83	15.92	15.97
		140°	19.00	15.89	15.93	15.92	15.97
		130°	18.96	15.83	15.99	15.92	15.94
	Laptop	120°	20.36	20.40	20.42	20.33	20.42
	Zaptop	125°	20.34	20.45	20.35	20.47	20.46
Tx2	Tablet	130°	18.97	15.83	15.84	15.90	15.83
		129°	20.33	20.42	20.45	20.49	20.44
		128°	20.50	20.48	20.43	20.35	20.45
		127°	20.35	20.45	20.39	20.33	20.46
		126°	20.46	20.49	20.33	20.49	20.33
		125°	20.33	20.49	20.32	20.45	20.34
		115°	20.37	20.38	20.48	20.48	20.44
		105°	20,45	20.39	20.39	20.33	20.49
	Laptop	95°	20.40	20.43	20.47	20.43	20.33
	_	85°	20.37	20.33	20.33	20.41	20.47
	-	75°	20.39	20.37	20.45	20.38	20.42
	-	65°	20.32	20.32	20.36	20.36	20.42
	-	55°	20.33	20.43	20.34	20.43	20.37
	_	45°	20.50	20.42	20.34	20.50	20.44
	<u> </u>	35°	20.31	20.47	20.34	20.40	20.39
<u> </u>		25°	n/a	n/a	n/a	n/a	20.39 n/a
	Lid close	30°	n/a	n/a	n/a	n/a	n/a
<u> </u>	Lonton	35°			20.47	20.46	20.44
<u> </u>	Laptop	34°	20.33 n/a	20.37 n/a	20.47 n/a	20.46 n/a	20.44 n/a
	<u> </u>	33°	n/a	n/a	n/a	n/a	n/a
	<u> </u>	32°	n/a	n/a	n/a		n/a
	-	32°			n/a n/a	n/a	n/a n/a
	Lid close	30°	n/a n/a	n/a n/a	n/a	n/a n/a	n/a
	-	20°	n/a	n/a	n/a	n/a	n/a
	-	10°	n/a	n/a	n/a	n/a	n/a
		0°	n/a	IVa	II/a		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號 SGS Taiwan Ltd. t (886-2) 2299-3279 f (886-2) 2298-0488



Page: 47 of 89

Antenna	Operation mode	Lid angle	802.11b	802.11 a 5.2G	802.11 a 5.3G	802.11 a 5.6G	
		200°	20.35	20.36	20.37	20.48	802.11 a 5.80 20.50 20.34 20.48 20.50 20.35 20.45 20.48 20.48 20.43 20.36 20.46 20.47 20.40 20.46 20.40 20.46 20.40 20.46 20.40 20.46 20.40 20.46 20.40 20.30 20.30 20.41 20.47 20.37 20.41 20.47 20.37 20.41 20.47 20.38 20.40 20.39 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38
		210°	20.40	20.48	20.39	20.49	20.34
		220°	20.44	20.50	20.50	20.32	20.48
	l l	230°	20.49	20.39	20.41	20.47	20.50 20.34 20.48 20.48 20.50 20.35 20.45 20.48 20.43 20.36 20.46 20.37 20.42 20.50 20.48 20.48 20.37 20.42 20.50 20.48 20.48 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.46 20.37 20.41 20.47 20.35 20.31 20.37 20.41 20.47 20.35 20.41 20.47 20.35 20.41 20.47 20.36 20.40 20.39 20.40 20.39 20.47 20.37 20.41 20.47 20.37 20.41 20.47 20.38 20.40 20.39 20.47 20.37 20.41 20.47 20.37 20.41 20.47 20.38 20.40 20.39 20.47 20.37 20.41 20.45 20.38 20.40 20.39 20.47 20.37 20.41 20.47 20.37 20.41 20.47 20.37 20.41 20.47 20.37 20.41 20.47 20.38 20.40 20.39 20.47 20.37 20.38 20.41 20.45
	l l	240°	20.33	20,46	20.49	20.50	
		250°	20.45	20.42	20.34	20.42	
	Stand mode	260°	20.38	20.49	20.33	20.36	
	(Full power)	270°	20.39	20.43	20.39	20.38	
	(, , , , , ,	280°	20.50	20.34	20.38	20.32	
		290°	20.48	20.43	20.34	20.48	
		300°	20.44	20.49	20.34	20.43	
		310°	20.45	20.38	20.47	20.42	
		320°	20.45	20.42	20.47	20.42	
		330°		20.42		20.34	
	T		20.46		20.33		20.50 20.34 20.48 20.35 20.45 20.45 20.48 20.43 20.36 20.46 20.46 20.37 20.42 20.50 20.48 20.48 20.40 20.40 20.46 20.37 20.42 20.50 20.48 20.40 20.40 20.40 20.46 20.40 20.45 20.35
	Tablet	340°	18.81	15.82	16.00	15.89	
		335°	20.40	20.41	20.49	20.31	
	Stand mode	336°	20.39	20.33	20.38	20.44	
	(Full power)	337°	20.42	20.43	20.34	20.49	
	(· = p =)	338°	20.48	20.31	20.39	20.33	20.34 20.48 20.48 20.50 20.35 20.45 20.48 20.48 20.43 20.36 20.46 20.37 20.42 20.50 20.48 15.88 20.48 20.49 20.40 20.46 16.00 15.88 15.92 15.96 15.87 15.98 15.92 15.96 15.87 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.47 20.35 20.31 20.37 20.41 20.47 20.35 20.41 20.47 20.35 20.43 20.38 20.40 20.39 20.47 20.39 20.47 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.38 20.41 20.47 20.39 20.41 20.47 20.38 20.40 20.39 20.41 20.47 20.38 20.40 20.39 20.41 20.47 20.38 20.40 20.39 20.41 20.47 20.38 20.40 20.39 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.45 20.33 20.33 20.33 20.33
		339°	20.33	20.32	20.47	20.45	
		340°	18.89	15.96	15.86		
		341°	18.83	15.86	15.95	15.83 15.95 15.84 15.91 15.84 15.86	
		342°	18.95	15.88	15.84		20.50 20.34 20.48 20.48 20.50 20.35 20.45 20.48 20.43 20.36 20.46 20.37 20.42 20.50 20.48 20.48 20.37 20.42 20.50 20.48 20.49 20.40 20.40 20.46 16.00 15.88 15.92 15.96 15.87 15.98 15.95 15.99 15.84 15.83 20.45 20.35 20.45 20.35 20.40 20.36 20.37 20.41 20.47 20.35 20.43 20.37 20.41 20.47 20.35 20.43 20.39 20.47 20.37 20.38 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.47 20.37 20.38 20.41 20.45 20.33 20.33 20.33 20.33 20.33
	Tablet	343°	18.96	15.91	15.93		
	Tablet	344°	18.88	15.95	15.81	15.84	15.88 15.92 15.96 15.87 15.98 15.95 15.99
Tx2		345°	18.85	15.88	15.83	15.86	15.98
172		355°	18.82	15.84	15.92	15.81	
		360°	18.86	15.84	15.99	15.94	15.92 15.96 15.87 15.98 15.95 15.99 15.84 15.83 20.45 20.35
	Tablet	350°	18.82	15.94	15.94	15.84	15.84
	Tablet	340°	18.87	15.83	15.96	15.92	15.83
	Stand mode	330°	20.36	20.31	20.34	20.44	20.45
	(Full power)	335°	20.39	20.50	20.38	20.41	20.35
	Tablet	340°	18.92	15.84	15.94	15.84	15.93
		339°	20.50	20.31	20.37	20.50	20.31
		338°	20.39	20.39	20.45	20.34	20.37
		337°	20.49	20.48	20.32	20.39	20.41
		336°	20.41	20.38	20.36	20.45	
		335°	20.46	20.41	20.43	20.45	
		325°	20.45	20.50	20.43	20.37	
		315°	20.46	20.47	20.43	20.32	20.34 20.48 20.48 20.50 20.35 20.45 20.48 20.43 20.36 20.46 20.37 20.42 20.50 20.48 20.37 20.42 20.50 20.48 20.37 20.42 20.50 20.48 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.46 20.37 20.42 20.40 20.38 20.31 20.37 20.41 20.47 20.35 20.43 20.38 20.47 20.39 20.47 20.37 20.41 20.47 20.37 20.38 20.47 20.37 20.41 20.47 20.37 20.38 20.47 20.37 20.41 20.47 20.37 20.38 20.47 20.37 20.38 20.40 20.39 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.47 20.37 20.38 20.49 20.39 20.47 20.37 20.38 20.41 20.45 20.33 20.33 20.33 20.33 20.33 20.33
	l l	305°	20.44	20.37	20.42	20.40	
		295°	20.36	20.47	20.50	20.44	
	Stand mode	285°	20.45	20.39	20.49	20.39	
	(Full power)	275°	20.38	20.39	20.49	20.48	1
		265°	20.38	20.44	20.50	20.40	
		255°	20.38	20.44	20.37	20.36	
		245°	20.43	20.45	20.34	20.31	
		235°	20.41	20.50	20.48	20.48	
		225°	20.31	20.33	20.35	20.35	
		215°	20.41	20.46	20.45	20.49	
		205°	20.31	20.48	20.48	20.37	
		200°	20.49	20.43	20.41	20.40	20.45

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

f (886-2) 2298-0488

SGS Taiwan Ltd.



Page: 48 of 89

Antenna	Operation mode	Lid angle	802.11b	802.11 a 5.2G	802.11 a 5.3G	802.11 a 5.6G	802.11 a 5.8G
		0°	n/a	n/a	n/a	n/a	n/a
	Lid close	10°	n/a	n/a	n/a	n/a	n/a
	Lid close	20°	n/a	n/a	n/a	n/a	n/a
		30°	n/a	n/a	n/a	n/a	n/a
	Book mode	40°	18.87	15.91	15.98	15.82	15.81
	(Reduced power)	35°	18.89	15.82	15.92	15.89	
		30°	n/a	n/a	n/a	n/a	
		31°	n/a	n/a	n/a	n/a	n/a
	Lid close	32°	n/a	n/a	n/a	n/a	
	2.0 0.000	33°	n/a	n/a	n/a	n/a	
		34°	n/a	n/a	n/a	n/a	
		35°	18.94	15.82	15.89	15.90	
		36°	18.84	15.98	15.96	15.85	
		37°	18.92	15.92	15.92	15.98	
		38°	18.92	16.00	15.85	15.86	
		39°	18.91	15.90	15.97	15.81	
		40°	18.93	15.86	15.85	15.91	
	Ī	50°	18.87	15.98	15.88	15.82	15.82
	Ţ	60°	18.85	15.99	15.97	15.83	
		70°	18.93	15.98	15.82	15.97	15.88
	Ţ	80°	18.98	15.97	15.84	15.88	16.00
	Book mode	90°	18.84	15.94	15.93	15.91	15.85
	(Reduced power)	100°	18.81	15.94	15.82	16.00	15.90
	(110°	18.96	15.92	15.85	15.82	
		120°	18.94	15.94	15.90	15.94	
		130°	18.86	15.88	15.96	15.82	
	F	140°	18.85	15.83	15.99	15.84	
		150°		15.88	15.82	15.98	
			18.93				15.95 15.87 16.00 15.84 15.96 15.84 15.94 15.97 15.88 16.00 15.99 15.81
		160°	18.84	15.86	15.95	15.83	
Tx2		170°	19.00	15.94	15.87	15.94	
		180°	18.91	15.92	15.87	15.96	
		190°	18.94	15.97	15.90	15.89	15.97
		199°	18.90	15.96	15.99	15.89	n/a n/a 15.81 15.87 n/a
		190°	18.94	15.90	15.87	15.84	16.00
		180°	18.83	15.92	15.91	15.88	15.99
		170°	18.89	15.92	15.92	15.89	15.81
		160°	18.91	15.84	15.98	15.84	15.99
	1	150°	18.82	15.92	15.95	15.84	15.84
		140°	18.84	15.83	15.90	15.85	
		130°	18.96	15.86	15.83	15.93	
	Book mode	120°	18.95	15.91	15.99	15.85	
	(Reduced power)	110°	18.97	15.98	15.86	15.87	
	(iveranced bowel)	100°	18.94	16.00	15.99	15.83	
		90°	18.88	15.92	15.89	15.91	
		80°	18.83	15.97	15.82	15.97	
	<u> </u>	70°	18.86	15.93	15.83	15.81	
		60°	18.85	16.00	15.85	15.88	
		50°	18.87	16.00	15.99	15.88	
		40°	18.90	15.89	15.87	15.89	15.95
	Lid close	30°	n/a	n/a	n/a	n/a	n/a
	Book mode (Reduced power)	35°	18.93	15.90	15.93	15.85	15.84
	(Incadosa powel)	34°	n/a	n/a	n/a	n/a	n/a
		33°	n/a	n/a	n/a	n/a	
		32°	n/a	n/a	n/a	n/a	
	Lid close	31°	n/a	n/a	n/a	n/a	
		30°	n/a	n/a	n/a	n/a	
		20°	n/a	n/a	n/a	n/a	
	[10°	n/a	n/a	n/a	n/a	n/a
	ı	0°	n/a	n/a	n/a	n/a	n/a

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 49 of 89

1.7 The SAR Measurement System

A block diagram of the SAR measurement System is given in Fig. a. This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY 5 professional system). The model EX3DV4 field probe is used to determine the internal electric fields. The SAR can be obtained from the equation SAR= σ (|Ei|²)/ ρ where σ and ρ are the conductivity and mass density of the tissuesimulant.

The DASY 5 system for performing compliance tests consists of the following items:

- 1. A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
- 2. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage intissue simulating liquid. The probe is equipped with an optical surface detector system.
- 3. A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.




Fig. a The block diagram of SAR system

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms-e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

t (886-2) 2299-3279 f (886-2) 2298-0488 www.tw.sas.com



Page: 50 of 89

- 4. The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- 5. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- 6. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- 7. A computer operating Windows 7.
- 8. DASY 5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validate the proper functioning of the system.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 1 No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279



Page: 51 of 89

1.8 System Components

EX3DV4 E-Field Probe

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Basic Broad Band Calibration in air Conversion Factors (CF) for HSL 2450/5200/5300/5600/5800 MHz Additional CF for other liquids and frequencies upon request
Frequency	10 MHz to > 6 GHz
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic	$10 \mu\text{W/g}$ to > 100mW/g
Range	Linearity: ± 0.2 dB (noise: typically < 1 µW/g)
Dimensions	Tip diameter: 2.5 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision o better 30%.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 52 of 89

PHANTOM

FITANTOW	
Model	ELI
Construction	The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.
Shell	2 ± 0.2 mm
Thickness	
Filling Volume	Approx. 30 liters
Dimensions	Major axis: 600 mm
	Minor axis: 400 mm

DEVICE HOLDER

DEVICE HOLD	EK	
Construction	The device holder (Supporter) for Notebook is made by POM (polyoxymethylene resin), which is non-metal and non-conductive. The height can be adjusted to fit varies kind of notebooks.	E
		Device Holder

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 53 of 89

1.9 SAR System Verification

The microwave circuit arrangement for system verification is sketched in Fig. b. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within +/from the target SAR values. These tests were 2450/5200/5300/5600/5800 MHz. The tests were conducted on the same days as the measurement of the DUT. The obtained results from the system accuracy verification are displayed in the table 1 (SAR values are normalized to 1W forward power delivered to the dipole). During the tests, the liquid depth above the ear reference points was ≥ 15 cm ± 5 mm (frequency ≤ 3 GHz) or ≥ 10 cm ± 5 mm (frequency > 3 G Hz) in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.




Fig. b The block diagram of system verification

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,併報先結果做學訓練之樣是台書,同時什樣是僅保留的主。太報先去獨太公司書而許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 54 of 89

Validation Kit	S/N		(MHz) SA		V Target SAR-1g mW/g) pin=250mW Measured SAR-1g (mW/g) n		Deviation (%)	Measured Date
D2450V2	727	2450	Head	53	13.00	52	-1.89%	Nov, 26, 2019
Validation Kit	S/N	Frequency (MHz)		1W Target SAR-1g (mW/g)	Pin=100mW Measured SAR-1g (mW/g)	Measured SAR-1g normalized to 1W (mW/g)	Deviation (%)	Measured Date
		5200	Head	79.2	8.27	82.7	4.42%	Nov, 27, 2019
D5GHzV2	1023	5300	Head	82.6	8.15	81.5	-1.33%	Nov, 28, 2019
DOGHZVZ	1023	5600	Head	85.7	8.74	87.4	1.98%	Nov, 29, 2019
		5800	Head	80.4	7.72	77.2	-3.98%	Nov, 30, 2019

Table 1. Results of system validation

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 55 of 89

1.10 Tissue Simulant Fluid for the Frequency Band

The dielectric properties for this Head-simulant fluid were measured by using the Agilent Model 85070E Dielectric Probe (rates frequency band 200 MHz to 20 GHz) in conjunction with Network Analyzer.

All dielectric parameters of tissue simulates were measured within 24 hours of SAR measurements. The measured conductivity and permittivity are all within \pm 5% of the target values.

The depth of the tissue simulant in the flat section of the phantom was ≥ 15 cm ± 5 mm (Frequency $\leq 3G$) or ≥ 10 cm ± 5 mm (Frequency $\geq 3G$) during all tests. (Fig. 2)

Tissue Type	Measurement Date	Measured Frequency (MHz)	Target Dielectric Constant, εr	Target Conductivity, σ (S/m)	Measured Dielectric Constant, εr	Measured Conductivity , σ (S/m)	% dev ɛr	% dev σ
		2402.00	39.285	1.757	39.782	1.725	1.26%	-1.84%
		2412.00	39.268	1.766	39.773	1.733	1.29%	-1.88%
		2417.00	39.259	1.771	39.767	1.741	1.29%	-1.69%
		2437.00	39.223	1.788	39.693	1.752	1.20%	-2.04%
	Nov, 26. 2019	2441.00	39.216	1.792	39.677	1.761	1.18%	-1.73%
		2450.00	39.200	1.800	39.643	1.772	1.13%	-1.56%
		2457.00	39.191	1.808	39.631	1.775	1.12%	-1.83%
-		2462.00	39.185	1.813	39.622	1.783	1.12%	-1.66%
		2480.00	39.162	1.833	39.615	1.791	1.16%	-2.28%
		5180.00	36.009	4.635	36.513	4.542	1.40%	-2.01%
		5190.00	35.997	4.645	36.431	4.548	1.21%	-2.09%
		5200.00	35.986	4.655	36.428	4.555	1.23%	-2.15%
	Nov, 27. 2019	5210.00	35.974	4.665	36.399	4.572	1.18%	-2.00%
		5220.00	35.963	4.676	36.377	4.581	1.15%	-2.03%
		5230.00	35.951	4.686	36.369	4.625	1.16%	-1.30%
		5240.00	35.940	4.696	36.355	4.641	1.15%	-1.17%
l [5260.00	35.917	4.717	36.314	4.649	1.11%	-1.44%
Head		5270.00	35.906	4.727	36.295	4.655	1.08%	-1.52%
		5280.00	35.894	4.737	36.288	4.673	1.10%	-1.35%
	Nov, 28. 2019	5290.00	35.883	4.747	36.274	4.695	1.09%	-1.10%
		5300.00	35.871	4.758	36.266	4.713	1.10%	-0.94%
		5310.00	35.860	4.768	36.261	4.716	1.12%	-1.09%
		5320.00	35.849	4.778	36.258	4.721	1.14%	-1.19%
		5530.00	35.609	4.993	36.213	4.931	1.70%	-1.25%
		5600.00	35.529	5.065	36.175	4.964	1.82%	-1.99%
	Nov, 29. 2019	5610.00	35.517	5.075	36.169	4.972	1.84%	-2.03%
		5690.00	35.426	5.157	36.161	5.031	2.08%	-2.45%
		5745.00	35.363	5.214	36.158	5.123	2.25%	-1.75%
		5755.00	35.351	5.224	36.152	5.157	2.27%	-1.28%
		5775.00	35.329	5.244	36.144	5.166	2.31%	-1.49%
	Nov, 30. 2019	5785.00	35.317	5.255	36.127	5.173	2.29%	-1.56%
		5795.00	35.306	5.265	36.113	5.211	2.29%	-1.03%
		5800.00	35.300	5.270	36.106	5.217	2.28%	-1.01%
		5825.00	35.271	5.296	36.063	5.221	2.25%	-1.42%

Table 2. Dielectric Parameters of Tissue Simulant Fluid

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,併報生结果僅對測試之樣具負責,同時什樣具僅保留的子。太報生去經太公司惠面許可,不可部份複劃。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 56 of 89

The composition of the tissue simulating liquid:

_				Ingre	edient			
Frequency (MHz)	Mode	DGMBE	Water	Salt	Preventol D-7	Cellulose	Sugar	Total amount
2450	Head	550ml	450ml	_	_	_	_	1.0L(Kg)

Simulating Liquids for 5 GHz, Manufactured by SPEAG:

Ingredients	Water	Esters, Emulsifiers, Inhibitors	Sodium and Salt
(% by weight)	60-80	20-40	0-1.5

Table 3. Recipes for Tissue Simulating Liquid

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279 www.tw.sas.com



Page: 57 of 89

1.11 Evaluation Procedures

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- 1. The extraction of the measured data (grid and values) from the Zoom Scan.
- 2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- 3. The generation of a high-resolution mesh within the measured volume
- 4. The interpolation of all measured values from the measurement grid to the highresolution grid
- 5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- 6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within –2 dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7x7x7 scans. The routines are verified and optimized for the grid dimensions used in these cube measurements.

The measured volume of 30x30x30mm contains about 30g of tissue.

The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非兄有论明,此据华结里做影测过之缘是台書,同時什樣是做保留00千。木都华未领太公司事而纯可,不可部份複测。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 58 of 89

interpolation to get all points within the measured volume. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is the moved around until the highest averaged SAR is found. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

1.12 Probe Calibration Procedures

For the calibration of E-field probes in lossy liquids, an electric field with an accurately known field strength must be produced within the measured liquid. For standardization purposes it would be desirable if all measurements which are necessary to assess the correct field strength would be traceable to standardized measurement procedures. In the following two different calibration techniques are summarized:

1.12.1 Transfer Calibration with Temperature Probes

In lossy liquids the specific absorption rate (SAR) is related both to the electric field (E) and the temperature gradient ($\delta T/\delta t$) in the liquid.

$$SAR = C \frac{\delta T}{\delta t}$$
,

whereby σ is the conductivity, ρ the density and c the heat capacity of the liquid.

Hence, the electric field in lossy liquid can be measured indirectly by measuring the temperature gradient in the liquid. Non-disturbing temperature probes (optical probes or thermistor probes with resistive lines) with high spatial resolution (<1-2 mm) and fast reaction time (<1 s) are available and can be easily calibrated with high precision [1]. The setup and the exciting source have no influence on the calibration; only the relative positioning uncertainties of the standard temperature probe and the E-field probe to be calibrated must be considered. However, several problems limit the available accuracy of probe calibrations with temperature probes:

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,併報生结果僅對測試之樣具色書,同時什樣具僅保留的主。大報生主經太公司書面許可,不可無份複制。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 59 of 89

 The temperature gradient is not directly measurable but must be evaluated from temperature measurements at different time steps. Special precaution is necessary to avoid measurement errors caused by temperature gradients due to energy equalizing effects or convection currents in the liquid. Such effects cannot be completely avoided, as the measured field itself destroys the thermal equilibrium in the liquid. With a careful setup these errors can be kept small.

- The measured volume around the temperature probe is not well defined. It is difficult to calculate the energy transfer from a surrounding gradient temperature field into the probe. These effects must be considered, since temperature probes are calibrated in liquid with homogeneous temperatures. There is no traceable standard for temperature rise measurements.
- The calibration depends on the assessment of the specific density, the heat capacity and the conductivity of the medium. While the specific density and heat capacity can be measured accurately with standardized procedures (\sim 2% for c; much better for ρ) , there is no standard for the measurement of the conductivity. Depending on the method and liquid, the error can well exceed ±5%.
- Temperature rise measurements are not very sensitive and therefore are often performed at a higher power level than the E-field measurements. The nonlinearities in the system (e.g., power measurements, different components, etc.) must be considered.

Considering these problems, the possible accuracy of the calibration of Efield probes with temperature gradient measurements in a carefully designed setup is about ±10% (RSS) [2]. Recently, a setup which is a combination of the waveguide techniques and the thermal measurements was presented in [3]. The estimated uncertainty of the setup is ±5% (RSS) when the same liquid is used for the calibration and for actual measurements and ±7-9% (RSS) when not, which is in good agreement with the estimates given in [2].

1.12.2 Calibration with Analytical Fields

In this method a technical setup is used in which the field can be calculated analytically from measurements of other physical magnitudes (e.g., input power). This corresponds to the standard field method for probe calibration in air; however, there is no standard defined for fields in lossy liquids. When using calculated fields in lossy liquids for probe calibration, several points must be considered in the assessment of the uncertainty:

- The setup must enable accurate determination of the incident power.
- The accuracy of the calculated field strength will depend on the assessment of the dielectric parameters of the liquid.
- Due to the small wavelength in liquids with high permittivity, even small

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 1 台灣檢驗科技股份有限公司



Page: 60 of 89

setups might be above the resonant cutoff frequencies. The field distribution in the setup must be carefully checked for conformity with the theoretical field distribution.

References

- 1. N. Kuster, Q. Balzano, and J.C. Lin, Eds., Mobile Communications Safety, Chapman & Hall, London, 1997.
- K. Meier, M. Burkhardt, T. Schmid, and N. Kuster, \Broadband 2. calibration of E-field probes in lossy media", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1954{1962, Oct.
- K. Jokela, P. Hyysalo, and L. Puranen, \Calibration of specific 3. absorption rate (SAR) probes in waveguide at 900 MHz", IEEE Transactions on Instrumentation and Measurements, vol. 47, no. 2, pp. 432{438, Apr. 1998.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 61 of 89

1.13 Test Standards and Limits

According to FCC 47CFR §2.1093(d) The limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate ("SAR") in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.1, By the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017. These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86, Section 17.4.5. Copyright NCRP, 1986, Bethesda, Maryland 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards. The criteria to be used are specified in paragraphs (d)(1) and (d)(2) of this section and shall apply for portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified in § 1.1310 of this chapter. Measurements and calculations to demonstrate compliance with MPE field strength or power density limits for devices operating above 6 GHz should be made at a minimum distance of 5 cm from the radiating source.

- (1) Limits for Occupational/Controlled exposure: 0.4 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 8 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 20 W/kg, as averaged over an 10 grams of tissue (defined as a tissue volume in the shape of a cube).
- (2) Occupational/Controlled limits apply when persons are exposed as a consequence of their employment provided these persons are fully aware of and exercise control over their exposure. Awareness of exposure can be accomplished by use of warning labels or by specific training or education through appropriate means, such as an RF safety program in a work environment.
- (3) Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 险非只有的阻,此想些结果做到到这种是否是,同时此样只像是2000年。太祖生主领大人司事而统可,不可能以推制。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司 No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號

Member of SGS Group



Page: 62 of 89

devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section. (Table 4.)

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR (Brain)	1.60 W/kg	8.00 W/kg
Spatial Average SAR (Whole Body)	0.08 W/kg	0.40 W/kg
Spatial Peak SAR (Hands/Feet/Ankle/Wrist)	4.00 W/kg	20.00 W/kg

Table 4. RF exposure limits

Notes:

- 1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
- 2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,此報告結果僅對測計之緣品台書,同時什樣品僅保留仍天。木報告未經太公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 63 of 89

2. Summary of Results

2.1 Decision rules

Reported measurement data comply with IEEE 1528-2013: Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.2 Summary of Results

Tablet mode

WLAN Tx1 Antenna

Antenna	Mode	Position	Distance (mm)	СН	Freq.	Max. Rated Avg. Power + Max.	Measured Avg. Power	Scaling	Averaged S (W)		Plot page
			()		()	Tolerance (dBm)	(dBm)		Measured	Reported	pago
		Back side	0	6	2437	19.00	18.99	100.23%	0.677	0.679	-
		Top side	0	6	2437	19.00	18.99	100.23%	0.916	0.918	71
		Top side*	0	6	2437	19.00	18.99	100.23%	0.911	0.913	-
	WLAN 802.11b	Top side	0	11	2462	19.00	18.98	100.46%	0.903	0.907	-
		Bottom side	0	6	2437	19.00	18.99	100.23%	0.004	0.004	-
		Right side	0	6	2437	19.00	18.99	100.23%	0.331	0.332	-
		Left side	0	6	2437	19.00	18.99	100.23%	0.010	0.010	-
		Back side	0	42	5210	16.00	15.95	101.16%	0.631	0.638	-
		Top side	0	42	5210	16.00	15.95	101.16%	0.872	0.882	72
	WLAN 802.11ac(80M) 5.2G	Top side*	0	42	5210	16.00	15.95	101.16%	0.855	0.865	-
	WLAN 602. Hac(60W) 5.2G	Bottom side	0	42	5210	16.00	15.95	101.16%	0.003	0.003	-
		Right side	0	42	5210	16.00	15.95	101.16%	0.324	0.328	-
		Left side	0	42	5210	16.00	15.95	101.16%	0.009	0.009	-
		Back side	0	58	5290	16.00	15.97	100.69%	0.628	0.632	-
		Top side	0	58	5290	16.00	15.97	100.69%	0.872	0.878	73
Tx1	N// AN 000 44 (00N 5 5 00	Top side*	0	58	5290	16.00	15.97	100.69%	0.863	0.869	-
	WLAN 802.11ac(80M) 5.3G	Bottom side	0	58	5290	16.00	15.97	100.69%	0.003	0.003	-
		Right side	0	58	5290	16.00	15.97	100.69%	0.321	0.323	-
		Left side	0	58	5290	16.00	15.97	100.69%	0.009	0.009	-
		Back side	0	106	5530	16.00	15.96	100.93%	0.773	0.780	-
		Top side	0	106	5530	16.00	15.96	100.93%	1.030	1.040	74
		Top side*	0	106	5530	16.00	15.96	100.93%	1.010	1.019	-
	WLAN 802.11ac(80M) 5.6G	Top side	0	122	5610	16.00	15.91	102.09%	0.997	1.018	-
		Bottom side	0	106	5530	16.00	15.96	100.93%	0.005	0.005	-
		Right side	0	106	5530	16.00	15.96	100.93%	0.354	0.357	-
		Left side	0	106	5530	16.00	15.96	100.93%	0.013	0.013	-
		Back side	0	155	5775	16.00	15.90	102.33%	0.591	0.605	-
		Top side	0	155	5775	16.00	15.90	102.33%	0.710	0.727	75
	WLAN 802.11ac(80M) 5.8G	Bottom side	0	155	5775	16.00	15.90	102.33%	0.002	0.002	-
		Right side	0	155	5775	16.00	15.90	102.33%	0.311	0.318	-
		Left side	0	155	5775	16.00	15.90	102.33%	0.006	0.006	-

^{* -} repeated at the highest SAR measurement according to the KDB 865664 D01

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有铅明,件据华廷国佛教训献之样具色者,同时件撰具届保留的子。大器华主领太公司事而许可,不可部份推制。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 64 of 89

WLAN Tx2 Antenna

Back side	Antenna	Mode	Position	Distance (mm)	СН	Freq.	Max. Rated Avg. Power + Max.	Measured Avg. Power	Scaling	Averaged S (W/		Plot
Top side				()		()	Tolerance (dBm)	(dBm)		Measured	Reported	pago
Titop side** 0			Back side	0	1	2412	19.00	18.97	100.69%	0.613	0.617	-
TX2 WLAN 802.11b Top side 0			Top side	0	1	2412	19.00	18.97	100.69%	1.140	1.148	76
Bolton side			Top side*	0	1	2412	19.00	18.97	100.69%	1.120	1.128	-
Right side		WLAN 802.11b	Top side	0	11	2462	19.00	18.96	100.93%	1.110	1.120	-
TX2 Left side			Bottom side	0	1	2412	19.00	18.97	100.69%	0.005	0.005	-
Bluetooth (GFSK) Back side 0 78 2480 10.80 10.13 116.69% 0.072 0.084			Right side	0	1	2412	19.00	18.97	100.69%	0.010	0.010	-
Tx2 Bluetooth (GFSK) Bottom side 0 78 2480 10.80 10.13 116.68% 0.195 0.228 77			Left side	0	1	2412	19.00	18.97	100.69%	0.322	0.324	-
Bluetooth (GFSK) Bottom side 0 78 2480 10.80 10.13 116.68% 0.001 0.001 . Right side 0 78 2480 10.80 10.13 116.68% 0.004 0.005 . Left side 0 78 2480 10.80 10.13 116.68% 0.004 0.005 . Back side 0 42 5210 16.00 15.97 100.69% 0.463 0.466 . Top side 0 42 5210 16.00 15.97 100.69% 0.929 0.935 78 Top side 0 42 5210 16.00 15.97 100.69% 0.002 0.002 . Right side 0 42 5210 16.00 15.97 100.69% 0.002 0.002 . Left side 0 42 5210 16.00 15.97 100.69% 0.002 0.002 . Left side 0 42 5210 16.00 15.97 100.69% 0.002 0.002 . Left side 0 42 5210 16.00 15.97 100.69% 0.007 0.007 . Left side 0 42 5210 16.00 15.97 100.69% 0.007 0.007 . Left side 0 58 5290 16.00 15.97 100.69% 0.0173 0.174 . Top side 0 58 5290 16.00 15.99 100.23% 0.421 0.422 . Top side 0 58 5290 16.00 15.99 100.23% 0.882 0.854 79 Top side 0 58 5290 16.00 15.99 100.23% 0.002 0.002 . Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 . Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 . Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 . Left side 0 106 5530 16.00 15.99 100.23% 0.007 0.408 . Top side 0 106 5530 16.00 15.99 100.23% 0.007 0.007 . Right side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 . Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 . Left side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 . Right side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 . Right side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 . WILAN 802.11ac(80M) 5.8G Bottom side 0 155 5775 16.00 15.98 100.46% 0.004 0.004 .			Back side	0	78	2480	10.80	10.13	116.68%	0.072	0.084	-
Right side			Top side	0	78	2480	10.80	10.13	116.68%	0.195	0.228	77
Left side		Bluetooth (GFSK)	Bottom side	0	78	2480	10.80	10.13	116.68%	0.001	0.001	-
TX2 WLAN 802.11ac(80M) 5.2G Back side 0			Right side	0	78	2480	10.80	10.13	116.68%	0.004	0.005	-
TX2 WLAN 802.11ac(80M) 5.2G Top side 0 42 5210 16.00 15.97 100.69% 0.929 0.935 78 Top side 0 42 5210 16.00 15.97 100.69% 0.925 0.931 - Bottom side 0 42 5210 16.00 15.97 100.69% 0.002 0.002 - Right side 0 42 5210 16.00 15.97 100.69% 0.007 0.007 - Left side 0 42 5210 16.00 15.97 100.69% 0.007 0.007 - Left side 0 42 5210 16.00 15.97 100.69% 0.007 0.007 - Back side 0 58 5290 16.00 15.99 100.23% 0.421 0.422 - Top side 0 58 5290 16.00 15.99 100.23% 0.852 0.854 79 Bottom side 0 58 5290 16.00 15.99 100.23% 0.864 0.850 - Bottom side 0 58 5290 16.00 15.99 100.23% 0.002 0.002 - Right side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Bottom side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.007 0.408 - Top side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 - Top side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 - Right side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 -			Left side	0	78	2480	10.80	10.13	116.68%	0.002	0.002	-
Top side			Back side	0	42	5210	16.00	15.97	100.69%	0.463	0.466	-
Tx2 Bottom side 0			Top side	0	42	5210	16.00	15.97	100.69%	0.929	0.935	78
Bottom side		W/I ANI 902 11 00/90MM E 2G	Top side*	0	42	5210	16.00	15.97	100.69%	0.925	0.931	-
Variable Left side 0		WLAN 602. Frac (60N) 5.2G	Bottom side	0	42	5210	16.00	15.97	100.69%	0.002	0.002	-
Left side	Tv2		Right side	0	42	5210	16.00	15.97	100.69%	0.007	0.007	-
WLAN 802.11ac(80M) 5.3G Top side 0 58 5290 16.00 15.99 100.23% 0.848 0.850 - Bottom side 0 58 5290 16.00 15.99 100.23% 0.002 0.002 - Right side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Back side 0 106 5530 16.00 15.99 100.23% 0.407 0.408 - Top side 0 106 5530 16.00 15.99 100.23% 0.792 0.794 80 WLAN 802.11ac(80M) 5.6G Bottom side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 - Right side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 - Right side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 - Right side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Top side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 - Top side 0 155 5775 16.00 15.98 100.46% 0.730 0.733 81 Bottom side 0 155 5775 16.00 15.98 100.46% 0.004 0.004 -	1 1 1 2		Left side	0	42	5210	16.00	15.97	100.69%	0.173	0.174	-
Top side			Back side	0	58	5290	16.00	15.99	100.23%	0.421	0.422	-
Bottom side 0 58 5290 16.00 15.99 100.23% 0.002 0.002 - Right side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.157 0.157 - Back side 0 106 5530 16.00 15.99 100.23% 0.407 0.408 - Top side 0 106 5530 16.00 15.99 100.23% 0.792 0.794 80 80 80 80 80 80 80 8			Top side	0	58	5290	16.00	15.99	100.23%	0.852	0.854	79
Bottom side 0 58 5290 16.00 15.99 100.23% 0.002 0.002 - Right side 0 58 5290 16.00 15.99 100.23% 0.006 0.006 - Left side 0 58 5290 16.00 15.99 100.23% 0.157 0.157 - Back side 0 106 5530 16.00 15.99 100.23% 0.407 0.408 - Top side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 - Right side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 - Right side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Back side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Top side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Top side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 - Top side 0 155 5775 16.00 15.98 100.46% 0.730 0.733 81 WLAN 802.11ac(80M) 5.8G Bottom side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 -		WILANI 000 44 (00M) 5 00	Top side*	0	58	5290	16.00	15.99	100.23%	0.848	0.850	
Left side 0 58 5290 16.00 15.99 100.23% 0.157 0.157 - Back side 0 106 5530 16.00 15.99 100.23% 0.407 0.408 - Top side 0 106 5530 16.00 15.99 100.23% 0.792 0.794 80 Bottom side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 - Right side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.151 0.151 - Back side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 - Top side 0 155 5775 16.00 15.98 100.46% 0.730 0.733 81 Bottom side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 - Right side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 -		WLAN 802.11ac(80M) 5.3G	Bottom side	0	58	5290	16.00	15.99	100.23%	0.002	0.002	-
Back side 0 106 5530 16.00 15.99 100.23% 0.407 0.408 - Top side 0 106 5530 16.00 15.99 100.23% 0.792 0.794 80			Right side	0	58	5290	16.00	15.99	100.23%	0.006	0.006	-
Top side			Left side	0	58	5290	16.00	15.99	100.23%	0.157	0.157	-
WLAN 802.11ac(80M) 5.6G Bottom side 0 106 5530 16.00 15.99 100.23% 0.001 0.001 - Right side 0 106 5530 16.00 15.99 100.23% 0.005 0.005 - Left side 0 106 5530 16.00 15.99 100.23% 0.151 0.151 - Back side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 - Top side 0 155 5775 16.00 15.98 100.46% 0.730 0.733 81 WLAN 802.11ac(80M) 5.8G Bottom side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 - Right side 0 155 5775 16.00 15.98 100.46% 0.004 0.004 -			Back side	0	106	5530	16.00	15.99	100.23%	0.407	0.408	
Right side			Top side	0	106	5530	16.00	15.99	100.23%	0.792	0.794	80
Left side 0 106 5530 16.00 15.99 100.23% 0.151 0.151 - Back side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 - Top side 0 155 5775 16.00 15.98 100.46% 0.730 0.733 81 WLAN 802.11ac(80M) 5.8G Bottom side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 - Right side 0 155 5775 16.00 15.98 100.46% 0.004 0.004 -		WLAN 802.11ac(80M) 5.6G	Bottom side	0	106	5530	16.00	15.99	100.23%	0.001	0.001	
Back side 0 155 5775 16.00 15.98 100.46% 0.388 0.390 - Top side 0 155 5775 16.00 15.98 100.46% 0.730 0.733 81 WLAN 802.11ac(80M) 5.8G Bottom side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 - Right side 0 155 5775 16.00 15.98 100.46% 0.004 0.004 -			Right side	0	106	5530	16.00	15.99	100.23%	0.005	0.005	-
Top side 0 155 5775 16.00 15.98 100.46% 0.730 0.733 81			Left side	0	106	5530	16.00	15.99	100.23%	0.151	0.151	-
WLAN 802.11ac(80M) 5.8G Bottom side 0 155 5775 16.00 15.98 100.46% 0.001 0.001 - Right side 0 155 5775 16.00 15.98 100.46% 0.004 0.004 -			Back side	0	155	5775	16.00	15.98	100.46%	0.388	0.390	-
Right side 0 155 5775 16.00 15.98 100.46% 0.004 0.004 -			Top side	0	155	5775	16.00	15.98	100.46%	0.730	0.733	81
		WLAN 802.11ac(80M) 5.8G	Bottom side	0	155	5775	16.00	15.98	100.46%	0.001	0.001	-
Left side 0 155 5775 16.00 15.98 100.46% 0.147 0.148 -			Right side	0	155	5775	16.00	15.98	100.46%	0.004	0.004	-
			Left side	0	155	5775	16.00	15.98	100.46%	0.147	0.148	-

^{* -} repeated at the highest SAR measurement according to the KDB 865664 D01

Note:

Scaling =
$$\frac{\text{reported SAR}}{\text{measured SAR}} = \frac{P2(\text{mW})}{P1(\text{mW})} = 10^{\left(\frac{P2-P1}{10}\right)(\text{dBm})}$$

Reported SAR = measured SAR * (scaling)

Where P2 is maximum specified power, P1 is measured conducted power

2.3 Reporting statements of conformity

The conformity statement in this report is based solely on the test results, measurement uncertainty is excluded.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 65 of 89

3. Simultaneous Transmission Analysis

Simultaneous Transmission Scenarios:

Simultaneous Transmit Configurations	Body
2.4GHz WLAN MIMO	Yes
5GHz WLAN MIMO	Yes
BT + 2.4GHz WLAN Tx1	Yes
BT + 5GHz WLAN Tx1	Yes

Note:

- 1. Bluetooth and WLAN Tx2 share the same antenna path, and BT can transmit with WLAN Tx1 simultaneously.
- 2. For 2.4/5GHz WLAN Tx2 and Tx1 antennas, the maximum output power of each antenna during simultaneous transmission is less than that used in standalone transmission, and we used the sum of standalone 1-g SAR provision in KDB447498D01 to exclude the simultaneous transmitted SAR measurement.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 66 of 89

3.1 Estimated SAR calculation

According to KDB447498 D01v06 – When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

Estimated SAR =
$$\frac{\text{Max. tune up power (mW)}}{\text{Min. test separation distance(mm)}} \times \frac{\sqrt{\text{f(GHz)}}}{7.5}$$

If the minimum test separation distance is < 5mm, a distance of 5mm is used for estimated SAR calculation. When the test separation distance is >50mm, the 0.4W/kg is used for SAR-1g.

3.2 SPLSR evaluation and analysis

Per KDB447498D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR sum to peak location separation ratio(SPLSR).

The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion.

The ratio is determined by (SAR1 + SAR2)^1.5/Ri, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

SAR1 and SAR2 are the highest reported or estimated SAR for each antenna in the pair, and Ri is the separation distance between the peak SAR locations for the antenna pair in mm.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format

documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms-e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd. No.134, 台灣檢驗科技股份有限公司 t (886-2)

prosecuted to the fullest extent of the law.



Page: 67 of 89


Tablet mode

2.4 GHz WLAN MIMO

	LIT OHE WEAR MINIO								
No.	Conditions	Position	Max. WLAN Tx1	Max. WLAN Tx2	SAR Sum	SPLSR			
		Back side	0.679	0.617	1.296	ΣSAR<1.6, Not required			
		Top side	0.918	1.148	2.066	Analyzed as below			
1	2.4 GHz WLAN Tx1 + WLAN Tx2	Bottom side	0.004	0.005	0.009	Not required Analyzed as below ΣSAR<1.6, Not required ΣSAR<1.6,			
		Right side	0.332	0.010	0.342	ΣSAR<1.6, Not required			
		Left side	0.010	0.324	0.334	ΣSAR<1.6, Not required			

2.4 GHz WI AN MIMO

		SAR	Cod	ordinates (d	cm)	ΣSAR	Peak Location		Simultaneous
Conditions	Position	Value (W/kg)	ie (W/kc		(W/kg)	Separation Distance (mm)	SPLSR	Transmission SAR Test	
WLAN Tx1	Top side	0.918	-0.38	10.52	-0.03	2.066	187.23	0.016	SPLSR<0.04,
WLAN Tx2	Top side	1.148	-0.68	-8.20	0.05	2.000		0.010	Not required



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司




Page: 68 of 89

5 GHz WLAN MIMO

No.	Conditions	Position	Max. WLAN Tx1	Max. WLAN Tx2	SAR Sum	SPLSR
		Back side	0.780	0.466	1.246	ΣSAR<1.6, Not required
		Top side	1.040	0.935	1.975	Analyzed as below
2	5 GHz WLAN Tx1 + WLAN Tx2	Bottom side	0.005	0.002	0.007	ΣSAR<1.6, Not required
		Right side	0.357	0.007	0.364	ΣSAR<1.6, Not required
		Left side	0.013	0.174	0.187	ΣSAR<1.6, Not required

5 GHz WLAN MIMO

Conditions	Position	SAR Value	Coordinates (cm)			ΣSAR (W/kg)	Peak Location Separation Distance (mm)	SPLSR	Simultaneous Transmission SAR Test
		(W/kg)	x y z						
WLAN Tx1	Top side	1.04	-0.56	11.42	-0.28	1.975	206.63	0.013	SPLSR<0.04,
WLAN Tx2		0.935	-0.80	-9.24	-0.04	1.975	200.03	0.013	Not required



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 69 of 89

BT+ 2.4GHz WLAN Tx1

No.	Conditions	Position	Max. WLAN Tx1	ВТ	SAR Sum	SPLSR
		Back side	0.679	0.084	0.763	ΣSAR<1.6, Not required
		Top side	0.918	0.228	1.146	ΣSAR<1.6, Not required
3	2.4 GHz WLAN Tx1 + BT	Bottom side	0.004	0.001	0.005	ΣSAR<1.6, Not required
		Right side	0.332	0.005	0.337	ΣSAR<1.6, Not required
		Left side	0.010	0.002	0.012	ΣSAR<1.6, Not required

BT+5GHz WLAN Tx1

No.	Conditions	Position	Max. WLAN Tx1	ВТ	SAR Sum	SPLSR
		Back side	0.780	0.084	0.864	ΣSAR<1.6, Not required
		Top side	1.040	0.228	1.268	ΣSAR<1.6, Not required
4	5 GHz WLAN Tx1 + BT	Bottom side	0.005	0.001	0.006	ΣSAR<1.6, Not required
		Right side	0.357	0.005	0.362	ΣSAR<1.6, Not required
		Left side	0.013	0.002	0.015	ΣSAR<1.6, Not required

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 70 of 89

4. Instruments List

Manufacturer	Device	Туре	Serial number	Date of last calibration	Date of next calibration
SPEAG	Dosimetric E- Field Probe	EX3DV4	7466	Feb.04,2019	Feb.03,2020
CDEAC	System Validation	D2450V2	727	Apr.24,2019	Apr.23,2020
SPEAG	Dipole	D5GHzV2	1023	Jan.30,2019	Jan.29,2020
SPEAG	Data acquisition Electronics	DAE4	1260	Sep.11,2019	Sep.10,2020
SPEAG	Software	DASY 52 52.10.2	N/A	Calibration not required	Calibration not required
SPEAG	Phantom	ELI	N/A	Calibration not required	Calibration not required
Agilent	Network Analyzer	E5071C	MY46107530	-	Feb.22,2020
Agilent	Dielectric Probe Kit	85070E	MY44300677	Calibration not required	Calibration not required
Agilent	Dual-directional	772D	MY46151242	Jul.30,2019	Jul.29,2020
Agilent	coupler	778D	MY48220468	Jul.30,2019	Jul.29,2020
Agilent	Signal Generator	N5181A	MY50141235	Apr.22,2019	Apr.21,2020
Agilent	Power Meter	E4417A	MY51410006	Feb.19,2019	Feb.18,2020
A allow t	Dower Concer	E9301H	MY51470001	Feb.19,2019	Feb.18,2020
Agilent	Power Sensor		MY51470002	Feb.19,2019	Feb.18,2020
TECPEL	Digital thermometer	DTM-303A	TP130074	Mar.26,2019	Mar.25,2020

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 71 of 89

5. Measurements

Date: 2019/11/26

WLAN 802.11b Tablet Top side CH 6 Tx1 0mm

Communication System: WLAN 2.45G; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2437 MHz; $\sigma = 1.752$ S/m; $\varepsilon_r = 39.693$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient temperature: 21.7°C; Liquid temperature: 22.3°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(7.66, 7.66, 7.66);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x131x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 1.33 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.543 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 2.36 W/kg

SAR(1 g) = 0.916 W/kg; SAR(10 g) = 0.359 W/kg

Maximum value of SAR (measured) = 1.38 W/kg



0 dB = 1.38 W/kg = 1.40 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 72 of 89

Date: 2019/11/27

WLAN 802.11ac(80M) 5.2G_Tablet_Top side_CH 42_Tx1_0mm

Communication System: WLAN 5G; Frequency: 5210 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5210 MHz; $\sigma = 4.572 \text{ S/m}$; $\epsilon_r = 36.399$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.4°C; Liquid temperature: 21.8°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.56, 5.56, 5.56);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

• DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.59 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.995 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 3.58 W/kg

SAR(1 g) = 0.872 W/kg; SAR(10 g) = 0.276 W/kg Maximum value of SAR (measured) = 1.70 W/kg



0 dB = 1.70 W/kg = 2.30 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅累到關訊之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sg.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sg.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 73 of 89

Date: 2019/11/28

WLAN 802.11ac(80M) 5.3G_Tablet_Top side_CH 58_Tx1_0mm

Communication System: WLAN 5G; Frequency: 5290 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5290 MHz; $\sigma = 4.695 \text{ S/m}$; $\varepsilon_r = 36.274$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.5°C; Liquid temperature: 21.7°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.41, 5.41, 5.41);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.52 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.237 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 4.84 W/kg

SAR(1 g) = 0.872 W/kg; SAR(10 g) = 0.269 W/kg

Maximum value of SAR (measured) = 1.64 W/kg


Zoom Scan (7x7x12)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.237 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 3.70 W/kg

SAR(1 g) = 0.655 W/kg; SAR(10 g) = 0.182 W/kg

Maximum value of SAR (measured) = 1.36 W/kg



0 dB = 1.36 W/kg = 1.34 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Page: 74 of 89

Date: 2019/11/29

WLAN 802.11ac(80M) 5.6G_Tablet_Top side_CH 106_Tx1_0mm

Communication System: WLAN 5G; Frequency: 5530 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5530 MHz; $\sigma = 4.931 \text{ S/m}$; $\varepsilon_r = 36.213$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.6°C; Liquid temperature: 22.1°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(4.88, 4.88, 4.88);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.65 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.727 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 6.22 W/kg

SAR(1 q) = 1.03 W/kq; SAR(10 q) = 0.293 W/kq

Maximum value of SAR (measured) = 2.06 W/kg

Zoom Scan (7x7x12)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.727 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 3.31 W/kg

SAR(1 g) = 0.648 W/kg; SAR(10 g) = 0.228 W/kg


Maximum value of SAR (measured) = 1.39 W/kg

Zoom Scan (7x7x12)/Cube 2: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.727 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 5.08 W/kg

SAR(1 g) = 0.589 W/kg; SAR(10 g) = 0.228 W/kgMaximum value of SAR (measured) = 2.09 W/kg



0 dB = 2.09 W/kg = 3.20 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Page: 75 of 89

Date: 2019/11/30

WLAN 802.11ac(80M) 5.8G_Tablet_Top side_CH 155_Tx1_0mm

Communication System: WLAN 5G; Frequency: 5775 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5775 MHz; $\sigma = 5.166$ S/m; $\varepsilon_r = 36.144$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient temperature: 21.5°C; Liquid temperature: 21.9°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.06, 5.06, 5.06);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.25 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.583 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 3.68 W/kg

SAR(1 g) = 0.697 W/kg; SAR(10 g) = 0.225 W/kg

Maximum value of SAR (measured) = 1.50 W/kg

Zoom Scan (7x7x12)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.583 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 3.60 W/kg

SAR(1 g) = 0.710 W/kg; SAR(10 g) = 0.221 W/kg


Maximum value of SAR (measured) = 1.44 W/kg

Zoom Scan (7x7x12)/Cube 2: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.583 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 3.76 W/kg

SAR(1 g) = 0.579 W/kg; SAR(10 g) = 0.211 W/kg Maximum value of SAR (measured) = 1.47 W/kg



0 dB = 1.47 W/kg = 1.67 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非兄有论明,此据华结里做影测过之缘是台書,同時什樣是做保留00千。木都华未领木公司事而纯可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 76 of 89

Date: 2019/11/26

WLAN 802.11b_Tablet_Top side_CH 1_TX2_0mm

Communication System: WLAN 2.45G; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2412 MHz; $\sigma = 1.733$ S/m; $\epsilon_r = 39.773$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient temperature: 21.7°C; Liquid temperature: 22.3°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(7.66, 7.66, 7.66);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

· Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x131x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 1.05 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.175 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 3.35 W/kg

SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.449 W/kg

Maximum value of SAR (measured) = 1.82 W/kg



0 dB = 1.82 W/kg = 3.12 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非兄有论明,此据华结里做影测过之缘是台書,同時什樣是做保留00千。木都华未领木公司事而纯可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 77 of 89

Date: 2019/11/26

Bluetooth(GFSK)_Tablet_Top side_CH 78_TX2_0mm

Communication System: Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2480 MHz; $\sigma = 1.791 \text{ S/m}$; $\varepsilon_r = 39.615$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.7°C; Liquid temperature: 22.3°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(7.66, 7.66, 7.66);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (71x131x1): Interpolated grid: dx=12 mm, dy=12 mm


Maximum value of SAR (interpolated) = 0.323 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.436 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.524 W/kg

SAR(1 g) = 0.195 W/kg; SAR(10 g) = 0.070 W/kgMaximum value of SAR (measured) = 0.323 W/kg



0 dB = 0.323 W/kg = -4.91 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Page: 78 of 89

Date: 2019/11/27

WLAN 802.11ac(80M) 5.2G_Tablet_Top side_CH 42_TX2_0mm

Communication System: WLAN 5G; Frequency: 5210 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5210 MHz; $\sigma = 4.572 \text{ S/m}$; $\epsilon_r = 36.399$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.4°C; Liquid temperature: 21.8°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.56, 5.56, 5.56);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

· Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm


Maximum value of SAR (interpolated) = 1.01 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.473 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.15 W/kg

SAR(1 g) = 0.929 W/kg; SAR(10 g) = 0.319 W/kg Maximum value of SAR (measured) = 1.32 W/kg



0 dB = 1.32 W/kg = 2.94 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,此報告結果僅對測試之緣品負責,同時此樣品僅保留00天。木報告表經太公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Page: 79 of 89

Date: 2019/11/28

WLAN 802.11ac(80M) 5.3G_Tablet_Top side_CH 58_TX2_0mm

Communication System: WLAN 5G; Frequency: 5290 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5290 MHz; $\sigma = 4.695 \text{ S/m}$; $\epsilon_r = 36.274$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.5°C; Liquid temperature: 21.7°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.41, 5.41, 5.41);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

· Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm


Maximum value of SAR (interpolated) = 0.817 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.558 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.82 W/kg

SAR(1 g) = 0.852 W/kg; SAR(10 g) = 0.308 W/kg Maximum value of SAR (measured) = 1.49 W/kg



0 dB = 1.49 W/kg = 2.08 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,此報告結果僅對測試之緣品負責,同時此樣品僅保留00天。木報告表經太公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format formation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Page: 80 of 89

Date: 2019/11/29

WLAN 802.11ac(80M) 5.6G_Tablet_Top side_CH 106_TX2_0mm

Communication System: WLAN 5G; Frequency: 5530 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5530 MHz; $\sigma = 4.931 \text{ S/m}$; $\varepsilon_r = 36.213$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.6°C; Liquid temperature: 22.1°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(4.88, 4.88, 4.88);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm


Maximum value of SAR (interpolated) = 0.717 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.441 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.792 W/kg; SAR(10 g) = 0.289 W/kgMaximum value of SAR (measured) = 1.42 W/kg



0 dB = 1.42 W/kg = 2.01 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 81 of 89

Date: 2019/11/30

WLAN 802.11ac(80M) 5.8G_Tablet_Top side_CH 155_TX2_0mm

Communication System: WLAN 5G; Frequency: 5775 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5775 MHz; $\sigma = 5.166$ S/m; $\varepsilon_r = 36.144$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient temperature: 21.5°C; Liquid temperature: 21.9°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.06, 5.06, 5.06);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

· Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Area Scan (61x101x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.517 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.745 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.730 W/kg; SAR(10 g) = 0.253 W/kg Maximum value of SAR (measured) = 1.31 W/kg



0 dB = 1.31 W/kg = 1.89 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此藝告結果僅對測試之樣品負責,同時此樣品僅保留90天。本藝告未經本公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format formation or failured therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司 No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Page: 82 of 89

6. SAR System Performance Verification

Date: 2019/11/26

Dipole 2450 MHz SN:727

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2450 MHz; $\sigma = 1.772 \text{ S/m}$; $\varepsilon_r = 39.643$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.7°C; Liquid temperature: 22.3°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(7.66, 7.66, 7.66);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Pin=250mW/Area Scan (71x91x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 20.8 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 107.6 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 26.5 W/kg

SAR(1 g) = 13 W/kg; SAR(10 g) = 6.05 W/kg

Maximum value of SAR (measured) = 19.8 W/kg



0 dB = 19.8 W/kg = 12.97 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,此報告結果僅對測試之緣品負責,同時此樣品僅保留00天。木報告表經太公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Page: 83 of 89

Date: 2019/11/27

Dipole 5200 MHz_SN:1023

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5200 MHz; $\sigma = 4.555 \text{ S/m}$; $\varepsilon_r = 36.428$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.4°C; Liquid temperature: 21.8°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.56, 5.56, 5.56);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Pin=100mW/Area Scan (51x51x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 17.2 W/kg


Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 65.18 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 32.7 W/kg

SAR(1 g) = 8.27 W/kg; SAR(10 g) = 2.37 W/kg

Maximum value of SAR (measured) = 17.1 W/kg



0 dB = 17.1 W/kg = 12.33 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 84 of 89

Date: 2019/11/28

Dipole 5300 MHz_SN:1023

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5300 MHz; $\sigma = 4.713 \text{ S/m}$; $\varepsilon_r = 36.266$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.5°C; Liquid temperature: 21.7°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(5.41, 5.41, 5.41);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Pin=100mW/Area Scan (61x91x1): Interpolated grid: dx=10 mm, dy=10 mm


Maximum value of SAR (interpolated) = 17.3 W/kg

Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 65.14 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 31.9 W/kg

SAR(1 g) = 8.15 W/kg; SAR(10 g) = 2.34 W/kg Maximum value of SAR (measured) = 16.8 W/kg



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,此報告結果僅對測試之緣品負責,同時此樣品僅保留00天。木報告表經太公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 85 of 89

Date: 2019/11/29

Dipole 5600 MHz_SN:1023

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5600 MHz; $\sigma = 4.964 \text{ S/m}$; $\varepsilon_r = 36.175$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.6°C; Liquid temperature: 22.1°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466;ConvF(4.88, 4.88, 4.88);Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Pin=100mW/Area Scan (51x51x1): Interpolated grid: dx=10 mm, dy=10 mm


Maximum value of SAR (interpolated) = 19.2 W/kg

Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 65.15 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 38.3 W/kg

SAR(1 g) = 8.74 W/kg; SAR(10 g) = 2.45 W/kg Maximum value of SAR (measured) = 18.4 W/kg



0 dB = 18.4 W/kg = 12.65 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,此報告結果僅對測試之緣品負責,同時此樣品僅保留00天。木報告表經太公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 86 of 89

Date: 2019/11/30

Dipole 5800 MHz_SN:1023

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used: f = 5800 MHz; $\sigma = 5.217 \text{ S/m}$; $\varepsilon_r = 36.106$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 21.5°C; Liquid temperature: 21.9°C

DASY5 Configuration:

Probe: EX3DV4 - SN7466; ConvF(5.06, 5.06, 5.06); Calibrated: 2019/2/4

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1260; Calibrated: 2019/9/11

Phantom: ELI

DASY52 52.10.2(1495); SEMCAD X 14.6.12(7463)

Pin=100mW/Area Scan (61x91x1): Interpolated grid: dx=10 mm, dy=10 mm Maximum value of SAR (interpolated) = 16.6 W/kg


Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm,

dz=2mm

Reference Value = 57.59 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 39.9 W/kg

SAR(1 g) = 7.72 W/kg; SAR(10 g) = 2.16 W/kg Maximum value of SAR (measured) = 16.6 W/kg



0 dB = 16.6 W/kg = 12.20 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,此報告結果僅對測試之緣品負責,同時此樣品僅保留00天。木報告表經太公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_and_conditions.htm and for electronic format documents, or fall findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 87 of 89

7. Uncertainty Budget

Measurement Uncertainty evaluation template for DUT SAR test (3-6G)

A	С	D	е		f	g	h=c * f / e	i=c * g / e	k
Source of Uncertainty	Tolerance/ Uncertainty	Probability Distributio	Div	Div Value	ci (1g)	ci (10g)	Standard uncertainty	Standard uncertainty	vi, or Veff
Measurement system									
Probe calibration	6.55%	N	1	1	1	1	6.55%	6.55%	∞
Isotropy , Axial	3.50%	R	√3	1.732	1	1	2.02%	2.02%	∞
Isotropy, Hemispherical	9.60%	R	√3	1.732	1	1	5.54%	5.54%	8
Modulation Response	2.40%	R	√3	1.732	1	1	1.40%	1.40%	∞
Boundary Effect	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Linearity	4.70%	R	√3	1.732	1	1	2.71%	2.71%	∞
Detection Limits	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Readout Electronics	0.30%	N	1	1	1	1	0.30%	0.30%	∞
Response time	0.80%	R	√3	1.732	1	1	0.46%	0.46%	∞
Integration Time	2.60%	R	√3	1.732	1	1	1.50%	1.50%	∞
Measurement drift (class A evaluation)	1.75%	R	√3	1.732	1	1	1.01%	1.01%	∞
RF ambient condition - noise	3.00%	R	√3	1.732	1	1	1.73%	1.73%	∞
RF ambient conditions - reflections	3.00%	R	√3	1.732	1	1	1.73%	1.73%	∞
Probe positioner Mechanical restrictions	0.40%	R	√3	1.732	1	1	0.23%	0.23%	∞
Probe Positioning with respect to phantom shell	2.90%	R	√3	1.732	1	1	1.67%	1.67%	~
Post-processing	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Max SAR Eval	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Test Sample related									
Test sample positioning	2.90%	N	1	1	1	1	2.90%	2.90%	M-1
Device Holder Uncertainty	3.60%	N	1	1	1	1	3.60%	3.60%	M-1
Drift of output power	5.00%	R	√3	1.732	1	1	2.89%	2.89%	∞
Phantom and Setup									
Phantom Uncertainty	4.00%	R	√3	1.732	1	1	2.31%	2.31%	∞
Liquid permittivity (mea.)	2.31%	N	1	1	0.64	0.43	1.48%	0.99%	М
Liquid Conductivity (mea.)	2.45%	N	1	1	0.6	0.49	1.47%	1.20%	М
Combined standard uncertainty		RSS					11.90%	11.81%	
Expant uncertainty (95% confidence interval), K=2							23.80%	23.62%	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 88 of 89

Measurement Uncertainty evaluation template for DUT SAR test (0.3-3G)

A	С	D	е		f	g	h=c * f / e	i=c * g / e	k
Source of Uncertainty	Tolerance/ Uncertainty	Probability Distributio	Div	Div Value	ci (1g)	ci (10g)	Standard uncertainty	Standard uncertainty	vi, or Veff
Measurement system									
Probe calibration	6.00%	N	1	1	1	1	6.00%	6.00%	∞
Isotropy , Axial	3.50%	R	√3	1.732	1	1	2.02%	2.02%	∞
Isotropy, Hemispherical	9.60%	R	√3	1.732	1	1	5.54%	5.54%	8
Modulation Response	2.40%	R	√3	1.732	1	1	1.40%	1.40%	∞
Boundary Effect	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Linearity	4.70%	R	√3	1.732	1	1	2.71%	2.71%	∞
Detection Limits	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Readout Electronics	0.30%	N	1	1	1	1	0.30%	0.30%	8
Response time	0.80%	R	√3	1.732	1	1	0.46%	0.46%	8
Integration Time	2.60%	R	√3	1.732	1	1	1.50%	1.50%	8
Measurement drift (class A evaluation)	1.75%	R	√3	1.732	1	1	1.01%	1.01%	8
RF ambient condition - noise	3.00%	R	√3	1.732	1	1	1.73%	1.73%	8
RF ambient conditions - reflections	3.00%	R	√3	1.732	1	1	1.73%	1.73%	8
Probe positioner Mechanical restrictions	0.40%	R	√3	1.732	1	1	0.23%	0.23%	8
Probe Positioning with respect to phantom shell	2.90%	R	√3	1.732	1	1	1.67%	1.67%	8
Post-processing	1.00%	R	√3	1.732	1	1	0.58%	0.58%	8
Max SAR Eval	1.00%	R	√3	1.732	1	1	0.58%	0.58%	8
Test Sample related									
Test sample positioning	2.90%	N	1	1	1	1	2.90%	2.90%	M-1
Device Holder Uncertainty	3.60%	N	1	1	1	1	3.60%	3.60%	M-1
Drift of output power	5.00%	R	√3	1.732	1	1	2.89%	2.89%	∞
Phantom and Setup									
Phantom Uncertainty	4.00%	R	√3	1.732	1	1	2.31%	2.31%	∞
Liquid permittivity (mea.)	1.29%	N	1	1	0.64	0.43	0.83%	0.55%	М
Liquid Conductivity (mea.)	2.28%	N	1	1	0.6	0.49	1.37%	1.12%	М
Combined standard uncertainty		RSS					11.53%	11.48%	
Expant uncertainty (95% confidence interval), K=2							23.06%	22.95%	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 89 of 89

Appendixes

Refer to separated files for the following appendixes.

ES2019B0007 SAR_Appendix A Photographs

ES2019B0007 SAR_Appendix B DAE & Probe Cal. Certificate

ES2019B0007 SAR_Appendix C Phantom Description & Dipole Cal. Certificate

- End of report -

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司