



Middy antenna Measurement Report CEB005L CEB005R

Manufacturing name: Dongguan Dongcheng Tymphany Acoustic Technology Co., Ltd.

Address: 135 Shijie Keji East Road, Dongguan City, Guangdong Province, Ching

Measurement Setup






Free Space

Phantom Head

Return Loss – Free Space




Left Side

Return Loss – Phantom Head


E5071C Network Analyzer



3 Views of Antenna




2D Radiation – Free space L




| | ZX plane | | ZY plane | | XY plane | |
|--------------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|
| Frequency [MHz] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] |
| 2400 | -7.08 | -9.45 | -6.51 | -9.91 | -7.36 | -9.14 |
| 2450 | -6.41 | -8.23 | -5.75 | -8.92 | -6.60 | -8.11 |
| 2500 | -7.80 | -10.29 | -7.92 | -10.81 | -8.03 | -9.84 |

2D Radiation – Free space R




| ZX plane | | lane | ZY plane | | XY plane | |
|--------------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|
| Frequency [MHz] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] |
| 2400 | -8.39 | -10.42 | -5.70 | -9.15 | -8.18 | -10.22 |
| 2450 | -7.07 | -8.90 | -5.59 | -8.06 | -6.86 | -8.29 |
| 2500 | -8.61 | -10.44 | -7.81 | -9.91 | -8.17 | -10.15 |

2D Radiation – Phantom Head L



| | ZX plane | | ZY plane | | XY plane | |
|--------------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|
| Frequency [MHz] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] |
| 2400 | -5.70 | -9.67 | -6.93 | -10.57 | -6.38 | -10.07 |
| 2450 | -5.38 | -9.47 | -6.43 | -10.37 | -5.48 | -9.45 |
| 2500 | -7.07 | -11.09 | -8.59 | -12.16 | -7.20 | -11.36 |

2D Radiation – Phantom Head R



| | ZX plane | | ZY plane | | XY plane | |
|--------------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|
| Frequency [MHz] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] | Max Value [dB] | Average [dB] |
| 2400 | -5.38 | -10.40 | -8.49 | -11.89 | -7.46 | -10.48 |
| 2450 | -4.84 | -9.89 | -7.55 | -10.96 | -6.12 | -9.53 |
| 2500 | - 6. 77 | -11.35 | -9.52 | -12.57 | -7.03 | -10.99 |

Antenna Efficiency and Gain

| | 單體法 | 則試 | 上人頭測試 | | |
|---------------------------|---------------|-------|-------|-------|--|
| | L | R | L | R | |
| Maximum Efficiency (%) | 15.61 | 15.32 | 10.93 | 10.32 | |
| Maximum Gain (dBi) | - 4.77 | -3.68 | -5.23 | -4.41 | |

Antenna size/photo

