



Prüfbericht-Nr.: <i>Test report no.:</i>	CN217P5O (P15C-2.4G) 001	Auftrags-Nr.: <i>Order no.:</i>	238515716	Seite 1 von 27 Page 1 of 27	
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2021-05-27		
Auftraggeber: <i>Client:</i>	HP Inc. 3390 East Harmony Road, Mailstop 66, Fort Collins, CO 80528, United States				
Prüfgegenstand: <i>Test item:</i>	Wireless adapter				
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	CL002WA1				
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (2.4GHz)				
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247				
Wareneingangsdatum: <i>Date of sample receipt:</i>	2021-06-21				
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003075904-021 A003075904-004				
Prüfzeitraum: <i>Testing period:</i>	2021-07-05 - 2021-07-10				
Ort der Prüfung: <i>Place of testing:</i>	EMC/RF Taipei Testing Site				
Prüflaboratorium: <i>Testing laboratory:</i>	Taipei Testing Laboratories				
Prüfergebnis*: <i>Test result*:</i>	Pass				
überprüft von: <i>compiled by:</i>		genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	2021-07-15	Ausstellungsdatum: <i>Issue date:</i>	2021-07-15		
Stellung / Position:	Senior Project Manager	Stellung / Position:	Senior Project Manager		
Sonstiges / Other:					
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>				
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar	5 = mangelhaft N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable	5 = poor N/T = not tested
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>					

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
5.1.3	15.247(a)(2)	6 dB Bandwidth	Pass
5.1.3	2.1049	99% Occupied Bandwidth	Pass
5.1.4	15.247(e)	Power Spectral Density	Pass
5.1.5	15.247(d)	Conducted Spurious Emissions and Band Edges	Pass
5.1.6	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	5
1. GENERAL REMARKS	6
1.1 COMPLEMENTARY MATERIALS.....	6
1.2 DECISION RULE OF CONFORMITY	6
2. TEST SITES	7
2.1 TEST LABORATORY	7
2.2 TEST FACILITY.....	7
2.3 TRACEABILITY	8
2.4 CALIBRATION	8
2.5 MEASUREMENT UNCERTAINTY	8
3. GENERAL PRODUCT INFORMATION.....	9
3.1 PRODUCT FUNCTION AND INTENDED USE	9
3.2 SYSTEM DETAILS AND RATINGS.....	9
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
3.4 SUBMITTED DOCUMENTS.....	10
4. TEST SET-UP AND OPERATION MODES.....	11
4.1 PRINCIPLE OF CONFIGURATION SELECTION	11
4.2 TEST OPERATION AND TEST SOFTWARE.....	12
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	13
4.4 TEST SETUP DIAGRAM	14
5. TEST RESULTS	15
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	15
5.1.1 <i>Antenna Requirement</i>	<i>15</i>
5.1.2 <i>Peak Output Power</i>	<i>16</i>
5.1.3 <i>6 dB Bandwidth and 99% Occupied Bandwidth.....</i>	<i>18</i>
5.1.4 <i>Power Spectral Density.....</i>	<i>19</i>
5.1.5 <i>Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth.....</i>	<i>20</i>
5.1.6 <i>Radiated Spurious Emissions and Band Edges</i>	<i>21</i>
5.2 MAINS EMISSION	26
5.2.1 <i>Mains Conducted Emission.....</i>	<i>26</i>

Prüfbericht - Nr.: CN217P50 (P15C-2.4G) 001
Test Report No.

Seite 4 von 27
Page 4 of 27

APPENDIX A - TEST RESULT OF CONDUCTED

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: CN217P50 (P15C-2.4G) 001
Test Report No.

Seite 5 von 27
Page 5 of 27

HISTORY OF THIS TEST REPORT

Report No.	Description	Date Issued
CN217P50 (P15C-2.4G) 001	Original Release	2021-07-15

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Conducted

Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10:2013
KDB 558074 D01 15.247 Meas Guidance v05r02

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 226631
ISED Registration No.: 25563

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless adapter. It contains a 2.4GHz compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Wireless adapter
Type Identification	CL002WA1
FCC ID	B94-CL002WA1

Technical Specification of EUT

Item	EUT information
Operating Frequency	2405.35 MHz ~ 2477.35 MHz
Channel Number	37
Operation Voltage	5 Vdc
Modulation	Pi/4 DQPSK
Maximum Output Power (mW)	2.77
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.3

Note: There're two antennas (Ant 1 and Ant 2) used for 2.4GHz function and supports SISO mode only.

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

Frequency (MHz)	Power Setting
2405.35	0x08
2439.35	0x08
2477.35	0x08

4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	VMItest-1.1.6.56
---------------	------------------

The samples were used as follows:

A003075904-021

A003075904-004

Full test was applied on all test modes, but only worst case was shown.

EUT Configure Mode	Applicable To			Mains Conducted Emission	Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz		
-	√	√	√	√	-

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **Z-plane**.
2. "-" means no effect.

Antenna Port Conducted Measurement

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)
ANT 1 / ANT 2 (Power)	2405.35 to 2477.35	2405.35, 2439.35, 2477.35
ANT 2 (other conducted test)	2405.35 to 2477.35	2405.35, 2439.35, 2477.35

Note: Based on the worst case of conducted power, only Ant 2 was performed for the full tests.

Radiated Spurious Emissions (Above 1 GHz)

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)
ANT 2	2405.35 to 2477.35	2405.35, 2439.35, 2477.35

Radiated Spurious Emissions (Below 1 GHz)

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)
ANT 2	2405.35 to 2477.35	2479.35

Mains Conducted Emission

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)
ANT 2	2405.35 to 2477.35	2479.35

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	23.9 °C	65.4 %	Stanislas Charles
Radiated Spurious Emissions above 1 GHz	21.3-23.3 °C	56-58 %	Temo Chen
Radiated Spurious Emissions below 1 GHz	21.3-23.3 °C	56-58 %	Temo Chen
Mains Conducted Emission	19.5 °C	61 %	Simon Tsai

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


None

Support Unit


Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
1	Notebook	HP	15-da1046TX	CND911MY2	No	No	-	Radiated Emission
2	Adaptor	HP	TPN-LA16	N/A	Yes	No	180	
1	Adapter	HP	TPN-CA16	N/A	Yes	No	180	Mains Conducted
2	Notebook	HP	15s-du0007TX	CND93662VF	No	No	-	

4.4 Test Setup Diagram

<Radiated Spurious Emissions mode>



<Mains Conducted Emission mode>



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the antenna information is as listed below. The antenna is with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Antenna	Antenna Type	Antenna Gain (dBi)
Ant 1	PCB Antenna	1.1
Ant 2	PCB Antenna	3.26

Refer to EUT photo for details.

5.1.2 Peak Output Power

Limit 1 watt (30 dBm)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2021/3/24	2022/3/23	2021/7/5	2021/7/5
Power Sensor	Anritsu	MA2411B	1725269	2021/3/24	2022/3/23	2021/7/5	2021/7/5

Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Test Result
Peak Output Power
<Ant 1>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2405.35	4.16	2.61	30
Middle Channel	2439.35	4.11	2.58	30
High Channel	2477.35	3.87	2.44	30

<Ant 2>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2405.35	4.43	2.77	30
Middle Channel	2439.35	4.38	2.74	30
High Channel	2477.35	4.14	2.59	30

Average Power
<Ant 1>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2405.35	1.73	1.49
Middle Channel	2439.35	1.63	1.46
High Channel	2477.35	1.46	1.40

<Ant 2>


Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2405.35	2.02	1.59
Middle Channel	2439.35	1.91	1.55
High Channel	2477.35	1.71	1.48

5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth

Limit The minimum 6 dB bandwidth shall be at least 500 kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV40	101512	2021/1/29	2022/1/28	2021/7/5	2021/7/5

Test Procedure

- a. Set resolution bandwidth (RBW) = 100 kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- f. For 99% occupied bandwidth measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A.


5.1.4 Power Spectral Density

Limit

The power spectral density shall not be greater than 8 dBm in any 3 kHz band.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV40	101512	2021/1/29	2022/1/28	2021/7/5	2021/7/5

Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d. Set the VBW $\geq 3 \times \text{RBW}$.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

Test Results

Please refer to Appendix A.


5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth

Limit

20dB (below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV40	101512	2021/1/29	2022/1/28	2021/7/5	2021/7/5

Test Procedure

Measurement procedure REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement procedure OOBE

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

Test Results

Please refer to Appendix A.

5.1.6 Radiated Spurious Emissions and Band Edges

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Signal Analyzer	R&S	FSV40	101509	2021/3/24	2022/3/23
Receiver	R&S	ESR7	102108	2021/3/17	2022/3/16
Bilog Antenna	SCHWARZBECK	VULB-9168	00950	2021/1/25	2022/1/24
Horn Antenna	ETS-Lindgren	3117	00218929	2020/11/6	2021/11/5
LF-AMP	Agilent	8447D	2727A05146	2021/2/1	2022/1/31
HF-AMP + AC source	EMCI	EMC051845SE	980635	2021/2/1	2022/1/31
HF-AMP + AC source	EMCI	EMC184045SE	980656	2021/2/9	2022/2/8
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2021/4/14	2022/4/13
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104EA	800057/4EA	2021/4/14	2022/4/13
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	802244/4	2021/4/14	2022/4/13
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	MY37203/4	2021/4/14	2022/4/13
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800897/2EA	2021/3/11	2022/3/10
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800902/2EA	2021/3/11	2022/3/10
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	801026/2EA	2021/3/11	2022/3/10
Loop Antenna	Chance Most	EMCILPA600 +calibration	287	2021/1/18	2022/1/17

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.

Prüfbericht - Nr.: **CN217P50 (P15C-2.4G) 001**
Test Report No.

Seite 25 von 27
Page 25 of 27

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

5.2 Mains Emission


5.2.1 Mains Conducted Emission

Limit

Mains Conducted Emission as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
TWO-LINE V-NETWORK	R&S	ENV216	1816064	2020/9/10	2021/9/9
EMI Test Receiver	R&S	ESCI	1816063	2020/11/17	2021/11/16
RF Cable	N/A	N/A	EMC-003	2020/11/15	2021/11/14

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.


Test Results

Please refer to Appendix B.

Appendix A: Test Results of Conducted Test


Test Result of 6 dB Bandwidth

Channel	Channel Frequency (MHz)	6 dB Bandwidth (kHz)	Limit (kHz)	Result
Low Channel	2405.35	1643.36	> 500	Pass
Middle Channel	2439.35	1638.36	> 500	Pass
High Channel	2477.35	1638.36	> 500	Pass




Test Result of 99% Occupied Bandwidth

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2405.35	1.913
Middle Channel	2439.35	1.913
High Channel	2477.35	1.918




Test Result of Power Spectral Density


Channel	Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	2405.35	-13.12	8	Pass
Middle Channel	2439.35	-13.54	8	Pass
High Channel	2477.35	-13.31	8	Pass



Test Result of Conducted Spurious Emissions, Tx Mode



Test Result of Conducted Band Edge, Tx Mode



Appendix B: Test Results of Radiated Spurious Emissions & Mains

Conducted Emission Test

Band Edges, 2.31GHz ~ 2.9GHz

SRD																																																																																																					
Low Channel (Horizontal) Peak	Low Channel (Vertical) Peak																																																																																																				
<div style="text-align: right; font-size: small;"> TÜV Rheinland Taiwan Ltd. No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.) Tel: +886-2172-1000 Fax: +886-2172-1322 </div> <div style="text-align: left; margin-top: 10px;"> <p style="text-align: right; font-size: x-small;">Date: 2021-07-10</p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: x-small;"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Read</th> <th>Limit</th> <th>Over</th> <th>APos</th> <th>TPos</th> <th>Remark</th> <th>Pol/Phase</th> <th>Note</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>53.65</td> <td>16.35</td> <td>37.30</td> <td>74.00</td> <td>-20.35</td> <td>100</td> <td>63 Peak</td> <td>Horizontal</td> </tr> <tr> <td>2</td> <td>2495.35</td> <td>100.04</td> <td>63.51</td> <td>37.33</td> <td>74.00</td> <td>26.04</td> <td>100</td> <td>63 Peak</td> <td>Horizontal</td> </tr> <tr> <td>3</td> <td>2814.21</td> <td>55.11</td> <td>16.92</td> <td>38.19</td> <td>74.00</td> <td>-18.89</td> <td>100</td> <td>63 Peak</td> <td>Horizontal</td> </tr> </tbody> </table> </div>	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			1	2390.00	53.65	16.35	37.30	74.00	-20.35	100	63 Peak	Horizontal	2	2495.35	100.04	63.51	37.33	74.00	26.04	100	63 Peak	Horizontal	3	2814.21	55.11	16.92	38.19	74.00	-18.89	100	63 Peak	Horizontal	<div style="text-align: right; font-size: small;"> TÜV Rheinland Taiwan Ltd. No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan(R.O.C.) Tel: +886-2172-1000 Fax: +886-2172-1322 </div> <div style="text-align: left; margin-top: 10px;"> <p style="text-align: right; font-size: x-small;">Date: 2021-07-10</p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: x-small;"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Read</th> <th>Limit</th> <th>Over</th> <th>APos</th> <th>TPos</th> <th>Remark</th> <th>Pol/Phase</th> <th>Note</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2358.50</td> <td>53.80</td> <td>16.53</td> <td>37.27</td> <td>74.00</td> <td>-20.20</td> <td>277</td> <td>237 Peak</td> <td>Vertical</td> </tr> <tr> <td>2</td> <td>2495.35</td> <td>99.43</td> <td>62.10</td> <td>37.33</td> <td>74.00</td> <td>25.43</td> <td>277</td> <td>237 Peak</td> <td>Vertical</td> </tr> <tr> <td>3</td> <td>2643.94</td> <td>55.05</td> <td>17.14</td> <td>37.91</td> <td>74.00</td> <td>-18.95</td> <td>277</td> <td>237 Peak</td> <td>Vertical</td> </tr> </tbody> </table> </div>	Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			1	2358.50	53.80	16.53	37.27	74.00	-20.20	277	237 Peak	Vertical	2	2495.35	99.43	62.10	37.33	74.00	25.43	277	237 Peak	Vertical	3	2643.94	55.05	17.14	37.91	74.00	-18.95	277	237 Peak	Vertical
Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note																																																																																												
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg																																																																																														
1	2390.00	53.65	16.35	37.30	74.00	-20.35	100	63 Peak	Horizontal																																																																																												
2	2495.35	100.04	63.51	37.33	74.00	26.04	100	63 Peak	Horizontal																																																																																												
3	2814.21	55.11	16.92	38.19	74.00	-18.89	100	63 Peak	Horizontal																																																																																												
Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note																																																																																												
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg																																																																																														
1	2358.50	53.80	16.53	37.27	74.00	-20.20	277	237 Peak	Vertical																																																																																												
2	2495.35	99.43	62.10	37.33	74.00	25.43	277	237 Peak	Vertical																																																																																												
3	2643.94	55.05	17.14	37.91	74.00	-18.95	277	237 Peak	Vertical																																																																																												


SRD

Low Channel (Horizontal) Average

Low Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2390.00	48.38	3.00	37.30	54.00	-13.62	100	63 Average	Horizontal	
2	2405.35	96.82	59.49	37.33	54.00	42.82	100	63 Average	Horizontal	
3	2814.21	41.93	3.74	38.19	54.00	-12.07	100	63 Average	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2358.50	40.41	3.14	37.27	54.00	-13.59	277	237 Average	Vertical	
2	2405.35	95.63	58.28	37.33	54.00	41.63	277	237 Average	Vertical	
3	2643.94	41.90	3.99	37.91	54.00	-12.10	277	237 Average	Vertical	


SRD

High Channel (Horizontal) Peak

High Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua, Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2384.93	52.97	15.67	37.30	74.00	-21.03	266	91	Peak	Horizontal	
2	2479.35	97.66	59.99	37.69	74.00	23.66	266	91	Peak	Horizontal	
3	2483.58	58.44	20.73	37.71	74.00	-15.56	266	91	Peak	Horizontal	




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua, Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2323.81	52.96	15.89	37.07	74.00	-21.04	269	243	Peak	Vertical	
2	2479.35	96.99	59.38	37.69	74.00	22.99	269	243	Peak	Vertical	
3	2484.76	55.46	17.74	37.72	74.00	-18.54	269	243	Peak	Vertical	

SRD
High Channel (Horizontal) Average
High Channel (Vertical) Average



TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec. 2, Fenhua, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2384.93	48.15	2.85	37.30	54.00	-13.85	266	91 Average	Horizontal	
2	2479.35	93.51	55.82	37.69	54.00	39.51	266	91 Average	Horizontal	
3	2483.50	46.15	8.44	37.71	54.00	-7.85	266	91 Average	Horizontal	




TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec. 2, Fenhua, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2323.81	48.19	3.12	37.07	54.00	-13.81	268	243 Average	Vertical	
2	2479.35	92.86	55.17	37.69	54.00	38.86	268	243 Average	Vertical	
3	2484.76	45.92	8.20	37.72	54.00	-8.08	268	243 Average	Vertical	

Spurious Emissions, Tx Mode, 9kHz ~ 30MHz
SRD
High Channel (Open) 9kHz~150kHz
High Channel (Open) 150kHz~30MHz



TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.01	77.22	2.17	75.05	124.57	-47.35	100	344 QP	Open
2	0.03	70.93	1.29	69.64	118.75	-47.82	100	257 QP	Open
3	0.05	61.83	-1.50	63.33	113.01	-51.18	100	219 QP	Open
4	0.08	57.39	-1.93	59.32	109.11	-51.72	100	353 QP	Open
5	0.10	54.39	-2.83	57.22	107.60	-53.21	100	289 QP	Open
6	0.12	52.00	-4.33	56.33	105.97	-53.97	100	175 QP	Open




TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.76	55.55	12.61	42.94	70.00	-14.45	100	27 QP	Open
2	4.43	48.88	12.36	36.52	69.50	-20.62	100	337 QP	Open
3	9.76	50.72	12.53	38.19	69.50	-18.78	100	100 QP	Open
4	16.21	50.74	12.88	37.86	69.50	-18.76	100	33 QP	Open
5	21.74	50.80	12.37	38.43	69.50	-18.70	100	287 QP	Open
6	26.06	53.61	13.13	40.48	69.50	-15.89	100	70 QP	Open

SRD
High Channel (Close) 9kHz~150kHz
High Channel (Close) 150kHz~30MHz



TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.01	75.96	1.13	74.83	124.23	-48.27	100	245 QP	Close
2	0.04	66.34	-0.66	67.00	116.23	-49.89	100	18 QP	Close
3	0.07	58.15	-2.94	61.09	110.62	-52.47	100	8 QP	Close
4	0.09	56.59	-2.31	58.90	108.78	-52.19	100	267 QP	Close
5	0.12	52.43	-4.05	56.48	106.22	-53.79	100	304 QP	Close
6	0.14	51.91	-3.69	55.08	104.83	-52.92	100	336 QP	Close



TÜV Rheinland Taiwan Ltd.
 No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
 Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	0.01	54.31	11.79	42.52	69.41	-15.10	100	161 QP	Close
2	3.98	49.23	12.55	36.68	69.50	-20.27	100	80 QP	Close
3	7.46	48.59	11.32	37.27	69.50	-20.91	100	163 QP	Close
4	14.33	50.41	12.42	37.99	69.50	-19.09	100	167 QP	Close
5	22.04	50.14	11.57	38.57	69.50	-19.36	100	300 QP	Close
6	25.66	51.98	11.70	40.28	69.50	-17.52	100	124 QP	Close

Spurious Emissions, Tx Mode, 30MHz ~ 1GHz


SRD

High Channel (Horizontal)

High Channel (Vertical)




TUV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	Apos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	49.01	23.92	29.94	-6.02	48.00	-16.08	200	214 QP	Horizontal
2	181.18	26.38	37.22	-10.82	43.50	-17.28	200	368 QP	Horizontal
3	168.03	23.84	29.65	-5.81	43.50	-19.66	100	127 QP	Horizontal
4	506.76	29.07	30.42	-1.35	46.00	-16.93	100	358 QP	Horizontal
5	657.78	31.39	30.37	1.02	46.00	-14.61	100	25 QP	Horizontal
6	836.88	34.08	30.11	3.97	46.00	-11.92	100	247 QP	Horizontal



TUV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	Apos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	72.00	23.27	32.06	-8.79	48.00	-16.73	100	248 QP	Vertical
2	159.30	24.62	30.37	-5.75	43.50	-18.88	200	129 QP	Vertical
3	423.92	27.08	29.55	-2.47	46.00	-18.92	100	299 QP	Vertical
4	593.76	30.34	30.13	0.21	46.00	-15.66	200	289 QP	Vertical
5	781.63	31.95	30.17	1.78	46.00	-14.05	100	106 QP	Vertical
6	826.18	33.87	30.11	3.76	46.00	-12.13	110	360 QP	Vertical

Spurious Emissions, Tx Mode, 1GHz ~ 26.5GHz


SRD

Low Channel (Horizontal)

Low Channel (Vertical)




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note	
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4810.70	48.90	50.30	-9.40	74.00	-33.10	398	360	Peak	Horizontal



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read	Limit	Over	APos	TPos	Remark	Pol/Phase	Note	
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4810.70	43.09	52.49	-9.40	74.00	-30.91	100	0	Peak	Vertical


SRD

Middle Channel (Horizontal)

Middle Channel (Vertical)




TUV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenliiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1 4878.70	38.96	48.32	-9.36	74.00	-35.04	400	360	Peak	Horizontal	



TUV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenliiao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1 4878.70	39.13	48.49	-9.36	74.00	-34.87	100	296	Peak	Vertical	


SRD

High Channel (Horizontal)

High Channel (Vertical)




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Read Level	Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dB/m	dBuV/m	dB	cm	deg		
1 4958.70	40.01	49.28	-9.27	74.00	-33.99	100	37 Peak	Horizontal



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec. 2, Fenhua Rd., Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Read Level	Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dB/m	dBuV/m	dB	cm	deg		
1 4958.70	40.36	49.63	-9.27	74.00	-33.64	100	260 Peak	Vertical

Mains Conducted Emission, 150kHz ~ 30MHz

Worst Band

(Line)


(Neutral)



TUV Rheinland Taiwan Ltd(New Taipei City Branch).
No. 458-19, Sec. 2, Fenliao Rd., Linkou Dist., New Taipei City 244
Tel:+886-2172-1000 Fax:+886-2172-1322




TUV Rheinland Taiwan Ltd(New Taipei City Branch).
No. 458-19, Sec. 2, Fenliao Rd., Linkou Dist., New Taipei City 244
Tel:+886-2172-1000 Fax:+886-2172-1322



Trace: 1

	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase	Note
	MHz	dBuV	dB	dBuV	dBuV	dB			
1	0.156	36.82	9.66	46.48	65.67	-19.19	QP	line1	
2	0.156	20.61	9.66	30.27	55.67	-25.40	Average	line1	
3	0.364	30.90	9.65	40.55	58.63	-18.08	QP	line1	
4	0.364	27.49	9.65	37.14	48.63	-11.49	Average	line1	
5	0.958	7.58	9.67	17.25	56.00	-38.75	QP	line1	
6	0.958	2.57	9.67	12.24	46.00	-33.76	Average	line1	
7	3.249	8.62	9.70	18.32	56.00	-37.68	QP	line1	
8	3.249	2.09	9.70	11.79	46.00	-34.21	Average	line1	
9	7.140	10.89	9.74	20.63	60.00	-39.37	QP	line1	
10	7.140	5.15	9.74	14.89	50.00	-35.11	Average	line1	
11	16.251	9.67	9.75	19.42	60.00	-40.58	QP	line1	
12	16.251	2.90	9.75	12.65	50.00	-37.35	Average	line1	



Trace: 1

	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase	Note
	MHz	dBuV	dB	dBuV	dBuV	dB			
1	0.158	36.80	9.68	46.48	65.59	-19.11	QP	neutral	
2	0.158	19.72	9.68	29.40	55.59	-26.19	Average	neutral	
3	0.231	25.65	9.67	35.32	62.40	-27.08	QP	neutral	
4	0.231	10.66	9.67	20.33	52.40	-32.07	Average	neutral	
5	0.377	21.34	9.66	31.00	58.34	-27.34	QP	neutral	
6	0.377	8.83	9.66	18.49	48.34	-29.85	Average	neutral	
7	2.911	7.32	9.71	17.03	56.00	-38.97	QP	neutral	
8	2.911	0.45	9.71	10.16	46.00	-35.84	Average	neutral	
9	7.810	12.55	9.77	22.32	60.00	-37.68	QP	neutral	
10	7.810	6.81	9.77	16.58	50.00	-33.42	Average	neutral	
11	19.061	10.64	9.83	20.47	60.00	-39.53	QP	neutral	
12	19.061	5.62	9.83	15.45	50.00	-34.55	Average	neutral	