



FCC SAR TEST REPORT

FCC ID : B94-RTL8852AES
Equipment : 11ax RTL8852AE Combo module
Brand Name : REALTEK
Model Name : RTL8852AE
Applicant : HP Inc.
3390 East Harmony Road, Fort Collins Colorado, USA 80528
Standard : FCC 47 CFR Part 2 (2.1093)

The product was received on Apr 15, 2021 and testing was started from Apr 30, 2021 and completed on May 01, 2021. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager



Sporton International Inc. EMC & Wireless Communications Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan



Table of Contents

1. Statement of Compliance 4

2. Guidance Applied..... 4

3. Equipment Under Test (EUT) Information 5

 3.1 General Information 5

 3.2 Sensor Triggering angle and power verification 7

4. RF Exposure Limits.....15

 4.1 Uncontrolled Environment.....15

 4.2 Controlled Environment.....15

5. Specific Absorption Rate (SAR).....16

 5.1 Introduction16

 5.2 SAR Definition.....16

6. System Description and Setup17

 6.1 Test Site Location.....17

 6.2 E-Field Probe18

 6.3 Data Acquisition Electronics (DAE)18

 6.4 Phantom.....19

 6.5 Device Holder.....20

7. Measurement Procedures21

 7.1 Spatial Peak SAR Evaluation.....21

 7.2 Power Reference Measurement.....22

 7.3 Area Scan22

 7.4 Zoom Scan.....23

 7.5 Volume Scan Procedures.....23

 7.6 Power Drift Monitoring.....23

8. Test Equipment List24

9. System Verification25

 9.1 Tissue Verification25

 9.2 System Performance Check Results.....26

10. RF Exposure Positions26

 10.1 SAR Testing for Tablet.....26

11. WiFi/Bluetooth Output Power (Unit: dBm)27

12. Antenna Location39

13. SAR Test Exclusion Table41

14. SAR Test Results42

 14.1 Body SAR43

15. Simultaneous Transmission Analysis44

 15.1 Body Exposure Conditions44

16. Uncertainty Assessment45

17. References45

Appendix A. Plots of System Performance Check

Appendix B. Plots of High SAR Measurement

Appendix C. DASy Calibration Certificate

Appendix D. Test Setup Photos



History of this test report

Report No.	Version	Description	Issued Date
FA141502	01	Initial issue of report	May. 19, 2021



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for HP Inc., 11ax RTL8852AE Combo module, RTL8852AE, are as follows.

Equipment Class	Frequency Band		Highest SAR Summary	Highest Simultaneous Transmission 1g SAR (W/kg)
			Body	
			1g SAR (W/kg)	
DTS	WLAN	2.4GHz WLAN	0.49	0.52
NII		5GHz WLAN	0.49	0.52
DSS	2.4GHz Band	Bluetooth	0.03	0.52
Date of Testing:			2021/4/30 ~ 2021/5/1	

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Jason Wang
Report Producer: Carlie Tsai

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02



3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	11ax RTL8852AE Combo module
Brand Name	REALTEK
Model Name	RTL8852AE
FCC ID	B94-RTL8852AES
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2400 MHz ~ 2483.5 MHz WLAN U-NII 1: 5150 MHz ~ 5250 MHz WLAN U-NII 2: 5250 MHz ~ 5350 MHz WLAN U-NII 3: 5470 MHz ~ 5725 MHz WLAN U-NII 4: 5725 MHz ~ 5825 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/HE20/HE40/HE80 Bluetooth BR/EDR/LE
Remark:	
1. This device had two WLAN antenna vendors, RF exposure evaluation is selected High-Tek as the main tested, AWAN will spot check worst case found in High-Tek.	
2. This device is convertible type notebook PC, and there have Laptop and Tablet two usage way, when end user is used different mode which the device will according current mode to limit different maximum power.	

Host Information	
Equipment Name	Notebook PC
Brand Name	HP
Model Name	TPN-W149
EUT Stage	Production Unit

Antenna Information (NB mode)									
Antenna 1	Ant. Type	PIFA	connector	High-Tek	Antenna 2	Ant. Type	PIFA	connector	High-Tek
	Model No.	025.901S3.0031 (0ACAR020015N)				Model No.	025.901S3.0021 (0ACAR020014N)		
	Peak Gain (dBi)					Peak Gain (dBi)			
	2400~2483.5MHz	-1.98	5470~5725MHz	0.83		2400~2483.5MHz	-1.42	5470~5725MHz	0.52
	5150~5250MHz	0.47	5725~5850MHz	0.83		5150~5250MHz	-0.73	5725~5850MHz	1.71
5250~5350MHz	0.47			5250~5350MHz	-0.53				
Antenna 1	Ant. Type	PIFA	connector	WNC	Antenna 2	Ant. Type	PIFA	connector	WNC
	Model No.	025.901S3.0011 (81EABD15.G36)				Model No.	025.901S3.0001 (81EABD15.G35)		
	Peak Gain (dBi)					Peak Gain (dBi)			
	2400~2483.5MHz	1.37	5470~5725MHz	-0.1		2400~2483.5MHz	0.6	5470~5725MHz	-0.46
	5150~5250MHz	0.62	5725~5850MHz	-0.1		5150~5250MHz	1.21	5725~5850MHz	-0.46
5250~5350MHz	0.62			5250~5350MHz	1.21				

Antenna Information (TB mode)									
Antenna 1	Ant. Type	PIFA	connector	High-Tek	Antenna 2	Ant. Type	PIFA	connector	High-Tek
	Model No.	025.901S3.0031 (0ACAR020015N)				Model No.	025.901S3.0021 (0ACAR020014N)		
	Peak Gain (dBi)					Peak Gain (dBi)			
	2400~2483.5MHz	-1.65	5470~5725MHz	-0.18		2400~2483.5MHz	-1.5	5470~5725MHz	-0.32
	5150~5250MHz	-0.45	5725~5850MHz	0.06		5150~5250MHz	2.63	5725~5850MHz	-0.24
5250~5350MHz	-0.32			5250~5350MHz	2.63				
Antenna 1	Ant. Type	PIFA	connector	WNC	Antenna 2	Ant. Type	PIFA	connector	WNC
	Model No.	025.901S3.0011 (81EABD15.G36)				Model No.	025.901S3.0001 (81EABD15.G35)		
	Peak Gain (dBi)					Peak Gain (dBi)			
	2400~2483.5MHz	1.03	5470~5725MHz	1.64		2400~2483.5MHz	-0.12	5470~5725MHz	1.09
	5150~5250MHz	-1.04	5725~5850MHz	1.64		5150~5250MHz	1.19	5725~5850MHz	1.09
5250~5350MHz	1.05			5250~5350MHz	-1.33				



3.2 Sensor Triggering angle and power verification

General Note:

1. This device is convertible type notebook PC, and there have Laptop and Tablet two usage way, when end user is used different mode which the device will according current mode to limit different maximum power and the power verification in different usage mode was following below step:

For Lid close mode change to Tablet mode

Step 1: The device is in lid close mode, and then opens the screen rotate in 3 degree step until change to Laptop mode

Step 2: then the screen rotate back by at least 5 until the power is returned to lid close power table

Step 3: Again rotate the screen to laptop mode, but in 1 degree steps rotate the screen to the laptop mode until it is at least 5 mm past the triggering point.

Step 3: then move in 3 degree step until change to tablet power level (Reduce Power mode)

Step 4: the same procedure step 1 to Step 3 is used for Laptop mode until change to Tablet mode

Step 5: When Lid angle converting different configure there has +/- 5 degree tolerance. The procedures will accord step1 to step4 to verify the operation of the triggering mechanism whether it is within this tolerance range.

For Tablet mode until change to Lid close mode

The process is then reversed by rotate the screen from tablet mode change to lid close mode according to steps 1) to 4), to check triggering release

when the screen angle is from 0 degree to 360 degree								
Screen angle (degree) v.s. power	Wireless		WLAN Ant 1/2					
	Band		2.4GHz WLAN	5.2GHz WLAN	5.3GHz WLAN	5.5GHz WLAN	5.8GHz WLAN	
Lid Close	0		standby	standby	standby	standby	standby	
	10		standby	standby	standby	standby	standby	
	20		standby	standby	standby	standby	standby	
	30		standby	standby	standby	standby	standby	
	31		standby	standby	standby	standby	standby	
	32		standby	standby	standby	standby	standby	
	33		standby	standby	standby	standby	standby	
	34		standby	standby	standby	standby	standby	
	Laptop	35		23.5	22.5	22.5	22.5	23.5
		36		23.5	22.5	22.5	22.5	23.5
		37		23.5	22.5	22.5	22.5	23.5
		38		23.5	22.5	22.5	22.5	23.5
		39		23.5	22.5	22.5	22.5	23.5
		40		23.5	22.5	22.5	22.5	23.5
		50		23.5	22.5	22.5	22.5	23.5
		60		23.5	22.5	22.5	22.5	23.5
		70		23.5	22.5	22.5	22.5	23.5
		80		23.5	22.5	22.5	22.5	23.5
		90		23.5	22.5	22.5	22.5	23.5
		100		23.5	22.5	22.5	22.5	23.5
		110		23.5	22.5	22.5	22.5	23.5
120			23.5	22.5	22.5	22.5	23.5	
125			23.5	22.5	22.5	22.5	23.5	
126		23.5	22.5	22.5	22.5	23.5		
127		23.5	22.5	22.5	22.5	23.5		
128		23.5	22.5	22.5	22.5	23.5		
129		23.5	22.5	22.5	22.5	23.5		
Tablet	130		23.5	22.5	22.5	22.5	23.5	
	135		23.5	22.5	22.5	22.5	23.5	
	136		23.5	22.5	22.5	22.5	23.5	
	137		23.5	22.5	22.5	22.5	23.5	
	138		23.5	22.5	22.5	22.5	23.5	
	139		23.5	22.5	22.5	22.5	23.5	
140		18.5	18.0	18.0	17.5	17.0		



		141	18.5	18.0	18.0	17.5	17.0
		142	18.5	18.0	18.0	17.5	17.0
		143	18.5	18.0	18.0	17.5	17.0
		144	18.5	18.0	18.0	17.5	17.0
		145	18.5	18.0	18.0	17.5	17.0
		150	18.5	18.0	18.0	17.5	17.0
		160	18.5	18.0	18.0	17.5	17.0
		170	18.5	18.0	18.0	17.5	17.0
		180	18.5	18.0	18.0	17.5	17.0
		190	18.5	18.0	18.0	17.5	17.0
		195	18.5	18.0	18.0	17.5	17.0
		196	18.5	18.0	18.0	17.5	17.0
		197	18.5	18.0	18.0	17.5	17.0
		198	18.5	18.0	18.0	17.5	17.0
		199	18.5	18.0	18.0	17.5	17.0
		200	18.5	18.0	18.0	17.5	17.0
		201	23.5	22.5	22.5	22.5	23.5
		202	23.5	22.5	22.5	22.5	23.5
		203	23.5	22.5	22.5	22.5	23.5
		204	23.5	22.5	22.5	22.5	23.5
		205	23.5	22.5	22.5	22.5	23.5
		210	23.5	22.5	22.5	22.5	23.5
		220	23.5	22.5	22.5	22.5	23.5
		230	23.5	22.5	22.5	22.5	23.5
		240	23.5	22.5	22.5	22.5	23.5
		250	23.5	22.5	22.5	22.5	23.5
		260	23.5	22.5	22.5	22.5	23.5
		270	23.5	22.5	22.5	22.5	23.5
		280	23.5	22.5	22.5	22.5	23.5
		290	23.5	22.5	22.5	22.5	23.5
		300	23.5	22.5	22.5	22.5	23.5
		310	23.5	22.5	22.5	22.5	23.5
		320	23.5	22.5	22.5	22.5	23.5
		330	23.5	22.5	22.5	22.5	23.5
		335	23.5	22.5	22.5	22.5	23.5
		336	23.5	22.5	22.5	22.5	23.5
		337	23.5	22.5	22.5	22.5	23.5
		338	23.5	22.5	22.5	22.5	23.5
		339	23.5	22.5	22.5	22.5	23.5
		340	23.5	22.5	22.5	22.5	23.5
		341	18.5	18.0	18.0	17.5	17.0
		342	18.5	18.0	18.0	17.5	17.0
		343	18.5	18.0	18.0	17.5	17.0
		344	18.5	18.0	18.0	17.5	17.0
		345	18.5	18.0	18.0	17.5	17.0
		350	18.5	18.0	18.0	17.5	17.0
		360	18.5	18.0	18.0	17.5	17.0
	Stand mode (Screen orientation is set to 0° and base is horizontal)	201	23.5	22.5	22.5	22.5	23.5
		202	23.5	22.5	22.5	22.5	23.5
		203	23.5	22.5	22.5	22.5	23.5
		204	23.5	22.5	22.5	22.5	23.5
		205	23.5	22.5	22.5	22.5	23.5
		210	23.5	22.5	22.5	22.5	23.5
		220	23.5	22.5	22.5	22.5	23.5
		230	23.5	22.5	22.5	22.5	23.5
		240	23.5	22.5	22.5	22.5	23.5



		250	23.5	22.5	22.5	22.5	23.5	
		260	23.5	22.5	22.5	22.5	22.5	23.5
		270	23.5	22.5	22.5	22.5	22.5	23.5
		280	23.5	22.5	22.5	22.5	22.5	23.5
		290	23.5	22.5	22.5	22.5	22.5	23.5
		300	23.5	22.5	22.5	22.5	22.5	23.5
		310	23.5	22.5	22.5	22.5	22.5	23.5
		320	23.5	22.5	22.5	22.5	22.5	23.5
		330	23.5	22.5	22.5	22.5	22.5	23.5
		335	23.5	22.5	22.5	22.5	22.5	23.5
		336	23.5	22.5	22.5	22.5	22.5	23.5
		337	23.5	22.5	22.5	22.5	22.5	23.5
		338	23.5	22.5	22.5	22.5	22.5	23.5
		339	23.5	22.5	22.5	22.5	22.5	23.5
		340	23.5	22.5	22.5	22.5	22.5	23.5
	Tent mode (Screen orientation is set to 180° and base is not horizontal)	201	18.5	18.0	18.0	17.5	17.0	
		202	18.5	18.0	18.0	17.5	17.0	
		203	18.5	18.0	18.0	17.5	17.0	
		204	18.5	18.0	18.0	17.5	17.0	
		205	18.5	18.0	18.0	17.5	17.0	
		210	18.5	18.0	18.0	17.5	17.0	
		220	18.5	18.0	18.0	17.5	17.0	
		230	18.5	18.0	18.0	17.5	17.0	
		240	18.5	18.0	18.0	17.5	17.0	
		250	18.5	18.0	18.0	17.5	17.0	
		260	18.5	18.0	18.0	17.5	17.0	
		270	18.5	18.0	18.0	17.5	17.0	
		280	18.5	18.0	18.0	17.5	17.0	
		290	18.5	18.0	18.0	17.5	17.0	
		300	18.5	18.0	18.0	17.5	17.0	
		310	18.5	18.0	18.0	17.5	17.0	
		320	18.5	18.0	18.0	17.5	17.0	
		330	18.5	18.0	18.0	17.5	17.0	
		335	18.5	18	18	17.5	17	
		336	18.5	18.0	18.0	17.5	17.0	
	337	18.5	18.0	18.0	17.5	17.0		
	338	18.5	18.0	18.0	17.5	17.0		
	339	18.5	18.0	18.0	17.5	17.0		
	340	18.5	18.0	18.0	17.5	17.0		
	Lid Close	0	standby	standby	standby	standby	standby	
		10	standby	standby	standby	standby	standby	
		20	standby	standby	standby	standby	standby	
		30	standby	standby	standby	standby	standby	
		31	standby	standby	standby	standby	standby	
		32	standby	standby	standby	standby	standby	
33		standby	standby	standby	standby	standby		
34		standby	standby	standby	standby	standby		
Book (screen orientation is 90° or 270°)	35	18.5	18.0	18.0	17.5	17.0		
	36	18.5	18.0	18.0	17.5	17.0		
	37	18.5	18.0	18.0	17.5	17.0		
	38	18.5	18.0	18.0	17.5	17.0		
	39	18.5	18.0	18.0	17.5	17.0		
	40	18.5	18.0	18.0	17.5	17.0		
	50	18.5	18.0	18.0	17.5	17.0		
	60	18.5	18.0	18.0	17.5	17.0		
70	18.5	18.0	18.0	17.5	17.0			



		80	18.5	18.0	18.0	17.5	17.0	
		90	18.5	18.0	18.0	17.5	17.0	
		100	18.5	18.0	18.0	17.5	17.0	
		110	18.5	18.0	18.0	17.5	17.0	
		120	18.5	18.0	18.0	17.5	17.0	
		130	18.5	18.0	18.0	17.5	17.0	
		140	18.5	18.0	18.0	17.5	17.0	
		150	18.5	18.0	18.0	17.5	17.0	
		160	18.5	18.0	18.0	17.5	17.0	
		170	18.5	18.0	18.0	17.5	17.0	
		180	18.5	18.0	18.0	17.5	17.0	
		190	18.5	18.0	18.0	17.5	17.0	
		195	18.5	18.0	18.0	17.5	17.0	
		196	18.5	18.0	18.0	17.5	17.0	
		197	18.5	18.0	18.0	17.5	17.0	
		198	18.5	18.0	18.0	17.5	17.0	
		199	18.5	18.0	18.0	17.5	17.0	
		200	18.5	18.0	18.0	17.5	17.0	
		Tablet (screen orientation is 90° or 270°)	201	23.5	22.5	22.5	22.5	23.5
			202	23.5	22.5	22.5	22.5	23.5
	203		23.5	22.5	22.5	22.5	23.5	
	204		23.5	22.5	22.5	22.5	23.5	
	205		23.5	22.5	22.5	22.5	23.5	
	210		23.5	22.5	22.5	22.5	23.5	
	220		23.5	22.5	22.5	22.5	23.5	
	230		23.5	22.5	22.5	22.5	23.5	
	240		23.5	22.5	22.5	22.5	23.5	
	250		23.5	22.5	22.5	22.5	23.5	
	260		23.5	22.5	22.5	22.5	23.5	
	270		23.5	22.5	22.5	22.5	23.5	
	280		23.5	22.5	22.5	22.5	23.5	
	290		23.5	22.5	22.5	22.5	23.5	
	300		23.5	22.5	22.5	22.5	23.5	
	310		23.5	22.5	22.5	22.5	23.5	
	320	23.5	22.5	22.5	22.5	23.5		
	330	23.5	22.5	22.5	22.5	23.5		
340	23.5	22.5	22.5	22.5	23.5			
350	23.5	22.5	22.5	22.5	23.5			
360	23.5	22.5	22.5	22.5	23.5			



when the screen angle is from 0 degree to 360 degree						
Screen angle (degree) v.s. power	Wireless		WLAN Ant 1/2			
	Band	2.4GHz WLAN	5.2GHz WLAN	5.3GHz WLAN	5.5GHz WLAN	5.8GHz WLAN
	Tablet					
	360	18.5	18.0	18.0	17.5	17.0
	350	18.5	18.0	18.0	17.5	17.0
	345	18.5	18.0	18.0	17.5	17.0
	344	18.5	18.0	18.0	17.5	17.0
	343	18.5	18.0	18.0	17.5	17.0
	342	18.5	18.0	18.0	17.5	17.0
	341	18.5	18.0	18.0	17.5	17.0
	340	23.5	22.5	22.5	22.5	23.5
	339	23.5	22.5	22.5	22.5	23.5
	338	23.5	22.5	22.5	22.5	23.5
	337	23.5	22.5	22.5	22.5	23.5
	336	23.5	22.5	22.5	22.5	23.5
	335	23.5	22.5	22.5	22.5	23.5
	330	23.5	22.5	22.5	22.5	23.5
	320	23.5	22.5	22.5	22.5	23.5
	310	23.5	22.5	22.5	22.5	23.5
	300	23.5	22.5	22.5	22.5	23.5
	290	23.5	22.5	22.5	22.5	23.5
	280	23.5	22.5	22.5	22.5	23.5
	270	23.5	22.5	22.5	22.5	23.5
	260	23.5	22.5	22.5	22.5	23.5
	250	23.5	22.5	22.5	22.5	23.5
	240	23.5	22.5	22.5	22.5	23.5
	230	23.5	22.5	22.5	22.5	23.5
	220	23.5	22.5	22.5	22.5	23.5
	210	23.5	22.5	22.5	22.5	23.5
	205	23.5	22.5	22.5	22.5	23.5
	204	23.5	22.5	22.5	22.5	23.5
	203	23.5	22.5	22.5	22.5	23.5
	202	23.5	22.5	22.5	22.5	23.5
	201	23.5	22.5	22.5	22.5	23.5
	200	18.5	18.0	18.0	17.5	17.0
	199	18.5	18.0	18.0	17.5	17.0
	198	18.5	18.0	18.0	17.5	17.0
	197	18.5	18.0	18.0	17.5	17.0
	196	18.5	18.0	18.0	17.5	17.0
	195	18.5	18.0	18.0	17.5	17.0
	190	18.5	18.0	18.0	17.5	17.0
	180	18.5	18.0	18.0	17.5	17.0
	170	18.5	18.0	18.0	17.5	17.0
	160	18.5	18.0	18.0	17.5	17.0
	150	18.5	18.0	18.0	17.5	17.0
	145	18.5	18.0	18.0	17.5	17.0
	144	18.5	18.0	18.0	17.5	17.0
	143	18.5	18.0	18.0	17.5	17.0
	142	18.5	18.0	18.0	17.5	17.0
	141	18.5	18.0	18.0	17.5	17.0
	140	18.5	18.0	18.0	17.5	17.0
	139	23.5	22.5	22.5	22.5	23.5
	138	23.5	22.5	22.5	22.5	23.5
	137	23.5	22.5	22.5	22.5	23.5
	136	23.5	22.5	22.5	22.5	23.5



		135	23.5	22.5	22.5	22.5	23.5	
		130	23.5	22.5	22.5	22.5	22.5	23.5
	Laptop	129	23.5	22.5	22.5	22.5	22.5	23.5
		128	23.5	22.5	22.5	22.5	22.5	23.5
		127	23.5	22.5	22.5	22.5	22.5	23.5
		126	23.5	22.5	22.5	22.5	22.5	23.5
		125	23.5	22.5	22.5	22.5	22.5	23.5
		120	23.5	22.5	22.5	22.5	22.5	23.5
		110	23.5	22.5	22.5	22.5	22.5	23.5
		100	23.5	22.5	22.5	22.5	22.5	23.5
		90	23.5	22.5	22.5	22.5	22.5	23.5
		80	23.5	22.5	22.5	22.5	22.5	23.5
		70	23.5	22.5	22.5	22.5	22.5	23.5
		60	23.5	22.5	22.5	22.5	22.5	23.5
		50	23.5	22.5	22.5	22.5	22.5	23.5
		40	23.5	22.5	22.5	22.5	22.5	23.5
		39	23.5	22.5	22.5	22.5	22.5	23.5
		38	23.5	22.5	22.5	22.5	22.5	23.5
		37	23.5	22.5	22.5	22.5	22.5	23.5
		36	23.5	22.5	22.5	22.5	22.5	23.5
		35	23.5	22.5	22.5	22.5	22.5	23.5
	Lid Close	34	standby	standby	standby	standby	standby	standby
		33	standby	standby	standby	standby	standby	standby
		32	standby	standby	standby	standby	standby	standby
		31	standby	standby	standby	standby	standby	standby
		30	standby	standby	standby	standby	standby	standby
		20	standby	standby	standby	standby	standby	standby
		10	standby	standby	standby	standby	standby	standby
	0	standby	standby	standby	standby	standby	standby	
	Stand mode (Screen orientation is set to 0° and base is horizontal)	340	23.5	22.5	22.5	22.5	22.5	23.5
		339	23.5	22.5	22.5	22.5	22.5	23.5
		338	23.5	22.5	22.5	22.5	22.5	23.5
		337	23.5	22.5	22.5	22.5	22.5	23.5
		336	23.5	22.5	22.5	22.5	22.5	23.5
		335	23.5	22.5	22.5	22.5	22.5	23.5
		330	23.5	22.5	22.5	22.5	22.5	23.5
		320	23.5	22.5	22.5	22.5	22.5	23.5
		310	23.5	22.5	22.5	22.5	22.5	23.5
		300	23.5	22.5	22.5	22.5	22.5	23.5
		290	23.5	22.5	22.5	22.5	22.5	23.5
		280	23.5	22.5	22.5	22.5	22.5	23.5
		270	23.5	22.5	22.5	22.5	22.5	23.5
		260	23.5	22.5	22.5	22.5	22.5	23.5
		250	23.5	22.5	22.5	22.5	22.5	23.5
		240	23.5	22.5	22.5	22.5	22.5	23.5
230		23.5	22.5	22.5	22.5	22.5	23.5	
220		23.5	22.5	22.5	22.5	22.5	23.5	
210		23.5	22.5	22.5	22.5	22.5	23.5	
205	23.5	22.5	22.5	22.5	22.5	23.5		
204	23.5	22.5	22.5	22.5	22.5	23.5		
203	23.5	22.5	22.5	22.5	22.5	23.5		
202	23.5	22.5	22.5	22.5	22.5	23.5		
201	23.5	22.5	22.5	22.5	22.5	23.5		
Tent mode (Screen orientation is set	340	18.5	18.0	18.0	17.5	17.0	17.0	
	339	18.5	18.0	18.0	17.5	17.0	17.0	
	338	18.5	18.0	18.0	17.5	17.0	17.0	



to 180° and base is not horizontal)	337	18.5	18.0	18.0	17.5	17.0
	336	18.5	18.0	18.0	17.5	17.0
	335	18.5	18.0	18.0	17.5	17.0
	330	18.5	18.0	18.0	17.5	17.0
	320	18.5	18.0	18.0	17.5	17.0
	310	18.5	18.0	18.0	17.5	17.0
	300	18.5	18.0	18.0	17.5	17.0
	290	18.5	18.0	18.0	17.5	17.0
	280	18.5	18.0	18.0	17.5	17.0
	270	18.5	18.0	18.0	17.5	17.0
	260	18.5	18.0	18.0	17.5	17.0
	250	18.5	18.0	18.0	17.5	17.0
	240	18.5	18.0	18.0	17.5	17.0
	230	18.5	18.0	18.0	17.5	17.0
	220	18.5	18.0	18.0	17.5	17.0
	210	18.5	18	18	17.5	17
	205	18.5	18.0	18.0	17.5	17.0
	204	18.5	18.0	18.0	17.5	17.0
	203	18.5	18.0	18.0	17.5	17.0
	202	18.5	18.0	18.0	17.5	17.0
201	18.5	18.0	18.0	17.5	17.0	
Tablet (screen orientation is 90° or 270°)	360	23.5	22.5	22.5	22.5	23.5
	350	23.5	22.5	22.5	22.5	23.5
	340	23.5	22.5	22.5	22.5	23.5
	330	23.5	22.5	22.5	22.5	23.5
	320	23.5	22.5	22.5	22.5	23.5
	310	23.5	22.5	22.5	22.5	23.5
	300	23.5	22.5	22.5	22.5	23.5
	290	23.5	22.5	22.5	22.5	23.5
	280	23.5	22.5	22.5	22.5	23.5
	270	23.5	22.5	22.5	22.5	23.5
	260	23.5	22.5	22.5	22.5	23.5
	250	23.5	22.5	22.5	22.5	23.5
	240	23.5	22.5	22.5	22.5	23.5
	230	23.5	22.5	22.5	22.5	23.5
	220	23.5	22.5	22.5	22.5	23.5
	210	23.5	22.5	22.5	22.5	23.5
	205	23.5	22.5	22.5	22.5	23.5
	204	23.5	22.5	22.5	22.5	23.5
	203	23.5	22.5	22.5	22.5	23.5
	202	23.5	22.5	22.5	22.5	23.5
201	23.5	22.5	22.5	22.5	23.5	
Book (screen orientation is 90° or 270°)	200	18.5	18.0	18.0	17.5	17.0
	199	18.5	18.0	18.0	17.5	17.0
	198	18.5	18.0	18.0	17.5	17.0
	197	18.5	18.0	18.0	17.5	17.0
	196	18.5	18.0	18.0	17.5	17.0
	195	18.5	18.0	18.0	17.5	17.0
	190	18.5	18.0	18.0	17.5	17.0
	180	18.5	18.0	18.0	17.5	17.0
	170	18.5	18.0	18.0	17.5	17.0
	160	18.5	18.0	18.0	17.5	17.0
	150	18.5	18.0	18.0	17.5	17.0
	140	18.5	18.0	18.0	17.5	17.0
130	18.5	18.0	18.0	17.5	17.0	
120	18.5	18.0	18.0	17.5	17.0	



		110	18.5	18.0	18.0	17.5	17.0
		100	18.5	18.0	18.0	17.5	17.0
		90	18.5	18.0	18.0	17.5	17.0
		80	18.5	18.0	18.0	17.5	17.0
		70	18.5	18.0	18.0	17.5	17.0
		60	18.5	18.0	18.0	17.5	17.0
		50	18.5	18.0	18.0	17.5	17.0
		40	18.5	18.0	18.0	17.5	17.0
		39	18.5	18.0	18.0	17.5	17.0
		38	18.5	18.0	18.0	17.5	17.0
		37	18.5	18.0	18.0	17.5	17.0
		36	18.5	18.0	18.0	17.5	17.0
		35	18.5	18.0	18.0	17.5	17.0
	Lid Close	34	standby	standby	standby	standby	standby
		33	standby	standby	standby	standby	standby
		32	standby	standby	standby	standby	standby
		31	standby	standby	standby	standby	standby
		30	standby	standby	standby	standby	standby
		20	standby	standby	standby	standby	standby
		10	standby	standby	standby	standby	standby
0	standby	standby	standby	standby	standby		



4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 Test Site Location


The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Test Site	EMC & Wireless Communications Laboratory		Wensan Laboratory		
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan		
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	


6.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE


6.4 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.5 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	2450MHz System Validation Kit ⁽²⁾	D2450V2	736	Aug. 31, 2018	Aug. 28, 2021
SPEAG	5GHz System Validation Kit ⁽²⁾	D5GHzV2	1006	Sep. 27, 2018	Sep. 24, 2021
SPEAG	Data Acquisition Electronics	DAE4	1311	Aug. 25, 2020	Aug. 24, 2021
SPEAG	Dosimetric E-Field Probe	EX3DV4	7625	Jan. 19, 2021	Jan. 18, 2022
Testo	Hygro meter	608-H1	45196600	Nov. 10, 2020	Nov. 09, 2021
R&S	BT Base Station	CBT32	100519	Jun. 04, 2020	Jun. 03, 2021
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Nov. 11, 2020	Nov. 10, 2021
Keysight	ENA Network Analyzer	E5071C	MY46101588	Jun. 10, 2020	Jun. 09, 2021
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 16, 2020	Sep. 15, 2021
LINE SEIKI	Digital Thermometer	DTM3000-spezial	2942	Nov. 06, 2020	Nov. 05, 2021
Anritsu	Power Meter	ML2495A	1419002	Aug. 19, 2020	Aug. 18, 2021
Anritsu	Power Sensor	MA2411B	1911176	Aug. 18, 2020	Aug. 17, 2021
Anritsu	Power Meter	ML2495A	1804003	Oct. 21, 2020	Oct. 20, 2021
Anritsu	Power Sensor	MA2411B	1726150	Oct. 21, 2020	Oct. 20, 2021
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 30, 2020	Jun. 29, 2021
Anritsu	Spectrum Analyzer	N9010A	MY53470118	Jan. 15, 2021	Jan. 14, 2022
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 21, 2020	Oct. 20, 2021
Mini-Circuits	Power Amplifier	ZVE-8G+	479102029	Aug. 26, 2020	Aug. 25, 2021
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Warison	Directional Coupler	WCOU-10-50S-10	WR889BMC4B1	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.



9. System Verification

9.1 Tissue Verification

The tissue dielectric parameters of tissue-equivalent media used for SAR measurements must be characterized within a temperature range of 18°C to 25°C, measured with calibrated instruments and apparatuses, such as network analyzers and temperature probes. The temperature of the tissue-equivalent medium during SAR measurement must also be within 18°C to 25°C and within ± 2°C of the temperature when the tissue parameters are characterized. The tissue dielectric measurement system must be calibrated before use. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements.

The liquid tissue depth was at least 15cm in the phantom for all SAR testing

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε _r)	Conductivity Target (σ)	Permittivity Target (ε _r)	Delta (σ) (%)	Delta (ε _r) (%)	Limit (%)	Date
2450	22.4	1.761	38.558	1.80	39.20	-2.17	-1.64	±5	2021/4/30
5250	22.4	4.623	36.916	4.71	35.95	-1.85	2.69	±5	2021/5/1
5600	22.4	4.974	36.191	5.07	35.50	-1.89	1.95	±5	2021/5/1
5750	22.4	5.101	36.180	5.22	35.35	-2.28	2.35	±5	2021/5/1

9.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Test Site	Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
SAR05	2021/4/30	2450	50	D2450V2-736	EX3DV4 - SN7625	DAE4 Sn1311	2.61	52.70	52.2	-0.95
SAR05	2021/5/1	5250	100	D5GHzV2-1006-5250	EX3DV4 - SN7625	DAE4 Sn1311	8.44	80.70	84.4	4.58
SAR05	2021/5/1	5600	100	D5GHzV2-1006-5600	EX3DV4 - SN7625	DAE4 Sn1311	8.11	83.30	81.1	-2.64
SAR05	2021/5/1	5750	100	D5GHzV2-1006-5750	EX3DV4 - SN7625	DAE4 Sn1311	7.87	80.40	78.7	-2.11




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.



11. WiFi/Bluetooth Output Power (Unit: dBm)

General Note:

1. The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures. For "Not required", SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band or when MIMO mode was not performed, due to for each antenna, transmit power in SISO operation is larger than (or equal to) the power in MIMO operation, RF exposure compliance of MIMO mode can be deduced from the compliance simultaneous transmission of antennas operating in SISO mode. Additional output power measurements were not necessary.
2. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
3. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
4. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
5. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
6. Per 201904 TCBC workshops, General principles of FCC KDB Publication 248227 D01 can be applied to determine the SAR Initial Test Configurations and test reduction for 802.11ax SAR testing. For the table below the 802.11ax maximum power is SU (non-OFDMA), and the SU maximum power also higher than RU (OFDMA)
7. In applying the test guidance, the IEEE 802.11 mode with the maximum output power (out of all modes) should be considered for testing
8. For modes with the same maximum output power, the guidance from section 5.3.2 a) of FCC KDB Publication 248227 D01 should be applied, with 802.11ax being considered as the highest 802.11 mode for the appropriate frequency bands
9. When SAR testing for 802.11ax is required
 - a. If the maximum output power is highest for OFDMA scenarios, choose the tone size with the maximum number of tones and the highest maximum output power
 - b. Otherwise, consider the fully allocated channel for SAR testing
 - c. When SAR testing is required on RU sizes less than the fully allocated channel, use the RU number closest to the middle of the channel, choosing the higher RU number when two RUs are equidistant to the middle of the channel



<For Tablet Mode>

2.4GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2		
2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11b 1Mbps	1	2412	15.40	15.50	14.80	15.50	18.12	18.50	100.00
6		2437	15.50	15.50	15.00	15.50	18.27	18.50		
11		2462	15.50	15.50	15.30	15.50	18.41	18.50		
12		2467	14.40	14.50	14.20	14.50	17.31	17.50		
13		2472	11.00	11.00	10.70	11.00	13.86	14.00		
802.11g 6Mbps	1	2412	Not required	15.50	Not required	15.50	Not required	18.50	Not required	
	6	2437		15.50		15.50		18.50		
	11	2462		15.50		15.50		18.50		
	12	2467		12.00		12.00		15.00		
	13	2472		11.50		11.50		14.50		
802.11n-HT20 MCS0	1	2412	Not required	15.50	Not required	15.50	Not required	18.50	Not required	
	6	2437		15.50		15.50		18.50		
	11	2462		15.50		15.50		18.50		
	12	2467		12.00		12.00		15.00		
	13	2472		11.50		11.50		14.50		
802.11n-HT40 MCS0	3	2422	Not required	14.50	Not required	14.50	Not required	17.50	Not required	
	6	2437		15.50		15.50		18.50		
	9	2452		14.00		14.00		17.00		
	10	2457		11.00		11.00		14.00		
	11	2462		10.50		10.50		13.50		
802.11ac-VHT20 MCS0	1	2412	Not required	15.50	Not required	15.50	Not required	18.50	Not required	
	6	2437		15.50		15.50		18.50		
	11	2462		12.00		12.00		15.00		
	13	2472		11.50		11.50		14.50		
802.11ac-VHT40 MCS0	3	2422	Not required	14.50	Not required	14.50	Not required	17.50	Not required	
	6	2437		15.50		15.50		18.50		
	9	2452		14.00		14.00		17.00		
	10	2457		11.00		11.00		14.00		
	11	2462		10.50		10.50		13.50		
802.11ax-HE20 MCS0	1	2412	Not required	15.50	Not required	15.50	Not required	18.50	Not required	
	6	2437		15.50		15.50		18.50		
	11	2462		15.50		15.50		18.50		
	12	2467		12.00		12.00		15.00		
	13	2472		11.50		11.50		14.50		
802.11ax-HE40 MCS0	3	2422	Not required	14.50	Not required	14.50	Not required	17.50	Not required	
	6	2437		15.50		15.50		18.50		
	9	2452		14.00		14.00		17.00		
	10	2457		11.00		11.00		14.00		
	11	2462		10.50		10.50		13.50		



5.2GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2		
5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	5.2GHz WLAN	802.11a 6Mbps	36	5180	Not required	15.00	Not required	15.00	Not required	18.00
40			5200	15.00		15.00		18.00		
44			5220	15.00		15.00		18.00		
48			5240	15.00		15.00		18.00		
802.11n-HT20 MCS0		36	5180	15.00		15.00		18.00		
		40	5200	15.00		15.00		18.00		
		44	5220	15.00		15.00		18.00		
		48	5240	15.00		15.00		18.00		
802.11n-HT40 MCS0		38	5190	15.00		15.00		18.00		
		46	5230	15.00		15.00		18.00		
802.11ac-VHT20 MCS0		36	5180	15.00		15.00		18.00		
		40	5200	15.00		15.00		18.00		
		44	5220	15.00		15.00		18.00		
802.11ac-VHT40 MCS0		38	5190	15.00		15.00		18.00		
		46	5230	15.00		15.00		18.00		
802.11ac-VHT80 MCS0		42	5210	15.00		15.00		18.00		
802.11ax-HE20 MCS0		36	5180	15.00		15.00		18.00		
		40	5200	15.00		15.00		18.00		
		44	5220	15.00		15.00		18.00		
		48	5240	15.00		15.00		18.00		
802.11ax-HE40 MCS0		38	5190	15.00		15.00		18.00		
		46	5230	15.00		15.00		18.00		
802.11ax-HE80 MCS0		42	5210	15.00		15.00		18.00		



5.3GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2		
5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	5.3GHz WLAN	802.11a 6Mbps	52	5260	Not required	15.00	Not required	15.00	Not required	18.00
56			5280	15.00		15.00		18.00		
60			5300	15.00		15.00		18.00		
64			5320	15.00		15.00		18.00		
802.11n-HT20 MCS0		52	5260	15.00		15.00		18.00		
		56	5280	15.00		15.00		18.00		
		60	5300	15.00		15.00		18.00		
		64	5320	15.00		15.00		18.00		
802.11n-HT40 MCS0		54	5270	15.00		15.00		18.00		
		62	5310	15.00		15.00		18.00		
802.11ac-VHT20 MCS0		52	5260	15.00		15.00		18.00		
		56	5280	15.00		15.00		18.00		
		60	5300	15.00		15.00		18.00		
		64	5320	15.00		15.00		18.00		
802.11ac-VHT40 MCS0		54	5270	15.00		15.00		18.00		
		62	5310	15.00		15.00		18.00		
802.11ac-VHT80 MCS0	58	5290	14.80	15.00	14.70	15.00	17.76	18.00	100.00	
802.11ax-HE20 MCS0	52	5260	Not required	15.00	Not required	15.00	Not required	18.00	Not required	
	56	5280		15.00		15.00		18.00		
	60	5300		15.00		15.00		18.00		
	64	5320		15.00		15.00		18.00		
802.11ax-HE40 MCS0	54	5270		15.00		15.00		18.00		
	62	5310		15.00		15.00		18.00		
802.11ax-HE80 MCS0	58	5290		15.00		15.00		15.00		18.00



5.5GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2		
5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	5.5GHz WLAN	802.11a 6Mbps	100	5500	Not required	14.50	Not required	14.50	Not required	17.50
116			5580	14.50		17.50				
124			5620	14.50		17.50				
132			5660	14.50		17.50				
144			5720	14.50		17.50				
802.11n-HT20 MCS0		100	5500	14.50		17.50				
		116	5580	14.50		17.50				
		124	5620	14.50		17.50				
		132	5660	14.50		17.50				
		144	5720	14.50		17.50				
802.11n-HT40 MCS0		102	5510	14.50		17.50				
		110	5550	14.50		17.50				
		126	5630	14.50		17.50				
		134	5670	14.50		17.50				
802.11ac-VHT20 MCS0		100	5500	14.50		17.50				
		116	5580	14.50		17.50				
		124	5620	14.50		17.50				
		132	5660	14.50		17.50				
802.11ac-VHT40 MCS0		102	5510	14.50		17.50				
		110	5550	14.50		17.50				
	126	5630	14.50	17.50						
	134	5670	14.50	17.50						
802.11ac-VHT80 MCS0	106	5530	14.20	14.50	13.20	14.50	16.74	17.50	100.00	
	122	5610	14.30	14.50	14.30	14.50	17.31	17.50		
	138	5690	14.50	14.50	13.10	14.50	16.87	17.50		
802.11ax-HE20 MCS0	100	5500	Not required	14.50	Not required	14.50	Not required	17.50	Not required	
	116	5580		14.50		17.50				
	124	5620		14.50		17.50				
	132	5660		14.50		17.50				
	144	5720		14.50		17.50				
802.11ax-HE40 MCS0	102	5510		14.50		17.50				
	110	5550		14.50		17.50				
	126	5630		14.50		17.50				
	134	5670		14.50		17.50				
802.11ax-HE80 MCS0	106	5530		14.50		17.50				
	122	5610		14.50		17.50				
	138	5690		14.50		17.50				



5.8GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2								
5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %						
	802.11a 6Mbps	149	5745	Not required	14.00	Not required	14.00	Not required	17.00	Not required						
		157	5785								14.00					
		165	5825								14.00					
	802.11n-HT20 MCS0	149	5745								14.00					
		157	5785								14.00					
		165	5825								14.00					
	802.11n-HT40 MCS0	151	5755								14.00					
		159	5795								14.00					
	802.11ac-VHT20 MCS0	149	5745								14.00					
		157	5785								14.00					
		165	5825								14.00					
	802.11ac-VHT40 MCS0	151	5755								14.00					
		159	5795								14.00					
	802.11ac-VHT80 MCS0	155	5775								12.70	14.00	14.00	14.00	16.41	17.00
802.11ax-HE20 MCS0	149	5745	Not required								14.00	Not required	14.00	Not required	17.00	Not required
	157	5785		14.00												
	165	5825		14.00												
802.11ax-HE40 MCS0	151	5755		14.00												
	159	5795		14.00												
802.11ax-HE80 MCS0	155	5775		14.00												



<For Laptop Mode>

2.4GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2		
2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11b 1Mbps	1	2412	20.00	20.00	19.60	20.00	22.81	23.00	100.00
6		2437	20.40	20.50	20.10	20.50	23.26	23.50		
11		2462	16.80	17.00	16.60	17.00	19.71	20.00		
12		2467	14.40	14.50	14.20	14.50	17.31	17.50		
802.11g 6Mbps	13	2472	11.00	11.00	10.70	11.00	13.86	14.00	Not required	
	1	2412		17.00		17.00		20.00		
	6	2437		20.50		20.50		23.50		
	11	2462		16.50		16.50		19.50		
802.11n-HT20 MCS0	12	2467		12.00		12.00		15.00	Not required	
	13	2472		11.50		11.50		14.50		
	1	2412		17.00		17.00		20.00		
	6	2437		20.50		20.50		23.50		
802.11n-HT40 MCS0	9	2452		14.00		14.00		17.00	Not required	
	10	2457		11.00		11.00		14.00		
	11	2462		10.50		10.50		13.50		
	1	2412		17.00		17.00		20.00		
802.11ac-VHT20 MCS0	6	2437	Not required	20.50	Not required	20.50	Not required	23.50	Not required	
	11	2462		16.50		16.50		19.50		
	12	2467		12.00		12.00		15.00		
	13	2472		11.50		11.50		14.50		
802.11ac-VHT40 MCS0	3	2422		14.50		14.50		17.50	Not required	
	6	2437		16.50		16.50		19.50		
	9	2452		14.00		14.00		17.00		
	10	2457		11.00		11.00		14.00		
802.11ac-VHT40 MCS0	11	2462		10.50		10.50		13.50	Not required	
	1	2412		17.00		17.00		20.00		
	6	2437		20.50		20.50		23.50		
	11	2462		16.50		16.50		19.50		
802.11ax-HE20 MCS0	12	2467		12.00		12.00		15.00	Not required	
	13	2472		11.50		11.50		14.50		
	1	2412		17.00		17.00		20.00		
	6	2437		20.50		20.50		23.50		
802.11ax-HE20 MCS0	11	2462		16.50		16.50		19.50	Not required	
	12	2467		12.00		12.00		15.00		
	13	2472		11.50		11.50		14.50		
	1	2412		17.00		17.00		20.00		
802.11ax-HE40 MCS0	6	2437		16.50		16.50		19.50	Not required	
	9	2452		14.00		14.00		17.00		
	10	2457		11.00		11.00		14.00		
	11	2462		10.50		10.50		13.50		



5.2GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2		
5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	5.2GHz WLAN	802.11a 6Mbps	36	5180	Not required	18.50	Not required	18.50	Not required	21.50
40			5200	18.50		18.50		21.50		
44			5220	18.50		18.50		21.50		
48			5240	18.50		18.50		21.50		
802.11n-HT20 MCS0		36	5180	18.50		18.50		21.50		
		40	5200	18.50		18.50		21.50		
		44	5220	18.50		18.50		21.50		
		48	5240	18.50		18.50		21.50		
802.11n-HT40 MCS0		38	5190	16.00		16.00		19.00		
		46	5230	19.50		19.50		22.50		
802.11ac-VHT20 MCS0		36	5180	18.50		18.50		21.50		
		40	5200	18.50		18.50		21.50		
		44	5220	18.50		18.50		21.50		
802.11ac-VHT40 MCS0		38	5190	16.00		16.00		19.00		
		46	5230	19.50		19.50		22.50		
802.11ac-VHT80 MCS0		42	5210	15.50		15.50		18.50		
802.11ax-HE20 MCS0		36	5180	18.50		18.50		21.50		
		40	5200	18.50		18.50		21.50		
		44	5220	18.50		18.50		21.50		
		48	5240	18.50		18.50		21.50		
802.11ax-HE40 MCS0		38	5190	16.00		16.00		19.00		
		46	5230	19.50		19.50		22.50		
802.11ax-HE80 MCS0		42	5210	15.50		15.50		18.50		



5.3GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2									
5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %							
	5.3GHz WLAN	802.11a 6Mbps	52	5260	Not required	18.50	Not required	18.50	Not required	21.50	Not required						
56			5280	18.50		18.50		21.50									
60			5300	18.50		18.50		21.50									
64			5320	18.50		18.50		21.50									
802.11n-HT20 MCS0		52	5260	18.50		18.50		21.50									
		56	5280	18.50		18.50		21.50									
		60	5300	18.50		18.50		21.50									
		64	5320	18.50		18.50		21.50									
802.11n-HT40 MCS0		54	5270	19.30		19.50		18.90		19.50		22.11	22.50	100.00			
		62	5310	15.70		16.00		15.30		16.00		18.51	19.00				
802.11ac-VHT20 MCS0		52	5260	Not required		18.50		Not required		18.50		Not required	21.50	Not required			
		56	5280			18.50				18.50			21.50				
		60	5300			18.50				18.50			21.50				
		64	5320			18.50				18.50			21.50				
802.11ac-VHT40 MCS0		54	5270			19.50				19.50			19.50		19.50	22.50	22.50
		62	5310			16.00				16.00			16.00		16.00	19.00	19.00
802.11ac-VHT80 MCS0	58	5290	15.50		15.50	15.50	15.50		18.50	18.50							
802.11ax-HE20 MCS0	52	5260	18.50		18.50	18.50	18.50		21.50	21.50							
	56	5280	18.50		18.50	18.50	18.50		21.50	21.50							
	60	5300	18.50		18.50	18.50	18.50		21.50	21.50							
	64	5320	18.50		18.50	18.50	18.50		21.50	21.50							
802.11ax-HE40 MCS0	54	5270	19.50		19.50	19.50	19.50		22.50	22.50							
	62	5310	16.00		16.00	16.00	16.00		19.00	19.00							
802.11ax-HE80 MCS0	58	5290	15.50		15.50	15.50	15.50		18.50	18.50							



5.5GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2				
5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %		
	5.5GHz WLAN	802.11a 6Mbps	100	5500	Not required	18.50	Not required	18.50	Not required	21.50	Not required	
116			5580	18.50		18.50		21.50				
124			5620	18.50		18.50		21.50				
132			5660	18.50		18.50		21.50				
144			5720	18.50		18.50		21.50				
802.11n-HT20 MCS0		100	5500	18.50		18.50		21.50				
		116	5580	18.50		18.50		21.50				
		124	5620	18.50		18.50		21.50				
		132	5660	18.50		18.50		21.50				
		144	5720	18.50		18.50		21.50				
802.11n-HT40 MCS0		102	5510	15.50		15.50		18.50				
		110	5550	19.50		19.50		22.50				
		126	5630	18.50		18.50		21.50				
		134	5670	19.50		19.50		22.50				
802.11ac-VHT20 MCS0		100	5500	18.50		18.50		21.50				
		116	5580	18.50		18.50		21.50				
		124	5620	18.50		18.50		21.50				
		132	5660	18.50		18.50		21.50				
802.11ac-VHT40 MCS0		102	5510	15.50		15.50		18.50				
		110	5550	19.50		19.50		22.50				
	126	5630	18.50	18.50	21.50							
	134	5670	19.50	19.50	22.50							
802.11ac-VHT80 MCS0	106	5530	15.50	15.50	14.40	15.50	18.00	18.50	100.00			
	122	5610	18.70	19.50	19.20	19.50	21.97	22.50				
	138	5690	19.30	19.50	18.10	19.50	21.75	22.50				
802.11ax-HE20 MCS0	100	5500	Not required	18.50	Not required	18.50	Not required	21.50	Not required			
	116	5580		18.50		18.50		21.50				
	124	5620		18.50		18.50		21.50				
	132	5660		18.50		18.50		21.50				
	144	5720		18.50		18.50		21.50				
802.11ax-HE40 MCS0	102	5510		15.50		15.50		18.50				
	110	5550		19.50		19.50		22.50				
	126	5630		18.50		18.50		21.50				
	134	5670		19.50		19.50		22.50				
802.11ax-HE80 MCS0	106	5530		15.50		15.50		15.50		15.50	18.50	Not required
	122	5610		19.50		19.50		19.50		19.50	22.50	
	138	5690		19.50		19.50		19.50		19.50	22.50	



5.8GHz WLAN				Ant 1+2(1)		Ant 1+2(2)		Ant 1+2		
5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	149	5745	19.60	20.50	20.40	20.50	23.03	23.50	100.00
		157	5785	19.10	20.50	20.40	20.50	22.81	23.50	
		165	5825	19.30	20.50	20.50	20.50	22.95	23.50	
	802.11n-HT20 MCS0	149	5745	Not required	20.50	Not required	20.50	Not required	23.50	Not required
		157	5785		20.50		23.50			
		165	5825		20.50		23.50			
	802.11n-HT40 MCS0	151	5755		19.50		19.50		22.50	
		159	5795		19.50		19.50		22.50	
	802.11ac-VHT20 MCS0	149	5745		20.50		20.50		23.50	
		157	5785		20.50		20.50		23.50	
		165	5825		20.50		20.50		23.50	
	802.11ac-VHT40 MCS0	151	5755		19.50		19.50		22.50	
		159	5795		19.50		19.50		22.50	
	802.11ac-VHT80 MCS0	155	5775		19.50		19.50		22.50	
802.11ax-HE20 MCS0	149	5745	20.50		20.50		23.50			
	157	5785	20.50		20.50		23.50			
	165	5825	20.50		20.50		23.50			
802.11ax-HE40 MCS0	151	5755	19.50		19.50		22.50			
	159	5795	19.50	19.50	22.50					
802.11ax-HE80 MCS0	155	5775	19.50	19.50	22.50					




<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	5.90	6.00	5.90
	CH 39	2441	5.90	5.90	5.90
	CH 78	2480	5.70	5.70	5.70
Tune-up Limit			6	6	6

Mode	Channel	Frequency (MHz)	Average power (dBm)	
			1Mbps	2Mbps
LE	CH 00	2402	5.50	5.70
	CH 19	2440	5.90	6.00
	CH 39	2480	5.60	5.80
Tune-up Limit			6	6


General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 100% considered in SAR testing.



12. Antenna Location

<For Tablet>




Edge3

Front View

The separation distance for antenna to edge:

Antenna	To Edge1 (mm)	To Edge2 (mm)	To Edge3 (mm)	To Edge4 (mm)
WLAN/BT Antenna 1	2	252.51	221.8	45.45
WLAN Antenna 2	2	45.51	221.8	252.45

<For Laptop>



The separation distance for antenna to edge :

Antenna	To Bottom of Laptop (mm)
WLAN/BT Antenna 1	230.72
WLAN Antenna 2	230.72



13. SAR Test Exclusion Table

General Note:

- The below table, exemption limits for routine evaluation based on frequency and separation distance was according to SAR-based Exemption – §1.1307(b)(3)(i)(B).

<For Tablet>

Exposure Position	Wireless Interface	BT ANT 1	2.4GHz WLAN ANT 1+2	5GHz WLAN ANT 1+2
	Calculated Frequency (MHz)	2480	2462	5825
	Maximum power (dBm)	6	18.5	18
	Maximum rated power(mW)	4.0	71.0	63.0
Bottom Face	Separation distance(mm)	5.0	5.0	5.0
	exclusion threshold	2.7	2.7	1.4
	Testing required?	Yes	Yes	Yes
Edge 1	Separation distance(mm)	5.0	5.0	5.0
	exclusion threshold	2.7	2.7	1.4
	Testing required?	Yes	Yes	Yes
Edge 2	Separation distance(mm)	252.5	45.5	45.5
	exclusion threshold	3060.0	182.9	138.6
	Testing required?	No	No	No
Edge 3	Separation distance(mm)	221.8	221.8	221.8
	exclusion threshold	3060.0	3060.0	3060.0
	Testing required?	No	No	No
Edge 4	Separation distance(mm)	45.5	45.5	45.5
	exclusion threshold	182.0	182.4	138.3
	Testing required?	No	No	No

<For Laptop>

Exposure Position	Wireless Interface	BT ANT 1	2.4GHz WLAN ANT 1+2	5GHz WLAN ANT 1+2
	Calculated Frequency (MHz)	2480	2462	5825
	Maximum power (dBm)	6	23.5	23.5
	Maximum rated power(mW)	4.0	224.0	224.0
Bottom of Laptop	Separation distance(mm)	230.7	230.7	230.7
	exclusion threshold	3060.0	3060.0	3060.0
	Testing required?	No	No	No



14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.
6. Refer to tune-up procedure the channel 12 and 13 powers are low than others channel, therefore the SAR consideration is not necessary



14.1 Body SAR

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna Vendor	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	HTK	Ant 1+2	11	2462	18.41	18.50	1.021	100	1.000	0.02	0.081	0.083
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	HTK	Ant 1+2	11	2462	18.41	18.50	1.021	100	1.000	-0.08	0.212	0.216
01	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	HTK	Ant 1+2	1	2412	18.12	18.50	1.091	100	1.000	-0.14	0.451	0.492
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	HTK	Ant 1+2	6	2437	18.27	18.50	1.054	100	1.000	0.05	0.332	0.350
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	WNC	Ant 1+2	1	2412	18.12	18.50	1.091	100	1.000	0.01	0.268	0.293
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	HTK	Ant 1+2	58	5290	17.76	18.00	1.057	100	1.000	0.06	0.066	0.070
02	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	HTK	Ant 1+2	58	5290	17.76	18.00	1.057	100	1.000	-0.12	0.289	0.305
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	WNC	Ant 1+2	58	5290	17.76	18.00	1.057	100	1.000	0.16	0.288	0.304
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	HTK	Ant 1+2	122	5610	17.31	17.50	1.045	100	1.000	0.01	0.063	0.066
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	HTK	Ant 1+2	122	5610	17.31	17.50	1.045	100	1.000	-0.06	0.189	0.197
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	HTK	Ant 1+2	106	5530	16.74	17.50	1.191	100	1.000	0.03	0.182	0.217
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	HTK	Ant 1+2	138	5690	16.87	17.50	1.156	100	1.000	-0.05	0.210	0.243
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	WNC	Ant 1+2	138	5690	16.87	17.50	1.156	100	1.000	0.06	0.295	0.341
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	WNC	Ant 1+2	122	5610	17.31	17.50	1.045	100	1.000	0.01	0.335	0.350
03	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	WNC	Ant 1+2	106	5530	16.74	17.50	1.191	100	1.000	-0.04	0.413	0.492
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	HTK	Ant 1+2	155	5775	16.41	17.00	1.146	100	1.000	-0.05	0.073	0.084
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	HTK	Ant 1+2	155	5775	16.41	17.00	1.146	100	1.000	-0.02	0.364	0.417
04	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	WNC	Ant 1+2	155	5775	16.41	17.00	1.146	100	1.000	-0.01	0.427	0.489

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna Vendor	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Bottom Face	0mm	HTK	Ant 1	0	2402	5.90	6.00	1.023	100	1.000	0.05	0.010	0.010
05	Bluetooth	1Mbps	Edge 1	0mm	HTK	Ant 1	0	2402	5.90	6.00	1.023	100	1.000	-0.17	0.030	0.031
	Bluetooth	1Mbps	Edge 1	0mm	HTK	Ant 1	39	2441	5.90	6.00	1.023	100	1.000	-0.14	0.028	0.029
	Bluetooth	1Mbps	Edge 1	0mm	HTK	Ant 1	78	2480	5.70	6.00	1.072	100	1.000	-0.08	0.024	0.026
	Bluetooth	1Mbps	Edge 1	0mm	WNC	Ant 1	0	2402	5.90	6.00	1.023	100	1.000	0.08	0.027	0.028

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	2.4GHz WLAN Ant 1+2 + Bluetooth Ant 1	Yes
2.	5GHz WLAN Ant 1+2 + Bluetooth Ant 1	Yes

General Note:

1. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
2. The Scaled SAR summation is calculated based on the same configuration and test position.
3. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

15.1 Body Exposure Conditions

Exposure Position	1	2	3	1+3 Summed 1g SAR (W/kg)	2+3 Summed 1g SAR (W/kg)
	2.4GHz WLAN Ant 1+2	5GHz WLAN Ant 1+2	Bluetooth Ant 1		
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
Bottom Face at 0mm	0.083	0.084	0.010	0.093	0.094
Edge 1 at 0mm	0.492	0.492	0.031	0.523	0.523

Test Engineer : Bevis Chang



16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [8] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [9] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.