



# FCC RADIO TEST REPORT

**FCC ID** : B94HNC10C4TKR  
**Equipment** : Convertible PC  
**Brand Name** : HP  
**Model Name** : HSN-C10C-4  
**Applicant** : HP Inc.  
1501 Page Mill Road, Palo Alto CA 94304 USA  
**Standard** : FCC 47 CFR Part 2, 22(H), 24(E), 27

The product was received on Aug. 24, 2020 and testing was started from Oct. 06, 2020 and completed on Oct. 12, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Approved by: Louis Wu

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

**History of this test report..... 3**

**Summary of Test Result..... 4**

**1 General Description ..... 6**

    1.1 Product Feature of Equipment Under Test..... 6

    1.2 Modification of EUT ..... 7

    1.3 Testing Location ..... 8

    1.4 Applicable Standards..... 8

**2 Test Configuration of Equipment Under Test ..... 9**

    2.1 Test Mode..... 9

    2.2 Connection Diagram of Test System..... 9

    2.3 Support Unit used in test configuration and system ..... 10

    2.4 Frequency List of Low/Middle/High Channels ..... 10

**3 Radiated Test Items ..... 11**

    3.1 Measuring Instruments ..... 11

    3.2 Radiated Spurious Emission Measurement ..... 13

**4 List of Measuring Equipment..... 14**

**5 Uncertainty of Evaluation ..... 15**

**Appendix A. Test Results of Radiated Test**



### History of this test report

| Report No. | Version | Description             | Issued Date   |
|------------|---------|-------------------------|---------------|
| FG082501B  | 01      | Initial issue of report | Oct. 22, 2020 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |



## Summary of Test Result

| Report Clause | Ref Std. Clause   | Test Items   | Result (PASS/FAIL) | Remark |
|---------------|---|--|--------------------|--------|
| -             | §2.1046   | Conducted Output Power   | Not Required       | -      |
|               | §22.913 (a)(2)  | Effective Radiated Power (Band 5) (Band 26)  | Not Required       |        |
|               | §27.50 (b)(10)<br>§27.50 (c)(10)  | Effective Radiated Power (Band 12) (Band 13) (Band 17) (Band 71)   |                    |        |
|               | §24.232 (c)<br>§27.50 (h)(2)  | Equivalent Isotropic Radiated Power (Band 2) (Band 25) (Band 7) (Band 38) (Band 41)  |                    |        |
|               | §27.50 (d)(4)   | Equivalent Isotropic Radiated Power (Band 4) (Band 66)   |                    |        |
| -             | §24.232 (d)<br>§27.50 (d)(5)  | Peak-to-Average Ratio  | Not Required       | -      |
| -             | §2.1049   | Occupied Bandwidth   | Not Required       | -      |
| -             | §2.1051<br>§22.917 (a)<br>§24.238 (a)<br>§27.53 (c)(2)(4)<br>§27.53 (g)<br>§27.53 (h) | Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 17) (Band 25) (Band 26) (Band 66) (Band 71) | Not Required       | -      |
|               | §2.1051<br>§27.53 (m)(4)  | Conducted Band Edge Measurement (Band 7) (Band 38) (Band 41)   |                    |        |
| -             | §2.1051<br>§22.917 (a)<br>§24.238 (a)<br>§27.53 (c)(2)<br>§27.53 (g)<br>§27.53 (h)    | Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 17) (Band 25) (Band 26) (Band 66) (Band 71)     | Not Required       | -      |
|               | §2.1051<br>§27.53 (m)(4)  | Conducted Spurious Emission (Band 7) (Band 38) (Band 41)   |                    |        |
| -             | §2.1055<br>§22.355<br>§24.235<br>§27.54   | Frequency Stability<br>Temperature & Voltage   | Not Required       | -      |



| Report Clause | Ref Std. Clause  | Test Items  | Result (PASS/FAIL) | Remark                                     |
|---------------|--|---|--------------------|--|
| 3.2           | §2.1053<br>§22.917 (a)<br>§24.238 (a)<br>§27.53 (c)(2)<br>§27.53 (f)<br>§27.53 (g)<br>§27.53 (h) | Radiated Spurious Emission<br>(Band 2) (Band 4) (Band 5)<br>(Band 12) (Band 13) (Band 17)<br>(Band 25) (Band 26) (Band 66)<br>(Band 71) | Pass               | Under limit<br>19.04 dB at<br>1560.000 MHz |
|               | §2.1051<br>§27.53 (m)(4)   | Radiated Spurious Emission<br>(Band 7) (Band 38) (Band 41)  |                    |  |

Note:

1. Not required means after assessing, test items are not necessary to carry out.
2. This is a variant report by changing CPU and Model Name. All the test cases were performed on original report which can be referred to Sporton Report Number FG030919-04B.

|  |
|--|
| <b>Declaration of Conformity:</b>  |
| The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.   |
| <b>Comments and Explanations:</b>  |
| The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification. |

Reviewed by: Wii Chang

Report Producer: Yimin Ho



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

WCDMA/LTE/5G NR, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC, and GNSS.

| Product Specification subjective to this standard |   |
|---|---|
| <b>WWAN Module</b>                                | Brand Name: FOXCONN<br>Model Name: T99W175  |
| <b>Antenna Type</b>                               | WWAN<br><Ant. 1>: PIFA Antenna<br><Ant. 2>: PIFA Antenna (Rx only)<br><Ant. 3>: PIFA Antenna<br><Ant. 4>: PIFA Antenna (Rx only)<br>WLAN<br><Ant. 1>: PIFA Antenna<br><Ant. 2>: PIFA Antenna<br>Bluetooth: PIFA Antenna<br>GPS/Glonass/BDS/Galileo: PIFA Antenna<br>NFC: Loop Antenna |

| WWAN Antenna Information NB Mode                  |             |              |                               |
|---|-------------|--------------|-------------------------------|
| Antenna Part Number                               | Manufacture | Antenna Type | Peak Gain (dBi)               |
| Tx1 Main Antenna<br>AUP6Y-100015<br>(DC33002DS00) | AWAN        | PIFA         | 824-849MHz -1.42 dBi (peak)   |
|   |             |              | 880-915MHz -1.89 dBi (peak)   |
|   |             |              | 1710-1785MHz -1.67 dBi (peak) |
|   |             |              | 1850-1910MHz -2.43 dBi (peak) |
|   |             |              | 1920-1980MHz -1.44 dBi (peak) |
|   |             |              | 704-716MHz -1.25 dBi (peak)   |
|   |             |              | 746-756MHz -2.26 dBi (peak)   |
|   |             |              | 777-787MHz -1.63 dBi (peak)   |
|   |             |              | 832-862MHz -1.45 dBi (peak)   |
|   |             |              | 1710-1755MHz -1.54 dBi (peak) |
|   |             |              | 2305-2315MHz -2.12 dBi (peak) |
|   |             |              | 2570-2620MHz -3.68 dBi (peak) |
|   |             |              | 2300-2400MHz -0.94 dBi (peak) |
|   |             |              | 2500-2570MHz -2.12 dBi (peak) |
|   |             |              | 3400-3600MHz -2.05 dBi (peak) |
| 3600-3800MHz -2.99 dBi (peak)                     |             |              |                               |
| 5150-5925MHz -0.62 dBi (peak)                     |             |              |                               |
| MIMO3 Antenna<br>AXP6Y-100004<br>(DC33002DS30)    | AWAN        | PIFA         | 1710-1785MHz 0.95 dBi (peak)  |
|   |             |              | 1805-1880MHz 0.34 dBi (peak)  |
|   |             |              | 1850-1915MHz 1.39 dBi (peak)  |
|   |             |              | 1920-1980MHz 0.13 dBi (peak)  |
|   |             |              | 1930-1995MHz 0.18 dBi (peak)  |
|   |             |              | 2110-2200MHz -0.91 dBi (peak) |
|   |             |              | 2300-2400MHz -0.40 dBi (peak) |
|   |             |              | 2496-2690MHz -1.10 dBi (peak) |
| 3300-4200MHz -1.9 dBi (peak)                      |             |              |                               |



| WWAN Antenna Information TB Mode                  |             |              |                               |
|---|-------------|--------------|-------------------------------|
| Antenna Part Number                               | Manufacture | Antenna Type | Peak Gain (dBi)               |
| Tx1 Main Antenna<br>AUP6Y-100015<br>(DC33002DS00) | AWAN        | PIFA         | 824-849MHz -4.39 dBi (peak)   |
|   |             |              | 880-915MHz -4.51 dBi (peak)   |
|   |             |              | 1710-1785MHz -2.98 dBi (peak) |
|   |             |              | 1850-1910MHz -1.38 dBi (peak) |
|   |             |              | 1920-1980MHz 0.48 dBi (peak)  |
|   |             |              | 704-716MHz -4.33 dBi (peak)   |
|   |             |              | 746-756MHz -4.97 dBi (peak)   |
|   |             |              | 777-787MHz -2.02 dBi (peak)   |
|   |             |              | 832-862MHz -4.63 dBi (peak)   |
|   |             |              | 1710-1755MHz -2.76 dBi (peak) |
|   |             |              | 2305-2315MHz -2.14 dBi (peak) |
|   |             |              | 2570-2620MHz -3.23 dBi (peak) |
|   |             |              | 2300-2400MHz -1.13dBi (peak)  |
|   |             |              | 2500-2570MHz -2.04 dBi (peak) |
|   |             |              | 3400-3600MHz -1.46 dBi (peak) |
|   |             |              | 3600-3800MHz -2.45 dBi (peak) |
| MIMO3 Antenna<br>AXP6Y-100004<br>(DC33002DS30)    | AWAN        | PIFA         | 5150-5925MHz 1.39 dBi (peak)  |
|   |             |              | 1710-1785MHz -0.49 dBi (peak) |
|   |             |              | 1805-1880MHz -2.07 dBi (peak) |
|   |             |              | 1850-1915MHz -1.56 dBi (peak) |
|   |             |              | 1920-1980MHz -3.04 dBi (peak) |
|   |             |              | 1930-1995MHz -3.52 dBi (peak) |
|   |             |              | 2110-2200MHz -4.53 dBi (peak) |
|   |             |              | 2300-2400MHz -0.83 dBi (peak) |
| 2496-2690MHz -2.22 dBi (peak)                     |             |              |                               |
|   |             |              | 3300-4200MHz -4.87 dBi (peak) |

### 1.2 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.3 Testing Location

|                           |   |
|---------------------------|---|
| <b>Test Site</b>          | SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory   |
| <b>Test Site Location</b> | No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist.,<br>Taoyuan City, Taiwan (R.O.C.)<br>TEL: +886-3-327-0868<br>FAX: +886-3-327-0855 |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>   |
|                           | 03CH13-HY   |
| <b>Test Engineer</b>      | Daniel Lee, Jacky Hong and Wilson Wu  |
| <b>Temperature</b>        | 21.5~25.5°C   |
| <b>Relative Humidity</b>  | 49.5~55.5%  |

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW0007

### 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 22(H), 24(E), 27
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



## 2 Test Configuration of Equipment Under Test


### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in Tablet Type (three orthogonal panels, X, Y, Z) and Notebook Type. The worst cases (Y Plane for LTE Band 41 (HPUE) and Notebook Type for LTE Band 13) were recorded in this report.

| Test Items                 | Band   | Bandwidth (MHz) |   |   |    |    |    | Modulation |       |       |        | RB # |      |      | Test Channel |   |   |
|----------------------------|--|-----------------|---|---|----|----|----|------------|-------|-------|--------|------|------|------|--------------|---|---|
|                            |  | 1.4             | 3 | 5 | 10 | 15 | 20 | QPSK       | 16QAM | 64QAM | 256QAM | 1    | Half | Full | L            | M | H |
| Radiated Spurious Emission | 13   | -               | - | v |    | -  | -  |            |       |       | v      | v    |      |      | v            | v | v |
|                            | 41   | -               | - | v |    |    |    |            |       |       | v      | v    |      |      | v            | v | v |
| Remark                     | 1. The mark "v " means that this configuration is chosen for testing<br>2. The mark "- " means that this bandwidth is not supported.<br>3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. |                 |   |   |    |    |    |            |       |       |        |      |      |      |              |   |   |

### 2.2 Connection Diagram of Test System





### 2.3 Support Unit used in test configuration and system

| Item | Equipment        | Brand Name | Model No. | FCC ID | Data Cable | Power Cord        |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1.   | System Simulator | Anritsu    | MT8821C   | N/A    | N/A        | Unshielded, 1.8 m |
| 2.   | Earphone         | SONY       | MH750     | N/A    | N/A        | N/A               |

### 2.4 Frequency List of Low/Middle/High Channels

| LTE Band 13 Channel and Frequency List |                        |        |        |         |
|--|------------------------|--------|--------|---------|
| BW [MHz]                               | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 5                                      | Channel                | 23205  | 23230  | 23255   |
|  | Frequency              | 779.5  | 782    | 784.5   |

| LTE Band 41 Channel and Frequency List |                        |        |        |         |
|--|------------------------|--------|--------|---------|
| BW [MHz]                               | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 5                                      | Channel                | 39675  | 40620  | 41565   |
|  | Frequency              | 2498.5 | 2593.0 | 2687.5  |


### 3 Radiated Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

##### 3.1.1 Test Setup


For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



### 3.1.2 Test Result of Radiated Test

Please refer to Appendix A.

**Note:**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



## 3.2 Radiated Spurious Emission Measurement

### 3.2.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

For LTE Band 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $55 + 10 \log (P)$  dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80$  dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)

For LTE Band 41

The limit line is derived from  $55 + 10\log(P)$ dB below the transmitter power P(Watts)

EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain

ERP (dBm) = EIRP - 2.15



## 4 List of Measuring Equipment

| Instrument           | Brand Name        | Model No.                           | Serial No.      | Characteristics               | Calibration Date | Test Date                       | Due Date      | Remark                   |
|----------------------|-------------------|-------------------------------------|-----------------|-------------------------------|------------------|---------------------------------|---------------|--------------------------|
| Amplifier            | Sonoma-Instrument | 310 N                               | 187282          | 9KHz~1GHz                     | Dec. 17, 2019    | Oct. 06, 2020~<br>Oct. 12, 2020 | Dec. 16, 2020 | Radiation<br>(03CH13-HY) |
| Loop Antenna         | Rohde & Schwarz   | HFH2-Z2                             | 100488          | 9 kHz~30 MHz                  | Jan. 09, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Jan. 08, 2021 | Radiation<br>(03CH13-HY) |
| Bilog Antenna        | TESEQ             | CBL<br>6111D&00800<br>N1D01N-06     | 40103&07        | 30MHz to 1GHz                 | Apr. 29, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Apr. 28, 2021 | Radiation<br>(03CH13-HY) |
| Bilog Antenna        | TESEQ             | CBL<br>6111D&00800<br>N1D01N-06     | 41912 & 07      | 30MHz to 1GHz                 | Apr. 29, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Apr. 28, 2021 | Radiation<br>(03CH13-HY) |
| Horn Antenna         | SCHWARZBECK       | BBHA 9120 D                         | 9120D-1212      | 1GHz ~ 18GHz                  | May 20, 2020     | Oct. 06, 2020~<br>Oct. 12, 2020 | May 19, 2021  | Radiation<br>(03CH13-HY) |
| Horn Antenna         | SCHWARZBECK       | BBHA 9120 D                         | 9120D-1241      | 1GHz ~ 18GHz                  | Jul. 15, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Jul. 14, 2021 | Radiation<br>(03CH13-HY) |
| Preamplifier         | MITEQ             | AMF-7D-0010<br>1800-30-10P          | 1590074         | 1GHz~18GHz                    | May 19, 2020     | Oct. 06, 2020~<br>Oct. 12, 2020 | May 18, 2021  | Radiation<br>(03CH13-HY) |
| Preamplifier         | Keysight          | 83017A                              | MY53270147      | 1GHz~26.5GHz                  | Oct. 28, 2019    | Oct. 06, 2020~<br>Oct. 12, 2020 | Oct. 27, 2020 | Radiation<br>(03CH13-HY) |
| Signal Generator     | Anritsu           | MG3694C                             | 163401          | 0.1Hz~40GHz                   | Feb. 15, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Feb. 14, 2021 | Radiation<br>(03CH13-HY) |
| Spectrum Analyzer    | Keysight          | N9010A                              | MY55370526      | 10Hz~44GHz                    | Mar. 20, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Mar. 19, 2021 | Radiation<br>(03CH13-HY) |
| Controller           | EMEC              | EM1000                              | N/A             | Control Turn table & Ant Mast | N/A              | Oct. 06, 2020~<br>Oct. 12, 2020 | N/A           | Radiation<br>(03CH13-HY) |
| Antenna Mast         | EMEC              | AM-BS-4500-B                        | N/A             | 1m~4m                         | N/A              | Oct. 06, 2020~<br>Oct. 12, 2020 | N/A           | Radiation<br>(03CH13-HY) |
| Turn Table           | EMEC              | TT2000                              | N/A             | 0~360 Degree                  | N/A              | Oct. 06, 2020~<br>Oct. 12, 2020 | N/A           | Radiation<br>(03CH13-HY) |
| Software             | Audix             | E3<br>6.2009-8-24                   | RK-000992       | N/A                           | N/A              | Oct. 06, 2020~<br>Oct. 12, 2020 | N/A           | Radiation<br>(03CH13-HY) |
| Preamplifier         | EMEC              | EM18G40G                            | 060715          | 18GHz ~ 40GHz                 | Dec. 13, 2019    | Oct. 06, 2020~<br>Oct. 12, 2020 | Dec. 12, 2020 | Radiation<br>(03CH13-HY) |
| RF Cable             | HUBER + SUHNER    | SUCOFLEX<br>126E                    | 0030/126E       | 30M-18G                       | Feb. 12, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Feb. 21, 2021 | Radiation<br>(03CH13-HY) |
| RF Cable             | HUBER + SUHNER    | SUCOFLEX<br>104                     | 804793/4        | 30M-18G                       | Feb. 12, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Feb. 11, 2021 | Radiation<br>(03CH13-HY) |
| RF Cable             | HUBER + SUHNER    | SUCOFLEX<br>102                     | 505134/2        | 30M~40GHz                     | Feb. 25, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Feb. 24, 2021 | Radiation<br>(03CH13-HY) |
| RF Cable             | HUBER + SUHNER    | SUCOFLEX<br>102                     | MY4274/2        | 30M~40GHz                     | Mar. 12, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Mar. 11, 2021 | Radiation<br>(03CH13-HY) |
| RF Cable             | HUBER + SUHNER    | SUCOFLEX<br>104                     | MY24961/4       | 30M-18G                       | Feb. 12, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Feb. 11, 2021 | Radiation<br>(03CH13-HY) |
| RF Cable             | HUBER + SUHNER    | SUCOFLEX<br>104                     | MY9837/4PE      | 9kHz~30MHz                    | Mar. 12, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Mar. 11, 2021 | Radiation<br>(03CH13-HY) |
| SHF-EHF Horn Antenna | SCHWARZBECK       | BBHA 9170                           | BBHA917058<br>4 | 18GHz- 40GHz                  | Dec. 10, 2019    | Oct. 06, 2020~<br>Oct. 12, 2020 | Dec. 09, 2020 | Radiation<br>(03CH13-HY) |
| SHF-EHF Horn Antenna | SCHWARZBECK       | BBHA 9170                           | BBHA917098<br>0 | 18GHz~40GHz                   | Jan. 10, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Jan. 09, 2021 | Radiation<br>(03CH13-HY) |
| Filter               | Wainwright        | WHKX12-2700<br>-3000-18000-6<br>OSS | SN2             | 3GHz High Pass Filter         | Jul. 13, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Jul. 12, 2021 | Radiation<br>(03CH13-HY) |
| Filter               | Wainwright        | WHKX12-1080<br>-1200-15000-6<br>OSS | SN3             | 1.2GHz High Pass Filter       | Jul. 02, 2020    | Oct. 06, 2020~<br>Oct. 12, 2020 | Jul. 01, 2021 | Radiation<br>(03CH13-HY) |



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|   |      |
|---|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 3.10 |
|---|------|

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

|   |      |
|---|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 3.12 |
|---|------|

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

|   |      |
|---|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 3.77 |
|---|------|



### Appendix A. Test Results of Radiated Test

### LTE Band 13

| LTE Band 13 / 5MHz / 256QAM |                   |             |               |                   |                   |                    |                      |                       |                    |
|-----------------------------|-------------------|-------------|---------------|-------------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Channel                     | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest                      | 1554              | -61.17      | -13           | -48.17            | -74.51            | -66.23             | 1.19                 | 8.41                  | H                  |
|                             | 2332              | -58.04      | -13           | -45.04            | -75.44            | -64.84             | 1.41                 | 10.37                 | H                  |
|                             | 3109              | -56.72      | -13           | -43.72            | -75.44            | -64.25             | 1.55                 | 11.23                 | H                  |
|                             | 1554              | -61.69      | -13           | -48.69            | -74.81            | -66.75             | 1.19                 | 8.41                  | V                  |
|                             | 2332              | -57.78      | -13           | -44.78            | -75.71            | -64.58             | 1.41                 | 10.37                 | V                  |
|                             | 3109              | -56.95      | -13           | -43.95            | -75.96            | -64.48             | 1.55                 | 11.23                 | V                  |
| Middle                      | 1560              | -61.19      | -42.15        | -19.04            | -74.46            | -66.28             | 1.19                 | 8.43                  | H                  |
|                             | 2340              | -58.17      | -13           | -45.17            | -75.51            | -64.98             | 1.41                 | 10.37                 | H                  |
|                             | 3120              | -56.42      | -13           | -43.42            | -75.20            | -63.97             | 1.56                 | 11.26                 | H                  |
|                             | 1560              | -61.81      | -42.15        | -19.66            | -74.86            | -66.90             | 1.19                 | 8.43                  | V                  |
|                             | 2340              | -57.99      | -13           | -44.99            | -75.86            | -64.80             | 1.41                 | 10.37                 | V                  |
|                             | 3120              | -56.51      | -13           | -43.51            | -75.56            | -64.06             | 1.56                 | 11.26                 | V                  |
| Highest                     | 1564              | -61.71      | -42.15        | -19.56            | -74.94            | -66.81             | 1.19                 | 8.44                  | H                  |
|                             | 2347              | -58.69      | -13           | -45.69            | -75.99            | -65.50             | 1.42                 | 10.38                 | H                  |
|                             | 3129              | -56.64      | -13           | -43.64            | -75.46            | -64.21             | 1.57                 | 11.29                 | H                  |
|                             | 1564              | -61.61      | -42.15        | -19.46            | -74.62            | -66.71             | 1.19                 | 8.44                  | V                  |
|                             | 2347              | -58.02      | -13           | -45.02            | -75.85            | -64.83             | 1.42                 | 10.38                 | V                  |
|                             | 3129              | -56.75      | -13           | -43.75            | -75.82            | -64.32             | 1.57                 | 11.29                 | V                  |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.





**LTE Band 41 (HPUE)**

| LTE Band 41 (HPUE) / 5MHz / 256QAM |                   |              |               |                   |                   |                    |                      |                       |                    |
|------------------------------------|-------------------|--------------|---------------|-------------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Channel                            | Frequency ( MHz ) | EIRP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest                             | 5009              | -63.20       | -25           | -38.20            | -56.21            | -72.95             | 2.36                 | 12.10                 | H                  |
|                                    | 7515              | -53.28       | -25           | -28.28            | -51.68            | -61.22             | 2.11                 | 10.05                 | H                  |
|                                    | 10020             | -59.03       | -25           | -34.03            | -61.33            | -69.01             | 1.83                 | 11.81                 | H                  |
|                                    | 5009              | -57.92       | -25           | -32.92            | -51.54            | -67.67             | 2.36                 | 12.10                 | V                  |
|                                    | 7515              | -55.60       | -25           | -30.60            | -53.88            | -63.54             | 2.11                 | 10.05                 | V                  |
|                                    | 10020             | -59.95       | -25           | -34.95            | -61.36            | -69.93             | 1.83                 | 11.81                 | V                  |
| Middle                             | 5184              | -64.55       | -25           | -39.55            | -58.15            | -74.40             | 2.28                 | 12.14                 | H                  |
|                                    | 7774              | -57.73       | -25           | -32.73            | -56.22            | -66.60             | 2.11                 | 10.99                 | H                  |
|                                    | 10365             | -59.14       | -25           | -34.14            | -62.04            | -68.71             | 2.38                 | 11.95                 | H                  |
|                                    | 5184              | -55.33       | -25           | -30.33            | -49.48            | -65.18             | 2.28                 | 12.14                 | V                  |
|                                    | 7774              | -55.72       | -25           | -30.72            | -54.28            | -64.59             | 2.11                 | 10.99                 | V                  |
|                                    | 10365             | -59.35       | -25           | -34.35            | -62.02            | -68.92             | 2.38                 | 11.95                 | V                  |
| Highest                            | 5355              | -53.46       | -25           | -28.46            | -47.51            | -63.42             | 2.21                 | 12.17                 | H                  |
|                                    | 8033              | -54.91       | -25           | -29.91            | -54.72            | -64.65             | 2.11                 | 11.85                 | H                  |
|                                    | 10711             | -58.33       | -25           | -33.33            | -61.75            | -67.42             | 2.62                 | 11.70                 | H                  |
|                                    | 5355              | -60.90       | -25           | -35.90            | -55.47            | -70.86             | 2.21                 | 12.17                 | V                  |
|                                    | 8033              | -56.34       | -25           | -31.34            | -55.9             | -66.08             | 2.11                 | 11.85                 | V                  |
|                                    | 10711             | -58.13       | -25           | -33.13            | -61.59            | -67.22             | 2.62                 | 11.70                 | V                  |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

————THE END————