



# FCC RF Test Report

**APPLICANT** : Hewlett-Packard Company  
**EQUIPMENT** : Tablet PC  
**BRAND NAME** : hp  
**MODEL NAME** : HSTNN-C78C  
**FCC ID** : B94HNC78CHWWR  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)

The product was received on Oct. 21, 2013 and testing was completed on Nov. 05, 2013. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : B94HNC78CHWWR

Page Number : 1 of 58

Report Issued Date : Dec. 17, 2013

Report Version : Rev. 02



## TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT .....	4
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test .....	6
1.5 Modification of EUT .....	6
1.6 Maximum ERP/EIRP Power.....	7
1.7 Testing Site.....	7
1.8 Applied Standards .....	7
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System .....	10
2.3 Support Unit used in test configuration and system.....	10
2.4 Measurement Results Explanation Example .....	10
<b>3. TEST RESULT.....</b>	<b>11</b>
3.1 Conducted Output Power Measurement and ERP/EIRP Measurement.....	11
3.2 Field Strength of Spurious Radiation Measurement .....	14
<b>4. LIST OF MEASURING EQUIPMENT.....</b>	<b>58</b>





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	RSS-132 (5.4) RSS-133 (6.4) RSS-139 (6.4)	Conducted Output Power	Reporting Only	PASS	-
3.1	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.1	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.1	§27.50(d)(4)	RSS-139 (6.4) SRSP-513(5.1.2)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.2	§2.1053 §22.917(a) §24.238(a) §27.53(g)	RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.5)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 13.93 dB at 1672.000 MHz



# 1. General Description

## 1.1 Applicant

Hewlett-Packard Company  
3000 Hanover Street, Palo Alto, California 94304, USA

## 1.2 Manufacturer

COMPAL ELECTRONICS, INC.  
No. 581, Ruiguang Rd., Neihu District, Taipei City 11492, Taiwan (R.O.C.)

## 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	hp
Model Name	HSTNN-C78C
FCC ID	B94HNC78CHWWR
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA WLAN 11abgn / Bluetooth v4.0
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 32.91 dBm GSM1900 : 30.23 dBm WCDMA Band V : 24.30 dBm WCDMA Band IV : 23.83 dBm WCDMA Band II : 23.98 dBm
<b>Antenna Type</b>	Main: PIFA Antenna Aux.: Coupling Antenna
<b>Antenna Gain</b>	Cellular Band: 1.34 dBi PCS Band: 0.56 dBi AWS Band: 0.56 dBi
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum ERP/EIRP Power

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP(W)
Part 22	GSM850 GPRS class 8	GMSK	0.88
Part 22	GSM850 EDGE class 8	8PSK	0.22
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.12
Part 24	GSM1900 GPRS class 8	GMSK	1.20
Part 24	GSM1900 EDGE class 8	8PSK	0.43
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.28
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.28

## 1.7 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL INC.		
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC/IC Registration No.</b>
	TH02-HY	03CH07-HY	722060/4086B-1

## 1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01
- ♦ FCC KDB 412172 D01 Determining ERP and ERIP v01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2. Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes	
Band	Radiated TCs
GSM 850	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>
GSM 1900	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>
WCDMA Band V	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band IV	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>

**Note:**

1. The maximum power levels are GPRS multi-slot class8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, RMC 12.2Kbps mode for WCDMA band IV, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN, WLAN, and Bluetooth, the co-location test modes are not required.




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GPRS class 8	32.90	32.89	32.91	30.13	30.22	30.23
GPRS class 10	30.70	30.62	30.61	27.36	27.45	27.47
EGPRS class 8	26.99	26.89	26.84	25.62	25.68	25.74
EGPRS class 10	24.56	24.41	24.39	23.43	23.46	23.38
EGPRS class 11	23.01	22.88	22.88	21.90	21.81	21.87
EGPRS class 12	21.43	21.45	21.33	20.44	20.64	20.43

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	24.30	24.10	24.11	23.80	23.83	23.72	23.98	23.82	23.87
HSDPA Subtest-1	24.08	23.91	23.92	23.58	23.65	23.33	23.67	23.52	23.59
HSDPA Subtest-2	23.04	22.86	22.88	22.53	22.59	22.57	22.68	22.50	22.61
HSDPA Subtest-3	22.75	22.60	22.61	22.29	22.37	22.13	22.44	22.28	22.32
HSDPA Subtest-4	22.48	22.30	22.31	21.99	22.09	21.88	22.15	22.03	22.05
HSUPA Subtest-1	23.02	22.82	22.85	22.48	22.57	22.34	22.67	22.57	22.59
HSUPA Subtest-2	20.90	20.75	20.78	20.54	20.55	20.38	20.64	20.55	20.58
HSUPA Subtest-3	21.73	21.56	21.58	21.28	21.29	21.09	21.40	21.33	21.37
HSUPA Subtest-4	21.24	21.07	21.09	20.81	20.90	20.65	21.01	20.97	20.98
HSUPA Subtest-5	23.11	22.88	22.89	22.57	22.64	22.41	22.74	22.34	22.43

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	N/A	Unshielded, 1.0 m	N/A

## 2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3. Test Result

#### 3.1 Conducted Output Power Measurement and ERP/EIRP Measurement

##### 3.1.1 Description of the Conducted Output Power and ERP/EIRP Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band). According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for GSM and WCDMA modes.
5. The procedure section 2.0 of FCC KDB 412172 is used to determine the Radiated Power Measurement.

##### 3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band ( $G_T - L_C = -1.34$ dB)									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.9	32.89	32.91	26.99	26.89	26.84	24.3	24.1	24.11
Conducted Power (Watts)	1.95	1.95	1.95	0.50	0.49	0.48	0.27	0.26	0.26
ERP(dBm)	29.41	29.40	29.42	23.50	23.40	23.35	20.81	20.61	20.62
ERP(Watts)	0.87	0.87	0.88	0.22	0.22	0.22	0.12	0.12	0.12

PCS Band ( $G_T - L_C = 0.56$ dB)									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	30.13	30.22	30.23	25.62	25.68	25.74	23.80	23.83	23.72
Conducted Power (Watts)	1.03	1.05	1.05	0.36	0.37	0.37	0.24	0.24	0.24
EIRP(dBm)	30.69	30.78	30.79	26.18	26.24	26.30	24.36	24.39	24.28
EIRP(Watts)	1.17	1.20	1.20	0.42	0.42	0.43	0.27	0.28	0.27



AWS Band ( $G_T - L_C = 0.56$ dB)			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	23.98	23.82	23.87
Conducted Power (Watts)	0.25	0.24	0.24
EIRP(dBm)	24.54	24.38	24.43
EIRP(Watts)	0.28	0.27	0.28

**Note:** maximum burst average power for GSM, and maximum average power for WCDMA.

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB



## 3.2 Field Strength of Spurious Radiation Measurement

### 3.2.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.2.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] (dB)$   
 $= [30 + 10\log(P)] (dBm) - [43 + 10\log(P)] (dB)$   
 $= -13dBm$
12.  $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
13.  $ERP (dBm) = EIRP - 2.15$

### 3.2.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz






3.2.5 Test Result of Field Strength of Spurious Radiated

<Low Channel>

Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	51~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1649	-29.10	-13	-16.10	-38.1	-33.1	1.53	5.53	H	Pass
2474	-27.11	-13	-14.11	-40.45	-31.2	2.06	6.15	H	Pass
3298	-40.45	-13	-27.45	-55	-45.9	2.48	7.93	H	Pass
4123	-35.87	-13	-22.87	-52.48	-42.5	2.54	9.17	H	Pass
4948	-36.58	-13	-23.58	-54.52	-44.1	2.74	10.26	H	Pass
5772	-38.17	-13	-25.17	-59.58	-45.9	2.97	10.70	H	Pass
6597	-36.32	-13	-23.32	-61.05	-44.2	3.2	11.08	H	Pass
7422	-39.43	-13	-26.43	-66.97	-48	3.47	12.04	H	Pass





<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1649	-28.10	-13	-15.10	-39.26	-32.1	1.53	5.53	V	Pass
2474	-33.61	-13	-20.61	-47.27	-37.7	2.06	6.15	V	Pass
3298	-42.25	-13	-29.25	-58.05	-47.7	2.48	7.93	V	Pass
4123	-35.37	-13	-22.37	-52.44	-42	2.54	9.17	V	Pass
4948	-38.38	-13	-25.38	-56.38	-45.9	2.74	10.26	V	Pass
5772	-32.37	-13	-19.37	-53.77	-40.1	2.97	10.70	V	Pass
6597	-34.22	-13	-21.22	-57.45	-42.1	3.2	11.08	V	Pass
7422	-38.06	-13	-25.06	-65.14	-46.63	3.47	12.04	V	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1649	-33.70	-13	-20.70	-42.6	-37.7	1.53	5.53	H	Pass
2474	-28.91	-13	-15.91	-42.14	-33	2.06	6.15	H	Pass
3298	-40.45	-13	-27.45	-54.84	-45.9	2.48	7.93	H	Pass
4123	-43.57	-13	-30.57	-60.17	-50.2	2.54	9.17	H	Pass
4948	-44.98	-13	-31.98	-62.76	-52.5	2.74	10.26	H	Pass
5772	-47.07	-13	-34.07	-68.48	-54.8	2.97	10.70	H	Pass
6597	-40.52	-13	-27.52	-65.15	-48.4	3.2	11.08	H	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1649	-31.20	-13	-18.20	-42.53	-35.2	1.53	5.53	V	Pass
2474	-36.41	-13	-23.41	-50.38	-40.5	2.06	6.15	V	Pass
3298	-43.75	-13	-30.75	-59.44	-49.2	2.48	7.93	V	Pass
4123	-45.47	-13	-32.47	-62.43	-52.1	2.54	9.17	V	Pass
4948	-42.58	-13	-29.58	-60.69	-50.1	2.74	10.26	V	Pass
5772	-43.17	-13	-30.17	-64.26	-50.9	2.97	10.70	V	Pass
6597	-36.02	-13	-23.02	-60.63	-43.9	3.2	11.08	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3700	-43.57	-13	-30.57	-58.62	-49.72	2.59	8.74	H	Pass
5552	-39.63	-13	-26.63	-60.12	-47.29	3.04	10.70	H	Pass
7400	-40.91	-13	-27.91	-68.36	-49.65	3.28	12.02	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3700	-46.32	-13	-33.32	-62.39	-52.47	2.59	8.74	V	Pass
5552	-40.26	-13	-27.26	-60.43	-47.92	3.04	10.70	V	Pass
7400	-42.14	-13	-29.14	-69.02	-50.88	3.28	12.02	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3700	-34.87	-13	-21.87	-50.01	-41.02	2.59	8.74	H	Pass
5552	-27.22	-13	-14.22	-47.54	-34.88	3.04	10.70	H	Pass
7400	-31.72	-13	-18.72	-59.3	-40.46	3.28	12.02	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3700	-39.81	-13	-26.81	-56.08	-45.96	2.59	8.74	V	Pass
5552	-27.49	-13	-14.49	-47.85	-35.15	3.04	10.70	V	Pass
7400	-37.27	-13	-24.27	-64.23	-46.01	3.28	12.02	V	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1651	-43.22	-13	-30.22	-52.01	-47.22	1.53	5.53	H	Pass
2482	-46.39	-13	-33.39	-59.51	-50.48	2.06	6.15	H	Pass
3301	-52.24	-13	-39.24	-66.11	-57.69	2.48	7.93	H	Pass





<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1651	-40.85	-13	-27.85	-51.77	-44.85	1.53	5.53	V	Pass
2482	-41.27	-13	-28.27	-55.02	-45.36	2.06	6.15	V	Pass
3302	-51.21	-13	-38.21	-66.81	-56.66	2.48	7.93	V	Pass



<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3420	-32.37	-13	-19.37	-46.81	-36.2	4.48	8.31	H	Pass
5140	-39.26	-13	-26.26	-57.8	-43.9	5.332	9.98	H	Pass
6848	-43.86	-13	-30.86	-69.73	-49.1	6.1	11.34	H	Pass



<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3420	-32.27	-13	-19.27	-48.85	-36.1	4.48	8.31	V	Pass
5140	-38.56	-13	-25.56	-57.48	-43.2	5.332	9.98	V	Pass
6848	-43.86	-13	-30.86	-69.26	-49.1	6.1	11.34	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3704	-42.95	-13	-29.95	-58.14	-49.1	2.59	8.74	H	Pass
5552	-46.44	-13	-33.44	-66.94	-54.1	3.04	10.70	H	Pass
7408	-41.36	-13	-28.36	-68.68	-50.1	3.28	12.02	H	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3700	-44.35	-13	-31.35	-60.82	-50.5	2.59	8.74	V	Pass
5556	-43.84	-13	-30.84	-64.29	-51.5	3.04	10.70	V	Pass
7412	-41.66	-13	-28.66	-68.92	-50.4	3.28	12.02	V	Pass



<Middle Channel>

<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-26.93	-13	-13.93	-35.94	-30.8	1.62	5.49	H	Pass
2509	-29.98	-13	-16.98	-43.45	-34.1	2.1	6.22	H	Pass
3345	-40.66	-13	-27.66	-54.7	-45.7	3.03	8.07	H	Pass
4182	-35.41	-13	-22.41	-51.71	-42.1	2.52	9.21	H	Pass
5018	-37.50	-13	-24.50	-55.58	-45.1	3.1	10.70	H	Pass
5854	-39.11	-13	-26.11	-60.7	-46.5	2.92	10.31	H	Pass
6691	-37.33	-13	-24.33	-62.84	-45.1	3.38	11.15	H	Pass
7527	-40.20	-13	-27.20	-62.77	-48.8	3.52	12.12	H	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-30.43	-13	-17.43	-41.91	-34.3	1.62	5.49	V	Pass
2509	-36.76	-13	-23.76	-50.66	-40.88	2.1	6.22	V	Pass
3345	-40.36	-13	-27.36	-56.15	-45.4	3.03	8.07	V	Pass
4182	-31.81	-13	-18.81	-48.94	-38.5	2.52	9.21	V	Pass
5018	-37.40	-13	-24.40	-55.79	-45	3.1	10.70	V	Pass
5854	-33.81	-13	-20.81	-55.42	-41.2	2.92	10.31	V	Pass
6691	-33.63	-13	-20.63	-58.12	-41.4	3.38	11.15	V	Pass
7527	-36.80	-13	-23.80	-64.21	-45.4	3.52	12.12	V	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-28.33	-13	-15.33	-37.52	-32.2	1.62	5.49	H	Pass
2509	-31.18	-13	-18.18	-44.55	-35.3	2.1	6.22	H	Pass
3345	-39.06	-13	-26.06	-53.1	-44.1	3.03	8.07	H	Pass
4182	-42.51	-13	-29.51	-58.1	-49.2	2.52	9.21	H	Pass
5018	-38.00	-13	-25.00	-55.93	-45.6	3.1	10.70	H	Pass
5854	-43.81	-13	-30.81	-65.84	-51.2	2.92	10.31	H	Pass
6691	-40.33	-13	-27.33	-65.7	-48.1	3.38	11.15	H	Pass





<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-34.83	-13	-21.83	-46.02	-38.7	1.62	5.49	V	Pass
2509	-30.68	-13	-17.68	-44.51	-34.8	2.1	6.22	V	Pass
3345	-41.36	-13	-28.36	-57.15	-46.4	3.03	8.07	V	Pass
4182	-45.01	-13	-32.01	-62.21	-51.7	2.52	9.21	V	Pass
5018	-39.50	-13	-26.50	-57.37	-47.1	3.1	10.70	V	Pass
5854	-38.81	-13	-25.81	-60.63	-46.2	2.92	10.31	V	Pass
6691	-35.43	-13	-22.43	-59.88	-43.2	3.38	11.15	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-42.06	-13	-29.06	-57.44	-48.36	2.51	8.81	H	Pass
5640	-41.47	-13	-28.47	-62.37	-49.18	2.99	10.70	H	Pass
7520	-38.58	-13	-25.58	-65.86	-47.11	3.59	12.12	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-41.71	-13	-28.71	-58.01	-48.01	2.51	8.81	V	Pass
5640	-38.12	-13	-25.12	-58.7	-45.83	2.99	10.70	V	Pass
7520	-38.09	-13	-25.09	-65.12	-46.62	3.59	12.12	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-39.28	-13	-26.28	-54.78	-45.58	2.51	8.81	H	Pass
5640	-33.52	-13	-20.52	-54.3	-41.23	2.99	10.70	H	Pass
7520	-37.34	-13	-24.34	-64.38	-45.87	3.59	12.12	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-41.33	-13	-28.33	-57.45	-47.63	2.51	8.81	V	Pass
5640	-31.57	-13	-18.57	-52.1	-39.28	2.99	10.70	V	Pass
7520	-40.16	-13	-27.16	-67.34	-48.69	3.59	12.12	V	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1669	-39.14	-13	-26.14	-48	-43.01	1.62	5.49	H	Pass
2512	-38.27	-13	-25.27	-51.8	-42.39	2.1	6.22	H	Pass
3338	-53.39	-13	-40.39	-67.36	-58.43	3.03	8.07	H	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1669	-41.07	-13	-28.07	-52	-44.94	1.62	5.49	V	Pass
2512	-36.73	-13	-23.73	-50.65	-40.85	2.1	6.22	V	Pass
3338	-52.32	-13	-39.32	-67.94	-57.36	3.03	8.07	V	Pass



<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3464	-38.27	-13	-25.27	-52.84	-42.1	4.48	8.31	H	Pass
5200	-37.06	-13	-24.06	-55.96	-41.7	5.332	9.98	H	Pass
6931	-43.56	-13	-30.56	-69.83	-48.8	6.1	11.34	H	Pass





<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3464	-36.67	-13	-23.67	-52.42	-40.5	4.48	8.31	V	Pass
5200	-36.56	-13	-23.56	-55.57	-41.2	5.332	9.98	V	Pass
6931	-44.16	-13	-31.16	-69.65	-49.4	6.1	11.34	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3756	-44.70	-13	-31.70	-60.25	-51	2.51	8.81	H	Pass
5644	-47.39	-13	-34.39	-68.33	-55.1	2.99	10.70	H	Pass
7520	-39.57	-13	-26.57	-67.27	-48.1	3.59	12.12	H	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3756	-46.00	-13	-33.00	-62.4	-52.3	2.51	8.81	V	Pass
5644	-47.69	-13	-34.69	-68.67	-55.4	2.99	10.70	V	Pass
7520	-38.67	-13	-25.67	-66.25	-47.2	3.59	12.12	V	Pass



<High Channel>

Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	51~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1696	-28.62	-13	-15.62	-37.93	-32.5	1.57	5.45	H	Pass
2544	-35.24	-13	-22.24	-48.72	-39.5	2.02	6.28	H	Pass
3393	-36.20	-13	-23.20	-50.37	-42.1	2.3	8.20	H	Pass
4241	-39.29	-13	-26.29	-55.64	-45.8	2.73	9.24	H	Pass
5089	-39.48	-13	-26.48	-58.03	-47.1	2.75	10.37	H	Pass
5938	-38.81	-13	-25.81	-60.96	-46.5	3.01	10.70	H	Pass
6786	-38.07	-13	-25.07	-64.06	-45.9	3.4	11.23	H	Pass
7634	-39.28	-13	-26.28	-65.81	-48	3.49	12.21	H	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1696	-35.62	-13	-22.62	-47.06	-39.5	1.57	5.45	V	Pass
2544	-39.94	-13	-26.94	-54.13	-44.2	2.02	6.28	V	Pass
3393	-37.50	-13	-24.50	-53.56	-43.4	2.3	8.20	V	Pass
4241	-37.39	-13	-24.39	-54.51	-43.9	2.73	9.24	V	Pass
5089	-37.38	-13	-24.38	-55.73	-45	2.75	10.37	V	Pass
5938	-35.51	-13	-22.51	-57.31	-43.2	3.01	10.70	V	Pass
6786	-30.67	-13	-17.67	-55.7	-38.5	3.4	11.23	V	Pass
7634	-38.88	-13	-25.88	-65.17	-47.6	3.49	12.21	V	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-32.90	-13	-19.90	-40.91	-36.78	1.57	5.45	H	Pass
2544	-38.66	-13	-25.66	-50.96	-42.92	2.02	6.28	H	Pass
3393	-38.52	-13	-25.52	-51.7	-44.42	2.3	8.20	H	Pass
4241	-43.59	-13	-30.59	-59.95	-50.1	2.73	9.24	H	Pass
5089	-45.88	-13	-32.88	-64.01	-53.5	2.75	10.37	H	Pass
5938	-44.11	-13	-31.11	-66.16	-51.8	3.01	10.70	H	Pass
6786	-42.27	-13	-29.27	-68.8	-50.1	3.4	11.23	H	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-34.32	-13	-21.32	-45.84	-38.2	1.57	5.45	V	Pass
2544	-39.24	-13	-26.24	-53.39	-43.5	2.02	6.28	V	Pass
3393	-37.30	-13	-24.30	-53.18	-43.2	2.3	8.20	V	Pass
4241	-45.59	-13	-32.59	-62.53	-52.1	2.73	9.24	V	Pass
5089	-41.88	-13	-28.88	-60.21	-49.5	2.75	10.37	V	Pass
5938	-42.01	-13	-29.01	-63.64	-49.7	3.01	10.70	V	Pass
6786	-32.97	-13	-19.97	-57.91	-40.8	3.4	11.23	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3820	-47.81	-13	-34.81	-63.45	-54.22	2.47	8.88	H	Pass
5732	-45.40	-13	-32.40	-66.42	-53.1	3	10.70	H	Pass
7640	-40.36	-13	-27.36	-66.74	-49.14	3.43	12.21	H	Pass





<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3820	-47.60	-13	-34.60	-63.96	-54.01	2.47	8.88	V	Pass
5730	-48.17	-13	-35.17	-68.87	-55.87	3	10.70	V	Pass
7640	-39.24	-13	-26.24	-65.38	-48.02	3.43	12.21	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3820	-39.60	-13	-26.60	-55.03	-46.01	2.47	8.88	H	Pass
5732	-40.22	-13	-27.22	-61.24	-47.92	3	10.70	H	Pass
7640	-41.25	-13	-28.25	-67.52	-50.03	3.43	12.21	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3820	-45.33	-13	-32.33	-61.73	-51.74	2.47	8.88	V	Pass
5732	-41.51	-13	-28.51	-62.79	-49.21	3	10.70	V	Pass
7636	-39.99	-13	-26.99	-66.34	-48.77	3.43	12.21	V	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1693	-43.22	-13	-30.22	-52.12	-47.1	1.57	5.45	H	Pass
2542	-50.99	-13	-37.99	-64.22	-55.25	2.02	6.28	H	Pass
3385	-52.27	-13	-39.27	-66.53	-58.17	2.3	8.20	H	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1696	-44.37	-13	-31.37	-55.7	-48.25	1.57	5.45	V	Pass
2536	-49.50	-13	-36.50	-63.31	-53.76	2.02	6.28	V	Pass
3385	-52.40	-13	-39.40	-67.71	-58.3	2.3	8.20	V	Pass



<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3504	-38.27	-13	-25.27	-52.92	-42.1	4.48	8.31	H	Pass
5260	-40.06	-13	-27.06	-59.36	-44.7	5.332	9.98	H	Pass
7012	-42.26	-13	-29.26	-68.96	-47.5	6.1	11.34	H	Pass



<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3504	-32.27	-13	-19.27	-48.02	-36.1	4.48	8.31	V	Pass
5260	-36.86	-13	-23.86	-56.28	-41.5	5.332	9.98	V	Pass
7012	-43.66	-13	-30.66	-68.86	-48.9	6.1	11.34	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) HORIZONTAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3817	-44.69	-13	-31.69	-60.25	-51.1	2.47	8.88	H	Pass
5726	-48.40	-13	-35.40	-69.81	-56.1	3	10.70	H	Pass
7635	-40.22	-13	-27.22	-66.59	-49	3.43	12.21	H	Pass





<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~24°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	51~54%
<b>Test Engineer :</b>	Eric Shih	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY  
 Condition : -13 HF-EIRP(080306) VERTICAL  
 Project : FG 392719-03

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3817	-44.09	-13	-31.09	-60.61	-50.5	2.47	8.88	V	Pass
5726	-48.70	-13	-35.70	-69.87	-56.4	3	10.70	V	Pass
7635	-39.32	-13	-26.32	-66.08	-48.1	3.43	12.21	V	Pass



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	Rohde & Schwarz	CMU200	117995	N/A	Aug. 01, 2013	Nov. 05, 2013	Jul. 31, 2014	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz~30GHz	Nov. 30, 2012	Oct. 31, 2013 ~ Nov. 02, 2013	Nov. 29, 2013	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Oct. 10, 2013	Oct. 31, 2013 ~ Nov. 02, 2013	Oct. 09, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1GHz~18GHz	Aug. 22, 2013	Oct. 31, 2013 ~ Nov. 02, 2013	Aug. 21, 2014	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 03, 2013	Oct. 31, 2013 ~ Nov. 02, 2013	Oct. 02, 2014	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	30MHz~1GHz	Feb. 26, 2013	Oct. 31, 2013 ~ Nov. 02, 2013	Feb. 25, 2014	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Dec. 01, 2012	Oct. 31, 2013 ~ Nov. 02, 2013	Nov. 30, 2013	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Oct. 31, 2013 ~ Nov. 02, 2013	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	ChainTek 3000	N/A	N/A	N/A	Oct. 31, 2013 ~ Nov. 02, 2013	N/A	Radiation (03CH07-HY)