

Label information Model : HSN-I29C

1. Images of the e-label screen are provided below:

FCC ID: B94HNI29CPK
 Contains IC: 21374-L860GL, Model: L860-GL
 Contains FCC ID: B94-AX200D2LZ
 Contains IC: 466Q-AX200D2LCN , Model: AX200D2WL

2. The information that will be displayed on the e-label and information that will remain in the user manual is shown below:

Information	on E-label	In Manual
FCC ID/IC number	Yes	No
DoC logo	No	No
<i>Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.”)</i>	No	Yes
Class A / B Digital Device user manual statements ₁	No	Yes

3. Users are able to access the information in no more than four steps in a device’s menu.

The actual Steps are: Press esc or f10 > Advanced > Electronic Labels
 No special access codes or permissions are required to go through the above steps beyond entering a user-defined password to protect against unauthorized access to the device.

4. The information is stored on the device, no special accessories or supplemental plug-ins (e.g., a SIM/USIM card) are required to access the information.

No.

5. Users are provided specific instructions on how to access the information.


Yes.

6. The above information must be programmed by the responsible party and the information must be secured in such a manner that third-parties cannot modify it.

The e-label information is pre-programmed by the grantee. The user cannot modify the e-label formation.

7. When e-label is used, a physical temporary label is also required on the product, or a label on the packaging, at the time of importation, marketing, and sales.

The physical label will be on the packaging box.

	CAN ICES-3 (B)/NMB-3(B)
FCC ID: B94HNI29CPK Contains IC: 21374-L860GL, Model: L860-GL Contains FCC ID: B94-AX200D2LZ Contains IC: 466Q-AX200D2LCN , Model: AX200D2WL	
This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause Harmful interference, and (2) this device must accept any interference received, Including Interference that may cause undesired operation.	