



Statement of compliance to Maximum Permissible Exposure (MPE)

Equipment : HP Photosmart 5510 e-All-in-One series
Type/Model : SNPRH-1001
Applicant : Hewlett Packard Company
3000 Hanover Street, Palo Alto, California, 94304, USA

Here assuming a worst-case prediction of power density (100% reflection), then
 $S = 4PG / (4\pi R^2) = PG / (\pi R^2)$.

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report SH11071523-001:

The maximum P = 22.10dBm = 162.18

G = 3.80dBi = 2.40

Here R is chosen to be 20cm,

$$S = PG / (\pi R^2) = 162.18 * 2.40 / (3.14 * 20 * 20) = 0.31 \text{mW/cm}^2$$

This level is below the 1 mW/cm² MPE for General Population / Uncontrolled Exposure as stated in OET BULLETIN 65 Edition 97-01.

Conclusion: this EUT fulfills 47CFR Part 15.247(i) (2007) with the definition outlined in the User's Manual. (See appendix I)

Date of issue: Sep 7, 2011

Prepared by:

Wakeyou Wang (Project Engineer)

Reviewed by:

Daniel Zhao (Reviewer)



FCC ID: B94SNPRH1001
IC: 466D-SNPRH001

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.