

## FCC Test Report (Part 96)

**Report No.:** RF200109E02-4

**FCC ID:** 2AQ68T99W175

**Test Model:** T99W175

**Received Date:** Jan. 10, 2020

**Test Date:** Feb. 11 ~ May 27, 2020

**Issued Date:** May 28, 2020

**Applicant:** Hon Lin Technology Co., Ltd.

**Address:** 11F, No. 32, Jihu Rd., Neihu Dist., Taipei City 114, Taiwan R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan

**FCC Registration/  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>4</b>
<b>1 Certificate of Conformity</b> .....	<b>5</b>
<b>2 Summary of Test Results</b> .....	<b>6</b>
2.1 Measurement Uncertainty .....	6
2.2 Modification Record .....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Test Mode Applicability and Tested Channel Detail .....	11
3.3 Description of Support Units .....	14
3.3.1 Configuration of System under Test .....	14
3.4 General Description of Applied Standards and References.....	15
<b>4 Test Types and Results</b> .....	<b>16</b>
4.1 Maximum Output Power Measurement .....	16
4.1.1 Limits of Maximum Output Power Measurement .....	16
4.1.2 Test Setup.....	16
4.1.3 Test Instruments .....	17
4.1.4 Test Procedures.....	18
4.1.5 Deviation from Test Standard .....	18
4.1.6 EUT Operating Conditions.....	18
4.1.7 Test Results .....	19
4.2 Modulation Characteristics Measurement.....	35
4.2.1 Limits of Modulation Characteristics.....	35
4.2.2 Test Procedure .....	35
4.2.3 Test Setup.....	35
4.2.4 Test Results .....	35
4.3 Frequency Stability Measurement.....	36
4.3.1 Limits of Frequency Stability Measurement.....	36
4.3.2 Test Procedure .....	36
4.3.3 Test Setup.....	36
4.3.4 Test Results .....	37
4.4 Emission Bandwidth Measurement.....	45
4.4.1 Emission Bandwidth Measurement.....	45
4.4.2 Test Setup.....	45
4.4.3 Test Instruments .....	45
4.4.4 Test Procedure .....	45
4.4.5 Deviation from Test Standard .....	45
4.4.6 EUT Operating Conditions.....	45
4.4.7 Test Result (-26dB Bandwidth).....	46
4.4.8 Test Result (Occupied Bandwidth) .....	50
4.5 Peak to Average Ratio Measurement .....	54
4.5.1 Limits of Peak to Average Ratio Measurement .....	54
4.5.2 Test Setup.....	54
4.5.3 Test Procedures.....	54
4.5.4 Test Results .....	55
4.6 Conducted Spurious Emissions .....	59
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	59
4.6.2 Test Setup.....	59
4.6.3 Test Procedure .....	59
4.6.4 Test Results .....	60
4.7 Radiated Emission Measurement .....	80
4.7.1 Limits of Radiated Emission Measurement.....	80
4.7.2 Test Instruments .....	80

4.7.3 Test Procedures.....	80
4.7.4 Deviation from Test Standard .....	80
4.7.5 Test Set Up .....	81
4.7.6 Test Results .....	82
<b>5 Pictures of Test Arrangements.....</b>	<b>90</b>
<b>Appendix – Information of the Testing Laboratories .....</b>	<b>91</b>

### Release Control Record

Issue No.	Description	Date Issued
RF200109E02-4	Original release	May 28, 2020

## 1 Certificate of Conformity

**Product:** 5G WWAN Module

**Brand:** Foxconn

**Test Model:** T99W175

**Sample Status:** Engineering sample

**Applicant:** Hon Lin Technology Co., Ltd.

**Test Date:** Feb. 11 ~ May 27, 2020

**Standards:** FCC 47 CFR Part 96

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Pettie Chen , **Date:** May 28, 2020  
Pettie Chen / Senior Specialist

**Approved by :** Bruce Chen , **Date:** May 28, 2020  
Bruce Chen / Senior Project Engineer

## 2 Summary of Test Results

47 CFR FCC Part 96			
FCC Clause	Test Item	Result	Remarks
2.1046 96.41(b)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1047 96.41(a)	Modulation Characteristics	Pass	Meet the requirement
2.1046 96.41(b)	Maximum Power Spectral Density	Pass	Meet the requirement of limit.
96.41(g)	Peak to Average Ration	Pass	Meet the requirement of limit.
2.1049	Emission Bandwidth	Pass	Meet the requirement of limit.
2.1055	Frequency Stability	Pass	Meet the requirement of limit.
2.1051 96.41(e)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 96.41(e)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -4.2dB at 58.13MHz.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	9 kHz ~ 30MHz	3.04 dB
	30 MHz ~ 200 MHz	3.59 dB
	200 MHz ~ 1000 MHz	3.60 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	5G WWAN Module						
Brand	Foxconn						
Test Model	T99W175						
Status of EUT	Engineering sample						
Power Supply Rating	5 Vdc (Host equipment) 3.135Vdc~3.63Vdc (Module)						
Modulation Type	QPSK, 16QAM, 64QAM						
Operating Frequency	LTE Band 48	Channel Bandwidth 5MHz	TX: 3552.5 ~ 3697.5 MHz RX: 3552.5 ~ 3697.5 MHz				
		Channel Bandwidth 10MHz	TX: 3555 ~ 3695 MHz RX: 3555 ~ 3695 MHz				
		Channel Bandwidth 15MHz	TX: 3557.5 ~ 3692.5 MHz RX: 3557.5 ~ 3692.5 MHz				
		Channel Bandwidth 20MHz	TX: 3560 ~ 3690 MHz RX: 3560 ~ 3690 MHz				
	LTE Band 42	Channel Bandwidth 5MHz	TX: 3552.5 ~ 3597.5 MHz RX: 3552.5 ~ 3597.5 MHz				
		Channel Bandwidth 10MHz	TX: 3555 ~ 3595 MHz RX: 3555 ~ 3595 MHz				
		Channel Bandwidth 15MHz	TX: 3557.5 ~ 3592.5 MHz RX: 3557.5 ~ 3592.5 MHz				
		Channel Bandwidth 20MHz	TX: 3560 ~ 3590 MHz RX: 3560 ~ 3590 MHz				
	Max. EIRP Power	LTE Band 48		QPSK	16QAM	64QAM	
			<b>Per 10M</b>				
			Channel Bandwidth 5MHz	164.816mW (22.17dBm)	141.254mW (21.50dBm)	107.399mW (20.31dBm)	
			Channel Bandwidth 10MHz	170.216mW (22.31dBm)	141.579mW (21.51dBm)	111.944mW (20.49dBm)	
Channel Bandwidth 15MHz			189.671mW (22.78dBm)	153.109mW (21.85dBm)	122.462mW (20.88dBm)		
Channel Bandwidth 20MHz			187.068mW (22.72dBm)	145.546mW (21.63dBm)	121.899mW (20.86dBm)		
<b>Full Power</b>							
Channel Bandwidth 5MHz			164.816mW (22.17dBm)	141.254mW (21.50dBm)	107.399mW (20.31dBm)		
Channel Bandwidth 10MHz			170.216mW (22.31dBm)	141.579mW (21.51dBm)	111.944mW (20.49dBm)		
Channel Bandwidth 15MHz			190.985mW (22.81dBm)	165.577mW (22.19dBm)	127.644mW (21.06dBm)		
Channel Bandwidth 20MHz			195.884mW (22.92dBm)	169.434mW (22.29dBm)	127.350mW (21.05dBm)		

Max. EIRP Power	LTE Band 42		QPSK	16QAM	64QAM	
		<b>Per 10M</b>				
		Channel Bandwidth 5MHz	160.694mW (22.06dBm)	136.144mW (21.34dBm)	105.925mW (20.25dBm)	
		Channel Bandwidth 10MHz	168.267mW (22.26dBm)	138.995mW (21.43dBm)	109.648mW (20.40dBm)	
		Channel Bandwidth 15MHz	180.302mW (22.56dBm)	144.544mW (21.60dBm)	114.551mW (20.59dBm)	
		Channel Bandwidth 20MHz	177.011mW (22.48dBm)	138.995mW (21.43dBm)	111.686mW (20.48dBm)	
		<b>Full Power</b>				
		Channel Bandwidth 5MHz	160.694mW (22.06dBm)	136.144mW (21.34dBm)	105.925mW (20.25dBm)	
		Channel Bandwidth 10MHz	168.267mW (22.26dBm)	138.995mW (21.43dBm)	109.648mW (20.40dBm)	
		Channel Bandwidth 15MHz	183.654mW (22.64dBm)	155.597mW (21.92dBm)	120.226mW (20.80dBm)	
Channel Bandwidth 20MHz	190.108mW (22.79dBm)	167.109mW (22.23dBm)	123.310mW (20.91dBm)			
Emission Designator	LTE Band 48	Channel Bandwidth 5MHz	4M49G7D	4M49D7W	4M49D7W	
		Channel Bandwidth 10MHz	8M96G7D	8M97D7W	8M96D7W	
		Channel Bandwidth 15MHz	13M5G7D	13M4D7W	13M4D7W	
		Channel Bandwidth 20MHz	17M9G7D	17M9D7W	17M9D7W	
	LTE Band 42	Channel Bandwidth 5MHz	4M48G7D	4M49D7W	4M49D7W	
		Channel Bandwidth 10MHz	8M95G7D	8M97D7W	8M96D7W	
		Channel Bandwidth 15MHz	13M5G7D	13M4D7W	13M4D7W	
		Channel Bandwidth 20MHz	17M9G7D	17M9D7W	17M9D7W	
Antenna Type	Refer to Note as below					
Antenna Connector	Refer to Note as below					
Accessory Device	NA					
Cable Supplied	NA					

Note:

1. There are four Difference HW of T99W175.

Brand	Model	HW
Foxconn	T99W175	1. 3G+LTE+Sub6+eSIM
		2. 3G+LTE+Sub6 only w/o eSIM
		3. 3G+LTE+Sub6+eSIM+GNSS connector
		4. 3G+LTE+Sub6 only+w/o eSIM+GNSS connector

\*After pre-testing, "HW: 1. 3G+LTE+Sub6+eSIM" is the worst for the final tests.



## 2. The following antennas were provided to the EUT.

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain(dBi)	Frequency range (MHz)	Antenna Type	Connector Type
1		WHA YU	C107-511720-A	4.41	660~803	PCB	I-PEX
2		WHA YU	C107-511721-A	3.81 4.03	791~960 1447.9~1606	PCB	I-PEX
3		WHA YU	C107-511722-A	4.27 5.31	1710~2170 2500~2690	PCB	I-PEX
4		WHA YU	C107-511723-A	2.99 0.92	2300~2400 3500~3700	PCB	I-PEX
5		WHA YU	C107-511724-A	6.45	5150~5925	PCB	I-PEX
6		WHA YU	C107-511725-A	4.89	3400~3700	PCB	I-PEX
7		AVX	5000106-R1-X01	2.91	699~803	Monopole	I-PEX
8		AVX	5000107-R1-X01	2.59	791~960	Monopole	I-PEX
9		AVX	5000108-R1-X01	2.85	1427~1610	Monopole	I-PEX
10		AVX	5000109-R1-X01	2.23 2.94	1710~2200 5150~5925	Monopole	I-PEX
11		AVX	5000110-R1-X01	0.9	2300~2690	Monopole	I-PEX
12		AVX	5000111-R1-X01	0.87	3300~5000	Monopole	I-PEX
13	Tx1/ Rx1	Ethertronics	5003806	0.4 -1.61 0.39 2.95 1.98 0.38 0.83 2.31	698-821 824-960 1425-1515 1710-2200 2300-2690 3300-4200 4400-5000 5150-5925	PIFA	I-PEX
	Rx2	Ethertronics	5003807	-2.24 -4.52 2.87 2.99 2.93 2.91 2.23 -0.85 -3.04	716-821 824-960 1425-1515 1557-1610 1805-2200 2300-2690 3300-4200 4400-5000 5150-5925	PIFA	I-PEX
	Tx2/ Rx3	Ethertronics	5003806	2.21 2.25 -0.45 2.6	1710-2200 2300-2690 3300-4200 4400-5000	PIFA	I-PEX
	Rx4	Ethertronics	5003700	1.38 2.87 0.6 -2.09	1805-2200 2300-2690 3300-4200 4400-5000	PIFA	I-PEX

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain(dBi)	Frequency range (MHz)	Antenna Type	Connector Type
14	Ant. 0 (TX/RX)	Master Wave	NA	2.4 2.2 2.9 2.9 2.9 NA	880~960 1020~2170 2545~2595 3565~3600 3900~4000 GPS	PCB	I-PEX
	Ant. 2 (TX/RX)	Master Wave	NA	NA 2.2 2.8 2.9 2.8 NA	880~960 1020~2170 2545~2595 3565~3600 3900~4000 GPS	PCB	I-PEX
	Ant. 1 (RX)	Master Wave	NA	NA 5.3 5.1 4.3 4.5 NA	880~960 1020~2170 2545~2595 3565~3600 3900~4000 GPS	PCB	I-PEX
	Ant. 3 (RX)	Master Wave	NA	1.3 6.8 3.7 6.4 6.2 3.7	880~960 1020~2170 2545~2595 3565~3600 3900~4000 GPS	PCB	I-PEX

\*The antenna for the final tests as following table.

	Band	Antenna
WCDMA	2	Antenna 3
	4	Antenna 3
	5	Antenna 2
LTE	2	Antenna 3
	4	Antenna 3
	5	Antenna 2
	7	Antenna 3
	12	Antenna 1
	13	Antenna 1
	14	Antenna 1
	17	Antenna 1
	25	Antenna 3
	26	Antenna 2
	30	Antenna 4
	66	Antenna 3
	71	Antenna 1
	38	Antenna 3
	41	Antenna 3
42	Antenna 4	
48	Antenna 4	

### 3.2 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X-plane. Following channel(s) was (were) selected for the final test as listed below:

#### LTE Band 48

Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Maximum Output Power	55265 to 56715	55265 (3552.5MHz), 55990 (3625.0MHz), 56715 (3697.5MHz)	5MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
	55290 to 56690	55290 (3555.0MHz), 55990 (3625.0MHz), 56690 (3695.0MHz)	10MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
	55315 to 56665	55315 (3557.5MHz), 55990 (3625.0MHz), 56665 (3692.5MHz)	15MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
	55340 to 56640	55340 (3560.0MHz), 55990 (3625.0MHz), 56640 (3690.0MHz)	20MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 50 RB Offset 1 RB / 99 RB Offset 50 RB / 0 RB Offset 50 RB / 25 RB Offset 50 RB / 50 RB Offset 100 RB / 0 RB Offset
Modulation Characteristics	55340 to 56640	55990 (3625.0MHz)	20MHz	QPSK / 16QAM / 64QAM	100 RB / 0 RB Offset
Frequency Stability	55265 to 56715	55265 (3552.5MHz), 56715 (3697.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
	55290 to 56690	55290 (3555.0MHz), 56690 (3695.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
	55315 to 56665	55315 (3557.5MHz), 56665 (3692.5MHz)	15MHz	QPSK	75 RB / 0 RB Offset
	55340 to 56640	55340 (3560.0MHz), 56640 (3690.0MHz)	20MHz	QPSK	100 RB / 0 RB Offset
Occupied Bandwidth	55265 to 56715	55265 (3552.5MHz), 55990 (3625.0MHz), 56715 (3697.5MHz)	5MHz	QPSK / 16QAM / 64QAM	25 RB / 0 RB Offset
	55290 to 56690	55290 (3555.0MHz), 55990 (3625.0MHz), 56690 (3695.0MHz)	10MHz	QPSK / 16QAM / 64QAM	50 RB / 0 RB Offset
	55315 to 56665	55315 (3557.5MHz), 55990 (3625.0MHz), 56665 (3692.5MHz)	15MHz	QPSK / 16QAM / 64QAM	75 RB / 0 RB Offset
	55340 to 56640	55340 (3560.0MHz), 55990 (3625.0MHz), 56640 (3690.0MHz)	20MHz	QPSK / 16QAM / 64QAM	100 RB / 0 RB Offset

Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Peak to Average Ratio	55265 to 56715	55265 (3552.5MHz), 55990 (3625.0MHz), 56715 (3697.5MHz)	5MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset
	55290 to 56690	55290 (3555.0MHz), 55990 (3625.0MHz), 56690 (3695.0MHz)	10MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset
	55315 to 56665	55315 (3557.5MHz), 55990 (3625.0MHz), 56665 (3692.5MHz)	15MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset
	55340 to 56640	55340 (3560.0MHz), 55990 (3625.0MHz), 56640 (3690.0MHz)	20MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset
Conducted Emission	55265 to 56715	55265 (3552.5MHz), 55990 (3625.0MHz), 56715 (3697.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
	55290 to 56690	55290 (3555.0MHz), 55990 (3625.0MHz), 56690 (3695.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
	55315 to 56665	55315 (3557.5MHz), 55990 (3625.0MHz), 56665 (3692.5MHz)	15MHz	QPSK	1 RB / 0 RB Offset
	55340 to 56640	55340 (3560.0MHz), 55990 (3625.0MHz), 56640 (3690.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset
Radiated Emission Below 1GHz	55265 to 56715	55265 (3552.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
Radiated Emission Above 1GHz	55265 to 56715	55265 (3552.5MHz), 55990 (3625.0MHz), 56715 (3697.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
	55315 to 56665	55315 (3557.5MHz), 55990 (3625.0MHz), 56665 (3692.5MHz)	15MHz	QPSK	1 RB / 0 RB Offset
	55340 to 56640	55340 (3560.0MHz), 55990 (3625.0MHz), 56640 (3690.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset

**Note:**

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.
2. For radiated emission below 1GHz, low, mid and high channels were pre-tested in chamber. Low channel in 5MHz was found to be the worst case and therefore had been chosen for all final tests.
3. For radiated emission above 1GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5MHz & highest channel bandwidth for final test.

## LTE Band 42

Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Maximum Output Power	43115 to 43565	43115 (3552.5MHz), 43340 (3575.0MHz), 43565 (3597.5MHz)	5MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
	43140 to 43540	43140 (3555.0MHz), 43340 (3575.0MHz), 43540 (3595.0MHz)	10MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
	43165 to 43515	43165 (3557.5MHz), 43340 (3575.0MHz), 43515 (3592.5MHz)	15MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
	43190 to 43490	43190 (3560.0MHz), 43340 (3575.0MHz), 43490 (3590.0MHz)	20MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset 1 RB / 50 RB Offset 1 RB / 99 RB Offset 50 RB / 0 RB Offset 50 RB / 25 RB Offset 50 RB / 50 RB Offset 100 RB / 0 RB Offset
Frequency Stability	43115 to 43565	43115 (3552.5MHz), 43565 (3597.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
	43140 to 43540	43140 (3555.0MHz), 43540 (3595.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
	43165 to 43515	43165 (3557.5MHz), 43515 (3592.5MHz)	15MHz	QPSK	75 RB / 0 RB Offset
	43190 to 43490	43190 (3560.0MHz), 43490 (3590.0MHz)	20MHz	QPSK	100 RB / 0 RB Offset
Occupied Bandwidth	43115 to 43565	43115 (3552.5MHz), 43340 (3575.0MHz), 43565 (3597.5MHz)	5MHz	QPSK / 16QAM / 64QAM	25 RB / 0 RB Offset
	43140 to 43540	43140 (3555.0MHz), 43340 (3575.0MHz), 43540 (3595.0MHz)	10MHz	QPSK / 16QAM / 64QAM	50 RB / 0 RB Offset
	43165 to 43515	43165 (3557.5MHz), 43340 (3575.0MHz), 43515 (3592.5MHz)	15MHz	QPSK / 16QAM / 64QAM	75 RB / 0 RB Offset
	43190 to 43490	43190 (3560.0MHz), 43340 (3575.0MHz), 43490 (3590.0MHz)	20MHz	QPSK / 16QAM / 64QAM	100 RB / 0 RB Offset
Peak to Average Ratio	43115 to 43565	43115 (3552.5MHz), 43340 (3575.0MHz), 43565 (3597.5MHz)	5MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset
	43140 to 43540	43140 (3555.0MHz), 43340 (3575.0MHz), 43540 (3595.0MHz)	10MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset
	43165 to 43515	43165 (3557.5MHz), 43340 (3575.0MHz), 43515 (3592.5MHz)	15MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset
	43190 to 43490	43190 (3560.0MHz), 43340 (3575.0MHz), 43490 (3590.0MHz)	20MHz	QPSK / 16QAM / 64QAM	1 RB / 0 RB Offset

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

### Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
Maximum Output Power	25deg. C, 70%RH	5Vdc	Han Wu
Modulation characteristics	24deg. C, 64%RH	5Vdc	James Yang
Frequency Stability	24deg. C, 64%RH	5Vdc	James Yang
Occupied Bandwidth	24deg. C, 64%RH	5Vdc	James Yang
Peak to Average Ratio	24deg. C, 64%RH	5Vdc	James Yang
Conducuted Emission	24deg. C, 64%RH	5Vdc	James Yang
Radiated Emission	22deg. C, 68%RH 25deg. C, 70%RH	120Vac, 60Hz	Greg Lin Luis Lee

### 3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Wideband Radio Communication Tester	R&S	CMW500	151084	NA	-
B.	Adapter	LITEON	PA-1050-39	NA	NA	-
C.	Fixture	NA	NA	NA	NA	Provided by client.

Note:

- All power cords of the above support units are non-shielded (1.8m).
- Items A acted as communication partners to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB cable	1	1.5	Y	0	-

#### 3.3.1 Configuration of System under Test



### **3.4 General Description of Applied Standards and References**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**Test Standard:**

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 96**

**ANSI/TIA/EIA-603-D-2010**

All test items have been performed and recorded as per the above standards.

**References Test Guidance:**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

**KDB 662911 D01 Multiple Transmitter Output v02r01**

**KDB 940660 D01 Part 96 CBRS Eqpt v02**

All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results


### 4.1 Maximum Output Power Measurement

#### 4.1.1 Limits of Maximum Output Power Measurement

Device		Maximum Output Power (dBm/10 MHz)
<input checked="" type="checkbox"/>	End User Device	23
<input type="checkbox"/>	Category A CBSD	30
<input type="checkbox"/>	Category B CBSD	47

#### 4.1.2 Test Setup

Conducted Measurement Method





## 4.1.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Dec. 31, 2019	Dec. 30, 2020
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Sep. 23, 2019	Sep. 22, 2020
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Nov. 11, 2019	Nov. 10, 2020
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-1170	Nov. 24, 2019	Nov. 23, 2020
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 24, 2019	Nov. 23, 2020
Loop Antenna TESEQ	HLA 6121	45745	Jul. 01, 2019	Jun. 30, 2020
Radio Communication Analyzer Anritsu	MT8821C	6261806803	Jan. 18, 2020	Jan. 19, 2021
Preamplifier Agilent (Below 1GHz)	8447D	2944A10631	Jul. 11, 2019	Jul. 10, 2020
Preamplifier KEYSIGHT (Above 1GHz)	83017A	MY53270295	Jun. 11, 2019	Jun. 10, 2020
RF Coaxial Cable WORKEN With 5dB PAD	8D-FB	Cable-CH4-01	Aug. 20, 2019	Aug. 19, 2020
RF Coaxial Cable EMCI	EMC102-KM-KM-3000	150929	Aug. 20, 2019	Aug. 19, 2020
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	Aug. 20, 2019	Aug. 19, 2020
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MY 13380+295012/04	Jul. 11, 2019	Jul. 10, 2020
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH4-03 (250724)	Jul. 11, 2019	Jul. 10, 2020
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021703	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 03, 2019	Jun. 02, 2020
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
Digital Multimeter Fluke	87-III	70360742	Jun. 27, 2019	Jun. 26, 2020

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 4.

#### 4.1.4 Test Procedures

##### Conducted output power measurement

1. Connect the DUT transmitter output to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
2. Set span to at least 1.5 times the OBW.
3. Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
4. Set VBW  $\geq 3 \times$  RBW.
5. Set number of points in sweep  $\geq 2 \times$  span / RBW.
6. Sweep time = auto-couple.
7. Detector = RMS (power averaging).
8. If the EUT can be configured to transmit continuously (i.e., burst duty cycle  $\geq 98\%$ ), then set the trigger to free run.
9. If the EUT cannot be configured to transmit continuously (i.e., burst duty cycle  $< 98\%$ ), then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Ensure that the sweep time is less than or equal to the transmission burst duration.
10. Trace average at least 100 traces in power averaging (i.e., RMS) mode.
11. Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band or channel power measurement function, with the band/channel limits set equal to the OBW band edges. If the instrument does not have a band or channel power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
12. For per 10MHz method, channel power integrating bandwidth 10MHz is used for bandwidth 5M, 10M, 15M and 20M. 13. For full power method, channel power integrating bandwidth 10MHz is used for bandwidth 5M, 10M, integrating bandwidth 15MHz is used for bandwidth 15M, integrating bandwidth 20MHz is used for bandwidth 20M.

##### Maximum EIRP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}}$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively  
(expressed in the same units as  $P_{\text{Meas}}$ , e.g., dBm or dBW)

$P_{\text{Meas}}$  measured transmitter output power or PSD, in dBm or dBW

$G_{\text{T}}$  gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

#### 4.1.5 Deviation from Test Standard

No deviation.

#### 4.1.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

## 4.1.7 Test Results




## Conducted Output Power (dBm) / Per 10M

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55265	55990	56715	55265	55990	56715	55265	55990	56715
			3552.5	3625	3697.5	3552.5	3625	3697.5	3552.5	3625	3697.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 5M	1	0	21.18	21.21	21.19	20.44	20.50	20.58	19.26	19.38	19.39
	1	12	21.11	21.17	21.12	20.47	20.46	20.54	19.21	19.29	19.32
	1	24	21.24	21.25	21.23	20.50	20.54	20.56	19.27	19.28	19.37
	12	0	20.28	20.31	20.39	19.36	19.37	19.36	18.44	18.42	18.46
	12	6	20.31	20.34	20.32	19.34	19.38	19.39	18.38	18.40	18.49
	12	13	20.22	20.29	20.38	19.32	19.40	19.36	18.41	18.44	18.46
	25	0	20.31	20.38	20.35	19.39	19.38	19.44	18.38	18.42	18.44

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55290	55990	56690	55290	55990	56690	55290	55990	56690
			3555	3625	3695	3555	3625	3695	3555	3625	3695
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 10M	1	0	21.35	21.39	21.20	20.50	20.56	20.59	19.46	19.57	19.52
	1	12	21.25	21.31	21.12	20.49	20.47	20.51	19.35	19.25	19.34
	1	24	21.14	21.16	21.23	20.47	20.57	20.53	19.32	19.41	19.49
	12	0	20.34	20.36	20.38	19.34	19.41	19.39	18.43	18.46	18.54
	12	6	20.31	20.31	20.41	19.47	19.45	19.43	18.53	18.51	18.55
	12	13	20.27	20.26	20.40	19.38	19.36	19.32	18.36	18.41	18.51
	25	0	20.31	20.33	20.29	19.37	19.40	19.43	18.31	18.44	18.48

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55315	55990	56665	55315	55990	56665	55315	55990	56665
			3557.5	3625	3692.5	3557.5	3625	3692.5	3557.5	3625	3692.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 15M	1	0	21.86	21.23	21.15	20.93	20.47	20.40	19.86	19.22	19.63
	1	12	21.74	21.15	21.41	20.68	20.38	20.29	19.81	19.11	19.32
	1	24	21.66	21.03	21.05	20.54	20.31	20.23	19.96	19.25	19.26
	12	0	20.05	19.61	19.46	19.07	18.64	18.43	18.06	17.68	17.51
	12	6	19.99	19.57	19.44	19.01	18.58	18.46	18.11	17.65	17.48
	12	13	19.94	19.44	19.52	18.93	18.36	18.37	17.94	17.53	17.52
	25	0	18.52	18.11	18.02	17.56	17.20	17.06	16.58	16.14	16.09

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55340 3560 MHz	55990 3625 MHz	56640 3690 MHz	55340 3560 MHz	55990 3625 MHz	56640 3690 MHz	55340 3560 MHz	55990 3625 MHz	56640 3690 MHz
48 / 20M	1	0	21.80	21.19	21.50	20.71	20.22	20.06	19.94	19.54	19.33
	1	12	21.48	21.14	21.29	20.65	20.12	19.98	19.59	19.41	19.04
	1	24	21.45	20.81	20.97	20.54	20.20	19.97	19.71	19.45	19.29
	12	0	19.99	19.55	19.47	18.98	18.59	18.51	18.01	17.63	17.54
	12	6	19.86	19.48	19.50	18.91	18.51	18.50	17.96	17.58	17.59
	12	13	19.81	19.46	19.47	18.89	18.49	18.54	17.92	17.52	17.57
	25	0	17.34	16.98	16.96	16.35	15.96	16.01	15.39	15.07	14.99



**EIRP Power(dBm) / Per 10M**

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55265	55990	56715	55265	55990	56715	55265	55990	56715
			3552.5	3625	3697.5	3552.5	3625	3697.5	3552.5	3625	3697.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 5M	1	0	22.10	22.13	22.11	21.36	21.42	<b>21.50</b>	20.18	20.30	<b>20.31</b>
	1	12	22.03	22.09	22.04	21.39	21.38	21.46	20.13	20.21	20.24
	1	24	22.16	<b>22.17</b>	22.15	21.42	21.46	21.48	20.19	20.20	20.29
	12	0	21.20	21.23	21.31	20.28	20.29	20.28	19.36	19.34	19.38
	12	6	21.23	21.26	21.24	20.26	20.30	20.31	19.30	19.32	19.41
	12	13	21.14	21.21	21.30	20.24	20.32	20.28	19.33	19.36	19.38
	25	0	21.23	21.30	21.27	20.31	20.30	20.36	19.30	19.34	19.36

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55290	55990	56690	55290	55990	56690	55290	55990	56690
			3555	3625	3695	3555	3625	3695	3555	3625	3695
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 10M	1	0	22.27	<b>22.31</b>	22.12	21.42	21.48	<b>21.51</b>	20.38	<b>20.49</b>	20.44
	1	12	22.17	22.23	22.04	21.41	21.39	21.43	20.27	20.17	20.26
	1	24	22.06	22.08	22.15	21.39	21.49	21.45	20.24	20.33	20.41
	12	0	21.26	21.28	21.30	20.26	20.33	20.31	19.35	19.38	19.46
	12	6	21.23	21.23	21.33	20.39	20.37	20.35	19.45	19.43	19.47
	12	13	21.19	21.18	21.32	20.30	20.28	20.24	19.28	19.33	19.43
	25	0	21.23	21.25	21.21	20.29	20.32	20.35	19.23	19.36	19.40

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55315	55990	56665	55315	55990	56665	55315	55990	56665
			3557.5	3625	3692.5	3557.5	3625	3692.5	3557.5	3625	3692.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 15M	1	0	<b>22.78</b>	22.15	22.07	<b>21.85</b>	21.39	21.32	20.78	20.14	20.55
	1	12	22.66	22.07	22.33	21.60	21.30	21.21	20.73	20.03	20.24
	1	24	22.58	21.95	21.97	21.46	21.23	21.15	<b>20.88</b>	20.17	20.18
	12	0	20.97	20.53	20.38	19.99	19.56	19.35	18.98	18.60	18.43
	12	6	20.91	20.49	20.36	19.93	19.50	19.38	19.03	18.57	18.40
	12	13	20.86	20.36	20.44	19.85	19.28	19.29	18.86	18.45	18.44
	25	0	19.44	19.03	18.94	18.48	18.12	17.98	17.50	17.06	17.01

\*EIRP = Conducted + antenna gain(0.92dBi).

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55340	55990	56640	55340	55990	56640	55340	55990	56640
			3560 MHz	3625 MHz	3690 MHz	3560 MHz	3625 MHz	3690 MHz	3560 MHz	3625 MHz	3690 MHz
48 / 20M	1	0	22.72	22.11	22.42	21.63	21.14	20.98	20.86	20.46	20.25
	1	12	22.40	22.06	22.21	21.57	21.04	20.90	20.51	20.33	19.96
	1	24	22.37	21.73	21.89	21.46	21.12	20.89	20.63	20.37	20.21
	12	0	20.91	20.47	20.39	19.90	19.51	19.43	18.93	18.55	18.46
	12	6	20.78	20.40	20.42	19.83	19.43	19.42	18.88	18.50	18.51
	12	13	20.73	20.38	20.39	19.81	19.41	19.46	18.84	18.44	18.49
	25	0	18.26	17.90	17.88	17.27	16.88	16.93	16.31	15.99	15.91

\*EIRP = Conducted + antenna gain(0.92dBi).




**Conducted Output Power (dBm) / Full Power**

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55265	55990	56715	55265	55990	56715	55265	55990	56715
			3552.5	3625	3697.5	3552.5	3625	3697.5	3552.5	3625	3697.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 5M	1	0	21.18	21.21	21.19	20.44	20.50	<b>20.58</b>	19.26	19.38	<b>19.39</b>
	1	12	21.11	21.17	21.12	20.47	20.46	20.54	19.21	19.29	19.32
	1	24	21.24	<b>21.25</b>	21.23	20.50	20.54	20.56	19.27	19.28	19.37
	12	0	20.28	20.31	20.39	19.36	19.37	19.36	18.44	18.42	18.46
	12	6	20.31	20.34	20.32	19.34	19.38	19.39	18.38	18.40	18.49
	12	13	20.22	20.29	20.38	19.32	19.40	19.36	18.41	18.44	18.46
	25	0	20.31	20.38	20.35	19.39	19.38	19.44	18.38	18.42	18.44

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55290	55990	56690	55290	55990	56690	55290	55990	56690
			3555	3625	3695	3555	3625	3695	3555	3625	3695
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 10M	1	0	21.35	<b>21.39</b>	21.20	20.50	20.56	<b>20.59</b>	19.46	<b>19.57</b>	19.52
	1	12	21.25	21.31	21.12	20.49	20.47	20.51	19.35	19.25	19.34
	1	24	21.14	21.16	21.23	20.47	20.57	20.53	19.32	19.41	19.49
	12	0	20.34	20.36	20.38	19.34	19.41	19.39	18.43	18.46	18.54
	12	6	20.31	20.31	20.41	19.47	19.45	19.43	18.53	18.51	18.55
	12	13	20.27	20.26	20.40	19.38	19.36	19.32	18.36	18.41	18.51
	25	0	20.31	20.33	20.29	19.37	19.40	19.43	18.31	18.44	18.48

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55315	55990	56665	55315	55990	56665	55315	55990	56665
			3557.5	3625	3692.5	3557.5	3625	3692.5	3557.5	3625	3692.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 15M	1	0	21.88	<b>21.89</b>	21.86	21.13	21.26	<b>21.27</b>	19.97	20.00	20.02
	1	12	21.78	21.86	21.83	21.10	21.23	21.19	19.83	19.93	19.94
	1	24	21.73	21.83	21.88	21.12	21.21	21.22	19.89	20.01	<b>20.14</b>
	12	0	20.98	21.09	21.06	20.01	20.09	20.10	19.01	19.15	19.17
	12	6	20.97	21.02	21.11	19.99	20.06	20.05	18.96	19.06	19.14
	12	13	20.94	20.96	21.05	19.93	20.00	20.08	18.97	18.98	19.16
	25	0	20.88	21.03	21.06	19.98	20.02	20.15	18.96	19.04	19.12

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55340	55990	56640	55340	55990	56640	55340	55990	56640
			3560	3625	3690	3560	3625	3690	3560	3625	3690
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 20M	1	0	21.85	21.98	21.91	21.27	21.37	21.32	19.96	20.13	20.06
	1	12	21.77	21.95	21.86	21.11	21.26	21.18	19.87	19.98	19.92
	1	24	21.80	22.00	21.82	21.14	21.32	21.21	19.84	20.07	20.04
	12	0	20.99	21.09	21.06	20.09	20.24	20.12	19.08	19.17	19.21
	12	6	20.90	21.02	21.07	20.02	20.14	20.15	18.97	19.13	19.18
	12	13	20.86	21.08	21.09	19.99	20.12	20.08	19.02	19.16	19.19
	25	0	20.93	20.97	21.06	19.97	20.13	20.13	18.97	19.15	19.11





**EIRP Power (dBm) / Full Power**

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55265	55990	56715	55265	55990	56715	55265	55990	56715
			3552.5	3625	3697.5	3552.5	3625	3697.5	3552.5	3625	3697.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 5M	1	0	22.10	22.13	22.11	21.36	21.42	<b>21.50</b>	20.18	20.30	<b>20.31</b>
	1	12	22.03	22.09	22.04	21.39	21.38	21.46	20.13	20.21	20.24
	1	24	22.16	<b>22.17</b>	22.15	21.42	21.46	21.48	20.19	20.20	20.29
	12	0	21.20	21.23	21.31	20.28	20.29	20.28	19.36	19.34	19.38
	12	6	21.23	21.26	21.24	20.26	20.30	20.31	19.30	19.32	19.41
	12	13	21.14	21.21	21.30	20.24	20.32	20.28	19.33	19.36	19.38
	25	0	21.23	21.30	21.27	20.31	20.30	20.36	19.30	19.34	19.36

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55290	55990	56690	55290	55990	56690	55290	55990	56690
			3555	3625	3695	3555	3625	3695	3555	3625	3695
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 10M	1	0	22.27	<b>22.31</b>	22.12	21.42	21.48	<b>21.51</b>	20.38	<b>20.49</b>	20.44
	1	12	22.17	22.23	22.04	21.41	21.39	21.43	20.27	20.17	20.26
	1	24	22.06	22.08	22.15	21.39	21.49	21.45	20.24	20.33	20.41
	12	0	21.26	21.28	21.30	20.26	20.33	20.31	19.35	19.38	19.46
	12	6	21.23	21.23	21.33	20.39	20.37	20.35	19.45	19.43	19.47
	12	13	21.19	21.18	21.32	20.30	20.28	20.24	19.28	19.33	19.43
	25	0	21.23	21.25	21.21	20.29	20.32	20.35	19.23	19.36	19.40

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55315	55990	56665	55315	55990	56665	55315	55990	56665
			3557.5	3625	3692.5	3557.5	3625	3692.5	3557.5	3625	3692.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 15M	1	0	22.80	<b>22.81</b>	22.78	22.05	22.18	<b>22.19</b>	20.89	20.92	20.94
	1	12	22.70	22.78	22.75	22.02	22.15	22.11	20.75	20.85	20.86
	1	24	22.65	22.75	22.80	22.04	22.13	22.14	20.81	20.93	<b>21.06</b>
	12	0	21.90	22.01	21.98	20.93	21.01	21.02	19.93	20.07	20.09
	12	6	21.89	21.94	22.03	20.91	20.98	20.97	19.88	19.98	20.06
	12	13	21.86	21.88	21.97	20.85	20.92	21.00	19.89	19.90	20.08
	25	0	21.80	21.95	21.98	20.90	20.94	21.07	19.88	19.96	20.04

\*EIRP = Conducted + antenna gain(0.92dBi).

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			55340	55990	56640	55340	55990	56640	55340	55990	56640
			3560	3625	3690	3560	3625	3690	3560	3625	3690
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
48 / 20M	1	0	22.77	22.90	22.83	22.19	22.29	22.24	20.88	21.05	20.98
	1	12	22.69	22.87	22.78	22.03	22.18	22.10	20.79	20.90	20.84
	1	24	22.72	22.92	22.74	22.06	22.24	22.13	20.76	20.99	20.96
	12	0	21.91	22.01	21.98	21.01	21.16	21.04	20.00	20.09	20.13
	12	6	21.82	21.94	21.99	20.94	21.06	21.07	19.89	20.05	20.10
	12	13	21.78	22.00	22.01	20.91	21.04	21.00	19.94	20.08	20.11
	25	0	21.85	21.89	21.98	20.89	21.05	21.05	19.89	20.07	20.03

\*EIRP = Conducted + antenna gain(0.92dBi).


**Conducted Output Power (dBm) / Per 10M**

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43115	43340	43565	43115	43340	43565	43115	43340	43565
			3552.5	3575	3597.5	3552.5	3575	3597.5	3552.5	3575	3597.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 5M	1	0	21.11	21.06	21.08	20.32	20.29	20.36	19.18	19.26	19.33
	1	12	21.09	21.14	21.05	20.39	20.42	20.31	19.02	19.13	19.25
	1	24	21.04	21.10	21.01	20.26	20.22	20.24	19.11	19.15	19.21
	12	0	20.22	20.26	20.31	19.22	19.18	19.23	18.32	18.28	18.35
	12	6	20.26	20.19	20.25	19.28	19.22	19.31	18.26	18.33	18.26
	12	13	20.15	20.13	20.26	19.18	19.22	19.28	18.29	18.17	18.24
	25	0	20.25	20.32	20.29	19.31	19.32	19.29	18.22	18.31	18.27

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43140	43340	43540	43140	43340	43540	43140	43340	43540
			3555	3575	3595	3555	3575	3595	3555	3575	3595
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 10M	1	0	21.28	21.32	21.11	20.44	20.42	20.48	19.39	19.33	19.29
	1	12	21.18	21.34	21.05	20.45	20.51	20.42	19.42	19.48	19.35
	1	24	21.10	21.18	21.16	20.32	20.48	20.40	19.31	19.26	19.31
	12	0	20.26	20.33	20.29	19.24	19.33	19.28	18.32	18.28	18.46
	12	6	20.22	20.25	20.17	19.33	19.41	19.36	18.42	18.37	18.49
	12	13	20.11	20.18	20.37	19.28	19.26	19.31	18.25	18.32	18.34
	25	0	20.15	20.27	20.13	19.25	19.18	19.22	18.26	18.31	18.22

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43165	43340	43515	43165	43340	43515	43165	43340	43515
			3557.5	3575	3592.5	3557.5	3575	3592.5	3557.5	3575	3592.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 15M	1	0	21.64	21.01	20.93	20.68	20.20	20.18	19.53	19.01	19.41
	1	12	21.46	20.90	21.05	20.33	20.06	19.94	19.61	18.87	19.09
	1	24	21.27	20.81	20.78	20.31	20.06	19.97	19.67	18.95	18.97
	12	0	19.81	19.25	19.13	18.82	18.35	18.03	17.77	17.28	17.25
	12	6	19.59	19.25	19.20	18.71	18.35	18.26	17.84	17.33	17.28
	12	13	19.70	19.21	19.17	18.70	18.13	18.07	17.61	17.16	17.28
	25	0	18.18	17.75	17.71	17.25	16.88	16.86	16.37	15.85	15.76

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43190	43340	43490	43190	43340	43490	43190	43340	43490
			3560	3575	3590	3560	3575	3590	3560	3575	3590
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 20M	1	0	21.56	20.89	21.29	20.51	19.96	19.77	19.56	19.29	18.99
	1	12	21.16	20.80	20.96	20.27	19.88	19.63	19.22	19.02	18.83
	1	24	21.25	20.45	20.64	20.15	19.84	19.64	19.31	19.25	19.06
	12	0	19.66	19.22	19.17	18.72	18.35	18.28	17.62	17.29	17.18
	12	6	19.62	19.11	19.11	18.55	18.27	18.17	17.75	17.25	17.30
	12	13	19.48	19.12	19.18	18.56	18.18	18.22	17.71	17.20	17.35
	25	0	16.95	16.73	16.68	16.02	15.61	15.72	15.13	14.69	14.72



**EIRP Power(dBm) / Per 10M**

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43115	43340	43565	43115	43340	43565	43115	43340	43565
			3552.5	3575	3597.5	3552.5	3575	3597.5	3552.5	3575	3597.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 5M	1	0	22.03	21.98	22.00	21.24	21.21	21.28	20.10	20.18	20.25
	1	12	22.01	22.06	21.97	21.31	21.34	21.23	19.94	20.05	20.17
	1	24	21.96	22.02	21.93	21.18	21.14	21.16	20.03	20.07	20.13
	12	0	21.14	21.18	21.23	20.14	20.10	20.15	19.24	19.20	19.27
	12	6	21.18	21.11	21.17	20.20	20.14	20.23	19.18	19.25	19.18
	12	13	21.07	21.05	21.18	20.10	20.14	20.20	19.21	19.09	19.16
	25	0	21.17	21.24	21.21	20.23	20.24	20.21	19.14	19.23	19.19

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43140	43340	43540	43140	43340	43540	43140	43340	43540
			3555	3575	3595	3555	3575	3595	3555	3575	3595
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 10M	1	0	22.20	22.24	22.03	21.36	21.34	21.40	20.31	20.25	20.21
	1	12	22.10	22.26	21.97	21.37	21.43	21.34	20.34	20.40	20.27
	1	24	22.02	22.10	22.08	21.24	21.40	21.32	20.23	20.18	20.23
	12	0	21.18	21.25	21.21	20.16	20.25	20.20	19.24	19.20	19.38
	12	6	21.14	21.17	21.09	20.25	20.33	20.28	19.34	19.29	19.41
	12	13	21.03	21.10	21.29	20.20	20.18	20.23	19.17	19.24	19.26
	25	0	21.07	21.19	21.05	20.17	20.10	20.14	19.18	19.23	19.14

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43165	43340	43515	43165	43340	43515	43165	43340	43515
			3557.5	3575	3592.5	3557.5	3575	3592.5	3557.5	3575	3592.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 15M	1	0	22.56	21.93	21.85	21.60	21.12	21.10	20.45	19.93	20.33
	1	12	22.38	21.82	21.97	21.25	20.98	20.86	20.53	19.79	20.01
	1	24	22.19	21.73	21.70	21.23	20.98	20.89	20.59	19.87	19.89
	12	0	20.73	20.17	20.05	19.74	19.27	18.95	18.69	18.20	18.17
	12	6	20.51	20.17	20.12	19.63	19.27	19.18	18.76	18.25	18.20
	12	13	20.62	20.13	20.09	19.62	19.05	18.99	18.53	18.08	18.20
	25	0	19.10	18.67	18.63	18.17	17.80	17.78	17.29	16.77	16.68

\*EIRP = Conducted + antenna gain(0.92dBi).

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43190	43340	43490	43190	43340	43490	43190	43340	43490
			3560	3575	3590	3560	3575	3590	3560	3575	3590
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 20M	1	0	22.48	21.81	22.21	21.43	20.88	20.69	20.48	20.21	19.91
	1	12	22.08	21.72	21.88	21.19	20.80	20.55	20.14	19.94	19.75
	1	24	22.17	21.37	21.56	21.07	20.76	20.56	20.23	20.17	19.98
	12	0	20.58	20.14	20.09	19.64	19.27	19.20	18.54	18.21	18.10
	12	6	20.54	20.03	20.03	19.47	19.19	19.09	18.67	18.17	18.22
	12	13	20.40	20.04	20.10	19.48	19.10	19.14	18.63	18.12	18.27
	25	0	17.87	17.65	17.60	16.94	16.53	16.64	16.05	15.61	15.64

\*EIRP = Conducted + antenna gain(0.92dBi).




**Conducted Output Power (dBm) / Full Power**

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43115	43340	43565	43115	43340	43565	43115	43340	43565
			3552.5	3575	3597.5	3552.5	3575	3597.5	3552.5	3575	3597.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 5M	1	0	21.11	21.06	21.08	20.32	20.29	20.36	19.18	19.26	<b>19.33</b>
	1	12	21.09	<b>21.14</b>	21.05	20.39	<b>20.42</b>	20.31	19.02	19.13	19.25
	1	24	21.04	21.10	21.01	20.26	20.22	20.24	19.11	19.15	19.21
	12	0	20.22	20.26	20.31	19.22	19.18	19.23	18.32	18.28	18.35
	12	6	20.26	20.19	20.25	19.28	19.22	19.31	18.26	18.33	18.26
	12	13	20.15	20.13	20.26	19.18	19.22	19.28	18.29	18.17	18.24
	25	0	20.25	20.32	20.29	19.31	19.32	19.29	18.22	18.31	18.27

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43140	43340	43540	43140	43340	43540	43140	43340	43540
			3555	3575	3595	3555	3575	3595	3555	3575	3595
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 10M	1	0	21.28	21.32	21.11	20.44	20.42	20.48	19.39	19.33	19.29
	1	12	21.18	<b>21.34</b>	21.05	20.45	<b>20.51</b>	20.42	19.42	<b>19.48</b>	19.35
	1	24	21.10	21.18	21.16	20.32	20.48	20.40	19.31	19.26	19.31
	12	0	20.26	20.33	20.29	19.24	19.33	19.28	18.32	18.28	18.46
	12	6	20.22	20.25	20.17	19.33	19.41	19.36	18.42	18.37	18.49
	12	13	20.11	20.18	20.37	19.28	19.26	19.31	18.25	18.32	18.34
	25	0	20.15	20.27	20.13	19.25	19.18	19.22	18.26	18.31	18.22

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43165	43340	43515	43165	43340	43515	43165	43340	43515
			3557.5	3575	3592.5	3557.5	3575	3592.5	3557.5	3575	3592.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 15M	1	0	21.52	21.57	21.56	20.68	20.81	20.75	19.67	19.39	19.50
	1	12	21.68	21.69	21.66	20.92	20.80	20.89	19.67	19.69	<b>19.88</b>
	1	24	<b>21.72</b>	21.66	21.52	20.82	<b>21.00</b>	20.65	19.71	19.68	19.43
	12	0	20.93	20.88	20.82	20.31	20.06	20.17	19.02	18.96	18.99
	12	6	21.13	20.91	20.95	20.47	20.16	20.13	19.35	19.16	18.82
	12	13	21.09	20.89	20.91	20.26	20.01	20.16	19.05	18.72	18.84
	25	0	20.91	20.87	20.77	20.08	20.11	20.10	18.93	18.84	18.86

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43190	43340	43490	43190	43340	43490	43190	43340	43490
			3560	3575	3590	3560	3575	3590	3560	3575	3590
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 20M	1	0	21.63	21.76	21.59	20.98	20.88	20.70	19.64	19.65	19.78
	1	12	<b>21.87</b>	21.79	21.72	<b>21.31</b>	21.23	20.98	19.96	<b>19.99</b>	19.65
	1	24	21.67	21.80	21.57	20.92	21.18	20.95	19.79	19.65	19.61
	12	0	21.07	20.85	20.91	20.29	19.98	20.09	19.01	18.98	19.14
	12	6	21.11	20.95	20.93	20.26	20.34	20.07	19.00	19.04	19.10
	12	13	20.98	20.91	20.78	20.13	20.25	20.13	18.91	19.02	18.99
	25	0	20.92	20.88	20.81	20.13	20.10	20.04	19.14	18.90	19.00





**EIRP Power (dBm) / Full Power**

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43115	43340	43565	43115	43340	43565	43115	43340	43565
			3552.5	3575	3597.5	3552.5	3575	3597.5	3552.5	3575	3597.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 5M	1	0	22.03	21.98	22.00	21.24	21.21	21.28	20.10	20.18	<b>20.25</b>
	1	12	22.01	<b>22.06</b>	21.97	21.31	<b>21.34</b>	21.23	19.94	20.05	20.17
	1	24	21.96	22.02	21.93	21.18	21.14	21.16	20.03	20.07	20.13
	12	0	21.14	21.18	21.23	20.14	20.10	20.15	19.24	19.20	19.27
	12	6	21.18	21.11	21.17	20.20	20.14	20.23	19.18	19.25	19.18
	12	13	21.07	21.05	21.18	20.10	20.14	20.20	19.21	19.09	19.16
	25	0	21.17	21.24	21.21	20.23	20.24	20.21	19.14	19.23	19.19

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43140	43340	43540	43140	43340	43540	43140	43340	43540
			3555	3575	3595	3555	3575	3595	3555	3575	3595
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 10M	1	0	22.20	22.24	22.03	21.36	21.34	21.40	20.31	20.25	20.21
	1	12	22.10	<b>22.26</b>	21.97	21.37	<b>21.43</b>	21.34	20.34	<b>20.40</b>	20.27
	1	24	22.02	22.10	22.08	21.24	21.40	21.32	20.23	20.18	20.23
	12	0	21.18	21.25	21.21	20.16	20.25	20.20	19.24	19.20	19.38
	12	6	21.14	21.17	21.09	20.25	20.33	20.28	19.34	19.29	19.41
	12	13	21.03	21.10	21.29	20.20	20.18	20.23	19.17	19.24	19.26
	25	0	21.07	21.19	21.05	20.17	20.10	20.14	19.18	19.23	19.14

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43165	43340	43515	43165	43340	43515	43165	43340	43515
			3557.5	3575	3592.5	3557.5	3575	3592.5	3557.5	3575	3592.5
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 15M	1	0	22.44	22.49	22.48	21.60	21.73	21.67	20.59	20.31	20.42
	1	12	22.60	22.61	22.58	21.84	21.72	21.81	20.59	20.61	<b>20.80</b>
	1	24	<b>22.64</b>	22.58	22.44	21.74	<b>21.92</b>	21.57	20.63	20.60	20.35
	12	0	21.85	21.80	21.74	21.23	20.98	21.09	19.94	19.88	19.91
	12	6	22.05	21.83	21.87	21.39	21.08	21.05	20.27	20.08	19.74
	12	13	22.01	21.81	21.83	21.18	20.93	21.08	19.97	19.64	19.76
	25	0	21.83	21.79	21.69	21.00	21.03	21.02	19.85	19.76	19.78

\*EIRP = Conducted + antenna gain(0.92dBi).

Band / BW	RB Size	RB Offset	QPSK			16QAM			64QAM		
			Low CH	Mid CH	High CH	Low CH	Mid CH	High CH	Low CH	Mid CH	High CH
			43190	43340	43490	43190	43340	43490	43190	43340	43490
			3560	3575	3590	3560	3575	3590	3560	3575	3590
			MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz	MHz
42 / 20M	1	0	22.55	22.68	22.51	21.90	21.80	21.62	20.56	20.57	20.70
	1	12	<b>22.79</b>	22.71	22.64	<b>22.23</b>	22.15	21.90	20.88	<b>20.91</b>	20.57
	1	24	22.59	22.72	22.49	21.84	22.10	21.87	20.71	20.57	20.53
	12	0	21.99	21.77	21.83	21.21	20.90	21.01	19.93	19.90	20.06
	12	6	22.03	21.87	21.85	21.18	21.26	20.99	19.92	19.96	20.02
	12	13	21.90	21.83	21.70	21.05	21.17	21.05	19.83	19.94	19.91
	25	0	21.84	21.80	21.73	21.05	21.02	20.96	20.06	19.82	19.92

\*EIRP = Conducted + antenna gain(0.92dBi).

## 4.2 Modulation Characteristics Measurement

### 4.2.1 Limits of Modulation Characteristics

N/A


### 4.2.2 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector, The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

### 4.2.3 Test Setup



### 4.2.4 Test Results



### 4.3 Frequency Stability Measurement

#### 4.3.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency band.

#### 4.3.2 Test Procedure

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5$  °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

#### 4.3.3 Test Setup



#### 4.3.4 Test Results

##### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 48			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3552.500002	0.001	3697.500004	0.001
5	3552.500004	0.001	3697.500003	0.001
5.75	3552.500004	0.001	3697.500004	0.001

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

##### Frequency Error vs. Temperature

Temp. (°C)	LTE Band 48			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3552.500003	0.001	3697.500003	0.001
-20	3552.500004	0.001	3697.500001	0.000
-10	3552.500001	0.000	3697.500001	0.000
0	3552.500003	0.001	3697.500001	0.000
10	3552.500004	0.001	3697.500004	0.001
20	3552.499997	-0.001	3697.499998	-0.001
30	3552.499997	-0.001	3697.499998	-0.001
40	3552.499996	-0.001	3697.499999	0.000
50	3552.499998	0.000	3697.499998	0.000

**Frequency Error vs. Voltage**

Voltage (Volts)	LTE Band 48			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3555.000002	0.000	3695.000004	0.001
5	3555.000004	0.001	3695.000003	0.001
5.75	3555.000003	0.001	3695.000003	0.001

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

**Frequency Error vs. Temperature**

Temp. (°C)	LTE Band 48			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3555.000002	0.001	3695.000004	0.001
-20	3555.000002	0.000	3695.000004	0.001
-10	3555.000004	0.001	3695.000001	0.000
0	3555.000002	0.000	3695.000003	0.001
10	3555.000002	0.001	3695.000003	0.001
20	3554.999999	0.000	3694.999999	0.000
30	3554.999998	-0.001	3694.999997	-0.001
40	3554.999999	0.000	3694.999996	-0.001
50	3554.999999	0.000	3694.999998	-0.001

**Frequency Error vs. Voltage**

Voltage (Volts)	LTE Band 48			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3557.500001	0.000	3692.500004	0.001
5	3557.500003	0.001	3692.500001	0.000
5.75	3557.500002	0.001	3692.500001	0.000

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

**Frequency Error vs. Temperature**

Temp. (°C)	LTE Band 48			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3557.500003	0.001	3692.500002	0.001
-20	3557.500002	0.001	3692.500003	0.001
-10	3557.500004	0.001	3692.500002	0.000
0	3557.500003	0.001	3692.500003	0.001
10	3557.500003	0.001	3692.500001	0.000
20	3557.499996	-0.001	3692.499996	-0.001
30	3557.499997	-0.001	3692.499999	0.000
40	3557.499996	-0.001	3692.499999	0.000
50	3557.499997	-0.001	3692.499996	-0.001

**Frequency Error vs. Voltage**

Voltage (Volts)	LTE Band 48			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3560.000002	0.001	3690.000001	0.000
5	3560.000001	0.000	3690.000003	0.001
5.75	3560.000003	0.001	3690.000002	0.001

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

**Frequency Error vs. Temperature**

Temp. (°C)	LTE Band 48			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3560.000003	0.001	3690.000002	0.000
-20	3560.000004	0.001	3690.000004	0.001
-10	3560.000002	0.001	3690.000004	0.001
0	3560.000003	0.001	3690.000003	0.001
10	3560.000004	0.001	3690.000002	0.001
20	3559.999997	-0.001	3689.999996	-0.001
30	3559.999999	0.000	3689.999997	-0.001
40	3559.999998	-0.001	3689.999999	0.000
50	3559.999998	-0.001	3689.999998	0.000



## Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 42			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3552.500004	0.001	3597.500002	0.001
5	3552.500003	0.001	3597.500002	0.001
5.75	3552.500002	0.001	3597.500001	0.000

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

## Frequency Error vs. Temperature

Temp. (°C)	LTE Band 42			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3552.500002	0.000	3597.500003	0.001
-20	3552.500002	0.001	3597.500002	0.001
-10	3552.500002	0.001	3597.500004	0.001
0	3552.500003	0.001	3597.500002	0.001
10	3552.500003	0.001	3597.500002	0.001
20	3552.499999	0.000	3597.499997	-0.001
30	3552.499999	0.000	3597.499997	-0.001
40	3552.499997	-0.001	3597.499998	0.000
50	3552.499997	-0.001	3597.499999	0.000

**Frequency Error vs. Voltage**

Voltage (Volts)	LTE Band 42			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3555.000001	0.000	3595.000002	0.001
5	3555.000003	0.001	3595.000003	0.001
5.75	3555.000003	0.001	3595.000001	0.000

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

**Frequency Error vs. Temperature**

Temp. (°C)	LTE Band 42			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3555.000002	0.000	3595.000002	0.000
-20	3555.000004	0.001	3595.000001	0.000
-10	3555.000002	0.001	3595.000002	0.001
0	3555.000003	0.001	3595.000001	0.000
10	3555.000003	0.001	3595.000002	0.000
20	3554.999996	-0.001	3594.999996	-0.001
30	3554.999998	-0.001	3594.999998	-0.001
40	3554.999997	-0.001	3594.999997	-0.001
50	3554.999998	-0.001	3594.999998	-0.001

**Frequency Error vs. Voltage**

Voltage (Volts)	LTE Band 42			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3557.500001	0.000	3592.500003	0.001
5	3557.500003	0.001	3592.500002	0.001
5.75	3557.500002	0.000	3592.500002	0.001

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

**Frequency Error vs. Temperature**

Temp. (°C)	LTE Band 42			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3557.500001	0.000	3592.500002	0.001
-20	3557.500001	0.000	3592.500003	0.001
-10	3557.500004	0.001	3592.500004	0.001
0	3557.500002	0.001	3592.500002	0.000
10	3557.500002	0.001	3592.500001	0.000
20	3557.499998	-0.001	3592.499998	-0.001
30	3557.499999	0.000	3592.499996	-0.001
40	3557.499996	-0.001	3592.499998	-0.001
50	3557.499996	-0.001	3592.499999	0.000

### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 42			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
4.25	3560.000001	0.000	3590.000003	0.001
5	3560.000003	0.001	3590.000001	0.000
5.75	3560.000004	0.001	3590.000002	0.001

Note: The applicant defined the normal working voltage is from 4.25Vdc to 5.75Vdc.

### Frequency Error vs. Temperature


Temp. (°C)	LTE Band 42			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	3560.000001	0.000	3590.000002	0.000
-20	3560.000002	0.001	3590.000002	0.001
-10	3560.000003	0.001	3590.000004	0.001
0	3560.000004	0.001	3590.000001	0.000
10	3560.000003	0.001	3590.000002	0.001
20	3559.999998	-0.001	3589.999997	-0.001
30	3559.999997	-0.001	3589.999998	-0.001
40	3559.999996	-0.001	3589.999998	-0.001
50	3559.999998	-0.001	3589.999999	0.000

## 4.4 Emission Bandwidth Measurement

### 4.4.1 Emission Bandwidth Measurement

Reference only

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

### 4.4.4 Test Procedure

#### Occupied Bandwidth:

All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

#### 26dBc Bandwidth:

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW =51 kHz (5 MHz bandwidth), 100 kHz (10 MHz bandwidth), 150 kHz (15 MHz bandwidth), 200 kHz (20 MHz bandwidth). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.4.7 Test Result (-26dB Bandwidth)

##### LTE Band 48

LTE Band 48, Channel Bandwidth 5MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55265	3552.5	4.79	4.79	4.79
55990	3625.0	4.79	4.80	4.80
56715	3697.5	4.78	4.78	4.81
LTE Band 48, Channel Bandwidth 10MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55290	3555.0	9.47	9.49	9.51
55990	3625.0	9.48	9.49	9.48
56690	3695.0	9.48	9.49	9.51
LTE Band 48, Channel Bandwidth 15MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55315	3557.5	14.25	14.23	14.25
55990	3625.0	14.24	14.20	14.25
56665	3692.5	14.23	14.23	14.24
LTE Band 48, Channel Bandwidth 20MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55340	3560.0	19.04	19.02	19.01
55990	3625.0	19.00	18.98	19.00
56640	3690.0	19.01	19.02	19.03

### Spectrum Plot of Worst Value


5MHz / 64QAM



10MHz / 64QAM



15MHz / 64QAM



20MHz / QPSK



LTE Band 42, Channel Bandwidth 5MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43115	3552.5	4.79	4.79	4.79
43340	3575.0	4.73	4.72	4.72
43565	3597.5	4.75	4.72	4.73
LTE Band 42, Channel Bandwidth 10MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43140	3555.0	9.47	9.49	9.51
43340	3575.0	9.30	9.30	9.28
43540	3595.0	9.29	9.27	9.29
LTE Band 42, Channel Bandwidth 15MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43165	3557.5	14.25	14.23	14.25
43340	3575.0	13.89	13.91	13.92
43515	3592.5	13.90	13.92	13.91
LTE Band 42, Channel Bandwidth 20MHz				
Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43190	3560.0	19.04	19.02	19.01
43340	3575.0	18.51	18.48	18.50
43490	3590.0	18.51	18.48	18.52



### Spectrum Plot of Worst Value

5MHz / 64QAM




10MHz / 64QAM



15MHz / 64QAM



20MHz / QPSK




#### 4.4.8 Test Result (Occupied Bandwidth)


LTE Band 48, Channel Bandwidth 5MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55265	3552.5	4.48	4.49	4.49
55990	3625.0	4.49	4.48	4.49
56715	3697.5	4.49	4.48	4.49
LTE Band 48, Channel Bandwidth 10MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55290	3555.0	8.95	8.97	8.96
55990	3625.0	8.96	8.96	8.96
56690	3695.0	8.95	8.96	8.96
LTE Band 48, Channel Bandwidth 15MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55315	3557.5	13.46	13.44	13.44
55990	3625.0	13.46	13.44	13.44
56665	3692.5	13.46	13.44	13.44
LTE Band 48, Channel Bandwidth 20MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
55340	3560.0	17.92	17.92	17.93
55990	3625.0	17.92	17.93	17.93
56640	3690.0	17.93	17.91	17.94

### Spectrum Plot of Worst Value

5MHz / 64QAM



10MHz / 16QAM



15MHz / QPSK



20MHz / 64QAM



LTE Band 42, Channel Bandwidth 5MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43115	3552.5	4.48	4.49	4.49
43340	3575.0	4.46	4.45	4.46
43565	3597.5	4.47	4.46	4.46
LTE Band 42, Channel Bandwidth 10MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43140	3555.0	8.95	8.97	8.96
43340	3575.0	8.91	8.91	8.91
43540	3595.0	8.92	8.92	8.91
LTE Band 42, Channel Bandwidth 15MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43165	3557.5	13.47	13.44	13.44
43340	3575.0	13.37	13.37	13.37
43515	3592.5	13.39	13.36	13.33
LTE Band 42, Channel Bandwidth 20MHz				
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		QPSK	16QAM	64QAM
43190	3560.0	17.92	17.92	17.93
43340	3575.0	17.82	17.84	17.83
43490	3590.0	17.81	17.83	17.80

### Spectrum Plot of Worst Value


**5MHz / 64QAM**




**10MHz / 16QAM**



**15MHz / QPSK**



**20MHz / 64QAM**




## 4.5 Peak to Average Ratio Measurement

### 4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

### 4.5.2 Test Setup



### 4.5.3 Test Procedures

- Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
- Set the number of counts to a value that stabilizes the measured CCDF curve;
- Record the maximum PAPR level associated with a probability of 0.1%.

#### 4.5.4 Test Results

##### LTE Band 48


LTE Band 48, Channel Bandwidth 5MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
55265	3552.5	3.69	5.33	6.76
55990	3625.0	3.71	4.94	6.61
56715	3697.5	3.71	5.42	6.82
LTE Band 48, Channel Bandwidth 10MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
55290	3555.0	3.69	5.65	7.11
55990	3625.0	6.34	6.34	7.22
56690	3695.0	3.73	5.64	7.08
LTE Band 48, Channel Bandwidth 15MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
55315	3557.5	4.64	6.13	6.90
55990	3625.0	4.42	5.32	6.93
56665	3692.5	4.24	5.52	6.83
LTE Band 48, Channel Bandwidth 20MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
55340	3560.0	4.64	6.42	7.19
55990	3625.0	4.47	6.07	6.89
56640	3690.0	4.41	5.66	7.09

### Spectrum Plot of Worst Value


5MHz / 64QAM




10MHz / 64QAM



15MHz / 64QAM



20MHz / 64QAM






## LTE Band 42


LTE Band 42, Channel Bandwidth 5MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
43115	3552.5	3.69	5.33	6.76
43340	3575.0	3.75	6.71	7.26
43565	3597.5	3.92	6.47	7.13
LTE Band 42, Channel Bandwidth 10MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
43140	3555.0	3.69	5.65	7.11
43340	3575.0	3.78	6.47	7.19
43540	3595.0	3.77	6.44	7.08
LTE Band 42, Channel Bandwidth 15MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
43165	3557.5	4.64	6.13	6.90
43340	3575.0	3.77	6.23	7.22
43515	3592.5	3.94	6.31	7.07
LTE Band 42, Channel Bandwidth 20MHz				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM
43190	3560.0	4.64	6.42	7.19
43340	3575.0	4.72	6.29	7.08
43490	3590.0	4.93	6.08	7.04

### Spectrum Plot of Worst Value


5MHz / 64QAM




10MHz / 64QAM



15MHz / 64QAM



20MHz / 64QAM




## 4.6 Conducted Spurious Emissions

### 4.6.1 Limits of Conducted Spurious Emissions Measurement

Power of any emissions outside the Fundamental	Limit
Within 0-10MHz above the Assigned Channel	-13 dBm/MHz
Within 0-10MHz below the Assigned Channel	
Greater than 0-10MHz above the Assigned Channel	-25 dBm/MHz
Greater than 0-10MHz below the Assigned Channel	
Power of any emission below 3530MHz	-40 dBm/MHz
Power of any emission above 3720MHz	


### 4.6.2 Test Setup



### 4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 37 GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.
- Measuring frequency band edge, 20dB attenuation pad is connected with spectrum. 1% of the fundamental emission bandwidth is used for conducted emission measurement.
- For 5MHz channel BW mode, extend the 1% range from 1M to 2M above and below the channel edge and then reduce the limit further by  $10 \log(1000/51) = 13\text{dB}$  (i.e. total  $-13 + -13 = -26\text{dB}$ ) to compensate for the integration from 51k to 1M.


### 4.6.4 Test Results




LTE Band 48, Channel Bandwidth 5MHz

Channel 56715 (3697.5MHz)

1RB



1RB 24




Full RB



LTE Band 48, Channel Bandwidth 5MHz

Channel 55265 (3552.5MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz




LTE Band 48, Channel Bandwidth 5MHz

Channel 55990 (3625.0MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz



LTE Band 48, Channel Bandwidth 5MHz

Channel 56715 (3697.50MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz




Frequency Range : 18GHz~40GHz









LTE Band 48, Channel Bandwidth 10MHz

Channel 55290 (3555.0MHz)




Channel 55990 (3625.0MHz)




LTE Band 48, Channel Bandwidth 10MHz

Channel 56690 (3695.0MHz)

1RB



1RB 49



Full RB




LTE Band 48, Channel Bandwidth 10MHz

Channel 55290 (3555.0MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz




Frequency Range : 18GHz~40GHz




LTE Band 48, Channel Bandwidth 10MHz

Channel 55990 (3625.00MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz



LTE Band 48, Channel Bandwidth 10MHz

Channel 56690 (3695.0MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz



LTE Band 48, Channel Bandwidth 15MHz

Channel 55315 (3557.50MHz)

1RB



Channel 55990 (3625.0MHz)

1RB



1RB 74



1RB 74



Full RB



Full RB



LTE Band 48, Channel Bandwidth 15MHz

Channel 56665 (3692.5MHz)

1RB



1RB 74




Full RB




LTE Band 48, Channel Bandwidth 15MHz

Channel 55315 (3557.50MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz







LTE Band 48, Channel Bandwidth 15MHz

Channel 55990 (3625.0MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz




LTE Band 48, Channel Bandwidth 15MHz

Channel 56665 (3692.50MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz




Frequency Range : 18GHz~40GHz








LTE Band 48, Channel Bandwidth 20MHz

Channel 55340 (3560.0MHz)




Channel 55990 (3625.0MHz)




LTE Band 48, Channel Bandwidth 20MHz

Channel 56640 (3690.0MHz)

1RB



1RB 99




Full RB



LTE Band 48, Channel Bandwidth 20MHz

Channel 55340 (3560.0MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz




LTE Band 48, Channel Bandwidth 20MHz

Channel 55990 (3625.0MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz




Frequency Range : 18GHz~40GHz




LTE Band 48, Channel Bandwidth 20MHz

Channel 56640 (3690.0MHz)


Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~18GHz



Frequency Range : 18GHz~40GHz



## 4.7 Radiated Emission Measurement

### 4.7.1 Limits of Radiated Emission Measurement

The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed  $-40\text{dBm/MHz}$ .

### 4.7.2 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

### 4.7.3 Test Procedures

- a. Substitution method is used for EIRP measurement. In the semi-anechoic chamber, EUT placed on the 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c.  $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ .
- d. ERP power can be calculated form EIRP power by subtracting the gain of dipole,  $\text{ERP power} = \text{EIRP power} - 2.15\text{dBi}$ .

**Note:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.


### 4.7.4 Deviation from Test Standard

No deviation.




#### 4.7.5 Test Set Up

##### <Frequency Range below 1GHz>



##### <Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.7.6 Test Results

Test was done with 50ohm terminator on antenna port.

Below 1GHz Data :

LTE Band 48


Channel Bandwidth: 5 MHz / QPSK

Mode	TX channel 55265 (3552.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	30.97	-51.5	-29.0	-18.8	-47.8	-40.0	-7.8
2	89.17	-37.3	-45.0	-0.1	-45.1	-40.0	-5.1
3	148.34	-60.1	-61.9	-3.0	-64.9	-40.0	-24.9
4	257.95	-56.9	-60.5	-1.6	-62.1	-40.0	-22.1
5	613.94	-68.0	-69.7	3.7	-66.0	-40.0	-26.0
6	755.56	-65.4	-65.3	3.8	-61.5	-40.0	-21.5

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).




Mode	TX channel 55265 (3552.5MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	58.13	-37.3	-40.0	-4.2	-44.2	-40.0	-4.2
2	123.12	-40.7	-44.0	-3.1	-47.1	-40.0	-7.1
3	204.60	-58.2	-58.1	-2.0	-60.1	-40.0	-20.1
4	262.80	-60.6	-58.0	-1.6	-59.6	-40.0	-19.6
5	601.33	-68.2	-68.2	3.8	-64.4	-40.0	-24.4
6	741.01	-65.9	-62.8	3.7	-59.1	-40.0	-19.1

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).



### Above 1GHz

LTE Band 48, Channel Bandwidth 5MHz

Mode	TX channel 55265 (3552.5MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

#### Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7105.00	-64.8	-46.7	0.7	-46.0	-40.0	-6.0

#### Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7105.00	-63.0	-45.3	0.7	-44.6	-40.0	-4.6

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

Mode	TX channel 55990 (3625.0MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

#### Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7250.00	-65.0	-47.2	0.9	-46.3	-40.0	-6.3

#### Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7250.00	-63.4	-45.5	0.9	-44.6	-40.0	-4.6

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

Mode	TX channel 56715 (3697.5MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7395.00	-65.1	-46.5	0.9	-45.6	-40.0	-5.6
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7395.00	-63.6	-45.9	0.9	-45.0	-40.0	-5.0

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

## LTE Band 48, Channel Bandwidth 15MHz

Mode	TX channel 55315 (3557.5MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

## Antenna Polarity &amp; Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7115.00	-65.6	-47.6	0.7	-46.9	-40.0	-6.9

## Antenna Polarity &amp; Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7115.00	-63.9	-46.2	0.7	-45.5	-40.0	-5.5

## Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

Mode	TX channel 55990 (3625.0MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

## Antenna Polarity &amp; Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7250.00	-64.9	-47.1	0.9	-46.2	-40.0	-6.2

## Antenna Polarity &amp; Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7250.00	-63.4	-45.5	0.9	-44.6	-40.0	-4.6

## Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

Mode	TX channel 56665 (3692.5MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7385.00	-64.7	-46.1	0.9	-45.2	-40.0	-5.2
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7385.00	-63.1	-45.4	0.9	-44.5	-40.0	-4.5

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

LTE Band 48, Channel Bandwidth 20MHz

Mode	TX channel 55340 (3560.0MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7120.00	-65.3	-47.3	0.7	-46.6	-40.0	-6.6

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7120.00	-63.6	-45.9	0.7	-45.2	-40.0	-5.2

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

Mode	TX channel 55990 (3625.00MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7250.00	-64.7	-46.9	0.9	-46.0	-40.0	-6.0

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7250.00	-63.1	-45.2	0.9	-44.3	-40.0	-4.3

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).



Mode	TX channel 56640 (3690.00MHz)	Frequency Range	1GHz ~ 40GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7380.00	-64.5	-46.0	0.9	-45.1	-40.0	-5.1
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1	7380.00	-62.9	-45.2	0.9	-44.3	-40.0	-4.3

Remarks:

1. EIRP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) - Cable Loss (dB).

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---