

# MPE/RF EXPOSURE EVALUATION REPORT

FCC CFR 47 Part 1.1310

**HWPD93 FCC MPE Rev A** 

Company: HP Inc.

Model Name: 0960-4025,0960-4034 and 0960-4745



## MPE/RF EXPOSURE EVALUATION REPORT

Company: HP Inc

Model Name: 0960-4025, 0960-4034, 0960-4745

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: HWPD93 FCC MPE Rev A

This report supersedes: MARS11\_FCC\_MPE Rev B

Applicant: HP Inc.

1115 SE 164<sup>th</sup> Ave, Suite 210

Vancouver

Washington 98683

USA

Issue Date: 20th August 2020

#### This Test Report is Issued Under the Authority of:

#### MiCOM Labs, Inc.

575 Boulder Court Pleasanton California 94566 USA

Phone: +1 (925) 462-0304 Fax: +1 (925) 462-0306 www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



itle: HP Inc 0960-4025,0960-4034 and 0960-4745

To: FCC CFR 47 Part 1.1310
Serial #: HWPD93 FCC MPE Rev A

### 1. MAXIMUM PERMISSABLE EXPOSURE

**Calculations for Maximum Permissible Exposure Levels** 

Power Density = Pd (mW/cm<sup>2</sup>) = EIRP/( $4*\pi*d^2$ )

EIRP = P \* G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain =  $10 ^ (G (dBi)/10)$ 

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1mW/cm<sup>2</sup>.

These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Total Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm²)	Min Calculated safe distance for Limit (cm)
2400.0 - 2483.5 (BLE DTS GFSK)	2.5	1.78	7.55	5.69	0.002	1	0.90
2400.0-2483.5 (BLE FHSS)	2.5	1.78	7.25	5.31	0.002	1	0.90
2400.0 - 2483.5 (WiFi)	2.5	1.78	18.47	70.31	0.025	1	3.15
5150.0-5250.0 (WiFi)	3.8	2.40	16.59	45.60	0.022	1	2.95
5250.0-5350.0 (WiFi)	3.8	2.40	16.23	41.98	0.020	1	2.83
5470.0-5725.0 (WiFi)	3.8	2.40	17.70	58.88	0.029	1	3.35
5725.0 - 5850.0 (WiFi)	3.8	2.40	17.55	56.89	0.028	1	3.30

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

#### **Specification - Maximum Permissible Exposure Limits**

The Limit is defined in Table 1 of FCC §1.1310.

Issue Date: 20th August 2020 Page: 3 of 4





575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com