

**CETECOM Inc.**



**CETECOM Inc.**

411 Dixon Landing Road, Milpitas, CA-95035, USA  
Phone: +1 408 586 6200 Fax: +1 408 586 6299  
www.cetecomusa.com

---

Issued test report consists of 52 Pages

Page 1 (52)

---

**RECOGNIZED BY INDUSTRY CANADA**

**IC - 3925**

**Test report no.: 141FCC/2001/A  
FCC Part 15.247  
HP OmniBook 6100**

**Table of Contents**

**1 General information**

**1.1 Notes**

**1.2 Testing laboratory**

**1.3 Details of applicant**

**1.4 Application details**

**1.5 Test item**

**1.6 Test standards**

**2 Technical test**

**2.1 Summary of test results**

**2.2 Test report**

**1 General information**

**1.1 Notes**

**The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc. USA.**

**1.2 Testing laboratory****CETECOM Inc.**

411 Dixon Landing Road, Milpitas, CA-95035, USA

Phone: +1 408 586 6200 Fax: +1 408 586 6299

E-mail: lothar.schmidt@cetecomusa.com

Internet: www.cetecomusa.com

**1.3 Details of applicant****Name : Hewlett Packard Co.; Mobile Computing Division****Street : 1000 NE Circle Blvd.****City : Corvallis, OR 97330****Country : USA****Telephone : +1 541 715 2171****Telefax : +1 541 715 3607****Contact : Kathy Warnock****e-mail : Kathy\_warnock@hp.com****1.4 Application details**

Date of receipt of application : 2001-04-01

Date of receipt of test item : 2001-04-15

Date of test : 2001-04-18/19/20

**1.5 Test item**

Manufacturer : Hewlett Packard.

Address : See above

Name of EUT : HP OmniBook 6100 Series (with Mini PCI 802.11b wireless card)

Type Designation : HP OmniBook 6100 Series

Model : 802MIP(W)

**Additional informations:**

Frequency : 2.412 – 2.484 GHz

Type of modulation : DBPSK at 1Mb/s; DQPSK at 2Mb/s; CCK at 5.5.and 11Mb/s

Number of channels : 11 Channels in US

Antenna : Integral

Power supply : 5.0V

Type of equipment : Temperature range : 0°C - +35°C

Tests were carried out at the maximum number of channels available (13) in the test software. The US version will set to 11 channels only.

**1.6 Test standards** FCC Part 15 §15.247

The tests were done following the public notice DA 00-705 released March 30, 2000

**2 Technical test**

**2.1 Summary of test results**

**No deviations from the technical specification(s) were ascertained in the course of the tests performed.**

**Technical responsibility for area of testing :**

**2001-05-10**

**EMC&  
Radio**

**Lothar  
Schmidt**



---

**Date**

**Section**

**Name**

**Signature**

**2.2 Testreport**

**TEST REPORT**

**Testreport no. : 141FCC/2001/A  
HP OmniBook 6100**

**TEST REPORT REFERENCE**

**LIST OF MEASUREMENTS**

<b>Paragraph</b>	<b>PARAMETER TO BE MEASURED</b>	<b>PAGE</b>
	<b>Transmitter parameters</b>	
§ 15.247 (a)(2)	<b>Spectrum Bandwith of a DSSS System</b>	<b>7</b>
§ 15.247 (b)(1)	<b>Maximum peak output power</b>	<b>11</b>
§ 15.247 (c)(1)	<b>Emission limitations</b>	<b>16</b>
§ 15.247 (d)	<b>Power Spectral Density</b>	<b>33</b>
§ 15.247 (e)	<b>Processing Gain of DSSS System</b>	<b>37</b>
	<b>Receiver parameters</b>	
§ 15.209	<b>Spurious radiations - Radiated</b>	<b>39</b>
	<b>Test equipment listing</b>	<b>47</b>
	<b>Test Site</b>	<b>48</b>
	<b>Photographs of the equipment</b>	<b>50</b>

**ANNEX: Details about processing gain.**

**NOTE: Conducted Emissions as per § 15.107 are not applicable for the EUT since it is a built in a laptop computer. The Laptop was measured in accordance with FCC part 15 B including the Wireless LAN .**

**SPECTRUM BANDWITH OF DSSS-SYSTEM**

**SUBCLAUSE § 15.247 (a)(2)**

<b>TEST CONDITIONS</b>		<b>6 dB BANDWIDTH ( kHz )</b>		
		<b>2412</b>	<b>2442</b>	<b>2472</b>
<b>Frequency (MHz)</b>				
<b>T<sub>nom</sub>( 20 )°C</b>	<b>V<sub>nom</sub>(5.0)V</b>	<b>10220</b>	<b>95190</b>	<b>96192</b>
<b>Measurement uncertainty</b>		<b>±3dB</b>		


**LIMIT**

**SUBCLAUSE §15.247(a) (2)**

**The minimum 6dB bandwidth shall be at least 500 KHz**

SPECTRUM BANDWITH OF DSSS-SYSTEM  
2412 MHz

SUBCLAUSE § 15.247 (a)(2)



Date: 18.APR.01 7:46:34

LIMIT


SUBCLAUSE §15.247(a) (2)

The minimum 6dB bandwidth shall be at least 500 KHz , here 10.02 MHz

ANALYZER SETTINGS: RBW=100KHz , VBW=1MHz

**SPECTRUM BANDWITH OF DSSS-SYSTEM  
2442 MHz**

**SUBCLAUSE § 15.247 (a)(2)**



**LIMIT**


**SUBCLAUSE §15.247(a) (2)**

**The minimum 6dB bandwidth shall be at least 500 KHz , here 11.42 MHz**

**ANALYZER SETTINGS: RBW=100KHz , VBW=1MHz**

SPECTRUM BANDWITH OF DSSS-SYSTEM  
2472 MHz

SUBCLAUSE § 15.247 (a)(2)



LIMIT

SUBCLAUSE §15.247(a) (2)

The minimum 6dB bandwidth shall be at least 500 KHz , here 10.02 MHz

ANALYZER SETTINGS: RBW=100KHz , VBW=1MHz

**MAXIMUM PEAK OUTPUT POWER  
(CONDUCTED)**

**SUBCLAUSE § 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)					
		2412		2442		2472	
Frequency (MHz)		Pk	Av	Pk	Av	Pk	Av
<b>T<sub>nom</sub>( 23 )°C</b>	<b>V<sub>nom</sub>(5.0)V</b>	<b>13.94</b>	<b>8.29</b>	<b>14.50</b>	<b>8.29</b>	<b>13.05</b>	<b>7.28</b>
<b>T<sub>nom</sub>( 0 )°C</b>	<b>V<sub>nom</sub>(5.0)V</b>	<b>13.14</b>	<b>7.85</b>	<b>12.60</b>	<b>7.16</b>	<b>12.09</b>	<b>6.59</b>
<b>T<sub>nom</sub>( 35 )°C</b>	<b>V<sub>nom</sub>(5.0)V</b>	<b>12.43</b>	<b>6.46</b>	<b>11.09</b>	<b>5.93</b>	<b>10.33</b>	<b>5.12</b>
<b>Measurement uncertainty</b>		<b>±3dB</b>					

**LIMIT**

**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
<b>2400-2483.5 MHz / 5725 – 5850 MHz</b>	<b>1.0 Watt</b>

**MAXIMUM PEAK OUTPUT POWER (EIRP)  
(RADIATED)**

**SUBCLAUSE § 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)					
		2412		2442		2472	
T <sub>nom</sub> ( 23 )°C	V <sub>nom</sub> (5.0)V	Pk	11.75	Pk	10.45	Pk	10.46
		Av	5.85	Av	4.28	Av	3.18
Maximum deviation from output power under extreme test conditions (dBc)		not performed		not performed		not performed	
Measurement uncertainty		±3dB					


**LIMIT**

**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz / 5725 – 5850 MHz	1.0 Watt


ANALYZER SETTINGS: RBW=3MHz, VBW=3MHz

EIRP:2412MHz




Date: 18.APR.01 11:28:10

EIRP:2442MHz



Date: 18.APR.01 11:33:48

EIRP:2472MHz



Date: 18.APR.01 11:35:31


EMISSION LIMITATIONS (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

conducted

2412 MHz up to 25 GHz

	Ref Lvl	Marker 1 [T1]	RBW	100 kHz	RF Att	20 dB
	98.8 dBμV	45.36 dBμV	VBW	1 MHz		
		6.58186373 GHz	SWT	5.8 s	Unit	dBμV



Date: 18.APR.01 13:55:14

**LIMITS**

**SUBCLAUSE § 15.247 (c)**

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


ANALYZER SETTINGS: RBW=100KHz , VBW=1MHZ

EMISSION LIMITATIONS (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

conducted

2442 MHz up to 25 GHz



Date: 18.APR.01 13:58:02

**LIMITS**

**SUBCLAUSE § 15.247 (c)**

**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**


**ANALYZER SETTINGS: RBW=100KHz , VBW=1MHz**

EMISSION LIMITATIONS (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

conducted

2472 MHz up to 25 GHz



Date: 18.APR.01 13:59:56

**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: RBW=100KHz , VBW=1MHz**

EMISSION LIMITATIONS (Transmitter)

SUBCLAUSE § 15.247 (c) (2)

**conducted**  
**spurious in the restricted band 2483.5 – 2500 MHz**  
**(Higher Band Edge)**




Date: 24.APR.01 10:58:45

**ANALYZER SETTINGS: RBW=1MHz , VBW=10Hz**

Lower Band Edge

conducted



**ANALYZER SETTINGS: RBW=1MHz, VBW=10Hz**


**EMISSION LIMITATIONS (Transmitter)**

**SUBCLAUSE § 15.247 (c) (1)**

The spurious emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 18 and 26 GHz very short cable connections to the antenna was used to minimize the noise level. Channel 1: 2412 MHz; Channel 2: 2442 MHz; Channel 3: 2472 MHz

**All emission measurements were done in Peak mode to reduce measurement time. In case limits are exceeded the measurements will be repeated and documented in the test report either with Quasi Peak or average detector depending on the frequency range specified in FCC 15 and/or DA00-705. Bandwidth, sweptime etc. Were set according DA00-705 and recorded**

**Channel 1: 30MHz-1GHz**



**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz**

**f ≥ 1GHz : RBW/VBW: 1 MHz**

**EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)**

**Channel 1: 1GHz-8GHz**



**NOTE:** The peak above the limit is the carrier frequency. This is related to all the spurious emissions measurements.

**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS:** f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

**EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)**

**Channel 1: 8GHz -18GHz**



**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz**

**f ≥ 1GHz : RBW/VBW: 1 MHz**

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Channel 1: 18GHz -26GHz



**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz**

**f ≥ 1GHz : RBW/VBW: 1 MHz**

**EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)**

**Channel 2: 30MHz -1GHz**



**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz**

**f ≥ 1GHz : RBW/VBW: 1 MHz**

**EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)**

**Channel 2: 1GHz -8GHz**



**NOTE:** The peak above the limit is the carrier frequency. This is related to all the spurious emissions measurements.

**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS:** f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Channel 2: 8GHz -18GHz



LIMITS

SUBCLAUSE § 15.247 (c)


In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ANALYZER SETTINGS:  $f < 1 \text{ GHz}$  : RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$  : RBW/VBW: 1 MHz

**EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)**

**Channel 2: 18GHz -26GHz**



**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz**

**f ≥ 1GHz : RBW/VBW: 1 MHz**

**EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)**

**Channel 3: 30MHz -1GHz**



**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz**

**f ≥ 1GHz : RBW/VBW: 1 MHz**

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Channel 3: 1GHz -8GHz



NOTE: The peak above the limit is the carrier frequency. This is related to all the spurious emissions measurements.

**LIMITS**

**SUBCLAUSE § 15.247 (c)**


In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ANALYZER SETTINGS:  $f < 1 \text{ GHz}$  : RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$  : RBW/VBW: 1 MHz

**EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)**

**Channel 3: 8GHz -18GHz**



**LIMITS**

**SUBCLAUSE § 15.247 (c)**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz**

**f ≥ 1GHz : RBW/VBW: 1 MHz**

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Channel 3: 18GHz -26GHz



**LIMITS**

**SUBCLAUSE § 15.247 (c)**

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

**POWER SPECTRAL DENSITY**

**SUBCLAUSE § 15.247 (d)**

TEST CONDITIONS		RF POWER LEVEL IN 3 kHz BW		
		2412	2442	2472
Frequency (MHz)				
T <sub>nom</sub> ( 23 )°C	V <sub>nom</sub> (5.0)V	-9.8 dBm	-9.9dBm	-10.5 dBm
Maximum deviation from output power under extreme test conditions (dBc)		not performed	not performed	not performed
Measurement uncertainty		±3dB		

**LIMIT**


**SUBCLAUSE §15.247(d)**

**The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band**

**ANALYZER SETTINGS: RBW=3KHz , VBW=3KHz**

**POWER SPECTRAL DENSITY**  
**2412 MHz**

**SUBCLAUSE § 15.247 (d)**



**LIMIT**


**SUBCLAUSE §15.247(d)**

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band

POWER SPECTRAL DENSITY

SUBCLAUSE § 15.247 (d)

2442 MHz




LIMIT

SUBCLAUSE §15.247(d)

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band

**POWER SPECTRAL DENSITY**  
**2472 MHz**

**SUBCLAUSE § 15.247 (d)**



Date: 18.APR.01 7:28:29

**LIMIT**

**SUBCLAUSE §15.247(d)**

**The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band**

**PROCESSING GAIN OF DSSS SYSTEMS SUBCLAUSE §15.247 (e)**

(NOTE: The processing gain data is provided by Chip Set Manufacturer)

**Chip/symbol rate, the symbol/bit rate and the Chip/bit**

<b>Bit rate</b>	<b>Chip/symbol rate</b>	<b>Bit/symbol rate</b>	<b>Chip/bit rate</b>	<b>Gp (dB)</b>	<b>Spec (dB)</b>
1 Mbit/sec	11	1, DBPSK	11	13.2	10
2 Mbit/sec	11	2, DQPSK	5.5	12.6	10
5.5 Mbit/sec	8	4, CCK	2	13.4	10
11 Mbit/sec	8	8, CCK	1	12.9	10


Note: 1. Gp is Processing Gain;

2. Spec is Processing Gain specifications defined by FCC for DSSS systems

### Test Set-up - Processing Gain

**NOTES:**


1. If Spectrum Analyzer is not used, delete optional 2-Way Splitter, connect RF Wattmeter "B" directly to previous Splitter and change 16 dB Attenuator to 10 dB.



**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**Channel 1: 30MHz – 1GHz**



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3


(NOTE: All measurements were done in peak mode)

ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz f ≥ 1GHz : RBW/VBW: 1 MHz

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**Channel 1: 1GHz – 8GHz**



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)


ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**Channel 2: 30MHz – 1GHz**



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)


ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**Channel 2: 1GHz – 8GHz**



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)


ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**Channel 3: 30MHz – 1GHz**



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)


**ANALYZER SETTINGS:** f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**Channel 3: 1GHz – 8GHz**



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)

ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz


f ≥ 1GHz : RBW/VBW: 1 MHz

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**8GHz – 18GHz**

(NOTE: This plot is applicable for all three channels)



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)

ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz


f ≥ 1GHz : RBW/VBW: 1 MHz

**RECEIVER SPURIOUS RADIATION**

§ 15.209

**18GHz – 26GHz**

(NOTE: This plot is applicable for all three channels)



**Limits**

**SUBCLAUSE § 15.209**

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)

ANALYZER SETTINGS: f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz



## Brief Explanations on Processing Gain Data

1. The formula of Processing Gain is:  $G_p = (S/N)_o + M_j + L_{sys}$

Where  $G_p$ : Processing Gain;

$(S/N)_o$ : the ratio of signal energy vs noise power density. Based on the data provided by the chip set manufacturer, it is 16.4dB @11Mb/s, 13.4dB @5.5Mb/s, 13.3dB @2.0Mb/s, 10.3dB @1.0Mb/s;

$L_{sys}$ : test system loss. The measurement result to our test set-up is 2.0dB;

$M_j$ : Jamming Margin. It is the ratio of jammer vs WLAN channel signal;

2. The purpose of the measurement here is to figure out  $M_j$  at different frequencies. Processing Gain will be gotten through calculation based on the above formula at different frequencies;
3. During the tests (see the Block Diagram of Test Set-up), the input signal to RX is about -60dBm (not exactly at -60dBm) and  $M_j$  (dB) = Jammer level (dBm) - Channel signal level (dBm);
4. The criteria we define the transmission link failure is: PER = 8%;
5. FCC defines that when testing the Processing Gain for a specific channel, if the frequency is  $f_o$ , the jammer frequency has to scan from  $f_o - 8.5$  MHz to  $f_o + 8.5$  MHz with 50 KHz per step. In another word, 340 data will be taken just for a single channel measurement;
6. Having calculated out 340 Processing Gains for a specific channel, use the percentile average function of Microsoft Excel to figure out the final result.

Example: see the first row of 11Mb/s @ Channel 6

Frequency—Jammer frequency =  $f_o - 8.5 = 2437 - 8.5 = 2428.50$  MHz;

$(S/N)_o$ —16.4 dB @11 Mb/s (see Item 1);

$L_{sys}$ —2.0 dB (see Item 1);

PER— 8.0%, which is the failure criteria;

Jammer— -57.2dBm, which is the Jammer level @ PER=8.0%;

$M_j$ —Jamming Margin. 5.5 (dB) = -57.2 (dBm) - (-62.7) (dBm) (see Item 3). On here, also see the next page of spread sheet, which shows that XMIT level = -62.7 dBm);

$G_p$ —Processing Gain =  $(S/N)_o + M_j + L_{sys} = 16.4 + 5.5 + 2.0 = 23.9$  (dB).

After having calculated out 340  $G_p$ s, use the percentile function of Microsoft Excel, the final  $G_p$  of 11Mb/s @ Ch 6 is 12.9 dB. At the same time, incorporate those 340 data into f— $G_p$  chart, you'll get a whole picture of it.

### Chip/symbol rate, the symbol/bit rate and the Chip/bit

Bit rate	Chip/symbol rate	Bit/symbol rate	Chip/bit rate	Gp (dB)	Spec (dB)
1 Mbit/sec	11	1, DBPSK	11	13.2	10
2 Mbit/sec	11	2, DQPSK	5.5	12.6	10
5.5 Mbit/sec	8	4, CCK	2	13.4	10
11 Mbit/sec	8	8, CCK	1	12.9	10

Note: 1. Gp is Processing Gain;

2. Spec is Processing Gain specifications defined by FCC on DSSS systems.

**Processing Gain**

ISL37400M

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2428.50	23.9	16.4	5.5	2.0	-57.2	<=8.0
2428.55	23.9	16.4	5.5	2.0	-57.2	<=8.0
2428.60	23.9	16.4	5.5	2.0	-57.2	<=8.0
2428.65	23.8	16.4	5.4	2.0	-57.3	<=8.0
2428.70	23.8	16.4	5.4	2.0	-57.3	<=8.0
2428.75	24.0	16.4	5.6	2.0	-57.1	<=8.0
2428.80	24.1	16.4	5.7	2.0	-57.0	<=8.0
2428.85	24.1	16.4	5.7	2.0	-57.0	<=8.0
2428.90	24.2	16.4	5.8	2.0	-56.9	<=8.0
2428.95	24.1	16.4	5.7	2.0	-57.0	<=8.0
2429.00	24.4	16.4	6.0	2.0	-56.7	<=8.0
2429.05	24.3	16.4	5.9	2.0	-56.8	<=8.0
2429.10	24.3	16.4	5.9	2.0	-56.8	<=8.0
2429.15	24.3	16.4	5.9	2.0	-56.8	<=8.0
2429.20	24.4	16.4	6.0	2.0	-56.7	<=8.0
2429.25	23.7	16.4	5.3	2.0	-57.4	<=8.0
2429.30	23.3	16.4	4.9	2.0	-57.8	<=8.0
2429.35	23.2	16.4	4.8	2.0	-57.9	<=8.0
2429.40	22.2	16.4	3.8	2.0	-58.9	<=8.0
2429.45	21.3	16.4	2.9	2.0	-59.8	<=8.0
2429.50	21.2	16.4	2.8	2.0	-59.9	<=8.0
2429.55	21.1	16.4	2.7	2.0	-60.0	<=8.0
2429.60	21.1	16.4	2.7	2.0	-60.0	<=8.0
2429.65	21.0	16.4	2.6	2.0	-60.1	<=8.0
2429.70	21.0	16.4	2.6	2.0	-60.1	<=8.0
2429.75	20.8	16.4	2.4	2.0	-60.3	<=8.0
2429.80	20.7	16.4	2.3	2.0	-60.4	<=8.0
2429.85	21.1	16.4	2.7	2.0	-60.0	<=8.0
2429.90	21.0	16.4	2.6	2.0	-60.1	<=8.0
2429.95	21.1	16.4	2.7	2.0	-60.0	<=8.0
2430.00	20.9	16.4	2.5	2.0	-60.2	<=8.0
2430.05	20.9	16.4	2.5	2.0	-60.2	<=8.0
2430.10	20.5	16.4	2.1	2.0	-60.6	<=8.0
2430.15	19.5	16.4	1.1	2.0	-61.6	<=8.0
2430.20	19.5	16.4	1.1	2.0	-61.6	<=8.0
2430.25	19.0	16.4	0.6	2.0	-62.1	<=8.0
2430.30	19.0	16.4	0.6	2.0	-62.1	<=8.0
2430.35	18.7	16.4	0.3	2.0	-62.4	<=8.0
2430.40	18.7	16.4	0.3	2.0	-62.4	<=8.0
2430.45	18.5	16.4	0.1	2.0	-62.6	<=8.0
2430.50	18.4	16.4	0.0	2.0	-62.7	<=8.0
2430.55	18.4	16.4	0.0	2.0	-62.7	<=8.0
2430.60	18.4	16.4	0.0	2.0	-62.7	<=8.0
2430.65	18.1	16.4	-0.3	2.0	-63.0	<=8.0
2430.70	17.9	16.4	-0.5	2.0	-63.2	<=8.0
2430.75	17.4	16.4	-1.0	2.0	-63.7	<=8.0
2430.80	17.4	16.4	-1.0	2.0	-63.7	<=8.0
2430.85	17.1	16.4	-1.3	2.0	-64.0	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2430.90	17.1	16.4	-1.3	2.0	-64.0	<=8.0
2430.95	16.9	16.4	-1.5	2.0	-64.2	<=8.0
2431.00	16.8	16.4	-1.6	2.0	-64.3	<=8.0
2431.05	16.7	16.4	-1.7	2.0	-64.4	<=8.0
2431.10	16.7	16.4	-1.7	2.0	-64.4	<=8.0
2431.15	16.3	16.4	-2.1	2.0	-64.8	<=8.0
2431.20	16.5	16.4	-1.9	2.0	-64.6	<=8.0
2431.25	16.4	16.4	-2.0	2.0	-64.7	<=8.0
2431.30	16.3	16.4	-2.1	2.0	-64.8	<=8.0
2431.35	16.3	16.4	-2.1	2.0	-64.8	<=8.0
2431.40	15.8	16.4	-2.6	2.0	-65.3	<=8.0
2431.45	15.9	16.4	-2.5	2.0	-65.2	<=8.0
2431.50	15.7	16.4	-2.7	2.0	-65.4	<=8.0
2431.55	15.5	16.4	-2.9	2.0	-65.6	<=8.0
2431.60	15.4	16.4	-3.0	2.0	-65.7	<=8.0
2431.65	15.2	16.4	-3.2	2.0	-65.9	<=8.0
2431.70	15.1	16.4	-3.3	2.0	-66.0	<=8.0
2431.75	15.0	16.4	-3.4	2.0	-66.1	<=8.0
2431.80	15.0	16.4	-3.4	2.0	-66.1	<=8.0
2431.85	14.9	16.4	-3.5	2.0	-66.2	<=8.0
2431.90	15.0	16.4	-3.4	2.0	-66.1	<=8.0
2431.95	15.1	16.4	-3.3	2.0	-66.0	<=8.0
2432.00	15.1	16.4	-3.3	2.0	-66.0	<=8.0
2432.05	15.1	16.4	-3.3	2.0	-66.0	<=8.0
2432.10	15.0	16.4	-3.4	2.0	-66.1	<=8.0
2432.15	14.8	16.4	-3.6	2.0	-66.3	<=8.0
2432.20	14.9	16.4	-3.5	2.0	-66.2	<=8.0
2432.25	14.9	16.4	-3.5	2.0	-66.2	<=8.0
2432.30	14.8	16.4	-3.6	2.0	-66.3	<=8.0
2432.35	14.6	16.4	-3.8	2.0	-66.5	<=8.0
2432.40	14.3	16.4	-4.1	2.0	-66.8	<=8.0
2432.45	14.5	16.4	-3.9	2.0	-66.6	<=8.0
2432.50	14.6	16.4	-3.8	2.0	-66.5	<=8.0
2432.55	14.5	16.4	-3.9	2.0	-66.6	<=8.0
2432.60	14.3	16.4	-4.1	2.0	-66.8	<=8.0
2432.65	14.3	16.4	-4.1	2.0	-66.8	<=8.0
2432.70	14.2	16.4	-4.2	2.0	-66.9	<=8.0
2432.75	14.1	16.4	-4.3	2.0	-67.0	<=8.0
2432.80	14.1	16.4	-4.3	2.0	-67.0	<=8.0
2432.85	13.8	16.4	-4.6	2.0	-67.3	<=8.0
2432.90	13.5	16.4	-4.9	2.0	-67.6	<=8.0
2432.95	13.7	16.4	-4.7	2.0	-67.4	<=8.0
2433.00	13.6	16.4	-4.8	2.0	-67.5	<=8.0
2433.05	13.5	16.4	-4.9	2.0	-67.6	<=8.0
2433.10	13.5	16.4	-4.9	2.0	-67.6	<=8.0
2433.15	13.5	16.4	-4.9	2.0	-67.6	<=8.0
2433.20	13.6	16.4	-4.8	2.0	-67.5	<=8.0
2433.25	13.7	16.4	-4.7	2.0	-67.4	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2433.30	13.7	16.4	-4.7	2.0	-67.4	<=8.0
2433.35	13.6	16.4	-4.8	2.0	-67.5	<=8.0
2433.40	13.5	16.4	-4.9	2.0	-67.6	<=8.0
2433.45	13.4	16.4	-5.0	2.0	-67.7	<=8.0
2433.50	13.4	16.4	-5.0	2.0	-67.7	<=8.0
2433.55	13.4	16.4	-5.0	2.0	-67.7	<=8.0
2433.60	13.4	16.4	-5.0	2.0	-67.7	<=8.0
2433.65	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2433.70	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2433.75	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2433.80	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2433.85	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2433.90	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2433.95	13.4	16.4	-5.0	2.0	-67.7	<=8.0
2434.00	13.4	16.4	-5.0	2.0	-67.7	<=8.0
2434.05	13.4	16.4	-5.0	2.0	-67.7	<=8.0
2434.10	13.3	16.4	-5.1	2.0	-67.8	<=8.0
2434.15	13.2	16.4	-5.2	2.0	-67.9	<=8.0
2434.20	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2434.25	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2434.30	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2434.35	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2434.40	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2434.45	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2434.50	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2434.55	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2434.60	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2434.65	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2434.70	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2434.75	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2434.80	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2434.85	12.3	16.4	-6.1	2.0	-68.8	<=8.0
2434.90	12.1	16.4	-6.3	2.0	-69.0	<=8.0
2434.95	12.4	16.4	-6.0	2.0	-68.7	<=8.0
2435.00	12.4	16.4	-6.0	2.0	-68.7	<=8.0
2435.05	12.4	16.4	-6.0	2.0	-68.7	<=8.0
2435.10	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2435.15	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2435.20	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2435.25	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2435.30	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2435.35	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2435.40	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2435.45	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2435.50	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2435.55	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2435.60	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2435.65	12.8	16.4	-5.6	2.0	-68.3	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2435.70	12.4	16.4	-6.0	2.0	-68.7	<=8.0
2435.75	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2435.80	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2435.85	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2435.90	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2435.95	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2436.00	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2436.05	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.10	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.15	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.20	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2436.25	13.2	16.4	-5.2	2.0	-67.9	<=8.0
2436.30	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.35	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2436.40	12.4	16.4	-6.0	2.0	-68.7	<=8.0
2436.45	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2436.50	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.55	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2436.60	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2436.65	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2436.70	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.75	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.80	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2436.85	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2436.90	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2436.95	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2437.00	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2437.05	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2437.10	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2437.15	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2437.20	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2437.25	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2437.30	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2437.35	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2437.40	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2437.45	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2437.50	13.3	16.4	-5.1	2.0	-67.8	<=8.0
2437.55	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2437.60	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2437.65	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2437.70	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2437.75	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2437.80	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2437.85	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2437.90	12.2	16.4	-6.2	2.0	-68.9	<=8.0
2437.95	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2438.00	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2438.05	13.1	16.4	-5.3	2.0	-68.0	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2438.10	13.2	16.4	-5.2	2.0	-67.9	<=8.0
2438.15	13.3	16.4	-5.1	2.0	-67.8	<=8.0
2438.20	13.2	16.4	-5.2	2.0	-67.9	<=8.0
2438.25	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2438.30	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2438.35	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2438.40	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2438.45	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2438.50	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2438.55	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2438.60	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2438.65	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2438.70	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2438.75	13.1	16.4	-5.3	2.0	-68.0	<=8.0
2438.80	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2438.85	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2438.90	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2438.95	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2439.00	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2439.05	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2439.10	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2439.15	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2439.20	12.7	16.4	-5.7	2.0	-68.4	<=8.0
2439.25	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2439.30	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2439.35	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2439.40	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2439.45	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2439.50	13.0	16.4	-5.4	2.0	-68.1	<=8.0
2439.55	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2439.60	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2439.65	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2439.70	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2439.75	12.4	16.4	-6.0	2.0	-68.7	<=8.0
2439.80	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2439.85	12.3	16.4	-6.1	2.0	-68.8	<=8.0
2439.90	12.6	16.4	-5.8	2.0	-68.5	<=8.0
2439.95	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2440.00	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2440.05	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2440.10	13.2	16.4	-5.2	2.0	-67.9	<=8.0
2440.15	13.2	16.4	-5.2	2.0	-67.9	<=8.0
2440.20	13.3	16.4	-5.1	2.0	-67.8	<=8.0
2440.25	13.5	16.4	-4.9	2.0	-67.6	<=8.0
2440.30	13.6	16.4	-4.8	2.0	-67.5	<=8.0
2440.35	13.2	16.4	-5.2	2.0	-67.9	<=8.0
2440.40	12.8	16.4	-5.6	2.0	-68.3	<=8.0
2440.45	13.3	16.4	-5.1	2.0	-67.8	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2440.50	13.5	16.4	-4.9	2.0	-67.6	<=8.0
2440.55	13.3	16.4	-5.1	2.0	-67.8	<=8.0
2440.60	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2440.65	12.5	16.4	-5.9	2.0	-68.6	<=8.0
2440.70	13.7	16.4	-4.7	2.0	-67.4	<=8.0
2440.75	13.7	16.4	-4.7	2.0	-67.4	<=8.0
2440.80	13.8	16.4	-4.6	2.0	-67.3	<=8.0
2440.85	12.9	16.4	-5.5	2.0	-68.2	<=8.0
2440.90	13.8	16.4	-4.6	2.0	-67.3	<=8.0
2440.95	14.0	16.4	-4.4	2.0	-67.1	<=8.0
2441.00	14.1	16.4	-4.3	2.0	-67.0	<=8.0
2441.05	13.9	16.4	-4.5	2.0	-67.2	<=8.0
2441.10	13.9	16.4	-4.5	2.0	-67.2	<=8.0
2441.15	13.8	16.4	-4.6	2.0	-67.3	<=8.0
2441.20	14.1	16.4	-4.3	2.0	-67.0	<=8.0
2441.25	14.1	16.4	-4.3	2.0	-67.0	<=8.0
2441.30	14.0	16.4	-4.4	2.0	-67.1	<=8.0
2441.35	14.4	16.4	-4.0	2.0	-66.7	<=8.0
2441.40	14.4	16.4	-4.0	2.0	-66.7	<=8.0
2441.45	14.3	16.4	-4.1	2.0	-66.8	<=8.0
2441.50	14.5	16.4	-3.9	2.0	-66.6	<=8.0
2441.55	14.6	16.4	-3.8	2.0	-66.5	<=8.0
2441.60	14.7	16.4	-3.7	2.0	-66.4	<=8.0
2441.65	14.6	16.4	-3.8	2.0	-66.5	<=8.0
2441.70	14.6	16.4	-3.8	2.0	-66.5	<=8.0
2441.75	14.5	16.4	-3.9	2.0	-66.6	<=8.0
2441.80	14.4	16.4	-4.0	2.0	-66.7	<=8.0
2441.85	14.3	16.4	-4.1	2.0	-66.8	<=8.0
2441.90	14.3	16.4	-4.1	2.0	-66.8	<=8.0
2441.95	14.5	16.4	-3.9	2.0	-66.6	<=8.0
2442.00	14.7	16.4	-3.7	2.0	-66.4	<=8.0
2442.05	14.9	16.4	-3.5	2.0	-66.2	<=8.0
2442.10	15.0	16.4	-3.4	2.0	-66.1	<=8.0
2442.15	15.1	16.4	-3.3	2.0	-66.0	<=8.0
2442.20	15.2	16.4	-3.2	2.0	-65.9	<=8.0
2442.25	15.5	16.4	-2.9	2.0	-65.6	<=8.0
2442.30	15.7	16.4	-2.7	2.0	-65.4	<=8.0
2442.35	15.7	16.4	-2.7	2.0	-65.4	<=8.0
2442.40	15.5	16.4	-2.9	2.0	-65.6	<=8.0
2442.45	15.9	16.4	-2.5	2.0	-65.2	<=8.0
2442.50	15.9	16.4	-2.5	2.0	-65.2	<=8.0
2442.55	16.0	16.4	-2.4	2.0	-65.1	<=8.0
2442.60	16.1	16.4	-2.3	2.0	-65.0	<=8.0
2442.65	16.1	16.4	-2.3	2.0	-65.0	<=8.0
2442.70	16.1	16.4	-2.3	2.0	-65.0	<=8.0
2442.75	16.2	16.4	-2.2	2.0	-64.9	<=8.0
2442.80	16.3	16.4	-2.1	2.0	-64.8	<=8.0
2442.85	16.4	16.4	-2.0	2.0	-64.7	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2442.90	16.7	16.4	-1.7	2.0	-64.4	<=8.0
2442.95	16.9	16.4	-1.5	2.0	-64.2	<=8.0
2443.00	17.0	16.4	-1.4	2.0	-64.1	<=8.0
2443.05	17.1	16.4	-1.3	2.0	-64.0	<=8.0
2443.10	17.2	16.4	-1.2	2.0	-63.9	<=8.0
2443.15	17.2	16.4	-1.2	2.0	-63.9	<=8.0
2443.20	17.4	16.4	-1.0	2.0	-63.7	<=8.0
2443.25	17.6	16.4	-0.8	2.0	-63.5	<=8.0
2443.30	17.7	16.4	-0.7	2.0	-63.4	<=8.0
2443.35	17.7	16.4	-0.7	2.0	-63.4	<=8.0
2443.40	17.7	16.4	-0.7	2.0	-63.4	<=8.0
2443.45	18.0	16.4	-0.4	2.0	-63.1	<=8.0
2443.50	18.3	16.4	-0.1	2.0	-62.8	<=8.0
2443.55	18.6	16.4	0.2	2.0	-62.5	<=8.0
2443.60	18.6	16.4	0.2	2.0	-62.5	<=8.0
2443.65	18.9	16.4	0.5	2.0	-62.2	<=8.0
2443.70	19.0	16.4	0.6	2.0	-62.1	<=8.0
2443.75	19.1	16.4	0.7	2.0	-62.0	<=8.0
2443.80	19.2	16.4	0.8	2.0	-61.9	<=8.0
2443.85	19.2	16.4	0.8	2.0	-61.9	<=8.0
2443.90	19.4	16.4	1.0	2.0	-61.7	<=8.0
2443.95	19.7	16.4	1.3	2.0	-61.4	<=8.0
2444.00	19.8	16.4	1.4	2.0	-61.3	<=8.0
2444.05	20.1	16.4	1.7	2.0	-61.0	<=8.0
2444.10	20.5	16.4	2.1	2.0	-60.6	<=8.0
2444.15	20.8	16.4	2.4	2.0	-60.3	<=8.0
2444.20	21.1	16.4	2.7	2.0	-60.0	<=8.0
2444.25	21.6	16.4	3.2	2.0	-59.5	<=8.0
2444.30	21.7	16.4	3.3	2.0	-59.4	<=8.0
2444.35	21.8	16.4	3.4	2.0	-59.3	<=8.0
2444.40	21.9	16.4	3.5	2.0	-59.2	<=8.0
2444.45	21.9	16.4	3.5	2.0	-59.2	<=8.0
2444.50	22.0	16.4	3.6	2.0	-59.1	<=8.0
2444.55	23.3	16.4	4.9	2.0	-57.8	<=8.0
2444.60	23.4	16.4	5.0	2.0	-57.7	<=8.0
2444.65	23.6	16.4	5.2	2.0	-57.5	<=8.0
2444.70	24.0	16.4	5.6	2.0	-57.1	<=8.0
2444.75	24.0	16.4	5.6	2.0	-57.1	<=8.0
2444.80	23.9	16.4	5.5	2.0	-57.2	<=8.0
2444.85	23.9	16.4	5.5	2.0	-57.2	<=8.0
2444.90	23.8	16.4	5.4	2.0	-57.3	<=8.0
2444.95	25.0	16.4	6.6	2.0	-56.1	<=8.0
2445.00	25.2	16.4	6.8	2.0	-55.9	<=8.0
2445.05	25.3	16.4	6.9	2.0	-55.8	<=8.0
2445.10	25.4	16.4	7.0	2.0	-55.7	<=8.0
2445.15	25.6	16.4	7.2	2.0	-55.5	<=8.0
2445.20	25.8	16.4	7.4	2.0	-55.3	<=8.0
2445.25	25.9	16.4	7.5	2.0	-55.2	<=8.0

11Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2445.30	26.3	16.4	7.9	2.0	-54.8	<=8.0
2445.35	26.5	16.4	8.1	2.0	-54.6	<=8.0
2445.40	26.6	16.4	8.2	2.0	-54.5	<=8.0
2445.45	26.5	16.4	8.1	2.0	-54.6	<=8.0
2445.50	26.3	16.4	7.9	2.0	-54.8	<=8.0

**12.9**

Test Conditions

TX Card **HWB3163-04 Rev B**  
 S/N **99360038**  
 RX Card **ISL37400M Rev A**  
 S/N **00500038**  
 TX Firmware **P10002C0, MS11168A3**  
 RX Firmware **ID010000, PK010001, SF010000**  
 Software Ver. **3.0.24**  
 Mode **11 MB Pseudo IBSS**  
 Pkt Size **1024**  
 Pkt Dly **1**  
 Pkt Burst **6**

Intersil Chips on Card: **ISL3984**  
**ISL3685**  
**HFA3783**  
**ISL3183**  
**ISL3874**

Processing Gain (dB)	XMIT level	-62.7
	S/N+Ls	18.4
	0dB J/S	0.0
PG	offset	Signal Generator Delta
23.9	-8500	5.5
23.9	-8450	5.5
23.9	-8400	5.5
23.8	-8350	5.4
23.8	-8300	5.4
24.0	-8250	5.6
24.1	-8200	5.7
24.1	-8150	5.7
24.2	-8100	5.8
24.1	-8050	5.7
24.4	-8000	6.0
24.3	-7950	5.9
24.3	-7900	5.9
24.3	-7850	5.9
24.4	-7800	6.0
23.7	-7750	5.3
23.3	-7700	4.9
23.2	-7650	4.8
22.2	-7600	3.8
21.3	-7550	2.9
21.2	-7500	2.8
21.1	-7450	2.7
21.1	-7400	2.7
21.0	-7350	2.6
21.0	-7300	2.6
20.8	-7250	2.4
20.7	-7200	2.3
21.1	-7150	2.7
21.0	-7100	2.6
21.1	-7050	2.7
20.9	-7000	2.5
20.9	-6950	2.5
20.5	-6900	2.1
19.5	-6850	1.1
19.5	-6800	1.1
19.0	-6750	0.6
19.0	-6700	0.6
18.7	-6650	0.3
18.7	-6600	0.3
18.5	-6550	0.1
18.4	-6500	0.0
18.4	-6450	0.0
18.4	-6400	0.0
18.1	-6350	-0.3
17.9	-6300	-0.5
17.4	-6250	-1.0
17.4	-6200	-1.0

17.1	-6150	-1.3
17.1	-6100	-1.3
16.9	-6050	-1.5
16.8	-6000	-1.6
16.7	-5950	-1.7
16.7	-5900	-1.7
16.3	-5850	-2.1
16.5	-5800	-1.9
16.4	-5750	-2.0
16.3	-5700	-2.1
16.3	-5650	-2.1
15.8	-5600	-2.6
15.9	-5550	-2.5
15.7	-5500	-2.7
15.5	-5450	-2.9
15.4	-5400	-3.0
15.2	-5350	-3.2
15.1	-5300	-3.3
15.0	-5250	-3.4
15.0	-5200	-3.4
14.9	-5150	-3.5
15.0	-5100	-3.4
15.1	-5050	-3.3
15.1	-5000	-3.3
15.1	-4950	-3.3
15.0	-4900	-3.4
14.8	-4850	-3.6
14.9	-4800	-3.5
14.9	-4750	-3.5
14.8	-4700	-3.6
14.6	-4650	-3.8
14.3	-4600	-4.1
14.5	-4550	-3.9
14.6	-4500	-3.8
14.5	-4450	-3.9
14.3	-4400	-4.1
14.3	-4350	-4.1
14.2	-4300	-4.2
14.1	-4250	-4.3
14.1	-4200	-4.3
13.8	-4150	-4.6
13.5	-4100	-4.9
13.7	-4050	-4.7
13.6	-4000	-4.8
13.5	-3950	-4.9
13.5	-3900	-4.9
13.5	-3850	-4.9
13.6	-3800	-4.8
13.7	-3750	-4.7
13.7	-3700	-4.7
13.6	-3650	-4.8
13.5	-3600	-4.9

13.4	-3550	-5.0
13.4	-3500	-5.0
13.4	-3450	-5.0
13.4	-3400	-5.0
12.9	-3350	-5.5
12.9	-3300	-5.5
12.9	-3250	-5.5
13.1	-3200	-5.3
12.9	-3150	-5.5
12.7	-3100	-5.7
13.4	-3050	-5.0
13.4	-3000	-5.0
13.4	-2950	-5.0
13.3	-2900	-5.1
13.2	-2850	-5.2
13.0	-2800	-5.4
13.0	-2750	-5.4
13.0	-2700	-5.4
13.0	-2650	-5.4
12.6	-2600	-5.8
12.8	-2550	-5.6
12.9	-2500	-5.5
12.8	-2450	-5.6
12.8	-2400	-5.6
12.7	-2350	-5.7
12.7	-2300	-5.7
12.8	-2250	-5.6
12.8	-2200	-5.6
12.3	-2150	-6.1
12.1	-2100	-6.3
12.4	-2050	-6.0
12.4	-2000	-6.0
12.4	-1950	-6.0
12.6	-1900	-5.8
12.5	-1850	-5.9
12.7	-1800	-5.7
12.7	-1750	-5.7
12.9	-1700	-5.5
12.9	-1650	-5.5
12.9	-1600	-5.5
12.6	-1550	-5.8
12.9	-1500	-5.5
12.9	-1450	-5.5
12.9	-1400	-5.5
12.8	-1350	-5.6
12.4	-1300	-6.0
12.5	-1250	-5.9
12.5	-1200	-5.9
12.5	-1150	-5.9
12.6	-1100	-5.8
12.8	-1050	-5.6
12.9	-1000	-5.5


13.1	-950	-5.3
13.1	-900	-5.3
13.1	-850	-5.3
13.0	-800	-5.4
13.2	-750	-5.2
13.1	-700	-5.3
13.0	-650	-5.4
12.4	-600	-6.0
13.0	-550	-5.4
13.1	-500	-5.3
13.0	-450	-5.4
12.5	-400	-5.9
12.6	-350	-5.8
13.1	-300	-5.3
13.1	-250	-5.3
13.1	-200	-5.3
12.9	-150	-5.5
12.8	-100	-5.6
12.8	-50	-5.6
12.7	0	-5.7
12.9	50	-5.5
12.7	100	-5.7
12.8	150	-5.6
13.0	200	-5.4
13.0	250	-5.4
13.0	300	-5.4
13.1	350	-5.3
13.1	400	-5.3
13.0	450	-5.4
13.3	500	-5.1
13.0	550	-5.4
13.1	600	-5.3
12.6	650	-5.8
12.9	700	-5.5
12.6	750	-5.8
12.8	800	-5.6
12.6	850	-5.8
12.2	900	-6.2
12.8	950	-5.6
13.0	1000	-5.4
13.1	1050	-5.3
13.2	1100	-5.2
13.3	1150	-5.1
13.2	1200	-5.2
13.0	1250	-5.4
13.1	1300	-5.3
13.1	1350	-5.3
12.5	1400	-5.9
13.1	1450	-5.3
13.1	1500	-5.3
13.0	1550	-5.4
12.9	1600	-5.5

12.9	1650	-5.5
13.1	1700	-5.3
13.1	1750	-5.3
13.0	1800	-5.4
13.0	1850	-5.4
12.9	1900	-5.5
12.9	1950	-5.5
12.8	2000	-5.6
12.7	2050	-5.7
12.8	2100	-5.6
12.7	2150	-5.7
12.7	2200	-5.7
12.8	2250	-5.6
12.8	2300	-5.6
12.8	2350	-5.6
12.9	2400	-5.5
12.9	2450	-5.5
13.0	2500	-5.4
12.8	2550	-5.6
12.8	2600	-5.6
12.5	2650	-5.9
12.5	2700	-5.9
12.4	2750	-6.0
12.6	2800	-5.8
12.3	2850	-6.1
12.6	2900	-5.8
12.5	2950	-5.9
12.5	3000	-5.9
12.9	3050	-5.5
13.2	3100	-5.2
13.2	3150	-5.2
13.3	3200	-5.1
13.5	3250	-4.9
13.6	3300	-4.8
13.2	3350	-5.2
12.8	3400	-5.6
13.3	3450	-5.1
13.5	3500	-4.9
13.3	3550	-5.1
12.5	3600	-5.9
12.5	3650	-5.9
13.7	3700	-4.7
13.7	3750	-4.7
13.8	3800	-4.6
12.9	3850	-5.5
13.8	3900	-4.6
14.0	3950	-4.4
14.1	4000	-4.3
13.9	4050	-4.5
13.9	4100	-4.5
13.8	4150	-4.6
14.1	4200	-4.3

14.1	4250	-4.3
14.0	4300	-4.4
14.4	4350	-4.0
14.4	4400	-4.0
14.3	4450	-4.1
14.5	4500	-3.9
14.6	4550	-3.8
14.7	4600	-3.7
14.6	4650	-3.8
14.6	4700	-3.8
14.5	4750	-3.9
14.4	4800	-4.0
14.3	4850	-4.1
14.3	4900	-4.1
14.5	4950	-3.9
14.7	5000	-3.7
14.9	5050	-3.5
15.0	5100	-3.4
15.1	5150	-3.3
15.2	5200	-3.2
15.5	5250	-2.9
15.7	5300	-2.7
15.7	5350	-2.7
15.5	5400	-2.9
15.9	5450	-2.5
15.9	5500	-2.5
16.0	5550	-2.4
16.1	5600	-2.3
16.1	5650	-2.3
16.1	5700	-2.3
16.2	5750	-2.2
16.3	5800	-2.1
16.4	5850	-2.0
16.7	5900	-1.7
16.9	5950	-1.5
17.0	6000	-1.4
17.1	6050	-1.3
17.2	6100	-1.2
17.2	6150	-1.2
17.4	6200	-1.0
17.6	6250	-0.8
17.7	6300	-0.7
17.7	6350	-0.7
17.7	6400	-0.7
18.0	6450	-0.4
18.3	6500	-0.1
18.6	6550	0.2
18.6	6600	0.2
18.9	6650	0.5
19.0	6700	0.6
19.1	6750	0.7
19.2	6800	0.8

19.2	6850	0.8
19.4	6900	1.0
19.7	6950	1.3
19.8	7000	1.4
20.1	7050	1.7
20.5	7100	2.1
20.8	7150	2.4
21.1	7200	2.7
21.6	7250	3.2
21.7	7300	3.3
21.8	7350	3.4
21.9	7400	3.5
21.9	7450	3.5
22.0	7500	3.6
23.3	7550	4.9
23.4	7600	5.0
23.6	7650	5.2
24.0	7700	5.6
24.0	7750	5.6
23.9	7800	5.5
23.9	7850	5.5
23.8	7900	5.4
25.0	7950	6.6
25.2	8000	6.8
25.3	8050	6.9
25.4	8100	7.0
25.6	8150	7.2
25.8	8200	7.4
25.9	8250	7.5
26.3	8300	7.9
26.5	8350	8.1
26.6	8400	8.2
26.5	8450	8.1
26.3	8500	7.9
<b>12.9</b>		

### Processing Gain Channel 6 (fc=2437MHz) @ 11Mbps



**Processing Gain**

ISL37400M

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2453.50	25.4	16.4	7.0	2.0	-55.2	<=8.0
2453.55	24.7	16.4	6.3	2.0	-55.9	<=8.0
2453.60	24.2	16.4	5.8	2.0	-56.4	<=8.0
2453.65	24.0	16.4	5.6	2.0	-56.6	<=8.0
2453.70	24.0	16.4	5.6	2.0	-56.6	<=8.0
2453.75	24.2	16.4	5.8	2.0	-56.4	<=8.0
2453.80	24.3	16.4	5.9	2.0	-56.3	<=8.0
2453.85	24.3	16.4	5.9	2.0	-56.3	<=8.0
2453.90	24.2	16.4	5.8	2.0	-56.4	<=8.0
2453.95	24.2	16.4	5.8	2.0	-56.4	<=8.0
2454.00	24.0	16.4	5.6	2.0	-56.6	<=8.0
2454.05	24.4	16.4	6.0	2.0	-56.2	<=8.0
2454.10	24.4	16.4	6.0	2.0	-56.2	<=8.0
2454.15	24.4	16.4	6.0	2.0	-56.2	<=8.0
2454.20	24.5	16.4	6.1	2.0	-56.1	<=8.0
2454.25	24.5	16.4	6.1	2.0	-56.1	<=8.0
2454.30	23.7	16.4	5.3	2.0	-56.9	<=8.0
2454.35	23.7	16.4	5.3	2.0	-56.9	<=8.0
2454.40	23.6	16.4	5.2	2.0	-57.0	<=8.0
2454.45	23.2	16.4	4.8	2.0	-57.4	<=8.0
2454.50	23.3	16.4	4.9	2.0	-57.3	<=8.0
2454.55	23.2	16.4	4.8	2.0	-57.4	<=8.0
2454.60	22.8	16.4	4.4	2.0	-57.8	<=8.0
2454.65	21.9	16.4	3.5	2.0	-58.7	<=8.0
2454.70	22.3	16.4	3.9	2.0	-58.3	<=8.0
2454.75	22.1	16.4	3.7	2.0	-58.5	<=8.0
2454.80	22.0	16.4	3.6	2.0	-58.6	<=8.0
2454.85	20.4	16.4	2.0	2.0	-60.2	<=8.0
2454.90	20.8	16.4	2.4	2.0	-59.8	<=8.0
2454.95	20.7	16.4	2.3	2.0	-59.9	<=8.0
2455.00	21.0	16.4	2.6	2.0	-59.6	<=8.0
2455.05	21.0	16.4	2.6	2.0	-59.6	<=8.0
2455.10	20.7	16.4	2.3	2.0	-59.9	<=8.0
2455.15	19.9	16.4	1.5	2.0	-60.7	<=8.0
2455.20	20.0	16.4	1.6	2.0	-60.6	<=8.0
2455.25	20.0	16.4	1.6	2.0	-60.6	<=8.0
2455.30	19.4	16.4	1.0	2.0	-61.2	<=8.0
2455.35	19.4	16.4	1.0	2.0	-61.2	<=8.0
2455.40	19.2	16.4	0.8	2.0	-61.4	<=8.0
2455.45	19.0	16.4	0.6	2.0	-61.6	<=8.0
2455.50	18.8	16.4	0.4	2.0	-61.8	<=8.0
2455.55	18.8	16.4	0.4	2.0	-61.8	<=8.0
2455.60	18.8	16.4	0.4	2.0	-61.8	<=8.0
2455.65	18.4	16.4	0.0	2.0	-62.2	<=8.0
2455.70	18.2	16.4	-0.2	2.0	-62.4	<=8.0
2455.75	17.5	16.4	-0.9	2.0	-63.1	<=8.0
2455.80	17.5	16.4	-0.9	2.0	-63.1	<=8.0
2455.85	17.0	16.4	-1.4	2.0	-63.6	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2455.90	17.2	16.4	-1.2	2.0	-63.4	<=8.0
2455.95	17.0	16.4	-1.4	2.0	-63.6	<=8.0
2456.00	17.0	16.4	-1.4	2.0	-63.6	<=8.0
2456.05	16.8	16.4	-1.6	2.0	-63.8	<=8.0
2456.10	16.9	16.4	-1.5	2.0	-63.7	<=8.0
2456.15	16.6	16.4	-1.8	2.0	-64.0	<=8.0
2456.20	16.5	16.4	-1.9	2.0	-64.1	<=8.0
2456.25	16.5	16.4	-1.9	2.0	-64.1	<=8.0
2456.30	16.7	16.4	-1.7	2.0	-63.9	<=8.0
2456.35	16.5	16.4	-1.9	2.0	-64.1	<=8.0
2456.40	16.1	16.4	-2.3	2.0	-64.5	<=8.0
2456.45	16.0	16.4	-2.4	2.0	-64.6	<=8.0
2456.50	15.9	16.4	-2.5	2.0	-64.7	<=8.0
2456.55	15.8	16.4	-2.6	2.0	-64.8	<=8.0
2456.60	15.7	16.4	-2.7	2.0	-64.9	<=8.0
2456.65	15.4	16.4	-3.0	2.0	-65.2	<=8.0
2456.70	15.4	16.4	-3.0	2.0	-65.2	<=8.0
2456.75	15.2	16.4	-3.2	2.0	-65.4	<=8.0
2456.80	15.1	16.4	-3.3	2.0	-65.5	<=8.0
2456.85	14.9	16.4	-3.5	2.0	-65.7	<=8.0
2456.90	15.1	16.4	-3.3	2.0	-65.5	<=8.0
2456.95	15.1	16.4	-3.3	2.0	-65.5	<=8.0
2457.00	15.1	16.4	-3.3	2.0	-65.5	<=8.0
2457.05	15.1	16.4	-3.3	2.0	-65.5	<=8.0
2457.10	15.0	16.4	-3.4	2.0	-65.6	<=8.0
2457.15	14.9	16.4	-3.5	2.0	-65.7	<=8.0
2457.20	14.9	16.4	-3.5	2.0	-65.7	<=8.0
2457.25	14.9	16.4	-3.5	2.0	-65.7	<=8.0
2457.30	14.9	16.4	-3.5	2.0	-65.7	<=8.0
2457.35	14.7	16.4	-3.7	2.0	-65.9	<=8.0
2457.40	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2457.45	14.5	16.4	-3.9	2.0	-66.1	<=8.0
2457.50	14.7	16.4	-3.7	2.0	-65.9	<=8.0
2457.55	14.7	16.4	-3.7	2.0	-65.9	<=8.0
2457.60	14.5	16.4	-3.9	2.0	-66.1	<=8.0
2457.65	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2457.70	14.3	16.4	-4.1	2.0	-66.3	<=8.0
2457.75	14.3	16.4	-4.1	2.0	-66.3	<=8.0
2457.80	14.1	16.4	-4.3	2.0	-66.5	<=8.0
2457.85	13.9	16.4	-4.5	2.0	-66.7	<=8.0
2457.90	13.5	16.4	-4.9	2.0	-67.1	<=8.0
2457.95	13.7	16.4	-4.7	2.0	-66.9	<=8.0
2458.00	13.7	16.4	-4.7	2.0	-66.9	<=8.0
2458.05	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2458.10	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2458.15	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2458.20	13.5	16.4	-4.9	2.0	-67.1	<=8.0
2458.25	13.5	16.4	-4.9	2.0	-67.1	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2458.30	13.7	16.4	-4.7	2.0	-66.9	<=8.0
2458.35	13.7	16.4	-4.7	2.0	-66.9	<=8.0
2458.40	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2458.45	13.5	16.4	-4.9	2.0	-67.1	<=8.0
2458.50	13.4	16.4	-5.0	2.0	-67.2	<=8.0
2458.55	13.5	16.4	-4.9	2.0	-67.1	<=8.0
2458.60	13.3	16.4	-5.1	2.0	-67.3	<=8.0
2458.65	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2458.70	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2458.75	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2458.80	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2458.85	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2458.90	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2458.95	13.2	16.4	-5.2	2.0	-67.4	<=8.0
2459.00	13.3	16.4	-5.1	2.0	-67.3	<=8.0
2459.05	13.4	16.4	-5.0	2.0	-67.2	<=8.0
2459.10	13.3	16.4	-5.1	2.0	-67.3	<=8.0
2459.15	13.2	16.4	-5.2	2.0	-67.4	<=8.0
2459.20	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2459.25	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2459.30	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2459.35	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2459.40	12.4	16.4	-6.0	2.0	-68.2	<=8.0
2459.45	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2459.50	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2459.55	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2459.60	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2459.65	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2459.70	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2459.75	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2459.80	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2459.85	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2459.90	12.3	16.4	-6.1	2.0	-68.3	<=8.0
2459.95	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.00	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.05	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.10	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2460.15	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2460.20	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2460.25	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2460.30	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2460.35	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2460.40	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.45	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2460.50	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2460.55	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2460.60	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2460.65	12.4	16.4	-6.0	2.0	-68.2	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2460.70	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.75	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.80	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.85	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2460.90	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2460.95	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2461.00	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2461.05	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2461.10	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2461.15	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2461.20	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2461.25	13.2	16.4	-5.2	2.0	-67.4	<=8.0
2461.30	13.2	16.4	-5.2	2.0	-67.4	<=8.0
2461.35	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2461.40	12.4	16.4	-6.0	2.0	-68.2	<=8.0
2461.45	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2461.50	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2461.55	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2461.60	12.4	16.4	-6.0	2.0	-68.2	<=8.0
2461.65	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2461.70	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2461.75	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2461.80	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2461.85	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2461.90	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2461.95	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2462.00	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2462.05	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2462.10	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2462.15	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2462.20	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2462.25	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2462.30	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2462.35	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2462.40	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2462.45	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2462.50	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2462.55	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2462.60	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2462.65	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2462.70	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2462.75	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2462.80	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2462.85	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2462.90	12.1	16.4	-6.3	2.0	-68.5	<=8.0
2462.95	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2463.00	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2463.05	13.0	16.4	-5.4	2.0	-67.6	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2463.10	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2463.15	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2463.20	13.2	16.4	-5.2	2.0	-67.4	<=8.0
2463.25	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2463.30	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2463.35	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2463.40	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2463.45	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2463.50	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2463.55	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2463.60	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2463.65	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2463.70	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2463.75	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2463.80	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2463.85	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2463.90	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2463.95	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2464.00	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2464.05	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2464.10	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2464.15	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2464.20	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2464.25	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2464.30	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2464.35	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2464.40	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2464.45	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2464.50	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2464.55	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2464.60	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2464.65	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2464.70	12.4	16.4	-6.0	2.0	-68.2	<=8.0
2464.75	12.3	16.4	-6.1	2.0	-68.3	<=8.0
2464.80	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2464.85	12.3	16.4	-6.1	2.0	-68.3	<=8.0
2464.90	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2464.95	12.6	16.4	-5.8	2.0	-68.0	<=8.0
2465.00	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2465.05	12.5	16.4	-5.9	2.0	-68.1	<=8.0
2465.10	12.8	16.4	-5.6	2.0	-67.8	<=8.0
2465.15	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2465.20	13.0	16.4	-5.4	2.0	-67.6	<=8.0
2465.25	13.3	16.4	-5.1	2.0	-67.3	<=8.0
2465.30	13.4	16.4	-5.0	2.0	-67.2	<=8.0
2465.35	13.4	16.4	-5.0	2.0	-67.2	<=8.0
2465.40	12.9	16.4	-5.5	2.0	-67.7	<=8.0
2465.45	13.2	16.4	-5.2	2.0	-67.4	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2465.50	13.4	16.4	-5.0	2.0	-67.2	<=8.0
2465.55	13.5	16.4	-4.9	2.0	-67.1	<=8.0
2465.60	13.5	16.4	-4.9	2.0	-67.1	<=8.0
2465.65	12.7	16.4	-5.7	2.0	-67.9	<=8.0
2465.70	13.5	16.4	-4.9	2.0	-67.1	<=8.0
2465.75	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2465.80	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2465.85	13.1	16.4	-5.3	2.0	-67.5	<=8.0
2465.90	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2465.95	13.8	16.4	-4.6	2.0	-66.8	<=8.0
2466.00	13.9	16.4	-4.5	2.0	-66.7	<=8.0
2466.05	14.0	16.4	-4.4	2.0	-66.6	<=8.0
2466.10	14.0	16.4	-4.4	2.0	-66.6	<=8.0
2466.15	13.6	16.4	-4.8	2.0	-67.0	<=8.0
2466.20	13.8	16.4	-4.6	2.0	-66.8	<=8.0
2466.25	14.0	16.4	-4.4	2.0	-66.6	<=8.0
2466.30	13.9	16.4	-4.5	2.0	-66.7	<=8.0
2466.35	14.1	16.4	-4.3	2.0	-66.5	<=8.0
2466.40	14.1	16.4	-4.3	2.0	-66.5	<=8.0
2466.45	14.1	16.4	-4.3	2.0	-66.5	<=8.0
2466.50	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2466.55	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2466.60	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2466.65	14.5	16.4	-3.9	2.0	-66.1	<=8.0
2466.70	14.5	16.4	-3.9	2.0	-66.1	<=8.0
2466.75	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2466.80	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2466.85	14.2	16.4	-4.2	2.0	-66.4	<=8.0
2466.90	14.2	16.4	-4.2	2.0	-66.4	<=8.0
2466.95	14.2	16.4	-4.2	2.0	-66.4	<=8.0
2467.00	14.4	16.4	-4.0	2.0	-66.2	<=8.0
2467.05	14.5	16.4	-3.9	2.0	-66.1	<=8.0
2467.10	14.6	16.4	-3.8	2.0	-66.0	<=8.0
2467.15	14.7	16.4	-3.7	2.0	-65.9	<=8.0
2467.20	14.8	16.4	-3.6	2.0	-65.8	<=8.0
2467.25	15.1	16.4	-3.3	2.0	-65.5	<=8.0
2467.30	15.4	16.4	-3.0	2.0	-65.2	<=8.0
2467.35	15.5	16.4	-2.9	2.0	-65.1	<=8.0
2467.40	15.3	16.4	-3.1	2.0	-65.3	<=8.0
2467.45	15.6	16.4	-2.8	2.0	-65.0	<=8.0
2467.50	15.6	16.4	-2.8	2.0	-65.0	<=8.0
2467.55	15.6	16.4	-2.8	2.0	-65.0	<=8.0
2467.60	15.7	16.4	-2.7	2.0	-64.9	<=8.0
2467.65	15.7	16.4	-2.7	2.0	-64.9	<=8.0
2467.70	15.8	16.4	-2.6	2.0	-64.8	<=8.0
2467.75	15.8	16.4	-2.6	2.0	-64.8	<=8.0
2467.80	16.0	16.4	-2.4	2.0	-64.6	<=8.0
2467.85	16.1	16.4	-2.3	2.0	-64.5	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2467.90	16.3	16.4	-2.1	2.0	-64.3	<=8.0
2467.95	16.3	16.4	-2.1	2.0	-64.3	<=8.0
2468.00	16.6	16.4	-1.8	2.0	-64.0	<=8.0
2468.05	16.8	16.4	-1.6	2.0	-63.8	<=8.0
2468.10	16.9	16.4	-1.5	2.0	-63.7	<=8.0
2468.15	16.9	16.4	-1.5	2.0	-63.7	<=8.0
2468.20	17.2	16.4	-1.2	2.0	-63.4	<=8.0
2468.25	17.1	16.4	-1.3	2.0	-63.5	<=8.0
2468.30	17.2	16.4	-1.2	2.0	-63.4	<=8.0
2468.35	17.3	16.4	-1.1	2.0	-63.3	<=8.0
2468.40	17.6	16.4	-0.8	2.0	-63.0	<=8.0
2468.45	17.6	16.4	-0.8	2.0	-63.0	<=8.0
2468.50	17.7	16.4	-0.7	2.0	-62.9	<=8.0
2468.55	17.7	16.4	-0.7	2.0	-62.9	<=8.0
2468.60	17.7	16.4	-0.7	2.0	-62.9	<=8.0
2468.65	17.7	16.4	-0.7	2.0	-62.9	<=8.0
2468.70	18.0	16.4	-0.4	2.0	-62.6	<=8.0
2468.75	17.9	16.4	-0.5	2.0	-62.7	<=8.0
2468.80	18.1	16.4	-0.3	2.0	-62.5	<=8.0
2468.85	18.1	16.4	-0.3	2.0	-62.5	<=8.0
2468.90	18.2	16.4	-0.2	2.0	-62.4	<=8.0
2468.95	18.7	16.4	0.3	2.0	-61.9	<=8.0
2469.00	19.1	16.4	0.7	2.0	-61.5	<=8.0
2469.05	19.1	16.4	0.7	2.0	-61.5	<=8.0
2469.10	19.8	16.4	1.4	2.0	-60.8	<=8.0
2469.15	20.5	16.4	2.1	2.0	-60.1	<=8.0
2469.20	20.8	16.4	2.4	2.0	-59.8	<=8.0
2469.25	20.8	16.4	2.4	2.0	-59.8	<=8.0
2469.30	20.8	16.4	2.4	2.0	-59.8	<=8.0
2469.35	21.4	16.4	3.0	2.0	-59.2	<=8.0
2469.40	21.4	16.4	3.0	2.0	-59.2	<=8.0
2469.45	21.4	16.4	3.0	2.0	-59.2	<=8.0
2469.50	21.5	16.4	3.1	2.0	-59.1	<=8.0
2469.55	21.5	16.4	3.1	2.0	-59.1	<=8.0
2469.60	21.7	16.4	3.3	2.0	-58.9	<=8.0
2469.65	21.7	16.4	3.3	2.0	-58.9	<=8.0
2469.70	21.7	16.4	3.3	2.0	-58.9	<=8.0
2469.75	21.8	16.4	3.4	2.0	-58.8	<=8.0
2469.80	21.8	16.4	3.4	2.0	-58.8	<=8.0
2469.85	22.7	16.4	4.3	2.0	-57.9	<=8.0
2469.90	23.5	16.4	5.1	2.0	-57.1	<=8.0
2469.95	24.0	16.4	5.6	2.0	-56.6	<=8.0
2470.00	24.0	16.4	5.6	2.0	-56.6	<=8.0
2470.05	23.9	16.4	5.5	2.0	-56.7	<=8.0
2470.10	24.1	16.4	5.7	2.0	-56.5	<=8.0
2470.15	24.3	16.4	5.9	2.0	-56.3	<=8.0
2470.20	24.7	16.4	6.3	2.0	-55.9	<=8.0
2470.25	25.0	16.4	6.6	2.0	-55.6	<=8.0

11Mbps CHANNEL 11 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2470.30	25.0	16.4	6.6	2.0	-55.6	<=8.0
2470.35	25.0	16.4	6.6	2.0	-55.6	<=8.0
2470.40	25.2	16.4	6.8	2.0	-55.4	<=8.0
2470.45	25.2	16.4	6.8	2.0	-55.4	<=8.0
2470.50	25.3	16.4	6.9	2.0	-55.3	<=8.0

**12.8**

**Test Conditions**

TX Card **HWB3163-04 Rev B**  
 S/N **99360038**  
 RX Card **ISL37400M Rev A**  
 S/N **00500038**  
 TX Firmware **P10002C0, MS11168A3**  
 RX Firmware **ID010000, PK010001, SF010000**  
 Software Ver. **3.0.24**  
 Mode **11 MB Pseudo IBSS**  
 Pkt Size **1024**  
 Pkt Dly **1**  
 Pkt Burst **6**

Intersil Chips on Card: **ISL3984**  
**ISL3685**  
**HFA3783**  
**ISL3183**  
**ISL3874**

Processing Gain (dB)	XMIT level	-62.2
	<b>S/N+Ls</b>	<b>18.4</b>
	<b>0dB J/S</b>	<b>0.0</b>
PG	offset	Signal Generator Delta
25.4	-8500	7.0
24.7	-8450	6.3
24.2	-8400	5.8
24.0	-8350	5.6
24.0	-8300	5.6
24.2	-8250	5.8
24.3	-8200	5.9
24.3	-8150	5.9
24.2	-8100	5.8
24.2	-8050	5.8
24.0	-8000	5.6
24.4	-7950	6.0
24.4	-7900	6.0
24.4	-7850	6.0
24.5	-7800	6.1
24.5	-7750	6.1
23.7	-7700	5.3
23.7	-7650	5.3
23.6	-7600	5.2
23.2	-7550	4.8
23.3	-7500	4.9
23.2	-7450	4.8
22.8	-7400	4.4
21.9	-7350	3.5
22.3	-7300	3.9
22.1	-7250	3.7
22.0	-7200	3.6
20.4	-7150	2.0
20.8	-7100	2.4
20.7	-7050	2.3
21.0	-7000	2.6
21.0	-6950	2.6
20.7	-6900	2.3
19.9	-6850	1.5
20.0	-6800	1.6
20.0	-6750	1.6
19.4	-6700	1.0
19.4	-6650	1.0
19.2	-6600	0.8
19.0	-6550	0.6
18.8	-6500	0.4
18.8	-6450	0.4
18.8	-6400	0.4
18.4	-6350	0.0
18.2	-6300	-0.2
17.5	-6250	-0.9
17.5	-6200	-0.9

17.0	-6150	-1.4	
17.2	-6100	-1.2	
17.0	-6050	-1.4	
17.0	-6000	-1.4	
16.8	-5950	-1.6	
16.9	-5900	-1.5	
16.6	-5850	-1.8	
16.5	-5800	-1.9	
16.5	-5750	-1.9	
16.7	-5700	-1.7	
16.5	-5650	-1.9	
16.1	-5600	-2.3	
16.0	-5550	-2.4	
15.9	-5500	-2.5	
15.8	-5450	-2.6	
15.7	-5400	-2.7	
15.4	-5350	-3.0	
15.4	-5300	-3.0	
15.2	-5250	-3.2	
15.1	-5200	-3.3	
14.9	-5150	-3.5	
15.1	-5100	-3.3	
15.1	-5050	-3.3	
15.1	-5000	-3.3	
15.1	-4950	-3.3	
15.0	-4900	-3.4	
14.9	-4850	-3.5	
14.9	-4800	-3.5	
14.9	-4750	-3.5	
14.9	-4700	-3.5	
14.7	-4650	-3.7	
14.4	-4600	-4.0	
14.5	-4550	-3.9	
14.7	-4500	-3.7	
14.7	-4450	-3.7	
14.5	-4400	-3.9	
14.4	-4350	-4.0	
14.3	-4300	-4.1	
14.3	-4250	-4.1	
14.1	-4200	-4.3	
13.9	-4150	-4.5	
13.5	-4100	-4.9	
13.7	-4050	-4.7	
13.7	-4000	-4.7	
13.6	-3950	-4.8	
13.6	-3900	-4.8	
13.6	-3850	-4.8	
13.5	-3800	-4.9	
13.5	-3750	-4.9	
13.7	-3700	-4.7	
13.7	-3650	-4.7	
13.6	-3600	-4.8	

13.5	-3550	-4.9	
13.4	-3500	-5.0	
13.5	-3450	-4.9	
13.3	-3400	-5.1	
13.0	-3350	-5.4	
13.0	-3300	-5.4	
12.9	-3250	-5.5	
13.1	-3200	-5.3	
13.0	-3150	-5.4	
12.6	-3100	-5.8	
13.2	-3050	-5.2	
13.3	-3000	-5.1	
13.4	-2950	-5.0	
13.3	-2900	-5.1	
13.2	-2850	-5.2	
13.0	-2800	-5.4	
13.0	-2750	-5.4	
13.0	-2700	-5.4	
12.9	-2650	-5.5	
12.4	-2600	-6.0	
12.6	-2550	-5.8	
12.6	-2500	-5.8	
12.6	-2450	-5.8	
12.6	-2400	-5.8	
12.7	-2350	-5.7	
12.6	-2300	-5.8	
12.8	-2250	-5.6	
12.8	-2200	-5.6	
12.6	-2150	-5.8	
12.3	-2100	-6.1	
12.5	-2050	-5.9	
12.5	-2000	-5.9	
12.5	-1950	-5.9	
12.6	-1900	-5.8	
12.7	-1850	-5.7	
12.8	-1800	-5.6	
12.8	-1750	-5.6	
12.8	-1700	-5.6	
12.8	-1650	-5.6	
12.5	-1600	-5.9	
12.9	-1550	-5.5	
12.8	-1500	-5.6	
12.8	-1450	-5.6	
12.7	-1400	-5.7	
12.4	-1350	-6.0	
12.5	-1300	-5.9	
12.5	-1250	-5.9	
12.5	-1200	-5.9	
12.5	-1150	-5.9	
12.6	-1100	-5.8	
12.8	-1050	-5.6	
12.9	-1000	-5.5	


13.0	-950	-5.4	
13.1	-900	-5.3	
13.1	-850	-5.3	
13.0	-800	-5.4	
13.2	-750	-5.2	
13.2	-700	-5.2	
13.1	-650	-5.3	
12.4	-600	-6.0	
13.0	-550	-5.4	
13.0	-500	-5.4	
13.0	-450	-5.4	
12.4	-400	-6.0	
12.7	-350	-5.7	
13.0	-300	-5.4	
13.1	-250	-5.3	
13.0	-200	-5.4	
12.9	-150	-5.5	
12.8	-100	-5.6	
12.8	-50	-5.6	
12.8	0	-5.6	
12.8	50	-5.6	
12.7	100	-5.7	
12.7	150	-5.7	
12.8	200	-5.6	
12.8	250	-5.6	
13.0	300	-5.4	
13.1	350	-5.3	
13.1	400	-5.3	
13.0	450	-5.4	
13.1	500	-5.3	
13.0	550	-5.4	
13.1	600	-5.3	
12.7	650	-5.7	
12.8	700	-5.6	
12.6	750	-5.8	
12.8	800	-5.6	
12.5	850	-5.9	
12.1	900	-6.3	
12.9	950	-5.5	
12.9	1000	-5.5	
13.0	1050	-5.4	
13.1	1100	-5.3	
13.1	1150	-5.3	
13.2	1200	-5.2	
13.1	1250	-5.3	
13.1	1300	-5.3	
13.1	1350	-5.3	
12.5	1400	-5.9	
13.0	1450	-5.4	
13.0	1500	-5.4	
12.9	1550	-5.5	
12.8	1600	-5.6	

12.8	1650	-5.6	
12.9	1700	-5.5	
13.0	1750	-5.4	
13.0	1800	-5.4	
13.0	1850	-5.4	
12.9	1900	-5.5	
12.9	1950	-5.5	
12.8	2000	-5.6	
12.7	2050	-5.7	
12.7	2100	-5.7	
12.7	2150	-5.7	
12.7	2200	-5.7	
12.8	2250	-5.6	
12.8	2300	-5.6	
12.8	2350	-5.6	
12.8	2400	-5.6	
12.8	2450	-5.6	
13.0	2500	-5.4	
12.8	2550	-5.6	
12.7	2600	-5.7	
12.6	2650	-5.8	
12.4	2700	-6.0	
12.3	2750	-6.1	
12.6	2800	-5.8	
12.3	2850	-6.1	
12.5	2900	-5.9	
12.6	2950	-5.8	
12.5	3000	-5.9	
12.5	3050	-5.9	
12.8	3100	-5.6	
12.9	3150	-5.5	
13.0	3200	-5.4	
13.3	3250	-5.1	
13.4	3300	-5.0	
13.4	3350	-5.0	
12.9	3400	-5.5	
13.2	3450	-5.2	
13.4	3500	-5.0	
13.5	3550	-4.9	
13.5	3600	-4.9	
12.7	3650	-5.7	
13.5	3700	-4.9	
13.6	3750	-4.8	
13.6	3800	-4.8	
13.1	3850	-5.3	
13.6	3900	-4.8	
13.8	3950	-4.6	
13.9	4000	-4.5	
14.0	4050	-4.4	
14.0	4100	-4.4	
13.6	4150	-4.8	
13.8	4200	-4.6	

14.0	4250	-4.4	
13.9	4300	-4.5	
14.1	4350	-4.3	
14.1	4400	-4.3	
14.1	4450	-4.3	
14.4	4500	-4.0	
14.4	4550	-4.0	
14.4	4600	-4.0	
14.5	4650	-3.9	
14.5	4700	-3.9	
14.4	4750	-4.0	
14.4	4800	-4.0	
14.2	4850	-4.2	
14.2	4900	-4.2	
14.2	4950	-4.2	
14.4	5000	-4.0	
14.5	5050	-3.9	
14.6	5100	-3.8	
14.7	5150	-3.7	
14.8	5200	-3.6	
15.1	5250	-3.3	
15.4	5300	-3.0	
15.5	5350	-2.9	
15.3	5400	-3.1	
15.6	5450	-2.8	
15.6	5500	-2.8	
15.6	5550	-2.8	
15.7	5600	-2.7	
15.7	5650	-2.7	
15.8	5700	-2.6	
15.8	5750	-2.6	
16.0	5800	-2.4	
16.1	5850	-2.3	
16.3	5900	-2.1	
16.3	5950	-2.1	
16.6	6000	-1.8	
16.8	6050	-1.6	
16.9	6100	-1.5	
16.9	6150	-1.5	
17.2	6200	-1.2	
17.1	6250	-1.3	
17.2	6300	-1.2	
17.3	6350	-1.1	
17.6	6400	-0.8	
17.6	6450	-0.8	
17.7	6500	-0.7	
17.7	6550	-0.7	
17.7	6600	-0.7	
17.7	6650	-0.7	
18.0	6700	-0.4	
17.9	6750	-0.5	
18.1	6800	-0.3	

18.1	6850	-0.3	
18.2	6900	-0.2	
18.7	6950	0.3	
19.1	7000	0.7	
19.1	7050	0.7	
19.8	7100	1.4	
20.5	7150	2.1	
20.8	7200	2.4	
20.8	7250	2.4	
20.8	7300	2.4	
21.4	7350	3.0	
21.4	7400	3.0	
21.4	7450	3.0	
21.5	7500	3.1	
21.5	7550	3.1	
21.7	7600	3.3	
21.7	7650	3.3	
21.7	7700	3.3	
21.8	7750	3.4	
21.8	7800	3.4	
22.7	7850	4.3	
23.5	7900	5.1	
24.0	7950	5.6	
24.0	8000	5.6	
23.9	8050	5.5	
24.1	8100	5.7	
24.3	8150	5.9	
24.7	8200	6.3	
25.0	8250	6.6	
25.0	8300	6.6	
25.0	8350	6.6	
25.2	8400	6.8	
25.2	8450	6.8	
25.3	8500	6.9	
<b>12.8</b>	<b>Processing Gain (dB) @ 80th Percentile =</b>		

### Processing Gain Channel 11 (fc=2462MHz) @ 11Mbps



**Processing Gain**

ISL37400M

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2403.50	22.6	16.4	4.2	2.0	-58.7	<=8.0
2403.55	22.3	16.4	3.9	2.0	-59.0	<=8.0
2403.60	22.2	16.4	3.8	2.0	-59.1	<=8.0
2403.65	22.0	16.4	3.6	2.0	-59.3	<=8.0
2403.70	21.7	16.4	3.3	2.0	-59.6	<=8.0
2403.75	21.1	16.4	2.7	2.0	-60.2	<=8.0
2403.80	20.8	16.4	2.4	2.0	-60.5	<=8.0
2403.85	20.7	16.4	2.3	2.0	-60.6	<=8.0
2403.90	23.2	16.4	4.8	2.0	-58.1	<=8.0
2403.95	20.8	16.4	2.4	2.0	-60.5	<=8.0
2404.00	22.5	16.4	4.1	2.0	-58.8	<=8.0
2404.05	23.8	16.4	5.4	2.0	-57.5	<=8.0
2404.10	23.9	16.4	5.5	2.0	-57.4	<=8.0
2404.15	24.2	16.4	5.8	2.0	-57.1	<=8.0
2404.20	24.2	16.4	5.8	2.0	-57.1	<=8.0
2404.25	24.2	16.4	5.8	2.0	-57.1	<=8.0
2404.30	23.6	16.4	5.2	2.0	-57.7	<=8.0
2404.35	23.6	16.4	5.2	2.0	-57.7	<=8.0
2404.40	23.2	16.4	4.8	2.0	-58.1	<=8.0
2404.45	23.1	16.4	4.7	2.0	-58.2	<=8.0
2404.50	23.1	16.4	4.7	2.0	-58.2	<=8.0
2404.55	22.8	16.4	4.4	2.0	-58.5	<=8.0
2404.60	22.1	16.4	3.7	2.0	-59.2	<=8.0
2404.65	21.5	16.4	3.1	2.0	-59.8	<=8.0
2404.70	21.8	16.4	3.4	2.0	-59.5	<=8.0
2404.75	21.6	16.4	3.2	2.0	-59.7	<=8.0
2404.80	21.6	16.4	3.2	2.0	-59.7	<=8.0
2404.85	20.3	16.4	1.9	2.0	-61.0	<=8.0
2404.90	20.3	16.4	1.9	2.0	-61.0	<=8.0
2404.95	20.4	16.4	2.0	2.0	-60.9	<=8.0
2405.00	20.4	16.4	2.0	2.0	-60.9	<=8.0
2405.05	20.6	16.4	2.2	2.0	-60.7	<=8.0
2405.10	20.6	16.4	2.2	2.0	-60.7	<=8.0
2405.15	20.4	16.4	2.0	2.0	-60.9	<=8.0
2405.20	19.9	16.4	1.5	2.0	-61.4	<=8.0
2405.25	19.8	16.4	1.4	2.0	-61.5	<=8.0
2405.30	19.8	16.4	1.4	2.0	-61.5	<=8.0
2405.35	19.2	16.4	0.8	2.0	-62.1	<=8.0
2405.40	19.2	16.4	0.8	2.0	-62.1	<=8.0
2405.45	18.9	16.4	0.5	2.0	-62.4	<=8.0
2405.50	18.7	16.4	0.3	2.0	-62.6	<=8.0
2405.55	18.5	16.4	0.1	2.0	-62.8	<=8.0
2405.60	18.5	16.4	0.1	2.0	-62.8	<=8.0
2405.65	18.5	16.4	0.1	2.0	-62.8	<=8.0
2405.70	18.2	16.4	-0.2	2.0	-63.1	<=8.0
2405.75	17.9	16.4	-0.5	2.0	-63.4	<=8.0
2405.80	17.5	16.4	-0.9	2.0	-63.8	<=8.0
2405.85	17.1	16.4	-1.3	2.0	-64.2	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2405.90	16.8	16.4	-1.6	2.0	-64.5	<=8.0
2405.95	16.8	16.4	-1.6	2.0	-64.5	<=8.0
2406.00	16.8	16.4	-1.6	2.0	-64.5	<=8.0
2406.05	16.7	16.4	-1.7	2.0	-64.6	<=8.0
2406.10	16.6	16.4	-1.8	2.0	-64.7	<=8.0
2406.15	16.3	16.4	-2.1	2.0	-65.0	<=8.0
2406.20	16.1	16.4	-2.3	2.0	-65.2	<=8.0
2406.25	16.3	16.4	-2.1	2.0	-65.0	<=8.0
2406.30	16.3	16.4	-2.1	2.0	-65.0	<=8.0
2406.35	16.1	16.4	-2.3	2.0	-65.2	<=8.0
2406.40	15.8	16.4	-2.6	2.0	-65.5	<=8.0
2406.45	15.8	16.4	-2.6	2.0	-65.5	<=8.0
2406.50	15.6	16.4	-2.8	2.0	-65.7	<=8.0
2406.55	15.4	16.4	-3.0	2.0	-65.9	<=8.0
2406.60	15.3	16.4	-3.1	2.0	-66.0	<=8.0
2406.65	15.1	16.4	-3.3	2.0	-66.2	<=8.0
2406.70	15.0	16.4	-3.4	2.0	-66.3	<=8.0
2406.75	15.0	16.4	-3.4	2.0	-66.3	<=8.0
2406.80	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2406.85	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2406.90	14.9	16.4	-3.5	2.0	-66.4	<=8.0
2406.95	14.9	16.4	-3.5	2.0	-66.4	<=8.0
2407.00	14.9	16.4	-3.5	2.0	-66.4	<=8.0
2407.05	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2407.10	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2407.15	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2407.20	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2407.25	14.7	16.4	-3.7	2.0	-66.6	<=8.0
2407.30	14.7	16.4	-3.7	2.0	-66.6	<=8.0
2407.35	14.6	16.4	-3.8	2.0	-66.7	<=8.0
2407.40	14.5	16.4	-3.9	2.0	-66.8	<=8.0
2407.45	14.5	16.4	-3.9	2.0	-66.8	<=8.0
2407.50	14.5	16.4	-3.9	2.0	-66.8	<=8.0
2407.55	14.5	16.4	-3.9	2.0	-66.8	<=8.0
2407.60	14.3	16.4	-4.1	2.0	-67.0	<=8.0
2407.65	14.4	16.4	-4.0	2.0	-66.9	<=8.0
2407.70	14.2	16.4	-4.2	2.0	-67.1	<=8.0
2407.75	14.1	16.4	-4.3	2.0	-67.2	<=8.0
2407.80	14.0	16.4	-4.4	2.0	-67.3	<=8.0
2407.85	13.7	16.4	-4.7	2.0	-67.6	<=8.0
2407.90	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2407.95	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2408.00	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2408.05	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2408.10	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2408.15	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2408.20	13.3	16.4	-5.1	2.0	-68.0	<=8.0
2408.25	13.5	16.4	-4.9	2.0	-67.8	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2408.30	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2408.35	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2408.40	13.3	16.4	-5.1	2.0	-68.0	<=8.0
2408.45	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2408.50	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2408.55	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2408.60	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2408.65	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2408.70	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2408.75	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2408.80	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2408.85	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2408.90	12.2	16.4	-6.2	2.0	-69.1	<=8.0
2408.95	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2409.00	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2409.05	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2409.10	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2409.15	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2409.20	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2409.25	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2409.30	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2409.35	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2409.40	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2409.45	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2409.50	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2409.55	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2409.60	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2409.65	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2409.70	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2409.75	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2409.80	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2409.85	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2409.90	12.1	16.4	-6.3	2.0	-69.2	<=8.0
2409.95	12.3	16.4	-6.1	2.0	-69.0	<=8.0
2410.00	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2410.05	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2410.10	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2410.15	12.3	16.4	-6.1	2.0	-69.0	<=8.0
2410.20	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2410.25	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2410.30	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2410.35	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2410.40	12.5	16.4	-5.9	2.0	-68.8	<=8.0
2410.45	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2410.50	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2410.55	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2410.60	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2410.65	12.2	16.4	-6.2	2.0	-69.1	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2410.70	12.3	16.4	-6.1	2.0	-69.0	<=8.0
2410.75	12.3	16.4	-6.1	2.0	-69.0	<=8.0
2410.80	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2410.85	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2410.90	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2410.95	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2411.00	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2411.05	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2411.10	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2411.15	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2411.20	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2411.25	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2411.30	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2411.35	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2411.40	12.2	16.4	-6.2	2.0	-69.1	<=8.0
2411.45	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2411.50	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2411.55	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2411.60	12.1	16.4	-6.3	2.0	-69.2	<=8.0
2411.65	12.3	16.4	-6.1	2.0	-69.0	<=8.0
2411.70	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2411.75	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2411.80	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2411.85	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2411.90	12.5	16.4	-5.9	2.0	-68.8	<=8.0
2411.95	12.5	16.4	-5.9	2.0	-68.8	<=8.0
2412.00	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2412.05	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2412.10	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2412.15	12.5	16.4	-5.9	2.0	-68.8	<=8.0
2412.20	12.5	16.4	-5.9	2.0	-68.8	<=8.0
2412.25	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2412.30	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2412.35	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2412.40	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2412.45	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2412.50	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2412.55	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2412.60	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2412.65	12.3	16.4	-6.1	2.0	-69.0	<=8.0
2412.70	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2412.75	12.3	16.4	-6.1	2.0	-69.0	<=8.0
2412.80	12.5	16.4	-5.9	2.0	-68.8	<=8.0
2412.85	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2412.90	12.1	16.4	-6.3	2.0	-69.2	<=8.0
2412.95	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2413.00	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2413.05	12.8	16.4	-5.6	2.0	-68.5	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2413.10	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2413.15	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2413.20	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2413.25	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2413.30	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2413.35	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2413.40	12.4	16.4	-6.0	2.0	-68.9	<=8.0
2413.45	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2413.50	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2413.55	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2413.60	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2413.65	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2413.70	13.3	16.4	-5.1	2.0	-68.0	<=8.0
2413.75	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2413.80	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2413.85	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2413.90	13.3	16.4	-5.1	2.0	-68.0	<=8.0
2413.95	13.3	16.4	-5.1	2.0	-68.0	<=8.0
2414.00	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2414.05	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2414.10	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2414.15	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2414.20	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2414.25	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2414.30	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2414.35	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2414.40	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2414.45	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2414.50	13.3	16.4	-5.1	2.0	-68.0	<=8.0
2414.55	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2414.60	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2414.65	12.9	16.4	-5.5	2.0	-68.4	<=8.0
2414.70	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2414.75	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2414.80	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2414.85	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2414.90	12.6	16.4	-5.8	2.0	-68.7	<=8.0
2414.95	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2415.00	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2415.05	12.8	16.4	-5.6	2.0	-68.5	<=8.0
2415.10	13.0	16.4	-5.4	2.0	-68.3	<=8.0
2415.15	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2415.20	13.2	16.4	-5.2	2.0	-68.1	<=8.0
2415.25	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2415.30	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2415.35	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2415.40	13.1	16.4	-5.3	2.0	-68.2	<=8.0
2415.45	13.0	16.4	-5.4	2.0	-68.3	<=8.0

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2415.50	13.5	16.4	-4.9	2.0	-67.8	<=8.0
2415.55	13.6	16.4	-4.8	2.0	-67.7	<=8.0
2415.60	13.6	16.4	-4.8	2.0	-67.7	<=8.0
2415.65	12.7	16.4	-5.7	2.0	-68.6	<=8.0
2415.70	13.6	16.4	-4.8	2.0	-67.7	<=8.0
2415.75	13.8	16.4	-4.6	2.0	-67.5	<=8.0
2415.80	13.8	16.4	-4.6	2.0	-67.5	<=8.0
2415.85	13.4	16.4	-5.0	2.0	-67.9	<=8.0
2415.90	13.7	16.4	-4.7	2.0	-67.6	<=8.0
2415.95	13.8	16.4	-4.6	2.0	-67.5	<=8.0
2416.00	14.1	16.4	-4.3	2.0	-67.2	<=8.0
2416.05	14.1	16.4	-4.3	2.0	-67.2	<=8.0
2416.10	14.2	16.4	-4.2	2.0	-67.1	<=8.0
2416.15	14.0	16.4	-4.4	2.0	-67.3	<=8.0
2416.20	14.1	16.4	-4.3	2.0	-67.2	<=8.0
2416.25	14.3	16.4	-4.1	2.0	-67.0	<=8.0
2416.30	14.2	16.4	-4.2	2.0	-67.1	<=8.0
2416.35	14.4	16.4	-4.0	2.0	-66.9	<=8.0
2416.40	14.2	16.4	-4.2	2.0	-67.1	<=8.0
2416.45	14.3	16.4	-4.1	2.0	-67.0	<=8.0
2416.50	14.5	16.4	-3.9	2.0	-66.8	<=8.0
2416.55	14.7	16.4	-3.7	2.0	-66.6	<=8.0
2416.60	14.7	16.4	-3.7	2.0	-66.6	<=8.0
2416.65	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2416.70	14.7	16.4	-3.7	2.0	-66.6	<=8.0
2416.75	14.7	16.4	-3.7	2.0	-66.6	<=8.0
2416.80	14.6	16.4	-3.8	2.0	-66.7	<=8.0
2416.85	14.4	16.4	-4.0	2.0	-66.9	<=8.0
2416.90	14.4	16.4	-4.0	2.0	-66.9	<=8.0
2416.95	14.4	16.4	-4.0	2.0	-66.9	<=8.0
2417.00	14.6	16.4	-3.8	2.0	-66.7	<=8.0
2417.05	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2417.10	14.8	16.4	-3.6	2.0	-66.5	<=8.0
2417.15	15.0	16.4	-3.4	2.0	-66.3	<=8.0
2417.20	15.1	16.4	-3.3	2.0	-66.2	<=8.0
2417.25	15.4	16.4	-3.0	2.0	-65.9	<=8.0
2417.30	15.4	16.4	-3.0	2.0	-65.9	<=8.0
2417.35	15.7	16.4	-2.7	2.0	-65.6	<=8.0
2417.40	15.5	16.4	-2.9	2.0	-65.8	<=8.0
2417.45	15.8	16.4	-2.6	2.0	-65.5	<=8.0
2417.50	15.9	16.4	-2.5	2.0	-65.4	<=8.0
2417.55	15.9	16.4	-2.5	2.0	-65.4	<=8.0
2417.60	16.0	16.4	-2.4	2.0	-65.3	<=8.0
2417.65	16.0	16.4	-2.4	2.0	-65.3	<=8.0
2417.70	16.0	16.4	-2.4	2.0	-65.3	<=8.0
2417.75	16.2	16.4	-2.2	2.0	-65.1	<=8.0
2417.80	16.2	16.4	-2.2	2.0	-65.1	<=8.0
2417.85	16.3	16.4	-2.1	2.0	-65.0	<=8.0

**Processing Gain**

ISL37400M

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2417.90	16.7	16.4	-1.7	2.0	-64.6	<=8.0
2417.95	16.7	16.4	-1.7	2.0	-64.6	<=8.0
2418.00	16.8	16.4	-1.6	2.0	-64.5	<=8.0
2418.05	16.9	16.4	-1.5	2.0	-64.4	<=8.0
2418.10	17.2	16.4	-1.2	2.0	-64.1	<=8.0
2418.15	17.2	16.4	-1.2	2.0	-64.1	<=8.0
2418.20	17.2	16.4	-1.2	2.0	-64.1	<=8.0
2418.25	17.2	16.4	-1.2	2.0	-64.1	<=8.0
2418.30	17.4	16.4	-1.0	2.0	-63.9	<=8.0
2418.35	17.4	16.4	-1.0	2.0	-63.9	<=8.0
2418.40	17.4	16.4	-1.0	2.0	-63.9	<=8.0
2418.45	17.4	16.4	-1.0	2.0	-63.9	<=8.0
2418.50	17.5	16.4	-0.9	2.0	-63.8	<=8.0
2418.55	17.5	16.4	-0.9	2.0	-63.8	<=8.0
2418.60	17.6	16.4	-0.8	2.0	-63.7	<=8.0
2418.65	17.7	16.4	-0.7	2.0	-63.6	<=8.0
2418.70	17.9	16.4	-0.5	2.0	-63.4	<=8.0
2418.75	18.0	16.4	-0.4	2.0	-63.3	<=8.0
2418.80	18.0	16.4	-0.4	2.0	-63.3	<=8.0
2418.85	18.0	16.4	-0.4	2.0	-63.3	<=8.0
2418.90	17.9	16.4	-0.5	2.0	-63.4	<=8.0
2418.95	18.1	16.4	-0.3	2.0	-63.2	<=8.0
2419.00	18.3	16.4	-0.1	2.0	-63.0	<=8.0
2419.05	18.7	16.4	0.3	2.0	-62.6	<=8.0
2419.10	19.3	16.4	0.9	2.0	-62.0	<=8.0
2419.15	20.1	16.4	1.7	2.0	-61.2	<=8.0
2419.20	20.7	16.4	2.3	2.0	-60.6	<=8.0
2419.25	21.1	16.4	2.7	2.0	-60.2	<=8.0
2419.30	21.2	16.4	2.8	2.0	-60.1	<=8.0
2419.35	21.6	16.4	3.2	2.0	-59.7	<=8.0
2419.40	21.9	16.4	3.5	2.0	-59.4	<=8.0
2419.45	22.3	16.4	3.9	2.0	-59.0	<=8.0
2419.50	22.4	16.4	4.0	2.0	-58.9	<=8.0
2419.55	22.6	16.4	4.2	2.0	-58.7	<=8.0
2419.60	23.1	16.4	4.7	2.0	-58.2	<=8.0
2419.65	23.3	16.4	4.9	2.0	-58.0	<=8.0
2419.70	23.5	16.4	5.1	2.0	-57.8	<=8.0
2419.75	23.8	16.4	5.4	2.0	-57.5	<=8.0
2419.80	23.8	16.4	5.4	2.0	-57.5	<=8.0
2419.85	23.9	16.4	5.5	2.0	-57.4	<=8.0
2419.90	23.9	16.4	5.5	2.0	-57.4	<=8.0
2419.95	24.0	16.4	5.6	2.0	-57.3	<=8.0
2420.00	24.5	16.4	6.1	2.0	-56.8	<=8.0
2420.05	25.2	16.4	6.8	2.0	-56.1	<=8.0
2420.10	25.3	16.4	6.9	2.0	-56.0	<=8.0
2420.15	25.3	16.4	6.9	2.0	-56.0	<=8.0
2420.20	25.4	16.4	7.0	2.0	-55.9	<=8.0
2420.25	25.7	16.4	7.3	2.0	-55.6	<=8.0

11Mbps CHANNEL 1 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2420.30	25.9	16.4	7.5	2.0	-55.4	<=8.0
2420.35	25.9	16.4	7.5	2.0	-55.4	<=8.0
2420.40	25.9	16.4	7.5	2.0	-55.4	<=8.0
2420.45	26.0	16.4	7.6	2.0	-55.3	<=8.0
2420.50	25.8	16.4	7.4	2.0	-55.5	<=8.0

**12.8**

**Test Conditions**

TX Card **HWB3163-04 Rev B**  
 S/N **99360038**  
 RX Card **ISL37400M Rev A**  
 S/N **00500038**  
 TX Firmware **P10002C0, MS11168A3**  
 RX Firmware **ID010000, PK010001, SF010000**  
 Software Ver. **3.0.24**  
 Mode **11 MB Pseudo IBSS**  
 Pkt Size **1024**  
 Pkt Dly **1**  
 Pkt Burst **6**

Intersil Chips on Card: **ISL3984**  
**ISL3685**  
**HFA3783**

Processing Gain (dB)	XMIT level	-62.9
	S/N+Ls	18.4
	Conversion	0.0
PG	offset	Signal Generator Delta
22.6	-8500	4.2
22.3	-8450	3.9
22.2	-8400	3.8
22.0	-8350	3.6
21.7	-8300	3.3
21.1	-8250	2.7
20.8	-8200	2.4
20.7	-8150	2.3
23.2	-8100	4.8
20.8	-8050	2.4
22.5	-8000	4.1
23.8	-7950	5.4
23.9	-7900	5.5
24.2	-7850	5.8
24.2	-7800	5.8
24.2	-7750	5.8
23.6	-7700	5.2
23.6	-7650	5.2
23.2	-7600	4.8
23.1	-7550	4.7
23.1	-7500	4.7
22.8	-7450	4.4
22.1	-7400	3.7
21.5	-7350	3.1
21.8	-7300	3.4
21.6	-7250	3.2
21.6	-7200	3.2
20.3	-7150	1.9
20.3	-7100	1.9
20.4	-7050	2.0
20.4	-7000	2.0
20.6	-6950	2.2
20.6	-6900	2.2
20.4	-6850	2.0
19.9	-6800	1.5
19.8	-6750	1.4
19.8	-6700	1.4
19.2	-6650	0.8
19.2	-6600	0.8
18.9	-6550	0.5
18.7	-6500	0.3
18.5	-6450	0.1
18.5	-6400	0.1
18.5	-6350	0.1
18.2	-6300	-0.2
17.9	-6250	-0.5
17.5	-6200	-0.9

17.1	-6150	-1.3
16.8	-6100	-1.6
16.8	-6050	-1.6
16.8	-6000	-1.6
16.7	-5950	-1.7
16.6	-5900	-1.8
16.3	-5850	-2.1
16.1	-5800	-2.3
16.3	-5750	-2.1
16.3	-5700	-2.1
16.1	-5650	-2.3
15.8	-5600	-2.6
15.8	-5550	-2.6
15.6	-5500	-2.8
15.4	-5450	-3.0
15.3	-5400	-3.1
15.1	-5350	-3.3
15.0	-5300	-3.4
15.0	-5250	-3.4
14.8	-5200	-3.6
14.8	-5150	-3.6
14.9	-5100	-3.5
14.9	-5050	-3.5
14.9	-5000	-3.5
14.8	-4950	-3.6
14.8	-4900	-3.6
14.8	-4850	-3.6
14.8	-4800	-3.6
14.7	-4750	-3.7
14.7	-4700	-3.7
14.6	-4650	-3.8
14.5	-4600	-3.9
14.5	-4550	-3.9
14.5	-4500	-3.9
14.5	-4450	-3.9
14.3	-4400	-4.1
14.4	-4350	-4.0
14.2	-4300	-4.2
14.1	-4250	-4.3
14.0	-4200	-4.4
13.7	-4150	-4.7
13.5	-4100	-4.9
13.5	-4050	-4.9
13.4	-4000	-5.0
13.4	-3950	-5.0
13.4	-3900	-5.0
13.4	-3850	-5.0
13.3	-3800	-5.1
13.5	-3750	-4.9
13.5	-3700	-4.9
13.5	-3650	-4.9
13.3	-3600	-5.1

13.2	-3550	-5.2
13.2	-3500	-5.2
13.2	-3450	-5.2
13.1	-3400	-5.3
12.8	-3350	-5.6
12.8	-3300	-5.6
12.8	-3250	-5.6
12.8	-3200	-5.6
12.8	-3150	-5.6
12.2	-3100	-6.2
13.0	-3050	-5.4
13.1	-3000	-5.3
13.2	-2950	-5.2
13.2	-2900	-5.2
13.2	-2850	-5.2
12.9	-2800	-5.5
12.9	-2750	-5.5
12.8	-2700	-5.6
12.8	-2650	-5.6
12.4	-2600	-6.0
12.7	-2550	-5.7
12.7	-2500	-5.7
12.7	-2450	-5.7
12.6	-2400	-5.8
12.6	-2350	-5.8
12.6	-2300	-5.8
12.6	-2250	-5.8
12.6	-2200	-5.8
12.4	-2150	-6.0
12.1	-2100	-6.3
12.3	-2050	-6.1
12.4	-2000	-6.0
12.4	-1950	-6.0
12.4	-1900	-6.0
12.3	-1850	-6.1
12.6	-1800	-5.8
12.6	-1750	-5.8
12.6	-1700	-5.8
12.6	-1650	-5.8
12.5	-1600	-5.9
12.6	-1550	-5.8
12.7	-1500	-5.7
12.7	-1450	-5.7
12.6	-1400	-5.8
12.2	-1350	-6.2
12.3	-1300	-6.1
12.3	-1250	-6.1
12.4	-1200	-6.0
12.4	-1150	-6.0
12.4	-1100	-6.0
12.6	-1050	-5.8
12.7	-1000	-5.7


12.8	-950	-5.6
12.9	-900	-5.5
12.9	-850	-5.5
12.7	-800	-5.7
12.9	-750	-5.5
13.0	-700	-5.4
12.8	-650	-5.6
12.2	-600	-6.2
12.7	-550	-5.7
12.7	-500	-5.7
12.6	-450	-5.8
12.1	-400	-6.3
12.3	-350	-6.1
12.8	-300	-5.6
12.8	-250	-5.6
12.8	-200	-5.6
12.7	-150	-5.7
12.5	-100	-5.9
12.5	-50	-5.9
12.4	0	-6.0
12.4	50	-6.0
12.4	100	-6.0
12.5	150	-5.9
12.5	200	-5.9
12.6	250	-5.8
12.7	300	-5.7
12.8	350	-5.6
12.9	400	-5.5
12.8	450	-5.6
12.8	500	-5.6
12.8	550	-5.6
12.9	600	-5.5
12.3	650	-6.1
12.6	700	-5.8
12.3	750	-6.1
12.5	800	-5.9
12.4	850	-6.0
12.1	900	-6.3
12.4	950	-6.0
12.7	1000	-5.7
12.8	1050	-5.6
13.0	1100	-5.4
13.0	1150	-5.4
13.0	1200	-5.4
12.9	1250	-5.5
12.9	1300	-5.5
12.8	1350	-5.6
12.4	1400	-6.0
12.8	1450	-5.6
12.8	1500	-5.6
12.8	1550	-5.6
12.6	1600	-5.8

13.1	1650	-5.3
13.3	1700	-5.1
13.4	1750	-5.0
13.4	1800	-5.0
13.4	1850	-5.0
13.3	1900	-5.1
13.3	1950	-5.1
13.1	2000	-5.3
13.0	2050	-5.4
13.0	2100	-5.4
12.9	2150	-5.5
12.9	2200	-5.5
12.9	2250	-5.5
13.0	2300	-5.4
13.0	2350	-5.4
13.1	2400	-5.3
13.1	2450	-5.3
13.3	2500	-5.1
13.1	2550	-5.3
13.0	2600	-5.4
12.9	2650	-5.5
12.7	2700	-5.7
12.6	2750	-5.8
12.8	2800	-5.6
12.6	2850	-5.8
12.6	2900	-5.8
12.8	2950	-5.6
12.8	3000	-5.6
12.8	3050	-5.6
13.0	3100	-5.4
13.2	3150	-5.2
13.2	3200	-5.2
13.5	3250	-4.9
13.5	3300	-4.9
13.5	3350	-4.9
13.1	3400	-5.3
13.0	3450	-5.4
13.5	3500	-4.9
13.6	3550	-4.8
13.6	3600	-4.8
12.7	3650	-5.7
13.6	3700	-4.8
13.8	3750	-4.6
13.8	3800	-4.6
13.4	3850	-5.0
13.7	3900	-4.7
13.8	3950	-4.6
14.1	4000	-4.3
14.1	4050	-4.3
14.2	4100	-4.2
14.0	4150	-4.4
14.1	4200	-4.3

14.3	4250	-4.1
14.2	4300	-4.2
14.4	4350	-4.0
14.2	4400	-4.2
14.3	4450	-4.1
14.5	4500	-3.9
14.7	4550	-3.7
14.7	4600	-3.7
14.8	4650	-3.6
14.7	4700	-3.7
14.7	4750	-3.7
14.6	4800	-3.8
14.4	4850	-4.0
14.4	4900	-4.0
14.4	4950	-4.0
14.6	5000	-3.8
14.8	5050	-3.6
14.8	5100	-3.6
15.0	5150	-3.4
15.1	5200	-3.3
15.4	5250	-3.0
15.4	5300	-3.0
15.7	5350	-2.7
15.5	5400	-2.9
15.8	5450	-2.6
15.9	5500	-2.5
15.9	5550	-2.5
16.0	5600	-2.4
16.0	5650	-2.4
16.0	5700	-2.4
16.2	5750	-2.2
16.2	5800	-2.2
16.3	5850	-2.1
16.7	5900	-1.7
16.7	5950	-1.7
16.8	6000	-1.6
16.9	6050	-1.5
17.2	6100	-1.2
17.2	6150	-1.2
17.2	6200	-1.2
17.2	6250	-1.2
17.4	6300	-1.0
17.4	6350	-1.0
17.4	6400	-1.0
17.4	6450	-1.0
17.5	6500	-0.9
17.5	6550	-0.9
17.6	6600	-0.8
17.7	6650	-0.7
17.9	6700	-0.5
18.0	6750	-0.4
18.0	6800	-0.4

18.0	6850	-0.4
17.9	6900	-0.5
18.1	6950	-0.3
18.3	7000	-0.1
18.7	7050	0.3
19.3	7100	0.9
20.1	7150	1.7
20.7	7200	2.3
21.1	7250	2.7
21.2	7300	2.8
21.6	7350	3.2
21.9	7400	3.5
22.3	7450	3.9
22.4	7500	4.0
22.6	7550	4.2
23.1	7600	4.7
23.3	7650	4.9
23.5	7700	5.1
23.8	7750	5.4
23.8	7800	5.4
23.9	7850	5.5
23.9	7900	5.5
24.0	7950	5.6
24.5	8000	6.1
25.2	8050	6.8
25.3	8100	6.9
25.3	8150	6.9
25.4	8200	7.0
25.7	8250	7.3
25.9	8300	7.5
25.9	8350	7.5
25.9	8400	7.5
26.0	8450	7.6
25.8	8500	7.4
<b>12.8</b>	<b>Processing Gain (dB) @ 80th Percentile =</b>	

### Processing Gain Channel 1 (fc=2412Mhz) @ 11Mbps



**Processing Gain**

ISL37400M

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2428.50	22.1	13.4	6.7	2.0	-55.4	<=8.0
2428.55	21.5	13.4	6.1	2.0	-56.0	<=8.0
2428.60	20.9	13.4	5.5	2.0	-56.6	<=8.0
2428.65	20.8	13.4	5.4	2.0	-56.7	<=8.0
2428.70	20.8	13.4	5.4	2.0	-56.7	<=8.0
2428.75	20.8	13.4	5.4	2.0	-56.7	<=8.0
2428.80	20.9	13.4	5.5	2.0	-56.6	<=8.0
2428.85	21.2	13.4	5.8	2.0	-56.3	<=8.0
2428.90	21.2	13.4	5.8	2.0	-56.3	<=8.0
2428.95	21.0	13.4	5.6	2.0	-56.5	<=8.0
2429.00	21.0	13.4	5.6	2.0	-56.5	<=8.0
2429.05	21.2	13.4	5.8	2.0	-56.3	<=8.0
2429.10	21.2	13.4	5.8	2.0	-56.3	<=8.0
2429.15	21.3	13.4	5.9	2.0	-56.2	<=8.0
2429.20	21.4	13.4	6.0	2.0	-56.1	<=8.0
2429.25	21.7	13.4	6.3	2.0	-55.8	<=8.0
2429.30	21.9	13.4	6.5	2.0	-55.6	<=8.0
2429.35	21.9	13.4	6.5	2.0	-55.6	<=8.0
2429.40	22.0	13.4	6.6	2.0	-55.5	<=8.0
2429.45	21.6	13.4	6.2	2.0	-55.9	<=8.0
2429.50	20.8	13.4	5.4	2.0	-56.7	<=8.0
2429.55	20.2	13.4	4.8	2.0	-57.3	<=8.0
2429.60	19.7	13.4	4.3	2.0	-57.8	<=8.0
2429.65	19.6	13.4	4.2	2.0	-57.9	<=8.0
2429.70	19.6	13.4	4.2	2.0	-57.9	<=8.0
2429.75	19.5	13.4	4.1	2.0	-58.0	<=8.0
2429.80	20.1	13.4	4.7	2.0	-57.4	<=8.0
2429.85	20.1	13.4	4.7	2.0	-57.4	<=8.0
2429.90	20.1	13.4	4.7	2.0	-57.4	<=8.0
2429.95	19.9	13.4	4.5	2.0	-57.6	<=8.0
2430.00	20.1	13.4	4.7	2.0	-57.4	<=8.0
2430.05	20.2	13.4	4.8	2.0	-57.3	<=8.0
2430.10	20.1	13.4	4.7	2.0	-57.4	<=8.0
2430.15	20.3	13.4	4.9	2.0	-57.2	<=8.0
2430.20	20.5	13.4	5.1	2.0	-57.0	<=8.0
2430.25	20.7	13.4	5.3	2.0	-56.8	<=8.0
2430.30	20.3	13.4	4.9	2.0	-57.2	<=8.0
2430.35	20.3	13.4	4.9	2.0	-57.2	<=8.0
2430.40	20.3	13.4	4.9	2.0	-57.2	<=8.0
2430.45	20.3	13.4	4.9	2.0	-57.2	<=8.0
2430.50	20.2	13.4	4.8	2.0	-57.3	<=8.0
2430.55	19.8	13.4	4.4	2.0	-57.7	<=8.0
2430.60	19.0	13.4	3.6	2.0	-58.5	<=8.0
2430.65	18.8	13.4	3.4	2.0	-58.7	<=8.0
2430.70	18.7	13.4	3.3	2.0	-58.8	<=8.0
2430.75	18.9	13.4	3.5	2.0	-58.6	<=8.0
2430.80	19.0	13.4	3.6	2.0	-58.5	<=8.0
2430.85	18.8	13.4	3.4	2.0	-58.7	<=8.0

**Processing Gain**

ISL37400M

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2430.90	18.6	13.4	3.2	2.0	-58.9	<=8.0
2430.95	17.2	13.4	1.8	2.0	-60.3	<=8.0
2431.00	18.2	13.4	2.8	2.0	-59.3	<=8.0
2431.05	18.3	13.4	2.9	2.0	-59.2	<=8.0
2431.10	17.5	13.4	2.1	2.0	-60.0	<=8.0
2431.15	17.4	13.4	2.0	2.0	-60.1	<=8.0
2431.20	17.3	13.4	1.9	2.0	-60.2	<=8.0
2431.25	17.9	13.4	2.5	2.0	-59.6	<=8.0
2431.30	17.8	13.4	2.4	2.0	-59.7	<=8.0
2431.35	17.8	13.4	2.4	2.0	-59.7	<=8.0
2431.40	18.0	13.4	2.6	2.0	-59.5	<=8.0
2431.45	18.0	13.4	2.6	2.0	-59.5	<=8.0
2431.50	18.2	13.4	2.8	2.0	-59.3	<=8.0
2431.55	18.3	13.4	2.9	2.0	-59.2	<=8.0
2431.60	18.3	13.4	2.9	2.0	-59.2	<=8.0
2431.65	18.2	13.4	2.8	2.0	-59.3	<=8.0
2431.70	18.0	13.4	2.6	2.0	-59.5	<=8.0
2431.75	17.7	13.4	2.3	2.0	-59.8	<=8.0
2431.80	17.3	13.4	1.9	2.0	-60.2	<=8.0
2431.85	17.0	13.4	1.6	2.0	-60.5	<=8.0
2431.90	16.9	13.4	1.5	2.0	-60.6	<=8.0
2431.95	16.6	13.4	1.2	2.0	-60.9	<=8.0
2432.00	16.5	13.4	1.1	2.0	-61.0	<=8.0
2432.05	16.5	13.4	1.1	2.0	-61.0	<=8.0
2432.10	16.1	13.4	0.7	2.0	-61.4	<=8.0
2432.15	15.4	13.4	0.0	2.0	-62.1	<=8.0
2432.20	16.4	13.4	1.0	2.0	-61.1	<=8.0
2432.25	16.6	13.4	1.2	2.0	-60.9	<=8.0
2432.30	16.5	13.4	1.1	2.0	-61.0	<=8.0
2432.35	16.3	13.4	0.9	2.0	-61.2	<=8.0
2432.40	16.6	13.4	1.2	2.0	-60.9	<=8.0
2432.45	16.8	13.4	1.4	2.0	-60.7	<=8.0
2432.50	17.0	13.4	1.6	2.0	-60.5	<=8.0
2432.55	17.0	13.4	1.6	2.0	-60.5	<=8.0
2432.60	17.0	13.4	1.6	2.0	-60.5	<=8.0
2432.65	16.8	13.4	1.4	2.0	-60.7	<=8.0
2432.70	16.4	13.4	1.0	2.0	-61.1	<=8.0
2432.75	16.2	13.4	0.8	2.0	-61.3	<=8.0
2432.80	15.8	13.4	0.4	2.0	-61.7	<=8.0
2432.85	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2432.90	14.8	13.4	-0.6	2.0	-62.7	<=8.0
2432.95	14.3	13.4	-1.1	2.0	-63.2	<=8.0
2433.00	14.6	13.4	-0.8	2.0	-62.9	<=8.0
2433.05	14.6	13.4	-0.8	2.0	-62.9	<=8.0
2433.10	13.9	13.4	-1.5	2.0	-63.6	<=8.0
2433.15	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2433.20	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2433.25	14.8	13.4	-0.6	2.0	-62.7	<=8.0

**Processing Gain**

ISL37400M

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2433.30	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2433.35	14.4	13.4	-1.0	2.0	-63.1	<=8.0
2433.40	14.6	13.4	-0.8	2.0	-62.9	<=8.0
2433.45	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2433.50	15.4	13.4	0.0	2.0	-62.1	<=8.0
2433.55	15.4	13.4	0.0	2.0	-62.1	<=8.0
2433.60	15.4	13.4	0.0	2.0	-62.1	<=8.0
2433.65	15.1	13.4	-0.3	2.0	-62.4	<=8.0
2433.70	15.0	13.4	-0.4	2.0	-62.5	<=8.0
2433.75	14.7	13.4	-0.7	2.0	-62.8	<=8.0
2433.80	14.5	13.4	-0.9	2.0	-63.0	<=8.0
2433.85	14.2	13.4	-1.2	2.0	-63.3	<=8.0
2433.90	14.2	13.4	-1.2	2.0	-63.3	<=8.0
2433.95	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2434.00	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2434.05	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2434.10	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2434.15	12.3	13.4	-3.1	2.0	-65.2	<=8.0
2434.20	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2434.25	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2434.30	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2434.35	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2434.40	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2434.45	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2434.50	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2434.55	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2434.60	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2434.65	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2434.70	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2434.75	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2434.80	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2434.85	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2434.90	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2434.95	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2435.00	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2435.05	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2435.10	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2435.15	12.9	13.4	-2.5	2.0	-64.6	<=8.0
2435.20	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2435.25	14.5	13.4	-0.9	2.0	-63.0	<=8.0
2435.30	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2435.35	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2435.40	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2435.45	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2435.50	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2435.55	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2435.60	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2435.65	13.2	13.4	-2.2	2.0	-64.3	<=8.0

**Processing Gain**

ISL37400M

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2435.70	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2435.75	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2435.80	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2435.85	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2435.90	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2435.95	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2436.00	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2436.05	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2436.10	12.6	13.4	-2.8	2.0	-64.9	<=8.0
2436.15	12.6	13.4	-2.8	2.0	-64.9	<=8.0
2436.20	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2436.25	14.2	13.4	-1.2	2.0	-63.3	<=8.0
2436.30	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2436.35	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2436.40	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2436.45	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2436.50	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2436.55	12.9	13.4	-2.5	2.0	-64.6	<=8.0
2436.60	12.9	13.4	-2.5	2.0	-64.6	<=8.0
2436.65	12.8	13.4	-2.6	2.0	-64.7	<=8.0
2436.70	12.9	13.4	-2.5	2.0	-64.6	<=8.0
2436.75	12.9	13.4	-2.5	2.0	-64.6	<=8.0
2436.80	13.0	13.4	-2.4	2.0	-64.5	<=8.0
2436.85	12.9	13.4	-2.5	2.0	-64.6	<=8.0
2436.90	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2436.95	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2437.00	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2437.05	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2437.10	14.2	13.4	-1.2	2.0	-63.3	<=8.0
2437.15	14.2	13.4	-1.2	2.0	-63.3	<=8.0
2437.20	14.1	13.4	-1.3	2.0	-63.4	<=8.0
2437.25	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2437.30	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2437.35	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2437.40	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2437.45	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2437.50	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2437.55	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2437.60	13.0	13.4	-2.4	2.0	-64.5	<=8.0
2437.65	13.0	13.4	-2.4	2.0	-64.5	<=8.0
2437.70	13.0	13.4	-2.4	2.0	-64.5	<=8.0
2437.75	13.0	13.4	-2.4	2.0	-64.5	<=8.0
2437.80	13.0	13.4	-2.4	2.0	-64.5	<=8.0
2437.85	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2437.90	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2437.95	12.1	13.4	-3.3	2.0	-65.4	<=8.0
2438.00	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2438.05	14.2	13.4	-1.2	2.0	-63.3	<=8.0

**Processing Gain**

ISL37400M

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2438.10	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2438.15	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2438.20	12.3	13.4	-3.1	2.0	-65.2	<=8.0
2438.25	13.9	13.4	-1.5	2.0	-63.6	<=8.0
2438.30	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2438.35	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2438.40	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2438.45	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2438.50	13.5	13.4	-1.9	2.0	-64.0	<=8.0
2438.55	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2438.60	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2438.65	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2438.70	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2438.75	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2438.80	13.8	13.4	-1.6	2.0	-63.7	<=8.0
2438.85	14.1	13.4	-1.3	2.0	-63.4	<=8.0
2438.90	14.3	13.4	-1.1	2.0	-63.2	<=8.0
2438.95	14.2	13.4	-1.2	2.0	-63.3	<=8.0
2439.00	14.0	13.4	-1.4	2.0	-63.5	<=8.0
2439.05	14.5	13.4	-0.9	2.0	-63.0	<=8.0
2439.10	13.1	13.4	-2.3	2.0	-64.4	<=8.0
2439.15	13.0	13.4	-2.4	2.0	-64.5	<=8.0
2439.20	13.6	13.4	-1.8	2.0	-63.9	<=8.0
2439.25	14.1	13.4	-1.3	2.0	-63.4	<=8.0
2439.30	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2439.35	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2439.40	13.9	13.4	-1.5	2.0	-63.6	<=8.0
2439.45	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2439.50	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2439.55	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2439.60	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2439.65	13.4	13.4	-2.0	2.0	-64.1	<=8.0
2439.70	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2439.75	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2439.80	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2439.85	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2439.90	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2439.95	12.1	13.4	-3.3	2.0	-65.4	<=8.0
2440.00	12.6	13.4	-2.8	2.0	-64.9	<=8.0
2440.05	12.6	13.4	-2.8	2.0	-64.9	<=8.0
2440.10	13.2	13.4	-2.2	2.0	-64.3	<=8.0
2440.15	12.2	13.4	-3.2	2.0	-65.3	<=8.0
2440.20	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2440.25	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2440.30	13.3	13.4	-2.1	2.0	-64.2	<=8.0
2440.35	14.1	13.4	-1.3	2.0	-63.4	<=8.0
2440.40	14.7	13.4	-0.7	2.0	-62.8	<=8.0
2440.45	14.7	13.4	-0.7	2.0	-62.8	<=8.0

**Processing Gain**

ISL37400M

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2440.50	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.55	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.60	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.65	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.70	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.75	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.80	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.85	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.90	15.2	13.4	-0.2	2.0	-62.3	<=8.0
2440.95	15.1	13.4	-0.3	2.0	-62.4	<=8.0
2441.00	14.9	13.4	-0.5	2.0	-62.6	<=8.0
2441.05	14.9	13.4	-0.5	2.0	-62.6	<=8.0
2441.10	13.7	13.4	-1.7	2.0	-63.8	<=8.0
2441.15	14.7	13.4	-0.7	2.0	-62.8	<=8.0
2441.20	14.7	13.4	-0.7	2.0	-62.8	<=8.0
2441.25	15.1	13.4	-0.3	2.0	-62.4	<=8.0
2441.30	15.0	13.4	-0.4	2.0	-62.5	<=8.0
2441.35	15.0	13.4	-0.4	2.0	-62.5	<=8.0
2441.40	14.9	13.4	-0.5	2.0	-62.6	<=8.0
2441.45	14.9	13.4	-0.5	2.0	-62.6	<=8.0
2441.50	14.9	13.4	-0.5	2.0	-62.6	<=8.0
2441.55	14.9	13.4	-0.5	2.0	-62.6	<=8.0
2441.60	14.9	13.4	-0.5	2.0	-62.6	<=8.0
2441.65	15.0	13.4	-0.4	2.0	-62.5	<=8.0
2441.70	15.0	13.4	-0.4	2.0	-62.5	<=8.0
2441.75	15.0	13.4	-0.4	2.0	-62.5	<=8.0
2441.80	15.8	13.4	0.4	2.0	-61.7	<=8.0
2441.85	15.7	13.4	0.3	2.0	-61.8	<=8.0
2441.90	15.7	13.4	0.3	2.0	-61.8	<=8.0
2441.95	15.3	13.4	-0.1	2.0	-62.2	<=8.0
2442.00	15.3	13.4	-0.1	2.0	-62.2	<=8.0
2442.05	15.3	13.4	-0.1	2.0	-62.2	<=8.0
2442.10	15.3	13.4	-0.1	2.0	-62.2	<=8.0
2442.15	15.3	13.4	-0.1	2.0	-62.2	<=8.0
2442.20	15.7	13.4	0.3	2.0	-61.8	<=8.0
2442.25	16.4	13.4	1.0	2.0	-61.1	<=8.0
2442.30	16.5	13.4	1.1	2.0	-61.0	<=8.0
2442.35	16.5	13.4	1.1	2.0	-61.0	<=8.0
2442.40	17.3	13.4	1.9	2.0	-60.2	<=8.0
2442.45	17.2	13.4	1.8	2.0	-60.3	<=8.0
2442.50	17.2	13.4	1.8	2.0	-60.3	<=8.0
2442.55	18.3	13.4	2.9	2.0	-59.2	<=8.0
2442.60	18.5	13.4	3.1	2.0	-59.0	<=8.0
2442.65	18.5	13.4	3.1	2.0	-59.0	<=8.0
2442.70	18.6	13.4	3.2	2.0	-58.9	<=8.0
2442.75	18.6	13.4	3.2	2.0	-58.9	<=8.0
2442.80	18.5	13.4	3.1	2.0	-59.0	<=8.0
2442.85	18.3	13.4	2.9	2.0	-59.2	<=8.0

**Processing Gain**

ISL37400M

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2442.90	18.3	13.4	2.9	2.0	-59.2	<=8.0
2442.95	18.0	13.4	2.6	2.0	-59.5	<=8.0
2443.00	18.0	13.4	2.6	2.0	-59.5	<=8.0
2443.05	18.0	13.4	2.6	2.0	-59.5	<=8.0
2443.10	17.9	13.4	2.5	2.0	-59.6	<=8.0
2443.15	17.7	13.4	2.3	2.0	-59.8	<=8.0
2443.20	18.0	13.4	2.6	2.0	-59.5	<=8.0
2443.25	18.0	13.4	2.6	2.0	-59.5	<=8.0
2443.30	18.0	13.4	2.6	2.0	-59.5	<=8.0
2443.35	17.9	13.4	2.5	2.0	-59.6	<=8.0
2443.40	18.2	13.4	2.8	2.0	-59.3	<=8.0
2443.45	18.1	13.4	2.7	2.0	-59.4	<=8.0
2443.50	18.1	13.4	2.7	2.0	-59.4	<=8.0
2443.55	18.1	13.4	2.7	2.0	-59.4	<=8.0
2443.60	18.1	13.4	2.7	2.0	-59.4	<=8.0
2443.65	18.2	13.4	2.8	2.0	-59.3	<=8.0
2443.70	18.2	13.4	2.8	2.0	-59.3	<=8.0
2443.75	18.2	13.4	2.8	2.0	-59.3	<=8.0
2443.80	18.1	13.4	2.7	2.0	-59.4	<=8.0
2443.85	18.2	13.4	2.8	2.0	-59.3	<=8.0
2443.90	18.2	13.4	2.8	2.0	-59.3	<=8.0
2443.95	18.4	13.4	3.0	2.0	-59.1	<=8.0
2444.00	18.5	13.4	3.1	2.0	-59.0	<=8.0
2444.05	18.5	13.4	3.1	2.0	-59.0	<=8.0
2444.10	18.7	13.4	3.3	2.0	-58.8	<=8.0
2444.15	18.8	13.4	3.4	2.0	-58.7	<=8.0
2444.20	18.9	13.4	3.5	2.0	-58.6	<=8.0
2444.25	19.1	13.4	3.7	2.0	-58.4	<=8.0
2444.30	19.4	13.4	4.0	2.0	-58.1	<=8.0
2444.35	19.6	13.4	4.2	2.0	-57.9	<=8.0
2444.40	20.3	13.4	4.9	2.0	-57.2	<=8.0
2444.45	20.6	13.4	5.2	2.0	-56.9	<=8.0
2444.50	20.6	13.4	5.2	2.0	-56.9	<=8.0
2444.55	20.5	13.4	5.1	2.0	-57.0	<=8.0
2444.60	20.5	13.4	5.1	2.0	-57.0	<=8.0
2444.65	20.6	13.4	5.2	2.0	-56.9	<=8.0
2444.70	20.9	13.4	5.5	2.0	-56.6	<=8.0
2444.75	20.8	13.4	5.4	2.0	-56.7	<=8.0
2444.80	20.8	13.4	5.4	2.0	-56.7	<=8.0
2444.85	20.8	13.4	5.4	2.0	-56.7	<=8.0
2444.90	20.9	13.4	5.5	2.0	-56.6	<=8.0
2444.95	21.1	13.4	5.7	2.0	-56.4	<=8.0
2445.00	21.1	13.4	5.7	2.0	-56.4	<=8.0
2445.05	21.1	13.4	5.7	2.0	-56.4	<=8.0
2445.10	22.2	13.4	6.8	2.0	-55.3	<=8.0
2445.15	22.3	13.4	6.9	2.0	-55.2	<=8.0
2445.20	22.2	13.4	6.8	2.0	-55.3	<=8.0
2445.25	22.2	13.4	6.8	2.0	-55.3	<=8.0

5.5Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2445.30	23.1	13.4	7.7	2.0	-54.4	<=8.0
2445.35	23.4	13.4	8.0	2.0	-54.1	<=8.0
2445.40	23.4	13.4	8.0	2.0	-54.1	<=8.0
2445.45	23.2	13.4	7.8	2.0	-54.3	<=8.0
2445.50	23.2	13.4	7.8	2.0	-54.3	<=8.0

**13.4**

Test Conditions

TX Card **HWB3163-04 Rev B**  
 S/N **99360038**  
 RX Card **ISL37400M Rev A**  
 S/N **00500038**  
 TX Firmware **P10002C0, MS11168A3**  
 RX Firmware **ID010000, PK010001, SF010000**  
 Software Ver. **3.0.24**  
 Mode **5.5 MB Pseudo IBSS**  
 Pkt Size **1024**  
 Pkt Dly **1**  
 Pkt Burst **6**

Intersil Chips on Card: **ISL3984**  
**ISL3685**  
**HFA3783**  
**ISL3183**  
**ISL3874**

Processing Gain (dB)	XMIT level	-62.1
	<b>S/N+Ls</b>	<b>15.4</b>
	<b>0dB J/S</b>	<b>0.0</b>
PG	Offset	Signal Generator Delta
22.1	-8500	6.7
21.5	-8450	6.1
20.9	-8400	5.5
20.8	-8350	5.4
20.8	-8300	5.4
20.8	-8250	5.4
20.9	-8200	5.5
21.2	-8150	5.8
21.2	-8100	5.8
21.0	-8050	5.6
21.0	-8000	5.6
21.2	-7950	5.8
21.2	-7900	5.8
21.3	-7850	5.9
21.4	-7800	6.0
21.7	-7750	6.3
21.9	-7700	6.5
21.9	-7650	6.5
22.0	-7600	6.6
21.6	-7550	6.2
20.8	-7500	5.4
20.2	-7450	4.8
19.7	-7400	4.3
19.6	-7350	4.2
19.6	-7300	4.2
19.5	-7250	4.1
20.1	-7200	4.7
20.1	-7150	4.7
20.1	-7100	4.7
19.9	-7050	4.5
20.1	-7000	4.7
20.2	-6950	4.8
20.1	-6900	4.7
20.3	-6850	4.9
20.5	-6800	5.1
20.7	-6750	5.3
20.3	-6700	4.9
20.3	-6650	4.9
20.3	-6600	4.9
20.3	-6550	4.9
20.2	-6500	4.8
19.8	-6450	4.4
19.0	-6400	3.6
18.8	-6350	3.4
18.7	-6300	3.3
18.9	-6250	3.5
19.0	-6200	3.6

18.8	-6150	3.4	
18.6	-6100	3.2	
17.2	-6050	1.8	
18.2	-6000	2.8	
18.3	-5950	2.9	
17.5	-5900	2.1	
17.4	-5850	2.0	
17.3	-5800	1.9	
17.9	-5750	2.5	
17.8	-5700	2.4	
17.8	-5650	2.4	
18.0	-5600	2.6	
18.0	-5550	2.6	
18.2	-5500	2.8	
18.3	-5450	2.9	
18.3	-5400	2.9	
18.2	-5350	2.8	
18.0	-5300	2.6	
17.7	-5250	2.3	
17.3	-5200	1.9	
17.0	-5150	1.6	
16.9	-5100	1.5	
16.6	-5050	1.2	
16.5	-5000	1.1	
16.5	-4950	1.1	
16.1	-4900	0.7	
15.4	-4850	0.0	
16.4	-4800	1.0	
16.6	-4750	1.2	
16.5	-4700	1.1	
16.3	-4650	0.9	
16.6	-4600	1.2	
16.8	-4550	1.4	
17.0	-4500	1.6	
17.0	-4450	1.6	
17.0	-4400	1.6	
16.8	-4350	1.4	
16.4	-4300	1.0	
16.2	-4250	0.8	
15.8	-4200	0.4	
15.2	-4150	-0.2	
14.8	-4100	-0.6	
14.3	-4050	-1.1	
14.6	-4000	-0.8	
14.6	-3950	-0.8	
13.9	-3900	-1.5	
13.7	-3850	-1.7	
13.7	-3800	-1.7	
14.8	-3750	-0.6	
14.0	-3700	-1.4	
14.4	-3650	-1.0	
14.6	-3600	-0.8	

15.2	-3550	-0.2	
15.4	-3500	0.0	
15.4	-3450	0.0	
15.4	-3400	0.0	
15.1	-3350	-0.3	
15.0	-3300	-0.4	
14.7	-3250	-0.7	
14.5	-3200	-0.9	
14.2	-3150	-1.2	
14.2	-3100	-1.2	
14.0	-3050	-1.4	
14.0	-3000	-1.4	
14.0	-2950	-1.4	
13.7	-2900	-1.7	
12.3	-2850	-3.1	
13.5	-2800	-1.9	
13.5	-2750	-1.9	
13.5	-2700	-1.9	
13.5	-2650	-1.9	
13.4	-2600	-2.0	
13.4	-2550	-2.0	
13.3	-2500	-2.1	
13.2	-2450	-2.2	
13.2	-2400	-2.2	
13.2	-2350	-2.2	
13.2	-2300	-2.2	
13.2	-2250	-2.2	
13.4	-2200	-2.0	
13.4	-2150	-2.0	
13.6	-2100	-1.8	
13.6	-2050	-1.8	
13.8	-2000	-1.6	
14.0	-1950	-1.4	
13.4	-1900	-2.0	
12.9	-1850	-2.5	
14.0	-1800	-1.4	
14.5	-1750	-0.9	
13.5	-1700	-1.9	
13.5	-1650	-1.9	
13.8	-1600	-1.6	
13.7	-1550	-1.7	
13.7	-1500	-1.7	
13.5	-1450	-1.9	
13.3	-1400	-2.1	
13.2	-1350	-2.2	
13.1	-1300	-2.3	
13.1	-1250	-2.3	
13.1	-1200	-2.3	
13.1	-1150	-2.3	
13.1	-1100	-2.3	
13.3	-1050	-2.1	
13.1	-1000	-2.3	


13.8	-950	-1.6	
12.6	-900	-2.8	
12.6	-850	-2.8	
14.0	-800	-1.4	
14.2	-750	-1.2	
14.0	-700	-1.4	
13.8	-650	-1.6	
13.6	-600	-1.8	
13.4	-550	-2.0	
13.2	-500	-2.2	
12.9	-450	-2.5	
12.9	-400	-2.5	
12.8	-350	-2.6	
12.9	-300	-2.5	
12.9	-250	-2.5	
13.0	-200	-2.4	
12.9	-150	-2.5	
13.1	-100	-2.3	
13.4	-50	-2.0	
13.6	0	-1.8	
13.8	50	-1.6	
14.2	100	-1.2	
14.2	150	-1.2	
14.1	200	-1.3	
13.6	250	-1.8	
13.6	300	-1.8	
13.5	350	-1.9	
13.4	400	-2.0	
13.2	450	-2.2	
13.1	500	-2.3	
13.1	550	-2.3	
13.0	600	-2.4	
13.0	650	-2.4	
13.0	700	-2.4	
13.0	750	-2.4	
13.0	800	-2.4	
13.2	850	-2.2	
13.3	900	-2.1	
12.1	950	-3.3	
14.0	1000	-1.4	
14.2	1050	-1.2	
13.8	1100	-1.6	
13.8	1150	-1.6	
12.3	1200	-3.1	
13.9	1250	-1.5	
13.6	1300	-1.8	
13.7	1350	-1.7	
13.7	1400	-1.7	
13.5	1450	-1.9	
13.5	1500	-1.9	
13.3	1550	-2.1	
13.3	1600	-2.1	

13.4	1650	-2.0	
13.6	1700	-1.8	
13.8	1750	-1.6	
13.8	1800	-1.6	
14.1	1850	-1.3	
14.3	1900	-1.1	
14.2	1950	-1.2	
14.0	2000	-1.4	
14.5	2050	-0.9	
13.1	2100	-2.3	
13.0	2150	-2.4	
13.6	2200	-1.8	
14.1	2250	-1.3	
13.3	2300	-2.1	
13.3	2350	-2.1	
13.9	2400	-1.5	
13.7	2450	-1.7	
13.4	2500	-2.0	
13.4	2550	-2.0	
13.4	2600	-2.0	
13.4	2650	-2.0	
13.2	2700	-2.2	
13.2	2750	-2.2	
13.2	2800	-2.2	
13.2	2850	-2.2	
13.2	2900	-2.2	
12.1	2950	-3.3	
12.6	3000	-2.8	
12.6	3050	-2.8	
13.2	3100	-2.2	
12.2	3150	-3.2	
13.3	3200	-2.1	
13.3	3250	-2.1	
13.3	3300	-2.1	
14.1	3350	-1.3	
14.7	3400	-0.7	
14.7	3450	-0.7	
15.2	3500	-0.2	
15.2	3550	-0.2	
15.2	3600	-0.2	
15.2	3650	-0.2	
15.2	3700	-0.2	
15.2	3750	-0.2	
15.2	3800	-0.2	
15.2	3850	-0.2	
15.2	3900	-0.2	
15.1	3950	-0.3	
14.9	4000	-0.5	
14.9	4050	-0.5	
13.7	4100	-1.7	
14.7	4150	-0.7	
14.7	4200	-0.7	

15.1	4250	-0.3	
15.0	4300	-0.4	
15.0	4350	-0.4	
14.9	4400	-0.5	
14.9	4450	-0.5	
14.9	4500	-0.5	
14.9	4550	-0.5	
14.9	4600	-0.5	
15.0	4650	-0.4	
15.0	4700	-0.4	
15.0	4750	-0.4	
15.8	4800	0.4	
15.7	4850	0.3	
15.7	4900	0.3	
15.3	4950	-0.1	
15.3	5000	-0.1	
15.3	5050	-0.1	
15.3	5100	-0.1	
15.3	5150	-0.1	
15.7	5200	0.3	
16.4	5250	1.0	
16.5	5300	1.1	
16.5	5350	1.1	
17.3	5400	1.9	
17.2	5450	1.8	
17.2	5500	1.8	
18.3	5550	2.9	
18.5	5600	3.1	
18.5	5650	3.1	
18.6	5700	3.2	
18.6	5750	3.2	
18.5	5800	3.1	
18.3	5850	2.9	
18.3	5900	2.9	
18.0	5950	2.6	
18.0	6000	2.6	
18.0	6050	2.6	
17.9	6100	2.5	
17.7	6150	2.3	
18.0	6200	2.6	
18.0	6250	2.6	
18.0	6300	2.6	
17.9	6350	2.5	
18.2	6400	2.8	
18.1	6450	2.7	
18.1	6500	2.7	
18.1	6550	2.7	
18.1	6600	2.7	
18.2	6650	2.8	
18.2	6700	2.8	
18.2	6750	2.8	
18.1	6800	2.7	



**Processing Gain  
Channel 6 (fc=2437MHz) @ 5.5Mbps**



**Processing Gain**

ISL37400M

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2428.50	21.7	13.3	6.4	2.0	-55.8	<=8.0
2428.55	21.0	13.3	5.7	2.0	-56.5	<=8.0
2428.60	20.6	13.3	5.3	2.0	-56.9	<=8.0
2428.65	20.0	13.3	4.7	2.0	-57.5	<=8.0
2428.70	19.9	13.3	4.6	2.0	-57.6	<=8.0
2428.75	19.7	13.3	4.4	2.0	-57.8	<=8.0
2428.80	19.5	13.3	4.2	2.0	-58.0	<=8.0
2428.85	19.5	13.3	4.2	2.0	-58.0	<=8.0
2428.90	19.5	13.3	4.2	2.0	-58.0	<=8.0
2428.95	19.5	13.3	4.2	2.0	-58.0	<=8.0
2429.00	19.4	13.3	4.1	2.0	-58.1	<=8.0
2429.05	19.4	13.3	4.1	2.0	-58.1	<=8.0
2429.10	19.3	13.3	4.0	2.0	-58.2	<=8.0
2429.15	20.0	13.3	4.7	2.0	-57.5	<=8.0
2429.20	20.2	13.3	4.9	2.0	-57.3	<=8.0
2429.25	20.2	13.3	4.9	2.0	-57.3	<=8.0
2429.30	20.3	13.3	5.0	2.0	-57.2	<=8.0
2429.35	20.3	13.3	5.0	2.0	-57.2	<=8.0
2429.40	20.3	13.3	5.0	2.0	-57.2	<=8.0
2429.45	20.2	13.3	4.9	2.0	-57.3	<=8.0
2429.50	20.1	13.3	4.8	2.0	-57.4	<=8.0
2429.55	19.4	13.3	4.1	2.0	-58.1	<=8.0
2429.60	19.0	13.3	3.7	2.0	-58.5	<=8.0
2429.65	18.8	13.3	3.5	2.0	-58.7	<=8.0
2429.70	18.8	13.3	3.5	2.0	-58.7	<=8.0
2429.75	18.6	13.3	3.3	2.0	-58.9	<=8.0
2429.80	18.4	13.3	3.1	2.0	-59.1	<=8.0
2429.85	18.4	13.3	3.1	2.0	-59.1	<=8.0
2429.90	18.2	13.3	2.9	2.0	-59.3	<=8.0
2429.95	18.3	13.3	3.0	2.0	-59.2	<=8.0
2430.00	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.05	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.10	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.15	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.20	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.25	18.5	13.3	3.2	2.0	-59.0	<=8.0
2430.30	18.5	13.3	3.2	2.0	-59.0	<=8.0
2430.35	18.5	13.3	3.2	2.0	-59.0	<=8.0
2430.40	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.45	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.50	18.4	13.3	3.1	2.0	-59.1	<=8.0
2430.55	18.5	13.3	3.2	2.0	-59.0	<=8.0
2430.60	18.3	13.3	3.0	2.0	-59.2	<=8.0
2430.65	18.1	13.3	2.8	2.0	-59.4	<=8.0
2430.70	17.0	13.3	1.7	2.0	-60.5	<=8.0
2430.75	16.6	13.3	1.3	2.0	-60.9	<=8.0
2430.80	16.4	13.3	1.1	2.0	-61.1	<=8.0
2430.85	16.4	13.3	1.1	2.0	-61.1	<=8.0

**Processing Gain**

ISL37400M

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2430.90	15.1	13.3	-0.2	2.0	-62.4	<=8.0
2430.95	15.1	13.3	-0.2	2.0	-62.4	<=8.0
2431.00	15.2	13.3	-0.1	2.0	-62.3	<=8.0
2431.05	15.2	13.3	-0.1	2.0	-62.3	<=8.0
2431.10	15.2	13.3	-0.1	2.0	-62.3	<=8.0
2431.15	15.3	13.3	0.0	2.0	-62.2	<=8.0
2431.20	15.3	13.3	0.0	2.0	-62.2	<=8.0
2431.25	16.3	13.3	1.0	2.0	-61.2	<=8.0
2431.30	17.5	13.3	2.2	2.0	-60.0	<=8.0
2431.35	17.9	13.3	2.6	2.0	-59.6	<=8.0
2431.40	17.9	13.3	2.6	2.0	-59.6	<=8.0
2431.45	19.0	13.3	3.7	2.0	-58.5	<=8.0
2431.50	20.5	13.3	5.2	2.0	-57.0	<=8.0
2431.55	23.0	13.3	7.7	2.0	-54.5	<=8.0
2431.60	25.6	13.3	10.3	2.0	-51.9	<=8.0
2431.65	25.6	13.3	10.3	2.0	-51.9	<=8.0
2431.70	22.1	13.3	6.8	2.0	-55.4	<=8.0
2431.75	20.5	13.3	5.2	2.0	-57.0	<=8.0
2431.80	18.5	13.3	3.2	2.0	-59.0	<=8.0
2431.85	17.4	13.3	2.1	2.0	-60.1	<=8.0
2431.90	17.0	13.3	1.7	2.0	-60.5	<=8.0
2431.95	16.9	13.3	1.6	2.0	-60.6	<=8.0
2432.00	16.9	13.3	1.6	2.0	-60.6	<=8.0
2432.05	16.8	13.3	1.5	2.0	-60.7	<=8.0
2432.10	16.5	13.3	1.2	2.0	-61.0	<=8.0
2432.15	15.2	13.3	-0.1	2.0	-62.3	<=8.0
2432.20	15.1	13.3	-0.2	2.0	-62.4	<=8.0
2432.25	14.8	13.3	-0.5	2.0	-62.7	<=8.0
2432.30	14.8	13.3	-0.5	2.0	-62.7	<=8.0
2432.35	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2432.40	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2432.45	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2432.50	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2432.55	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2432.60	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2432.65	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2432.70	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2432.75	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2432.80	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2432.85	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2432.90	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2432.95	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2433.00	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2433.05	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2433.10	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2433.15	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2433.20	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2433.25	13.1	13.3	-2.2	2.0	-64.4	<=8.0

**Processing Gain**

ISL37400M

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2433.30	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2433.35	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2433.40	12.2	13.3	-3.1	2.0	-65.3	<=8.0
2433.45	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2433.50	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2433.55	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2433.60	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2433.65	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2433.70	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2433.75	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2433.80	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2433.85	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2433.90	12.4	13.3	-2.9	2.0	-65.1	<=8.0
2433.95	12.4	13.3	-2.9	2.0	-65.1	<=8.0
2434.00	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2434.05	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2434.10	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2434.15	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2434.20	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2434.25	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2434.30	12.7	13.3	-2.6	2.0	-64.8	<=8.0
2434.35	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2434.40	12.1	13.3	-3.2	2.0	-65.4	<=8.0
2434.45	12.1	13.3	-3.2	2.0	-65.4	<=8.0
2434.50	12.0	13.3	-3.3	2.0	-65.5	<=8.0
2434.55	12.2	13.3	-3.1	2.0	-65.3	<=8.0
2434.60	12.2	13.3	-3.1	2.0	-65.3	<=8.0
2434.65	12.2	13.3	-3.1	2.0	-65.3	<=8.0
2434.70	12.2	13.3	-3.1	2.0	-65.3	<=8.0
2434.75	12.2	13.3	-3.1	2.0	-65.3	<=8.0
2434.80	12.8	13.3	-2.5	2.0	-64.7	<=8.0
2434.85	12.8	13.3	-2.5	2.0	-64.7	<=8.0
2434.90	12.8	13.3	-2.5	2.0	-64.7	<=8.0
2434.95	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2435.00	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2435.05	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2435.10	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2435.15	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2435.20	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2435.25	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2435.30	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2435.35	11.6	13.3	-3.7	2.0	-65.9	<=8.0
2435.40	11.9	13.3	-3.4	2.0	-65.6	<=8.0
2435.45	12.0	13.3	-3.3	2.0	-65.5	<=8.0
2435.50	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2435.55	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2435.60	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2435.65	12.3	13.3	-3.0	2.0	-65.2	<=8.0

**Processing Gain**

ISL37400M

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2435.70	11.9	13.3	-3.4	2.0	-65.6	<=8.0
2435.75	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2435.80	12.8	13.3	-2.5	2.0	-64.7	<=8.0
2435.85	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2435.90	12.4	13.3	-2.9	2.0	-65.1	<=8.0
2435.95	13.3	13.3	-2.0	2.0	-64.2	<=8.0
2436.00	14.9	13.3	-0.4	2.0	-62.6	<=8.0
2436.05	14.9	13.3	-0.4	2.0	-62.6	<=8.0
2436.10	14.4	13.3	-0.9	2.0	-63.1	<=8.0
2436.15	14.2	13.3	-1.1	2.0	-63.3	<=8.0
2436.20	14.1	13.3	-1.2	2.0	-63.4	<=8.0
2436.25	14.0	13.3	-1.3	2.0	-63.5	<=8.0
2436.30	14.1	13.3	-1.2	2.0	-63.4	<=8.0
2436.35	11.2	13.3	-4.1	2.0	-66.3	<=8.0
2436.40	12.7	13.3	-2.6	2.0	-64.8	<=8.0
2436.45	12.7	13.3	-2.6	2.0	-64.8	<=8.0
2436.50	12.2	13.3	-3.1	2.0	-65.3	<=8.0
2436.55	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2436.60	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2436.65	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2436.70	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2436.75	12.8	13.3	-2.5	2.0	-64.7	<=8.0
2436.80	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2436.85	13.9	13.3	-1.4	2.0	-63.6	<=8.0
2436.90	16.1	13.3	0.8	2.0	-61.4	<=8.0
2436.95	17.5	13.3	2.2	2.0	-60.0	<=8.0
2437.00	21.5	13.3	6.2	2.0	-56.0	<=8.0
2437.05	23.0	13.3	7.7	2.0	-54.5	<=8.0
2437.10	23.8	13.3	8.5	2.0	-53.7	<=8.0
2437.15	23.7	13.3	8.4	2.0	-53.8	<=8.0
2437.20	23.8	13.3	8.5	2.0	-53.7	<=8.0
2437.25	22.3	13.3	7.0	2.0	-55.2	<=8.0
2437.30	20.8	13.3	5.5	2.0	-56.7	<=8.0
2437.35	16.7	13.3	1.4	2.0	-60.8	<=8.0
2437.40	17.7	13.3	2.4	2.0	-59.8	<=8.0
2437.45	17.0	13.3	1.7	2.0	-60.5	<=8.0
2437.50	16.2	13.3	0.9	2.0	-61.3	<=8.0
2437.55	15.6	13.3	0.3	2.0	-61.9	<=8.0
2437.60	14.6	13.3	-0.7	2.0	-62.9	<=8.0
2437.65	14.2	13.3	-1.1	2.0	-63.3	<=8.0
2437.70	11.4	13.3	-3.9	2.0	-66.1	<=8.0
2437.75	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2437.80	13.9	13.3	-1.4	2.0	-63.6	<=8.0
2437.85	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2437.90	11.3	13.3	-4.0	2.0	-66.2	<=8.0
2437.95	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2438.00	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2438.05	13.5	13.3	-1.8	2.0	-64.0	<=8.0

**Processing Gain**

ISL37400M

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2438.10	13.9	13.3	-1.4	2.0	-63.6	<=8.0
2438.15	13.9	13.3	-1.4	2.0	-63.6	<=8.0
2438.20	14.0	13.3	-1.3	2.0	-63.5	<=8.0
2438.25	14.0	13.3	-1.3	2.0	-63.5	<=8.0
2438.30	14.3	13.3	-1.0	2.0	-63.2	<=8.0
2438.35	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2438.40	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2438.45	14.4	13.3	-0.9	2.0	-63.1	<=8.0
2438.50	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2438.55	14.1	13.3	-1.2	2.0	-63.4	<=8.0
2438.60	14.1	13.3	-1.2	2.0	-63.4	<=8.0
2438.65	14.1	13.3	-1.2	2.0	-63.4	<=8.0
2438.70	11.8	13.3	-3.5	2.0	-65.7	<=8.0
2438.75	13.3	13.3	-2.0	2.0	-64.2	<=8.0
2438.80	13.3	13.3	-2.0	2.0	-64.2	<=8.0
2438.85	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2438.90	11.7	13.3	-3.6	2.0	-65.8	<=8.0
2438.95	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2439.00	13.3	13.3	-2.0	2.0	-64.2	<=8.0
2439.05	13.3	13.3	-2.0	2.0	-64.2	<=8.0
2439.10	13.5	13.3	-1.8	2.0	-64.0	<=8.0
2439.15	13.5	13.3	-1.8	2.0	-64.0	<=8.0
2439.20	13.5	13.3	-1.8	2.0	-64.0	<=8.0
2439.25	13.5	13.3	-1.8	2.0	-64.0	<=8.0
2439.30	14.5	13.3	-0.8	2.0	-63.0	<=8.0
2439.35	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2439.40	12.4	13.3	-2.9	2.0	-65.1	<=8.0
2439.45	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2439.50	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2439.55	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2439.60	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2439.65	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2439.70	12.1	13.3	-3.2	2.0	-65.4	<=8.0
2439.75	12.7	13.3	-2.6	2.0	-64.8	<=8.0
2439.80	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2439.85	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2439.90	11.6	13.3	-3.7	2.0	-65.9	<=8.0
2439.95	11.7	13.3	-3.6	2.0	-65.8	<=8.0
2440.00	12.1	13.3	-3.2	2.0	-65.4	<=8.0
2440.05	12.1	13.3	-3.2	2.0	-65.4	<=8.0
2440.10	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2440.15	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2440.20	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2440.25	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2440.30	13.3	13.3	-2.0	2.0	-64.2	<=8.0
2440.35	13.1	13.3	-2.2	2.0	-64.4	<=8.0
2440.40	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2440.45	12.9	13.3	-2.4	2.0	-64.6	<=8.0

**Processing Gain**

ISL37400M

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2440.50	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2440.55	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2440.60	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2440.65	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2440.70	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2440.75	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2440.80	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2440.85	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2440.90	12.3	13.3	-3.0	2.0	-65.2	<=8.0
2440.95	12.5	13.3	-2.8	2.0	-65.0	<=8.0
2441.00	12.7	13.3	-2.6	2.0	-64.8	<=8.0
2441.05	12.7	13.3	-2.6	2.0	-64.8	<=8.0
2441.10	12.7	13.3	-2.6	2.0	-64.8	<=8.0
2441.15	12.8	13.3	-2.5	2.0	-64.7	<=8.0
2441.20	13.5	13.3	-1.8	2.0	-64.0	<=8.0
2441.25	13.5	13.3	-1.8	2.0	-64.0	<=8.0
2441.30	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2441.35	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2441.40	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2441.45	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2441.50	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2441.55	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2441.60	13.8	13.3	-1.5	2.0	-63.7	<=8.0
2441.65	13.7	13.3	-1.6	2.0	-63.8	<=8.0
2441.70	13.7	13.3	-1.6	2.0	-63.8	<=8.0
2441.75	13.7	13.3	-1.6	2.0	-63.8	<=8.0
2441.80	13.7	13.3	-1.6	2.0	-63.8	<=8.0
2441.85	13.6	13.3	-1.7	2.0	-63.9	<=8.0
2441.90	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2441.95	12.6	13.3	-2.7	2.0	-64.9	<=8.0
2442.00	12.9	13.3	-2.4	2.0	-64.6	<=8.0
2442.05	13.0	13.3	-2.3	2.0	-64.5	<=8.0
2442.10	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2442.15	13.2	13.3	-2.1	2.0	-64.3	<=8.0
2442.20	14.1	13.3	-1.2	2.0	-63.4	<=8.0
2442.25	14.1	13.3	-1.2	2.0	-63.4	<=8.0
2442.30	14.5	13.3	-0.8	2.0	-63.0	<=8.0
2442.35	16.0	13.3	0.7	2.0	-61.5	<=8.0
2442.40	16.7	13.3	1.4	2.0	-60.8	<=8.0
2442.45	19.3	13.3	4.0	2.0	-58.2	<=8.0
2442.50	21.3	13.3	6.0	2.0	-56.2	<=8.0
2442.55	23.3	13.3	8.0	2.0	-54.2	<=8.0
2442.60	25.0	13.3	9.7	2.0	-52.5	<=8.0
2442.65	25.0	13.3	9.7	2.0	-52.5	<=8.0
2442.70	25.0	13.3	9.7	2.0	-52.5	<=8.0
2442.75	24.2	13.3	8.9	2.0	-53.3	<=8.0
2442.80	22.4	13.3	7.1	2.0	-55.1	<=8.0
2442.85	20.8	13.3	5.5	2.0	-56.7	<=8.0

**Processing Gain**

ISL37400M

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2442.90	18.9	13.3	3.6	2.0	-58.6	<=8.0
2442.95	18.8	13.3	3.5	2.0	-58.7	<=8.0
2443.00	18.2	13.3	2.9	2.0	-59.3	<=8.0
2443.05	18.2	13.3	2.9	2.0	-59.3	<=8.0
2443.10	17.6	13.3	2.3	2.0	-59.9	<=8.0
2443.15	17.1	13.3	1.8	2.0	-60.4	<=8.0
2443.20	16.7	13.3	1.4	2.0	-60.8	<=8.0
2443.25	16.7	13.3	1.4	2.0	-60.8	<=8.0
2443.30	16.6	13.3	1.3	2.0	-60.9	<=8.0
2443.35	16.3	13.3	1.0	2.0	-61.2	<=8.0
2443.40	15.9	13.3	0.6	2.0	-61.6	<=8.0
2443.45	15.9	13.3	0.6	2.0	-61.6	<=8.0
2443.50	15.9	13.3	0.6	2.0	-61.6	<=8.0
2443.55	16.2	13.3	0.9	2.0	-61.3	<=8.0
2443.60	16.4	13.3	1.1	2.0	-61.1	<=8.0
2443.65	16.4	13.3	1.1	2.0	-61.1	<=8.0
2443.70	16.4	13.3	1.1	2.0	-61.1	<=8.0
2443.75	16.4	13.3	1.1	2.0	-61.1	<=8.0
2443.80	17.5	13.3	2.2	2.0	-60.0	<=8.0
2443.85	17.5	13.3	2.2	2.0	-60.0	<=8.0
2443.90	17.5	13.3	2.2	2.0	-60.0	<=8.0
2443.95	17.5	13.3	2.2	2.0	-60.0	<=8.0
2444.00	17.6	13.3	2.3	2.0	-59.9	<=8.0
2444.05	17.6	13.3	2.3	2.0	-59.9	<=8.0
2444.10	18.3	13.3	3.0	2.0	-59.2	<=8.0
2444.15	18.5	13.3	3.2	2.0	-59.0	<=8.0
2444.20	18.7	13.3	3.4	2.0	-58.8	<=8.0
2444.25	18.9	13.3	3.6	2.0	-58.6	<=8.0
2444.30	19.2	13.3	3.9	2.0	-58.3	<=8.0
2444.35	19.2	13.3	3.9	2.0	-58.3	<=8.0
2444.40	19.2	13.3	3.9	2.0	-58.3	<=8.0
2444.45	19.2	13.3	3.9	2.0	-58.3	<=8.0
2444.50	19.8	13.3	4.5	2.0	-57.7	<=8.0
2444.55	20.4	13.3	5.1	2.0	-57.1	<=8.0
2444.60	20.1	13.3	4.8	2.0	-57.4	<=8.0
2444.65	20.3	13.3	5.0	2.0	-57.2	<=8.0
2444.70	20.3	13.3	5.0	2.0	-57.2	<=8.0
2444.75	20.4	13.3	5.1	2.0	-57.1	<=8.0
2444.80	20.5	13.3	5.2	2.0	-57.0	<=8.0
2444.85	20.6	13.3	5.3	2.0	-56.9	<=8.0
2444.90	20.8	13.3	5.5	2.0	-56.7	<=8.0
2444.95	20.9	13.3	5.6	2.0	-56.6	<=8.0
2445.00	20.8	13.3	5.5	2.0	-56.7	<=8.0
2445.05	20.9	13.3	5.6	2.0	-56.6	<=8.0
2445.10	20.8	13.3	5.5	2.0	-56.7	<=8.0
2445.15	21.0	13.3	5.7	2.0	-56.5	<=8.0
2445.20	21.0	13.3	5.7	2.0	-56.5	<=8.0
2445.25	22.2	13.3	6.9	2.0	-55.3	<=8.0

2Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2445.30	22.5	13.3	7.2	2.0	-55.0	<=8.0
2445.35	22.7	13.3	7.4	2.0	-54.8	<=8.0
2445.40	22.8	13.3	7.5	2.0	-54.7	<=8.0
2445.45	22.8	13.3	7.5	2.0	-54.7	<=8.0
2445.50	22.8	13.3	7.5	2.0	-54.7	<=8.0

**12.6**

**Test Conditions**

TX Card **HWB3163-04 Rev B**  
 S/N **99360038**  
 RX Card **ISL37400M Rev A**  
 S/N **00500038**  
 TX Firmware **P10002C0, MS11168A3**  
 RX Firmware **ID010000, PK010001, SF010000**  
 Software Ver. **3.0.24**  
 Mode **2 MB Pseudo IBSS**  
 Pkt Size **1024**  
 Pkt Dly **1**  
 Pkt Burst **6**

Intersil Chips on Card: **ISL3984**  
**ISL3685**  
**HFA3783**  
**ISL3183**  
**ISL3874**

Processing Gain (dB)	XMIT level	-62.2
	<b>S/N+Ls</b>	<b>15.3</b>
	<b>0dB J/S</b>	<b>0.0</b>
PG	Offset	Signal Generator Delta
21.7	-8500	6.4
21.0	-8450	5.7
20.6	-8400	5.3
20.0	-8350	4.7
19.9	-8300	4.6
19.7	-8250	4.4
19.5	-8200	4.2
19.5	-8150	4.2
19.5	-8100	4.2
19.5	-8050	4.2
19.4	-8000	4.1
19.4	-7950	4.1
19.3	-7900	4.0
20.0	-7850	4.7
20.2	-7800	4.9
20.2	-7750	4.9
20.3	-7700	5.0
20.3	-7650	5.0
20.3	-7600	5.0
20.2	-7550	4.9
20.1	-7500	4.8
19.4	-7450	4.1
19.0	-7400	3.7
18.8	-7350	3.5
18.8	-7300	3.5
18.6	-7250	3.3
18.4	-7200	3.1
18.4	-7150	3.1
18.2	-7100	2.9
18.3	-7050	3.0
18.4	-7000	3.1
18.4	-6950	3.1
18.4	-6900	3.1
18.4	-6850	3.1
18.4	-6800	3.1
18.5	-6750	3.2
18.5	-6700	3.2
18.5	-6650	3.2
18.4	-6600	3.1
18.4	-6550	3.1
18.4	-6500	3.1
18.5	-6450	3.2
18.3	-6400	3.0
18.1	-6350	2.8
17.0	-6300	1.7
16.6	-6250	1.3
16.4	-6200	1.1

16.4	-6150	1.1	
15.1	-6100	-0.2	
15.1	-6050	-0.2	
15.2	-6000	-0.1	
15.2	-5950	-0.1	
15.2	-5900	-0.1	
15.3	-5850	0.0	
15.3	-5800	0.0	
16.3	-5750	1.0	
17.5	-5700	2.2	
17.9	-5650	2.6	
17.9	-5600	2.6	
19.0	-5550	3.7	
20.5	-5500	5.2	
23.0	-5450	7.7	
25.6	-5400	10.3	
25.6	-5350	10.3	
22.1	-5300	6.8	
20.5	-5250	5.2	
18.5	-5200	3.2	
17.4	-5150	2.1	
17.0	-5100	1.7	
16.9	-5050	1.6	
16.9	-5000	1.6	
16.8	-4950	1.5	
16.5	-4900	1.2	
15.2	-4850	-0.1	
15.1	-4800	-0.2	
14.8	-4750	-0.5	
14.8	-4700	-0.5	
13.8	-4650	-1.5	
13.2	-4600	-2.1	
13.2	-4550	-2.1	
13.2	-4500	-2.1	
13.1	-4450	-2.2	
13.2	-4400	-2.1	
12.9	-4350	-2.4	
12.9	-4300	-2.4	
13.0	-4250	-2.3	
13.1	-4200	-2.2	
13.1	-4150	-2.2	
13.1	-4100	-2.2	
13.1	-4050	-2.2	
13.1	-4000	-2.2	
13.1	-3950	-2.2	
13.1	-3900	-2.2	
13.1	-3850	-2.2	
13.0	-3800	-2.3	
13.1	-3750	-2.2	
13.2	-3700	-2.1	
12.5	-3650	-2.8	
12.2	-3600	-3.1	

12.5	-3550	-2.8	
12.5	-3500	-2.8	
12.5	-3450	-2.8	
12.6	-3400	-2.7	
12.6	-3350	-2.7	
12.6	-3300	-2.7	
12.6	-3250	-2.7	
12.6	-3200	-2.7	
12.6	-3150	-2.7	
12.4	-3100	-2.9	
12.4	-3050	-2.9	
12.3	-3000	-3.0	
12.5	-2950	-2.8	
12.6	-2900	-2.7	
12.6	-2850	-2.7	
12.6	-2800	-2.7	
12.6	-2750	-2.7	
12.7	-2700	-2.6	
13.2	-2650	-2.1	
12.1	-2600	-3.2	
12.1	-2550	-3.2	
12.0	-2500	-3.3	
12.2	-2450	-3.1	
12.2	-2400	-3.1	
12.2	-2350	-3.1	
12.2	-2300	-3.1	
12.2	-2250	-3.1	
12.8	-2200	-2.5	
12.8	-2150	-2.5	
12.8	-2100	-2.5	
12.3	-2050	-3.0	
12.3	-2000	-3.0	
12.5	-1950	-2.8	
12.5	-1900	-2.8	
12.5	-1850	-2.8	
12.5	-1800	-2.8	
12.6	-1750	-2.7	
13.2	-1700	-2.1	
11.6	-1650	-3.7	
11.9	-1600	-3.4	
12.0	-1550	-3.3	
12.3	-1500	-3.0	
12.3	-1450	-3.0	
12.3	-1400	-3.0	
12.3	-1350	-3.0	
11.9	-1300	-3.4	
12.3	-1250	-3.0	
12.8	-1200	-2.5	
13.0	-1150	-2.3	
12.4	-1100	-2.9	
13.3	-1050	-2.0	
14.9	-1000	-0.4	


14.9	-950	-0.4	
14.4	-900	-0.9	
14.2	-850	-1.1	
14.1	-800	-1.2	
14.0	-750	-1.3	
14.1	-700	-1.2	
11.2	-650	-4.1	
12.7	-600	-2.6	
12.7	-550	-2.6	
12.2	-500	-3.1	
12.3	-450	-3.0	
12.3	-400	-3.0	
12.3	-350	-3.0	
12.3	-300	-3.0	
12.8	-250	-2.5	
13.0	-200	-2.3	
13.9	-150	-1.4	
16.1	-100	0.8	
17.5	-50	2.2	
21.5	0	6.2	
23.0	50	7.7	
23.8	100	8.5	
23.7	150	8.4	
23.8	200	8.5	
22.3	250	7.0	
20.8	300	5.5	
16.7	350	1.4	
17.7	400	2.4	
17.0	450	1.7	
16.2	500	0.9	
15.6	550	0.3	
14.6	600	-0.7	
14.2	650	-1.1	
11.4	700	-3.9	
13.8	750	-1.5	
13.9	800	-1.4	
13.2	850	-2.1	
11.3	900	-4.0	
12.9	950	-2.4	
12.9	1000	-2.4	
13.5	1050	-1.8	
13.9	1100	-1.4	
13.9	1150	-1.4	
14.0	1200	-1.3	
14.0	1250	-1.3	
14.3	1300	-1.0	
12.6	1350	-2.7	
13.8	1400	-1.5	
14.4	1450	-0.9	
13.8	1500	-1.5	
14.1	1550	-1.2	
14.1	1600	-1.2	

14.1	1650	-1.2	
11.8	1700	-3.5	
13.3	1750	-2.0	
13.3	1800	-2.0	
12.6	1850	-2.7	
11.7	1900	-3.6	
13.0	1950	-2.3	
13.3	2000	-2.0	
13.3	2050	-2.0	
13.5	2100	-1.8	
13.5	2150	-1.8	
13.5	2200	-1.8	
13.5	2250	-1.8	
14.5	2300	-0.8	
12.5	2350	-2.8	
12.4	2400	-2.9	
12.5	2450	-2.8	
13.1	2500	-2.2	
13.1	2550	-2.2	
13.1	2600	-2.2	
13.1	2650	-2.2	
12.1	2700	-3.2	
12.7	2750	-2.6	
12.9	2800	-2.4	
12.9	2850	-2.4	
11.6	2900	-3.7	
11.7	2950	-3.6	
12.1	3000	-3.2	
12.1	3050	-3.2	
12.3	3100	-3.0	
12.3	3150	-3.0	
12.5	3200	-2.8	
13.0	3250	-2.3	
13.3	3300	-2.0	
13.1	3350	-2.2	
13.0	3400	-2.3	
12.9	3450	-2.4	
12.9	3500	-2.4	
13.2	3550	-2.1	
13.2	3600	-2.1	
13.2	3650	-2.1	
12.9	3700	-2.4	
12.9	3750	-2.4	
13.0	3800	-2.3	
13.0	3850	-2.3	
12.3	3900	-3.0	
12.5	3950	-2.8	
12.7	4000	-2.6	
12.7	4050	-2.6	
12.7	4100	-2.6	
12.8	4150	-2.5	
13.5	4200	-1.8	

13.5	4250	-1.8	
13.8	4300	-1.5	
13.8	4350	-1.5	
13.8	4400	-1.5	
13.8	4450	-1.5	
13.8	4500	-1.5	
13.8	4550	-1.5	
13.8	4600	-1.5	
13.7	4650	-1.6	
13.7	4700	-1.6	
13.7	4750	-1.6	
13.7	4800	-1.6	
13.6	4850	-1.7	
12.6	4900	-2.7	
12.6	4950	-2.7	
12.9	5000	-2.4	
13.0	5050	-2.3	
13.2	5100	-2.1	
13.2	5150	-2.1	
14.1	5200	-1.2	
14.1	5250	-1.2	
14.5	5300	-0.8	
16.0	5350	0.7	
16.7	5400	1.4	
19.3	5450	4.0	
21.3	5500	6.0	
23.3	5550	8.0	
25.0	5600	9.7	
25.0	5650	9.7	
25.0	5700	9.7	
24.2	5750	8.9	
22.4	5800	7.1	
20.8	5850	5.5	
18.9	5900	3.6	
18.8	5950	3.5	
18.2	6000	2.9	
18.2	6050	2.9	
17.6	6100	2.3	
17.1	6150	1.8	
16.7	6200	1.4	
16.7	6250	1.4	
16.6	6300	1.3	
16.3	6350	1.0	
15.9	6400	0.6	
15.9	6450	0.6	
15.9	6500	0.6	
16.2	6550	0.9	
16.4	6600	1.1	
16.4	6650	1.1	
16.4	6700	1.1	
16.4	6750	1.1	
17.5	6800	2.2	

17.5	6850	2.2	
17.5	6900	2.2	
17.5	6950	2.2	
17.6	7000	2.3	
17.6	7050	2.3	
18.3	7100	3.0	
18.5	7150	3.2	
18.7	7200	3.4	
18.9	7250	3.6	
19.2	7300	3.9	
19.2	7350	3.9	
19.2	7400	3.9	
19.2	7450	3.9	
19.8	7500	4.5	
20.4	7550	5.1	
20.1	7600	4.8	
20.3	7650	5.0	
20.3	7700	5.0	
20.4	7750	5.1	
20.5	7800	5.2	
20.6	7850	5.3	
20.8	7900	5.5	
20.9	7950	5.6	
20.8	8000	5.5	
20.9	8050	5.6	
20.8	8100	5.5	
21.0	8150	5.7	
21.0	8200	5.7	
22.2	8250	6.9	
22.5	8300	7.2	
22.7	8350	7.4	
22.8	8400	7.5	
22.8	8450	7.5	
22.8	8500	7.5	
<b>12.6</b>	<b>Processing Gain (dB) @ 80th Percentile =</b>		

### Processing Gain Channel 6 (fc=2437MHz) @ 2Mbps



**Processing Gain**

ISL37400M

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2428.50	19.0	10.3	6.7	2.0	-54.1	<=8.0
2428.55	18.3	10.3	6.0	2.0	-54.8	<=8.0
2428.60	17.6	10.3	5.3	2.0	-55.5	<=8.0
2428.65	17.0	10.3	4.7	2.0	-56.1	<=8.0
2428.70	16.9	10.3	4.6	2.0	-56.2	<=8.0
2428.75	16.6	10.3	4.3	2.0	-56.5	<=8.0
2428.80	16.4	10.3	4.1	2.0	-56.7	<=8.0
2428.85	16.3	10.3	4.0	2.0	-56.8	<=8.0
2428.90	16.3	10.3	4.0	2.0	-56.8	<=8.0
2428.95	16.2	10.3	3.9	2.0	-56.9	<=8.0
2429.00	16.1	10.3	3.8	2.0	-57.0	<=8.0
2429.05	16.5	10.3	4.2	2.0	-56.6	<=8.0
2429.10	17.3	10.3	5.0	2.0	-55.8	<=8.0
2429.15	17.1	10.3	4.8	2.0	-56.0	<=8.0
2429.20	17.1	10.3	4.8	2.0	-56.0	<=8.0
2429.25	17.6	10.3	5.3	2.0	-55.5	<=8.0
2429.30	17.6	10.3	5.3	2.0	-55.5	<=8.0
2429.35	17.7	10.3	5.4	2.0	-55.4	<=8.0
2429.40	17.7	10.3	5.4	2.0	-55.4	<=8.0
2429.45	17.7	10.3	5.4	2.0	-55.4	<=8.0
2429.50	17.3	10.3	5.0	2.0	-55.8	<=8.0
2429.55	16.9	10.3	4.6	2.0	-56.2	<=8.0
2429.60	16.2	10.3	3.9	2.0	-56.9	<=8.0
2429.65	16.0	10.3	3.7	2.0	-57.1	<=8.0
2429.70	15.9	10.3	3.6	2.0	-57.2	<=8.0
2429.75	16.3	10.3	4.0	2.0	-56.8	<=8.0
2429.80	16.2	10.3	3.9	2.0	-56.9	<=8.0
2429.85	16.2	10.3	3.9	2.0	-56.9	<=8.0
2429.90	16.3	10.3	4.0	2.0	-56.8	<=8.0
2429.95	16.4	10.3	4.1	2.0	-56.7	<=8.0
2430.00	16.3	10.3	4.0	2.0	-56.8	<=8.0
2430.05	16.2	10.3	3.9	2.0	-56.9	<=8.0
2430.10	15.8	10.3	3.5	2.0	-57.3	<=8.0
2430.15	16.0	10.3	3.7	2.0	-57.1	<=8.0
2430.20	16.6	10.3	4.3	2.0	-56.5	<=8.0
2430.25	16.8	10.3	4.5	2.0	-56.3	<=8.0
2430.30	17.6	10.3	5.3	2.0	-55.5	<=8.0
2430.35	17.8	10.3	5.5	2.0	-55.3	<=8.0
2430.40	17.9	10.3	5.6	2.0	-55.2	<=8.0
2430.45	17.4	10.3	5.1	2.0	-55.7	<=8.0
2430.50	16.7	10.3	4.4	2.0	-56.4	<=8.0
2430.55	15.8	10.3	3.5	2.0	-57.3	<=8.0
2430.60	15.4	10.3	3.1	2.0	-57.7	<=8.0
2430.65	15.1	10.3	2.8	2.0	-58.0	<=8.0
2430.70	15.0	10.3	2.7	2.0	-58.1	<=8.0
2430.75	15.3	10.3	3.0	2.0	-57.8	<=8.0
2430.80	15.2	10.3	2.9	2.0	-57.9	<=8.0
2430.85	15.4	10.3	3.1	2.0	-57.7	<=8.0

**Processing Gain**

ISL37400M

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2430.90	15.6	10.3	3.3	2.0	-57.5	<=8.0
2430.95	15.3	10.3	3.0	2.0	-57.8	<=8.0
2431.00	14.9	10.3	2.6	2.0	-58.2	<=8.0
2431.05	15.0	10.3	2.7	2.0	-58.1	<=8.0
2431.10	15.1	10.3	2.8	2.0	-58.0	<=8.0
2431.15	14.9	10.3	2.6	2.0	-58.2	<=8.0
2431.20	15.4	10.3	3.1	2.0	-57.7	<=8.0
2431.25	16.0	10.3	3.7	2.0	-57.1	<=8.0
2431.30	17.3	10.3	5.0	2.0	-55.8	<=8.0
2431.35	17.7	10.3	5.4	2.0	-55.4	<=8.0
2431.40	18.5	10.3	6.2	2.0	-54.6	<=8.0
2431.45	19.9	10.3	7.6	2.0	-53.2	<=8.0
2431.50	20.4	10.3	8.1	2.0	-52.7	<=8.0
2431.55	21.3	10.3	9.0	2.0	-51.8	<=8.0
2431.60	22.2	10.3	9.9	2.0	-50.9	<=8.0
2431.65	23.9	10.3	11.6	2.0	-49.2	<=8.0
2431.70	22.9	10.3	10.6	2.0	-50.2	<=8.0
2431.75	22.6	10.3	10.3	2.0	-50.5	<=8.0
2431.80	19.0	10.3	6.7	2.0	-54.1	<=8.0
2431.85	19.9	10.3	7.6	2.0	-53.2	<=8.0
2431.90	18.0	10.3	5.7	2.0	-55.1	<=8.0
2431.95	17.6	10.3	5.3	2.0	-55.5	<=8.0
2432.00	16.2	10.3	3.9	2.0	-56.9	<=8.0
2432.05	15.4	10.3	3.1	2.0	-57.7	<=8.0
2432.10	14.7	10.3	2.4	2.0	-58.4	<=8.0
2432.15	14.1	10.3	1.8	2.0	-59.0	<=8.0
2432.20	14.3	10.3	2.0	2.0	-58.8	<=8.0
2432.25	14.3	10.3	2.0	2.0	-58.8	<=8.0
2432.30	14.2	10.3	1.9	2.0	-58.9	<=8.0
2432.35	14.1	10.3	1.8	2.0	-59.0	<=8.0
2432.40	14.3	10.3	2.0	2.0	-58.8	<=8.0
2432.45	14.0	10.3	1.7	2.0	-59.1	<=8.0
2432.50	13.9	10.3	1.6	2.0	-59.2	<=8.0
2432.55	14.0	10.3	1.7	2.0	-59.1	<=8.0
2432.60	14.0	10.3	1.7	2.0	-59.1	<=8.0
2432.65	14.1	10.3	1.8	2.0	-59.0	<=8.0
2432.70	14.0	10.3	1.7	2.0	-59.1	<=8.0
2432.75	14.5	10.3	2.2	2.0	-58.6	<=8.0
2432.80	14.3	10.3	2.0	2.0	-58.8	<=8.0
2432.85	13.9	10.3	1.6	2.0	-59.2	<=8.0
2432.90	14.3	10.3	2.0	2.0	-58.8	<=8.0
2432.95	14.0	10.3	1.7	2.0	-59.1	<=8.0
2433.00	13.9	10.3	1.6	2.0	-59.2	<=8.0
2433.05	14.0	10.3	1.7	2.0	-59.1	<=8.0
2433.10	13.6	10.3	1.3	2.0	-59.5	<=8.0
2433.15	13.7	10.3	1.4	2.0	-59.4	<=8.0
2433.20	13.6	10.3	1.3	2.0	-59.5	<=8.0
2433.25	13.6	10.3	1.3	2.0	-59.5	<=8.0

**Processing Gain**

ISL37400M

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2433.30	13.3	10.3	1.0	2.0	-59.8	<=8.0
2433.35	13.4	10.3	1.1	2.0	-59.7	<=8.0
2433.40	13.6	10.3	1.3	2.0	-59.5	<=8.0
2433.45	13.2	10.3	0.9	2.0	-59.9	<=8.0
2433.50	13.5	10.3	1.2	2.0	-59.6	<=8.0
2433.55	13.1	10.3	0.8	2.0	-60.0	<=8.0
2433.60	13.3	10.3	1.0	2.0	-59.8	<=8.0
2433.65	13.7	10.3	1.4	2.0	-59.4	<=8.0
2433.70	13.4	10.3	1.1	2.0	-59.7	<=8.0
2433.75	13.7	10.3	1.4	2.0	-59.4	<=8.0
2433.80	13.4	10.3	1.1	2.0	-59.7	<=8.0
2433.85	13.5	10.3	1.2	2.0	-59.6	<=8.0
2433.90	13.4	10.3	1.1	2.0	-59.7	<=8.0
2433.95	13.3	10.3	1.0	2.0	-59.8	<=8.0
2434.00	13.6	10.3	1.3	2.0	-59.5	<=8.0
2434.05	13.2	10.3	0.9	2.0	-59.9	<=8.0
2434.10	12.8	10.3	0.5	2.0	-60.3	<=8.0
2434.15	13.2	10.3	0.9	2.0	-59.9	<=8.0
2434.20	12.9	10.3	0.6	2.0	-60.2	<=8.0
2434.25	12.9	10.3	0.6	2.0	-60.2	<=8.0
2434.30	12.8	10.3	0.5	2.0	-60.3	<=8.0
2434.35	13.0	10.3	0.7	2.0	-60.1	<=8.0
2434.40	13.1	10.3	0.8	2.0	-60.0	<=8.0
2434.45	12.5	10.3	0.2	2.0	-60.6	<=8.0
2434.50	13.0	10.3	0.7	2.0	-60.1	<=8.0
2434.55	13.0	10.3	0.7	2.0	-60.1	<=8.0
2434.60	12.9	10.3	0.6	2.0	-60.2	<=8.0
2434.65	13.1	10.3	0.8	2.0	-60.0	<=8.0
2434.70	13.0	10.3	0.7	2.0	-60.1	<=8.0
2434.75	13.3	10.3	1.0	2.0	-59.8	<=8.0
2434.80	13.2	10.3	0.9	2.0	-59.9	<=8.0
2434.85	13.5	10.3	1.2	2.0	-59.6	<=8.0
2434.90	13.3	10.3	1.0	2.0	-59.8	<=8.0
2434.95	13.5	10.3	1.2	2.0	-59.6	<=8.0
2435.00	13.6	10.3	1.3	2.0	-59.5	<=8.0
2435.05	14.0	10.3	1.7	2.0	-59.1	<=8.0
2435.10	13.9	10.3	1.6	2.0	-59.2	<=8.0
2435.15	13.4	10.3	1.1	2.0	-59.7	<=8.0
2435.20	13.1	10.3	0.8	2.0	-60.0	<=8.0
2435.25	12.9	10.3	0.6	2.0	-60.2	<=8.0
2435.30	12.6	10.3	0.3	2.0	-60.5	<=8.0
2435.35	12.5	10.3	0.2	2.0	-60.6	<=8.0
2435.40	13.3	10.3	1.0	2.0	-59.8	<=8.0
2435.45	13.0	10.3	0.7	2.0	-60.1	<=8.0
2435.50	13.2	10.3	0.9	2.0	-59.9	<=8.0
2435.55	13.4	10.3	1.1	2.0	-59.7	<=8.0
2435.60	13.2	10.3	0.9	2.0	-59.9	<=8.0
2435.65	13.7	10.3	1.4	2.0	-59.4	<=8.0

**Processing Gain**

ISL37400M

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2435.70	13.1	10.3	0.8	2.0	-60.0	<=8.0
2435.75	13.4	10.3	1.1	2.0	-59.7	<=8.0
2435.80	13.3	10.3	1.0	2.0	-59.8	<=8.0
2435.85	13.6	10.3	1.3	2.0	-59.5	<=8.0
2435.90	13.3	10.3	1.0	2.0	-59.8	<=8.0
2435.95	13.2	10.3	0.9	2.0	-59.9	<=8.0
2436.00	13.4	10.3	1.1	2.0	-59.7	<=8.0
2436.05	13.7	10.3	1.4	2.0	-59.4	<=8.0
2436.10	13.7	10.3	1.4	2.0	-59.4	<=8.0
2436.15	13.3	10.3	1.0	2.0	-59.8	<=8.0
2436.20	13.6	10.3	1.3	2.0	-59.5	<=8.0
2436.25	13.2	10.3	0.9	2.0	-59.9	<=8.0
2436.30	13.1	10.3	0.8	2.0	-60.0	<=8.0
2436.35	13.0	10.3	0.7	2.0	-60.1	<=8.0
2436.40	12.9	10.3	0.6	2.0	-60.2	<=8.0
2436.45	12.8	10.3	0.5	2.0	-60.3	<=8.0
2436.50	12.5	10.3	0.2	2.0	-60.6	<=8.0
2436.55	12.6	10.3	0.3	2.0	-60.5	<=8.0
2436.60	12.7	10.3	0.4	2.0	-60.4	<=8.0
2436.65	13.3	10.3	1.0	2.0	-59.8	<=8.0
2436.70	13.2	10.3	0.9	2.0	-59.9	<=8.0
2436.75	13.1	10.3	0.8	2.0	-60.0	<=8.0
2436.80	14.8	10.3	2.5	2.0	-58.3	<=8.0
2436.85	15.2	10.3	2.9	2.0	-57.9	<=8.0
2436.90	16.3	10.3	4.0	2.0	-56.8	<=8.0
2436.95	20.8	10.3	8.5	2.0	-52.3	<=8.0
2437.00	19.0	10.3	6.7	2.0	-54.1	<=8.0
2437.05	20.4	10.3	8.1	2.0	-52.7	<=8.0
2437.10	20.3	10.3	8.0	2.0	-52.8	<=8.0
2437.15	22.8	10.3	10.5	2.0	-50.3	<=8.0
2437.20	21.8	10.3	9.5	2.0	-51.3	<=8.0
2437.25	20.4	10.3	8.1	2.0	-52.7	<=8.0
2437.30	19.1	10.3	6.8	2.0	-54.0	<=8.0
2437.35	17.9	10.3	5.6	2.0	-55.2	<=8.0
2437.40	16.7	10.3	4.4	2.0	-56.4	<=8.0
2437.45	15.5	10.3	3.2	2.0	-57.6	<=8.0
2437.50	15.1	10.3	2.8	2.0	-58.0	<=8.0
2437.55	14.4	10.3	2.1	2.0	-58.7	<=8.0
2437.60	13.7	10.3	1.4	2.0	-59.4	<=8.0
2437.65	12.7	10.3	0.4	2.0	-60.4	<=8.0
2437.70	12.4	10.3	0.1	2.0	-60.7	<=8.0
2437.75	12.0	10.3	-0.3	2.0	-61.1	<=8.0
2437.80	12.2	10.3	-0.1	2.0	-60.9	<=8.0
2437.85	12.4	10.3	0.1	2.0	-60.7	<=8.0
2437.90	12.5	10.3	0.2	2.0	-60.6	<=8.0
2437.95	12.7	10.3	0.4	2.0	-60.4	<=8.0
2438.00	12.1	10.3	-0.2	2.0	-61.0	<=8.0
2438.05	13.2	10.3	0.9	2.0	-59.9	<=8.0

**Processing Gain**

ISL37400M

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2438.10	13.7	10.3	1.4	2.0	-59.4	<=8.0
2438.15	13.7	10.3	1.4	2.0	-59.4	<=8.0
2438.20	13.6	10.3	1.3	2.0	-59.5	<=8.0
2438.25	14.1	10.3	1.8	2.0	-59.0	<=8.0
2438.30	14.2	10.3	1.9	2.0	-58.9	<=8.0
2438.35	14.4	10.3	2.1	2.0	-58.7	<=8.0
2438.40	14.3	10.3	2.0	2.0	-58.8	<=8.0
2438.45	14.2	10.3	1.9	2.0	-58.9	<=8.0
2438.50	13.9	10.3	1.6	2.0	-59.2	<=8.0
2438.55	13.5	10.3	1.2	2.0	-59.6	<=8.0
2438.60	12.9	10.3	0.6	2.0	-60.2	<=8.0
2438.65	12.2	10.3	-0.1	2.0	-60.9	<=8.0
2438.70	12.4	10.3	0.1	2.0	-60.7	<=8.0
2438.75	12.4	10.3	0.1	2.0	-60.7	<=8.0
2438.80	12.7	10.3	0.4	2.0	-60.4	<=8.0
2438.85	12.7	10.3	0.4	2.0	-60.4	<=8.0
2438.90	12.1	10.3	-0.2	2.0	-61.0	<=8.0
2438.95	12.2	10.3	-0.1	2.0	-60.9	<=8.0
2439.00	12.3	10.3	0.0	2.0	-60.8	<=8.0
2439.05	12.5	10.3	0.2	2.0	-60.6	<=8.0
2439.10	13.2	10.3	0.9	2.0	-59.9	<=8.0
2439.15	12.2	10.3	-0.1	2.0	-60.9	<=8.0
2439.20	13.4	10.3	1.1	2.0	-59.7	<=8.0
2439.25	13.6	10.3	1.3	2.0	-59.5	<=8.0
2439.30	13.4	10.3	1.1	2.0	-59.7	<=8.0
2439.35	13.5	10.3	1.2	2.0	-59.6	<=8.0
2439.40	13.5	10.3	1.2	2.0	-59.6	<=8.0
2439.45	13.7	10.3	1.4	2.0	-59.4	<=8.0
2439.50	13.6	10.3	1.3	2.0	-59.5	<=8.0
2439.55	13.4	10.3	1.1	2.0	-59.7	<=8.0
2439.60	13.2	10.3	0.9	2.0	-59.9	<=8.0
2439.65	13.7	10.3	1.4	2.0	-59.4	<=8.0
2439.70	12.8	10.3	0.5	2.0	-60.3	<=8.0
2439.75	12.4	10.3	0.1	2.0	-60.7	<=8.0
2439.80	11.8	10.3	-0.5	2.0	-61.3	<=8.0
2439.85	12.6	10.3	0.3	2.0	-60.5	<=8.0
2439.90	12.4	10.3	0.1	2.0	-60.7	<=8.0
2439.95	12.8	10.3	0.5	2.0	-60.3	<=8.0
2440.00	12.6	10.3	0.3	2.0	-60.5	<=8.0
2440.05	12.8	10.3	0.5	2.0	-60.3	<=8.0
2440.10	12.7	10.3	0.4	2.0	-60.4	<=8.0
2440.15	13.6	10.3	1.3	2.0	-59.5	<=8.0
2440.20	13.4	10.3	1.1	2.0	-59.7	<=8.0
2440.25	13.6	10.3	1.3	2.0	-59.5	<=8.0
2440.30	13.9	10.3	1.6	2.0	-59.2	<=8.0
2440.35	14.2	10.3	1.9	2.0	-58.9	<=8.0
2440.40	14.3	10.3	2.0	2.0	-58.8	<=8.0
2440.45	14.2	10.3	1.9	2.0	-58.9	<=8.0

**Processing Gain**

ISL37400M

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2440.50	13.9	10.3	1.6	2.0	-59.2	<=8.0
2440.55	13.4	10.3	1.1	2.0	-59.7	<=8.0
2440.60	13.8	10.3	1.5	2.0	-59.3	<=8.0
2440.65	13.0	10.3	0.7	2.0	-60.1	<=8.0
2440.70	13.3	10.3	1.0	2.0	-59.8	<=8.0
2440.75	13.8	10.3	1.5	2.0	-59.3	<=8.0
2440.80	13.6	10.3	1.3	2.0	-59.5	<=8.0
2440.85	13.6	10.3	1.3	2.0	-59.5	<=8.0
2440.90	13.2	10.3	0.9	2.0	-59.9	<=8.0
2440.95	13.8	10.3	1.5	2.0	-59.3	<=8.0
2441.00	13.9	10.3	1.6	2.0	-59.2	<=8.0
2441.05	13.7	10.3	1.4	2.0	-59.4	<=8.0
2441.10	13.9	10.3	1.6	2.0	-59.2	<=8.0
2441.15	14.7	10.3	2.4	2.0	-58.4	<=8.0
2441.20	14.2	10.3	1.9	2.0	-58.9	<=8.0
2441.25	14.4	10.3	2.1	2.0	-58.7	<=8.0
2441.30	14.8	10.3	2.5	2.0	-58.3	<=8.0
2441.35	14.6	10.3	2.3	2.0	-58.5	<=8.0
2441.40	14.8	10.3	2.5	2.0	-58.3	<=8.0
2441.45	15.0	10.3	2.7	2.0	-58.1	<=8.0
2441.50	14.3	10.3	2.0	2.0	-58.8	<=8.0
2441.55	15.0	10.3	2.7	2.0	-58.1	<=8.0
2441.60	14.0	10.3	1.7	2.0	-59.1	<=8.0
2441.65	13.3	10.3	1.0	2.0	-59.8	<=8.0
2441.70	14.3	10.3	2.0	2.0	-58.8	<=8.0
2441.75	14.1	10.3	1.8	2.0	-59.0	<=8.0
2441.80	13.9	10.3	1.6	2.0	-59.2	<=8.0
2441.85	13.5	10.3	1.2	2.0	-59.6	<=8.0
2441.90	13.1	10.3	0.8	2.0	-60.0	<=8.0
2441.95	13.3	10.3	1.0	2.0	-59.8	<=8.0
2442.00	13.7	10.3	1.4	2.0	-59.4	<=8.0
2442.05	13.8	10.3	1.5	2.0	-59.3	<=8.0
2442.10	14.3	10.3	2.0	2.0	-58.8	<=8.0
2442.15	14.0	10.3	1.7	2.0	-59.1	<=8.0
2442.20	14.8	10.3	2.5	2.0	-58.3	<=8.0
2442.25	15.2	10.3	2.9	2.0	-57.9	<=8.0
2442.30	16.5	10.3	4.2	2.0	-56.6	<=8.0
2442.35	17.1	10.3	4.8	2.0	-56.0	<=8.0
2442.40	18.2	10.3	5.9	2.0	-54.9	<=8.0
2442.45	19.7	10.3	7.4	2.0	-53.4	<=8.0
2442.50	21.9	10.3	9.6	2.0	-51.2	<=8.0
2442.55	22.8	10.3	10.5	2.0	-50.3	<=8.0
2442.60	24.6	10.3	12.3	2.0	-48.5	<=8.0
2442.65	25.3	10.3	13.0	2.0	-47.8	<=8.0
2442.70	23.7	10.3	11.4	2.0	-49.4	<=8.0
2442.75	22.0	10.3	9.7	2.0	-51.1	<=8.0
2442.80	20.8	10.3	8.5	2.0	-52.3	<=8.0
2442.85	20.5	10.3	8.2	2.0	-52.6	<=8.0

**Processing Gain**

ISL37400M

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq.	Gp	(S/N)o	Mj=J/S	Lsys	Jammer	PER
(MHz)	(dB)	(dB)	(dB)	(dB)	(dBm)	(%)
2442.90	19.6	10.3	7.3	2.0	-53.5	<=8.0
2442.95	18.3	10.3	6.0	2.0	-54.8	<=8.0
2443.00	17.8	10.3	5.5	2.0	-55.3	<=8.0
2443.05	16.7	10.3	4.4	2.0	-56.4	<=8.0
2443.10	15.0	10.3	2.7	2.0	-58.1	<=8.0
2443.15	15.4	10.3	3.1	2.0	-57.7	<=8.0
2443.20	16.3	10.3	4.0	2.0	-56.8	<=8.0
2443.25	15.8	10.3	3.5	2.0	-57.3	<=8.0
2443.30	15.8	10.3	3.5	2.0	-57.3	<=8.0
2443.35	15.5	10.3	3.2	2.0	-57.6	<=8.0
2443.40	16.1	10.3	3.8	2.0	-57.0	<=8.0
2443.45	15.7	10.3	3.4	2.0	-57.4	<=8.0
2443.50	16.2	10.3	3.9	2.0	-56.9	<=8.0
2443.55	15.1	10.3	2.8	2.0	-58.0	<=8.0
2443.60	14.9	10.3	2.6	2.0	-58.2	<=8.0
2443.65	15.6	10.3	3.3	2.0	-57.5	<=8.0
2443.70	15.9	10.3	3.6	2.0	-57.2	<=8.0
2443.75	15.1	10.3	2.8	2.0	-58.0	<=8.0
2443.80	17.5	10.3	5.2	2.0	-55.6	<=8.0
2443.85	16.8	10.3	4.5	2.0	-56.3	<=8.0
2443.90	17.6	10.3	5.3	2.0	-55.5	<=8.0
2443.95	17.2	10.3	4.9	2.0	-55.9	<=8.0
2444.00	17.2	10.3	4.9	2.0	-55.9	<=8.0
2444.05	17.0	10.3	4.7	2.0	-56.1	<=8.0
2444.10	16.2	10.3	3.9	2.0	-56.9	<=8.0
2444.15	16.3	10.3	4.0	2.0	-56.8	<=8.0
2444.20	17.7	10.3	5.4	2.0	-55.4	<=8.0
2444.25	17.7	10.3	5.4	2.0	-55.4	<=8.0
2444.30	17.9	10.3	5.6	2.0	-55.2	<=8.0
2444.35	17.8	10.3	5.5	2.0	-55.3	<=8.0
2444.40	18.5	10.3	6.2	2.0	-54.6	<=8.0
2444.45	18.1	10.3	5.8	2.0	-55.0	<=8.0
2444.50	17.5	10.3	5.2	2.0	-55.6	<=8.0
2444.55	17.1	10.3	4.8	2.0	-56.0	<=8.0
2444.60	17.1	10.3	4.8	2.0	-56.0	<=8.0
2444.65	17.3	10.3	5.0	2.0	-55.8	<=8.0
2444.70	17.5	10.3	5.2	2.0	-55.6	<=8.0
2444.75	18.1	10.3	5.8	2.0	-55.0	<=8.0
2444.80	18.2	10.3	5.9	2.0	-54.9	<=8.0
2444.85	19.3	10.3	7.0	2.0	-53.8	<=8.0
2444.90	19.2	10.3	6.9	2.0	-53.9	<=8.0
2444.95	18.8	10.3	6.5	2.0	-54.3	<=8.0
2445.00	18.7	10.3	6.4	2.0	-54.4	<=8.0
2445.05	18.2	10.3	5.9	2.0	-54.9	<=8.0
2445.10	18.4	10.3	6.1	2.0	-54.7	<=8.0
2445.15	19.4	10.3	7.1	2.0	-53.7	<=8.0
2445.20	19.5	10.3	7.2	2.0	-53.6	<=8.0
2445.25	19.7	10.3	7.4	2.0	-53.4	<=8.0

1Mbps CHANNEL 6 Processing Gain						
Gp = (S/N)o + Mj + Lsys						
Freq. (MHz)	Gp (dB)	(S/N)o (dB)	Mj=J/S (dB)	Lsys (dB)	Jammer (dBm)	PER (%)
2445.30	20.1	10.3	7.8	2.0	-53.0	<=8.0
2445.35	19.3	10.3	7.0	2.0	-53.8	<=8.0
2445.40	20.2	10.3	7.9	2.0	-52.9	<=8.0
2445.45	20.3	10.3	8.0	2.0	-52.8	<=8.0
2445.50	19.8	10.3	7.5	2.0	-53.3	<=8.0

**13.2**

**Test Conditions**

TX Card **HWB3163-04 Rev B**  
 S/N **99360038**  
 RX Card **ISL37400M Rev A**  
 S/N **00500038**  
 TX Firmware **P10002C0, MS11168A3**  
 RX Firmware **ID010000, PK010001, SF010000**  
 Software Ver. **3.0.24**  
 Mode **1 MB Pseudo IBSS**  
 Pkt Size **1024**  
 Pkt Dly **1**  
 Pkt Burst **0**

Intersil Chips on Card: **ISL3984**  
**ISL3685**  
**HFA3783**  
**ISL3183**  
**ISL3874**

Processing Gain (dB)	XMIT level	-60.8
	S/N+Ls	12.3
	0dB J/S	0.0
PG	Offset	Signal Generator Delta
19.0	-8500	6.7
18.3	-8450	6.0
17.6	-8400	5.3
17.0	-8350	4.7
16.9	-8300	4.6
16.6	-8250	4.3
16.4	-8200	4.1
16.3	-8150	4.0
16.3	-8100	4.0
16.2	-8050	3.9
16.1	-8000	3.8
16.5	-7950	4.2
17.3	-7900	5.0
17.1	-7850	4.8
17.1	-7800	4.8
17.6	-7750	5.3
17.6	-7700	5.3
17.7	-7650	5.4
17.7	-7600	5.4
17.7	-7550	5.4
17.3	-7500	5.0
16.9	-7450	4.6
16.2	-7400	3.9
16.0	-7350	3.7
15.9	-7300	3.6
16.3	-7250	4.0
16.2	-7200	3.9
16.2	-7150	3.9
16.3	-7100	4.0
16.4	-7050	4.1
16.3	-7000	4.0
16.2	-6950	3.9
15.8	-6900	3.5
16.0	-6850	3.7
16.6	-6800	4.3
16.8	-6750	4.5
17.6	-6700	5.3
17.8	-6650	5.5
17.9	-6600	5.6
17.4	-6550	5.1
16.7	-6500	4.4
15.8	-6450	3.5
15.4	-6400	3.1
15.1	-6350	2.8
15.0	-6300	2.7
15.3	-6250	3.0
15.2	-6200	2.9

15.4	-6150	3.1
15.6	-6100	3.3
15.3	-6050	3.0
14.9	-6000	2.6
15.0	-5950	2.7
15.1	-5900	2.8
14.9	-5850	2.6
15.4	-5800	3.1
16.0	-5750	3.7
17.3	-5700	5.0
17.7	-5650	5.4
18.5	-5600	6.2
19.9	-5550	7.6
20.4	-5500	8.1
21.3	-5450	9.0
22.2	-5400	9.9
23.9	-5350	11.6
22.9	-5300	10.6
22.6	-5250	10.3
19.0	-5200	6.7
19.9	-5150	7.6
18.0	-5100	5.7
17.6	-5050	5.3
16.2	-5000	3.9
15.4	-4950	3.1
14.7	-4900	2.4
14.1	-4850	1.8
14.3	-4800	2.0
14.3	-4750	2.0
14.2	-4700	1.9
14.1	-4650	1.8
14.3	-4600	2.0
14.0	-4550	1.7
13.9	-4500	1.6
14.0	-4450	1.7
14.0	-4400	1.7
14.1	-4350	1.8
14.0	-4300	1.7
14.5	-4250	2.2
14.3	-4200	2.0
13.9	-4150	1.6
14.3	-4100	2.0
14.0	-4050	1.7
13.9	-4000	1.6
14.0	-3950	1.7
13.6	-3900	1.3
13.7	-3850	1.4
13.6	-3800	1.3
13.6	-3750	1.3
13.3	-3700	1.0
13.4	-3650	1.1
13.6	-3600	1.3

13.2	-3550	0.9
13.5	-3500	1.2
13.1	-3450	0.8
13.3	-3400	1.0
13.7	-3350	1.4
13.4	-3300	1.1
13.7	-3250	1.4
13.4	-3200	1.1
13.5	-3150	1.2
13.4	-3100	1.1
13.3	-3050	1.0
13.6	-3000	1.3
13.2	-2950	0.9
12.8	-2900	0.5
13.2	-2850	0.9
12.9	-2800	0.6
12.9	-2750	0.6
12.8	-2700	0.5
13.0	-2650	0.7
13.1	-2600	0.8
12.5	-2550	0.2
13.0	-2500	0.7
13.0	-2450	0.7
12.9	-2400	0.6
13.1	-2350	0.8
13.0	-2300	0.7
13.3	-2250	1.0
13.2	-2200	0.9
13.5	-2150	1.2
13.3	-2100	1.0
13.5	-2050	1.2
13.6	-2000	1.3
14.0	-1950	1.7
13.9	-1900	1.6
13.4	-1850	1.1
13.1	-1800	0.8
12.9	-1750	0.6
12.6	-1700	0.3
12.5	-1650	0.2
13.3	-1600	1.0
13.0	-1550	0.7
13.2	-1500	0.9
13.4	-1450	1.1
13.2	-1400	0.9
13.7	-1350	1.4
13.1	-1300	0.8
13.4	-1250	1.1
13.3	-1200	1.0
13.6	-1150	1.3
13.3	-1100	1.0
13.2	-1050	0.9
13.4	-1000	1.1

13.7	-950	1.4
13.7	-900	1.4
13.3	-850	1.0
13.6	-800	1.3
13.2	-750	0.9
13.1	-700	0.8
13.0	-650	0.7
12.9	-600	0.6
12.8	-550	0.5
12.5	-500	0.2
12.6	-450	0.3
12.7	-400	0.4
13.3	-350	1.0
13.2	-300	0.9
13.1	-250	0.8
14.8	-200	2.5
15.2	-150	2.9
16.3	-100	4.0
20.8	-50	8.5
19.0	0	6.7
20.4	50	8.1
20.3	100	8.0
22.8	150	10.5
21.8	200	9.5
20.4	250	8.1
19.1	300	6.8
17.9	350	5.6
16.7	400	4.4
15.5	450	3.2
15.1	500	2.8
14.4	550	2.1
13.7	600	1.4
12.7	650	0.4
12.4	700	0.1
12.0	750	-0.3
12.2	800	-0.1
12.4	850	0.1
12.5	900	0.2
12.7	950	0.4
12.1	1000	-0.2
13.2	1050	0.9
13.7	1100	1.4
13.7	1150	1.4
13.6	1200	1.3
14.1	1250	1.8
14.2	1300	1.9
14.4	1350	2.1
14.3	1400	2.0
14.2	1450	1.9
13.9	1500	1.6
13.5	1550	1.2
12.9	1600	0.6

12.2	1650	-0.1
12.4	1700	0.1
12.4	1750	0.1
12.7	1800	0.4
12.7	1850	0.4
12.1	1900	-0.2
12.2	1950	-0.1
12.3	2000	0.0
12.5	2050	0.2
13.2	2100	0.9
12.2	2150	-0.1
13.4	2200	1.1
13.6	2250	1.3
13.4	2300	1.1
13.5	2350	1.2
13.5	2400	1.2
13.7	2450	1.4
13.6	2500	1.3
13.4	2550	1.1
13.2	2600	0.9
13.7	2650	1.4
12.8	2700	0.5
12.4	2750	0.1
11.8	2800	-0.5
12.6	2850	0.3
12.4	2900	0.1
12.8	2950	0.5
12.6	3000	0.3
12.8	3050	0.5
12.7	3100	0.4
13.6	3150	1.3
13.4	3200	1.1
13.6	3250	1.3
13.9	3300	1.6
14.2	3350	1.9
14.3	3400	2.0
14.2	3450	1.9
13.9	3500	1.6
13.4	3550	1.1
13.8	3600	1.5
13.0	3650	0.7
13.3	3700	1.0
13.8	3750	1.5
13.6	3800	1.3
13.6	3850	1.3
13.2	3900	0.9
13.8	3950	1.5
13.9	4000	1.6
13.7	4050	1.4
13.9	4100	1.6
14.7	4150	2.4
14.2	4200	1.9

14.4	4250	2.1
14.8	4300	2.5
14.6	4350	2.3
14.8	4400	2.5
15.0	4450	2.7
14.3	4500	2.0
15.0	4550	2.7
14.0	4600	1.7
13.3	4650	1.0
14.3	4700	2.0
14.1	4750	1.8
13.9	4800	1.6
13.5	4850	1.2
13.1	4900	0.8
13.3	4950	1.0
13.7	5000	1.4
13.8	5050	1.5
14.3	5100	2.0
14.0	5150	1.7
14.8	5200	2.5
15.2	5250	2.9
16.5	5300	4.2
17.1	5350	4.8
18.2	5400	5.9
19.7	5450	7.4
21.9	5500	9.6
22.8	5550	10.5
24.6	5600	12.3
25.3	5650	13.0
23.7	5700	11.4
22.0	5750	9.7
20.8	5800	8.5
20.5	5850	8.2
19.6	5900	7.3
18.3	5950	6.0
17.8	6000	5.5
16.7	6050	4.4
15.0	6100	2.7
15.4	6150	3.1
16.3	6200	4.0
15.8	6250	3.5
15.8	6300	3.5
15.5	6350	3.2
16.1	6400	3.8
15.7	6450	3.4
16.2	6500	3.9
15.1	6550	2.8
14.9	6600	2.6
15.6	6650	3.3
15.9	6700	3.6
15.1	6750	2.8
17.5	6800	5.2



### Processing Gain Channel 6 (fc=2437MHz) @ 1Mbps

