

RF Exposure / SAR Statement

No. : 26GE0296-HO-1a

Applicant : FUJITSU TEN Limited
Type of Equipment : DISPLAY
Model No. : BT007A
FCC ID : BABBT007A

FUJITSU TEN Limited declares that Model : BT007A
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.
The “BT007A” has 0.52 mW of conducted Peak Output power and 0.4 mW of EIRP.
This kind of equipment is below 60/frequency[GHz] mW(TCB Exclusion List)
so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “BT007A” as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 0.52 mW (Maximum peak output power)
G = 0.77 Numerical Antenna gain; equal -1.14 dBi
r = 20.0 cm

For: BT007A

$$S = 0.00008 \text{ mW/cm}^2$$