

**Application for Certification
For an RF Power Amplifier**

**TPL Communications
3370 San Fernando Road, Suite 206
Los Angeles, CA 90065**

RF Power Amplifier:

Part # PA6-1AE-MAS

FCC ID: BBD6-1AE-MAS

REPORT # RV38004D

This report was prepared in accordance with the requirements of the FCC Rules and Regulations Part 2, Subpart J, 2.1031 through 2.1057, and Part 90 and other applicable sections of the rules as indicated herein.

Prepared By:

C. L. Payne III

**DNB Engineering, Inc.
5969 Robinson Avenue
Riverside, Ca 92503-8620**

4 June 2003

TABLE OF CONTENTS

Section Sheet

	Title	Page
1.0	ADMINISTRATIVE DATA	3
1.1	Certifications and Qualifications	3
1.2	Measurements and Repeatability Information	3

Note:

Paragraph numbers in this report follow the application section numbers found in the FEDERAL COMMUNICATIONS COMMISSION Rules and Regulations, Part 2, Subpart J for Certification of electronic equipment.

2.1033 (C) (1)	Application for Certification	4
2.1033 (C) (2)	FCC Identifier	5
2.1033 (C) (3)	Installation and Operating Instructions (Service manual)	6-20
2.1033 (C) (4)	Type of Emissions	21
2.1033 (C) (5)	Frequency Range	22
2.1033 (C) (6)	Operating Power	23
2.1033 (C) (7)	Maximum Power Allowed in Applicable part(s) of the Rules	24
2.1033 (C) (8)	Final RF Amplifier Input Power Characteristics	25
2.1033 (C) (9)	Tune Up Procedure	26
2.1033 (C) (10)	Schematic Diagram and Circuit Description	27-28
2.1033 (C) (11)	Equipment Identification Plate	29
2.1033 (C) (12)	Equipment Photographs (Internal)	30-33
2.1033 (C) (12)	Equipment Photographs (External)	34-39
2.1033 (C) (13)	Digital Modulation Techniques	40
2.1033 (C) (14)	Test Data	41
	Test Set-Up	42-43
2.1046	Measurement of RF Power Output	44-45
2.1049	Measurement of Occupied Bandwidth	46-47
2.1051	Spurious Emissions at Antenna Terminals	48-50
2.1053	Measurement of Field Strength of Spurious Radiation	51-52
2.1055	Measurement of Frequency Stability	53
2.1057	Frequency Spectrum to be Investigated	54
	RF Exposure	55
	Test Equipment Log	56

1.0 ADMINISTRATIVE DATA

1.1 Certifications and Qualifications

I certify that DNB Engineering, Inc conducted the tests performed in order to obtain the technical data presented in this application. Also, based on the results of the enclosed data, I have concluded that the equipment tested meets or exceeds the requirements of the Rules and Regulations governing this application.

1.2 Measurement Repeatability Information

The test data presented in this report has been acquired using the guidelines set forth in FCC Part 2.1031 through 2.1057, and Part 90. The test results presented in this document are valid only for the equipment identified herein under the test conditions described. Repeatability of these test results will only be achieved with identical measurement conditions. These conditions include: The same test distance, EUT Height, Measurement Site Characteristics, and the same EUT System Components. The system must have the same Interconnecting Cables arranged in identical placement to that in the test set-up, with the system and/or EUT functioning in the identical mode of operation (i.e. software and so on) as on the date of the test. Any deviation from the test conditions and the environment on the date of the test may result in measurement repeatability difficulties.

All changes made to the EUT during the course of testing as identified in this test report must be incorporated into the EUT or identical models to ensure compliance with the FCC regulations.



C. L. Payne III (Para. 1.1)
Manager, Commercial Products.
DNB Engineering, Inc.
Tel. (909) 637-2630
Fax (909) 637-2704
E-mail Les@dnbenginc.com

2.1033 (C) (1) Application for Certification

Name of Applicant: TPL Communications
3370 San Fernando Road, Suite 206
Los Angeles, Ca 90065

FRN: 0008271447

Applicant is: Manufacturer
Vendor
Licensee
Prospective Licensee
Other

Name of Manufacturer TPL Communications

Description: RF Power Amplifier

Part Number: PA6-1AE-MAS

Anticipated Production Quantity: Multiple Units

Applicable FCC Parts: 90

FCC ID No: BBD6-1AE-MAS

FCC Emissions Designator: F3E

Frequency Range: 450 – 512 MHz

Rated Output Power: 70-100W

2.1033 (C) (2) FCC Identifier

FCC ID: BBD6-1AE-MAS

2.1033 (C) (4) Type of Emission

N/A (FM Modulation)

Emission Designator: F3E

2.1033 (C) (5) Frequency Range

400-512MHz (Factory set for 460MHz)

2.1033 (C) (6) Operating Power

70 - 100 Watts

2.1033 (C) (7) Maximum Power Allowed in Applicable Part(s) of the Rules

<u>RULES PART</u>	<u>MAXIMUM POWER (WATTS)</u>
Part 90.205(q)	120

2.1033 (C) (11) Equipment Identification Plate



NOTES:


Label will be constructed of 0.02 inch aluminum as shown on the equipment with permanent adhesive.

All information on the label will be etched or stamped. Both methods will exceed the expected lifetime of the equipment.

The label will be large enough to allow all information to be legible.


2.1033 (C) (12) Equipment Photographs - Internal

Photo 1 Detail View – Internal – Component Side of PCB




2.1033 (C) (12) Equipment Photographs - Internal

Photo 2 Detail View – Internal – Component Side of PCB – Close Up




2.1033 (C) (12) Equipment Photographs - Internal

Photo 3 Detail View – Internal – Circuit Side of PCB



2.1033 (C) (12) Equipment Photographs - Internal

Photo 4 Detail View – Internal – Circuit Side of PCB – Close Up



2.1033 (C) (12) Equipment Photographs - External

Photo 5 Detail View – External – Front



2.1033 (C) (12) Equipment Photographs - External

Photo 6 Detail View – External – Left Side




2.1033 (C) (12) Equipment Photographs - External

Photo 7 Detail View – External - Rear



2.1033 (C) (12) Equipment Photographs - External

Photo 8 Detail View – External – Right Side



2.1033 (C) (12) Equipment Photographs - External

Photo 9 Detail View – External - Top



2.1033 (C) (12) Equipment Photographs - External

Photo 10 Detail View – External - Bottom




2.1033 (C) (13) Digital Modulation Techniques

Not Applicable

2.1033 (c) (14) Test Data

Refer to 2.1046 through 2.1057

2.1033 (c) (14) FIGURE 1: Block Diagram



2.1033 (c) (14) Photograph of Test Set Up



2.1046

Measurement of RF Power Output

Definition: For RF Amplifiers.

Test Method: See FIGURE 1.



Output Power is measured across a precision 50 ohm load with a Spectrum Analyzer. For the power measurement, CW (no modulation) is used.

Test Results:

POWER OUTPUT MEASURED AT NOMINAL VOLTAGE WAS:

<u>Frequency (MHz)</u>	<u>Power (dBm)</u>	<u>Power (W)</u>
460	50.0	100.00

	5969 Robinson Avenue Riverside, CA 92503 (909) 637-2630 FAX (909) 637-2704	Output Power	
DNB Job Number:	38004	Date: July 17, 2002	
Customer:	TPL Communications	Conformance Standards [X] FCC Part 15 [X] FCC Part 90	
Model Number:	PA6-1AE-MAS		Serial Number: 1000
Description:	RF Amplifier		



2.1049 Measurement of Occupied Bandwidth

Definition:

Occupied Bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are equal to 0.5 percent of the total mean power radiated by a given emission.



Test Method: Connect the Equipment per FIGURE 1.

Measurements were made while modulation the driving source with a FM signal.

Test Results: See Plots

The center frequency of the signal did not shift with modulation. The Spectrum Bandwidth was well within the limits specified in the FCC Regulations.

	5969 Robinson Avenue Riverside, CA 92503 (909) 637-2630 FAX (909) 637-2704	Occupied Bandwidth	
DNB Job Number:	38004	Date:	July 17, 2002
Customer:	TPL Communications		
Model Number:	PA6-1AE-MAS	Serial Number:	1000
Description:	RF Amplifier		Conformance Standards <input checked="" type="checkbox"/> FCC Part 15 <input checked="" type="checkbox"/> FCC Part 90



2.1051 Spurious Emissions at Antenna Terminals

Definition:

Conducted Spurious Emissions are emissions at the antenna terminals on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communication desired. The reduction in the level of these spurious emissions will not affect the quality of the information being transmitted.

Conducted Spurious Emissions shall be attenuated below the maximum level of the carrier frequency in accordance with the following formula:

$$\text{Spurious attenuation in dB} = 43 + 10 \log_{10} P_o$$

Where P_o = Output in Watts (CW)

$$= 43 + 10 \log_{10} (100)$$

$$= 63.0 \text{ dB}$$

Test Method: Per EIA RS 152-B, Paragraph 4 as modified below.

Connect the equipment as shown in FIGURE 1.


Adjust the drive source to produce FM modulation. Adjust the Spectrum Analyzer to display the Modulated Carrier.

Scan the frequency spectrum from the lowest radio frequency generated in the equipment through the 10th harmonic of the carrier frequency.


Test Results: See Plots

All spurious emissions at the antenna terminals are below the FCC specifications

	<p>5969 Robinson Avenue Riverside, CA 92503 (909) 637-2630 FAX (909) 637-2704</p>	<p>Antenna Conducted Spurious</p>
DNB Job Number:	38004	Date: July 17, 2002
Customer:	TPL Communications	
Model Number:	PA6-1AE-MAS	Serial Number: 1000
Description:	RF Amplifier	



	5969 Robinson Avenue Riverside, CA 92503 (909) 637-2630 FAX (909) 637-2704	Antenna Conducted Spurious	
DNB Job Number:	38004	Date:	July 17, 2002
Customer:	TPL Communications		
Model Number:	PA6-1AE-MAS	Serial Number:	1000
Description:	RF Amplifier		Conformance Standards <input checked="" type="checkbox"/> FCC Part 15 <input checked="" type="checkbox"/> FCC Part 90



2.1053 Field Strength of Spurious Radiation

Definition:

Emissions from the equipment when connected into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communication desired. The reduction in the level of these spurious emissions will not affect the quality of the information being transmitted.

Test Method: Per EIA RS 152-B.

Connect the equipment and follow the procedure described in paragraph 2.2.1.1 and paragraph 5.0. Measure the amplitude of each spurious radiated signal through the 10th harmonic. The spurious signals are then measured on the 3 meter range.

$$\text{Spurious attenuation in dBc} = 43 + 10 \log_{10} P_o$$

Where P_o = Output in Watts (CW)

$$= 43 + 10 \log_{10} (100)$$

$$= 63.0 \text{ dBc}$$

Test Results: All readings were at the spectrum analyzer ground floor above the fundamental.

All radiated spurious emissions are below the FCC Specifications.

		5969 Robinson Avenue Riverside, CA 92503 (909) 637-2630 FAX (909) 637-2704	Radiated Spurious	
DNB Job Number:		38004	Date: August 1, 2002	
Customer:		TPL Communications		Conformance Standards <input checked="" type="checkbox"/> FCC Part 15 <input checked="" type="checkbox"/> FCC Part 90
Model Number:		PA6-1AE-MAS	Serial Number: 1000	
Description:		RF Amplifier		

Freq (MHz)	Measured Signal (dBuV)	AF (dB/m)	Cable Loss (dB)	Pre-Amp Gain (dB)	Corrected Reading (dBuV/m)	Fundamental Field Strength (dBuV/m)	Spurious Below Carrier (dBc)	FCC Limit (dBc)	Antenna Polar
920	43.4	24.4	0.86	0	68.66	151	82.34	63	H
1380	55.0	25.6	1.10	0	81.50	151	69.50	63	H
1840	54.5	28.1	1.40	0	83.90	151	67.10	63	H
2300	31.1	29.3	1.60	0	62.00	151	89.00	63	H
2760	28.3	30.7	1.70	0	60.70	151	90.30	63	H
3220	26.9	31.8	1.90	0	60.60	151	90.40	63	H
3680	27.0	32.7	2.00	0	61.70	151	89.30	63	V
4140	33.4	33.4	2.20	0	68.10	151	82.90	63	V
4600	30.5	33.8	2.40	0	66.70	151	84.30	63	H

2.1055 Measurement of Frequency Stability

The EUT is a power amplifier and contains no circuitry for generating or stabilizing the RF signal. The driver will be responsible for this task.

2.1057 Frequency Spectrum to be Investigated

The Frequency was searched from the lowest radio frequency generated in the equipment through the 10th harmonic of the carrier frequency.

RF Exposure

The information contained in “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65; August 1997 is applicable when a radiating antenna is connected to this amplifier. Paging stations that utilize this amplifier authorized under Part 22 (Subpart E) and Part 90 are subject to routine environmental evaluation for RF exposure if an antenna is located on a rooftop and if its ERP exceeds 1000 watts.

This product is certified to meet the RF exposure guidelines of OET-65 as a stand-alone RF power amplifier. The RF spurious emissions recorded when the antenna output connector is terminated into a non-radiating 50 ohm load do not exceed the 27.5 V/m limit specified for General Population/Uncontrolled Exposure in OET Bulletin 65.

Test Equipment Log

Item No:	Description	Manufacturer	M/N	S/N	Calibration Due Date	Test Equip Used On
1	Push/Pull Scale	Imada	MF	70403	5/30/03	
2	Power Analyzer	Voltech	PM3000A	1273	5/7/03	Harm / Flick
3	Digital MultiMeter	Chief Engineer	104	31220125	8/26/03	
4	Digital MultiMeter	Amprobe	AM-1250	330224	10/24/03	
5	LCR Meter	B & K Precision	878	23702237	10/24/03	
6	Digital MultiMeter	Amprobe	AM-1250	330139	8/6/03	
7	Dial Caliper	General MG	MG 6"	958	12/2/03	
8	Micrometer	General MG	1050C	959	12/2/03	
9	Impact Hammer	E.D. & D.	F22-50	9606235-3	11/6/03	
10	Process Meter	Newport	INFCP-210	4381880	4/5/03	
11	Process Meter	Newport	INFCP-210	6150730	4/5/03	
12	Oscilloscope	Tektronix	464	B133241	9/16/03	
13	Line Leakage Tester	Associated Research	510L	A130511	4/19/03	
14	Safety Compl Analyzer	Associated Research	7564SA	A100601	4/19/03	
15	AC/DC Current Probe	Amprobe	CT600	30301828	4/9/03	
16	Data Acquisition Unit	Hewlett Packard	34970A	US37017024	4/29/03	
17	Data Acquisition Unit	Hewlett Packard	34970A	US37016877	5/21/03	
18	Input Multiplexer	Hewlett Packard	34901A	US37017773	5/21/03	
19	Input Multiplexer	Hewlett Packard	34901A	US37017729	5/21/03	
20	Input Multiplexer	Hewlett Packard	34901A	US37019488	5/4/03	
21	Weather Station	Davis	7400	PC70804A01	1/29/03	All Tests
22	Safety Analyzer	Dynatech Nevada	431A	431A-1230	4/12/03	
23	SA - RF Section	Hewlett Packard	85680B	2330A02791	8/27/03	CE / RE / CS
24	SA - Display Section	Hewlett Packard	85662A	2318A05282	8/27/03	CE / RE / CS
25	RF Preselector	Hewlett Packard	85685A	2724A00659	8/26/03	CE / RE / CS
26	QP Adapter	Hewlett Packard	85650A	2811A01240	8/27/03	CE / RE / CS
27	SA - RF Section	Hewlett Packard	85680B	2049A01403	6/14/03	CE / RE / CS
28	SA - Display Section	Hewlett Packard	85662A	2112A02234	6/14/03	CE / RE / CS
29	QP Adapter	Hewlett Packard	85650A	2043A00184	6/14/03	CE / RE / CS
30	ESD Power Supply/Gun	Haefely	PSD 25 B	083 427-05	3/29/03	ESD
31	ESD Simulator	Haefely	PESD3000	H002033	6/13/03	ESD
32	Signal Source 9Khz-2Ghz	Marconi	2024	112231/034	2/2/03	RS / CS
33	Scale 300lb Capacity	Hanson	8930	1403	6/3/03	
34	Scale 25lb Capacity	Hanson	40	1402	4/26/03	
35	Precision Torque Gauge	SeeKonik	SL-12	967	7/9/03	
36	Precision Torque Wrench	Husky	39104	4980656019	7/18/03	
37	Step Attenuator 120dB	Hewlett Packard	355D	2522A43896	10/25/03	As Req'd
38	Step Attenuator 12dB	Hewlett Packard	355C	2524A42578	10/25/03	As Req'd
39	Oscilloscope	LeCroy	9400	85584	2/26/03	Surg / EFT/ ESD
40	Pressure Gauge	Ashcroft	0-30 PSI	1500	9/13/03	
41	Pressure Gauge	Ashcroft	0-30 PSI	1501	9/13/03	
42	Pressure Gauge	Ashcroft	0-30 PSI	1502	9/13/03	
43	Artificial Mains Network	Schwarzbeck	NNLA 8120	8120288	6/13/03	CE / CS
44	A.C. Leakage Current Tstr	Simpson	229-2	948	10/28/03	
45	Leakage Current tester	Simpson	228	709721	10/28/03	
46	Insulation Tester	Amprobe	AMB-1A	340055	10/28/03	
47	Hypot Tester	Beckman	P-2B	64999	10/29/03	
48	Ground Continuity Tester	Rod-I	M25	12485	10/29/03	
49	Digital MultiMeter	Di-log	DL-297T	23702237	11/13/03	
50	Probe	Omega	HX94V		4/5/03	
51	LISN	ComPower Corp	L1-300	1331	5/13/03	CE / CS
52	LISN	ComPower Corp	L1-300	1373	5/13/03	CE / CS

* When necessary, equivalent calibrated equipment may be substituted for the equipment listed here.