

2.983(h) **Description and Test Data For Encoding Device(s)**

This section does not apply.

2.983(i) **Type acceptance Data For an External Power
Amplifier Used In Amateur Radio Service - Part 97**

This section does not apply

APPENDIX A
TEST EQUIPMENT

DNB ENGINEERING, INC. EMC TEST EQUIPMENT

<u>MANUFACTURER</u>	<u>DESCRIPTION</u>	<u>MODEL</u>
Hewlett Packard	Spectrum Analyzer	8566B
Hewlett Packard	Spectrum Analyzer	8568B
Hewlett Packard	Quasi Peak Adapter	85650A
Hewlett Packard	Computer/Controller	9825T
Hewlett Packard	Frequency Counter	5245L
Hewlett Packard	Printer	9876A
Hewlett Packard	Counter Plug-in	5253B
Hewlett Packard	Plotter	9872C
Hewlett Packard	Plotter	7470A
Hewlett Packard	Frequency Synthesizer	9662A
Hewlett Packard	Sweep Main Frame	8620C
Hewlett Packard	Plug-in 2-22 GHz	26290B
Polarad	Signal Generator 3.7 to 8.4 GHz	1107E
Telonics	Sweep Generator	4053A
Wiltron	Sweep Generator	6653A
Hewlett Packard	Signal Generator	614A
Hewlett Packard	Signal Generator	616B
Hewlett Packard	Signal Generator	618B
Hewlett Packard	Signal Generator	620B
Hewlett Packard	Signal Generator	626A
Hewlett Packard	Signal Generator	628A
Hewlett Packard	Signal Generator	8654A

DNB ENGINEERING, INC.

EMC TEST EQUIPMENT

Hewlett Packard	Signal Generator	8662A
Hewlett Packard	RF Voltmeter	3406A
Solar	Pulse Generator	8282-1
Solar (2)	Clamp on Probe	6747-1
Electro-Metrics	Clamp on Probe	PCL-10
Electro-Metrics	Clamp on Probe	PCL-25
Electro-Metrics	Loop Sensor	ELS-10
Electro-Metrics	Electro-Static Field Probe	EFP-25
Electro-Metrics	LISN	FCC-5-2
Solar	LISN	8012-50-r-24 BNC
Solar	Audio Isolation Transformer	6220-1A
Solar	Isolation Transformer	7032-1
Solar (14)	10 mfd Capacitors	6212-106R
Schaffner EMC, Inc.	Absorbing Clamp	MDS 21
Solar	100 W Audio Amplifier	6552-1A
Solar (2)	LISN	8018-50-TS-24 BNC
Stoddart	FIM	NM-12T
Krohn-Hite	Audio Oscillator	4400
Stoddart	FIM	URM-6
IFI	Field Strength Meter	EFS-1
Solar	Precision Resistor	7144-1.0
Solar	Precision Resistor	7144-10.0
Solar	Coupling Network	7835-891

DNB ENGINEERING, INC. EMC TEST EQUIPMENT

Solar	Coupling Network	7835-896
Solar	LISN (5 μ h)	6338-5
Solar	LISN (50 μ h)	6338-57
Solar	High Pass Filter	7205-.35
Solar	High Pass Filter	7205-2.4
Mini Circuits	Amplifier Wide Band	ZHL42
Mini Circuits	Amplifier Wide Band	ZHL-1042J
Mini Circuits	Amplifier Wide Band	ZHL32A
Mini Circuits	Amplifier Wide Band	ZHL-1A
Mini Circuits	Amplifier Wide Band	ZHL2-8
ENI	Amplifier	510L
ENI	Amplifier	350L
Hewlett Packard	Preamplifier	11975A
Hewlett Packard	Preamplifier	8349A
IFI	1 kHz - 200 MHz Amplifier (15 Watt)	5300L
Narda	400 W 50 Ω Load	376NM
Eaton	WBA 500 - 1000 MHz	15100B
ENI	WBA 250 KHz - 150 MHz	3100LA
ENI	WBA 1.5 - 500 MHz	5501
Avantek	Low Noise Amplifier 6-12.4 GHz	AFT12635
Hewlett Packard	500 MHz Digitizing Oscilloscope	54111D
Tenney	Temperature Chamber	THjr

DNB ENGINEERING, INC. EMC TEST EQUIPMENT

Hewlett Packard	5 Hz - 200 MHz Network Analyzer	3577A
Hewlett Packard	Frequency Doubler	11721A
Hewlett Packard	Harmonic Mixers	11970A
Hewlett Packard	Harmonic Mixers	11970K
Hewlett Packard	Computer/Controller	9836
Hewlett Packard	Computer/Controller	9826
Avantest	Spectrum Analyzer	TR4131E
Hewlett Packard	Spectrum Analyzer	8558B
Hewlett Packard	Spectrum Analyzer	8554L
Hewlett Packard	Pulse Generator	212A
Hewlett Packard	Pulse Generator	214A
Hewlett Packard	Pulse Generator	215A
Tektronix	Oscilloscope	453A
John Fluke	High Voltage power Supply	408A
LeCroy	Digital Storage Scope (125 MHz)	9400
Biddle	Micro Ohm Meter	247800
Hewlett Packard	Pulse Modulator	11720A
Topaz	Ultra Isolation Transformer (2.5 kVA)	0211T21SR
ENI	Ultra Isolation Transformer (2.5 kVA)	91002-22
Singer (5)	Current Probe	91550-2
Stoddart (4)	Current Probe	91550-1

DNB ENGINEERING, INC. EMC TEST EQUIPMENT

Hewlett Packard	Dual Directional Coupler	778D
Narda	Dual Directional Coupler	3022
Narda	Directional Coupler	3045C-20
Narda	Directional Coupler	3003-20
Narda	Directional Coupler	3002-10
Narda	Directional Coupler	23964
Narda (2)	Directional Coupler	22355
Narda	Power Divider	4326-2
Narda	Power Divider	4035C
Narda	Power Divider	4033C
Englemann	Power Divider	PSK-210
Bird	50 Ω Load 10 W 50's	80-53
Stoddart	50 Ω Load	90514
Micro Lab	50 Ω Load	TB-5MN
Tekscan	50 Ω Attenuator Kit	FP-50
Tenuline	50 Ω 100 W 20 dB Attenuator	8343-200
Micro Lab	50 Ω 40 dB Attenuator	AD-40N
Hughes	20 Watt TWT L Band	1277H04
Hughes	20 Watt TWT C Band	1277H04
Hughes	10 Watt TWT S Band	1177H
Hughes	10 X/Ku Band	1177H
IFI	2kW cw 1 kHz - 200 MHz Wide Band Power Amp	410ULP
DNB Engineering	EMP Pin/Wire Test Set	844

DNB ENGINEERING, INC.

EMC TEST EQUIPMENT

ANTENNAS

<u>MANUFACTURER</u>	<u>DESCRIPTION</u>	<u>MODEL</u>
AIL (3)	Dipole	DM105A-T1, T2, & T3
EMCO	Biconical	3109
EMCO	Log Periodic	3146
EMCO	Parallel Element	3107
Eaton	Vertical Rod	74607-1
Eaton (2)	Vertical Rod	75492-1
Ailtech	Loop	94608-1
Singer	Loop	LP-105 ASC
Electro-Metrics (2)	Biconical	BIA-25
Electro-Metrics (2)	Conical Log Spiral	LCA-25
Electro-Metrics (2)	Loop	ALP-10
Electro-Metrics (2)	Loop	ARL-25
Electro-Metrics (2)	Broadband Dipole	DBA-25
Electro-Metrics (3)	Turnable Dipole	TA-25, 25-1, & 25-2
EMCO	Double Ridge Guide	311525
Electro-Metrics (2)	Vertical Rod	RVR-25
Alpha	Standard Gain Horn	K861
Alpha	Standard Gain Horn	A861
Alpha	Standard Gain Horn	KV861
Solar	Loop Antenna	7429-1
Electro-Metrics	E Field SensorHorn	EFP-25

APPENDIX B
OPERATING/SERVICE/INSTRUCTION MANUAL

GENERAL SPECIFICATIONS

800/900 Mhz Band RF Power Amplifiers

FREQUENCY RANGE: 806 - 960 MHz

BANDWIDTH: 15 MHz, 60 MHz available on some models.

OPERATING MODE: FM

MODEL	POWER INPUT	POWER OUTPUT	NOMINAL CURRENT DRAIN	FUSE
PA8-1AC	1-5W	35-75W	12 AMPS	20 AMPS
PA8-1DC	5-15W	35-75W	10 AMPS	20 AMPS
PA8-1DD	5-15W	70-90W	18 AMPS	25 AMPS
PA8-1FD	20-40W	70-90W	14 AMPS	25 AMPS

OPERATING TEMPERATURE RANGE: -30° to +60° Celsius

OPERATING VOLTAGE: Minimum 11 VDC, maximum 15 VDC, as measured at the DC input connector. Rated voltage is 13.8 Volts and all specifications are given at 13.8 Volts. Reduced DC voltage will result in a decrease in power output and efficiency. Standby current is less than 3 mA.

EIA DUTY CYCLE: 100%.

RECEIVER INSERTION LOSS: 1 dB Maximum over 60 MHz bandwidth when optional receive relay is specified.

HARMONIC ATTENUATION: Models meet or exceed FCC requirements.

CONNECTORS: TYPE N Female RF input and output. DC input is a two terminal barrier strip unless unit is supplied with an AC power supply.

MOUNTING: These amplifiers are normally supplied with the -RF rack mounted heat sink. See next page.