




	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## DECLARATION OF COMPLIANCE - SAR RF EXPOSURE EVALUATION (FCC)


<b>Test Lab Information</b>	<b>Name</b>	<b>CELLTECH LABS INC.</b>			
	<b>Address</b>	21-364 Lougheed Road, Kelowna, British Columbia V1X 7R8 Canada			
<b>Applicant Information</b>	<b>Name</b>	<b>COBRA ELECTRONICS CORPORATION</b>			
	<b>Address</b>	6500 West Cortland Street, Chicago, IL 60707 United States			
<b>Standard(s) Applied</b>	<b>FCC</b>	47 CFR §2.1093			
<b>Procedure(s) Applied</b>	<b>FCC</b>	OET Bulletin 65, Supplement C (Edition 01-01) KDB 447498 D01v04			
	<b>IEEE</b>	1528-2003			
<b>Device Classification(s)</b>	<b>FCC</b>	Part 95 Family Radio Face Held Transmitter (FRF)			
<b>Application Type</b>	<b>FCC</b>	TCB Certification			
<b>Device Identifier(s)</b>	<b>FCC ID:</b>	BBO1102B			
<b>Device Model(s)</b>	CXT275, CXT225 (only difference is added charging contacts on bottom of CXT275 case)				
<b>Test Sample Serial No.</b>	None (Identical Prototype) - Model CXT275 provided for test sample				
<b>Software Revision No.</b>	T225_V08.h16				
<b>Firmware Revision No.</b>	V08				
<b>Date of Sample Receipt</b>	March 02, 2011				
<b>Date(s) of Evaluation</b>	March 04, 2011				
<b>Device Description</b>	Portable FM UHF GMRS/FRS Push-To-Talk (PTT) Radio Transceiver				
<b>Transmit Frequency Range(s)</b>	462.5500 - 462.7250 MHz (GMRS Channels 15-22)				
	462.5625 - 462.7125 MHz (GMRS/FRS Channels 1-7)				
	467.5625 - 467.7125 MHz (FRS Channels 8-14)				
<b>RF Output Power Tested</b>	0.9 Watts	29.5 dBm	Conducted	462.7250 MHz	GMRS Ch. 22
<b>Battery Type(s) Tested</b>	Ni-MH Battery	4x AAA	1.2 V	300 mAh	
	Alkaline Battery	4x AAA	1.5 V	Energizer Industrial	
<b>Antenna Type(s) Tested</b>	External Non-detachable				
<b>Body-worn Accessories Tested</b>	Plastic Belt-Clip (supplied with DUT)				
<b>Audio Accessories Tested</b>	Ear-bud with Lapel-Microphone & PTT (P/N: GA-EBM2)				
<b>Max. SAR Level(s) Evaluated</b>	Face-held	0.585 W/kg	1g	50% duty cycle	General Population / Uncontrolled
	Body-worn	1.08 W/kg	1g	50% duty cycle	General Population / Uncontrolled
<b>FCC Spatial Peak SAR Limit</b>	Head/Body	1.6 W/kg	1g	50% duty cycle	General Population / Uncontrolled
<p>Celltech Labs Inc. declares under its sole responsibility that this wireless portable device has demonstrated compliance with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 for the General Population / Uncontrolled Exposure environment. The device was tested in accordance with the measurement procedures described in FCC OET Bulletin 65, Supplement C (Edition 01-01) and IEEE Standard 1528-2003. All measurements were performed in accordance with the SAR system manufacturer recommendations.</p> <p>I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.</p> <p>The results and statements contained in this report pertain only to the device(s) evaluated.</p> <p>This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc.</p>					
<b>Test Report Approved By</b>			<b>Sean Johnston</b>	<b>Lab Manager</b>	<b>Celltech Labs Inc.</b>



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 1 of 41

 Testing and Engineering Services Lab	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## TABLE OF CONTENTS

1.0 INTRODUCTION	4
2.0 SAR MEASUREMENT SYSTEM	4
3.0 RF CONDUCTED OUTPUT POWER MEASUREMENTS	4
4.0 FLUID DIELECTRIC PARAMETERS	5
FLUID DIELECTRIC PARAMETERS (CONT.)	6
5.0 SAR MEASUREMENT SUMMARY	7
6.0 DETAILS OF SAR EVALUATION	8
7.0 SAR EVALUATION PROCEDURES	8
8.0 SYSTEM PERFORMANCE CHECK	9
9.0 SAR PROBE CALIBRATION & MEASUREMENT FREQUENCIES	10
10.0 SIMULATED EQUIVALENT TISSUES	10
11.0 SAR LIMITS	10
12.0 ROBOT SYSTEM SPECIFICATIONS	11
13.0 PROBE SPECIFICATION (ET3DV6)	12
14.0 SIDE PLANAR PHANTOM	12
15.0 BARKSI PLANAR PHANTOM	12
16.0 DEVICE HOLDER	12
17.0 TEST EQUIPMENT LIST	13
18.0 JUSTIFICATION FOR EXTENDED SAR DIPOLE CALIBRATION	13
19.0 MEASUREMENT UNCERTAINTIES	14
20.0 REFERENCES	15
APPENDIX A - SAR MEASUREMENT DATA	16
APPENDIX B - SYSTEM PERFORMANCE CHECK DATA	23
APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS	28
APPENDIX D - SAR TEST SETUP & DUT PHOTOGRAPHS	31
APPENDIX E - DIPOLE CALIBRATION	39
APPENDIX F - PROBE CALIBRATION	40
APPENDIX G - BARKSI PLANAR PHANTOM CERTIFICATE OF CONFORMITY	41

<b>Applicant:</b>	Cobra Electronics Corporation	<b>FCC ID:</b>	BBO1102B	<b>Model(s):</b>	CXT275, CXT225	
<b>DUT Type:</b>	Portable GMRS/FRS PTT Radio Transceiver		<b>Frequency Range:</b>	462.5500 - 467.7125 MHz		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 2 of 41


	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	



#### REVISION HISTORY

REVISION NO.	DESCRIPTION	IMPLEMENTED BY	RELEASE DATE
1.0	Initial Release	Jon Hughes	March 10, 2011

#### TEST REPORT SIGN-OFF

DEVICE TESTED BY	REPORT PREPARED BY	QA REVIEW BY	REPORT APPROVED BY
Sean Johnston	Sean Johnston	Jon Hughes	Sean Johnston

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## 1.0 INTRODUCTION


This measurement report demonstrates that the Cobra Electronics Corporation Models: CXT275, CXT225 Portable FM UHF GMRS/FRS PTT Radio Transceiver complies with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]) for the General Population / Uncontrolled Exposure environment. The measurement procedures described in FCC OET Bulletin 65, Supplement C 01-01 (see reference [2]) and IEEE Standard 1528-2003 (see reference [3]) were employed. A description of the device, operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used and the various provisions of the rules are included within this test report.



## 2.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for head and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot utilizes a controller with built in VME-bus computer.

## 3.0 RF CONDUCTED OUTPUT POWER MEASUREMENTS

MEASURED RF CONDUCTED OUTPUT POWER						
Mode	Frequency	Channel	Modulation	Power Setting	dBm	Watts
GMRS	462.7250 MHz	22	Unmodulated (Continuous Wave)	High	29.5	0.900
<b>Notes</b> 1. The RF conducted output power level of the DUT was measured by Celltech prior to the SAR evaluations using a Gigatronics 8652A Universal Power Meter in accordance with FCC 47 CFR §2.1046 (see reference [9]).						

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 4 of 41


	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	



Test Lab Certificate No. 2470.01

## 4.0 FLUID DIELECTRIC PARAMETERS

FLUID DIELECTRIC PARAMETERS						
Date: 03/04/2011		Frequency: 450 MHz			Tissue: Head	
Freq	Test_e	Test_s	450 MHz Target_e	450 MHz Target_s	Deviation Permittivity	Deviation Conductivity
0.35	45.58	0.77	43.5	0.87	4.78%	-11.49%
0.36	45.52	0.78	43.5	0.87	4.64%	-10.34%
0.37	45.05	0.79	43.5	0.87	3.56%	-9.20%
0.38	45.54	0.8	43.5	0.87	4.69%	-8.05%
0.39	44.64	0.81	43.5	0.87	2.62%	-6.90%
0.4	44.61	0.82	43.5	0.87	2.55%	-5.75%
0.41	44.33	0.83	43.5	0.87	1.91%	-4.60%
0.42	44.54	0.83	43.5	0.87	2.39%	-4.60%
0.43	44.63	0.84	43.5	0.87	2.60%	-3.45%
0.44	43.84	0.84	43.5	0.87	0.78%	-3.45%
0.45	43.43	0.86	43.5	0.87	-0.16%	-1.15%
0.46	43.36	0.86	43.5	0.87	-0.32%	-1.15%
0.462725*	43.40	0.86	43.5	0.87	-0.23%	-1.15%
0.47	43.37	0.87	43.5	0.87	-0.30%	0.00%
0.48	43.42	0.88	43.5	0.87	-0.18%	1.15%
0.49	42.75	0.88	43.5	0.87	-1.72%	1.15%
0.5	42.43	0.88	43.5	0.87	-2.46%	1.15%
0.51	42.6	0.9	43.5	0.87	-2.07%	3.45%
0.52	42.34	0.91	43.5	0.87	-2.67%	4.60%
0.53	42.06	0.91	43.5	0.87	-3.31%	4.60%
0.54	41.91	0.92	43.5	0.87	-3.66%	5.75%
0.55	41.62	0.93	43.5	0.87	-4.32%	6.90%

\*interpolated using DASY4 software

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 5 of 41


	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	



Test Lab Certificate No. 2470.01

## FLUID DIELECTRIC PARAMETERS (CONT.)

FLUID DIELECTRIC PARAMETERS						
Date: 03/04/2011		Frequency: 450 MHz			Tissue: Body	
Freq	Test_e	Test_s	450 MHz Target_e	450 MHz Target_s	Deviation Permittivity	Deviation Conductivity
0.35	57.57	0.83	56.7	0.94	1.53%	-11.70%
0.36	57.84	0.85	56.7	0.94	2.01%	-9.57%
0.37	57.02	0.86	56.7	0.94	0.56%	-8.51%
0.38	57.29	0.87	56.7	0.94	1.04%	-7.45%
0.39	56.31	0.87	56.7	0.94	-0.69%	-7.45%
0.4	56.29	0.88	56.7	0.94	-0.72%	-6.38%
0.41	56.74	0.89	56.7	0.94	0.07%	-5.32%
0.42	56.28	0.89	56.7	0.94	-0.74%	-5.32%
0.43	55.87	0.91	56.7	0.94	-1.46%	-3.19%
0.44	55.68	0.92	56.7	0.94	-1.80%	-2.13%
0.45	56.38	0.93	56.7	0.94	-0.56%	-1.06%
0.46	55.81	0.94	56.7	0.94	-1.57%	0.00%
0.462725*	55.80	0.94	56.7	0.94	-1.59%	0.00%
0.47	55.85	0.94	56.7	0.94	-1.50%	0.00%
0.48	55.08	0.95	56.7	0.94	-2.86%	1.06%
0.49	55.94	0.96	56.7	0.94	-1.34%	2.13%
0.5	55.27	0.98	56.7	0.94	-2.52%	4.26%
0.51	55.4	1	56.7	0.94	-2.29%	6.38%
0.52	55.01	1	56.7	0.94	-2.98%	6.38%
0.53	54.62	1.01	56.7	0.94	-3.67%	7.45%
0.54	55.15	1.01	56.7	0.94	-2.73%	7.45%
0.55	54.53	1.03	56.7	0.94	-3.83%	9.57%

\*interpolated using DASY4 software


<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 6 of 41

	Date(s) of Evaluation March 04, 2011	Test Report Serial No. 030211BBO-T1086-S95U	Test Report Revision No. Rev. 1.0 (Initial Release)	
	Test Report Issue Date March 10, 2011	Description of Test(s) Specific Absorption Rate	RF Exposure Category Gen. Pop. / Uncontrolled	



## 5.0 SAR MEASUREMENT SUMMARY

### SAR EVALUATION RESULTS

Test Config.	Freq.	Channel		Batt. Type	Accessories		DUT Spacing to Planar Phantom		Cond. Power Before Test	Measured SAR 1g (W/kg)		SAR Drift During Test	Scaled SAR with droop 1g (W/kg)			
	PTT Duty Cycle									PTT Duty Cycle						
	MHz				Body	Audio	DUT	Antenna	Watts	100%	50%	dB	100%	50%		
FACE	462.725	22	GMRS	Ni-MH	n/a	n/a	2.5 cm	3.0 cm	0.9	0.731	0.366	-0.474	0.815	0.408		
	462.725	22	GMRS	Alkaline	n/a	n/a	2.5 cm	3.0 cm	0.9	0.940	0.470	-0.934	1.17	0.585		
BODY	462.725	22	GMRS	Ni-MH	Belt-Clip	Ear-bud	0.6 cm	1.3 cm	0.9	1.38	0.690	-0.674	1.61	0.805		
	462.725	22	GMRS	Alkaline	Belt-Clip	Ear-bud	0.6 cm	1.3 cm	0.9	1.73	0.865	-0.935	2.15	1.08		
SAR LIMIT(S)				HEAD / BODY				SPATIAL PEAK				RF EXPOSURE CATEGORY				
FCC 47 CFR 2.1093				1.6 W/kg				averaged over 1 gram				General Population / Uncontrolled				
Test Date(s)		March 04, 2011				March 04, 2011				Atmosph. Pressure		H	101.1	B	101.1	kPa
Measured Fluid		450 MHz Head		462.725 MHz		450 MHz Body		462.725 MHz		Relative Humidity		H	35	B	35	%
Dielectric Constant $\epsilon_r$		IEEE Target		Interp.	Dev.	IEEE Target		Interp.	Dev.	Ambient Temp.		H	22.9	B	22.1	°C
		43.5	± 5%	43.4	-0.2%	56.7	± 5%	55.8	-1.6%	Fluid Temp.		H	21.8	B	21.2	°C
Conductivity $\sigma$ (mho/m)		IEEE Target		Interp.	Dev.	IEEE Target		Interp.	Dev.	Fluid Depth		H	≥ 15	B	≥ 15	cm
		0.87	± 5%	0.86	-1.1%	0.94	± 5%	0.94	0.0%	$\rho$ (Kg/m <sup>3</sup> )		1000				
Notes																
1.	Detailed measurement plots showing the maximum SAR location of the DUT are reported in Appendix A.															
2.	The number of test channels ( $N_c$ ) was selected in accordance with the procedures specified in FCC KDB 447498 Section 6)c) (see reference [4]).															
3.	The SAR droop measured by the DASY4 system for the duration of the SAR evaluation was added to the measured SAR level to report the scaled SAR result as shown in the above test data table.															
4.	The DUT was tested in unmodulated continuous transmit operation (Continuous Wave mode at 100% duty cycle) with the PTT depressed.															
5.	SAR Evaluation Power Thresholds for PTT Devices, $f \leq 0.5$ GHz per FCC KDB 447498 D01v04 Section 5)b)i)									RF Conducted Output Power Level						
										100% PTT Duty Cycle			50% PTT Duty Cycle			
	Exposure Conditions			P mW (General Population)				P mW (Occupational)		GMRS Mode			GMRS Mode			
	Held to face, $d \geq 2.5$ cm			250				1250		0.900 Watts			0.450 Watts			
	Body-worn, $d \geq 1.5$ cm			200				1000								
	Body-worn, $d < 1.5$ cm			150				750								
	1. The time-averaged output power, corresponding to the required PTT duty factor, is compared with these thresholds. 2. The closest distance between the user and the device or its antenna is used to determine the power thresholds.									1. The conducted output power level of the DUT exceeds the FCC power threshold and therefore SAR evaluation is required. 2. The conducted output power for FRS mode is below the power threshold for SAR evaluation.						

Applicant:	Cobra Electronics Corporation	FCC ID:	BBO1102B	Model(s):	CXT275, CXT225	
DUT Type:	Portable GMRS/FRS PTT Radio Transceiver		Frequency Range:		462.5500 - 467.7125 MHz	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 7 of 41



	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01


## 6.0 DETAILS OF SAR EVALUATION

The Cobra Electronics Corporation Models: CXT275, CXT225 Portable FM UHF GMRS/FRS PTT Radio Transceiver was compliant for localized Specific Absorption Rate (General Population / Uncontrolled Exposure) based on the test provisions and conditions described below. The detailed test setup photographs are shown in Appendix D.



1. The DUT was evaluated for SAR in a face-held configuration with the front of the radio placed parallel to the outer surface of the planar phantom. A 2.5 cm spacing was maintained between the front of the DUT and the outer surface of the planar phantom.
2. The DUT was evaluated for SAR in a body-worn configuration with the back of the radio facing the outer surface of the planar phantom. The DUT antenna was placed parallel to the planar phantom. The attached plastic belt-clip accessory was touching the planar phantom and provided 0.6 cm spacing from the back of the DUT to the outer surface of the planar phantom. The DUT was evaluated for body-worn SAR with the Cobra supplied ear-bud lapel-microphone audio accessory connected to the external audio port.
3. The SAR drift of the DUT was measured by the DASY4 system for the duration of the SAR evaluations. A SAR-versus-Time power droop evaluation was performed in the test configuration that reported the maximum measured SAR level. See Appendix A (SAR Test Plots) for SAR-versus-Time power droop evaluation plot.
4. The Ni-MH batteries were fully charged prior to the Ni-MH battery SAR evaluations. New alkaline batteries were used for the alkaline battery SAR evaluations.
5. The DUT was tested at the maximum power level preset by the manufacturer in unmodulated continuous transmit operation (Continuous Wave mode at 100% duty cycle) with the PTT transmit key constantly depressed. For a push-to-talk device the 50% duty cycle compensation reported assumes a transmit/receive cycle of equal time base.
6. The fluid temperature was measured prior to and after the SAR evaluations to ensure the temperature remained within  $\pm 2^{\circ}\text{C}$  of the fluid temperature reported during the dielectric parameter measurements. The measured fluid remained within  $\pm 2^{\circ}\text{C}$ .
7. The dielectric parameters of the simulated tissue mixtures were measured prior to the SAR evaluations using a Dielectric Probe Kit and a Network Analyzer (see Appendix C).

## 7.0 SAR EVALUATION PROCEDURES

- (i) The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.
- (ii) For body-worn and face-held devices a planar phantom was used.
- The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.  
An area scan was determined as follows:
- Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
- A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are  $>2$  dB from the global maximum. The remaining maxima are then used to position the cube scans.  
A 1g and 10g spatial peak SAR was determined as follows:
- Extrapolation is used to find the points between the dipole center of the probe and the surface of the phantom. This data cannot be measured, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.4 mm (see probe calibration document in Appendix E). The extrapolation was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
- Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).
- A zoom scan volume of 32 mm x 32 mm x 30 mm (5 x 5 x 7 points) centered at the peak SAR location determined from the area scan is used for all zoom scans for devices with a transmit frequency  $< 800$  MHz. Zoom scans for frequencies  $\geq 800$  MHz are determined with a scan volume of 30 mm x 30 mm x 30 mm (7 x 7 x 7) to ensure complete capture of the peak spatial-average SAR.

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 8 of 41



	Date(s) of Evaluation March 04, 2011	Test Report Serial No. 030211BBO-T1086-S95U	Test Report Revision No. Rev. 1.0 (Initial Release)	
	Test Report Issue Date March 10, 2011	Description of Test(s) Specific Absorption Rate	RF Exposure Category Gen. Pop. / Uncontrolled	

## 8.0 SYSTEM PERFORMANCE CHECK


Prior to the SAR evaluations, daily system checks were performed with the Barski planar phantom and 450 MHz SPEAG dipole (see Appendix B for system performance check test plots) in accordance with the procedures described in IEEE Standard 1528-2003 (see reference [3]). The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer (see Appendix C for measured fluid dielectric parameters). A forward power of 398 mW was applied to the dipole and the system was verified to a tolerance of  $\pm 10\%$  from the SAR system manufacturer's dipole calibration target SAR value (see Appendix E for system manufacturer's dipole calibration procedures).

### SYSTEM PERFORMANCE CHECK EVALUATION

Test Date	Equiv. Tissue	SAR 1g (W/kg)			Dielectric Constant $\epsilon_r$			Conductivity $\sigma$ (mho/m)			$\rho$ (Kg/m <sup>3</sup> )	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
	Freq. (MHz)	SPEAG Target	Meas.	Dev.	Target	Meas.	Dev.	Target	Meas.	Dev.						
Mar. 4	Head 450	1.87 $\pm 10\%$	1.88	+0.5%	43.5 $\pm 5\%$	43.4	-0.2%	0.87 $\pm 5\%$	0.86	-1.2%	1000	22.8	21.9	$\geq 15$	34	101.1
Mar. 4	Body 450	1.78 $\pm 10\%$	1.78	0.0%	56.7 $\pm 5\%$	56.4	-0.5%	0.94 $\pm 5\%$	0.93	-1.1%	1000	22.1	21.2	$\geq 15$	35	101.1


#### Notes



- The target SAR value is the measured values from the SAR system manufacturer's dipole calibration (see Appendix E).
- The target dielectric parameters are the nominal values from the SAR system manufacturer's dipole calibration (see Appendix E).
- The fluid temperature was measured prior to and after the system performance check to ensure the temperature remained within  $\pm 2^\circ\text{C}$  of the fluid temperature reported during the dielectric parameter measurements. The measured fluid remained within  $\pm 2^\circ\text{C}$ .
- The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer (see Appendix C).



System Performance Check Measurement Setup (IEEE Standard 1528-2003)

SPEAG 450 MHz Validation Dipole Setup

Applicant:	Cobra Electronics Corporation	FCC ID:	BBO1102B	Model(s):	CXT275, CXT225	
DUT Type:	Portable GMRS/FRS PTT Radio Transceiver		Frequency Range:		462.5500 - 467.7125 MHz	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 9 of 41

	Date(s) of Evaluation March 04, 2011	Test Report Serial No. 030211BBO-T1086-S95U	Test Report Revision No. Rev. 1.0 (Initial Release)	
	Test Report Issue Date March 10, 2011	Description of Test(s) Specific Absorption Rate	RF Exposure Category Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## 9.0 SAR PROBE CALIBRATION & MEASUREMENT FREQUENCIES

The following procedures are recommended for measurements at 150 MHz - 3 GHz to minimize probe calibration and tissue dielectric parameter discrepancies. In general, SAR measurements below 300 MHz should be within  $\pm 50$  MHz of the probe calibration frequency. At 300 MHz to 3 GHz, measurements should be within  $\pm 100$  MHz of the probe calibration frequency. Measurements exceeding 50% of these intervals,  $\pm 25$  MHz < 300 MHz and  $\pm 50$  MHz  $\geq$  300 MHz, require additional steps (per FCC KDB 450824 D01 v01r01, SAR Probe Calibration and System Verification Considerations for Measurements at 150 MHz - 3 GHz - see reference [5]).

Probe Calibration Freq.	Device Measurement Freq.	Frequency Interval	$\pm 50$ MHz $\geq$ 300 MHz
450 MHz	462.7250 MHz	12.725 MHz	< 50 MHz
The probe calibration and measurement frequency interval is < 50 MHz; therefore the additional steps are not required.			


## 10.0 SIMULATED EQUIVALENT TISSUES



The simulated equivalent tissue recipes in the table below are derived from the SAR system manufacturer's suggested recipes in the DASY4 manual (see references [6] and [7]) in accordance with the procedures and requirements specified in IEEE Standard 1528-2003 (see reference [3]). The ingredient percentage may have been adjusted minimally in order to achieve the appropriate target dielectric parameters within the specified tolerance.

SIMULATED TISSUE MIXTURES		
INGREDIENT	450 MHz Head	450 MHz Body
Water	38.56 %	52.00 %
Sugar	56.32 %	45.65 %
Salt	3.95 %	1.75 %
HEC	0.98 %	0.50 %
Bactericide	0.19 %	0.10 %

## 11.0 SAR LIMITS

SAR RF EXPOSURE LIMITS			
FCC 47 CFR 2.1093	Health Canada Safety Code 6	General Population	Occupational
Spatial Average (averaged over the whole body)		0.08 W/kg	0.4 W/kg
Spatial Peak (averaged over any 1 g of tissue)		1.6 W/kg	8.0 W/kg
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)		4.0 W/kg	20.0 W/kg
The Spatial Average value of the SAR averaged over the whole body.			
The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.			
The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.			
Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.			
Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.			

Applicant:	Cobra Electronics Corporation	FCC ID:	BBO1102B	Model(s):	CXT275, CXT225	
DUT Type:	Portable GMRS/FRS PTT Radio Transceiver	Frequency Range:	462.5500 - 467.7125 MHz			
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 10 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## 12.0 ROBOT SYSTEM SPECIFICATIONS

### Specifications

<b>Positioner</b>	Stäubli Unimation Corp. Robot Model: RX60L
<b>Repeatability</b>	0.02 mm
<b>No. of axis</b>	6

### Data Acquisition Electronic (DAE) System

<b><u>Cell Controller</u></b>	
<b>Processor</b>	AMD Athlon XP 2400+
<b>Clock Speed</b>	2.0 GHz
<b>Operating System</b>	Windows XP Professional
<b><u>Data Converter</u></b>	
<b>Features</b>	Signal Amplifier, multiplexer, A/D converter, and control logic
<b>Software</b>	Measurement Software: DASY4, V4.7 Build 44
	Postprocessing Software: SEMCAD, V1.8 Build 171
<b>Connecting Lines</b>	Optical downlink for data and status info., Optical uplink for commands and clock

### DASY4 Measurement Server

<b>Function</b>	Real-time data evaluation for field measurements and surface detection
<b>Hardware</b>	PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
<b>Connections</b>	COM1, COM2, DAE, Robot, Ethernet, Service Interface

### E-Field Probe


<b>Model</b>	ET3DV6
<b>Serial No.</b>	1590
<b>Construction</b>	Triangular core fiber optic detection system
<b>Frequency</b>	10 MHz to 6 GHz
<b>Linearity</b>	±0.2 dB (30 MHz to 3 GHz)



### Evaluation Phantom

<b>Type</b>	Side Planar Phantom
<b>Shell Material</b>	Plexiglas
<b>Thickness</b>	2.0 mm ± 0.1 mm
<b>Volume</b>	72.6 cm (L) x 20.3 cm (W) x 20.3 cm (H)

### Validation Phantom

<b>Type</b>	Planar Phantom
<b>Shell Material</b>	Fiberglass
<b>Thickness</b>	2.0 ±0.1 mm
<b>Volume</b>	Approx. 70 liters

<b>Applicant:</b>	Cobra Electronics Corporation	<b>FCC ID:</b>	BBO1102B	<b>Model(s):</b>	CXT275, CXT225	
<b>DUT Type:</b>	Portable GMRS/FRS PTT Radio Transceiver	<b>Frequency Range:</b>		462.5500 - 467.7125 MHz		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 11 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

### 13.0 PROBE SPECIFICATION (ET3DV6)


Construction:	Symmetrical design with triangular core; Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, glycol)
Calibration:	In air from 10 MHz to 2.5 GHz In head simulating tissue at frequencies of 900 MHz and 1.8 GHz (accuracy $\pm 8\%$ )
Frequency:	10 MHz to $> 6$ GHz; Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)
Directivity:	$\pm 0.2$ dB in head tissue (rotation around probe axis) $\pm 0.4$ dB in head tissue (rotation normal to probe axis)
Dynamic Range:	5 $\mu$ W/g to $> 100$ mW/g; Linearity: $\pm 0.2$ dB
Surface Detect:	$\pm 0.2$ mm repeatability in air and clear liquids over diffuse reflecting surfaces
Dimensions:	Overall length: 330 mm; Tip length: 16 mm; Body diameter: 12 mm; Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application:	General dosimetry up to 3 GHz; Compliance tests of mobile phone



ET3DV6 E-Field Probe

### 14.0 SIDE PLANAR PHANTOM

The side planar phantom is constructed of Plexiglas material with a 2.0 mm shell thickness for face-held and body-worn SAR evaluations of portable radio transceivers. The side planar phantom is mounted on the side of the DASY4 compact system table.



Plexiglas Side Planar Phantom

### 15.0 BARKSI PLANAR PHANTOM

The Barski planar phantom is a fiberglass shell phantom with a 2.0 mm ( $\pm 0.2$ mm) thick device measurement area at the center of the phantom for SAR evaluations of devices with a larger surface area than the planar section of the SAM phantom. The planar phantom is integrated in a wooden table. The planar phantom was used for the DUT SAR evaluations and the system performance check evaluations. See Appendix G for dimensions and specifications of the Barski planar phantom.




Barski Planar Phantom



### 16.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of  $65^\circ$ . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.



Device Holder

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 12 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01


## 17.0 TEST EQUIPMENT LIST



TEST EQUIPMENT		ASSET NO.	SERIAL NO.	DATE CALIBRATED	CALIBRATION INTERVAL
USED	DESCRIPTION				
x	Schmid & Partner DASY4 System	-	-	-	-
x	-DASY4 Measurement Server	00158	1078	CNR	CNR
x	-Robot	00046	599396-01	CNR	CNR
x	-DAE4	00019	353	27Apr10	Annual
x	-ET3DV6 E-Field Probe	00017	1590	15Jul10	Annual
x	-SPEAG D450V3 Validation Dipole	000217	1068	18Jan10	Biennial
x	-Side Planar Phantom	00156	161	CNR	CNR
x	-Barski Planar Phantom	00155	03-01	CNR	CNR
x	HP 85070C Dielectric Probe Kit	00033	none	CNR	CNR
x	Gigatronics 8652A Power Meter	00007	1835272	04May10	Biennial
x	Gigatronics 80701A Power Sensor	00014	1833699	04May10	Biennial
x	HP 8753ET Network Analyzer	00134	US39170292	04May10	Biennial
x	Rohde & Schwarz SMR20 Signal Generator	00006	100104	CNR	CNR
x	Amplifier Research 5S1G4 Power Amplifier	00106	26235	CNR	CNR
Abbr.	CNR = Calibration Not Required				

## 18.0 JUSTIFICATION FOR EXTENDED SAR DIPOLE CALIBRATION

SAR dipoles calibrated less than two years ago but more than one year ago were confirmed by maintaining return loss (< -20dB, within 20% of prior calibration) and impedance (within 5Ω from prior calibration) requirements per extended calibrations in FCC KDB 450824 (see reference [5]).

SPEAG VALIDATION DIPOLE D450V3 - SN: 1068						
Measurement Date	Freq.	TSL	Return Loss (dB)	Δ %	Impedance (Ω)	Δ Ω
January 18, 2010	450 MHz	Head	-21.0		57.5	
February 7, 2011			-21.3	1.5%	53.8	3.7
January 18, 2010	450 MHz	Body	-20.0		54.8	
February 7, 2011			-20.5	2.5%	50.4	4.4

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 13 of 41

	Date(s) of Evaluation March 04, 2011	Test Report Serial No. 030211BBO-T1086-S95U	Test Report Revision No. Rev. 1.0 (Initial Release)	
	Test Report Issue Date March 10, 2011	Description of Test(s) Specific Absorption Rate	RF Exposure Category Gen. Pop. / Uncontrolled	


Test Lab Certificate No. 2470.01

## 19.0 MEASUREMENT UNCERTAINTIES



UNCERTAINTY BUDGET FOR DEVICE EVALUATION									
Uncertainty Component	IEEE 1528 Section	Uncertainty Value $\pm\%$	Probability Distribution	Divisor	ci 1g	ci 10g	Uncertainty Value $\pm\%$ (1g)	Uncertainty Value $\pm\%$ (10g)	$V_i$ or $V_{eff}$
<b>Measurement System</b>									
Probe Calibration (450 MHz)	E.2.1	6.65	Normal	1	1	1	6.65	6.65	$\infty$
Axial Isotropy	E.2.2	4.7	Rectangular	1.732050808	0.7	0.7	1.9	1.9	$\infty$
Hemispherical Isotropy	E.2.2	9.6	Rectangular	1.732050808	0.7	0.7	3.9	3.9	$\infty$
Boundary Effect	E.2.3	1	Rectangular	1.732050808	1	1	0.6	0.6	$\infty$
Linearity	E.2.4	4.7	Rectangular	1.732050808	1	1	2.7	2.7	$\infty$
System Detection Limits	E.2.5	1	Rectangular	1.732050808	1	1	0.6	0.6	$\infty$
Readout Electronics	E.2.6	0.3	Normal	1	1	1	0.3	0.3	$\infty$
Response Time	E.2.7	0.8	Rectangular	1.732050808	1	1	0.5	0.5	$\infty$
Integration Time	E.2.8	2.6	Rectangular	1.732050808	1	1	1.5	1.5	$\infty$
RF Ambient Conditions	E.6.1	3	Rectangular	1.732050808	1	1	1.7	1.7	$\infty$
Probe Positioner Mechanical Tolerance	E.6.2	0.4	Rectangular	1.732050808	1	1	0.2	0.2	$\infty$
Probe Positioning wrt Phantom Shell	E.6.3	2.9	Rectangular	1.732050808	1	1	1.7	1.7	$\infty$
Extrapolation, interpolation & integration algorithms for max. SAR evaluation	E.5	1	Rectangular	1.732050808	1	1	0.6	0.6	$\infty$
<b>Test Sample Related</b>									
Test Sample Positioning	E.4.2	2.9	Normal	1	1	1	2.9	2.9	12
Device Holder Uncertainty	E.4.1	3.6	Normal	1	1	1	3.6	3.6	8
SAR Drift Measurement	6.6.2	5	Rectangular	1.732050808	1	1	2.9	2.9	$\infty$
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty	E.3.1	4	Rectangular	1.732050808	1	1	2.3	2.3	$\infty$
Liquid Conductivity (target)	E.3.2	5	Rectangular	1.732050808	0.64	0.43	1.8	1.2	$\infty$
Liquid Conductivity (measured)	E.3.3	1.2	Normal	1	0.64	0.43	0.8	0.5	$\infty$
Liquid Permittivity (target)	E.3.2	5	Rectangular	1.732050808	0.6	0.49	1.7	1.4	$\infty$
Liquid Permittivity (measured)	E.3.3	1.6	Normal	1	0.6	0.49	1.0	0.8	$\infty$
<b>Combined Standard Uncertainty</b>			<b>RSS</b>				<b>11.07</b>	<b>10.91</b>	
<b>Expanded Uncertainty (95% Confidence Interval)</b>			<b>k=2</b>				<b>22.15</b>	<b>21.83</b>	

Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2

Applicant:	Cobra Electronics Corporation	FCC ID:	BBO1102B	Model(s):	CXT275, CXT225	
DUT Type:	Portable GMRS/FRS PTT Radio Transceiver		Frequency Range:		462.5500 - 467.7125 MHz	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				




	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	



Test Lab Certificate No. 2470.01

## 20.0 REFERENCES


- [1] Federal Communications Commission - "Radiofrequency radiation exposure evaluation: portable devices", Rule Part 47 CFR §2.1093.
- [2] Federal Communications Commission - "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [3] IEEE Standard 1528-2003 - "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques": December 2003.
- [4] Federal Communications Commission, Office of Engineering and Technology - "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies"; KDB 447498 D01v04: November 2009.
- [5] Federal Communications Commission, Office of Engineering and Technology - "Application Note: SAR Probe Calibration and System Verification Considerations for Measurements at 150 MHz - 3 GHz"; KDB 450824 D01 v01r01: January 2007.
- [6] Schmid & Partner Engineering AG - DASY4 Manual V4.6, Chapter 16 Application Note, Head Tissue Recipe: Sept. 2005.
- [7] Schmid & Partner Engineering AG - DASY4 Manual V4.6, Chapter 17 Application Note, Body Tissue Recipe: Sept. 2005.
- [8] ISO/IEC 17025 - "General requirements for the competence of testing and calibration laboratories (ISO/IEC 17025:2005)."
- [9] Federal Communications Commission - "Measurements Required: RF Power Output"; Rule Part 47 CFR §2.1046.



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				



	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX A - SAR MEASUREMENT DATA

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 16 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Date Tested: 03/04/2011

## Face-held SAR - GMRS - Channel 22 - 462.7250 MHz - Ni-MH AAA Rechargeable Batteries

**DUT: Cobra; Model: CXT275; Type: Portable GMRS/FRS PTT Radio Transceiver; Serial: None**

Ambient Temp: 22.9°C; Fluid Temp: 21.8°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: UHF FM (CW)

Frequency: 462.725 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used (interpolated):  $f = 462.725 \text{ MHz}$ ;  $\sigma = 0.86 \text{ mho/m}$ ;  $\epsilon_r = 43.4$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Face-held SAR - 2.5 cm Spacing from Front of DUT to Planar Phantom

**NiMH/Area Scan (7x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.785 mW/g


**NiMH/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 31.4 V/m; Power Drift = -0.474 dB



Peak SAR (extrapolated) = 1.02 W/kg

**SAR(1 g) = 0.731 mW/g; SAR(10 g) = 0.532 mW/g**

Maximum value of SAR (measured) = 0.765 mW/g



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

Date Tested: 03/04/2011

## Face-held SAR - GMRS - Channel 22 - 462.7250 MHz - Energizer AAA Alkaline Batteries

**DUT: Cobra; Model: CXT275; Type: Portable GMRS/FRS PTT Radio Transceiver; Serial: None**

Ambient Temp: 22.9°C; Fluid Temp: 21.8°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: UHF FM (CW)

Frequency: 462.725 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used (interpolated):  $f = 462.725 \text{ MHz}$ ;  $\sigma = 0.86 \text{ mho/m}$ ;  $\epsilon_r = 43.4$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Face-held SAR - 2.5 cm Spacing from Front of DUT to Planar Phantom

**Alkaline/Area Scan (7x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.879 mW/g


**Alkaline/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 36.3 V/m; Power Drift = -0.934 dB



Peak SAR (extrapolated) = 1.30 W/kg

**SAR(1 g) = 0.940 mW/g; SAR(10 g) = 0.684 mW/g**


Maximum value of SAR (measured) = 0.986 mW/g






<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## Z-Axis Scan



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 19 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Date Tested: 03/04/2011

## Body-worn SAR - GMRS - Channel 22 - 462.7250 MHz - Ni-MH AAA Rechargeable Batteries

**DUT: Cobra; Model: CXT275; Type: Portable GMRS/FRS PTT Radio Transceiver; Serial: None**

**Body-worn Accessory: Plastic Belt-Clip; Audio Accessory: Earbud Lapel-Microphone with PTT (P/N: GA-EBM2)**

Ambient Temp: 22.1°C; Fluid Temp: 21.2°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: UHF FM (CW)

Frequency: 462.725 MHz; Duty Cycle: 1:1

Medium: M450 Medium parameters used:  $f = 462.725 \text{ MHz}$ ;  $\sigma = 0.94 \text{ mho/m}$ ;  $\epsilon_r = 55.8$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Body-worn SAR - 0.6 cm Belt-Clip Spacing from Back of DUT to Planar Phantom

**NiMH Earbud/Area Scan (7x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.47 mW/g


**NiMH Earbud/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 37.4 V/m; Power Drift = -0.674 dB



Peak SAR (extrapolated) = 2.07 W/kg

**SAR(1 g) = 1.38 mW/g; SAR(10 g) = 0.962 mW/g**

Maximum value of SAR (measured) = 1.44 mW/g



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Date Tested: 03/04/2011

## Body-worn SAR - GMRS - Channel 22 - 462.7250 MHz - Energizer Alkaline AAA Batteries

**DUT: Cobra; Model: CXT275; Type: Portable GMRS/FRS PTT Radio Transceiver; Serial: None**

**Body-worn Accessory: Plastic Belt-Clip; Audio Accessory: Earbud Lapel-Microphone with PTT (P/N: GA-EBM2)**

Ambient Temp: 22.1°C; Fluid Temp: 21.2°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: UHF FM (CW)

Frequency: 462.725 MHz; Duty Cycle: 1:1

Medium: M450 Medium parameters used:  $f = 462.725 \text{ MHz}$ ;  $\sigma = 0.94 \text{ mho/m}$ ;  $\epsilon_r = 55.8$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Body-worn SAR - 0.6 cm Belt-Clip Spacing from Back of DUT to Planar Phantom

**Alkaline Earbud/Area Scan (7x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.61 mW/g


**Alkaline Earbud/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 41.8 V/m; Power Drift = -0.935 dB



Peak SAR (extrapolated) = 2.59 W/kg

**SAR(1 g) = 1.73 mW/g; SAR(10 g) = 1.21 mW/g**

Maximum value of SAR (measured) = 1.82 mW/g




<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 21 of 41

	Date(s) of Evaluation March 04, 2011	Test Report Serial No. 030211BBO-T1086-S95U	Test Report Revision No. Rev. 1.0 (Initial Release)	
	Test Report Issue Date March 10, 2011	Description of Test(s) Specific Absorption Rate	RF Exposure Category Gen. Pop. / Uncontrolled	


Test Lab Certificate No. 2470.01

## Z-Axis Scan




## SAR-versus-Time Droop Evaluation



Body-worn Configuration  
GMRS Ch. 22 (462.7250 MHz)  
Alkaline AAA Batteries




Start SAR: 1.50153 mW/g  
End SAR: 1.29644 mW/g (-0.638 dB)  
SAR after 340s: 1.31357 mW/g (-0.581 dB)



Applicant:	Cobra Electronics Corporation	FCC ID:	BBO1102B	Model(s):	CXT275, CXT225	
DUT Type:	Portable GMRS/FRS PTT Radio Transceiver		Frequency Range:		462.5500 - 467.7125 MHz	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 22 of 41



	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX B - SYSTEM PERFORMANCE CHECK DATA

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 23 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Date Tested: 03/04/2011

## System Performance Check - 450 MHz Dipole - Head

**DUT: Dipole D450V3; Asset: 00217; Serial: 1068; Calibration: 01/18/2010**

Ambient Temp: 22.8°C; Fluid Temp: 21.9°C; Barometric Pressure: 101.1 kPa; Humidity: 34%

Communication System: CW

Forward Conducted Power: 398 mW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.86 \text{ mho/m}$ ;  $\epsilon_r = 43.4$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### System Performance Check - 450 MHz Dipole

**Head d=15mm Pin=398mW/Area Scan (6x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.98 mW/g


**Head d=15mm Pin=398mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 47.2 V/m; Power Drift = -0.002 dB



Peak SAR (extrapolated) = 2.92 W/kg

**SAR(1 g) = 1.88 mW/g; SAR(10 g) = 1.26 mW/g**


Maximum value of SAR (measured) = 2.01 mW/g






<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## Z-Axis Scan



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 25 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

Date Tested: 03/04/2011

## System Performance Check - 450 MHz Dipole - Body

**DUT: Dipole D450V3; Asset: 000217; Serial: 1068; Calibration: 01/18/2010**

Ambient Temp: 22.1°C; Fluid Temp: 21.2°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Forward Conducted Power: 398 mW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: M450 Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.93 \text{ mho/m}$ ;  $\epsilon_r = 56.4$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### System Performance Check - 450 MHz Dipole

**Body d=15mm Pin=398mW/Area Scan (6x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.87 mW/g


**Body d=15mm Pin=398mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 44.7 V/m; Power Drift = 0.013 dB


Peak SAR (extrapolated) = 2.80 W/kg

**SAR(1 g) = 1.78 mW/g; SAR(10 g) = 1.19 mW/g**


Maximum value of SAR (measured) = 1.88 mW/g






<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	


## Z-Axis Scan





<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 27 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 28 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

### 450 MHz Head

\*\*\*\*\*

Celltech Labs Inc.

Test Result for UIM Dielectric Parameter

04/Mar/2011

Frequency (GHz)

FCC\_eHFCC OET 65 Supplement C (June 2001) Limits for Head Epsilon


FCC\_sHFCC OET 65 Supplement C (June 2001) Limits for Head Sigma

Test\_e Epsilon of UIM



Test\_s Sigma of UIM

\*\*\*\*\*

Freq	FCC_eHFCC_sH	Test_e	Test_s
0.3500	44.70	0.87	45.58
0.3600	44.58	0.87	45.52
0.3700	44.46	0.87	45.05
0.3800	44.34	0.87	45.54
0.3900	44.22	0.87	44.64
0.4000	44.10	0.87	44.61
0.4100	43.98	0.87	44.33
0.4200	43.86	0.87	44.54
0.4300	43.74	0.87	44.63
0.4400	43.62	0.87	43.84
0.4500	43.50	0.87	43.43
0.4600	43.45	0.87	43.36
0.4700	43.40	0.87	43.37
0.4800	43.34	0.87	43.42
0.4900	43.29	0.87	42.75
0.5000	43.24	0.87	42.43
0.5100	43.19	0.87	42.60
0.5200	43.14	0.88	42.34
0.5300	43.08	0.88	42.06
0.5400	43.03	0.88	41.91
0.5500	42.98	0.88	41.62

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 29 of 41



	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

### 450 MHz Body

\*\*\*\*\*

Celltech Labs Inc.

Test Result for UIM Dielectric Parameter

04/Mar/2011

Frequency (GHz)

FCC\_eHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon

FCC\_sHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma

FCC\_eB FCC Limits for Body Epsilon


FCC\_sB FCC Limits for Body Sigma



Test\_e Epsilon of UIM

Test\_s Sigma of UIM


\*\*\*\*\*



Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.3500	57.70	0.93	57.57	0.83
0.3600	57.60	0.93	57.84	0.85
0.3700	57.50	0.93	57.02	0.86
0.3800	57.40	0.93	57.29	0.87
0.3900	57.30	0.93	56.31	0.87
0.4000	57.20	0.93	56.29	0.88
0.4100	57.10	0.93	56.74	0.89
0.4200	57.00	0.94	56.28	0.89
0.4300	56.90	0.94	55.87	0.91
0.4400	56.80	0.94	55.68	0.92
0.4500	56.70	0.94	56.38	0.93
0.4600	56.66	0.94	55.81	0.94
0.4700	56.62	0.94	55.85	0.94
0.4800	56.58	0.94	55.08	0.95
0.4900	56.54	0.94	55.94	0.96
0.5000	56.51	0.94	55.27	0.98
0.5100	56.47	0.94	55.40	1.00
0.5200	56.43	0.95	55.01	1.00
0.5300	56.39	0.95	54.62	1.01
0.5400	56.35	0.95	55.15	1.01
0.5500	56.31	0.95	54.53	1.03

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 30 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX D - SAR TEST SETUP & DUT PHOTOGRAPHS


<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 31 of 41



	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## FACE-HELD SAR TEST SETUP PHOTOGRAPHS

### 2.5 cm Spacing from Front of DUT to Planar Phantom





<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 32 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	



## BODY-WORN SAR TEST SETUP PHOTOGRAPHS

0.6 cm Belt-Clip Spacing from Back of DUT to Planar Phantom  
DUT with Earbud Lapel-Microphone Audio Accessory



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 33 of 41



	Date(s) of Evaluation March 04, 2011	Test Report Serial No. 030211BBO-T1086-S95U	Test Report Revision No. Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	Test Report Issue Date March 10, 2011	Description of Test(s) Specific Absorption Rate	RF Exposure Category Gen. Pop. / Uncontrolled	

## DUT PHOTOGRAPHS



Front Side of DUT



Back Side of DUT




Back Side of DUT with Plastic Belt-Clip





Top End of DUT



Bottom End of DUT

Applicant:	Cobra Electronics Corporation	FCC ID:	BBO1102B	Model(s):	CXT275, CXT225	
DUT Type:	Portable GMRS/FRS PTT Radio Transceiver		Frequency Range:	462.5500 - 467.7125 MHz		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 34 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	


## DUT PHOTOGRAPHS





Left Side of DUT with Plastic Belt-Clip



Right Side of DUT with Plastic Belt-Clip

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 35 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

Test Lab Certificate No. 2470.01

## DUT PHOTOGRAPHS




DUT Battery Housing





DUT with Ni-MH AAA Batteries



DUT with Alkaline AAA Batteries


<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 36 of 41





	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## DUT PHOTOGRAPHS






<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 37 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	


## DUT PHOTOGRAPHS



<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>	<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>		
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 38 of 41

	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX E - DIPOLE CALIBRATION

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 39 of 41



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Client **Celltech**

Certificate No: **D450V3-1068\_Jan10**

## CALIBRATION CERTIFICATE

Object **D450V3 - SN: 1068**

Calibration procedure(s) **QA CAL-15.v5**  
**Calibration Procedure for dipole validation kits below 800 MHz**

Calibration date: **January 18, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41495277	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41498087	1-Apr-09 (No. 217-01030)	Apr-10
Reference 3 dB Attenuator	SN: S5054 (3c)	31-Mar-09 (No. 217-01026)	Mar-10
Reference 20 dB Attenuator	SN: S5086 (20b)	31-Mar-09 (No. 217-01028)	Mar-10
Type-N mismatch combination	SN: 5047.2 / 06327	31-Mar-09 (No. 217-01029)	Mar-10
Reference Probe ET3DV6 (LF)	SN: 1507	03-Jul-09 (No. ET3-1507_Jul09)	Jul-10
DAE4	SN: 654	04-May-09 (No. DAE4-654_May09)	May-10
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	04-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-09)	In house check: Oct-10

Calibrated by: **Jeton Kastrati** Function: **Laboratory Technician** Signature: *i.v. [Signature]*

Approved by: **Katja Pokovic** Technical Manager *[Signature]*

Issued: January 20, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

TSL	tissue simulating liquid
ConF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

### Additional Documentation:

- DASY4 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

<b>DASY Version</b>	DASY5	V5.2
<b>Extrapolation</b>	Advanced Extrapolation	
<b>Phantom</b>	ELI4 Flat Phantom	Shell thickness: $2 \pm 0.2$ mm
<b>Distance Dipole Center - TSL</b>	15 mm	with Spacer
<b>Area Scan Resolution</b>	dx, dy = 15 mm	
<b>Zoom Scan Resolution</b>	dx, dy, dz = 5 mm	
<b>Frequency</b>	450 MHz $\pm$ 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
<b>Nominal Head TSL parameters</b>	22.0 °C	43.5	0.87 mho/m
<b>Measured Head TSL parameters</b>	(22.0 $\pm$ 0.2) °C	44.2 $\pm$ 6 %	0.86 mho/m $\pm$ 6 %
<b>Head TSL temperature during test</b>	(22.0 $\pm$ 0.2) °C	----	----

## SAR result with Head TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b>	condition	
SAR measured	398 mW input power	1.87 mW / g
SAR normalized	normalized to 1W	4.70 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>4.76 mW / g <math>\pm</math> 18.1 % (k=2)</b>

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b>	condition	
SAR measured	398 mW input power	1.25 mW / g
SAR normalized	normalized to 1W	3.14 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>3.17 mW / g <math>\pm</math> 17.6 % (k=2)</b>

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	56.7	0.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	54.1 ± 6 %	0.90 mho/m ± 6 %
Body TSL temperature during test	(22.0 ± 0.2) °C	----	----

## SAR result with Body TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Body TSL</b>	condition	
SAR measured	398 mW input power	1.78 mW / g
SAR normalized	normalized to 1W	4.47 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>4.58 mW / g ± 18.1 % (k=2)</b>

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Body TSL</b>	condition	
SAR measured	398 mW input power	1.19 mW / g
SAR normalized	normalized to 1W	2.99 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>3.06 mW / g ± 17.6 % (k=2)</b>

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	57.5 $\Omega$ - 5.9 j $\Omega$
Return Loss	- 21.0 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	54.8 $\Omega$ - 9.3 j $\Omega$
Return Loss	- 20.0 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.350 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 16, 2009



**DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN:1068**

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.86$  mho/m;  $\epsilon_r = 44.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ET3DV6 - SN1507 (LF); ConvF(6.66, 6.66, 6.66); Calibrated: 7/3/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 5/4/2009
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1003
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Head/d=15mm, Pin=398mW/Area Scan (41x111x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 1.99 mW/g


**Head/d=15mm, Pin=398mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 50.2 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 2.78 W/kg

**SAR(1 g) = 1.87 mW/g; SAR(10 g) = 1.25 mW/g**

Maximum value of SAR (measured) = 2 mW/g



0 dB = 2mW/g

# Impedance Measurement Plot for Head TSL

18 Jan 2010 10:25:40  
**CH1** S11 1 U FS 1: 57.502  $\Omega$  -5.9180  $\Omega$  59.763 pF 450.000 000 MHz


\*

Del

Cor

Avg  
16

↑




CH2 S11 LOG 5 dB/REF -20 dB 1:-21.035 dB 450.000 000 MHz

Cor

Avg  
16

↑



**DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN:1068**

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium: MSL450

Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.9 \text{ mho/m}$ ;  $\epsilon_r = 54.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ET3DV6 - SN1507 (LF); ConvF(7.11, 7.11, 7.11); Calibrated: 7/3/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 5/4/2009
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1003
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Body/d=15mm, Pin=398mW/Area Scan (61x201x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) = 1.9 mW/g


**Body/d=15mm, Pin=398mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 47.4 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 2.71 W/kg

**SAR(1 g) = 1.78 mW/g; SAR(10 g) = 1.19 mW/g**

Maximum value of SAR (measured) = 1.9 mW/g




0 dB = 1.9mW/g

# Impedance Measurement Plot for Body TSL

18 Jan 2010 12:18:41  
**CH1** S11 1 U FS 1: 54.824  $\Omega$  -9.3047  $\Omega$  38.011 pF 450.000 000 MHz

\*  
 Del  
 Cor



Avg  
 16


↑


**CH2** S11 L06 5 dB/REF -20 dB 1:-20.034 dB 450.000 000 MHz

Cor


Avg  
 16

↑



	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX F - PROBE CALIBRATION

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 40 of 41



Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Celltech**

Certificate No: **ET3-1590\_Jul10**

## CALIBRATION CERTIFICATE

Object **ET3DV6 - SN:1590**

Calibration procedure(s) **QA CAL-01.v6, QA CAL-12.v6, QA CAL-23.v3 and QA CAL-25.v2**  
**Calibration procedure for dosimetric E-field probes**

Calibration date: **July 15, 2010**



This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41498087	1-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5054 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5086 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	30-Dec-09 (No. ES3-3013_Dec09)	Dec-10
DAE4	SN: 660	20-Apr-10 (No. DAE4-660_Apr10)	Apr-11
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-09)	In house check: Oct10

Calibrated by	Name <b>Jeton Kastrati</b>	Function <b>Laboratory Technician</b>
Approved by:	<b>Katja Pokovic</b>	<b>Technical Manager</b>

Signature  
  


Issued: July 15, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

## Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

## Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

## Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe ET3DV6

## SN:1590

Manufactured:	March 19, 2001
Last calibrated:	July 16, 2009
Recalibrated:	July 15, 2010

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)



**DASY/EASY - Parameters of Probe: ET3DV6 SN:1590****Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	1.86	2.06	1.77	$\pm 10.1\%$
DCP (mV) <sup>B</sup>	91.4	92.4	83.5	

**Modulation Calibration Parameters**

UID	Communication System Name	PAR		A dB	B dBuV	C	VR mV	Unc <sup>E</sup> (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	300.0	$\pm 1.5\%$
			Y	0.00	0.00	1.00	300.0	
			Z	0.00	0.00	1.00	300.0	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6)

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ET3DV6 SN:1590

### Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz]	Validity [MHz] <sup>c</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	43.5 ± 5%	0.87 ± 5%	7.25	7.25	7.25	0.20	2.19 ± 13.3%
835	± 50 / ± 100	41.5 ± 5%	0.90 ± 5%	6.27	6.27	6.27	0.32	2.49 ± 11.0%
900	± 50 / ± 100	41.5 ± 5%	0.97 ± 5%	6.12	6.12	6.12	0.27	2.86 ± 11.0%

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

## DASY/EASY - Parameters of Probe: ET3DV6 SN:1590


### Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz]	Validity [MHz] <sup>c</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	56.7 ± 5%	0.94 ± 5%	7.73	7.73	7.73	0.13	2.06 ± 13.3%
835	± 50 / ± 100	55.2 ± 5%	0.97 ± 5%	6.33	6.33	6.33	0.22	3.60 ± 11.0%
900	± 50 / ± 100	55.0 ± 5%	1.05 ± 5%	6.15	6.15	6.15	0.28	2.94 ± 11.0%


<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

## Frequency Response of E-Field



(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )


Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$ Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

# Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

Conversion Factor Assessment



Deviation from Isotropy in HSL

Error (ϕ, θ), f = 900 MHz





Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)


## Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	enabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	6.8 mm
Probe Tip to Sensor X Calibration Point	2.7 mm
Probe Tip to Sensor Y Calibration Point	2.7 mm
Probe Tip to Sensor Z Calibration Point	2.7 mm
Recommended Measurement Distance from Surface	4 mm



	<u>Date(s) of Evaluation</u> March 04, 2011	<u>Test Report Serial No.</u> 030211BBO-T1086-S95U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> March 10, 2011	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Gen. Pop. / Uncontrolled	

## APPENDIX G - BARSKI PLANAR PHANTOM CERTIFICATE OF CONFORMITY

<b>Applicant:</b>	<b>Cobra Electronics Corporation</b>	<b>FCC ID:</b>	<b>BBO1102B</b>	<b>Model(s):</b>	<b>CXT275, CXT225</b>	
<b>DUT Type:</b>	<b>Portable GMRS/FRS PTT Radio Transceiver</b>		<b>Frequency Range:</b>		<b>462.5500 - 467.7125 MHz</b>	
2011 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 41 of 41

2378 Westlake Road  
Kelowna, B.C. Canada  
V1Z-2V2



Ph. # 250-769-6848  
Fax # 250-769-6334  
E-mail: [barskiind@shaw.ca](mailto:barskiind@shaw.ca)  
Web: [www.bcfiberglass.com](http://www.bcfiberglass.com)

## FIBERGLASS FABRICATORS

### Certificate of Conformity

Item : Flat Planar Phantom Unit # 03-01  
Date: June 16, 2003  
Manufacturer: Barski Industries (1985 Ltd)

Test	Requirement	Details
Shape	Compliance to geometry according to drawing	Supplied CAD drawing
Material Thickness	Compliant with the requirements	2mm +/- 0.2mm in measurement area
Material Parameters	Dielectric parameters for required frequencies Based on Dow Chemical technical data	100 MHz-5 GHz Relative permittivity<5 Loss Tangent<0.05

#### Conformity

Based on the above information, we certify this product to be compliant to the requirements specified.

Signature: \_\_\_\_\_

A handwritten signature in black ink, appearing to read 'Daniel Chailier', is written over a horizontal line.

Daniel Chailier



**Fiberglass Planar Phantom - Top View**



**Fiberglass Planar Phantom - Front View**




**Fiberglass Planar Phantom - Back View**



**Fiberglass Planar Phantom - Bottom View**

## Dimensions of Fiberglass Planar Phantom

(Manufactured by Barski Industries Ltd. - Unit# 03-01)



**Note: Measurements that aren't repeated for the opposite sides are the same as the side measured.  
This drawing is not to scale.**