



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR 352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

**FCC PART 95 SUBPART D CLASS II
PERMISSIVE CHANGE
TEST REPORT
FOR CB TRANSCEIVERS**

APPLICANT	COBRA ELECTRONICS CORPORATION
	6500 WEST CORTLAND STREET CHICAGO IL 60707 USA
FCC ID	BBO3K225LTD
MODEL NUMBER	25 LX
PRODUCT DESCRIPTION	CB TRANSCEIVER
DATE SAMPLE RECEIVED	10/20/2011
DATE TESTED	11/1/2011
TESTED BY	Joe Scoglio
APPROVED BY	Mario R. de Aranzeta
TIMCO REPORT NO.	2444BT11TestReport.doc
TEST RESULTS	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing Certificate # 0955-01



TABLE OF CONTENTS

GENERAL REMARKS.....	3
GENERAL INFORMATION.....	4
TEST ENVIRONMENT.....	5
TEST SETUP SUMMARY.....	5
EQUIPMENT LIST.....	6
TEST PROCEDURE	7
RF POWER OUTPUT.....	8
FIELD STRENGTH OF SPURIOUS EMISSIONS	9

APPLICANT: COBRA ELECTRONICS CORPORATION
FCC ID: BBO3K225LTD
REPORT #: C\COBRA\2444BT11\2444BT11TestReport.doc



GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T.
Compliance Engineer / Lab. Supervisor

Date: 11/7/2011

APPLICANT: COBRA ELECTRONICS CORPORATION
FCC ID: BBO3K225LTD
REPORT #: C\COBRA\2444BT11\2444BT11TestReport.doc



GENERAL INFORMATION

DUT Specification

DUT Description	CB TRANSCEIVER
FCC ID	BBO3K225LTD
Model Number	25 LX
Serial Number	N/A
Operating Frequency	26.965-27.405 MHz
No. of Channels	40
Type of Emission	6KOOA3E Bn = 2M M = 3000 Bn = 6000
Modulation	AM
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz <input checked="" type="checkbox"/> DC Power <input type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Production
Type of Equipment	<input type="checkbox"/> Fixed <input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable

APPLICANT: COBRA ELECTRONICS CORPORATION
FCC ID: BBO3K225LTD
REPORT #: C\COBRA\2444BT11\2444BT11TestReport.doc



TEST ENVIRONMENT

Test Facility	Timco Engineering, Inc. 849 NW State Road 45 Newberry, FL 32669 USA.
Test Condition in the laboratory	Temperature: 26°C Relative humidity: 50%

TEST SETUP SUMMARY

Test Setup Diagram/ Description	The DUT was placed on the turntable per setup per ANSI C63.4: 2003. A test set up photo is provided for clarification.
Deviation from the standard/ procedure	No deviation
Modification of DUT	No modification
Applicable Standards	EIA/TIA-382-A, FCC CFR 47 PART 95

APPLICANT: COBRA ELECTRONICS CORPORATION
FCC ID: BBO3K225LTD
REPORT #: C\COBRA\2444BT11\2444BT11TestReport.doc



EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 5/10/10	5/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 6/12/11	6/12/13
Antenna: Active Loop	ETS-Lindgren	6502	00062529	CAL 9/23/10	9/23/12
Frequency Counter	HP	5385A	2730A03025	CAL 8/17/11	8/17/13
Hygro-Thermometer	Extech	445703	0602	CAL 6/15/11	6/15/13
Modulation Analyzer	HP	8901A	3435A06868	CAL 7/18/11	7/18/13
Digital Multimeter	Fluke	FLUKE-77	35053830	CAL 9/9/11	9/9/13
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 10/28/11	10/28/13
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 10/28/11	10/28/13
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 10/28/11	10/28/13
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 10/28/11	10/28/13
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12
Antenna	ETS	3117	41534	9/22/2010	9/22/2012
Antenna	Electro metrics	LPA-25	1122	5/04/2011	5/04/2013
Antenna	Electro metrics	BIA-25	1171	1/15/2010	1/15/2012

APPLICANT: COBRA ELECTRONICS CORPORATION

FCC ID: BBO3K225LTD

REPORT #: C\COBRA\2444BT11\2444BT11TestReport.doc



TEST PROCEDURE

Power Line Conducted Interference: The procedure used was EIA/TIA-382-A using a 50uH LISN. Both lines were observed with the UUT transmitting. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

Bandwidth 20 dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 1 MHz and the video bandwidth (VBW) = 3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10th Harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Radiation Interference: The test procedure used was EIA/TIA-382-A using an Agilent spectrum receiver with pre-selector. The bandwidth (RBW) of the spectrum EIA/TIA-382-A receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

RF POWER OUTPUT


Rule Part No.: Part 2.1033(c), Part 95

Test Requirements:

Method of Measurement: RF power is measured by connecting a 50-ohm, resistive wattmeter to the RF output connector. With a nominal battery voltage, and the transmitter properly adjusted the RF output measures:

Test Data: OUTPUT POWER: HIGH – 4 Watts

Test Setup Diagram:



Part 2.1033 (C)(8) DC Input into the final amplifier

INPUT POWER: $(13.8V)(0.80A) = 11.04$ Watts



FIELD STRENGTH OF SPURIOUS EMISSIONS

Rule Parts. No.: Part 2.1053, 95.635(b)(8)(9)

Requirements: Emissions must be attenuated by at least the following below the output of the transmitter.

$$53 + 10\log(4.00) = 59.0 \text{ dB or}$$

FCC Limit for: 8 kHz Authorized BW

At least 53+10Log(T) dB on any frequency removed from the center of the authorized bandwidth by more than 250%. At least 60 dB on any frequency twice or greater than twice the fundamental.

Test Data:

TF (MHz)	Emission Frequency (MHz)	Ant. Polarity	dB Below Carrier (dBc)		TF (MHz)	Emission Frequency (MHz)	Ant. Polarity	dB Below Carrier (dBc)
26.9	53.90	V	73.90		27.4	54.80	V	74.70
	80.80	V	74.70			82.20	V	75.70
	107.80	V	73.90			109.60	V	75.20
	134.80	H	88.00			137.00	H	80.40
	161.70	H	73.90			164.40	H	79.70
	188.70	H	62.50			191.80	H	63.30
	215.70	H	69.10			219.20	H	68.20
	242.60	H	60.80			246.60	H	60.20
	269.60	H	68.50			274.00	H	69.60

METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 MHz to at least the tenth harmonic of the fundamental. This test was conducted per EIA/TIA-382-A using the substitution method. Measurements were made at the test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

Test Setup Diagram:

