



849 NW State Road 45  
Newberry, Fl 32669 USA  
Phone: 888.472.2424 or 352.472.5500  
Fax: 352.472.2030  
Email: [info@timcoengr.com](mailto:info@timcoengr.com)  
Website: [www.timcoengr.com](http://www.timcoengr.com)

## FCC PART 15 RADAR DETECTOR REPORT

<b>Applicant</b>	COBRA ELECTRONICS CORPORATION
<b>Address</b>	6500 WEST CORTLAND STREET CHICAGO IL IL USA
<b>FCC ID:</b>	BBOIRAD900
<b>Product Description</b>	RADAR DETECTOR WITH BLUETOOTH
<b>Date Sample Received</b>	1/16/2013
<b>Date Tested</b>	1/21/2013
<b>Tested By</b>	JOE SCOGLIO
<b>Approved By</b>	JOE SCOGLIO
<b>Report Number</b>	100AUT13TestReport.doc
<b>Test Results</b>	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL  
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Certificate # 0955-01

**TABLE OF CONTENTS**

GENERAL REMARKS ..... 3  
GENERAL INFORMATION ..... 4  
TEST EQUIPMENT LIST ..... 5  
TEST PROCEDURES ..... 6  
RADIATED SPURIOUS EMISSIONS ..... 8  
VERTICAL PLOT ..... 9  
HORIZONTAL PLOT ..... 10

## GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

### Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report  
 not fulfill the general approval requirements as identified in this test report

### Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.  
849 NW State Road 45  
Newberry, Fl 32669



### Authorized Signatory Name:

Joe Scoglio  
Testing Technician

**Date: January/21/2013**

APPLICANT: COBRA ELECTRONICS CORPORATION  
FCC ID:: BBOIRAD900  
REPORT: C\COBRA\100AUT13\100AUT13TestReport.doc

**GENERAL INFORMATION**

The test results relate only to the items tested.	
<b>DUT Description</b>	RADAR DETECTOR WITH BLUETOOTH
<b>FCC ID</b>	BBOIRAD900
<b>DUT Power Source</b>	<input type="checkbox"/> 110-120Vac/50- 60Hz
	<input checked="" type="checkbox"/> DC Power
	<input type="checkbox"/> Battery Operated Exclusively
<b>Test Item</b>	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
<b>Modifications to DUT</b>	None
<b>Test Standards</b>	FCC Part 15, Subpart B, ANSI C63.4-2003

**TEST EQUIPMENT LIST**

<b>Device</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial Number</b>	<b>Cal/Char Date</b>	<b>Due Date</b>
3/10-Meter OATS	TEI	N/A	N/A	12/31/11	12/31/13
3-Meter OATS	TEI	N/A	N/A	12/31/11	12/31/13
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	12/31/11	12/31/13
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	10/28/11	10/28/13
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	10/28/11	10/28/13
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	10/28/11	10/28/13
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	10/28/11	10/28/13
Antenna: Biconnical	Eaton	94455-1	1057	05/31/11	05/31/13
Antenna: Biconnical	Eaton	94455-1	1096	05/04/11	05/04/13
Antenna: Biconnical	Electro-Metrics	BIA-25	1171	06/13/12	06/13/14
Antenna: Log-Periodic	Eaton	96005	1243	05/31/11	05/31/13
Antenna: Log-Periodic	Electro-Metrics	LPA-25	1122	05/04/11	05/04/13
LISN	Electro-Metrics	ANS-25/2	2604	10/28/11	10/28/13
LISN	Electro-Metrics	EM-7820	2682	02/01/11	02/01/13
Signal Generator	HP	8640B	2308A21464	02/23/12	02/23/14

## TEST PROCEDURES

**General:** This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

**RADIATION INTERFERENCE:** Testing was done in accordance with ANSI C63.4-2003. Section 15.35(b) specifies the use of an average detector in this band. In addition, the peak level of an emission shall not exceed the average limit by more than 20 dB using a minimum Resolution Bandwidth (RBW) of 1 MHz and minimum Video Bandwidth (VBW) OF 1 MHz. The following procedure is designed to determine if there are any spurious emissions from the local oscillator within the band of interest along with any additional spurious emissions caused by other circuitry within the device.

- 1) Determine the frequency of the peak emission:  
Start Frequency 11.7 GHz  
Stop Frequency 12.2 GHz  
RBW equal to or greater than 1 MHz  
VBW equal to or greater than 1 MHz  
Detector Function Peak  
Maximize the emissions with regards to device orientation, antenna polarization, and antenna height. Sweep the band using Max Hold for a minimum of 2 minutes. Record this frequency for measuring the peak emission. In addition record the frequency of other spurious emissions noted.
- 2) Determine the peak level of the emission:  
Center Frequency Set to the frequency determined in Step 1 RBW Equal to or greater than 1 MHz VBW Equal to or greater than 1 MHz Detector Function Peak Measure the value of the peak emission using Max Hold for a minimum of 2 minutes. This can be done at zero span or a frequency span where the analyzer does not show a "Measurement Uncalibrated" message. Record the peak value. If the peak measurement is compliant with the average limit an average measurement is not necessary. If the peak value exceeds the average limit by less than 20 dB proceed to Step 3.
- 3) Determine the average level of the emission:  
Center Frequency Set to the frequency determined in Step 1  
Span Zero  
RBW Equal to or greater than 1 MHz  
VBW Equal to or greater than 10 Hz  
Detector Function Peak  
This measurement uses video averaging and must be done in Linear mode. The analyzer Reference Level is adjusted so that a signal is clearly visible on the screen. Measure the value of the emission using Max Hold for a minimum of 2 minutes. Record this as the average value. Step 2 and Step 3 should be repeated for other spurious emissions.

## TEST PROCEDURES CONTD.

**Formula Of Conversion Factors:** The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB $\mu$ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

**Example:**

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB $\mu$ V	+ 10.36 dB/m	+0.40 dB	=30.76 dB $\mu$ V/m @ 3m

**ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES:** The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

**RADIATED SPURIOUS EMISSIONS**

**Rules Part No.:** 15.109

**Requirements:**

Frequency	Limits
30 – 88	40.0 dBμV/m measured @ 3 meters
80 – 216	43.5 dBμV/m measured @ 3 meters
216 – 960	46.0 dBμV/m measured @ 3 meters
Above 960	54.0 dBμV/m measured @ 3 meters
11.7 to 12.2GHz	54.0 dBμV/m measured @ 3 meters

**Test Procedure:** A search was made of the spectrum from 30 to 1000MHz and from 11.7 to 12.2GHz. Measurements in the 11.7 to 12.2 GHz band were made with a standard gain horn. The measurements in the 11.7 to 12.2 GHz band represent the ambient noise levels. The attached plots were made with peak detector with the analyzer in a maximum hold for 2 minutes.


**Test Data:**

Emission Frequency MHz	Meter Reading dBμV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m	Margin dB
31.00	5.1	H	0.41	13.60	19.11	20.90
31.00	19.5	V	0.41	13.60	33.51	6.49
61.70	12.4	H	0.54	6.89	19.83	20.17
61.70	24.5	V	0.54	6.89	31.93	8.07
86.80	3.7	H	0.62	9.72	14.04	25.96
86.80	8.0	V	0.62	9.72	18.34	21.66
95.30	3.0	H	0.64	10.61	14.25	29.25
95.30	8.1	V	0.64	10.61	19.35	24.15
109.30	5.4	H	0.66	10.26	16.32	27.18
109.30	8.3	V	0.66	10.26	19.22	24.28
343.20	5.2	H	1.14	15.00	21.34	24.66
343.20	7.3	V	1.14	15.00	23.44	22.56
546.70	13.4	H	1.44	18.77	33.61	12.39
546.70	14.2	V	1.44	18.77	34.41	11.59
11,913.00	9.1	V	7.77	29.80	46.67	7.33
11,951.00	9.1	H	7.78	29.80	46.68	7.32

\* The EUT is operating on the following bands; 10.525GHz(X-Band), 24.150GHz(K-Band), 33.4-36.0GHz(KA Band)



**VERTICAL PLOT**



### HORIZONTAL PLOT

