



849 NW STATE ROAD 45
 NEWBERRY, FL 32669 USA
 PH: 888.472.2424 OR 352.472.5500
 FAX: 352.472.2030
 EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

FCC PART 80 TEST REPORT

APPLICANT	COBRA ELECTRONICS CORPORATION
	6500 WEST CORTLAND STREET CHICAGO IL 60707 USA
FCC ID	BBOMRHH500
IC CERTIFICATION	906A-MRHH500
MODEL NUMBER	MRHH500
PRODUCT DESCRIPTION	MARINE TRANSCEIVER
DATE SAMPLE RECEIVED	1/9/2013
DATE TESTED	1/10/2013
TESTED BY	Sushant Kadimdivan
APPROVED BY	Mario de Aranzeta
TIMCO REPORT NO.	56BUT13TestReport.doc
TEST RESULTS	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



TABLE OF CONTENTS

GENERAL REMARKS	3
GENERAL INFORMATION	4
TEST PROCEDURES.....	5
TECHNICAL DATA	6
RF POWER OUTPUT	7
MODULATION CHARACTERISTICS.....	8
AUDIO FREQUENCY RESPONSE.....	9
AUDIO LOW PASS FILTER	10
AUDIO INPUT VERSUS MODULATION.....	11
OCCUPIED BANDWIDTH	12
SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED).....	14
FIELD STRENGTH OF SPURIOUS EMISSIONS	16
FREQUENCY STABILITY	19
EMC EQUIPMENT LIST.....	20

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
 not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: 1/23/2013

Applicant: COBRA ELECTRONICS CORPORATION
FCC ID: BBOMRHH500
Report: C\COBRA\56BUT13\56BUT13TestReport.doc

GENERAL INFORMATION

DUT Specification

DUT Description	MARINE TRANSCIEVER
FCC ID	BBOMRHH500
Model Number	MRHH500
Operating Frequency	156.025-157.425 MHz
Test Frequencies	156.4 MHz, 157.475 MHz
Type of Emission	16K0G3E
Modulation	FM
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz
	<input type="checkbox"/> DC Power 12V
	<input checked="" type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
Type of Equipment	<input type="checkbox"/> Fixed
	<input type="checkbox"/> Mobile
	<input checked="" type="checkbox"/> Portable
Antenna Connector	SMA male
Test Conditions	The temperature was 26°C Relative humidity of 50%.
Modification to the DUT	None
Test Exercise	The DUT was placed in continuous transmit mode.
Applicable Standards	ANSI/TIA 603-C:2004, FCC CFR 47 Part 80
Test Facility	Timco Engineering Inc. at 849 NW State Road 45 Newberry, FL 32669 USA.

TEST PROCEDURES

Power Line Conducted Interference: The procedure used was ANSI/TIA 603-C: 2004 using a 50uH LISN. Both lines were observed with the DUT transmitting. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

Bandwidth 20 dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 1 MHz and the video bandwidth (VBW) = 3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Radiation Interference: The test procedure used was ANSI C63.4-2004 using an Agilent spectrum receiver with pre-selector. The bandwidth (RBW) of the spectrum receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a micro volt at the output of the antenna.

TECHNICAL DATA

- 80.203 (b) **External Controls:** The transmitter is capable of changing frequency between 156.05 – 157.425 MHz by external control. The available channels are shown in the User Manual description Channel List. These channels are preprogrammed by the manufacturer and change of frequency is inaccessible to the station operator.
- 80.203 (c) Five minutes continuous transmission test: The antenna was connected to a dummy load and the radio was locked in a transmit PTT mode. An external timer digital clock was used to observe the duration of the un-modulated transmission. The transmitter turned off and the radio went to receive mode at **4** minutes, **40** seconds as displayed by the external digital clock.
- 80.203 (n) DSC capability: This requirement does not apply to transmitters used with AMTS or hand-held portable transmitters.
The product is a hand-held transmitter and does not have DSC capability.
- 80.873; 80.956 Transmitter G3E emission capability: The transmitter was connected to 50 ohm resistive wattmeter and the frequency was set to 156.300 and to 156.800 MHz.

With normal modulation, the output power displayed was **5** Watts at the high power setting and **0.9** watt at low power setting, consistent with previous measurements.
The transmitter is a handheld device.
- 80.911 (a) 80.956 G3E Transmissions: This radio is capable of G3E emission on 156.300 and 156.800 MHz


RF POWER OUTPUT

Rule Part No.: FCC Part 2.1046(a), 80.215(e)(1)

Test Requirements:

Method of Measurement: RF power is measured by connecting a 50-ohm, resistive wattmeter to the RF output connector. With a nominal battery voltage and the transmitter properly adjusted the RF output measures:

Test Setup Diagram:



Test Data:

OUTPUT POWER: HIGH – 5.0 W
 LOW - 0.9 W

Part 2.1033 (C)(8) DC Input into the final amplifier

FOR LOW POWER SETTING INPUT POWER: (7.4 V) (0.8 A) = 5.92 Watts
 FOR HIGH POWER SETTING INPUT POWER: (7.4 V) (1.41 A) = 10.4 Watts

MODULATION CHARACTERISTICS

Part 2.1033(c) (4) Type of Emission: 16K0G3E, 16K0F3E

FCC Part 80.205(a)

RSS-182, RSS-GEN issue 3

$$B_n = 2M + 2DK$$

$$M = 3000$$

$$D = 4.6\text{kHz (Peak Deviation)}$$

$$K = 1$$

$$B_n = 2(3000) + 2(4.6\text{K})(1) = 16.0\text{K}$$

80.205(a) ALLOWED AUTHORIZED BANDWIDTH – 20.00 kHz

AUDIO FREQUENCY RESPONSE


Rule Part No.: FCC Part 2.1047(a)(b)

Test Requirements:

Method of Measurement:

The audio frequency response was measured in accordance with ANSI/TIA 603-C: 2004. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 – 5000 Hz shall be submitted. The audio frequency response curve is shown below.

AUDIO FREQUENCY RESPONSE PLOT




AUDIO LOW PASS FILTER

VOICE MODULATED COMMUNICATION EQUIPMENT

Rule Part No.: 2.1047(a)

For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all the circuitry installed between the modulation limiter and the modulated stage shall be submitted.

AUDIO LOW PASS FILTER



AUDIO INPUT VERSUS MODULATION


Rule Part No.: FCC Part 2.1047(b) & 80

Test Requirements: Modulation cannot exceed 100%.

Method of Measurement: The audio input level needed for a particular percentage of modulation was measured in accordance with ANSI/TIA 603-C: 2004. The audio input curves versus modulation are shown below. Curves are provided for audio input frequencies of 300, 1000, and 3000 Hz.

Test data:

Modulation Limiting Plot



OCCUPIED BANDWIDTH


**FCC Part 2.1049(c), EMISSION BANDWIDTH
FCC Part 80.213(b)**

Data in the plots show that on any frequency removed from the assigned frequency by more than 50%, but not more than 100%: At least 25dB. On any frequency removed from the assigned frequency by more than 100%, but not more than 250%: At least 35 dB. On any frequency removed from the assigned frequency by more than 250%, of the authorized bandwidth: At least 43 + 10log(P)dB.

Method of Measurement: ANSI/TIA-603-C: 2004

Test Setup Diagram:

OCCUPIED BANDWIDTH MEASUREMENT




Test Data: See the plot below

NOTES:

OCCUPIED BANDWIDTH - 2500 Hz

FCC 90.210 Mask B

REF dBuV/m 77.00 SPAN (Hz) 100.00k Timco Engineering, Inc.



RBW 300 Hz	VBW 300 Hz	ST (sec) 2	Peak 156.801 76.20 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
Center Frequency (Hz) 156.801M			MKR2 156.791 -2.30 <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
Marker Delta (Hz) 0.00			MKR3 156.750 -6.50 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
			HWMK 23.076 6.27 <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)

Rule Part No.: FCC Part 2.1051(a), 80.211

Requirements: Emissions must be 43+10 log (PO) dB below the mean power output of the transmitter.
 43+10 log (5) = 50 dB
 43+10 log (0.9) = 42.5 dB


Method of Measurement: The carrier was modulated 100% using a 2500 Hz tone. The spectrum was scanned from 0.4 to at least the 10th harmonic of the fundamental. The measurements were made in accordance with standard ANSI/TIA 603-C: 2004.

Test Data:

TF HIGH POWER	EF MHz	dB below carrier		TF LOW POWER	EF MHz	dB below carrier
156.4 MHz		0		156.4 MHz		0
	118	88.4			118	73.6
	135.5	87.3			135.5	65.6
	312.8	82.2			312.8	67.4
	469.2	89.6			469.2	90
	625.6	99.6			625.6	93
	782	100.8			782	97
	938.4	102.4			938.4	93
	1094.8	102.5			1094.8	93.4
	1251.2	102.2			1251.2	93.2
	1407.6	100.7			1407.6	93.6
	1564	103.8			1564	93

TF HIGH POWER	EF MHz	dB below carrier		TF LOW POWER	EF MHz	dB below carrier
157.4 MHz		0		157.4 MHz		0
	118.1	88.5			118.1	73.6
	136.5	86.8			136.5	66.7
	314.8	80.9			314.8	67.9
	472.2	92.3			472.2	88.9
	629.6	101.1			629.6	94.2
	787	101.6			787	93.2
	944.4	102.3			944.4	92.7
	1101.8	100.9			1101.8	93.4
	1259.2	101.8			1259.2	93.1
	1416.6	99.9			1416.6	93.2
	1574	100.8			1574	92.9

Method of Measuring Conducted Spurious Emissions



METHOD OF MEASUREMENT: The procedure used was ANSI/TIA 603-C: 2004 without any exceptions. The measurements were made at TIMCO ENGINEERING INC. 849 N.W. State Road 45, Newberry, Florida 32669.


FIELD STRENGTH OF SPURIOUS EMISSIONS

Rule Parts. No.: FCC Part 2.1053

Requirements: Emissions must be $43+10\log(PO)$ dB below the mean power output of the transmitter.
 $43+10 \log (5) = 50$ dB
 $43+10 \log (0.9) = 42.5$ dB

METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 MHz to at least the tenth harmonic of the fundamental. This test was conducted per ANSI/TIA 603-C:2004 using the substitution method. Measurements were made at the test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

Test Setup Diagram:



Test Data:

156.4 MHz - HIGH POWER

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
156.40	0	0
312.80	H	91.5
469.20	V	79.0
625.60	H	85.7
782.00	H	95.4
938.40	V	91.8
1094.80	V	90.0
1251.20	V	82.9
1407.60	V	80.5
1564.00	V	90.7

156.4 MHz - LOW POWER

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
156.40	0	0
312.80	H	81.1
469.20	H	86.7
625.60	H	87.1
782.00	H	93.1
938.40	H	93.7
1094.80	V	89.2
1251.20	V	87.2
1407.60	V	87.4
1564.00	V	88.6

157.425 MHz – HIGH POWER

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
157.43		0
314.85	H	90.6
472.28	V	80.5
629.70	H	86.6
787.13	H	95.9
944.55	V	91.1
1101.98	V	90.9
1259.40	V	81.8
1416.83	V	81.2
1574.25	V	91.4

157.425 MHz – LOW POWER

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
157.43		0
314.85	H	81.3
472.28	H	89.1
629.70	H	88.8
787.13	H	94.3
944.55	H	94.5
1101.98	V	91.3
1259.40	V	87.0
1416.83	V	87.1
1574.25	V	89.0

FREQUENCY STABILITY

Rule Parts. No.: FCC Part 2.1055, Part 80.209(a)

Requirements: Temperature and voltage tests were performed to verify that the frequency remains within the .0010%, 10.0 ppm, specification limit, for 20 kHz spacing. The test was conducted as follows: The transmitter was placed in the temperature chamber at 25°C and allowed to stabilize for one hour. The transmitter was keyed ON for one minute during which four frequency readings were recorded at 15 second intervals. The worst-case number was taken for temperature plotting. The assigned channel frequency was considered to be the reference frequency. The temperature was then reduced to -20°C after which the transmitter was again allowed to stabilize for one hour. The transmitter was keyed ON for one minute and was again allowed to stabilize for one hour. The transmitter was keyed ON for one minute and again frequency readings were noted at 15 sec intervals. The worst-case number was recorded for temperature plotting. This procedure was repeated in 10-degree increments up to +50°C.

Method of Measurements: ANSI/TIA 603-C: 2004

Test Data:

Assigned Frequency (Ref. Frequency) (MHz)		
Temperature (°C)	Frequency (MHz)	Frequency Stability (PPM)
-30	156.79863	-9.31
-20	156.79935	-4.72
-10	156.79981	-1.79
0	156.80001	-0.51
+10	156.80003	-0.38
+20	156.79994	-0.96
+30	156.80020	0.70
+40	156.80007	-0.13
+50	156.80008	-0.06

Assigned Frequency (Ref. Frequency) (MHz)		
% Battery (%)	Frequency (MHz)	Frequency Stability (PPM)
-15%	156.80009	0
0	156.80009	0
+15%	156.80009	0

EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	10/28/11	10/28/13
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	10/28/11	10/28/13
Antenna: Biconnical	Electro-Metrics	BIA-25	1171	06/13/12	06/13/14
Antenna: Biconnical	Eaton	94455-1	1096	05/04/11	05/04/13
Antenna: Log-Periodic	Electro-Metrics	LPA-25	1122	05/04/11	05/04/13
Frequency Counter	HP	5352B	2632A00165	06/22/11	06/22/13
Frequency Counter	HP	5385A	2730A03025	08/17/11	08/17/13
Signal Generator	HP	8640B	2308A21464	02/23/12	02/23/14
Hygro-Thermometer	Extech	445703	0602	06/15/11	06/15/13
Digital Multimeter	Fluke	77	35053830	09/09/11	09/09/13
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	10/28/11	10/28/13
Antenna: Passive Loop	EMC Test Systems	EMCO 6512	9706-1211	06/14/12	06/14/14
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	10/28/11	10/28/13
Temperature Chamber	Tenney Engineering	TTRC	11717-7	07/03/12	07/03/14
Frequency Counter	HP	5385A	3242A07460	06/22/11	06/22/13
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	12/31/11	12/31/13