



849 NW State Road 45  
Newberry, FL 32669 USA  
Ph: 888.472.2424 or 352.472.5500  
Fax: 352.472.2030  
Email: [info@timcoengr.com](mailto:info@timcoengr.com)  
Website: [www.timcoengr.com](http://www.timcoengr.com)

---

## FCC PART 15.249 TEST REPORT UNLICENSED INTENTIONAL RADIATOR

Applicant	COBRA ELECTRONICS CORPORATION
Address	6500 WEST CORTLAND STREET CHICAGO IL 60707 USA
FCC ID	BBORBTM100
Model Number	RBTM100
Product Description	BLUETOOTH TRANSMITTER
Date Sample Received	7/8/2010
Date Tested	8/2/2010
Tested By	Nam Nguyen
Approved By	Mario de Aranzeta
Report Number	1643AT10TestReport.doc
Test Results	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL  
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Certificate # 0955-01



## TABLE OF CONTENT

GENERAL REMARKS.....	3
GENERAL INFORMATION.....	4
EMC EQUIPMENT LIST .....	5
TEST PROCEDURES .....	6
RADIATION INTERFERENCE.....	7
OCCUPIED BANDWIDTH.....	9
BAND EDGE COMPLIANCE.....	10
POWER LINE CONDUCTED INTERFERENCE .....	14

APPLICANT: COBRA ELECTRONICS CORPORATION  
FCC ID: BBORBTM100  
REPORT #: C\COBRA\1643AT10\1643AT10TestReport.doc

## GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

## Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report  
 not fulfill the general approval requirements as identified in this test report

## Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.  
849 NW State Road 45  
Newberry, Fl 32669



## Authorized Signatory Name:

Mario de Aranzeta C.E.T.  
Compliance Engineer/ Lab. Supervisor

**Date:** 8/2/2010

APPLICANT: COBRA ELECTRONICS CORPORATION  
FCC ID: BBORBTM100  
REPORT #: C\COBRA\1643AT10\1643AT10TestReport.doc

**GENERAL INFORMATION**

**DUT Specification**

The test results relate only to the items tested.			
Applicable Standard	Part 15.249		
DUT Description	BLUETOOTH TRANSMITTER		
FCC ID	BBORBTM100		
Model Number	RBTM100		
Operating Frequency	TX: (2402.00 – 2480.00) MHz	RX: Same	
DUT Power Source	<input type="checkbox"/> 110–120Vac/50– 60Hz		
	<input checked="" type="checkbox"/> DC Power		
	<input type="checkbox"/> Battery Operated Exclusively		
Test Item	<input type="checkbox"/> Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production
Type of Equipment	<input type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input checked="" type="checkbox"/> Portable
Antenna Connector	None, integrated antenna		
Test Facility	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
Test Conditions	Temperature: 26°C Relative humidity: 50%		
Test Exercise	The DUT was placed in continuous transmit mode of operation.		
Modifications	none		

**Test Supporting Equipment**

Supporting Device	Manufacturer	Model / FCC ID	Serial Number
iPod touch	Apple Inc.	A1288	8M0127P975J

**EMC EQUIPMENT LIST**

<b>Device</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial Number</b>	<b>Cal/Char Date</b>	<b>Due Date</b>
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 3/10/10	3/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 3/23/09	3/23/11
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 6/10/09	6/10/11
Frequency Counter	HP	5385A	3242A07460	CAL 5/26/09	5/26/11
Hygro-Thermometer	Extech	445703	0602	CAL 1/30/09	1/30/11
Modulation Analyzer	HP	8901A	3435A06868	CAL 5/26/09	5/26/11
Digital Multimeter	Fluke	FLUKE-77-3	79510405	CAL 5/18/09	5/18/11
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/21/09	11/21/11
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 11/22/09	11/22/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/21/09	11/21/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/24/09	11/24/11
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12

APPLICANT: COBRA ELECTRONICS CORPORATION  
 FCC ID: BBORBTM100  
 REPORT #: C\COBRA\1643AT10\1643AT10TestReport.doc

## TEST PROCEDURES

**Radiation Interference:** ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

**Formula Of Conversion Factors:** The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+ CL = FS
33	20 dBuV	+ 10.36 dB	+ 0.5 = 30.86 dBuV/m @ 3m

**Power Line Conducted Interference:** The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

**Occupied Bandwidth:** A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

**ANSI C63.4-2003 10.1 Measurement Procedures:** The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

**RADIATION INTERFERENCE**

**Rules Part No.:** 15.249, 15.209

**Requirements:**

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) $\mu$ V/m @ 300 meters
490 to 1705 kHz	24000/F (kHz) $\mu$ V/m @ 30 meters
1705 kHz to 30 MHz	29.54 dB $\mu$ V/m @ 30 meters
30 – 88	40.0 dB $\mu$ V/m @ 3 meters
80 – 216	43.5 dB $\mu$ V/m @ 3 meters
216 – 960	46.0 dB $\mu$ V/m @ 3 meters
Above 960	54.0 dB $\mu$ V/m @ 3 meters
Part 15.249	
Fundamental 902 – 928 MHz	94.0 dB $\mu$ V/m @ 3 meters
Fundamental 2.4 – 2.4835 MHz	94.0 dB $\mu$ V/m @ 3 meters
Harmonics	54.0 dB $\mu$ V/m @ 3 meters

**Test Data:** The EUT paired with iPod touch to turn on its blue tooth.  
Part 15.209

Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBuV/m	Margin dB
30.50	8.9	V	0.40	12.43	21.73	18.27
69.10	9.3	V	0.56	5.65	15.51	24.49
70.80	5.9	H	0.57	5.51	11.98	28.02
84.60	13.5	V	0.61	10.18	24.29	15.71
113.00	8.0	V	0.66	10.88	19.54	23.96
131.70	15.9	H	0.68	13.28	29.86	13.64
142.40	11.6	H	0.69	15.44	27.73	15.77
161.60	11.3	H	0.75	16.34	28.39	15.11
250.23	3.9	H	1.00	12.51	17.41	28.59
250.52	4.1	V	1.00	12.52	17.62	28.38
352.78	4.9	V	1.15	14.66	20.71	25.29
547.14	8.0	V	1.44	18.10	27.54	18.46
547.60	6.7	H	1.44	18.53	26.67	19.33
749.13	4.5	H	1.80	21.57	27.87	18.13



Part 15.249

Test data: The test result 3 places in the band worst case data presented below.

Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBuV/m	Margin dB
2,413.90	57.0	H	3.19	32.28	92.47	1.53
2,413.90	57.2	V	3.19	32.28	92.67	1.33
4827.80	7.5	H	4.91	34.10	46.51	7.49
4827.80	6.8	V	4.91	34.10	45.81	8.19
7241.70	7.2	V	5.74	36.05	48.99	5.01
7241.70	7.7	H	5.74	36.05	49.49	4.51
9655.60	7.4	V	6.80	36.76	50.96	3.04
9655.60	7.6	H	6.80	36.76	51.16	2.84
2,437.20	57.8	V	3.20	32.32	93.32	0.68
2,437.20	53.9	H	3.21	32.34	89.45	4.55
4874.40	7.1	H	4.94	34.10	46.14	7.86
4874.40	6.6	V	4.94	34.10	45.64	8.36
7311.60	7.5	H	5.79	36.06	49.35	4.65
7311.60	7.1	V	5.79	36.06	48.95	5.05
9748.80	7.3	V	6.83	36.90	51.03	2.97
9748.80	7.5	H	6.83	36.90	51.23	2.77
12186.00	5.3	V	7.94	38.86	52.10	1.90
12186.00	5.6	H	7.94	38.86	52.40	1.60
2,477.30	55.4	V	3.23	32.44	91.07	2.93
2,477.30	54.6	H	3.23	32.44	90.27	3.73
4954.60	7.8	H	5.00	34.30	47.10	6.90
4954.60	6.9	V	5.00	34.30	46.20	7.80
7431.90	7.8	H	5.84	36.11	49.75	4.25
7431.90	7.6	V	5.84	36.11	49.55	4.45
9909.20	7.1	V	6.85	36.91	50.86	3.14
9909.20	7.3	H	6.85	36.91	51.06	2.94
12386.50	5.3	V	8.01	38.86	52.17	1.83
12386.50	5.6	H	8.01	38.86	52.47	1.53




**OCCUPIED BANDWIDTH**

**Rules Part No.:** 15.249 (d)

**Requirements:** The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

**Test Data:**




**BAND EDGE COMPLIANCE**

**Rules Part No.:** 15.249 (d)

**Requirements:** 40 dBc or in the case of restricted bands 54 dBuV/m.

**Test Data:** Both vertical and horizontal antenna polarity was tested, and the following plots are the worst cases.

Lower bandedge




Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity V/H	Coax Loss dB	Correction Factor dB/m	Field Strength dBuV/m	Margin dB
2402.00	2402.00	53.80	V	3.18	32.25	89.23	4.77
2402.00	2400.00	14.0	V	3.18	32.25	49.43	4.57
2402.00	2321.90	9.60	V	3.13	32.04	44.76	9.24

APPLICANT: COBRA ELECTRONICS CORPORATION


FCC ID: BBORBTM100

REPORT: C:\COBRA\1643AT10\1643AT10TestReport.doc



Upper bandedge

Peak Plot



Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity V/H	Coax Loss dB	Correction Factor dB/m	Field Strength dBuV/m	Margin dB
2480.20	2480.20	51.20	V	3.24	32.45	86.89	7.11
2480.20	2488.95	8.20	V	3.24	32.47	43.91	10.09
2480.20	2483.5	8.20	V	3.24	32.46	43.90	10.1



APPLICANT: COBRA ELECTRONICS CORPORATION  
 FCC ID: BBORBTM100  
 REPORT: C:\COBRA\1643AT10\1643AT10TestReport.doc

**POWER LINE CONDUCTED INTERFERENCE**

**Rules Part No.:** 15.207

**Requirements:**

Frequency (MHz)	Quasi Peak Limits (dB $\mu$ V)	Average Limits (dB $\mu$ V)
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5.0	56	46
5.0 – 30	60	50

**Test Data:** The attached graphs represent the emissions read for power line conducted for this device. Both lines were observed.

N/A  
Battery or vehicle powered DUT.