



RF TEST REPORT

Report No.: 20240317G03742X-W4

Product Name: Cobra-SC120

Model No.: SC120, SC110 Series

FCC ID: BBOSC120

Applicant: Cobra Electronics Corporation

Address: 1701 Golf Road Suite 3-900, Rolling Meadows, IL 60008, United States.

Dates of Testing: 03/06/2024 - 05/21/2024

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.


Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 122 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product.....: Cobra-SC120
Brand Name.....: Cobra
Trade Name: Cobra
Applicant.....: Cobra Electronics Corporation
Applicant Address.....: 1701 Golf Road Suite 3-900, Rolling Meadows, IL 60008,
United States.
Manufacturer.....: Cobra Electronics Corporation
Manufacturer Address.....: 1701 Golf Road Suite 3-900, Rolling Meadows, IL 60008,
United States.
Test Standards.....: 47 CFR Part 15 Subpart E 15.407
ANSI C63.10-2013
Test Result.....: Pass

Tested by:  2024.05.21

Chuiwang Zhang, Test Engineer

Reviewed by.....:  2024.05.21

Chris You, Senior Engineer

Approved by.....:  2024.05.21

Yang Fan, Manager



Table of Contents

1. GENERAL INFORMATION	5
1.1. EUT Description	5
1.2. Test Standards and Results	7
1.3. Channel List	8
1.4. Test environment and mode	9
1.5. Table for Supporting Units	10
1.6. Laboratory Facilities	11
2. TEST REQUIREMENTS	12
2.1. Antenna requirement	12
2.2. Maximum Conducted Output Power	13
2.3. Power spectral density (PSD)	15
2.4. 26dB Emission Bandwidth and 99% Occupied Bandwidth	17
2.5. Frequency Stability	19
2.6. Radiated Band Edge and Spurious Emission	21
2.7. AC Power Line Conducted Emission	40
3. LIST OF MEASURING EQUIPMENT	42
4. UNCERTAINTY OF EVALUATION	43
APPENDIX A	44



Change History		
Issue	Date	Reason for change
1.0	2024.05.21	First edition



1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Cobra-SC120
Model No.	SC120, SC110 Series
Hardware Version	90100S00002757
Software Version	V1.5
EUT supports Radios application	WLAN5.0GHz 802.11a/n/ac
Product Type	Client devices
Modulation Type	802.11a/n: OFDM (BPSK/QPSK/16QAM/64QAM) 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)
Transfer Rate	802.11a: 54/48/36/24/18/12/9/6 Mbps 802.11n: up to 150 Mbps 802.11ac: up to 433.333 Mbps
Frequency Range	UNII-1: 5150 ~ 5250MHz UNII-2a: 5250 ~ 5350MHz UNII-2c: 5470 ~ 5725MHz UNII-3: 5725 ~ 5850MHz
Channel Bandwidth	802.11a: 20MHz 802.11n: 20MHz/40MHz 802.11ac: 20MHz/40MHz/80MHz
Channel Number	UNII-1: 4 for 802.11a, 802.11n(HT20), 802.11ac(VHT20) 2 for 802.11n(HT40), 802.11ac(VHT40) 1 for 802.11ac(VHT80) UNII-2a: 4 for 802.11a, 802.11n(HT20), 802.11ac(VHT20) 2 for 802.11n(HT40), 802.11ac(VHT40), 1 for 802.11ac(VHT80) UNII-2c: 11 for 802.11a, 802.11n(HT20), 802.11ac(VHT20) 5 for 802.11n(HT40), 802.11ac(VHT40) 2 for 802.11ac(VHT80) UNII-3: 5 for 802.11a, 802.11n(HT20), 802.11ac(VHT20) 2 for 802.11n(HT40), 802.11ac(VHT40) 1 for 802.11ac(VHT80)
Antenna Type	Internal Antenna
Antenna Gain	1.47dBi
Output Power (Max.)	UNII-1: 11.94dBm UNII-2a: 9.85dBm



	UNII-2c: 8.36dBm UNII-3: 10.94dBm
Test Control Software	SecureCRT
Power supply	DC 5V(USB)

Note 1: The information of antenna gain and cable loss is provided by the manufacturer and our lab is not responsible for the accuracy of the antenna gain and cable loss information.

Note 2: Model: SC120 SC110 Series have the same PCB board, electromagnetic emissions and electromagnetic compatibility characteristics. The below table show differences:

Model No.	Differences
SC120	With SD card
SC110 Series	Without SD card

1.2. Test Standards and Results

The purpose of the report is to conduct testing according to the following FCC/IC certification standards:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart E §15.407	Radio Frequency Devices
2	KDB789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test detailed items/section required by FCC rules and results are as below:

No.	FCC Rule	Description	Result
1	15.203 15.407(a)	Antenna Requirement	PASS
2	15.407(a)(1)(iv) 15.407 (a)(2) 15.407(a)(3)(i)	Maximum Conducted Output Power	PASS
3	15.407(a)(12)	26dB Emission Bandwidth 99% Occupied Bandwidth	PASS
4	15.407(e)	6dB Emission Bandwidth	PASS
5	15.407(a)(1)(iv) 15.407 (a)(2) 15.407(a)(3)(i)	Power spectral density (PSD)	PASS
6	15.207	AC Power Line Conducted Emission	N/A ^{Note 1}
7	15.205 15.209 15.407(b)(1) 15.407(b)(2) 15.407(b)(3) 15.407(b)(4)	Radiated Band Edges and Spurious Emission	PASS
8	15.407(g)	Frequency Stability	PASS

Note 1: Not applicable, the product is only powered by car charger DC.

1.3. Channel List

Operated band in 5150 MHz ~ 5250MHz

4 channels are provided for 802.11a, 802.11n-HT20 and 802.11ac-VHT20.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	44	5220
40	5200	48	5240

2 channels are provided for 802.11n-HT40 and 802.11ac-VHT40.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
38	5190	46	5230

1 channels are provided for 802.11ac-VHT80.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
42	5210	/	/

Operated band in 5250 MHz ~ 5350MHz

4 channels are provided for 802.11a, 802.11n-HT20 and 802.11ac-VHT20.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
52	5260	60	5300
56	5280	64	5320

2 channels are provided for 802.11n-HT40 and 802.11ac-VHT40.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
54	5270	62	5310

1 channels are provided for 802.11ac-VHT80.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
58	5290	/	/

Operated band in 5470 MHz ~ 5725MHz

11 channels are provided for 802.11a, 802.11n-HT20 and 802.11ac-VHT20.

Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
100	5500	116	5580	132	5660
104	5520	120	5600	136	5680
108	5540	124	5620	140	5700
112	5560	128	5640	/	/

5 channels are provided for 802.11n-HT40 and 802.11ac-VHT40.

Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
102	5510	118	5590	134	5670
110	5550	126	5630	/	/

2 channels are provided for 802.11ac-VHT80.

Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
106	5530	122	5610	/	/

Operated band in 5725 MHz ~ 5850MHz

5 channels are provided for 802.11a, 802.11n-HT20 and 802.11ac-VHT20.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

2 channels are provided for 802.11n-HT40 and 802.11ac-VHT40.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
151	5755	159	5795

1 channel are provided for 802.11ac-VHT80

Channel	Frequency(MHz)	Channel	Frequency(MHz)
155	5775	/	/

1.4. Test environment and mode

During the measurement, the environmental conditions were within the listed ranges:

Operating Environment	
Temperature	15°C - 35°C
Humidity	30% -60%
Atmospheric Pressure	86kPa-106kPa
Test mode:	
Continuously transmitting mode	Keeps the EUT in 100% duty cycle transmitting with modulation in SISO, duty cycle factor is not required.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

For Frequency band 5150 ~ 5250 MHz				
Test Mode	Frequency(MHz)			Data rate
	LCH	MCH	HCH	
802.11a	5180	5220	5240	6 Mbps
802.11n-HT20/ac-VHT20				MCS 0
802.11n-HT40/ac-VHT40	5190	/	5230	MCS 0
802.11ac-VHT80	5210	/	/	MCS 0
Note: After scanning all modulation types and data rates for all test patterns, the above list was found to be the worst case.				

For Frequency band 5250 ~ 5350 MHz				
Test Mode	Frequency(MHz)			Data rate
	LCH	MCH	HCH	
802.11a	5260	5300	5320	6 Mbps
802.11n-HT20/ac-VHT20				MCS 0
802.11n-HT40/ac-VHT40	5270	/	5310	MCS 0
802.11ac-VHT80	5290	/	/	MCS 0
Note: After scanning all modulation types and data rates for all test patterns, the above list was found to be the worst case.				

For Frequency band 5470 ~ 5725 MHz				
Test Mode	Frequency(MHz)			Data rate
	LCH	MCH	HCH	
802.11a	5500	5580	5700	6 Mbps
802.11n-HT20/ac-VHT20				MCS 0
802.11n-HT40/ac-VHT40	5510	5550	5670	MCS 0
802.11ac-VHT80	5530	/	/	MCS 0
Note: After scanning all modulation types and data rates for all test patterns, the above list was found to be the worst case.				

For Frequency band 5725 ~ 5850 MHz				
Test Mode	Frequency(MHz)			Data rate
	LCH	MCH	HCH	
802.11a	5745	5785	5825	6 Mbps
802.11n-HT20/ac-VHT20				MCS 0
802.11n-HT40/ac-VHT40	5755	/	5795	MCS 0
802.11ac-VHT80	5775	/	/	MCS 0
Note: After scanning all modulation types and data rates for all test patterns, the above list was found to be the worst case.				

1.5. Table for Supporting Units

Support Equipment:

No.	Equipment	Brand Name	Model Name	Manufacturer	Serial No.	Note
1	Laptop	HP	TPN-Q221	HP	5CD14347QB	FCC DOC

Support Cable:

Description	Shield Type	Ferrite Core	Length
DC Power Cable	Un- shielding	/	3.5m



1.6. Laboratory Facilities

FCC-Registration No.: 406086

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Jun. 30th, 2025.

ISED Registration: 11185A

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A on Aug. 04, 2016, valid time is until Jun. 30th, 2025.

CAB number: CN0064

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

2. Test Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

According to FCC 15.407(a)(1): For client devices in the 5.15-5.25 GHz band, If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to FCC 15.407(a)(2): For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to FCC 15.407(a)(3): For the band 5.725-5.850 GHz, If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

2.1.2. Antenna Information

Antenna Category: Internal Antenna

A internal Antenna was soldered to the antenna port of EUT via an adaptor cable, can't be removed.

Antenna General Information:

No.	EUT	Operating frequency range	Ant. Type	Ant. Gain
1	Cobra-SC120	UNII-1, UNII-2a, UNII-2c, UNII-3	Internal	1.47dBi

2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Maximum Conducted Output Power

2.2.1. Limit of Maximum Conducted Output Power

FCC Part 15.407(a):

The maximum conducted output power should not exceed:


Band	EUT Category	Limit
U-NII-1	☐ Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21dBm) at any elevation angle above 30 degrees as measured from the horizon)
	☐ Fixed point-to-point Access device	1 Watt (30 dBm)
	☐ Indoor Access Point	1 Watt (30 dBm)
	☒ Mobile and portable client device	250mW (24 dBm)
U-NII-2A	☒	250mW (24 dBm) or 11dBm+10logB* Whichever is less.
U-NII-2C	☒	250mW (24 dBm) or 11dBm+10logB* Whichever is less.
U-NII-3	☒	1 Watt (30 dBm)

Note: B* is the 26 dB emission bandwidth in MHz.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

1. The testing follows the of KDB 789033 D02 v02r01 Section II.E.2.b and ANSI C63.10-2013 Section 12.3.2.2.
2. The RF output of EUT was connected to spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Power is calculated by integrating over the spectrum of the entire 99% OBW signal using the instrument's band power measurement feature.
4. Set span to encompass the entire 99% OBW of the signal.
5. Set RBW = 1MHz, VBW $\geq$ 3MHz, Sweep time = Auto, Detector = power averaging (RMS).

6. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
7. Trace average at least 100 traces in power averaging (rms) mode.
8. Replace the EUT center frequency and repeat steps 3~7.

2.2.5. Test Results of Maximum Conducted Output Power

Please refer to APPENDIX A for detail.

2.3. Power spectral density (PSD)

2.3.1. Limit of Power Spectral Density

FCC Part 15.407(a)


The maximum power spectral density should not exceed:

Band	EUT Category	Limit
U-NII-1	☐ Outdoor Access Point	17 dBm/MHz
	☐ Fixed point-to-point Access device	
	☐ Indoor Access Point	
	☒ Mobile and portable client device	11 dBm/MHz
U-NII-2A	☒	11 dBm/MHz
U-NII-2C	☒	11 dBm/MHz
U-NII-3	☒	30dBm/500kHz

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

1. The testing follows the of KDB 789033 D02 v02r01 Section II.F and ANSI C63.10-2013 Section 12.5.
2. The RF output of EUT was connected to spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set span to encompass the entire 99% OBW of the signal.
4. For U-NII-1, U-NII-2a, U-NII-2c Band: Set RBW = 1MHz, VBW $\geq$ 3MHz, Sweep time = Auto, Detector = power averaging (RMS).
5. For U-NII-3 Band: Set RBW = 500kHz, VBW $\geq$ 3MHz, Sweep time = Auto, Detector = power averaging (RMS).
6. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
7. Trace average at least 100 traces in power averaging (rms) mode.
8. Use the peak search function on the instrument to find the peak of the spectrum.



9. Replace the EUT center frequency and repeat steps 3~8.

2.3.5. Test Result of Power Spectral Density

Please refer to APPENDIX A for detail.

2.4. 26dB Emission Bandwidth and 99% Occupied Bandwidth

2.4.1. Limit of 26dB Emission Bandwidth and 99% Occupied Bandwidth


26dB Emission Bandwidth and 99% Occupied Bandwidth no Bandwidth limit.

The minimum 6dB bandwidth of U-NII-3 shall be at least 500 kHz.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Description



2.4.4. Test Procedures

1. The testing follows the of KDB 789033 D02 v02r01 Section II.C.D and ANSI C63.10-2013 Section 12.4.
2. The RF output of EUT was connected to spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Use the spectrum analyzer “Channel Bandwidth” function to easurement the 26dB EBW, 6dB EBW and 99% OBW.
4. Set center frequency to the nominal EUT channel center frequency.
5. Set span = 1.5 times to 5.0 times the OBW or EBW.
6. For 26dB EBW and 99% OBW Measurement:
Set RBW = approximately 1% EBW or 1.5 times to 5.0 times the OBW, $VBW \geq 3 \times RBW$.
7. For 6dB EBW Measurement:
Set RBW =100kHz, $VBW \geq 3 \times RBW$.
8. Set Detector = Peak, Trace mode = max hold and Sweep time = auto couple.
9. Allow the trace to stabilize.
10. Replace the EUT center frequency and repeat steps 3~9.



2.4.5. Test Results of 26dB Emission Bandwidth and 99% Occupied Bandwidth

Please refer to APPENDIX A for detail.

2.5. Frequency Stability


2.5.1. Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedures

1. The testing follows the of KDB 789033 D02 v02r01 Section II.A.3 and ANSI C63.10-2013 Section 6.8.
2. The EUT is installed in an environment test chamber with external power source, was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set the chamber to operate at 50°C and external power source to output at nominal voltage of EUT.
5. A sufficient stabilization period at each temperatures in used prior to each frequency measurement.
6. The test shall be performed under -30°C to 50°C and 85% to 115% of the nominal voltage. Change setting of chamber and external power source to complete all conditions.
7. Replace the EUT center frequency and repeat steps 3~6.



2.5.5. Test Result of Frequency Stability

Please refer to APPENDIX A for detail.

2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

Radiated emission which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level ($\mu\text{V/m}$).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

FCC Part 15.407(b)			
Frequency Band (MHz)	Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength @3m (dB $\mu\text{V/m}$)
5150 - 5250	Outside of the 5.15~5.35 GHz	-27	68.2
5725 - 5850	< 5650	-27	68.2
	5650~5700	-27~10	68.2~105.2
	5700~5720	10~15.6	105.2~110.8
	5720~5725	15.6~27	110.8~122.2
	5850~5855	27~15.6	122.2~110.8
	5855~5875	15.6~10	110.8~105.2
	5875~5925	10~-27	105.2~68.2
	> 5925	-27	68.2

Note:

- 1) $\text{EIRP}[\text{dBm}] = \text{E}[\text{dB}\mu\text{V/m}] + 20 \log (d[\text{m}]) - 104.77$, d is the measurement distance in m.
- 2) $\text{E}[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2 = 68.2 \text{ dB}\mu\text{V/m}$, for $\text{EIRP}[\text{dBm}] = -27\text{dBm}$.
 $\text{E}[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2 = 105.2 \text{ dB}\mu\text{V/m}$, for $\text{EIRP}[\text{dBm}] = 10\text{dBm}$.
 $\text{E}[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2 = 110.8 \text{ dB}\mu\text{V/m}$, for $\text{EIRP}[\text{dBm}] = 15.6\text{dBm}$.
 $\text{E}[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2 = 122.2 \text{ dB}\mu\text{V/m}$, for $\text{EIRP}[\text{dBm}] = 27\text{dBm}$.

Applicable To	Limit	
KDB 789033 D02 General UNII Test Procedures New Rules v02r01	Field Strength at 3m	
	PK: 68.2(dB μ V/m)	AV: 54 (dB μ V/m)

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41	/	/	/


Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
²Above 38.6.

2.6.2. Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

2.6.3. Test Setup


For radiated emissions from 9 kHz to 30 MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.6.4. Test Procedures

1. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
6. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for

Quasi-peak detection (QP) at frequency below 1 GHz.

2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. Only worst-Case mode data provide here, 802.11a (20MHz) 5180MHz for Below 1GHz.

2.6.5. Test Result of Radiated Band Edge and Spurious Emission

For 9 kHz to 30MHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For 30MHz to 1GHz, All of the EUT Configure mode were tested and found 802.11a_5825MHz channel is the worst mode, the worst case is recorded in this report.


For 1GHz to 18GHz, Only worst-case data is reported.

For above 18GHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For 30MHz to 1000 MHz

Test site:	3M anechoic chamber	Environment:	Temp: 23℃; Humi:48%;101kPa
Operator:	Deng ShanFei	Test Date:	2024.03.08
Test Mode:	5G WIFI - TX	Test Result:	Pass

EMI Sweep-3M(30-1G)




Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Polarity	Corr. (dB/m)	Margin - QPK	Limit - QPK
30.000000	21.70	120.000	100.0	H	21.1	18.30	40.0
47.480000	15.77	120.000	100.0	H	11.7	24.23	40.0
138.840000	21.02	120.000	100.0	H	13.8	22.48	43.5
187.440000	22.82	120.000	100.0	H	11.3	20.68	43.5
232.160000	23.90	120.000	100.0	H	12.8	22.10	46.0
935.840000	27.94	120.000	100.0	H	25.0	18.06	46.0

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
3. Margin value = Limit value - Emission Level.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Only the antenna height (from 1m to 4m) at maximum reading are recorded.

Test site:	3M anechoic chamber	Environment:	Temp: 23°C; Humi:48%;101kPa
Operator:	Deng ShanFei	Test Date:	2024.03.08
Test Mode:	5G WIFI - TX	Test Result:	Pass

EMI Sweep-3M(30-1G)



Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Polarity	Corr. (dB/m)	Margin - QPK	Limit - QPK
31.960000	36.64	120.000	100.0	V	20.1	3.36	40.0
47.480000	29.29	120.000	100.0	V	11.7	10.71	40.0
117.480000	30.49	120.000	100.0	V	13.0	13.01	43.5
129.120000	28.00	120.000	100.0	V	13.6	15.50	43.5
230.240000	25.16	120.000	100.0	V	12.7	20.84	46.0
900.880000	32.12	120.000	100.0	V	24.3	13.88	46.0

Remark:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
- Margin value = Limit value - Emission Level.
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Only the antenna height (from 1m to 4m) at maximum reading are recorded.

**For 1GHz to 40 GHz**

U-NII-1_802.11a_5180MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5150.00	54.05	68.20	-14.15	1.50	240	53.61	0.44	Horizontal	Peak
5150.00	42.72	54.00	-11.28	1.50	240	42.28	0.44	Horizontal	Average
10360.00	51.57	68.20	-16.63	1.50	240	41.11	10.46	Horizontal	Peak
10360.00	42.38	54.00	-11.62	1.50	240	31.92	10.46	Horizontal	Average
5150.00	53.78	68.20	-14.42	1.50	80	53.34	0.44	Vertical	Peak
5150.00	42.78	54.00	-11.22	1.50	80	42.34	0.44	Vertical	Average
10360.00	51.36	68.20	-16.84	1.50	80	40.90	10.46	Vertical	Peak
10360.00	42.21	54.00	-11.79	1.50	80	31.75	10.46	Vertical	Average
U-NII-1_802.11a_5220MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
10440.00	51.46	68.20	-16.74	1.50	240	40.66	10.80	Horizontal	Peak
10440.00	42.18	54.00	-11.82	1.50	240	31.38	10.80	Horizontal	Average
10440.00	50.94	68.20	-17.26	1.50	80	40.14	10.80	Vertical	Peak
10440.00	42.20	54.00	-11.80	1.50	80	31.40	10.80	Vertical	Average
U-NII-1_802.11a_5240MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5350.00	47.99	68.20	-20.21	1.50	240	47.74	0.25	Horizontal	Peak
5350.00	37.71	54.00	-16.29	1.50	240	37.46	0.25	Horizontal	Average
10480.00	51.68	68.20	-16.52	1.50	240	40.68	11.00	Horizontal	Peak
10480.00	42.67	54.00	-11.33	1.50	240	31.67	11.00	Horizontal	Average
5350.00	47.31	68.20	-20.89	1.50	80	47.06	0.25	Vertical	Peak
5350.00	38.48	54.00	-15.52	1.50	80	38.23	0.25	Vertical	Average
10480.00	51.53	68.20	-16.67	1.50	80	40.53	11.00	Vertical	Peak
10480.00	42.79	54.00	-11.21	1.50	80	31.79	11.00	Vertical	Average
Remark: 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m) 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB) 3. Margin value = Emission Level – Limit value 4. The emission levels of other frequencies are very lower than the limit and not show in test report. 5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									

**U-NII-1_802.11n-HT40_5190MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5150.00	54.18	68.20	-14.02	1.50	240	53.74	0.44	Horizontal	Peak
5150.00	42.85	54.00	-11.15	1.50	240	42.41	0.44	Horizontal	Average
10380.00	51.01	68.20	-17.19	1.50	240	40.48	10.53	Horizontal	Peak
10380.00	42.83	54.00	-11.17	1.50	240	32.30	10.53	Horizontal	Average
5150.00	52.41	68.20	-15.79	1.50	80	51.97	0.44	Vertical	Peak
5150.00	42.00	54.00	-12.00	1.50	80	41.56	0.44	Vertical	Average
10380.00	51.16	68.20	-17.04	1.50	80	40.63	10.53	Vertical	Peak
10380.00	42.17	54.00	-11.83	1.50	80	31.64	10.53	Vertical	Average

U-NII-1_802.11n-HT40_5230MHz

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5350.00	47.65	68.20	-20.55	1.50	240	47.40	0.25	Horizontal	Peak
5350.00	37.84	54.00	-16.16	1.50	240	37.59	0.25	Horizontal	Average
10460.00	51.10	68.20	-17.10	1.50	240	40.19	10.91	Horizontal	Peak
10460.00	42.07	54.00	-11.93	1.50	240	31.16	10.91	Horizontal	Average
5350.00	47.56	68.20	-20.64	1.50	80	47.31	0.25	Vertical	Peak
5350.00	38.72	54.00	-15.28	1.50	80	38.47	0.25	Vertical	Average
10460.00	50.98	68.20	-17.22	1.50	80	40.07	10.91	Vertical	Peak
10460.00	42.95	54.00	-11.05	1.50	80	32.04	10.91	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

**U-NII-1_802.11ac-VHT80_5210MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5150.00	54.06	68.20	-14.14	1.50	240	53.62	0.44	Horizontal	Peak
5150.00	42.94	54.00	-11.06	1.50	240	42.50	0.44	Horizontal	Average
5350.00	47.85	68.20	-20.35	1.50	240	47.60	0.25	Horizontal	Peak
5350.00	38.20	54.00	-15.80	1.50	240	37.95	0.25	Horizontal	Average
10420.00	50.71	68.20	-17.49	1.50	240	40.00	10.71	Horizontal	Peak
10420.00	41.92	54.00	-12.08	1.50	240	31.21	10.71	Horizontal	Average
5150.00	52.88	68.20	-15.32	1.50	80	52.44	0.44	Vertical	Peak
5150.00	42.08	54.00	-11.92	1.50	80	41.64	0.44	Vertical	Average
5350.00	46.97	68.20	-21.23	1.50	80	46.72	0.25	Vertical	Peak
5350.00	39.16	54.00	-14.84	1.50	80	38.91	0.25	Vertical	Average
10420.00	51.74	68.20	-16.46	1.50	80	41.03	10.71	Vertical	Peak
10420.00	43.27	54.00	-10.73	1.50	80	32.56	10.71	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

U-NII-2A_802.11a_5260MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5150.00	54.34	68.20	-13.86	1.50	240	53.90	0.44	Horizontal	Peak
5150.00	42.93	54.00	-11.07	1.50	240	42.49	0.44	Horizontal	Average
10520.00	51.53	68.20	-16.67	1.50	240	40.35	11.18	Horizontal	Peak
10520.00	42.74	54.00	-11.26	1.50	240	31.56	11.18	Horizontal	Average
5150.00	53.98	68.20	-14.22	1.50	80	53.54	0.44	Vertical	Peak
5150.00	42.81	54.00	-11.19	1.50	80	42.37	0.44	Vertical	Average
10520.00	51.64	68.20	-16.56	1.50	80	40.46	11.18	Vertical	Peak
10520.00	42.43	54.00	-11.57	1.50	80	31.25	11.18	Vertical	Average
U-NII-2A_802.11a_5300MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
10600.00	51.26	68.20	-16.94	1.50	240	39.74	11.52	Horizontal	Peak
10600.00	41.90	54.00	-12.10	1.50	240	30.38	11.52	Horizontal	Average
10600.00	51.42	68.20	-16.78	1.50	80	39.90	11.52	Vertical	Peak
10600.00	42.49	54.00	-11.51	1.50	80	30.97	11.52	Vertical	Average
U-NII-2A_802.11a_5320MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5350.00	47.99	68.20	-20.21	1.50	240	47.74	0.25	Horizontal	Peak
5350.00	37.71	54.00	-16.29	1.50	240	37.46	0.25	Horizontal	Average
10640.00	51.68	68.20	-16.52	1.50	240	40.36	11.32	Horizontal	Peak
10640.00	42.34	54.00	-11.66	1.50	240	31.02	11.32	Horizontal	Average
5350.00	47.12	68.20	-21.08	1.50	80	46.87	0.25	Vertical	Peak
5350.00	38.48	54.00	-15.52	1.50	80	38.23	0.25	Vertical	Average
10640.00	51.24	68.20	-16.96	1.50	80	39.92	11.32	Vertical	Peak
10640.00	42.75	54.00	-11.25	1.50	80	31.43	11.32	Vertical	Average
Remark: 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m) 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB) 3. Margin value = Emission Level – Limit value 4. The emission levels of other frequencies are very lower than the limit and not show in test report. 5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									

U-NII-2A_802.11n-HT40_5270MHz

Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5150.00	54.20	68.20	-14.00	1.50	240	53.76	0.44	Horizontal	Peak
5150.00	42.73	54.00	-11.27	1.50	240	42.29	0.44	Horizontal	Average
10540.00	52.00	68.20	-16.20	1.50	240	40.74	11.26	Horizontal	Peak
10540.00	42.44	54.00	-11.56	1.50	240	31.18	11.26	Horizontal	Average
5150.00	53.19	68.20	-15.01	1.50	80	52.75	0.44	Vertical	Peak
5150.00	42.64	54.00	-11.36	1.50	80	42.20	0.44	Vertical	Average
10540.00	52.34	68.20	-15.86	1.50	80	41.08	11.26	Vertical	Peak
10540.00	42.25	54.00	-11.75	1.50	80	30.99	11.26	Vertical	Average

U-NII-2A_802.11n-HT40_5310MHz

Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5350.00	48.45	68.20	-19.75	1.50	240	48.20	0.25	Horizontal	Peak
5350.00	38.38	54.00	-15.62	1.50	240	38.13	0.25	Horizontal	Average
10620.00	51.90	68.20	-16.30	1.50	240	40.49	11.41	Horizontal	Peak
10620.00	41.96	54.00	-12.04	1.50	240	30.55	11.41	Horizontal	Average
5350.00	47.61	68.20	-20.59	1.50	80	47.36	0.25	Vertical	Peak
5350.00	38.23	54.00	-15.77	1.50	80	37.98	0.25	Vertical	Average
10620.00	51.28	68.20	-16.92	1.50	80	39.87	11.41	Vertical	Peak
10620.00	42.34	54.00	-11.66	1.50	80	30.93	11.41	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Tnly the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

**U-NII-2A_802.11ac-VHT80_5290MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5150.00	53.96	68.20	-14.24	1.50	240	53.52	0.44	Horizontal	Peak
5150.00	42.79	54.00	-11.21	1.50	240	42.35	0.44	Horizontal	Average
5350.00	47.48	68.20	-20.72	1.50	240	47.23	0.25	Horizontal	Peak
5350.00	37.94	54.00	-16.06	1.50	240	37.69	0.25	Horizontal	Average
10580.00	50.27	68.20	-17.93	1.50	240	38.83	11.44	Horizontal	Peak
10580.00	42.34	54.00	-11.66	1.50	240	30.90	11.44	Horizontal	Average
5150.00	52.57	68.20	-15.63	1.50	80	52.13	0.44	Vertical	Peak
5150.00	41.95	54.00	-12.05	1.50	80	41.51	0.44	Vertical	Average
5350.00	47.19	68.20	-21.01	1.50	80	46.94	0.25	Vertical	Peak
5350.00	39.45	54.00	-14.55	1.50	80	39.20	0.25	Vertical	Average
10580.00	51.79	68.20	-16.41	1.50	80	40.35	11.44	Vertical	Peak
10580.00	43.04	54.00	-10.96	1.50	80	31.60	11.44	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

U-NII-2C_802.11a_5500MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5470.00	56.51	68.20	-11.69	1.50	240	56.55	-0.04	Horizontal	Peak
5470.00	46.62	54.00	-7.38	1.50	240	46.66	-0.04	Horizontal	Average
11000.00	53.73	68.20	-14.47	1.50	240	42.31	11.42	Horizontal	Peak
11000.00	43.63	54.00	-10.37	1.50	240	32.21	11.42	Horizontal	Average
5470.00	56.57	68.20	-11.63	1.50	80	56.61	-0.04	Vertical	Peak
5470.00	47.01	54.00	-6.99	1.50	80	47.05	-0.04	Vertical	Average
11000.00	53.38	68.20	-14.82	1.50	80	41.96	11.42	Vertical	Peak
11000.00	44.13	54.00	-9.87	1.50	80	32.71	11.42	Vertical	Average
U-NII-2C_802.11a_5580MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
11160.00	51.61	68.20	-16.59	1.50	240	40.26	11.35	Horizontal	Peak
11160.00	42.17	54.00	-11.83	1.50	240	30.82	11.35	Horizontal	Average
11160.00	51.46	68.20	-16.74	1.50	80	40.11	11.35	Vertical	Peak
11160.00	42.66	54.00	-11.34	1.50	80	31.31	11.35	Vertical	Average
U-NII-2C_802.11a_5700MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5725.00	61.04	68.20	-7.16	1.50	240	59.74	1.30	Horizontal	Peak
5725.00	49.95	54.00	-4.05	1.50	240	48.65	1.30	Horizontal	Average
11400.00	51.75	68.20	-16.45	1.50	240	40.28	11.47	Horizontal	Peak
11400.00	42.71	54.00	-11.29	1.50	240	31.24	11.47	Horizontal	Average
5725.00	59.18	68.20	-9.02	1.50	80	57.88	1.30	Vertical	Peak
5725.00	49.82	54.00	-4.18	1.50	80	48.52	1.30	Vertical	Average
11400.00	51.56	68.20	-16.64	1.50	80	40.09	11.47	Vertical	Peak
11400.00	42.74	54.00	-11.26	1.50	80	31.27	11.47	Vertical	Average
Remark: - Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m) - Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB) - Margin value = Emission Level – Limit value - The emission levels of other frequencies are very lower than the limit and not show in test report. - Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									

U-NII-2C_802.11n-HT40_5510MHz

Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5470.00	56.07	68.20	-12.13	1.50	240	56.11	-0.04	Horizontal	Peak
5470.00	45.64	54.00	-8.36	1.50	240	45.68	-0.04	Horizontal	Average
11020.00	53.69	68.20	-14.51	1.50	240	42.23	11.46	Horizontal	Peak
11020.00	43.87	54.00	-10.13	1.50	240	32.41	11.46	Horizontal	Average
5470.00	56.68	68.20	-11.52	1.50	80	56.72	-0.04	Vertical	Peak
5470.00	46.11	54.00	-7.89	1.50	80	46.15	-0.04	Vertical	Average
11020.00	53.86	68.20	-14.34	1.50	80	42.40	11.46	Vertical	Peak
11020.00	44.56	54.00	-9.44	1.50	80	33.10	11.46	Vertical	Average

U-NII-2C_802.11n-HT40_5550MHz

Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
11100.00	50.88	68.20	-17.32	1.50	240	39.15	11.73	Horizontal	Peak
11100.00	41.68	54.00	-12.32	1.50	240	29.95	11.73	Horizontal	Average
11100.00	52.07	68.20	-16.13	1.50	80	40.34	11.73	Vertical	Peak
11100.00	43.24	54.00	-10.76	1.50	80	31.51	11.73	Vertical	Average

U-NII-2C_802.11n-HT40_5670MHz

Frequency (MHz)	Emssion Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5725.00	61.01	68.20	-7.19	1.50	240	59.71	1.30	Horizontal	Peak
5725.00	49.76	54.00	-4.24	1.50	240	48.46	1.30	Horizontal	Average
11340.00	51.42	68.20	-16.78	1.50	240	40.00	11.42	Horizontal	Peak
11340.00	42.41	54.00	-11.59	1.50	240	30.99	11.42	Horizontal	Average
5725.00	58.73	68.20	-9.47	1.50	80	57.43	1.30	Vertical	Peak
5725.00	49.44	54.00	-4.56	1.50	80	48.14	1.30	Vertical	Average
11340.00	51.14	68.20	-17.06	1.50	80	39.72	11.42	Vertical	Peak
11340.00	42.57	54.00	-11.43	1.50	80	31.15	11.42	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Tnly the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

**U-NII-2C_802.11ac-VHT80_5530MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5470.00	56.46	68.20	-11.74	1.50	240	56.50	-0.04	Horizontal	Peak
5470.00	46.29	54.00	-7.71	1.50	240	46.33	-0.04	Horizontal	Average
11060.00	53.43	68.20	-14.77	1.50	240	41.90	11.53	Horizontal	Peak
11060.00	43.44	54.00	-10.56	1.50	240	31.91	11.53	Horizontal	Average
5470.00	56.77	68.20	-11.43	1.50	80	56.81	-0.04	Vertical	Peak
5470.00	46.14	54.00	-7.86	1.50	80	46.18	-0.04	Vertical	Average
11060.00	53.10	68.20	-15.10	1.50	80	41.57	11.53	Vertical	Peak
11060.00	44.23	54.00	-9.77	1.50	80	32.70	11.53	Vertical	Average

Remark:

1. *Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)*
2. *Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)*
3. *Margin value = Emission Level – Limit value*
4. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
5. *Tnly the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.*

**U-NII-3_802.11a_5745MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5650.00	50.52	68.20	-17.68	1.50	240	49.72	0.80	Horizontal	Peak
5700.00	51.32	105.20	-53.88	1.50	240	50.08	1.24	Horizontal	Peak
5720.00	57.34	110.80	-53.46	1.50	240	56.06	1.28	Horizontal	Peak
5725.00	59.97	122.20	-62.23	1.50	240	58.67	1.30	Horizontal	Peak
11490.00	53.67	68.20	-14.53	1.50	240	42.12	11.55	Horizontal	Peak
11490.00	43.14	54.00	-10.86	1.50	240	31.59	11.55	Horizontal	Average
5650.00	51.57	68.20	-16.63	1.50	80	50.77	0.80	Vertical	Peak
5700.00	50.97	105.20	-54.23	1.50	80	49.73	1.24	Vertical	Peak
5720.00	54.76	110.80	-56.04	1.50	80	53.48	1.28	Vertical	Peak
5725.00	59.15	122.20	-63.05	1.50	80	57.85	1.30	Vertical	Peak
11490.00	52.94	68.20	-15.26	1.50	80	41.39	11.55	Vertical	Peak
11490.00	43.76	54.00	-10.24	1.50	80	32.21	11.55	Vertical	Average

U-NII-3_802.11a_5825MHz

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5850.00	51.85	122.20	-70.35	1.50	240	50.03	1.82	Horizontal	Peak
5855.00	52.26	110.80	-58.54	1.50	240	50.41	1.85	Horizontal	Peak
5875.00	51.21	105.20	-53.99	1.50	240	49.23	1.98	Horizontal	Peak
5925.00	51.51	68.20	-16.69	1.50	240	49.39	2.12	Horizontal	Peak
11650.00	53.31	68.20	-14.89	1.50	240	41.67	11.64	Horizontal	Peak
11650.00	43.28	54.00	-10.72	1.50	240	31.64	11.64	Horizontal	Average
5850.00	51.72	122.20	-70.48	1.50	80	49.90	1.82	Vertical	Peak
5855.00	50.41	110.80	-60.39	1.50	80	48.56	1.85	Vertical	Peak
5875.00	52.33	105.20	-52.87	1.50	80	50.35	1.98	Vertical	Peak
5925.00	52.00	68.20	-16.20	1.50	80	49.88	2.12	Vertical	Peak
11650.00	52.42	68.20	-15.78	1.50	80	40.78	11.64	Vertical	Peak
11650.00	43.52	54.00	-10.48	1.50	80	31.88	11.64	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Tnly the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

**U-NII-3_802.11n-HT40_5755MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5650.00	50.36	68.20	-17.84	1.50	240	49.56	0.80	Horizontal	Peak
5700.00	51.21	105.20	-53.99	1.50	240	49.97	1.24	Horizontal	Peak
5720.00	57.30	110.80	-53.50	1.50	240	56.02	1.28	Horizontal	Peak
5725.00	60.60	122.20	-61.60	1.50	240	59.30	1.30	Horizontal	Peak
11510.00	53.99	68.20	-14.21	1.50	240	42.43	11.56	Horizontal	Peak
11510.00	43.44	54.00	-10.56	1.50	240	31.88	11.56	Horizontal	Average
5650.00	51.73	68.20	-16.47	1.50	80	50.93	0.80	Vertical	Peak
5700.00	50.79	105.20	-54.41	1.50	80	49.55	1.24	Vertical	Peak
5720.00	55.05	110.80	-55.75	1.50	80	53.77	1.28	Vertical	Peak
5725.00	59.75	122.20	-62.45	1.50	80	58.45	1.30	Vertical	Peak
11510.00	53.38	68.20	-14.82	1.50	80	41.82	11.56	Vertical	Peak
11510.00	44.00	54.00	-10.00	1.50	80	32.44	11.56	Vertical	Average

U-NII-3_802.11n-HT40_5795MHz

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5850.00	51.89	122.20	-70.31	1.50	240	50.07	1.82	Horizontal	Peak
5855.00	51.98	110.80	-58.82	1.50	240	50.13	1.85	Horizontal	Peak
5875.00	50.74	105.20	-54.46	1.50	240	48.76	1.98	Horizontal	Peak
5925.00	51.42	68.20	-16.78	1.50	240	49.30	2.12	Horizontal	Peak
11590.00	53.70	68.20	-14.50	1.50	240	42.19	11.51	Horizontal	Peak
11590.00	42.14	54.00	-11.86	1.50	240	30.63	11.51	Horizontal	Average
5850.00	51.90	122.20	-70.30	1.50	80	50.08	1.82	Vertical	Peak
5855.00	50.96	110.80	-59.84	1.50	80	49.11	1.85	Vertical	Peak
5875.00	52.87	105.20	-52.33	1.50	80	50.89	1.98	Vertical	Peak
5925.00	52.52	68.20	-15.68	1.50	80	50.40	2.12	Vertical	Peak
11590.00	51.69	68.20	-16.51	1.50	80	40.18	11.51	Vertical	Peak
11590.00	43.42	54.00	-10.58	1.50	80	31.91	11.51	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Tnly the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

**U-NII-3_802.11a_5785MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
11570.00	53.68	68.20	-14.52	1.50	240	42.16	11.52	Horizontal	Peak
11570.00	42.52	54.00	-11.48	1.50	240	31.00	11.52	Horizontal	Average
11570.00	52.37	68.20	-15.83	1.50	80	40.85	11.52	Vertical	Peak
11570.00	41.25	54.00	-12.75	1.50	80	29.73	11.52	Vertical	Average

U-NII-3_802.11ac-VHT80_5775MHz

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
5650.00	50.42	68.20	-17.78	1.50	240	49.62	0.80	Horizontal	Peak
5700.00	51.66	105.20	-53.54	1.50	240	50.42	1.24	Horizontal	Peak
5720.00	57.55	110.80	-53.25	1.50	240	56.27	1.28	Horizontal	Peak
5725.00	61.03	122.20	-61.17	1.50	240	59.73	1.30	Horizontal	Peak
5850.00	52.31	122.20	-69.89	1.50	240	50.49	1.82	Horizontal	Peak
5855.00	52.15	110.80	-58.65	1.50	240	50.30	1.85	Horizontal	Peak
5875.00	50.94	105.20	-54.26	1.50	240	48.96	1.98	Horizontal	Peak
5925.00	51.46	68.20	-16.74	1.50	240	49.34	2.12	Horizontal	Peak
11550.00	53.15	68.20	-15.05	1.50	240	41.61	11.54	Horizontal	Peak
11550.00	42.23	54.00	-11.77	1.50	240	30.69	11.54	Horizontal	Average
5650.00	52.27	68.20	-15.93	1.50	80	51.47	0.80	Vertical	Peak
5700.00	50.72	105.20	-54.48	1.50	80	49.48	1.24	Vertical	Peak
5720.00	55.18	110.80	-55.62	1.50	80	53.90	1.28	Vertical	Peak
5725.00	59.37	122.20	-62.83	1.50	80	58.07	1.30	Vertical	Peak
5850.00	52.16	122.20	-70.04	1.50	80	50.34	1.82	Vertical	Peak
5855.00	50.67	110.80	-60.13	1.50	80	48.82	1.85	Vertical	Peak
5875.00	52.79	105.20	-52.41	1.50	80	50.81	1.98	Vertical	Peak
5925.00	52.94	68.20	-15.26	1.50	80	50.82	2.12	Vertical	Peak
11550.00	51.93	68.20	-16.27	1.50	80	40.39	11.54	Vertical	Peak
11550.00	43.73	54.00	-10.27	1.50	80	32.19	11.54	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Tnly the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

2.7. AC Power Line Conducted Emission

2.7.1. Limit of AC Power Line Conducted Emission

FCC Part 15.207:


For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

2.7.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.7.3. Test Setup



2.7.4. Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

2.7.5. Test Result of AC Power Line Conducted Emission

Not applicable, the product is only powered by car charger DC.