

TABLE OF CONTENTS LIST

APPLICANT: COBRA ELECTRONICS CORPORATION

FCC ID: BBOXRS9930

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST
PAGE 2-3.....TEST PROCEDURES
PAGE 4.....RADIATION INTERFERENCE TEST DATA
PAGE 5.....VERTICAL MEASUREMENT PLOT
PAGE 6.....HORIZONTAL MEASUREMENT PLOT
PAGE 7.....TEST SET UP PHOTO

EXHIBITS CONTAINING:

FCC ID LABEL SAMPLE
SKETCH OF LABEL LOCATION
BLOCK DIAGRAM
SCHEMATIC
USERS MANUAL
EXTERNAL PHOTOS
INTERNAL PHOTOS
CIRCUIT DESCRIPTION
TEST SET UP PHOTO

APPLICANT: COBRA ELECTRONICS CORPORATION
FCC ID : BBOXRS9930
REPORT #: C\COBRA\2438UT5\2438UT5TestReport.doc
TABLE OF CONTENTS LIST

Equipment List

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/27/04	3/26/07
3-Meter OATS	TEI	N/A	N/A	Listed 1/13/03	1/12/06
Biconnical Antenna	Eaton	94455-1	1096	CAL 8/17/04	8/17/06
Biconnical Antenna	Electro-Metrics	BIA-25	1171	CAL 4/29/05	4/29/07
Blue Tower Quasi-Peak Adapter	HP	85650A	2811A01279	CAL 4/13/05	4/13/07
Blue Tower RF	HP	85685A	2926A00983	CAL 8/3/05	8/3/07
Preselector Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/13/05	4/13/07
LISN	Electro-Metrics	ANS-25/2	2604	CAL 8/27/04	8/27/06
LISN	Electro-Metrics	EM-7820	2682	CAL 4/28/05	4/28/07
Log-Periodic Antenna	Electrometrics	LPA-30	409	CAL 5/2/05	5/2/07

TEST PROCEDURES

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: Testing was done in accordance with ANSI C63.4-2003. Section 15.35(b) specifies the use of an average detector in this band. In addition, the peak level of an emission shall not exceed the average limit by more than 20 dB using a minimum Resolution Bandwidth (RBW) of 1 MHz and minimum Video Bandwidth (VBW) OF 1 MHz. The following procedure is designed to determine if there are any spurious emissions from the local oscillator within the band of interest along with any additional spurious emissions caused by other circuitry within the device.

- 1) Determine the frequency of the peak emission:
Start Frequency 11.7 GHz
Stop Frequency 12.2 GHz
RBW equal to or greater than 1 MHz
VBW equal to or greater than 1 MHz
Detector Function Peak
Maximize the emissions with regards to device orientation, antenna polarization, and antenna height. Sweep the band using Max Hold for a minimum of 2 minutes. Record this frequency for measuring the peak emission. In addition record the frequency of other spurious emissions noted.
- 2) Determine the peak level of the emission:
Center Frequency Set to the frequency determined in Step 1 RBW Equal to or greater than 1 MHz VBW Equal to or greater than 1 MHz
Detector Function Peak Measure the value of the peak emission using Max Hold for a minimum of 2 minutes. This can be done at zero span or a frequency span where the analyzer does not show a "Measurement Uncalibrated" message. Record the peak value. If the peak measurement is compliant with the average limit an average measurement is not necessary. If the peak value exceeds the average limit by less than 20 dB proceed to Step 3.
- 3) Determine the average level of the emission:
Center Frequency Set to the frequency determined in Step 1
Span Zero
RBW Equal to or greater than 1 MHz
VBW Equal to or greater than 10 Hz
Detector Function Peak
This measurement uses video averaging and must be done in Linear mode. The analyzer Reference Level is adjusted so that a signal is clearly visible on the screen. Measure the value of the emission using Max Hold for a minimum of 2 minutes. Record this as the average value. Step 2 and Step 3 should be repeated for other spurious emissions.

The ambient temperature of the UUT was 80°F with a humidity of 70%.

TEST PROCEDURES CONTINUED

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS

33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

APPLICANT: COBRA ELECTRONICS CORPORATION

FCC ID: BBOXRS9930

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.109

REQUIREMENTS: 30 to 88 MHz: 40.0 dBuV/M @ 3 METERS
88 to 216 MHz: 43.5 dBuV/M
216 to 960 MHz: 46.0 dBuV/M
ABOVE 960 MHz: 54.0 dBuV/M
11.7 to 12.2GHz: 54.0dBuV/m

TEST RESULTS: A search was made of the spectrum from 30 to 1000MHz and from 11.7 to 12.2GHz the measurements indicate that the unit DOES meet the FCC requirements. Measurements in the 11.7 to 12.2GHz band were made with a Standard Gain Horn. The measurements in the 11.7 to 12.2GHz band represent the ambient noise levels. The attached plots were made with peak detector with the analyzer in a maximum hold for 2 minutes.

TEST DATA:

NO MEASURABLE EMISSIONS FOUND

* The EUT is operating on the following bands; 10.525GHz(X-Band), 24.150GHz(K-Band), 33.4-36.0GHz(KA Band)

PERFORMED BY: JOE SCOGLIO

DATE: DECEMBER 8, 2005


APPLICANT: COBRA ELECTRONICS CORPORATION

FCC ID : BBOXRS9930

REPORT #: C\COBRA\2438UT5\2438UT5TestReport.doc


Page 4 of 7

NOTES:
2438ut5 vertical



RBW	VBW	ST (sec)	Peak	11918.0	-93.50	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
1 MHz	1 MHz	20m	MKR2	0.000	0.00	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Center Frequency (Hz) 11.950G			MKR3	0.000	0.00	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Marker Delta (Hz) 0.00			HWMK	23.076	6.27	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

NOTES:
2438ut5 horizontal



RBW	VBW	ST (sec)	Peak	12105.1	-92.70	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
1 MHz	1 MHz	20m	MKR2	0.000	0.00	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Center Frequency (Hz) 11.950G			MKR3	0.000	0.00	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Marker Delta (Hz) 0.00			HWMK	23.076	6.27	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

TEST SET UP PHOTO

