



RADIO TEST REPORT

Test Report No. : 30IE0112-SH-01-A

Applicant : RICOH COMPANY LTD.
Type of Equipment : Color Copier
Model No. : Aficio MP C5501
FCC ID : BBP-RFAPL03
Test regulation : FCC Part15 Subpart C: 2010
Test result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test: June 21, 29 and 30, 2010

Tested by: H. Shirasawa

Hikaru Shirasawa
Engineer of EMC Services

T. Arai

Tatsuya Arai
Engineer of EMC Services

M. Hosaka

Makoto Hosaka
Engineer of EMC Services

Approved by: G. Ishiwata

Go Ishiwata
Assistant Manager of EMC Service

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
 There is no testing item of "Non-accreditation".



UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

MF060d (06.08.09)

Table of Contents	Page
1 Applicant information	3
2 Equipment under test (E.U.T.)	3
3 Test specification, procedures and results	4
4 System test configuration	6
5 Conducted emission	8
6 Radiated emissions (Fundamental, Spurious and Outside the Allocated bands)	9
7 20dB bandwidth & Occupied bandwidth (99%)	11
8 Frequency tolerance	11
<u>Contents of Appendixes</u>	12

1 Applicant information

Company Name : RICOH COMPANY LTD.
Address : 810 Shimoimaizumi, Ebina-shi, Kanagawa-ken 243-0460, Japan
Telephone Number : +81-46-292-9152
Facsimile Number : +81-46-292-9183
Contact Person : Akihiro Kurosaka

2 Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Color Copier
Model No. : Aficio MP C5501
Serial No. : V9610100004
Rating : AC120 - 127V, 12A
Country of Mass-production : China
Receipt Date of Sample : June 21, 2010
Condition of EUT : Engineering prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No Modification by the test lab

2.2 Product description

Model No: Aficio MP C5501, referred to as the EUT in this report, is the Color Copier.
Refer to the Appendix for the difference between the EUT and its similar models.

Radio Specification

Radio Type : Transceiver
Frequency of Operation : 13.56MHz
Clock frequency : 13.56MHz
Modulation : ASK 100%
Power Supply (inner) : DC 5.0V
Antenna type : Print pattern antenna
ITU code : A1D
Operating Temperature : +10 deg C - +32 deg C

FCC 15.31 (e)

Host device (Color Copier) provides the radio block with stable power supply, and the power is not changed when voltage of the Color Copier is varied. Therefore, the equipment complies power supply regulation.

FCC Part 15.203

The antenna is not removable from the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

3 Test specification, procedures and results

3.1 Test specification

Test specification : FCC Part15 Subpart C: 2010, final revised on January 22, 2010
 And effective March 1, 2010
 Title : FCC 47CFR Part15 Radio Frequency Device, Subpart C Intentional Radiators
 Section 15.207 Conducted limits
 Section 15.209 Radiated emission limits, general requirements
 Section 15.215 Additional provisions to the general radiated emission limitations.
 Section 15.225 Operation within the bands 13.110-14.010MHz.

* The EUT complies with FCC Part 15 Subpart B: 2010, final revised on January 22, 2010 and effective March 1, 2010.

3.2 Procedures & results

Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin	Results
Conducted emission	ANSI C63.4:2003 7. AC powerline conducted emission measurements	FCC Section15.207	-	N/A	5.8dB (0.70442MHz, QP, L1)	Complied
Electric Field Strength of Fundamental Emission	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.225 (a)	Radiated	N/A	81.3dB (Vertical, 0deg.)	Complied
Electric Field Strength of Outside the Allocated bands	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.225 (b)(c)	Radiated	N/A	42.0dB (14.01MHz, Vertical, 0deg.)	Complied
Electric Field Strength of Spurious Emission	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.209 FCC Section15.225 (d)	Radiated	N/A	11.4dB (449.860MHz, Horizontal)	Complied
20dB Bandwidth	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.215 (c)	Radiated	N/A	-	Complied
Frequency Tolerance	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.225 (e)	Radiated	N/A	-	Complied

Note: UL Japan's EMI Work Procedures No.QPM05 and QPM15.

3.3 Addition to standard

Item	Test Procedure	Specification	Remarks	Worst Margin	Results
Occupied Bandwidth (99%)	ANSI C63.4:2003 13. Measurement of intentional radiators RSS-Gen 4.6.1	RSS-Gen 4.6.1	Radiated	-	Complied

* Other than above, no addition, exclusion nor deviation has been made from the standard.

UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

	No.1 Semi anechoic chamber (±)	No.2 Semi anechoic chamber (±)	No.3 Semi anechoic chamber (±)
Conducted emission (AC mains)			
150kHz-30MHz	3.0 dB	2.6 dB	3.1 dB
Radiated emission (3m)			
9kHz-30MHz	3.4 dB	2.7 dB	3.4 dB
30MHz-300MHz	4.6 dB	4.5 dB	4.9 dB
300MHz-1000MHz	4.5 dB	4.6 dB	5.1 dB

*3m = Measurement distance

Frequency tolerance

Frequency (Normal condition) Measurement uncertainty (with a 95% confidence level) for this test was: (±) 1.3×10^{-6} .

Frequency (Extreme condition) Measurement uncertainty (with a 95% confidence level) for this test was: (±) 1.3×10^{-6} .

Conducted emission test

The data listed in this test report has enough margin, more than site margin.

Radiated Emission Test

The data listed in this test report has enough margin, more than site margin.

3.5 Test location

UL Japan, Inc. Shonan EMC Lab.

1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number : +81 463 50 6400

Facsimile number : +81 463 50 6401

JAB Accreditation No. : RTL02610

No.1/ No.2/ No.3 anechoic chamber has been fully described in a report submitted to FCC office, and accepted on April 17, 2009 (Registration No.: 697847).

IC Registration No. : 2973D-1 (No1 Semi anechoic chamber)
 2973D-2 (No2 Semi anechoic chamber)
 2973D-3 (No3 Semi anechoic chamber)

Test room	Width x Depth x Height (m)	Test room	Width x Depth x Height (m)
No.1 Semi-anechoic chamber	20.6 x 11.3 x 7.65 Maximum measurement distance: 10m	No.1 Shielded room	6.8 x 4.1 x 2.7
No.2 Semi-anechoic chamber	20.6 x 11.3 x 7.65 Maximum measurement distance: 10m	No.2 Shielded room	6.8 x 4.1 x 2.7
No.3 Semi-anechoic chamber	12.7 x 7.7 x 5.35 Maximum measurement distance: 5m	No.3 Shielded room	6.3 x 4.7 x 2.7
No.4 Semi-anechoic chamber	8.1 x 5.1 x 3.55	No.4 Shielded room	4.4 x 4.7 x 2.7
		No.5 Shielded room	7.8 x 6.4 x 2.7
		No.6 Shielded room	7.8 x 6.4 x 2.7

3.6 Test Configuration Photographs, Data of EMI test and Test instruments

Refer to APPENDIX 1 to 3, in this report

UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

4 System test configuration

4.1 Operating mode

The system was configured in typical fashion (as a customer would normally use it) for testing.


Test item	Operating mode	Tested frequency
All items except for Frequency tolerances	Transmitting (ASK), 26byte Mirror modulation from lower bit -> AM modulation 0x00, 0x00, 0xB3, 0x75, 0xB0, 0x00, 0x00, 0x80, 0x01, 0xff, 0xfe, 0x01, 0x23, 0x45, 0x67, 0x0B, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, CRC, CRC	13.56MHz
Frequency tolerances	Transmitting Unmodulated	13.56MHz

Software for testing: D0895119 (Rev: 0.09:04)

Above setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting.

Four RFID modules which have the same specification are mounted in the equipment and they don't have simultaneous transmitting function. They were previously checked and the one in which the maximum emission occurred was chosen. ID tag was mounted in the Toner bottle inside of the EUT to communicate with each module.

4.2 Configuration and peripherals



* Test data was taken under worse case conditions.

Description of EUT and support equipment

No.	Item	Model number	Serial number	Manufacturer	Remark
	Color Copier				EUT. This consists of A~H.
A	Color Copier	Aficio MP C5501	V9610100004	RICOH	
B	Document feeder	DF3010	3L39-208679	RICOH	
C	Booklet Finisher	Finisher SR3020	3L41-131436	RICOH	
D	Paper Bank	Paper Feed Unit PB3100	3M58-208447	RICOH	
E	Bridge Unit	Bridge Unit BU3030	3M36-132275	RICOH	
F	RF-ID part	RFID:RW D0895177	9C9065	RICOH	
G	Media Slot	Type 12	3M95-110849	RICOH	
H	Telephone Handset	Hand Set Type 1018	C036/1184 6443A	RICOH	
I	Telephone Exchanger	HP-208	8400066d	TAKACOM	Support equipment.
J	Digital Camera	Caplio R1	00117102	RICOH	Support equipment.
K	Personal Computer	OPTIPLEX 755	CGWWDBX	DELL	Support equipment.
L	LCD Monitor	E153FPb	CN-0C5378-46633-589-44G U	DELL	Support equipment.
M	Keyboard	L100	CN0RH6576589082Q01LV	DELL	Support equipment.
N	Mouse	MOC5U0	G1E025EP	DELL	Support equipment.
O	AC Adaptor	AC-HP2800	P1TT00000560	Nishinohon Denshi	Support equipment.
P	Modem	ME3314B	6K07040	OMRON	Support equipment.
Q	Printer	BJ F600	-	Canon	Support equipment.

*1) RFID modules are inside in the Color Copier.

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	AC power cable	2.5	Unshielded	Unshielded	-
2	Modular cable (1)	2	Unshielded	Unshielded	With a ferrite core (2 turns, K3 NF-75(N)BK0, FERRICO) at facsimile side.
3	Modular cable (2)	2	Unshielded	Unshielded	With a ferrite core (2 turns, K3 NF-75(N)BK0, FERRICO) at facsimile side.
4	Modular cable (2)	2	Unshielded	Unshielded	With a ferrite core (2 turns, K3 NF-75(N)BK0, FERRICO) at facsimile side.
5	USB cable (1)	3	Shield	Shield	-
6	USB cable (2)	3	Shield	Shield	-
7	LAN cable	3	Unshielded	Unshielded	With a ferrite core (2 turns, RFC-13, KG) at EUT side.
8	Keyboard cable	2	Unshielded	Unshielded	-
9	Mouse cable	1.8	Unshielded	Unshielded	-
10	Modular cable (3)	0.5	Unshielded	Unshielded	With a ferrite core (2 turns, RFC-8, KG) at EUT side.
11	RGB cable	1.5	Shielded	Shielded	-
12	AC power cable	1.5	Unshielded	Unshielded	-
13	AC power cable	1.5	Unshielded	Unshielded	-
14	AC power cable	1.5	Unshielded	Unshielded	-
15	COM Cable	1.8	Shielded	Shielded	-
16	Printer Cable	3	Shielded	Shielded	-
17	AC Power Cable	1	Unshielded	Unshielded	-
18	AC power cable	1	Unshielded	Unshielded	-

UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

5 Conducted emission

5.1 Operating environment

The test was carried out in No.3 Shielded room.

Temperature : See test data
Humidity : See test data

5.2 Test configuration

EUT was placed on a carpet for insulation above the ground plane. EUT was set up typical spacing for the other equipment. EUT was located 80cm from LISN and excess AC cable was bundled in center. I/O cables that were connected to the peripherals were bundled in center. I/O cables that were connected to the peripherals were bundled in center. They were folded back and for the forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane.

Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN to the input power source. All unused 50Ω connectors of the LISN were resistively terminated in 50Ω when not connected to the measuring equipment.

Photographs of the set up are shown in Appendix 1.

5.3 Test conditions

Frequency range : 0.15 - 30MHz
EUT position : Floor standing

5.4 Test procedure

The AC Mains Terminal Continuous disturbance Voltage had been measured with the EUT within a screened room. The EUT was connected to a Line Impedance Stabilization Network (LISN).

An overview sweep with peak detection has been performed.

The measurements had been performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver.

Detector Type : Quasi-Peak/ Average
IF Bandwidth : 9kHz

5.5 Results

Summary of the test results : Pass

UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

6 Radiated emissions (Fundamental, Spurious and Outside the Allocated bands)

6.1 Operating environment

The test was carried out in No.3 Semi anechoic chamber.

Temperature : Refer to the APPENDIX
 Humidity : Refer to the APPENDIX

6.2 Test configuration

EUT was placed on a carpet for insulation above the conducting ground plane to prevent the reflection influence. The configuration was set in accordance with ANSI C63.4: 2003. Photographs of the set up are shown in APPENDIX 1.

6.3 Test conditions

Frequency range : 9kHz - 1GHz
 Test distance : 3m
 EUT position : Floor standing

6.4 Test procedure

The Radiated Electric Field Strength intensity has been measured with a ground plane and at a distance of 3m.

Frequency: From 9kHz to 30MHz at distance 3m

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for vertical polarization (antenna angle: 0deg.to 360deg.) and horizontal polarization. Drawing of the antenna direction is shown in Figure 1.

Frequency: From 30MHz to 1GHz at distance 3m

The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

Measurements were performed with QP, PK, and AV detector.

The radiated emission measurements were made with the following detector function of the test receiver.

	9kHz to 90kHz & 110kHz to 150kHz	90kHz to 110kHz	150kHz to 490kHz	490kHz to 30MHz	30MHz to 1GHz
Detector Type	PK/AV	QP	PK/AV	QP	QP
IF Bandwidth	200Hz	200Hz	10kHz	9kHz	120kHz
Measuring antenna	Loop antenna				Biconical (30-299.99MHz) Logperiodic (300MHz-1GHz)

* FCC Part 15 Section 15.31 (f)(2) (9kHz-30MHz)

9kHz – 490kHz [Limit at 3m]= [Limit at 300m]-40log (3[m]/300[m])

490kHz – 30MHz [Limit at 3m]= [Limit at 30m]-40log (3[m]/30[m])

The carrier level and noise levels were confirmed at each case of module Ch0: Black, module Ch1: Magenta, module Ch2: Cyan and module Ch3: Yellow of EUT to see the module of maximum noise, and the test was made at the module that has the maximum noise.

UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401


Combinations of the worst case

Model	Worst case	
	Below 30MHz	Above 30MHz
Module	Module Ch3: Yellow	Module Ch3: Yellow


6.5 Results

Summary of the test results : Pass *No noise was detected above the 5th order harmonics.


Figure 1: Direction of the Loop Antenna



Top View (Horizontal)



Antenna was not rotated.



7 20dB bandwidth & Occupied bandwidth (99%)

Test procedure

The measurement was performed in the antenna height to gain the maximum of Electric field strength.

Summary of the test results: Pass

8 Frequency tolerances

Test procedure

The measurement was performed in the antenna height to gain the maximum of Electric field strength.
The temperature test was started after the temperature stabilization time of 30 minutes.

Summary of the test results: Pass

UL Japan, Inc.

SHONAN EMC LAB.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401

APPENDIX 1: Photographs of test setup

Page 13 : Conducted emission
Page 14 - 15 : Radiated emission

APPENDIX 2: Test data

Page 16 : Conducted emission
Page 17 - 19 : Radiated emission
17 : Fundamental and Outside the Allocated bands
18 - 19 : Spurious emission
Page 20 : Bandwidth
Page 21 - 23 : Frequency tolerance

APPENDIX 3: Test instruments

Page 24 : Test instruments

APPENDIX 4: Similar model description

Page 25 : Similar model description