

## RF Exposure / SAR Statement

**No. : 27IE0337-YK-A**

**Applicant** : RICOH COMPANY, LTD  
**Type of Equipment** : Option(s) for Radiocommunications  
**Model No.** : R-WL54MN  
**FCC ID** : BBP-WLRWL541

---

RICOH COMPANY, LTD declares that Model : Option(s) for Radiocommunications complies with FCC radiation exposure requirement specified in the FCC Rules 2.1093. The "R-WL54MN" has 115.35 mW of conducted Peak Output power and 230.14 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "R-WL54MN" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

**P = 115.35 mW (Maximum peak output power)**  
**G = 2.00 Numerical Antenna gain; equal 3.00 dBi**  
**r = 20.0 cm**

**For: R-WL54MN**

$$S = 0.04579 \text{ mW/cm}^2$$

---

***UL Japan, Inc.***

***YAMAKITA EMC LAB.***

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112