



**FCC CFR47 PART 15 SUBPART C  
INDUSTRY CANADA RSS-210 ISSUE 8**

**CERTIFICATION TEST REPORT**

**FOR**

**HANDHELD TERMINAL**

**MODEL NUMBER: IT- 800A-35U**

**FCC ID: BBQIT800A  
IC: 2388F-IT800A**

**REPORT NUMBER: 11J13697-3**

**ISSUE DATE: JUNE 22, 2011**

*Prepared for*  
**CASIO COMPUTER CO., LTD  
6-2 HON-MACHI 1-CHOME  
SHIBUYA-KU  
TOKYO, 151-8543, JAPAN**

*Prepared by*  
**COMPLIANCE CERTIFICATION SERVICES (UL CCS)  
47173 BENICIA STREET  
FREMONT, CA 94538, U.S.A.  
TEL: (510) 771-1000  
FAX: (510) 661-0888**



**NVLAP LAB CODE 200065-0**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	06/22/11	Initial Issue, updated to the latest RSS-210 and RSS-GEN from 09J12750-2A and changed EUT model number and FCC ID/IC ID	T. Chan

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b>	<b>5</b>
<b>2. TEST METHODOLOGY</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY</b>	<b>6</b>
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	6
<b>5. EQUIPMENT UNDER TEST</b>	<b>7</b>
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM OUTPUT POWER	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. SOFTWARE AND FIRMWARE	7
5.5. WORST-CASE CONFIGURATION AND MODE	7
5.6. DESCRIPTION OF TEST SETUP	8
<b>6. TEST AND MEASUREMENT EQUIPMENT</b>	<b>10</b>
<b>7. ANTENNA PORT TEST RESULTS</b>	<b>11</b>
7.1. BASIC DATA RATE GFSK MODULATION	11
7.1.1. 20 dB AND 99% BANDWIDTH	11
7.1.2. HOPPING FREQUENCY SEPARATION	15
7.1.3. NUMBER OF HOPPING CHANNELS	17
7.1.4. AVERAGE TIME OF OCCUPANCY	22
7.1.5. OUTPUT POWER	25
7.1.6. AVERAGE POWER	29
7.1.7. CONDUCTED SPURIOUS EMISSIONS	30
7.2. ENHANCED DATA RATE 8PSK MODULATION	39
7.2.1. 20 dB AND 99% BANDWIDTH	39
7.2.2. HOPPING FREQUENCY SEPARATION	43
7.2.3. NUMBER OF HOPPING CHANNELS	45
7.2.4. AVERAGE TIME OF OCCUPANCY	50
7.2.5. OUTPUT POWER	53
7.2.6. AVERAGE POWER	57
7.2.7. CONDUCTED SPURIOUS EMISSIONS	58
<b>8. RADIATED TEST RESULTS</b>	<b>67</b>
8.1. LIMITS AND PROCEDURE	67
8.2. TRANSMITTER ABOVE 1 GHz	68
8.2.1. BASIC DATA RATE GFSK MODULATION	68
8.2.2. ENHANCED DATA RATE 8PSK MODULATION	77

---

8.3. RECEIVER ABOVE 1 GHz ..... 86

8.4. WORST-CASE BELOW 1 GHz..... 87

**9. AC POWER LINE CONDUCTED EMISSIONS ..... 90**

**10. MAXIMUM PERMISSIBLE EXPOSURE ..... 94**

**11. SETUP PHOTOS..... 97**

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** CASIO COMPUTER CO., LTD  
6-2 HON-MACHI 1-CHOME  
SHIBUYA-KU  
TOKYO, 151-8543, JAPAN

**EUT DESCRIPTION:** HANDHELD TERMINAL

**MODEL:** IT-800A-35U (HANDHELD) & HA-H62IO (ETHERNET CRADLE)

**SERIAL NUMBER:** 75 (CONDUCTED) & 02121 (RADIATED)

**DATE TESTED:** AUGUST 21 TO OCTOBER 21, 2009


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass
INDUSTRY CANADA RSS-210 Issue 8 Annex 8	Pass
INDUSTRY CANADA RSS-GEN Issue 3	Pass

Compliance Certification Services (UL CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report. All Data are complied with the latest RSS-210 Issue 8 Standard.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL CCS By:

Tested By:



THU CHAN  
EMC MANAGER  
UL CCS

MENGISTU MEKURIA  
EMC ENGINEER  
UL CCS

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 3, and RSS-210 Issue 8.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is an 802.11abg, Bluetooth and RFID equipped Handheld Terminal

The Bluetooth module is manufactured by Murata Manufacturing Co., Ltd.

### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	0.65	1.16
2402 - 2480	Enhanced 8PSK	2.22	1.67

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a Chip antenna antenna, with a maximum gain of -2.6 dBi.

### 5.4. SOFTWARE AND FIRMWARE

The test utility software used during testing was BTRadioTest CE6.0, ver. 3.00.

### 5.5. WORST-CASE CONFIGURATION AND MODE

The worst-case data rate for each mode is determined to be as follows, based on input from the manufacturer of the radio.

All final tests in the GFSK mode were made at 1 Mb/s.

All final tests in the 8PSK mode were made at 3 Mb/s.

The EUT also has been evaluated at X, Y, Z-orientations and the worst among them with AC/DC Adapter and with Ethernet cradle. The highest measured emission was determined the EUT with cradle configuration.

## 5.6. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST			
Description	Manufacturer	Model	Serial Number
AC/DC Adapter	Casio	AD-S42120B	N/A
Ethernet Cradle	Casio	HA-H62IO	N/A
Micro SD	San Disk	09228042950J1	N/A

### I/O CABLES


I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	US 115V	Un-shielded	2m	N/A
2	DC	1	DC	Un-shielded	2m	one ferrite at Cradle end.

### TEST SETUP

The EUT is sitting on a cradle during the tests. Test software exercised the EUT



**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	Asset	Cal Date	Cal Due
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01011	1/14/2009	1/14/2010
Antenna, Horn, 18 GHz	EMCO	3115	C00945	1/29/2009	1/29/2010
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00885	12/16/2008	12/16/2009
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	2/4/2009	2/4/2010
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4440A	C01179	8/24/2009	8/24/2010
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	1/5/2009	1/5/2010
Power Meter	Agilent / HP	437B	N02785	6/2/2008	12/2/2009
Power Sensor, 18 GHz	Agilent / HP	8481A	N02783	5/2/2008	11/2/2009
Temperature / Humidity	Thermotron	SE 600-10-10	C00930	4/6/2009	4/6/2010

## 7. ANTENNA PORT TEST RESULTS

### 7.1. BASIC DATA RATE GFSK MODULATION

#### 7.1.1. 20 dB AND 99% BANDWIDTH

##### LIMIT

None; for reporting purposes only.


##### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq 1\%$  of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled.


##### RESULTS

Channel	Frequency (MHz)	20 dB Bandwidth (kHz)	99% Bandwidth (kHz)
Low	2402	934.056	910.2874
Middle	2441	932.618	908.767
High	2480	943.556	911.5935

**20 dB AND 99% BANDWIDTH**







## 7.1.2. HOPPING FREQUENCY SEPARATION

### LIMIT

FCC §15.247 (a) (1)

IC RSS-210 A8.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer.

### RESULTS

**HOPPING FREQUENCY SEPARATION**





### **7.1.3. NUMBER OF HOPPING CHANNELS**

#### **LIMIT**

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


#### **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


#### **RESULTS**


79 Channels observed.

**NUMBER OF HOPPING CHANNELS**









#### **7.1.4. AVERAGE TIME OF OCCUPANCY**

##### **LIMIT**

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

##### **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channels \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$ .


##### **RESULTS**

Time Of Occupancy =  $10 * 11 \text{ pulses} * 2.97 \text{ msec} = 326.7 \text{ msec}$

**PULSE WIDTH**



**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD**





### 7.1.5. OUTPUT POWER

#### LIMIT

§15.247 (b) (1)

IC RSS-210 A8.4

The maximum antenna gain is less than 6 dBi, therefore the limit is 30 dBm.


#### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


#### RESULTS

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	0.45	30	-29.56
Middle	2441	0.65	30	-29.35
High	2480	0.60	30	-29.40

**OUTPUT POWER**







### 7.1.6. AVERAGE POWER

#### LIMIT

None; for reporting purposes only.

#### TEST PROCEDURE

The transmitter output is connected to a power meter.

#### RESULTS

The cable assembly insertion loss of 0.8dB was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	-1.02
Middle	2441	-0.91
High	2480	-0.81

## 7.1.7. CONDUCTED SPURIOUS EMISSIONS

### LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Limit = -20 dBc

### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.

### RESULTS


**SPURIOUS EMISSIONS, LOW CHANNEL**










**SPURIOUS EMISSIONS, MID CHANNEL**







**SPURIOUS EMISSIONS, HIGH CHANNEL**





**SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON**





## 7.2. ENHANCED DATA RATE 8PSK MODULATION

### 7.2.1. 20 dB AND 99% BANDWIDTH

#### LIMIT

None; for reporting purposes only.


#### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq 1\%$  of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled.


#### RESULTS


Channel	Frequency (MHz)	20 dB Bandwidth (kHz)	99% Bandwidth (kHz)
Low	2402	1314	1196.4
Middle	2441	1314	1224
High	2480	1301	1212.6

**20 dB AND 99% BANDWIDTH**









## 7.2.2. HOPPING FREQUENCY SEPARATION

### LIMIT

FCC §15.247 (a) (1)

IC RSS-210 A8.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer.

### RESULTS

**HOPPING FREQUENCY SEPARATION**



## **7.2.3. NUMBER OF HOPPING CHANNELS**

### **LIMIT**

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


### **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


### **RESULTS**

79 Channels observed.


**NUMBER OF HOPPING CHANNELS**











## 7.2.4. AVERAGE TIME OF OCCUPANCY

### LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channels \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$ .


### RESULTS

Time Of Occupancy =  $10 * 11 \text{ pulses} * 2.98 \text{ msec} = 327.8 \text{ msec}$

**PULSE WIDTH**



**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD**



## 7.2.5. OUTPUT POWER

### LIMIT

§15.247 (b) (1)

IC RSS-210 A8.4

The Channel Separation is greater than two-thirds of the 20 dB bandwidth and the maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.


### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


### RESULTS

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	2.17	21	-18.83
Middle	2441	2.22	21	-18.78
High	2480	1.99	21	-19.01

**OUTPUT POWER**









## 7.2.6. AVERAGE POWER

### LIMIT

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to a power meter.

### RESULTS

The cable assembly insertion loss of 0.8 was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	-1.49
Middle	2441	-1.60
High	2480	-1.72

## **7.2.7. CONDUCTED SPURIOUS EMISSIONS**

### **LIMITS**

FCC §15.247 (d)

IC RSS-210 A8.5

Limit = -20 dBc

### **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


### **RESULTS**


**SPURIOUS EMISSIONS, LOW CHANNEL**







**SPURIOUS EMISSIONS, MID CHANNEL**






**SPURIOUS EMISSIONS, HIGH CHANNEL**








**SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON**





## 8. RADIATED TEST RESULTS

### 8.1. LIMITS AND PROCEDURE

#### LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.5 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

#### TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

## 8.2. TRANSMITTER ABOVE 1 GHz


### 8.2.1. BASIC DATA RATE GFSK MODULATION


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)






**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**







**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**








**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**





**HARMONICS AND SPURIOUS EMISSIONS**

**High Frequency Measurement**  
 Compliance Certification Services, Fremont 5m Chamber

Company: CASIO COMPUTER CO., LTD.  
 Project #: 09112750  
 Date: 10/25/2009  
 Test Engineer: MENGISTU MEKURIA  
 Configuration: EUT WITH ETHERNET CRADLE  
 Mode: TX GFSK MODE

**Test Equipment:**

Horn 1-18GHz	Pre-amplifier 1-26GHz	Pre-amplifier 26-40GHz	Horn > 18GHz	Limit
T73; S/N: 6717 @3m	T144 Miteq 3008A00931			FCC 15.209

Hi Frequency Cables

3' cable 22807700	12' cable 22807600	20' cable 22807500	HPF	Reject Filter	
3' cable 22807700	12' cable 22807600	20' cable 22807500		R_001	Peak Measurements RBW=VBW=1MHz Average Measurements RBW=1MHz, VBW=10Hz


f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fitr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
<b>LOW CH (2402.0 MHz)</b>															
1.602	3.0	49.4	43.1	25.9	3.0	-38.6	0.0	0.0	39.7	33.4	74	54	-34.3	-20.6	H
4.804	3.0	48.2	40.7	33.0	5.8	-36.5	0.0	0.0	50.6	43.0	74	54	-23.4	-11.0	H
1.602	3.0	51.0	47.0	25.9	3.0	-38.6	0.0	0.0	41.3	37.3	74	54	-32.7	-16.7	V
4.804	3.0	45.8	37.8	33.0	5.8	-36.5	0.0	0.0	48.1	40.2	74	54	-25.9	-13.8	V
<b>MID CH (2441.0 MHz)</b>															
1.208	3.0	51.1	45.3	24.6	2.6	-39.2	0.0	0.0	39.0	33.3	74	54	-35.0	-20.7	H
1.628	3.0	50.0	43.9	26.0	3.1	-38.6	0.0	0.0	40.5	34.3	74	54	-33.5	-19.7	H
1.716	3.0	48.5	40.7	26.3	3.2	-38.5	0.0	0.0	39.5	31.6	74	54	-34.5	-22.4	H
4.882	3.0	48.3	40.9	33.1	5.8	-36.5	0.0	0.0	50.8	43.3	74	54	-23.2	-10.7	H
7.323	3.0	41.3	29.7	35.3	7.3	-36.2	0.0	0.0	47.7	36.1	74	54	-26.3	-17.9	H
1.208	3.0	52.1	47.6	24.6	2.6	-39.2	0.0	0.0	40.0	35.5	74	54	-34.0	-18.5	V
1.628	3.0	51.9	47.9	26.0	3.1	-38.6	0.0	0.0	42.3	38.3	74	54	-31.7	-15.7	V
1.716	3.0	45.6	33.6	26.3	3.2	-38.5	0.0	0.0	36.6	24.6	74	54	-37.4	-29.4	V
4.882	3.0	46.6	39.4	33.1	5.8	-36.5	0.0	0.0	49.1	41.9	74	54	-24.9	-12.1	V
7.323	3.0	40.3	27.6	35.3	7.3	-36.2	0.0	0.0	46.7	33.9	74	54	-27.3	-20.1	V
<b>HI CH (2480 MHz)</b>															
1.654	3.0	49.6	43.7	26.1	3.1	-38.6	0.0	0.0	40.2	34.3	74	54	-33.8	-19.7	H
4.960	3.0	47.5	40.3	33.2	5.9	-36.5	0.0	0.0	50.2	42.9	74	54	-23.8	-11.1	H
7.440	3.0	40.6	29.0	35.5	7.3	-36.2	0.0	0.0	47.2	35.6	74	54	-26.8	-18.4	H
1.654	3.0	51.1	46.9	26.1	3.1	-38.6	0.0	0.0	41.7	37.5	74	54	-32.3	-16.5	V
4.960	3.0	47.1	39.5	33.2	5.9	-36.5	0.0	0.0	49.7	42.1	74	54	-24.3	-11.9	V
7.440	3.0	40.3	28.3	35.5	7.3	-36.2	0.0	0.0	46.9	34.9	74	54	-27.1	-19.1	V


Rev. 11.10.08

f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit
CL	Cable Loss	HPF	High Pass Filter		


### 8.2.2. ENHANCED DATA RATE 8PSK MODULATION


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)






**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**










**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**





**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**





**HARMONICS AND SPURIOUS EMISSIONS**

**High Frequency Measurement**  
 Compliance Certification Services, Fremont 5m Chamber

Company: CASIO COMPUTER CO., LTD.  
 Project #: 09112730  
 Date: 10/25/2009  
 Test Engineer: MENGISTU MEKURIA  
 Configuration: EUT WITH ETHERNET CRADLE  
 Mode: TX 8PSK MODE

**Test Equipment:**

Horn 1-18GHz	Pre-amplifier 1-26GHz	Pre-amplifier 26-40GHz	Horn > 18GHz	Limit
T73; S/N: 6717 @3m	T144 Miteq 3008A00931			FCC 15.209

Hi Frequency Cables

3' cable 22807700	12' cable 22807600	20' cable 22807500	HPF	Reject Filter	Peak Measurements RBW=VBW=1MHz
3' cable 22807700	12' cable 22807600	20' cable 22807500		R_001	Average Measurements RBW=1MHz ; VBW=10Hz

f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fldr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
<b>LOW CH (2402.0 MHz)</b>															
1.602	3.0	49.4	43.1	25.9	3.0	-38.6	0.0	0.0	39.7	33.4	74	54	-34.3	-20.6	H
4.804	3.0	43.5	29.2	33.0	5.8	-36.5	0.0	0.0	45.9	31.5	74	54	-28.1	-22.5	H
1.602	3.0	51.0	47.0	25.9	3.0	-38.6	0.0	0.0	41.3	37.3	74	54	-32.7	16.7	V
4.804	3.0	41.9	28.1	33.0	5.8	-36.5	0.0	0.0	44.3	30.4	74	54	-29.7	-23.6	V
<b>MID CH (2441.0 MHz)</b>															
1.208	3.0	51.1	45.3	24.6	2.6	-39.2	0.0	0.0	39.0	33.3	74	54	-35.0	-20.7	H
1.628	3.0	50.0	43.9	26.0	3.1	-38.6	0.0	0.0	40.5	34.3	74	54	-33.5	-19.7	H
1.716	3.0	48.5	40.7	26.3	3.2	-38.5	0.0	0.0	39.5	31.6	74	54	-34.5	-22.4	H
4.882	3.0	42.8	29.5	33.1	5.8	-36.5	0.0	0.0	45.3	32.0	74	54	-28.7	-22.0	H
1.208	3.0	52.1	47.6	24.6	2.6	-39.2	0.0	0.0	40.0	35.5	74	54	-34.0	-18.5	V
1.628	3.0	51.9	47.9	26.0	3.1	-38.6	0.0	0.0	42.3	38.3	74	54	-31.7	-15.7	V
1.716	3.0	41.0	33.6	26.3	3.2	-38.5	0.0	0.0	32.0	24.6	74	54	-42.0	-29.4	V
4.882	3.0	41.0	28.2	33.1	5.8	-36.5	0.0	0.0	43.5	30.6	74	54	-30.5	-23.4	V
<b>HI CH (2480 MHz)</b>															
1.654	3.0	49.6	43.7	26.1	3.1	-38.6	0.0	0.0	40.2	34.3	74	54	-33.8	-19.7	H
4.960	3.0	43.3	29.1	33.2	5.9	-36.5	0.0	0.0	45.9	31.7	74	54	-28.1	-22.3	H
1.654	3.0	51.1	46.9	26.1	3.1	-38.6	0.0	0.0	41.7	37.5	74	54	-32.3	-16.5	V
4.960	3.0	41.2	27.9	33.2	5.9	-36.5	0.0	0.0	43.9	30.6	74	54	-30.1	-23.4	V

Rev. 11.10.08

f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit
CL	Cable Loss	HPF	High Pass Filter		

### 8.3. RECEIVER ABOVE 1 GHz

**High Frequency Measurement**  
 Compliance Certification Services, Fremont 5m Chamber

Company: CASIO COMPUTER CO., LTD.  
 Project #: 09112750  
 Date: 10/25/2009  
 Test Engineer: MENGISTU MEKURIA  
 Configuration: EUT WITH ETHERNET CRADLE  
 Mode: RX WORST-CASE

**Test Equipment:**

Horn 1-18GHz	Pre-amplifer 1-26GHz	Pre-amplifer 26-40GHz	Horn > 18GHz	Limit
T73; S/N: 6717 @3m	T144 Miteq 3008A00931			RX RSS 210

Hi Frequency Cables

3' cable 22807700	12' cable 22807600	20' cable 22807500	HPF	Reject Filter	Peak Measurements RBW=VBW=1MHz
3' cable 22807700	12' cable 22807600	20' cable 22807500		R_001	Average Measurements RBW=1MHz; VBW=10Hz


f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fitr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
1.520	3.0	49.5	43.2	25.6	3.0	-38.7	0.0	0.0	39.3	33.0	74	54	-34.7	-21.0	V
1.626	3.0	52.7	49.6	26.0	3.1	-38.6	0.0	0.0	43.1	40.0	74	54	-30.9	-14.0	V
1.651	3.0	49.0	43.2	26.0	3.1	-38.6	0.0	0.0	39.6	33.7	74	54	-34.4	-20.3	V
1.520	3.0	49.1	42.5	25.6	3.0	-38.7	0.0	0.0	39.0	32.3	74	54	-35.0	-21.7	H
1.626	3.0	50.3	45.3	26.0	3.1	-38.6	0.0	0.0	40.8	35.8	74	54	-33.2	-18.2	H
1.651	3.0	50.8	45.6	26.0	3.1	-38.6	0.0	0.0	41.4	36.1	74	54	-32.6	-17.9	H
1.808	3.0	50.0	44.3	26.6	3.3	-38.3	0.0	0.0	41.5	35.8	74	54	-32.5	-18.2	H
1.820	3.0	49.4	43.6	26.6	3.3	-38.3	0.0	0.0	40.9	35.2	74	54	-33.1	-18.8	H
1.832	3.0	50.0	45.8	26.6	3.3	-38.3	0.0	0.0	41.7	37.4	74	54	-32.3	-16.6	H
1.846	3.0	50.8	45.6	26.7	3.3	-38.3	0.0	0.0	42.5	37.3	74	54	-31.5	-16.7	H

Rev. 11.10.08


f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit
CL	Cable Loss	HPF	High Pass Filter		

### 8.4. WORST-CASE BELOW 1 GHz

#### SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)



### VERTICAL PLOT





HORIZONTAL AND VERTICAL DATA

30-1000MHz Frequency Measurement  
 Compliance Certification Services, Fremont 5m Chamber

Test Engr: MENGISTU MEKURIA  
 Date: 10/25/2009  
 Project #: 09J12750  
 Company: CASIO COMPUTER CO., LTD.  
 EUT Description: EUT WITH ETHERNET CRADLE  
 EUT M/N: IT-800A-35U  
 Test Target: FCC PART CRF47  
 Mode Oper: TX WORST-CASE

f Measurement Frequency Amp Preamp Gain Margin Margin vs. Limit  
 Dist Distance to Antenna D Corr Distance Correct to 3 meters  
 Read Analyzer Reading Filter Filter Insert Loss  
 AF Antenna Factor Corr. Calculated Field Strength  
 CL Cable Loss Limit Field Strength Limit

f MHz	Dist (m)	Read dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Filter dB	Corr. dBuV/m	Limit dBuV/m	Margin dB	Ant. Pol. V/H	Det. P/A/QP	Notes
303.851	3.0	46.8	13.5	1.5	28.1	0.0	0.0	33.7	46.0	-12.3	H	P	
314.772	3.0	48.9	13.6	1.6	28.1	0.0	0.0	36.0	46.0	-10.0	H	P	
325.692	3.0	49.1	13.8	1.6	28.1	0.0	0.0	36.4	46.0	-9.6	H	P	
336.613	3.0	48.8	14.0	1.6	28.1	0.0	0.0	36.2	46.0	-9.8	H	P	
347.533	3.0	46.2	14.1	1.7	28.1	0.0	0.0	33.9	46.0	-12.1	H	P	
374.894	3.0	45.9	14.5	1.7	28.1	0.0	0.0	34.1	46.0	-11.9	H	P	
303.851	3.0	50.4	13.5	1.5	28.1	0.0	0.0	37.3	46.0	-8.7	V	P	
314.772	3.0	50.8	13.6	1.6	28.1	0.0	0.0	37.9	46.0	-8.1	V	P	
325.692	3.0	51.8	13.8	1.6	28.1	0.0	0.0	39.1	46.0	-6.9	V	P	
363.974	3.0	49.9	14.4	1.7	28.1	0.0	0.0	37.9	46.0	-8.1	V	P	
457.098	3.0	47.4	16.0	1.9	27.9	0.0	0.0	37.3	46.0	-8.7	V	P	
468.018	3.0	47.4	16.2	2.0	27.9	0.0	0.0	37.6	46.0	-8.4	V	P	

Rev. 1.27.09

Note: No other emissions were detected above the system noise floor.

## 9. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

IC RSS-Gen 7.2.4

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.


Line conducted data is recorded for both NEUTRAL and HOT lines.

### RESULTS


**6 WORST EMISSIONS**

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq. (MHz)	Reading			Class (dB)	Limit QP	EN B AV	Margin		Remark L1 / L2
	PK (dBuV)	QP (dBuV)	AV (dBuV)				QP (dB)	AV (dB)	
0.24	56.47	--	24.16	0.00	62.03	52.03	-5.56	-27.87	L1
0.37	43.61	--	25.04	0.00	58.61	48.61	-15.00	-23.57	L1
0.61	38.32	--	18.08	0.00	56.00	46.00	-17.68	-27.92	L1
0.18	51.30	--	29.05	0.00	64.35	54.35	-13.05	-25.30	L2
0.45	39.69	--	36.08	0.00	56.89	46.89	-17.20	-10.81	L2
0.80	40.33	--	24.83	0.00	56.00	46.00	-15.67	-21.17	L2
6 Worst Data									

**LINE 1 RESULTS**



**LINE 2 RESULTS**



## 10. MAXIMUM PERMISSIBLE EXPOSURE

### FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

**IC RULES**

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

**Table 5  
 Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)**

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m <sup>2</sup> )	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	280/ <i>f</i>	2.19/ <i>f</i>		6
10–30	28	2.19/ <i>f</i>		6
30–300	28	0.073	2*	6
300–1 500	1.585 <i>f</i> <sup>0.5</sup>	0.0042 <i>f</i> <sup>0.5</sup>	<i>f</i> /150	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	616 000 / <i>f</i> <sup>1.2</sup>
150 000–300 000	0.158 <i>f</i> <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> <i>f</i>	616 000 / <i>f</i> <sup>1.2</sup>

\* Power density limit is applicable at frequencies greater than 100 MHz.

- Notes:**
1. Frequency, *f*, is in MHz.
  2. A power density of 10 W/m<sup>2</sup> is equivalent to 1 mW/cm<sup>2</sup>.
  3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μT) or 12.57 milligauss (mG).

**EQUATIONS**

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * \text{D}^2)$$

where

- S = Power density in W/m<sup>2</sup>
- EIRP = Equivalent Isotropic Radiated Power in W
- D = Separation distance in m

Power density in units of W/m<sup>2</sup> is converted to units of mW/cm<sup>2</sup> by dividing by 10.

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

where

- D = Separation distance in m
- EIRP = Equivalent Isotropic Radiated Power in W
- S = Power density in W/m<sup>2</sup>

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

**LIMITS**

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm<sup>2</sup>

From IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m<sup>2</sup>

**RESULTS**

Band	Mode	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	IC Power Density (W/m <sup>2</sup> )	FCC Power Density (mW/cm <sup>2</sup> )
2.4 GHz	Bluetooth	0.20	2.22	-2.60	0.00	0.000