

CASIO COMPUTER CO.,LTD.

Technical Planning Department Hamura R & D Center
 2-1, Sakaecho 3-chome, Hamura-shi, Tokyo 205-8555, Japan
 TEL: +81-42-579-7282 FAX: +81-42-579-7702



Request for Limited Modular Transmitter Approval

November 12, 2019

FCC ID : BBQM1

Applicant: Casio Computer Co Ltd

This transmitter, model: M1 is designed by us.

It complies with the modular transmitters basic requirements (Item 1 to 8) in FCC Part 15 Subpart C Section 15.212 as indicated below:

Modular Approval Checklist:

| Modular approval requirement | Yes | No |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (1) Have its own RF shielding. | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| (2) Have buffered modulation/data inputs. | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| (3) Have its own power supply regulation. | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| (4) Comply with the antenna and transmission system requirements of § 15.203, 15.204(b) and 15.204(c). | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| (5) Tested in a stand-alone configuration. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in FCC § 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module. The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available. | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| (6) Equipped with either a permanently affixed label or must be capable of electronically displaying its FCC ID. If the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. | <input type="checkbox"/> | <input checked="" type="checkbox"/> The label which is indicated of FCC ID is firmly bonded to the shield surface, but it would peel off from the module. Therefore there are described on the manual and the removal label. |
| (7) Comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| (8) Comply with any applicable RF exposure requirements in its final configuration: The modular transmitter complies with FCC radiation exposure requirement. | <input checked="" type="checkbox"/> | <input type="checkbox"/> |


 Hiroaki Suzuki
 Casio Computer Co Ltd