



RADIO TEST REPORT

Test Report No. : 11019835S-A-R1

Applicant : CASIO COMPUTER CO., LTD.
Type of Equipment : Bluetooth Watch
Model No. : EQB-600
FCC ID : BBQS02W
Test regulation : FCC Part 15 Subpart C: 2015
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
7. This report is a revised version of 11019835S-A. 11019835S-A is replaced with this report.

Date of test:

November 28 to December 15, 2015

Representative test engineer:

Hiroyuki Morikawa
Engineer
Consumer Technology Division

Approved by:

Toyokazu Imamura
Leader
Consumer Technology Division



- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
 There is no testing item of "Non-accreditation".

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

13-EM-F0429

REVISION HISTORY

Original Test Report No.: 11019835S-A

Revision	Test report No.	Date	Page revised	Contents
- (Original)	11019835S-A	January 29, 2016	-	-
1	11019835S-A-R1	February 24, 2016	8	Addition of *4)

CONTENTS	PAGE
SECTION 1: Customer information.....	4
SECTION 2: Equipment under test (E.U.T.).....	4
SECTION 3: Test specification, procedures & results.....	5
SECTION 4: Operation of E.U.T. during testing.....	8
SECTION 5: Radiated Spurious Emission	9
SECTION 6: Antenna Terminal Conducted Tests.....	10
APPENDIX 1: Test data	11
6dB Bandwidth	11
Maximum Peak Output Power	13
Average Output Power	14
Radiated Spurious Emission	16
Conducted Spurious Emission	22
Power Density	25
99%Occupied Bandwidth	27
APPENDIX 2: Test instruments	28
APPENDIX 3: Photographs of test setup	29
Radiated Spurious Emission	29
Worst Case Position	30

SECTION 1: Customer information

Company Name : CASIO COMPUTER CO., LTD.
Address : 2-1, Sakaecho 3 chome, Hamura-shi, Tokyo 205-8555 Japan
Telephone Number : +81-42-579-7282
Facsimile Number : +81-42-579-7702
Contact Person : Hiroaki Suzuki

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Bluetooth Watch
Model No. : EQB-600
Serial No. : Refer to Section 4, Clause 4.2
Rating : DC 2.5 V
Receipt Date of Sample : November 18, 2015
Country of Mass-production : China, Thailand, Japan
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No Modification by the test lab

2.2 Product Description

Model: EQB-600 (referred to as the EUT in this report) is a Bluetooth Watch.

Series models: EQB-700

Models EQB-700 is identical to EQB-600 except for model designation, design of watch face (display), and design of enclosure. These differences have no influence to mechanical, electrical and radio condition of Bluetooth Watches.

General Specification

Clock frequency(ies) in the system : 26 MHz, 32.768 kHz

Radio Specification

Equipment type : Transceiver
Frequency of operation : 2402 MHz - 2480 MHz
Bandwidth & channel spacing : 2 MHz
Type of modulation : GFSK
Antenna type : Pattern (Mono Pole)
Antenna gain : -5.0 dBi

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C: 2015, final revised on November 23, 2015
Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.247 Operation within the bands 902-928MHz,
2400-2483.5MHz, and 5725-5850MHz

* Some parts are effective on and after December 17, 2015 or December 23, 2015. The revision does not affect the test specification applied to the EUT.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods IC: RSS-Gen 8.8	FCC: Section 15.207 IC: RSS-Gen 8.8	-	-	N/A *1)
6dB Bandwidth	FCC: KDB 558074 D01 DTS Meas Guidance v03r04 IC: -	FCC: Section 15.247(a)(2) IC: RSS-247 5.2(1)	See data.	Complied	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 DTS Meas Guidance v03r04 IC: RSS-Gen 6.12	FCC: Section 15.247(b)(3) IC: RSS-247 5.4(4)		Complied	Conducted
Power Density	FCC: KDB 558074 D01 DTS Meas Guidance v03r04 IC: -	FCC: Section 15.247(e) IC: RSS-247 5.2(2)		Complied	Conducted
Spurious Emission Restricted Band Edges	FCC: KDB 558074 D01 DTS Meas Guidance v03r04 IC: RSS-Gen 6.13	FCC: Section15.247(d) IC: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	0.9 dB 7320.00 MHz, AV, Vertical Tx BT LE 2440 MHz	Complied	Conducted (below 30 MHz)/ Radiated (above 30 MHz) *2)

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

*1) The test is not applicable since the EUT has no AC mains.

*2) Radiated test was selected over 30 MHz based on section 15.247(d).

* In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred. (ANSI C63.10:2013 is Non-accreditation)

FCC Part 15.31 (e)

The EUT provides stable voltage (DC 1.35 V) constantly to RF IC regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part 15.203

The antenna is not removable from the EUT. Therefore, the equipment complies with the antenna requirement.

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	IC: RSS-Gen 6.6	IC: -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.
Shonan EMC Lab.

Item	Frequency range	Uncertainty (+/-)		
		No. 1 SAC / SR	No. 2 SAC / SR	No. 3 SAC / SR
Conducted emission (AC Mains) LISN	150 kHz-30 MHz	3.6 dB	3.4 dB	3.4 dB
Radiated emission (Measurement distance: 3 m)	9 kHz-30 MHz	3.7 dB	3.5 dB	3.5 dB
	30 MHz-300 MHz	4.9 dB	4.9 dB	4.7 dB
	300 MHz-1 GHz	5.0 dB	5.0 dB	4.8 dB
	1 GHz-13 GHz	4.9 dB	4.9 dB	4.9 dB
Radiated emission (Measurement distance: 1 m)	13 GHz-18 GHz	5.7 dB	5.7 dB	5.7 dB
	18 GHz-40 GHz	4.5 dB	4.3 dB	4.3 dB

SAC=Semi-Anechoic Chamber

SR= Shielded Room is applied besides radiated emission

Antenna terminal test	Uncertainty (+/-)
Power Measurement above 1 GHz (Average Detector)_SPM-06	0.76 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-06	0.79 dB
Power Measurement above 1 GHz (Average Detector)_SPM-07	0.74 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-07	1.08 dB
Spurious emission (Conducted) below 1GHz	1.5 dB
Spurious emission (Conducted) 1 GHz-3 GHz	1.7 dB
Spurious emission (Conducted) 3 GHz-18 GHz	2.4 dB
Spurious emission (Conducted) 18 GHz-26.5 GHz	2.5 dB
Spurious emission (Conducted) 26.5 GHz-40 GHz	2.5 dB
Bandwidth Measurement	0.66 %
Duty cycle and Time Measurement	0.012 %

Radiated emission test

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

3.5 Test Location

UL Japan, Inc. Shonan EMC Lab.
1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN
Telephone: +81 463 50 6400, Facsimile: +81 463 50 6401
JAB Accreditation No. RTL02610

Test site	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
No.1 Semi-anechoic chamber	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
No.2 Semi-anechoic chamber	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
No.3 Semi-anechoic chamber	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5m
No.4 Semi-anechoic chamber	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
No.1 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.2 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.3 Shielded room	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
No.4 Shielded room	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
No.5 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.6 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.8 shielded room	-	3.45 x 5.5 x 2.4	3.45 x 5.5	-
No.1 Measurement room	-	2.55 x 4.1 x 2.5	-	-

3.6 Test data, Test instruments, and Test set up


Refer to APPENDIX.

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Mode(s)

Mode	Remarks*	Tested frequency
Bluetooth Low Energy	PN9	2402 MHz, 2440 MHz, 2480 MHz
* The worst condition was determined based on the test result of Maximum Peak Output Power (Mid Channel) Power settings: 0 dBm Test software: Ver. 96		

4.2 Configuration and peripherals



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

Description of EUT

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Bluetooth Watch	EQB-600	6 *1) 92 *2)	Casio Computer Co., Ltd.	EUT

*1) Used for Antenna Terminal conducted test

*2) Used for Radiated Emission test

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	0.05 + 2	Unshielded	Unshielded	*3)
2	Signal Cable	0.05	Unshielded	Unshielded	*4)

*3) Cable for test operation

*4) Cable for system reset during the development, not used for the product

SECTION 5: Radiated Spurious Emission

Test Procedure

It was measured based on "11.0 Emissions in non-restricted frequency bands" of "558074 D01 DTS Meas Guidance v03r04".

[For below 1GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9(IC) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (IC).

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV *2)	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	Average Power Method: <u>12.2.5.2</u> RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (Linear voltage) Trace: 100 traces Duty factor was added to the results.	RBW: 100 kHz VBW: 300 kHz
Test Distance	3 m	3 m (below 13 GHz), 1 m *1) (above 13 GHz)		3 m (below 13 GHz), 1 m *1) (above 13 GHz)

*1) Distance Factor: $20 \times \log(1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$

*2) Average Power Measurement was performed based on 6.0 & 12.2.5 of "KDB 558074 D01 DTS Meas Guidance v03r04"

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Antenna polarization	Carrier (Band edge)	Spurious (Below 1 GHz)	Spurious (1 G -13 GHz)	Spurious (13 G -18 GHz)	Spurious (18 G -26.5 GHz)
Horizontal	X	X	X	X	X
Vertical	Y	X	Z	X	X

Measurement range : 30 M – 26.5 GHz

Test data : APPENDIX

Test result : Pass

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 6: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
6dB Bandwidth	10 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Sample	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/Average *2)	-	Power Meter (Sensor: 50 MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3 kHz	9.1 kHz	Auto	Peak	Max Hold	Spectrum Analyzer *3)
Conducted Spurious Emission *4)	9kHz to 150kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150kHz to 30MHz	9.1 kHz	30 kHz				

*1) Peak hold was applied as Worst-case measurement.

*2) Reference data

*3) Section 10.2 Method PKPSD (peak PSD) of "KDB 558074 D01 DTS Meas Guidance v03r04".

*4) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart.

(9 kHz - 150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 9.1 kHz) *

The test results and limit are rounded off to two decimals place, so some differences might be observed.

Test data : **APPENDIX**
Test result : **Pass**

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401


APPENDIX 1: Test data

6dB Bandwidth

Test place Shonan EMC Lab. No.5 Shielded Room
Report No. 11019835S-A-R1
Date December 15, 2015
Temperature / Humidity 25 deg. C / 40 % RH
Engineer Tomohiro Hara
Mode Tx BT LE

Mode	Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
Tx BT LE	2402	0.788	> 500
	2440	0.712	> 500
	2480	0.785	> 500

6dB Bandwidth



Maximum Peak Output Power

Test place : Shonan EMC Lab. No.5 Shielded Room
Report No. : 11019835S-A-R1
Date : December 15, 2015
Temperature / Humidity : 25 deg. C / 40 % RH
Engineer : Tomohiro Hara
Mode : Tx BT LE

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2402	-11.74	1.34	9.67	-0.73	0.85	30.00	1000	30.73
2440	-11.93	1.35	9.67	-0.91	0.81	30.00	1000	30.91
2480	-12.43	1.36	9.67	-1.40	0.72	30.00	1000	31.40

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

*The equipment and cables were not used for factor 0 dB of the data sheets.

Average Output Power
(Reference data for RF Exposure)

Test place Shonan EMC Lab. No.5 Shielded Room
Report No. 11019835S-A-R1
Date December 15, 2015
Temperature / Humidity 25 deg. C / 40 % RH
Engineer Tomohiro Hara
Mode Tx BT LE

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Frame power)		Duty factor [dB]	Result (Burst power)	
				[dBm]	[mW]		[dBm]	[mW]
2402	-13.13	1.34	9.67	-2.12	0.61	0.83	-1.29	0.74
2440	-13.33	1.35	9.67	-2.31	0.59	0.83	-1.48	0.71
2480	-13.93	1.36	9.67	-2.90	0.51	0.83	-2.07	0.62

Sample Calculation:


Result (Frame power) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

Result (Burst power) = Frame power + Duty factor

*The equipment and cables were not used for factor 0 dB of the data sheets.

Burst rate confirmation

Test place : Shonan EMC Lab. No.5 Shielded Room
 Report No. : 11019835S-A-R1
 Date : December 15, 2015
 Temperature / Humidity : 25 deg. C / 40 % RH
 Engineer : Tomohiro Hara
 Mode : Tx BT LE



Radiated Spurious Emission

Test place	Shonan EMC Lab. No.3 Semi Anechoic Chamber	Shonan EMC Lab. No.2 Semi Anechoic Chamber
Report No.	11019835S-A-R1	
Date	November 28, 2015	November 29, 2015
Temperature / Humidity	25 deg. C / 57 % RH	22 deg. C / 35 % RH
Engineer	Hiroyuki Morikawa (30-1000MHz, 13-26.5GHz)	Yosuke Ishikawa (1-13GHz)
Mode	Tx BT LE 2402 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	214.892	QP	22.2	16.5	8.2	32.0	0.0	14.9	43.5	28.6	152	359	
Hori.	619.810	QP	21.7	19.2	10.0	31.9	0.0	19.0	46.0	27.0	100	328	
Hori.	878.200	QP	21.1	22.0	10.9	31.1	0.0	22.9	46.0	23.1	149	265	
Hori.	2390.000	PK	42.5	27.7	13.7	34.2	2.4	52.1	73.9	21.8	100	321	
Hori.	4804.000	PK	44.6	31.4	6.1	33.8	2.4	50.7	73.9	23.2	104	72	
Hori.	7206.000	PK	43.5	36.9	7.5	33.9	2.4	56.4	73.9	17.5	100	0	
Hori.	14412.000	PK	48.8	41.1	10.0	40.5	-9.5	49.9	73.9	24.0	100	292	
Hori.	21618.000	PK	39.6	40.5	14.2	46.8	-9.5	38.0	73.9	35.9	100	42	
Vert.	34.997	QP	22.2	15.7	6.8	32.2	0.0	12.5	40.0	27.5	100	23	
Vert.	132.736	QP	22.3	13.6	7.7	32.1	0.0	11.5	43.5	32.0	100	12	
Vert.	181.747	QP	22.5	15.9	8.0	32.0	0.0	14.4	43.5	29.1	100	11	
Vert.	821.002	QP	21.4	21.3	10.7	31.4	0.0	22.0	46.0	24.0	100	2	
Vert.	2390.000	PK	42.2	27.7	13.7	34.2	2.4	51.8	73.9	22.1	200	345	
Vert.	4804.000	PK	43.9	31.4	6.1	33.8	2.4	50.0	73.9	23.9	104	327	
Vert.	7206.000	PK	46.0	36.9	7.5	33.9	2.4	58.9	73.9	15.0	389	359	
Vert.	14412.000	PK	49.4	41.1	10.0	40.5	-9.5	50.5	73.9	23.4	100	7	
Vert.	21618.000	PK	39.4	40.5	14.2	46.8	-9.5	37.8	73.9	36.1	100	314	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 13 GHz : 20log(3.97 m / 3.0 m) = 2.4 dB

13 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.5 dB

Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2390.000	AV	34.3	27.7	13.7	34.2	1.6	2.4	45.5	53.9	8.4	*1)
Hori.	4804.000	AV	37.8	31.4	6.1	33.8	1.6	2.4	45.5	53.9	8.4	
Hori.	7206.000	AV	34.0	36.9	7.5	33.9	1.6	2.4	48.5	53.9	5.4	
Hori.	14412.000	AV	38.1	41.1	10.0	40.5	1.6	-9.5	40.8	53.9	13.1	
Hori.	21618.000	AV	28.2	40.5	14.2	46.8	1.6	-9.5	28.2	53.9	25.7	
Vert.	2390.000	AV	34.6	27.7	13.7	34.2	1.6	2.4	45.8	53.9	8.1	*1)
Vert.	4804.000	AV	37.4	31.4	6.1	33.8	1.6	2.4	45.1	53.9	8.8	
Vert.	7206.000	AV	38.2	36.9	7.5	33.9	1.6	2.4	52.7	53.9	1.2	
Vert.	14412.000	AV	37.6	41.1	10.0	40.5	1.6	-9.5	40.3	53.9	13.6	
Vert.	21618.000	AV	28.1	40.5	14.2	46.8	1.6	-9.5	28.1	53.9	25.8	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 13 GHz : 20log(3.97 m / 3.0 m) = 2.4 dB

13 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.5 dB

Duty factor refer to "Duty factor Calculation chart" sheet.

*1) Not out of band emission (Leakage Power)

20 dBc Data Sheet (RBW 100 kHz, VBW 300 kHz)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2402.000	PK	73.1	27.8	13.7	34.2	2.4	82.8	-	-	Carrier
Hori.	2400.000	PK	37.6	27.7	13.7	34.2	2.4	47.2	62.8	15.6	
Hori.	9608.000	PK	40.0	38.0	8.7	34.7	2.4	54.4	62.8	8.4	
Vert.	2402.000	PK	73.5	27.8	13.7	34.2	2.4	83.2	-	-	Carrier
Vert.	2400.000	PK	36.5	27.7	13.7	34.2	2.4	46.1	63.2	17.1	
Vert.	9608.000	PK	40.0	38.0	8.7	34.7	2.4	54.4	63.2	8.8	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 13 GHz : 20log(3.97 m / 3.0 m) = 2.4 dB

13 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.5 dB

UL Japan, Inc.

Shonan EMC Lab.



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Shonan EMC Lab. No.2 Semi Anechoic Chamber
Report No.	11019835S-A-R1
Date	November 29, 2015
Temperature / Humidity	22 deg. C / 35 % RH
Engineer	Yosuke Ishikawa (1-13GHz)
Mode	Tx BT LE 2402 MHz



* Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Test place	Shonan EMC Lab. No.3 Semi Anechoic Chamber	Shonan EMC Lab. No.2 Semi Anechoic Chamber
Report No.	11019835S-A-R1	
Date	November 28, 2015	November 29, 2015
Temperature / Humidity	25 deg. C / 57 % RH	22 deg. C / 35 % RH
Engineer	Hiroyuki Morikawa (30-1000MHz, 13-26.5GHz)	Yosuke Ishikawa (1-13GHz)
Mode	Tx BT LE 2440 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	215.374	QP	22.3	16.5	8.2	32.0	0.0	15.0	43.5	28.5	151	139	
Hori.	619.698	QP	21.7	19.2	10.0	31.9	0.0	19.0	46.0	27.0	100	12	
Hori.	878.123	QP	21.1	22.0	10.9	31.1	0.0	22.9	46.0	23.1	100	2	
Hori.	4880.000	PK	42.4	31.6	6.2	33.8	2.4	48.8	73.9	25.1	109	154	
Hori.	7320.000	PK	45.3	36.9	7.6	33.8	2.4	58.4	73.9	15.5	146	33	
Hori.	14640.000	PK	48.3	41.0	10.1	40.6	-9.5	49.3	73.9	24.6	100	297	
Hori.	21960.000	PK	39.1	40.7	14.4	46.9	-9.5	37.8	73.9	36.1	100	208	
Vert.	34.998	QP	22.2	15.7	6.8	32.2	0.0	12.5	40.0	27.5	100	358	
Vert.	132.704	QP	22.3	13.6	7.7	32.1	0.0	11.5	43.5	32.0	100	298	
Vert.	182.726	QP	22.3	15.9	8.0	32.0	0.0	14.2	43.5	29.3	100	12	
Vert.	820.005	QP	21.4	21.2	10.7	31.4	0.0	21.9	46.0	24.1	100	311	
Vert.	4880.000	PK	42.9	31.6	6.2	33.8	2.4	49.3	73.9	24.6	129	338	
Vert.	7320.000	PK	46.6	36.9	7.6	33.8	2.4	59.7	73.9	14.2	383	9	
Vert.	14640.000	PK	49.9	41.0	10.1	40.6	-9.5	50.9	73.9	23.0	100	1	
Vert.	21960.000	PK	39.3	40.7	14.4	46.9	-9.5	38.0	73.9	35.9	100	40	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 13 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.4\text{ dB}$

13 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	4880.000	AV	34.5	31.6	6.2	33.8	1.6	2.4	42.5	53.9	11.4	
Hori.	7320.000	AV	37.2	36.9	7.6	33.8	1.6	2.4	51.9	53.9	2.0	
Hori.	14640.000	AV	37.8	41.0	10.1	40.6	1.6	-9.5	40.4	53.9	13.5	
Hori.	21960.000	AV	28.7	40.7	14.4	46.9	1.6	-9.5	29.0	53.9	24.9	
Vert.	4880.000	AV	35.9	31.6	6.2	33.8	1.6	2.4	43.9	53.9	10.0	
Vert.	7320.000	AV	38.3	36.9	7.6	33.8	1.6	2.4	53.0	53.9	0.9	
Vert.	14640.000	AV	38.2	41.0	10.1	40.6	1.6	-9.5	40.8	53.9	13.1	
Vert.	21960.000	AV	28.6	40.7	14.4	46.9	1.6	-9.5	28.9	53.9	25.0	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 13 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.4\text{ dB}$

13 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

Duty factor refer to "Duty factor Calculation chart" sheet.

*1) Not out of band emission (Leakage Power)

20 dBc Data Sheet (RBW 100 kHz, VBW 300 kHz)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2440.000	PK	71.1	27.8	13.8	34.1	2.4	81.0	-	-	Carrier
Hori.	9760.000	PK	37.7	38.1	8.8	34.7	2.4	52.3	61.0	8.7	
Vert.	2440.000	PK	69.0	27.8	13.8	34.1	2.4	78.9	-	-	Carrier
Vert.	9760.000	PK	39.8	38.1	8.8	34.7	2.4	54.4	58.8	4.4	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 13 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.4\text{ dB}$

13 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Spurious Emission

Test place	Shonan EMC Lab. No.3 Semi Anechoic Chamber	Shonan EMC Lab. No.2 Semi Anechoic Chamber
Report No.	11019835S-A-R1	
Date	November 28, 2015	November 29, 2015
Temperature / Humidity	25 deg. C / 57 % RH	22 deg. C / 35 % RH
Engineer	Hiroyuki Morikawa (30-1000MHz, 13-26.5GHz)	Yosuke Ishikawa (1-13GHz)
Mode	Tx BT LE 2480 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	214.980	QP	22.2	16.5	8.2	32.0	0.0	14.9	43.5	28.6	148	331	
Hori.	619.976	QP	21.7	19.2	10.0	31.9	0.0	19.0	46.0	27.0	100	247	
Hori.	878.873	QP	21.0	22.0	10.9	31.1	0.0	22.8	46.0	23.2	100	146	
Hori.	2483.500	PK	43.5	27.9	13.8	34.1	2.4	53.5	73.9	20.4	100	130	
Hori.	4960.000	PK	43.8	31.9	6.3	33.9	2.4	50.5	73.9	23.4	103	147	
Hori.	7440.000	PK	44.2	37.0	7.7	33.7	2.4	57.6	73.9	16.3	100	333	
Hori.	14880.000	PK	49.0	40.9	10.1	40.6	-9.5	49.9	73.9	24.0	100	292	
Hori.	22320.000	PK	40.8	40.8	14.5	47.3	-9.5	39.3	73.9	34.6	100	50	
Vert.	35.002	QP	22.2	15.7	6.8	32.2	0.0	12.5	40.0	27.5	100	298	
Vert.	132.080	QP	22.2	13.5	7.7	32.1	0.0	11.3	43.5	32.2	100	341	
Vert.	182.722	QP	22.3	15.9	8.0	32.0	0.0	14.2	43.5	29.3	100	23	
Vert.	819.994	QP	21.4	21.2	10.7	31.4	0.0	21.9	46.0	24.1	100	52	
Vert.	2483.500	PK	43.4	27.9	13.8	34.1	2.4	53.4	73.9	20.5	379	295	
Vert.	4960.000	PK	41.9	31.9	6.3	33.9	2.4	48.6	73.9	25.3	203	341	
Vert.	7440.000	PK	46.3	37.0	7.7	33.7	2.4	59.7	73.9	14.2	391	7	
Vert.	14880.000	PK	48.5	40.9	10.1	40.6	-9.5	49.4	73.9	24.5	100	3	
Vert.	22320.000	PK	41.8	40.8	14.5	47.3	-9.5	40.3	73.9	33.6	100	45	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 13 GHz : 20log(3.97 m / 3.0 m) = 2.4 dB

13 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.5 dB

Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2483.500	AV	34.5	27.9	13.8	34.1	1.6	2.4	46.1	53.9	7.8	*1)
Hori.	4960.000	AV	33.8	31.9	6.3	33.9	1.6	2.4	42.1	53.9	11.8	
Hori.	7440.000	AV	35.8	37.0	7.7	33.7	1.6	2.4	50.8	53.9	3.1	
Hori.	14880.000	AV	37.5	40.9	10.1	40.6	1.6	-9.5	40.0	53.9	13.9	
Hori.	22320.000	AV	28.3	40.8	14.5	47.3	1.6	-9.5	28.4	53.9	25.5	
Vert.	2483.500	AV	34.0	27.9	13.8	34.1	1.6	2.4	45.6	53.9	8.3	*1)
Vert.	4960.000	AV	34.3	31.9	6.3	33.9	1.6	2.4	42.6	53.9	11.3	
Vert.	7440.000	AV	37.7	37.0	7.7	33.7	1.6	2.4	52.7	53.9	1.2	
Vert.	14880.000	AV	37.3	40.9	10.1	40.6	1.6	-9.5	39.8	53.9	14.1	
Vert.	22320.000	AV	29.7	40.8	14.5	47.3	1.6	-9.5	29.8	53.9	24.1	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 13 GHz : 20log(3.97 m / 3.0 m) = 2.4 dB

13 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.5 dB

Duty factor refer to "Duty factor Calculation chart" sheet.

*1) Not out of band emission (Leakage Power)

20 dBc Data Sheet (RBW 100 kHz, VBW 300 kHz)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2480.000	PK	69.1	27.9	13.8	34.1	2.4	79.1	-	-	Carrier
Hori.	9920.000	PK	36.9	38.2	8.9	34.7	2.4	51.7	59.1	7.4	
Vert.	2480.000	PK	65.1	27.9	13.8	34.1	2.4	75.1	-	-	Carrier
Vert.	9920.000	PK	37.5	38.2	8.9	34.7	2.4	52.3	55.1	2.8	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 13 GHz : 20log(3.97 m / 3.0 m) = 2.4 dB

13 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.5 dB

UL Japan, Inc.

Shonan EMC Lab.



1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Spurious Emission
(Reference Plot for band-edge)


Test place	Shonan EMC Lab. No.2 Semi Anechoic Chamber
Report No.	11019835S-A-R1
Date	November 29, 2015
Temperature / Humidity	22 deg. C / 35 % RH
Engineer	Yosuke Ishikawa (1-13GHz)
Mode	Tx BT LE 2480 MHz



* Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission (Plot data, Worst case)


Test place	Shonan EMC Lab. No.3 Semi Anechoic Chamber	Shonan EMC Lab. No.2 Semi Anechoic Chamber
Report No.	11019835S-A-R1	
Date	November 28, 2015	November 29, 2015
Temperature / Humidity	25 deg. C / 57 % RH	22 deg. C / 35 % RH
Engineer	Hiroyuki Morikawa (30-1000MHz, 13-26.5GHz)	Yosuke Ishikawa (1-13GHz)
Mode	Tx BT LE 2402 MHz	



*These plots data contains sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.5 Shielded Room
Report No.	11019835S-A-R1
Date	December 15, 2015
Temperature / Humidity	25 deg. C / 40 % RH
Engineer	Tomohiro Hara
Mode	Tx BT LE 2402 MHz



Frequency	Reading	Cable Loss	Attenuator Loss	Antenna Gain	N	EIRP	Distance	Ground bounce	E	Limit	Margin	Remark
[kHz]	[dBm]	[dB]	[dB]	[dBi] *1)	(Number of Output)	[dBm]	[m]	[dB]	(field strength) [dBuV/m]	[dBuV/m]	[dB]	
10.18	-90.4	0.01	9.5	2.0	1	-78.8	300	6.0	-17.6	47.4	65.0	
175.00	-80.3	0.01	9.5	2.0	1	-68.7	300	6.0	-7.5	22.7	30.2	


$E = \text{EIRP} - 20 \log(D) + \text{Ground bounce} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP} = \text{Reading} + \text{Cable Loss} + \text{Attenuator Loss} + \text{Antenna Gain} + 10 * \log(N)$

*1) Antenna Gain was based on KDB 558074 section 12.2.6.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.5 Shielded Room
Report No.	11019835S-A-R1
Date	December 15, 2015
Temperature / Humidity	25 deg. C / 40 % RH
Engineer	Tomohiro Hara
Mode	Tx BT LE 2440 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain [dBi] *1)	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
10.53	-89.8	0.01	9.5	2.0	1	-78.3	300	6.0	-17.0	47.1	64.1	
150.00	-78.4	0.01	9.5	2.0	1	-66.9	300	6.0	-5.6	24.0	29.6	


$E = \text{EIRP} - 20 \log(D) + \text{Ground bounce} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP} = \text{Reading} + \text{Cable Loss} + \text{Attenuator Loss} + \text{Antenna Gain} + 10 * \log(N)$

*1) Antenna Gain was based on KDB 558074 section 12.2.6.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.5 Shielded Room
Report No.	11019835S-A-R1
Date	December 15, 2015
Temperature / Humidity	25 deg. C / 40 % RH
Engineer	Tomohiro Hara
Mode	Tx BT LE 2480 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain [dBi] *1)	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
12.41	-90.2	0.01	9.5	2.0	1	-78.6	300	6.0	-17.3	45.7	63.0	
175.00	-79.2	0.01	9.5	2.0	1	-67.6	300	6.0	-6.4	22.7	29.1	

$E = \text{EIRP} - 20 \log(D) + \text{Ground bounce} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP} = \text{Reading} + \text{Cable Loss} + \text{Attenuator Loss} + \text{Antenna Gain} + 10 * \log(N)$

*1) Antenna Gain was based on KDB 558074 section 12.2.6.

Power Density

Test place Shonan EMC Lab. No.5 Shielded Room
Report No. 11019835S-A-R1
Date December 15, 2015
Temperature / Humidity 25 deg. C / 40 % RH
Engineer Tomohiro Hara
Mode Tx BT LE


Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result [dBm]	Limit [dBm]	Margin [dB]
2402.00	-22.29	1.34	9.67	-11.28	8.00	19.28
2440.00	-21.66	1.35	9.67	-10.64	8.00	18.64
2480.00	-22.43	1.36	9.67	-11.40	8.00	19.40

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator


*The equipment and cables were not used for factor 0 dB of the data sheets.

Power Density



99%Occupied Bandwidth

Test place	Shonan EMC Lab. No.5 Shielded Room
Report No.	11019835S-A-R1
Date	December 15, 2015
Temperature / Humidity	25 deg. C / 40 % RH
Engineer	Tomohiro Hara
Mode	Tx BT LE



APPENDIX 2: Test instruments

Test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
SSA-02	Spectrum Analyzer	Agilent	E4448A	MY48250106	AT, RE	2015/03/26 * 12
SCC-G13	Coaxial Cable	Suhner	SUCOFLEX 102	31599/2	AT	2015/03/11 * 12
SAT10-09	Attenuator	Weinschel Corp.	54A-10	W5692	AT	2015/11/04 * 12
SPSS-03	Power sensor	Anritsu	MA2411B	0917063	AT	2015/04/07 * 12
SPM-06	Power Meter	Anritsu	ML2495A	0850009	AT	2015/04/07 * 12
SOS-10	Humidity Indicator	A&D	AD-5681	4064561	AT	2015/10/22 * 12
STS-06	Digital Hitester	Hioki	3805-50	080997830	AT	2015/03/10 * 12
SAEC-03(NSA)	Semi-Anechoic Chamber	TDK	SAEC-03(NSA)	3	RE	2015/07/16 * 12
SBA-03	Biconical Antenna	Schwarzbeck	BBA9106	91032666	RE	2015/10/11 * 12
SLA-03	Logperiodic Antenna	Schwarzbeck	UHALP9108A	UHALP 9108-A 0901	RE	2015/10/11 * 12
SAT6-08	Attenuator	HIROSE ELECTRIC CO.,LTD.	AT-406(40)	-	RE	2015/08/31 * 12
SCC-C1/C2/C3/C4/C5/C10/SRSE-03	Coaxial Cable&RF Selector	Fujikura/Fujikura/Suhner/Suhner/Suhner/T OYO	8D2W/12DSFA /141PE/141PE/141PE/141PE/NS4906	-/0901-271(R F Selector)	RE	2015/04/17 * 12
SAF-03	Pre Amplifier	SONOMA	310N	290213	RE	2015/02/18 * 12
STR-06	Test Receiver	Rohde & Schwarz	ESCI	101259	RE	2015/03/24 * 12
COTS-SEMI-1	EMI Software	TSJ	TEPTO-DV(RE ,CE,RFI,MF)	-	RE	
SOS-05	Humidity Indicator	A&D	AD-5681	4062518	RE	2015/10/22 * 12
SJM-15	Measure	ASKUL	-	-	RE	-
STS-03	Digital Hitester	Hioki	3805-50	080997823	RE	2015/11/18 * 12
SAF-06	Pre Amplifier	TOYO Corporation	TPA0118-36	1440491	RE	2015/05/27 * 12
SCC-G04	Coaxial Cable	Junkosha	J12J102207-00	JUN-12-14-018	RE	2015/06/08 * 12
SCC-G23	Coaxial Cable	Suhner	SUCOFLEX 104	297342/4	RE	2015/05/19 * 12
SHA-03	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-739	RE	2015/08/11 * 12
KSA-08	Spectrum Analyzer	Agilent	E4446A	MY46180525	RE	2015/03/23 * 12
SCC-G15	Coaxial Cable	Suhner	SUCOFLEX 102	32703/2	RE	2015/03/11 * 12
SCC-G33	Coaxial Cable	Junkosha	MWX241-0100 0KMSKMS	-	RE	2015/04/09 * 12
SHA-04	Horn Antenna	ETS LINDGREN	3160-09	LM3640	RE	2015/03/17 * 12
SAF-09	Pre Amplifier	TOYO Corporation	HAP18-26W	00000018	RE	2015/09/07 * 12
SFL-18	Highpass Filter	MICRO-TRONICS	HPM50111	119	RE	2015/04/09 * 12
KAF-04	Pre Amplifier	Agilent	8449B	3008A01600	RE	2015/04/28 * 12
SCC-G05	Coaxial Cable	Junkosha	J12J102207-00	APR-30-15-037	RE	2015/05/11 * 12
SCC-G22	Coaxial Cable	Suhner	SUCOFLEX 104	296199/4	RE	2015/05/19 * 12
SHA-02	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-726	RE	2015/08/10 * 12
SOS-03	Humidity Indicator	A&D	AD-5681	4063325	RE	2015/10/22 * 12
SJM-14	Measure	ASKUL	-	-	RE	-
SAEC-02(SVSW R)	Semi-Anechoic Chamber	TDK	SAEC-02(SVSWR)	2	RE	2015/07/09 * 12
STS-02	Digital Hitester	Hioki	3805-50	080997819	RE	2015/03/10 * 12

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item: RE: Radiated Emission test, AT: Antenna Terminal Conducted test

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401