





# RADIO TEST REPORT

## Test Report No. 14807590S-A

Customer	CASIO COMPUTER CO., LTD.
Description of EUT	Watch
Model Number of EUT	GD-B500 (Bluetooth Module: CW3552 is contained.)
FCC ID	BBQS50W
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	June 29, 2023
Remarks	-

<b>Representative Test Engineer</b>	<b>Approved By</b>
	
Miku Ikudome Engineer	Akio Hayashi Manager
	 
CERTIFICATE 1266.03	
<input type="checkbox"/> The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.	
<input checked="" type="checkbox"/> There is no testing item of "Non-accreditation".	

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 22.0

---

## **ANNOUNCEMENT**

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.  
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Shonan EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided from the customer for this report is identified in Section 1.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

## **REVISION HISTORY**

**Original Test Report No.: 14807590S-A**

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	14807590S-A	June 29, 2023	-

**Reference: Abbreviations (Including words undescribed in this report)**

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

---

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer Information .....</b>	<b>5</b>
<b>SECTION 2: Equipment Under Test (EUT).....</b>	<b>5</b>
<b>SECTION 3: Test Specification, Procedures &amp; Results .....</b>	<b>6</b>
<b>SECTION 4: Operation of EUT during testing .....</b>	<b>9</b>
<b>SECTION 5: Radiated Spurious Emission.....</b>	<b>11</b>
<b>SECTION 6: Antenna Terminal Conducted Tests .....</b>	<b>13</b>
<b>APPENDIX 1: Test Data .....</b>	<b>14</b>
99 % Occupied Bandwidth and 6 dB Bandwidth.....	14
Maximum Peak Output Power .....	16
Average Output Power.....	17
Radiated Spurious Emission.....	19
Conducted Spurious Emission.....	25
Power Density .....	26
<b>APPENDIX 2: Test Instruments .....</b>	<b>28</b>
<b>APPENDIX 3: Photographs of Test Setup .....</b>	<b>30</b>
Radiated Spurious Emission.....	30
Pre-check of Worst Case Position .....	31
Antenna Terminal Conducted Tests .....	32

## **SECTION 1: Customer Information**

Company Name	CASIO COMPUTER CO., LTD.
Address	2-1, Sakaecho 3 chome, Hamura-shi, Tokyo 205-8555 Japan
Telephone Number	+81-42-579-7282
Contact Person	Shuji Yamashita

The information provided from the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

\* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

## **SECTION 2: Equipment Under Test (EUT)**

### **2.1 Identification of EUT**

Description	Watch
Model Number	GD-B500 (Bluetooth Module: CW3552 is contained.)
Alternative Name	R060
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	May 29, 2023
Test Date	June 7 to 17, 2023

### **2.2 Product Description**

#### **General Specification**

Rating	GD-B500 (Watch): Typical: DC 3.0 V, Min.: DC 1.9 V, Max.: DC 3.3 V CW3552 (Module): Typical: DC 3.0 V, Min.: DC 1.9 V, Max.: DC 3.3 V
Operating temperature	-10 deg. C to +60 deg. C

#### **Radio Specification**

##### **Bluetooth (Low Energy)**

Equipment Type	Transceiver
Frequency of Operation	2402 MHz to 2480 MHz
Type of Modulation	GFSK
Antenna Gain	2.5 dBi

## SECTION 3: Test Specification, Procedures & Results

### 3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

\* Also the EUT complies with FCC Part 15 Subpart B.

### 3.2 Procedures and Results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	-	N/A	*1)
6 dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(a)(2) ISED: RSS-247 5.2(a)	See data.	Complied	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section 15.247(b)(3) ISED: RSS-247 5.4(d)		Complied	Conducted
Power Density	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(e) ISED: RSS-247 5.2(b)		Complied	Conducted
Spurious Emission Restricted Band Edges	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section 15.247(d) ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10		8.9 dB 2390.000 MHz, AV, Horizontal, Tx BT LE 2402 MHz	Complied

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

\* In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.

\*1) The test is not applicable since the EUT does not have AC mains.

\*2 Radiated test was selected over 30 MHz based on section 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 8.5 and 8.6.

#### FCC Part 15.31 (e)

This EUT provides the stable voltage constantly to RF Module regardless of input voltage.  
Therefore, this EUT complies with the requirement.

#### FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.  
Therefore, the equipment complies with the antenna requirement of Section 15.203.

### 3.3 Addition to Standard

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
99 % Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement. Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k = 2$ .

Item	Frequency range	Uncertainty (+/-)
Conducted Emission (AC Mains) LISN	150 kHz-30 MHz	3.1 dB
Radiated Emission (Measurement distance: 3 m)	9 kHz-30 MHz	3.3 dB
	30 MHz-200 MHz	4.8 dB
	200 MHz-1 GHz	6.1 dB
	1 GHz-6 GHz	4.7 dB
	6 GHz-18 GHz	5.3 dB
	18 GHz-40 GHz	5.5 dB
Radiated Emission (Measurement distance: 1 m)	1 GHz-18 GHz	5.6 dB
	18 GHz-40 GHz	5.8 dB

Antenna terminal test	Uncertainty (+/-)
Power Measurement above 1 GHz (Average Detector) SPM-06	1.3 dB
Power Measurement above 1 GHz (Peak Detector) SPM-06	2.1 dB
Power Measurement above 1 GHz (Average Detector) SPM-07	1.1 dB
Power Measurement above 1 GHz (Peak Detector) SPM-07	1.2 dB
Power Measurement above 1 GHz (Average Detector) SPM-13	1.1 dB
Power Measurement above 1 GHz (Peak Detector) SPM-13	1.4 dB
Spurious Emission (Conducted) below 1 GHz	0.84 dB
Conducted Emissions Power Density Measurement 1 GHz-3 GHz	0.86 dB
Conducted Emissions Power Density Measurement 3 GHz-18 GHz	2.4 dB
Spurious Emission (Conducted) 18 GHz-26.5 GHz	2.4 dB
Spurious Emission (Conducted) 26.5 GHz-40 GHz	2.2 dB
Bandwidth Measurement	0.012 %
Duty Cycle and Time Measurement	0.27 %
Temperature_SCH-01	0.87 deg.C.
Humidity_SCH-01	3.5 %
Temperature_SCH-02	2.0 deg.C.
Humidity_SCH-02	6.7 %
Voltage	0.92 %

### 3.5 Test Location

UL Japan, Inc. Shonan EMC Lab.

1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 Japan

Telephone: +81-463-50-6400

A2LA Certificate Number: 1266.03

(FCC test firm registration number: 626366, ISED lab company number: 2973D / CAB identifier: JP0001)

Test site	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
No.1 Semi-anechoic chamber	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10 m
No.2 Semi-anechoic chamber	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10 m
No.3 Semi-anechoic chamber	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5 m
No.4 Semi-anechoic chamber	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
No.1 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.2 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.3 Shielded room	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
No.4 Shielded room	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
No.5 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.6 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.8 Shielded room	-	3.45 x 5.5 x 2.4	3.45 x 5.5	-
No.1 Measurement room	-	2.55 x 4.1 x 2.5	-	-

### 3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.



## **SECTION 4: Operation of EUT during testing**


### **4.1 Operating Mode(s)**

<b>Mode</b>	<b>Remarks*</b>
Bluetooth Low Energy (BT LE)	1M-PHY Uncoded PHY (1M-PHY), Maximum Packet Size, PRBS9
<p>*Power of the EUT was set by the software as follows;            Power Setting: Fixed            Software: BLE RF Test Version: 9.9            (Date: 2023.6.7, Storage location: EUT memory)</p> <p>*This setting of software is the worst case.            Any conditions under the normal use do not exceed the condition of setting.            In addition, end users cannot change the settings of the output power of the product.</p>	

\*The Details of Operating Mode(s)

<b>Test Item</b>	<b>Operating Mode</b>	<b>Tested Frequency</b>
Conducted Spurious Emission, Radiated Spurious Emission (Below 1 GHz)	Tx BT LE, 1M-PHY *1)	2440 MHz
Radiated Spurious Emission (Above 1 GHz), Maximum Peak Output Power, Power Density, 6 dB Bandwidth, 99 % Occupied Bandwidth,	Tx BT LE, 1M-PHY	2402 MHz 2440 MHz 2480 MHz
<p>*1) Conducted emissions and Spurious emissions for frequencies below 1 GHz were limited to the channel that had the highest power during the antenna terminal test, as preliminary testing indicated that changing the operating frequency had no significant impact on the emissions in those frequency bands.</p>		

## 4.2 Configuration and Peripherals



\* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

### Description of EUT and Support Equipment

No.	Item	Model Number	Serial Number	Manufacturer	Remarks
A	Watch	GD-B500	17 *1) *2) 24 *3)	CASIO COMPUTER CO., LTD.	EUT
B	Power Supply (DC)	PAN35-10A	BP002287	KIKUSUI	*1)
		PAN55-20A	DD000084	KIKUSUI	*2)
		PW18-2ATP	19050351	TEXIO	*3)

### List of Cables Used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC	0.1 + 1.8 + 0.4	Unshielded	Unshielded	*4)
2	DC	0.1 + 1.8 + 0.4	Unshielded	Unshielded	*4)
3	Signal	0.1	Unshielded	Unshielded	*5)
4	AC	1.8	Unshielded	Unshielded	-

\*1) Used for Radiated Emission (Below 1 GHz)

\*2) Used for Radiated Emission (Above 1 GHz)

\*3) Used for Antenna Terminal Conducted test

\*4) Cable for test operation

\*5) Cable is for system reset during the development, not used for the product.

## **SECTION 5: Radiated Spurious Emission**

### **Test Procedure**

It was measured based on "8.5 and 8.6 of KDB 558074 D01 15.247 Meas Guidance v05r02".

[For below 1 GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane. Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

### **Test Antennas are used as below;**

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn


In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

### **20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9(ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).**

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument Used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	11.12.2.5.2 RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (Linear voltage) Trace: 100 traces Duty factor was added to the results.	RBW: 100 kHz VBW: 300 kHz

**Figure 2: Test Setup**


Below 1 GHz



x : Center of turn table

Test Distance: 3 m

1 GHz to 10 GHz




r : Radius of an outer periphery of EUT  
 x : Center of turn table

Distance Factor:  $20 \times \log (3.97 \text{ m} / 3.0 \text{ m}) = 2.44 \text{ dB}$   
 \* Test Distance:  $(3 + \text{SVSWR Volume} / 2) - r = 3.97 \text{ m}$

SVSWR Volume : 2.0 m  
 (SVSWR Volume has been calibrated based on CISPR 16-1-4.)  
 $r = 0.03 \text{ m}$

10 GHz to 26.5 GHz



x : Center of turn table

Distance Factor:  $20 \times \log (1.0 \text{ m} / 3.0 \text{ m}) = -9.54 \text{ dB}$   
 \*Test Distance: 1 m

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Antenna polarization	Carrier	Spurious (30 MHz - 1 GHz)	Spurious (1 GHz - 2.8 GHz)	Spurious (2.8 GHz - 10 GHz)	Spurious (10 GHz - 18 GHz)	Spurious (18 GHz - 26.5 GHz)
Horizontal	Y	X	Y	X	X	X
Vertical	X	X	X	Y	X	X

The test results and limit are rounded off to one decimal place, so some differences might be observed.

**Measurement Range** : 30 MHz to 26.5 GHz  
**Test Data** : APPENDIX  
**Test Result** : Pass

## SECTION 6: Antenna Terminal Conducted Tests

### Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument Used
6 dB Bandwidth	3 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99 % Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/Average *2)	-	Power Meter (Sensor: 160 MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3 kHz	9.1 kHz	Auto	Peak	Max Hold	Spectrum Analyzer *3)
Conducted Spurious Emission *4) *5)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	10 kHz	30 kHz				

\*1) Peak hold was applied as Worst-case measurement.

\*2) Reference data

\*3) Section 11.10.2 Method PKPSD (peak PSD) of "ANSI C63.10-2013".

\*4) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was low enough as shown in the chart.

(9 kHz - 150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 10 kHz).

\*5) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to  $45.5 - 51.5 = -6.0$  dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

The test results and limit are rounded off to two decimals place, so some differences might be observed. The equipment and cables were not used for factor 0 dB of the data sheets.

**Test Data** : APPENDIX  
**Test Result** : Pass


## **APPENDIX 1: Test Data**

### **99 % Occupied Bandwidth and 6 dB Bandwidth**

Test place                      Shonan EMC Lab. No.5 Shielded Room  
Date                                June 7, 2023  
Temperature / Humidity        25 deg. C / 44 % RH  
Engineer                         Miku Ikudome  
Mode                                Tx BT LE

Frequency [MHz]	99 % Occupied Bandwidth [kHz]	6 dB Bandwidth [MHz]	Limit for 6 dB Bandwidth [MHz]
2402	1051.9	0.674	> 0.5000
2440	1053.4	0.672	> 0.5000
2480	1051.5	0.674	> 0.5000

**99 % Occupied Bandwidth and 6 dB Bandwidth**



## Maximum Peak Output Power

Test place	Shonan EMC Lab. No.5 Shielded Room
Date	June 7, 2023
Temperature / Humidity	25 deg. C / 44 % RH
Engineer	Miku Ikudome
Mode	Tx BT LE

### Maximum peak output power

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Conducted Power					e.i.r.p. for RSS-247					
				Result		Limit		Margin [dB]	Antenna Gain [dBi]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]			[dBm]	[mW]	[dBm]	[mW]	
2402	-12.34	1.75	10.18	-0.41	0.91	30.00	1000	30.41	2.50	2.09	1.62	36.02	4000	33.93
2440	-12.31	1.76	10.18	-0.37	0.92	30.00	1000	30.37	2.50	2.13	1.63	36.02	4000	33.89
2480	-12.36	1.77	10.18	-0.41	0.91	30.00	1000	30.41	2.50	2.09	1.62	36.02	4000	33.93

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

e.i.r.p. Result = Conducted Power Result + Antenna Gain

All comparison were carried out on same frequency and measurement factors.



**Average Output Power**  
**(Reference data for RF Exposure)**

Test place	Shonan EMC Lab. No.5 Shielded Room
Date	June 7, 2023
Temperature / Humidity	25 deg. C / 44 % RH
Engineer	Miku Ikudome
Mode	Tx BT LE

**Average power**

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
				[dBm]	[mW]		[dBm]	[mW]
2402	-14.64	1.75	10.18	-2.71	0.54	1.60	-1.11	0.77
2440	-14.59	1.76	10.18	-2.65	0.54	1.60	-1.05	0.79
2480	-14.62	1.77	10.18	-2.67	0.54	1.60	-1.07	0.78

Sample Calculation:


Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

Result (Burst power average) = Result (Time average) + Duty factor

**Burst rate confirmation**

Test place                      Shonan EMC Lab. No.5 Shielded Room  
 Date                              June 7, 2023  
 Temperature / Humidity      25 deg. C / 44 % RH  
 Engineer                         Miku Ikudome  
 Mode                              Tx BT LE

(for Average power) \*1)  
 (for Radiated emission) \*2)



## Radiated Spurious Emission

Test place    Shonan EMC Lab.  
Semi Anechoic Chamber                      No.2  
Date    June 17, 2023  
Temperature / Humidity                      24 deg. C / 55 % RH  
Engineer    Takahiro Suzuki  
    (1 GHz to 26.5 GHz)  
Mode    Tx BT LE 2402 MHz

(\* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	2390.000	PK	44.30	28.16	14.18	38.75	2.44	50.33	73.9	23.5	165	17	-
Hori.	4804.000	PK	45.44	31.50	7.00	38.57	2.44	47.81	73.9	26.0	132	10	-
Hori.	7206.000	PK	45.90	36.96	8.36	39.17	2.44	54.49	73.9	19.4	150	0	-
Hori.	7206.000	AV	36.46	36.96	8.36	39.17	2.44	45.05	53.9	<b>8.8</b>	150	0	Floor noise
Vert.	2390.000	PK	45.68	28.16	14.18	38.75	2.44	51.71	73.9	22.1	171	168	-
Vert.	4804.000	PK	45.26	31.50	7.00	38.57	2.44	47.63	73.9	26.2	261	351	-
Vert.	7206.000	PK	45.13	36.96	8.36	39.17	2.44	53.72	73.9	20.1	150	0	-
Vert.	7206.000	AV	36.40	36.96	8.36	39.17	2.44	44.99	53.9	8.9	150	0	Floor noise

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz :  $20\log(3.97 \text{ m} / 3.0 \text{ m}) = 2.44 \text{ dB}$

10 GHz - 40 GHz :  $20\log(1.0 \text{ m} / 3.0 \text{ m}) = -9.54 \text{ dB}$

### Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2390.000	AV	35.74	28.16	14.18	38.75	3.21	2.44	44.98	53.9	8.9	*1)
Hori.	4804.000	AV	35.15	31.50	7.00	38.57	3.21	2.44	40.73	53.9	13.1	-
Vert.	2390.000	AV	35.42	28.16	14.18	38.75	3.21	2.44	44.66	53.9	9.2	*1)
Vert.	4804.000	AV	35.15	31.50	7.00	38.57	3.21	2.44	40.73	53.9	13.1	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 10 GHz :  $20\log(3.97 \text{ m} / 3.0 \text{ m}) = 2.44 \text{ dB}$

10 GHz - 40 GHz :  $20\log(1.0 \text{ m} / 3.0 \text{ m}) = -9.54 \text{ dB}$

Duty factor refer to "Burst rate confirmation" sheet.

\*1) Not out of band emission (Leakage Power)

### 20 dBc Data Sheet (RBW 100 kHz, VBW 300 kHz)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2402.000	PK	81.39	28.15	14.20	38.74	2.44	87.44	-	-	Carrier
Hori.	2400.000	PK	41.87	28.15	14.19	38.74	2.44	47.91	67.4	19.4	-
Vert.	2402.000	PK	79.84	28.15	14.20	38.74	2.44	85.89	-	-	Carrier
Vert.	2400.000	PK	42.50	28.15	14.19	38.74	2.44	48.54	65.8	17.2	-



Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz :  $20\log(3.97 \text{ m} / 3.0 \text{ m}) = 2.44 \text{ dB}$

10 GHz - 40 GHz :  $20\log(1.0 \text{ m} / 3.0 \text{ m}) = -9.54 \text{ dB}$

## Radiated Spurious Emission (Reference Plot for band-edge)

Test place	Shonan EMC Lab.
Semi Anechoic Chamber	No.2
Date	June 17, 2023
Temperature / Humidity	24 deg. C / 55 % RH
Engineer	Takahiro Suzuki
Mode	Tx BT LE 2402 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
Final result of restricted band edge was shown in tabular data.

## Radiated Spurious Emission

Test place	Shonan EMC Lab.	No.2
Semi Anechoic Chamber	No.1	June 17, 2023
Date	June 13, 2023	24 deg.C, 55 %RH
Temperature / Humidity	21 deg.C, 63 %RH	Takahiro Suzuki
Engineer	Kouki Yamada	( 1 GHz -26.5 GHz )
	( 30 MHz -1 GHz )	
Mode	Tx BT LE 2440 MHz	

(\* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	30.978	QP	21.40	18.24	7.05	31.83	0.00	14.86	40.0	25.1	100	0	-
Hori.	52.481	QP	21.90	10.33	7.45	31.83	0.00	7.85	40.0	32.1	100	0	-
Hori.	194.747	QP	21.20	16.59	9.03	31.77	0.00	15.05	43.5	28.4	100	0	-
Hori.	463.295	QP	21.30	16.88	7.62	31.84	0.00	13.96	46.0	32.0	100	0	-
Hori.	893.136	QP	20.80	22.11	9.96	31.33	0.00	21.54	46.0	24.4	100	0	-
Hori.	4880.000	PK	45.56	31.53	7.04	38.60	2.44	47.97	73.9	25.9	119	350	-
Hori.	7320.000	PK	45.21	37.10	8.45	39.23	2.44	53.97	73.9	19.9	150	0	-
Hori.	7320.000	AV	36.20	37.10	8.45	39.23	2.44	44.96	53.9	<b>8.9</b>	150	0	Floor noise
Vert.	165.293	QP	21.50	15.48	8.98	31.77	0.00	14.19	43.5	29.3	100	0	-
Vert.	472.711	QP	21.20	17.12	7.68	31.84	0.00	14.16	46.0	31.8	100	0	-
Vert.	776.904	QP	21.40	20.54	9.31	31.85	0.00	19.40	46.0	26.6	100	0	-
Vert.	4880.000	PK	46.09	31.53	7.04	38.60	2.44	48.50	73.9	25.4	280	358	-
Vert.	7320.000	PK	44.83	37.10	8.45	39.23	2.44	53.59	73.9	20.3	150	0	-
Vert.	7320.000	AV	36.06	37.10	8.45	39.23	2.44	44.82	53.9	9.0	150	0	Floor noise

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz :  $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz :  $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

### Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	4880.000	AV	36.45	31.53	7.04	38.60	3.21	2.44	42.07	53.9	11.8	-
Vert.	4880.000	AV	35.93	31.53	7.04	38.60	3.21	2.44	41.55	53.9	12.3	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 10 GHz :  $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz :  $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Duty factor refer to "Burst rate confirmation" sheet.

## Radiated Spurious Emission

Test place                             Shonan EMC Lab.  
Semi Anechoic Chamber             No.2  
Date                                     June 17, 2023  
Temperature / Humidity               24 deg.C, 55 %RH  
Engineer                               Takahiro Suzuki  
  ( 1 GHz -26.5 GHz )  
Mode                                    Tx BT LE 2480 MHz

(\* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	2483.500	PK	45.24	28.05	14.28	38.70	2.44	51.31	73.9	22.5	138	44	-
Hori.	4960.000	PK	45.35	31.72	7.09	38.63	2.44	47.97	73.9	25.9	307	350	-
Hori.	7440.000	PK	46.04	37.28	8.53	39.30	2.44	54.99	73.9	18.9	150	0	-
Hori.	7440.000	AV	35.02	37.28	8.53	39.30	2.44	43.97	53.9	9.9	150	0	Floor noise
Vert.	2483.500	PK	44.62	28.05	14.28	38.70	2.44	50.69	73.9	23.2	151	185	-
Vert.	4960.000	PK	45.77	31.72	7.09	38.63	2.44	48.39	73.9	25.5	110	348	-
Vert.	7440.000	PK	45.03	37.28	8.53	39.30	2.44	53.98	73.9	19.9	150	0	-
Vert.	7440.000	AV	35.72	37.28	8.53	39.30	2.44	44.67	53.9	9.2	150	0	Floor noise

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz :  $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz :  $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

### Average measurement value with duty factor

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2483.500	AV	35.46	28.05	14.28	38.70	3.21	2.44	44.74	53.9	9.1	*1)
Hori.	4960.000	AV	36.10	31.72	7.09	38.63	3.21	2.44	41.93	53.9	11.9	-
Vert.	2483.500	AV	35.42	28.05	14.28	38.70	3.21	2.44	44.70	53.9	9.2	*1)
Vert.	4960.000	AV	36.30	31.72	7.09	38.63	3.21	2.44	42.13	53.9	11.7	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Duty factor + Distance factor

Distance factor : 1 GHz - 10 GHz :  $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz :  $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Duty factor refer to "Burst rate confirmation" sheet.



\*1) Not out of band emission (Leakage Power)

**Radiated Spurious Emission  
 (Reference Plot for band-edge)**

Test place  
 Semi Anechoic Chamber  
 Date  
 Temperature / Humidity  
 Engineer

Shonan EMC Lab.  
 No.2  
 June 17, 2023  
 24 deg.C, 55 %RH  
 Takahiro Suzuki


Mode Tx BT LE 2480 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
 Final result of restricted band edge was shown in tabular data.

**Radiated Spurious Emission**  
**(Plot data, Worst case mode for Maximum Peak Output Power)**

Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.1	No.2
Date	June 13, 2023	June 17, 2023
Temperature / Humidity	21 deg.C, 63 %RH	24 deg.C, 55 %RH
Engineer	Kouki Yamada ( 30 MHz -1 GHz )	Takahiro Suzuki ( 1 GHz -26.5 GHz )
Mode	Tx BT LE 2440 MHz	




\*These plots data contain sufficient number to show the trend of characteristic features for EUT.



### Conducted Spurious Emission

Test place	Shonan EMC Lab. No.5 Shielded Room
Date	June 7, 2023
Temperature / Humidity	25 deg. C / 44 % RH
Engineer	Miku Ikudome
Mode	Tx BT LE, 2440 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
11.23	-87.7	0.5	10.1	2.5	1.0	-74.5	300	6.0	-13.3	46.5	59.8	-
150.00	-89.2	0.5	10.1	2.5	1.0	-76.1	300	6.0	-14.8	24.0	38.8	-

$E \text{ [dBuV/m]} = \text{EIRP [dBm]} - 20 \log (\text{Distance [m]}) + \text{Ground bounce [dB]} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP [dBm]} = \text{Reading [dBm]} + \text{Cable loss [dB]} + \text{Attenuator Loss [dB]} + \text{Antenna gain [dBi]} + 10 * \log (N)$

N: Number of output

## Power Density


Test place                   Shonan EMC Lab. No.5 Shielded Room  
Date                           June 7, 2023  
Temperature / Humidity    25 deg. C / 44 % RH  
Engineer                    Miku Ikudome  
Mode                         Tx BT LE

Frequency [MHz]	Measured Frequency [MHz]	Reading [dBm/3 kHz]	Cable Loss [dB]	Atten. Loss [dB]	Result [dBm/3 kHz]	Limit [dBm/3 kHz]	Margin [dB]
2402	2401.942	-27.66	1.75	10.18	-15.73	8.00	23.73
2440	2439.943	-27.88	1.76	10.18	-15.94	8.00	23.94
2480	2480.021	-27.67	1.77	10.18	-15.72	8.00	23.72

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

### Power Density



## APPENDIX 2: Test Instruments

### Test Equipment [1/2]

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	SAT10-15	160493	Attenuator	Weinschel Corp.	54A-10	83406	2022/12/01	12
AT	SCC-G66	196947	Coaxial Cable	Huber+Suhner	SUCOFLEX 102	803478/2	2023/03/02	12
AT	SOS-27	191845	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	-	2022/08/08	12
AT	SPM-07	146247	Power Meter	Keysight Technologies Inc	8990B	MY51000272	2023/05/29	12
AT	SPSS-04	146310	Power sensor	Keysight Technologies Inc	N1923A	MY5326009	2023/05/29	12
AT	SRENT-15	160899	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46185516	2023/01/26	12
AT	STS-05	146212	Digital Hitester	HIOKI E.E. CORPORATION	3805-50	80997828	2022/09/20	12
RE	COTS-SEMI-5	170932	EMI Software	TSJ (Techno Science Japan)	TEPTO-DV3(RE,CE,ME, PE)	-	-	-
RE	KAT6-04	144899	Attenuator	Inmet	18N-6dB	-	2022/12/16	12
RE	KHA-04	146351	Horn Antenna	EMCO	3160-09	1278	2023/05/22	12
RE	SAEC-01(NSA)	145597	Semi-Anechoic Chamber	TDK	SAEC-01(NSA)	1	2023/04/04	12
RE	SAEC-02(SVSWR)	145598	Semi-Anechoic Chamber	TDK	SAEC-02(SVSWR)	2	2023/05/17	12
RE	SAF-01	145003	Pre Amplifier	SONOMA	310N	290211	2023/02/09	12
RE	SAF-05	145128	Pre Amplifier	Toyo Corporation	TPA0118-36	1440490	2023/05/19	12
RE	SAF-08	145007	Pre Amplifier	Toyo Corporation	HAP18-26W	19	2023/03/03	12
RE	SAT10-05	145136	Attenuator	Keysight Technologies Inc	8493C-010	74864	2022/10/20	12
RE	SAT3-09	144959	Attenuator	JFW	50HF-003N	-	2022/08/23	12
RE	SBA-01	145161	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	BBA9106	91032664	2023/04/12	12
RE	SCC-A1/A3/A5/A7/A8/A13/SRSE-01	144967	Coaxial Cable&RF Selector	Fujikura/Fujikura/Suhner/Suhner/Suhner/TOYO	8D2W/12DSFA/141PE/141PE/141PE/141PE/NS4906	-/0901-269(RF Selector)	2023/04/18	12
RE	SCC-A2/A4/A6/A7/A8/A13/SRSE-01	144968	Coaxial Cable&RF Selector	Fujikura/Fujikura/Suhner/Suhner/Suhner/TOYO	8D2W/12DSFA/141PE/141PE/141PE/141PE/NS4906	-/0901-269(RF Selector)	2023/04/18	12
RE	SCC-G15	145176	Coaxial Cable	Suhner	SUCOFLEX 102	32703/2	2023/03/03	12
RE	SCC-G41	151617	Coaxial Cable	Junkosha	MWX221-01000NFSNMS/B	1612S006	2023/01/12	12
RE	SCC-G50	178573	Coaxial Cable	Huber+Suhner	SUCOFLEX_104_E	MY13407/4E	2023/03/02	12
RE	SCC-G57	179540	Coaxial Cable	Huber+Suhner	SUCOFLEX 102	802815/2	2023/03/03	12
RE	SCC-G69	200009	Coaxial Cable	Huber+Suhner	SUCOFLEX 104	575617/4	2023/06/06	12
RE	SCC-G79	236869	Coaxial Cable	Huber+Suhner	SUCOFLEX 104	200084/4A	2023/06/06	12
RE	SFL-02	145301	Highpass Filter	Micro-Tronics	HPM50111	51	2022/10/20	12
RE	SHA-02	145384	Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	9120D-726	2023/03/09	12
RE	SHA-10	194685	Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA 9120 C	711	2023/03/27	12

**Test Equipment [2/2]**

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	SJM-20	207277	Measuring	ASKUL	-	-	-	-
RE	SJM-22	207279	Tape Measure	ASKUL	-	-	-	-
RE	SLA-05	145527	Logperiodic Antenna	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	193	2023/04/12	12
RE	SOS-20	191837	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	-	2022/08/06	12
RE	SOS-21	191838	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	-	2022/08/08	12
RE	SSA-03	145801	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY48250152	2022/08/04	12
RE	STR-01	145790	Test Receiver	Rohde & Schwarz	ESU40	100093	2023/04/22	12
RE	STS-01	145792	Digital Hitester	HIOKI E.E. CORPORATION	3805-50	80997812	2022/09/20	12
RE	STS-02	145793	Digital Hitester	HIOKI E.E. CORPORATION	3805-50	80997819	2023/05/26	12

\*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

- AT: Antenna Terminal Conducted test
- RE: Radiated Emission