RF Exposure / MPE Calculation

No.	:	13477241H
Applicant	:	CASIO COMPUTER CO., LTD
Type of Equipment	:	Wireless MIDI & audio adaptor
Model No.	:	WU-BT10 *Bluetooth Low Energy part
FCC ID	:	BBQWUBT10

CASIO COMPUTER CO., LTD declares that Model: WU-BT10 complies with FCC radiation exposure requirement specified in the FCC Rule 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "WU-BT10" as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm^2 uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

P = 3.33 mW (Maximum average output power)

☐ Time average was used for the above value in consideration of 6-minutes time-ave

☑ Burst power average was used for the above value in consideration of worst condit

G = 1.416 Numerical Antenna gain; equal to 1.51dBi

r = 20 cm (Separation distance)

Power Density Result S = **0.00094 mW/cm^2**

Even taking into account the tolerance, this device can be satisfied with the limits.

UL Japan, Inc.
Ise EMC Lab.
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124