

## UPCS (DECT based) – Implementation Conformance Statement

DUT	Description : GN9300 DECT and UPCS headset			
	Model : GN9300			
	Use : Office headset			
		FP	PP	Repeater
	System	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Type			
	HW version	v4rE	v6rB	
	SW version	v0036	v0035	
	RFPI / PIN			
	Decl. emission BW	1.4MHz	1.4MHz	
Decl. lower threshold				
Decl. upper threshold <sup>1)</sup>				
Product information	Standard: <input checked="" type="checkbox"/> FCC part 15D <input type="checkbox"/> other:			
	Frequency band: <input checked="" type="checkbox"/> 1920 – 1930 MHz <input type="checkbox"/> other:			
	Number of RF channels: 5			
	Number of logical channels: 60 (time and spectrum windows)			
	Used slot type: <input checked="" type="checkbox"/> single <input checked="" type="checkbox"/> double			
	Used slot(s): <input checked="" type="checkbox"/> even <input type="checkbox"/> odd			
	Operating mode: <input type="checkbox"/> simplex <input checked="" type="checkbox"/> duplex <input type="checkbox"/> other:			

<sup>1)</sup> if applicable

Product information	Antennas:					
	FP:	Antenna	Type	Gain [dBi]	internal	external
		1	PCB	0	<input checked="" type="checkbox"/>	<input type="checkbox"/>
		2	PCB	0	<input checked="" type="checkbox"/>	<input type="checkbox"/>
		3			<input type="checkbox"/>	<input type="checkbox"/>
	Do Tx and Rx use the same antenna(s)?: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No					
	PP:	Antenna	Type	Gain [dBi]	internal	external
		1	component (flex-PCB)	-5	<input checked="" type="checkbox"/>	<input type="checkbox"/>
		2			<input type="checkbox"/>	<input type="checkbox"/>
		3			<input type="checkbox"/>	<input type="checkbox"/>
Do Tx and Rx use the same antenna(s)?: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Antenna diversity: <sup>1)</sup>						
	Antenna	Diversity supported				
		Tx	Rx			
FP	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			
	2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			
	3	<input type="checkbox"/>	<input type="checkbox"/>			
PP	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			
	2	<input type="checkbox"/>	<input type="checkbox"/>			
	3	<input type="checkbox"/>	<input type="checkbox"/>			

<sup>1)</sup> if applicable

Product information	Supply and supported temperature ranges (Manufacturer declaration):			
		FP	PP	Repeater
	U <sub>normal</sub> [V]	9Vdc	3.6Vdc	
	U <sub>min</sub> [V]	7Vdc	3.3Vdc	
	U <sub>max</sub> [V]	12Vdc	4.2Vdc	
	T <sub>min</sub> [°C]	+5	+5	
	T <sub>max</sub> [°C]	+40	+40	
	Power Source	Type	Manufacturer	
	FP or WRS	ATL Technology	TEAD-41-070700U	
PP (charger)	built into FP	-		
Data connection: <input type="checkbox"/> PSTN <input checked="" type="checkbox"/> other				
-----				
<b>Used radio module <sup>1)</sup>:</b>				
Type :		Manufacturer:		
-----				
<b>Ancillary equipment <sup>1)</sup>:</b>				
Description :				
Type :				
Manufacturer :				
-----				
<b>Host device <sup>1)</sup>:</b>				
Description :				
Type :				
Manufacturer :				

<sup>1)</sup> if applicable



Product information	<b>Control software <sup>1)</sup>:</b> Name : Version : Manufacturer :
	<b>Additional remarks:</b>

<sup>1)</sup> if applicable



Manufacturer declarations

**FCC 15.323 (c) (5):**

This device or group of co-operating devices located within 1 meter of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively more than one third of the time and spectrum windows defined by the system.

Manufacturer agrees:  Yes  No

**FCC 15.323 (c) (12):**

This device shall not use the provisions of (c) (10) or (c) (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Manufacturer agrees:  Yes  No

**FCC 15.307 (b):**

The applicant is a participating member of UTAM, Inc. and will provide a related affidavit from UTAM, Inc. in course of certification.

Confirmation by applicant:  Yes  No

**FCC 15.319 (f) Automatic discontinuation of transmission:**

This device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. Automatic break off the transmissions means break off of connection and break of transmissions which are not control and signalling information or repetitive codes of complete frame or burst intervals. In case of devices using basics of DECT technology at least fixed parts and repeaters are using control and signalling information without direct connection without direct connection to their remote station.

*Please fill in the table below with the reaction of the EUT (FP and/or PP) using A, B or C.*

	Situation	Reaction of EUT		Verdict
		FP	PP	
1	Switch-off counter part	B	A	
2	Hook-off by counter part	B	A	
3	Switch-off by EUT	A	A	
4	Hook-off on EUT side	B	A	
5	Remote power from EUT	A	A	
6	Remote power from counterpart	B	A	

A – Connection break down, cease of transmit  
 B – Connection break down, EUT transmits signalling information  
 C – Connection break down, counter part transmits signalling information

<sup>1)</sup> if applicable



Supplement	<b>Additional remarks:</b>
	Declared by: Date: 30-Sep-05 Name (print): Kim Lybech Signature: <i>Kim Lybech</i>

<sup>1)</sup> if applicable