

FCC

EMC

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Bluetooth Speakerphone

ISSUED TO
GN Netcom Inc

900 Chelmsford Street, Tower II, 8th floor Lowell, MA 01851



Tested by: Xia Long
Xia Long
(Engineer)
Date: Nov. 03, 2017

Approved by: Wei Yanquan
Wei Yanquan
(Chief Engineer)
Date: Nov. 03, 2017



Report No.: BL-HK17A0105-401

EUT Name: Bluetooth Speakerphone

Model Name: PHS002W

Brand Name: Jabra

Test Standard: 47 CFR Part 15 Subpart B

FCC ID: BCE-PHS002WA

Test Conclusion: Pass

Test Date: Oct. 13, 2017 ~ Oct. 18, 2017

Date of Issue: Nov. 03, 2017

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Nov. 03, 2017</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Identification of the Testing Laboratory.....	4
1.2	Identification of the Responsible Testing Location.....	4
1.3	Laboratory Condition.....	4
1.4	Announce.....	4
2	PRODUCT INFORMATION.....	5
2.1	Applicant Information.....	5
2.2	Manufacturer Information.....	5
2.3	Factory Information.....	5
2.4	General Description for Equipment under Test (EUT).....	5
2.5	Ancillary Equipment.....	6
2.6	Technical Information.....	6
3	SUMMARY OF TEST RESULTS.....	7
3.1	Test Standards.....	7
3.2	Verdict.....	7
3.3	Test Uncertainty.....	7
4	GENERAL TEST CONFIGURATIONS.....	8
4.1	Test Environments.....	8
4.2	Test Equipment List.....	8
4.3	Test Enclosure list.....	9
4.4	Test Configurations.....	10
4.5	Test Setups.....	11
4.6	Test Conditions.....	13
5	TEST ITEMS.....	14
5.1	Emission Tests.....	14
ANNEX A	TEST RESULTS.....	16

A.1 Radiated Emission..... 16

A.2 Conducted Emission.....20

ANNEX B TEST SETUP PHOTOS..... 22

ANNEX C EUT EXTERNAL PHOTOS..... 22

ANNEX D EUT INTERNAL PHOTOS.....22

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.</p> <p>The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report refer to the BALUN report mode v6.5.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	GN Netcom Inc
Address	900 Chelmsford Street, Tower II, 8th floor Lowell, MA 01851

2.2 Manufacturer Information

Manufacturer	GN Audio A/S
Address	Lautrupbjerg 7, DK-2750 Ballerup, Denmark

2.3 Factory Information

Factory	VTECH COMMUNICATIONS LTD
Address	B5,B6,B8,VTECH SCIENCE PARK, XIA LING BEI MANAGEMENT ZONE LIAOBU, DONGGUAN, GUANGDONG, 523411, China

2.4 General Description for Equipment under Test (EUT)

EUT Name	Bluetooth Speakerphone
Model Name Under Test	PHS002W
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	28-03966
Software Version	2-0-7-0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	Bluetooth

2.5 Ancillary Equipment

Ancillary Equipment	Battery	
	Brand Name	SYNergy
	Model No.	AHB582035PR-03
	Serial No.	N/A
	Capacity	330 mAh
	Rated Voltage	3.7 V
	Limit Charge Voltage	4.2 V

2.6 Technical Information

Note: Not applicable.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	FCC 47 CFR Part 15 Subpart B (10-1-16 Edition)	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Result
1	Radiated Emission	15.109	Pass	Annex A .1
2	Conducted Emission	15.107	Pass	Annex A .2

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.23 dB
Radiated emissions (30 MHz-1 GHz)	4.30 dB
Radiated emissions (1 GHz-18 GHz)	4.81 dB
Radiated emissions (18 GHz-40 GHz)	5.71 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

Environment Parameter	Selected Values During Tests			
	Temperature	Voltage	Relative Humidity	Ambient Pressure
Normal Temperature, Normal Voltage (NTNV)	23°C~26°C	DC 3.7 V from Battery or DC 5 V from Laptop	50%-55%	100 to 102 kPa

4.2 Test Equipment List

Radiated Emission						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2016.09.09	2018.09.07	<input checked="" type="checkbox"/>
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2018.07.20	<input checked="" type="checkbox"/>
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2018.07.20	<input checked="" type="checkbox"/>
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2019.02.20	<input checked="" type="checkbox"/>

Conducted Emission Test						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2017.06.22	2018.06.21	<input checked="" type="checkbox"/>
LISN	SCHWARZBECK	NSLK 8127	8127-687	2017.06.22	2018.06.21	<input checked="" type="checkbox"/>
LISN	SCHWARZBECK	NNLK 8129	8129-462	2016.09.14	2018.09.12	<input type="checkbox"/>
AMN	SCHWARZBECK	NNBM8124	8124-509	2017.06.22	2018.06.21	<input type="checkbox"/>
AMN	SCHWARZBECK	NNBM8124	8124-510	2017.06.22	2018.06.21	<input type="checkbox"/>
ISN	TESEQ	ISN T800	34449	2017.06.22	2018.06.21	<input type="checkbox"/>
Shielded Enclosure	ChangNing	CN-130701	130703	N/A	N/A	<input checked="" type="checkbox"/>

4.3 Test Enclosure list


Description	Manufacturer	Model	Serial No.	Length	Description	Use
PC	Dell	015K3N	N/A	N/A	Special Handled	<input type="checkbox"/>
Laptop	Apple	A1465	N/A	N/A	N/A	<input checked="" type="checkbox"/>
Printer	HP	DESKJET 1000	N/A	N/A	N/A	<input type="checkbox"/>
Keyboard	Logitech	Y-BP62a	N/A	N/A	N/A	<input type="checkbox"/>
Mouse	Logitech	M100	N/A	N/A	N/A	<input type="checkbox"/>
USB Disk	Kingston	N/A	N/A	N/A	N/A	<input type="checkbox"/>
TF Card	Kingston	N/A	N/A	N/A	N/A	<input type="checkbox"/>
VGA Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>
HDMI Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>
DVI Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>
Coaxial video cable	N/A	N/A	N/A	2.0 m	Shielded with core	<input type="checkbox"/>
iPhone	Apple	A1586	N/A	N/A	N/A	<input type="checkbox"/>
Phone	MI	M4	N/A	N/A	N/A	<input checked="" type="checkbox"/>
Bluetooth Earphone	SAMSUNG	Gear Circle	N/A	N/A	N/A	<input type="checkbox"/>
GPS/GLONASS Vector signal generator	R&S	N5172B EXG	N/A	N/A	N/A	<input type="checkbox"/>
WIFI Router	TP-LINK	TL-WDR7500	N/A	N/A	N/A	<input type="checkbox"/>
Earphone	N/A	OPPO	N/A	1.1 m	N/A	<input type="checkbox"/>
Car Battery	Camel	55530	N/A	N/A	12 V/55 Ah	<input type="checkbox"/>
Artificial load	N/A	N/A	N/A	N/A	2.5 Ω/100 W	<input type="checkbox"/>
Artificial load	N/A	N/A	N/A	N/A	5 Ω/100 W	<input type="checkbox"/>
Electronic Load	ITECH	IT8511	N/A	N/A	N/A	<input type="checkbox"/>
USB Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>
DC Power Supply	ITECH	IT6863A	60001401068 7210006	N/A	N/A	<input type="checkbox"/>
LCD Monitor	SAMSUNG	UA32C4000P	N/A	N/A	N/A	<input type="checkbox"/>
LCD Monitor	Dell	U241HB	N/A	N/A	N/A	<input type="checkbox"/>
RJ45 Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>

4.4 Test Configurations

Test Configurations (TC) No.	Description
TC01	<u>The Working Test Mode</u> EUT + Battery + Laptop + BT Link + Phone
TC02	<u>The USB Audio Play Test Mode</u> EUT + Battery + Laptop


4.5 Test Setups

Test Setup 1




(For Radiated Emission Test (30 MHz-1 GHz))

Test Setup 2



(For Radiated Emission Test (above 1 GHz))

Test Setup 3



(For Conducted Emission, AC Ports Test)

4.6 Test Conditions

Test Case	Test Conditions	
Radiated Emission	Test Env.	NTNV
	Test Setup	Test Setup 1&2
	Test Configuration	TC01 ~TC02 ^{Note}
Conducted Emission	Test Env.	NTNV
	Test Setup	Test Setup 3
	Test Configuration	TC01 ~TC02 ^{Note}

Note: Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report. The Working Test Mode is the worst mode in this report.

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class B (at 10 m)	Class A (at 10 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)
30 - 88	100	40	30	90	39
88 - 216	150	43.5	33.5	150	43.5
216 - 960	200	46	36	210	46.4
Above 960	500	54	44	300	49.5

NOTE:

- 1) Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log$ [Field Strength ($\mu\text{V/m}$)].
- 2) In the emission tables above, the tighter limit applies at the band edges.

5.1.1.2 Test Setup

Refer to 4.5 section (test setup 1 to test setup 2) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

5.1.1.4 Test Result

Please refer to ANNEX A.1.

5.1.2 Conducted Emission

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.5 section test (test setup 3) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.1.2.4 Test Result

Please refer to ANNEX A.2.

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The marked spikes near 2400 MHz with circle should be ignored because they are Bluetooth carrier frequency.

Test Data and Plots


The Working Test Mode

A.1.1 Test Antenna Vertical, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	68.558	31.18	-21.29	40.0	8.82	Peak	277.90	100	Vertical	Pass
2	141.307	18.30	-22.58	43.5	25.20	Peak	282.50	100	Vertical	Pass
3	176.470	25.03	-21.01	43.5	18.47	Peak	226.40	200	Vertical	Pass
4	317.605	21.92	-15.79	46.0	24.08	Peak	345.90	100	Vertical	Pass
5	659.773	27.98	-8.70	46.0	18.02	Peak	170.20	100	Vertical	Pass
6	866.625	30.05	-5.77	46.0	15.95	Peak	108.60	200	Vertical	Pass

A.1.2 Test Antenna Horizontal, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	68.558	29.27	-21.29	40.0	10.73	Peak	0.30	100	Horizontal	Pass
2	114.147	15.55	-19.87	43.5	27.95	Peak	324.90	200	Horizontal	Pass
3	176.470	23.95	-21.01	43.5	19.55	Peak	342.00	100	Horizontal	Pass
4	317.847	28.70	-15.79	46.0	17.30	Peak	8.20	100	Horizontal	Pass
5	388.415	26.84	-14.16	46.0	19.16	Peak	0.00	100	Horizontal	Pass
6	529.550	26.44	-11.02	46.0	19.56	Peak	13.20	100	Horizontal	Pass

A.1.3 Test Antenna Vertical, 1 GHz – 12.75 GHz



No.	Frequency (MHz)	Results (dBUV/m)	Factor (dB)	Limit (dBUV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1451.000	42.20	-3.35	74.0	31.80	Peak	171.60	100	Vertical	Pass
2	2410.000	94.41	0.35	74.0	-20.41	Peak	240.10	100	Vertical	N/A
3	4312.000	43.72	10.99	74.0	30.28	Peak	0.70	100	Vertical	Pass
4	5776.000	48.93	14.54	74.0	25.07	Peak	239.00	100	Vertical	Pass
5	9663.867	49.93	26.04	74.0	24.07	Peak	202.70	160	Vertical	Pass
6	12127.563	50.45	18.19	74.0	23.55	Peak	133.40	100	Vertical	Pass

A.1.4 Test Antenna Horizontal, 1 GHz – 12.75 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1656.000	41.89	-3.60	74.0	32.11	Peak	255.20	100	Horizontal	Pass
2	2437.000	94.77	0.63	74.0	-20.77	Peak	323.80	100	Horizontal	N/A
3	4074.000	42.97	10.57	74.0	31.03	Peak	40.30	100	Horizontal	Pass
4	6012.000	48.14	14.87	74.0	25.86	Peak	328.50	100	Horizontal	Pass
5	8877.310	49.65	25.47	74.0	24.35	Peak	263.50	100	Horizontal	Pass
6	12064.312	50.23	18.39	74.0	23.77	Peak	39.70	100	Horizontal	Pass

A.2 Conducted Emission

Test Data and Plots


The Working Test Mode

A.2.1 L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.20	41.1	20.99	64.5	23.40	Peak	L Line	Pass
1**	0.20	36.2	20.99	54.5	18.30	AV	L Line	Pass
2	0.30	42.8	20.99	61.8	19.00	Peak	L Line	Pass
2**	0.30	41.3	20.99	51.8	10.50	AV	L Line	Pass
3	0.67	31.0	20.99	56.0	25.00	Peak	L Line	Pass
3**	0.67	25.0	20.99	46.0	21.00	AV	L Line	Pass
4	2.17	29.4	20.99	56.0	26.60	Peak	L Line	Pass
4**	2.17	19.2	20.99	46.0	26.80	AV	L Line	Pass
5	5.03	31.6	20.99	60.0	28.40	Peak	L Line	Pass
5**	5.03	18.4	20.99	50.0	31.60	AV	L Line	Pass
6	14.50	30.3	20.99	60.0	29.70	Peak	L Line	Pass
6**	14.50	18.5	20.99	50.0	31.50	AV	L Line	Pass

A.2.2 N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.20	40.2	20.99	64.5	24.30	Peak	N Line	Pass
1**	0.20	36.8	20.99	54.5	17.70	AV	N Line	Pass
2	0.30	42.6	20.99	61.8	19.20	Peak	N Line	Pass
2**	0.30	41.1	20.99	51.8	10.70	AV	N Line	Pass
3	0.67	31.7	20.99	56.0	24.30	Peak	N Line	Pass
3**	0.67	25.7	20.99	46.0	20.30	AV	N Line	Pass
4	2.50	30.9	20.99	56.0	25.10	Peak	N Line	Pass
4**	2.50	17.7	20.99	46.0	28.30	AV	N Line	Pass
5	7.80	31.2	20.99	60.0	28.80	Peak	N Line	Pass
5**	7.80	19.8	20.99	50.0	30.20	AV	N Line	Pass
6	21.58	30.9	20.99	60.0	29.10	Peak	N Line	Pass
6**	21.58	19.8	20.99	50.0	30.20	AV	N Line	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-HK17A0105-AE-1.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-HK17A0105-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-HK17A0105-AI.PDF".

--END OF REPORT--