

## Change description Jabra T5320bs

|          |                            |          |
|----------|----------------------------|----------|
| <b>1</b> | <b>Scope .....</b>         | <b>1</b> |
| <b>2</b> | <b>RF .....</b>            | <b>1</b> |
| <b>3</b> | <b>Firmware.....</b>       | <b>1</b> |
| <b>4</b> | <b>Interface .....</b>     | <b>1</b> |
| <b>5</b> | <b>Power supply.....</b>   | <b>1</b> |
| <b>6</b> | <b>Charge supply .....</b> | <b>1</b> |

### 1 Scope

This document describes the changes between Jabra T5330bs and Jabra T5320bs.

### 2 RF

There are no changes in the RF and antenna design.

### 3 Firmware

T5330bs and T5320bs use the same firmware.

### 4 Interface

The phone interface has been replaced with a USB interface.

### 5 Power supply

The T5320 can be supplied via USB only. The DC-plug does not supply any active parts of the base.

### 6 Charge supply

The headset charge interface is supplied via USB. If the USB is not present, the headset can be supplied via the DC-plug.

If both USB and the DC-plug are connected the headset will be charged via the DC-plug.

|                                       |                      |                           |              |
|---------------------------------------|----------------------|---------------------------|--------------|
| <b>Date:</b> 04-Dec-2006              | <b>Jabra T5320bs</b> | <b>Change description</b> |              |
| File: Jabra T5330bs - T5320bs changes |                      | Ref.: OBJ                 | Page: 1 of 1 |