



EMC TEST REPORT FCC 47 CFR Part 15B Industry Canada ICES-003 Electromagnetic compatibility - Unintentional radiators	
Report Reference No.	G0M-1608-5807-EF0115B-V01
Testing Laboratory	Eurofins Product Service GmbH
Address	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	<div style="text-align: center;">   </div> <p style="text-align: center;"> A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A </p>
Applicant's name	GN Audio A/S
Address	Lautrupbjerg 7 2750 Ballerup DENMARK
Test specification:	
Standard.....	47 CFR Part 15 Subpart B ICES-003, Issue 6:2016 ANSI C63.4:2014
Equipment under test (EUT):	
Product description	DECT base station
Model No.	WHB060BS
Additional Models	None
Hardware version	28-04656
Firmware / Software version	0.4.0
Contains	FCC-ID: BCE-WHB060BS IC: 2386C-WHB060BS
Test result	Passed

Possible test case verdicts:

- not applicable to test object: N/A
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Date of receipt of test item: 2016-08-19

Date (s) of performance of tests: 2016-09-06 – 2016-09-07

Compiled by: Matthias Handrik

Tested by (+ signature).....: Matthias Handrik 

Approved by (+ signature): Jens Marquardt 
Deputy Head of Lab

Date of issue: 2016-09-12

Total number of pages: 30

General remarks:

The test results presented in this report relate only to the object tested.
The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

Version History

Version	Issue Date	Remarks	Revised by
V01	2016-09-12	Initial Release	

REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Photos – Equipment external	6
1.2	Photos – Equipment internal	8
1.3	Photos – Test setup	9
1.4	Supporting Equipment Used During Testing	10
1.5	Input / Output Ports	10
1.6	Operating Modes and Configurations	11
1.7	Test Equipment Used During Testing	12
1.8	Sample emission level calculation	13
2	RESULT SUMMARY	14
3	TEST CONDITIONS AND RESULTS	15
3.1	Test Conditions and Results – Radiated emissions	15
3.2	Test Conditions and Results – AC power line conducted emissions	25

1 Equipment (Test item) Description



Description	DECT base station
Model	WHB060BS
Additional Models	None
Serial number	None
Hardware version	28-04656
Software / Firmware version	0.4.0
Contains FCC-ID	BCE-WHB060BS
Contains IC	2386C-WHB060BS
Power supply	48 VDC
AC/DC-Adaptor	Model : PSA15R-480P Manufacturer : PHIHONG Input : 100-240VAC / 50-60Hz Output : 48VDC / 0.31A
Manufacturer	GN Audio A/S Lautrupbjerg 7 2750 Ballerup DENMARK
Highest emission frequency	> 1000 MHz (up to 5th Harm)
Device classification	Class B
Equipment type	Tabletop
Number of tested samples	1

1.1 Photos – Equipment external







1.2 Photos – Equipment internal



1.3 Photos – Test setup



1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments (e.g. serial no.)
AE	Dummy desk telephone	Mitel	6873i	2EHFW154200I / FCC ID: EHTAQUA / IC: 173A-AQUA
AE	Headset	Jabra	WHB003HS	FCC ID: BCE-WHB003HS / IC: 2386C-WHB003HS-
AE	Laptop	DELL	Latitude E6420	S/N CXJ43R1

***Note:** Use the following abbreviations:

- AE : Auxiliary/Associated Equipment, or
- SIM : Simulator (Not Subjected to Test)
- CABL : Connecting cables

1.5 Input / Output Ports

Port #	Name	Type*	Max. Cable Length	Cable Shielded	Comments (e.g. Cat. of Cable)
1	-	-	-	-	-

***Note:** Use the following abbreviations:

- AC : AC power port
- DC : DC power port
- N/E : Non electrical
- I/O : Signal input or output port
- TP : Telecommunication port

1.6 Operating Modes and Configurations

Mode #	Description
1	Active DECT 6.0 link to Headset
2	Charging Headset + active DECT 6.0 link to Headset

Configuration #	EUT Configuration
DECT 6.0 link	Laptop (play MP3 file) connected via USB to dummy desk telephone. Active DECT 6.0 link to headset playback MP3 file from laptop.

1.7 Test Equipment Used During Testing

Measurement Software			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2015.1.12

Radiated emissions – 10m Chamber					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Biconical Antenna	R&S	HK 116	EF00012	2016-05	2019-05
LPD-Antenne	R&S	HL 223	EF00187	2016-05	2019-05
Horn antenna	Schwarzbeck	BBHA 9120D	EF00018	2013-09	2016-09
EMI Test Receiver	Keysight	N9038A-526	EF01070	2016-08	2017-08
RF Cable	Huber & Suhner	Sucoflex 106	-	System Cal.	System Cal
RF Cable	Huber & Suhner	Multiflex 141	-	System Cal.	System Cal

Conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	EF00182	2014-11	2016-11
AMN	R&S	ESH3-Z5	EF00036	2014-12	2016-12
AMN	Schwarzbeck	NSLK 8128	EF00975	2015-12	2016-12
EMI Test Receiver	R&S	ESR7	EF00943	2015-09	2016-09
EMI Test Receiver	Keysight	N9038A-526	EF01070	2016-08	2017-08
Cable	-	RG58/U	-	System Cal.	System Cal.

1.8 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB μ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB μ V/m). The FCC limits are given in units of μ V/m. The following formula is used to convert the units of μ V/m to dB μ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading - FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

2 Result Summary

FCC 47 CFR Part 15B, Industry Canada ICES-003				
Product Specific Standard	Requirement – Test	Reference Method	Result	Remarks
47 CFR 15.109 ICES-003 Item 6.2	Radiated emissions	ANSI C 63.4	PASS	
47 CFR 15.107 ICES-003 Item 6.1	AC power line conducted emissions	ANSI C63.4	PASS	
Remarks:				

3 Test Conditions and Results

3.1 Test Conditions and Results – Radiated emissions

Radiated emissions acc. FCC 47 CFR 15.109 / ICES-003				Verdict: PASS		
Laboratory Parameters:		Required prior to the test		During the test		
Ambient Temperature		15 to 35 °C		20°C		
Relative Humidity		30 to 60 %		50%		
Test according referenced standards		Reference Method				
		ANSI C63.4				
Sample is tested with respect to the requirements of the equipment class		Equipment class				
		Class B				
Test frequency range determined from highest emission frequency		Highest emission frequency				
		Fmax [MHz] = 1930				
Fully configured sample scanned over the following frequency range		Frequency range				
		30 MHz to 18 GHz				
Operating mode		1/2				
Configuration		DECT 6.0 link				
Limits and results Class B						
Frequency [MHz]	Quasi-Peak [dBµV/m]	Result	Average [dBµV/m]	Result	Peak [dBµV/m]	Result
30 – 88	40	PASS	-		-	-
88 – 216	43.5	PASS	-		-	-
216 – 960	46	PASS	-		-	-
960 – 1000	54	PASS	-		-	-
> 1000	-	-	54	PASS	74	PASS
Comments:						

Test Procedure:

The test site is in accordance with ANSI C63-4:2014 requirements and is listed by FCC.
The measurement procedure is as follows:

Exploratory measurement:

- The EUT was placed on a non-conductive table at a height of 0.8m.
- The EUT and support equipment, if needed, were set up to simulate typical usage.
- Cables, of type and length specified by the manufacturer, were connected to at least one port of each type and were terminated by a device or simulating load of actual usage.
- The antenna was placed at a distance of 3m and 10 m.
- The received signal was monitored at the measurement receiver.
 - Cables not bundled were manipulated within the range of likely arrangements to produce the highest emission amplitude
 - To maximize the suspected emissions the EUT is rotated 360 degrees. If the signal exceeds the previous amplitude, go back to the corresponding azimuth and manipulate the cables again for maximizing the emissions if possible.
 - Move the antenna from 1 to 4m to maximize the suspected highest amplitude signal.
- This procedure has to be performed in both antenna polarizations, horizontal and vertical.
- The arrangement of the equipment with the maximum emission level is shown on the setup picture at item 1.3.

Final measurement:


- The EUT was placed on a 0.8 m non-conductive table at a 3m and 10 m distance from the receive antenna. The antenna output was connected to the measurement receiver
- A biconical antenna was used for the frequency range 30 – 200 MHz, a logarithmic periodical antenna was used for the frequency range from 200 – 1000 MHz. Above one 1 GHz a Double Ridged Broadband Horn antenna was used. The antenna was placed on an adjustable height antenna mast
- The EUT and cable arrangement were based on the exploratory measurement results
- Emissions were maximized at each frequency by rotating the EUT and adjusting the receive antenna height and polarization. The maximum values were recorded.
- The test data of the worst-case conditions were recorded and shown on the next pages.

Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant: GN Audio A/S
 EUT Name: DECT base station
 Model: WHB060BS
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 20°C, Unom: 120V (AC/DC adaptor)
 Antenna: Schwarzbeck VULB 9162, Vertical
 Measurement distance: 10 m converted to 3 m
 Mode: active DECT link to headset
 Test Date: 2016-09-06
 Note:

Index 46



Peak Number	Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status	Angle	Height
1	41.988 MHz	31.8 dBµV/m	40 dBµV/m	-8.2 dB	Pass	0 Degree	1 m
2	48 MHz	34.1 dBµV/m	40 dBµV/m	-5.9 dB	Pass	0 Degree	1 m
3	36 MHz	36.1 dBµV/m	40 dBµV/m	-3.9 dB	Pass	0 Degree	1 m

Test Report No.: G0M-1608-5807-EF0115B-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant:	GN Audio A/S
EUT Name:	DECT base station
Model:	WHB060BS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 20°C, Unom: 120V (AC/DC adaptor)
Antenna:	Schwarzbeck VULB 9162, Horizontal
Measurement distance:	10m converted to 3 m
Mode:	active DECT link to headset
Test Date:	2016-09-06
Note:	

Index 47




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant: GN Audio A/S
 EUT Name: DECT base station
 Model: WHB060BS
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 20°C, Unom: 120V (AC/DC adaptor)
 Antenna: ETS-Lindgren 3117, Vertical
 Measurement distance: 3 m
 Mode: active DECT link to headset
 Test Date: 2016-09-06
 Note: DECT 6.0 notch filter

Index 48




Peak Number	Frequency	2th harmonic
1	3.854 GHz	2th harmonic

Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant: GN Audio A/S
 EUT Name: DECT base station
 Model: WHB060BS
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 20°C, Unom: 120V (AC/DC adaptor)
 Antenna: ETS-Lindgren 3117, Horizontal
 Measurement distance: 3 m
 Mode: active DECT link to headset
 Test Date: 2016-09-06
 Note: DECT 6.0 notch filter

Index 49



Peak Number	Frequency	2th harmonic
1	3.85 GHz	2th harmonic

Test Report No.: G0M-1608-5807-EF0115B-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant: GN Audio A/S
 EUT Name: DECT base station
 Model: WHB060BS
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 20°C, Unom: 120V (AC/DC adaptor)
 Antenna: Schwarzbeck VULB 9162, Vertical
 Measurement distance: 10m converted to 3 m
 Mode: charging headset, active DECT link to headset
 Test Date: 2016-09-06
 Note:

Index 45



Peak Number	Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status	Angle	Height
1	42.36 MHz	30.8 dBµV/m	40 dBµV/m	-9.2 dB	Pass	0 Degree	1 m
2	48 MHz	35.3 dBµV/m	40 dBµV/m	-4.7 dB	Pass	0 Degree	1 m
3	35.994 MHz	34.8 dBµV/m	40 dBµV/m	-5.2 dB	Pass	0 Degree	1 m

Test Report No.: G0M-1608-5807-EF0115B-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant:	GN Audio A/S
EUT Name:	DECT base station
Model:	WHB060BS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 20°C, Unom: 120V (AC/DC adaptor)
Antenna:	Schwarzbeck VULB 9162, Horizontal
Measurement distance:	10m converted to 3 m
Mode:	charging headset, active DECT link to headset
Test Date:	2016-09-06
Note:	

Index 44




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant: GN Audio A/S
 EUT Name: DECT base station
 Model: WHB060BS
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 20°C, Unom: 120V (AC/DC adaptor)
 Antenna: ETS-Lindgren 3117, Vertical
 Measurement distance: 3 m
 Mode: charging headset, active DECT link to headset
 Test Date: 2016-09-06
 Note: DECT 6.0 notch filter

Index 51




Peak Number	Frequency	2th harmonic
1	3.85 GHz	2th harmonic

Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1608-5807

Applicant:	GN Audio A/S
EUT Name:	DECT base station
Model:	WHB060BS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 20°C, Unom: 120V (AC/DC adaptor)
Antenna:	ETS-Lindgren 3117, Horizontal
Measurement distance:	3 m
Mode:	charging headset, active DECT link to headset
Test Date:	2016-09-06
Note:	DECT 6.0 notch filter

Index 50



3.2 Test Conditions and Results – AC power line conducted emissions

Conducted emissions acc. FCC 47 CFR 15.107 / ICES-003		Verdict: PASS		
Laboratory Parameters:		Required prior to the test		During the test
Ambient Temperature		15 to 35 °C		20°C
Relative Humidity		30 to 60 %		50%
Test according referenced standards		Reference Method		
		ANSI C63.4		
Fully configured sample scanned over the following frequency range		Frequency range		
		0.15 MHz to 30 MHz		
Sample is tested with respect to the requirements of the equipment class		Equipment class		
		Class B		
Points of Application		Application Interface		
AC Mains		LISN		
Operating mode		1/2		
Configuration		DECT 6.0 link		
Limits and results Class B				
Frequency [MHz]	Quasi-Peak [dB μ V]	Result	Average [dB μ V]	Result
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS
0.5 to 5	56	PASS	46	PASS
5 to 30	60	PASS	50	PASS
Comments:				
* Limit decreases linearly with the logarithm of the frequency.				

Test Procedure:

The test site is in accordance with ANSI C63-4:2014 requirements and is listed by FCC.
The measurement procedure is as follows:

Exploratory measurement:

- The EUT was placed on a non conductive table 0.8 m above the reference ground plane and 0.4 m away from the vertical conducting plane (ANSI C63.4: 2014 item 7.3.1)
- The power cord that is normally supplied or recommended by the manufacturer was connected to the LISN.
- The distance between the outer edge of the EUT and the LISN shall be set to 0.8 m. A longer power cord shall be bundled to this length (bundling shall not exceed 40 cm in length).
- The LISN measurement port was connected to a measurement receiver
- I/O cables were bundled not longer than 0.4 m
- Measurement was performed in the frequency range 0.15 – 30MHz on each current-carrying conductor
- To maximize the emissions the cable positions were manipulated
- The worst configuration of EUT and cables is shown on a test setup picture at item 1.3

Test Procedure:

Final measurement:


- The EUT was placed on a non conductive table 0.8 m above the reference ground plane and 0.4 m away from the vertical conducting plane (ANSI C63.4: 2014 item 7.3.1)
- The power cord that is normally supplied or recommended by the manufacturer was connected to the LISN.
- The distance between the outer edge of the EUT and the LISN shall be set to 0.8 m. A longer power cord shall be bundled to this length (bundling shall not exceed 40 cm in length).
- The LISN measurement port was connected to a measurement receiver
- The EUT and cable arrangement were based on the exploratory measurement results
- The test data of the worst-case conditions were recorded and shown on the next pages.

EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1608-5807

Applicant:	GN Audio A/S
EUT Name:	DECT base station
Model:	WHB060BS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 20°C, Unom: 120V (AC/DC adaptor)
LISN:	ESH2-Z5 N
Mode:	active DECT link to headset
Test Date:	2016-09-06
Note:	

Index 60




EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1608-5807

Applicant:	GN Audio A/S
EUT Name:	DECT base station
Model:	WHB060BS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 20°C, Unom: 120V (AC/DC adaptor)
LISN:	ESH2-Z5 L
Mode:	active DECT link to headset
Test Date:	2016-09-06
Note:	

Index 61




EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1608-5807

Applicant:	GN Audio A/S
EUT Name:	DECT base station
Model:	WHB060BS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 20°C, Unom: 120V (AC/DC adaptor)
LISN:	ESH2-Z5 N
Mode:	charging Headset, active DECT link to headset
Test Date:	2016-09-06
Note:	

Index 63



EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1608-5807

Applicant:	GN Audio A/S
EUT Name:	DECT base station
Model:	WHB060BS
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Handrik
Test Conditions:	Tnom: 20°C, Unom: 120V (AC/DC adaptor)
LISN:	ESH2-Z5 L
Mode:	charging Headset, active DECT link to headset
Test Date:	2016-09-06
Note:	

Index 62

