

APPENDIX D: SAR SYSTEM VALIDATION

FCC ID: BCG-A2622	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Watch		APPENDIX D: Page 1 of 2

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

**Table D-1
SAR System Validation Summary – 1g**

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (εr)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
AM6	750	08/03/2022	7532	750	Head	0.874	40.372	PASS	PASS	PASS	N/A	N/A	N/A
AM14	750	08/04/2022	7357	750	Head	0.905	42.251	PASS	PASS	PASS	N/A	N/A	N/A
AM12	835	06/08/2022	7499	835	Head	0.914	42.882	PASS	PASS	PASS	GMSK	PASS	N/A
AM13	1750	06/21/2022	7360	1750	Head	1.404	38.836	PASS	PASS	PASS	N/A	N/A	N/A
AM10	1900	06/08/2022	7308	1900	Head	1.397	41.750	PASS	PASS	PASS	GMSK	PASS	N/A
AM10	2450	06/02/2022	7308	2450	Head	1.882	38.829	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
AM11	2450	06/08/2022	7420	2450	Head	1.882	39.496	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
AM4	2600	03/25/2022	3837	2600	Head	1.955	39.728	PASS	PASS	PASS	TDD	PASS	N/A
AM10	2600	06/02/2022	7308	2600	Head	2.058	38.219	PASS	PASS	PASS	TDD	PASS	N/A
AM9	5250	04/12/2022	7638	5250	Head	4.606	35.527	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5600	04/12/2022	7638	5600	Head	5.018	34.950	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5750	04/12/2022	7638	5750	Head	5.190	34.628	PASS	PASS	PASS	OFDM	N/A	PASS

**Table D-2
SAR System Validation Summary – 10g**

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (εr)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
AM12	750	06/08/2022	7499	750	Head	0.874	43.491	PASS	PASS	PASS	N/A	N/A	N/A
AM12	835	06/08/2022	7499	835	Head	0.914	42.882	PASS	PASS	PASS	GMSK	PASS	N/A
AM13	1750	06/21/2022	7360	1750	Head	1.404	38.836	PASS	PASS	PASS	N/A	N/A	N/A
AM10	1900	06/08/2022	7308	1900	Head	1.397	41.750	PASS	PASS	PASS	GMSK	PASS	N/A
AM13	1900	06/13/2022	7360	1900	Head	1.442	40.951	PASS	PASS	PASS	GMSK	PASS	N/A
AM10	2450	06/02/2022	7308	2450	Head	1.882	38.829	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
AM11	2450	06/08/2022	7420	2450	Head	1.882	39.496	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
AM4	2600	03/25/2022	3837	2600	Head	1.955	39.728	PASS	PASS	PASS	TDD	PASS	N/A
AM10	2600	06/02/2022	7308	2600	Head	2.058	38.219	PASS	PASS	PASS	TDD	PASS	N/A
AM9	5250	04/12/2022	7638	5250	Head	4.606	35.527	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5600	04/12/2022	7638	5600	Head	5.018	34.950	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5750	04/12/2022	7638	5750	Head	5.190	34.628	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: While the probes have been calibrated for both CW and modulated signals. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: BCG-A2622	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Watch		APPENDIX D: Page 2 of 2