

APPENDIX A: SAR TEST PLOTS

ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: H3J9M4K3V6

Communication System: UID:10415 - AAA, WLAN; MAIA: Y; Frequency: 2437.0 MHz

Medium: 2450 Head; Medium parameters used:

$f = 2437.0$ MHz; $\text{cond} = 1.87$ S/m; $\text{perm} = 39.7$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 10.00 mm

Test Date: 06/14/2023; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7308; ConvF:(7.91,7.91,7.91); Calibrated: 2023-02-13

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn467; Calibrated: 2023-02-15

Phantom: Twin-SAM V4.0; Serial: 1275

Measurement SW: DASY Module SAR V16.2.0.1425

Mode: IEEE 802.11b, Head SAR, Front side, 22 MHz Bandwidth, Ch. 6, 1 Mbps, Aluminum, Sport Wristband

Area Scan (80.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.29 W/kg; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.389 W/kg

SAR(1 g) = 0.220 W/kg

Smallest distance from peaks to all points 3 dB below is 10.8 mm

Ratio of SAR at M2 to SAR at M1 = 83.3 %



ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: CN6YWY7HX1

Communication System: UID:10417 - AAC, WLAN; MAIA: Y; Frequency: 5500.0 MHz
Medium: 5200-5800 Head; Medium parameters used:
f = 5500.0 MHz; cond = 4.92 S/m; perm = 35.4; density = 1000 kg/m³
Phantom Section: Flat; Space: 10.00 mm

Test Date: 06/13/2023; Ambient Temp: 23.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7420; ConvF:(4.63,4.63,4.63); Calibrated: 2022-10-20
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1333; Calibrated: 2022-10-13
Phantom: Twin-SAM V8.0; Serial: 1736
Measurement SW: DASYS Module SAR V16.2.0.1425

**Mode: IEEE 801.11a, Head SAR, Front Side, 20 MHz Bandwidth, UNII-2C, Ch. 100,
6.0 Mbps, Aluminum, Sport Wristband**

Area Scan (80.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.10 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.712 W/kg

SAR(1 g) = 0.191 W/kg

Smallest distance from peaks to all points 3 dB below is 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 62.8 %



ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: WP4DY2DN79

Communication System: UID:10032 - CAA, Bluetooth; MAIA: Y; Frequency: 2441.0 MHz

Medium: 2450 Head; Medium parameters used:

$f = 2441.0$ MHz; $\text{cond} = 1.87$ S/m; $\text{perm} = 39.7$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 10.00 mm

Test Date: 06/14/2023; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7308; ConvF:(7.91,7.91,7.91); Calibrated: 2023-02-13

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn467; Calibrated: 2023-02-15

Phantom: Twin-SAM V4.0; Serial: 1275

Measurement SW: DASY Module SAR V16.2.0.1425

Mode: Bluetooth, Head SAR, Ch.39, 1Mbps, Front Side, Aluminum, Sport Wristband

Area Scan (80.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.27 W/kg; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.385 W/kg

SAR(1 g) = 0.212 W/kg

Smallest distance from peaks to all points 3 dB below is 10.5 mm

Ratio of SAR at M2 to SAR at M1 = 82.5 %



ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: CN6YWY7HX1

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 5728.75 MHz
Medium: 5200-5800 Head; Medium parameters used:
 $f = 5728.75$ MHz; $\text{cond} = 5.02$ S/m; $\text{perm} = 34.8$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10.00 mm

Test Date: 07/18/2023; Ambient Temp: 22.5°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7420; ConvF:(4.8,4.8,4.8); Calibrated: 2022-10-20
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1333; Calibrated: 2022-10-13
Phantom: Twin-SAM V8.0; Serial: 1736
Measurement SW: DASY Module SAR V16.2.0.1425

**Mode: 802.15.4 ab-NB, Head SAR, Front Side, Low Ch., 1 Mbps
Aluminum, Sport Wristband**

Area Scan (80.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: $dx=4.0$ mm, $dy=4.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.4


Reference Value = -0.01 W/kg; Power Drift = -0.21 dB

Peak SAR (extrapolated) = 0.062 W/kg

SAR(1 g) = 0.006 W/kg

Smallest distance from peaks to all points 3 dB below is 4.0 mm

Ratio of SAR at M2 to SAR at M1 = 83.3 %



ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: WP4DY2DN79

Communication System: UID:10415 - AAA, WLAN; MAIA: Y; Frequency: 2437.0 MHz
Medium: 2450 Head; Medium parameters used:
f = 2437.0 MHz; cond = 1.87 S/m; perm = 39.7; density = 1000 kg/m³
Phantom Section: Flat; Space: 0.00 mm

Test Date: 06/14/2023; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7308; ConvF:(7.91,7.91,7.91); Calibrated: 2023-02-13
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn467; Calibrated: 2023-02-15
Phantom: Twin-SAM V4.0; Serial: 1275
Measurement SW: DASYS Module SAR V16.2.0.1425

**Mode: IEEE 802.11b, Extremity SAR, Back side, 22 MHz Bandwidth, Ch. 6, 1 Mbps,
Aluminum, Metal Loop Wristband**

Area Scan (80.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.58 W/kg; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.819 W/kg

SAR(10 g) = 0.140 W/kg

Smallest distance from peaks to all points 3 dB below is 7.7 mm

Ratio of SAR at M2 to SAR at M1 = 79.9 %



ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: CN6YWY7HX1

Communication System: UID:10417 - AAC, WLAN; MAIA: Y; Frequency: 5500.0 MHz
Medium: 5200-5800 Head; Medium parameters used:
f = 5500.0 MHz; cond = 4.92 S/m; perm = 35.4; density = 1000 kg/m³
Phantom Section: Flat; Space: 0.00 mm

Test Date: 06/13/2023; Ambient Temp: 23.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7420; ConvF:(4.63,4.63,4.63); Calibrated: 2022-10-20
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1333; Calibrated: 2022-10-13
Phantom: Twin-SAM V8.0; Serial: 1736
Measurement SW: DASY Module SAR V16.2.0.1425

**Mode: IEEE 801.11a, Extremity SAR, Back Side, 20 MHz Bandwidth, UNII-2C, Ch. 100,
6.0 Mbps, Aluminum, Metal Links Wristband**

Area Scan (80.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=3.6 mm, dy=3.6 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.07 W/kg; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.606 W/kg

SAR(10 g) = 0.023 W/kg

Smallest distance from peaks to all points 3 dB below is 4.1 mm

Ratio of SAR at M2 to SAR at M1 = 58.5 %



ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: HJP24FGQ0X

Communication System: UID:10032 - CAA, Bluetooth; MAIA: Y; Frequency: 2480.0 MHz
Medium: 2450 Head; Medium parameters used:
f = 2480.0 MHz; cond = 1.87 S/m; perm = 39.2; density = 1000 kg/m³
Phantom Section: Flat; Space: 0.00 mm

Test Date: 06/12/2023; Ambient Temp: 22.1°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7308; ConvF:(7.91,7.91,7.91); Calibrated: 2023-02-13
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn467; Calibrated: 2023-02-15
Phantom: Twin-SAM V4.0; Serial: 1275
Measurement SW: DASY Module SAR V16.2.0.1425

Mode: Bluetooth, Extremity SAR, Ch.78, 1Mbps, Back Side, Aluminum, Sport Wristband

Area Scan (80.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.60 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.830 W/kg

SAR(10 g) = 0.156 W/kg

Smallest distance from peaks to all points 3 dB below is 8.0 mm

Ratio of SAR at M2 to SAR at M1 = 80.6 %



ELEMENT

DUT: BCG-A2978; Type: Watch; Serial: CN6YWY7HX1

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 5728.75 MHz
Medium: 5200-5800 Head; Medium parameters used:
 $f = 5728.75$ MHz; $\text{cond} = 5.02$ S/m; $\text{perm} = 34.8$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 0.00 mm

Test Date: 07/18/2023; Ambient Temp: 22.5°C; Tissue Temp: 20.7°C

Probe: EX3DV4 - SN7420; ConvF:(4.8,4.8,4.8); Calibrated: 2022-10-20
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1333; Calibrated: 2022-10-13
Phantom: Twin-SAM V8.0; Serial: 1736
Measurement SW: DASY Module SAR V16.2.0.1425

**Mode: 802.15.4 ab-NB, Extremity SAR, Back Side, Low Ch., 1 Mbps
Aluminum, Sport Wristband**

Area Scan (80.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (24.0 x 24.0 x 22.0): Measurement grid: $dx=4.0$ mm, $dy=4.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.4

Reference Value = -0.01 W/kg; Power Drift = -0.21 dB

Peak SAR (extrapolated) = 0.037 W/kg

SAR(10 g) = 0 W/kg

Smallest distance from peaks to all points 3 dB below is N/A

Ratio of SAR at M2 to SAR at M1 = n/a %

