



**FCC CFR47 PART 15 SUBPART C
INDUSTRY CANADA RSS-210 ISSUE 8**

CERTIFICATION TEST REPORT

FOR

QUAD-BAND RADIO WITH WLAN AND BT RADIO

Model: A1453 / A1533

FCC ID: BCG-E2642A

IC: 579C-E2642A

IC: 579C-E2642B

REPORT NUMBER: 13U14987-5

ISSUE DATE: JULY 22, 2013

Prepared for

APPLE, INC.

1 INFINITE LOOP

CUPERTINO, CA 95014, U.S.A.

Prepared by

UL VERIFICATION SERVICES INC.

47173 BENICIA STREET

FREMONT, CA 94538, U.S.A.

TEL: (510) 771-1000

FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
<u>---</u>	<u>07/22/13</u>	<u>Initial Issue</u>	<u>T. Chan</u>

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: APPLE, INC.
1 INFINITE LOOP
CUPERTINO, CA 95014, U.S.A.

EUT DESCRIPTION: QUAD-BAND RADIO WITH WLAN AND BT RADIO

MODEL: A1453 / A1533

SERIAL NUMBER: C39HV0HPF5P5 (Conducted), C7JKP0AEFLTW (Radiated)

DATE TESTED: MAY 02 - 28, 2013


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass
INDUSTRY CANADA RSS-210 Issue 8 Annex 8	Pass
INDUSTRY CANADA RSS-GEN Issue 3	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



Thu Chan
WiSE Operations Manager
UL Verification Services Inc.

Tony Wang
WiSE Technician
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 3, and RSS-210 Issue 8.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Model A1453/A1533 is a mobile phone with multimedia functions (music, application support, and video), cellular GSM/GPRS/EGPRS/WCDMA/HSPA+/DC-HSDPA/CDMA/EVDO/LTE radio, IEEE 802.11a/b/g/n, Bluetooth and GPS radio. The rechargeable battery is not user accessible.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	BLE	10.87	12.22

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PiFA antenna, with a maximum gain of 1,09dBi.

5.4. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was Broadcom Bluetool Version 1.4.8.7.

5.5. WORST-CASE CONFIGURATION AND MODE

For Radiated Emissions below 1 GHz and Power line Conducted Emissions, the channel with the highest conducted output power was selected as worst-case scenario.

The worst-position was the EUT with highest emissions. To determine the worst-case, the EUT is a portable device that has three orientations; therefore X, Y and Z orientations have been investigated with and without AC adapter, and the worst case was found to be at Z position without AC Adapter.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	7.40
Middle	2440	7.90
High	2480	7.51

I/O CABLES (Conducted Setup)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	SMA	Shielded	0.1m	To Spectrum Analyzer


I/O CABLES (Radiated Setup)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Jack	1	Earphone	Unshielded	0.5m	N/A


TEST SETUP

The EUT is a stand-alone device.

SETUP DIAGRAM FOR CONDUCTED TESTS



SETUP DIAGRAM FOR RADIATED TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Horn Antenna 1-18GHz	ETS Lindgren	3117	F00132	02/19/14
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/14
Antenna, Horn, 26.5 GHz	ARA	SWH-28	C01015	05/06/14
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB3	F00027	03/07/14
LISN, 30 MHz	FCC	LISN-50/250-25-2	N02625	01/14/14
Peak / Average Power Sensor	Agilent / HP	E9323A	F00026	07/27/13
P-Series single channel Power Meter	Agilent / HP	N1911A	F00153	07/26/13
Spectrum Analyzer, 44GHz	Agilent	E4446A	C01159	04/10/14
Spectrum Analyzer, 44GHz	Agilent	N9030A	F00129	02/22/14
PreApmplifier, 1-26.5GHz	Agilent	8449B	C01052	10/22/13
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	08/08/13

7. ANTENNA PORT TEST RESULTS

7.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.



TEST PROCEDURE


KDB 558074 D01 v01 "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under 15.247".

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (KHz)	Minimum Limit (KHz)
Low	2402	684.000	500.0
Middle	2440	683.000	500.0
High	2480	695.000	500.0

6 dB BANDWIDTH





7.2. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.



TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0339
Middle	2440	1.0172
High	2480	1.0560

99% BANDWIDTH





7.3. OUTPUT POWER

LIMIT

§15.247 (b) (1)



The maximum antenna gain is less than 6 dBi, therefore the limit is 30 dBm.


TEST PROCEDURE

KDB 558074 D01 v01 "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under 15.247".

RESULTS

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	10.51	30	-19.49
Middle	2440	10.87	30	-19.13
High	2480	10.48	30	-19.52





7.4. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	7.40
Middle	2440	7.90
High	2480	7.51

7.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.



TEST PROCEDURE


KDB 558074 D01 v01 "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under 15.247".

RESULTS

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-3.73	8	-11.73
Middle	2440	-3.40	8	-11.40
High	2480	-3.75	8	-11.75

POWER SPECTRAL DENSITY





7.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5



Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.

TEST PROCEDURE



KDB 558074 D01 v01 "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under 15.247".

RESULTS



SPURIOUS EMISSIONS, LOW CHANNEL



SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



8. RADIATED TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.



For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

For 2.4 GHz band, the spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.



The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

8.2. TRANSMITTER ABOVE 1 GHz



RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)




RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)




HARMONICS AND SPURIOUS EMISSIONS



Av - average detection
 PK - Peak detector


LOW CH, VERTICAL



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/3 GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
2	4.805	47.22	PK	34.4	-31.6	50.02	53.97	-3.95	74	-23.98	199	V
	4.804	36.42	Av	34.4	-31.6	39.22	53.97	-14.75	74	-34.78	174	V
3	4.959	43.54	PK	34.4	-31.4	46.54	53.97	-7.43	74	-27.46	199	V

Av - average detection
 PK - Peak detector

MID CH, HORIZONTAL




FCC Part 15 Subpart C 2400MHz Spurious Emissions with Average Scan TST 38915 19 Jun 2012 Rev 9.5 13 Jun 2012

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/3 GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
1	4.881	46.82	PK	34.4	-31.5	49.72	53.97	-4.25	74	-24.28	199	H
	4.88	37.76	Av	34.4	-31.5	40.66	53.97	-13.31	74	-33.34	156	H


PK - Peak detector
 Av - average detection

MID CH, VERTICAL



Marker	Frequency (GHz)	Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/3GHz HPF (dB)	Corrected (dBuV)	Avg Limit (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
2	4.881	44.59	PK	34.4	-31.5	47.49	53.97	-6.48	74	-26.51	199	V
4	1.901	37.06	PK	31.5	-24.8	43.76	53.97	-10.21	74	-30.24	199	V

HIGH CH, HORIZONTAL



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/3 GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
1	4.961	48.35	PK	34.4	-31.4	51.35	53.97	-2.62	74	-22.65	199	H
	4.96	36.57	Av	34.4	-31.4	39.57	53.97	-14.4	74	-34.43	148	H

Av - average detection
 PK - Peak detector

HIGH CH, VERTICAL




FCC Part 15 Subpart C 2400MHz Spurious Emissions with Average Scan, TST 30915 10 Jun 2013 Rev 9.5 '13 Jun 2011

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T346 (dB/m)	Amp/Cbl/3 GHz HPF (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarity
2	4.961	45.85	PK	34.4	-31.4	48.85	53.97	-5.12	74	-25.15	199	V
	4.96	36.02	Av	34.4	-31.4	39.02	53.97	-14.95	74	-34.98	259	V


Av - average detection
 PK - Peak detector

8.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



8.4. RECEIVER ABOVE 1 GHz

Note: No emissions were detected above the system noise floor.

9. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE


ANSI C63.4

RESULTS

6 WORST EMISSIONS

Project No:13U14987									
Client Name:									
Model/Device:WLAN Worst Case									
Test Volt/Freq:115V 60Hz									
Test By:Francisco Guarnero									
Line-L1 .15 - 30MHz									
Test Frequency	Meter Reading	Detector	T24 IL L1.TXT (dB)	LC Cables 1&3.TXT (dB)	dB(uVolts)	CISPR 11/22 Class B Quasi-peak	Margin	CISPR 11/22 Class B Average	Margin
0.1635	41.02	PK	0.1	0	41.12	65.3	-24.18	-	-
0.1635	-2.46	Av	0.1	0	-2.36	-	-	55.3	-57.66
0.249	37.2	PK	0.1	0	37.3	61.8	-24.5	-	-
0.249	-3.24	Av	0.1	0	-3.14	-	-	51.8	-54.94
0.3435	34.07	PK	0.1	0	34.17	59.1	-24.93	-	-
0.3435	-1.64	Av	0.1	0	-1.54	-	-	49.1	-50.64
0.7845	34.52	PK	0.1	0	34.62	56	-21.38	-	-
0.7845	5.76	Av	0.1	0	5.86	-	-	46	-40.14
18.303	23.71	PK	0.2	0.2	24.11	60	-35.89	-	-
18.303	-0.98	Av	0.2	0.2	-0.58	-	-	50	-50.58
Line-L2 .15 - 30MHz									
Test Frequency	Meter Reading	Detector	T24 IL L2.TXT (dB)	LC Cables 2&3.TXT (dB)	dB(uVolts)	CISPR 11/22 Class B Quasi-peak	Margin	CISPR 11/22 Class B Average	Margin
0.1725	40.56	PK	0.1	0	40.66	64.8	-24.14	-	-
0.1725	-2.94	Av	0.1	0	-2.84	-	-	54.8	-57.64
0.258	37.6	PK	0.1	0	37.7	61.5	-23.8	-	-
0.258	-3.12	Av	0.1	0	-3.02	-	-	51.5	-54.52
0.3345	33.88	PK	0.1	0	33.98	59.3	-25.32	-	-
0.3345	-4.07	Av	0.1	0	-3.97	-	-	49.3	-53.27
0.78	34.2	PK	0.1	0	34.3	56	-21.7	-	-
0.78	4.8	Av	0.1	0	4.9	-	-	46	-41.1
18.177	21.76	PK	0.2	0.2	22.16	60	-37.84	-	-
18.177	-4.17	Av	0.2	0.2	-3.77	-	-	50	-53.77

LINE 1 RESULTS



LINE 2 RESULTS

